



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS - 1963 - A AD-A159 064

# NAVAL POSTGRADUATE SCHOOL Monterey, California



# THESIS

OPTIMUM FREQUENCY FOR PROPAGATION OF SOUND IN SHALLOW SOUND CHANNELS

by

Wendy L. Bradfield-Smith

June 1985

OTIC FILE COPY

Thesis Advisor: Co-advisor: S. W. Yoon C. R. Dunlap

85

SEP 1 3 1985

D

9 10

077

Approved for public release; distribution is unlimited

| REPORT DOCUMENTAT                                    | ION PAGE                              | BEF                  | READ INSTRUCTIONS<br>ORE COMPLETING FORM       |
|--|---------------------------------------|----------------------|--|
| REPORT NUMBER  | 2. GOVT ACCESSION NO                  |                      | NT'S CATALOG NUMBER                            |
| . TITLE (and Subtitio)                               |                                       | S. TYPE OF           |  |
| Continum Frequency for Bro                           | pragation of                          | Maste                | er's Thesis                                    |
| Sound in Shallow Sound Ch                            | hannels                               | 6. PERFOR            | 1985<br>MING ORG. REPORT NUMBER                |
| AUTHOR(e)  |                                       | 8. CONTRA            | CT OR GRANT NUMBER(=)                          |
| W. L. Bradfield-Smith, LC                            | CDR, USN                              |                      |  |
| PERFORMING ORGANIZATION NAME AND ADD                 | RESS                                  | 10. PROGRA           | AM ELEMENT, PROJECT, TASK<br>WORK UNIT NUMBERS |
| Naval Postgraduate School<br>Monterey, California 93 | L<br>3943-5100                        |                      |  |
| 1. CONTROLLING OFFICE NAME AND ADDRESS               |                                       | 12. REPOR            | TDATE  |
| Naval Postgraduate School                            | 1                                     | June                 | 1985   |
| Monterey, California 93                              | 3943-5100                             | 106                  | T VE FAULD                                     |
| . MONITORING AGENCY NAME & ADDRESS(I di              | Iferent from Controlling Office)      | 18. SECURI           | TY CLASS. (of this repart)                     |
|  |                                       | Uncla                | assified                                       |
|  |                                       | 15a. DECLA<br>SCHED  | SSIFICATION/DOWNGRADING                        |
| '. DISTRIBUTION STATEMENT (of the abetract on        | tered in Block 20, if different fi    | rom Report)          | DTIC TAB<br>Umanneunced<br>Justification       |
| 8. SUPPLEMENTARY NOTES                               |                                       |                      | By   |
|  |                                       |                      | Distribution/                                  |
|  |                                       |                      | Availability Code<br>Avail and/or              |
| . KEY WORDS (Continue on reverse side if necess      | ary and identify by block numbe       | r)                   | A A  |
| Shallow sound channel<br>Deep sound channel          | Paradolic Ec<br>PE model              | Juation              | HI   |
| FACT   | Acoustic tra                          | ansmissi             | dn loss  |
| FACT 9H  |                                       |                      | /  |
| . ABSTRACT (Continue on reverse side if necessa      | ry and identify by block number       | 9                    |  |
| Optimum frequency fo                                 | r propagation of                      | f sound              | in shallow soundwa                             |
| channels was studied usi                             | ng two acoustic<br>Parabolic Equation | transmi<br>ion mode  | ssion loss 🔨 🔪                                 |
| model) and the Fast Asym                             | ptotic Coherent                       | Transmi              | ssion loss                                     |
| model, version 9H (a ray                             | -tracing model)                       | were te              | sted against                                   |
| experimental data collec                             | ted by Dosso and<br>The models we     | a Chapma<br>re found | n in the<br>to be valid                        |
| northeast facilite ocean.                            |                                       |                      |  |
| D I JAN 73 1473 EDITION OF 1 NOV 65 15 C             | Un                                    | classifi             | ed   |
|  |                                       |                      |  |

predictors of optimum frequency for the shallow sound channel observed by Dosso and Chapman. Both models were then used to predict optimum frequency for two sound velocity profiles obtained in a high-latitude deep ocean basin under summer conditions, exhibiting shallow sound channels. As expected, the split-step Parabolic Equation (PE) model adequately predicted optimum frequencies for these cases. The Fast Asymptotic Coherent Transmission loss model, version 9H (FACT 9H) model did not produce reasonable results for optimum frequencies.

S-N 0102- LF- 014- 6601

Approved for public release; distribution is unlimited.

Optimum Frequency for Propagation of Sound in Shallow Sound Channels

by

W. L. Bradfield-Smith Lieutenant Commander, United States Navy B. S., Duke University, 1975

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN SYSTEMS TECHNOLOGY (Antisubmarine Warfare)

from the

NAVAL POSTGRADUATE SCHOOL June 1985

Author:

d=smith

an Approved by: TODE Idvisor Duniap, R 77 С. Academić Group Forres Antisubmatr arfare chrady, D-Academic Dean

3

#### ABSTRACT

70ptimum frequency for propagation of sound in shallow sound channels was studied using two acoustic transmission model (a loss models. The split-step Parabolic Equation model) Fast Asymptotic full-wave and the Coherent Transmission loss mcdel  $\frac{4}{4}$  version 9H (a ray-tracing model)  $\frac{4}{2}$  -  $\frac{4}{2}$ were tested against experimental data collected by Dosso and Chapman in the northeast Pacific Ocean. The models were found to be valid predictors of optimum frequency for the shallow sound channel observed by Dosso and Chapman. Both models were then used to predict optimum frequency for two sound velocity profiles obtained in a high-latitude deep ocean basin under summer conditions, exhibiting shallow sound channels. As expected, the split-step Parabolic Equation (PE) model adequately predicted optimum frequencies for these cases. The Fast Asymptotic Coherent Transmission version 9H (FACT 9H) loss model, model did not produce reasonable results for optimum frequencies.

# TABLE OF CONTENTS

[

| I.   | INTR | ODU | CTJ         | ION        | •    | •   | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 13 |
|------|------|-----|-------------|------------|------|-----|-----|-------|-------|-----|-----|-----|-----|------------|----|----|----|------|----|----|---|---|---|----|
|      | A.   | BAC | K GI        | ROU        | IN I | . : | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | - | • | 13 |
|      | в.   | OBJ | EC'         | ri V       | E    | •   | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 14 |
| II.  | TEEO | RY  |             |            | •    | •   | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 17 |
|      | A.   | sou | ND          | IN         | נו   | CHE | S   | EA    | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 17 |
|      | Β.   | ACO | บรา         | <b>TIC</b> | : 1  | VAR | EG  | UII   | )ES   | 5   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 19 |
|      | с.   | TRA | n si        | MIS        | sı   | ICN | L   | 055   | 5     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 20 |
| III. | THE  | DOS | so          | A N        | D    | СН  | AP  | MAN   | N E   | EXE | PEF | RIM | EN  | T          | •  | •  | •  | •    | •  | •  | • | • | • | 25 |
|      | A.   | DAT | A (         | COI        | LI   | ECT | IO  | N     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 25 |
|      | в.   | RES | UL:         | TS         | A N  | ND  | DI  | sct   | JSS   | SIC | N   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 26 |
|      | c.   | COM | PAI         | RIS        | 501  | N B | ET  | WEI   | E N   | SS  | SC  | A N | D   | DS         | С  | PR | OF | AG   | AT | IC | N | • | • | 27 |
|      | D.   | MOD | ELJ         | ING        | ; 1  | PRO | PA  | GA!   | r I C | ) N | LC  | ss  | 5 I | N          | TH | E  | SS | C    | •  | •  | • | • | • | 28 |
|      | E.   | SUM | MAI         | R¥         | 01   | ? D | 05  | SO    | AX    | D   | CF  | IAP | MA  | N 1        | S  | EX | PI | er I | ME | NI | r | • | • | 29 |
| IV.  | THE  | NPS | P           | AR A       | BC   | II  | с   | EQI   | JAJ   | CIC | N   | MC  | DE  | L          | •  | •  | •  | •    | •  | •  | • | • | • | 39 |
|      | A.   | MOD | EL          | DĒ         | eso  | CRI | PT  | IOI   | N     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 39 |
|      | в.   | VAL | ID          | ATI        | :01  | N A | GA  | INS   | 5T    | DC  | ss  | 50  | A N | D          | CH | AP | MA | N 1  | S  |    |   |   |   |    |
|      |      | DAT | A .         |            |      |     | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 41 |
|      | c.   | DIS | CU          | SSI        | [0]  | N O | F   | NPS   | 5 1   | ?E  | RI  | ESU | ILI | <b>'</b> S | •  | •  | •  | •    | •  | •  | • | • | • | 45 |
| ۷.   | TWO  | HIG | <b>H</b> -1 | LAJ        | CI 2 | TUD | E   | SHI   | A LI  | 0   | 1 2 | 500 | INC | ) C        | HA | NN | EI | S    | •  | •  | • | • | • | 62 |
|      | A.   | OPT | IM          | UM         | Fl   | REQ | U E | INC : | I ES  | 5 1 | C N | ΤE  | IE  | SH         | AL | LC | )W | SC   | UN | D  |   |   |   |    |
|      |      | CHA | NN          | ELS        | 5.   |     | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 62 |
|      | в.   | OPT | IM          | UN         | Fl   | REQ | UE  | INC   | r 1   | ?0I | R 1 | PRC | PPA | GA         | TI | ON | A  | CF   | os | S  |   |   |   |    |
|      |      | THE | L           | A Y I      | ER   | •   | •   | •     | •     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | ۰ | 64 |
| VI.  | THE  | NPS | F           | ACI        | c :  | 9 E | MC  | DEI   | L     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | ٠ | 85 |
|      | A.   | MOD | EL          | DI         | ES   | CRI | PI  | IOI   | N     | •   | •   | •   | •   | •          | •  | •  | •  | •    | •  | •  | • | • | • | 85 |

|        | Β.    | V A  | LII        | DAT   | 10  | N. | AGA | IN  | IST | D  | 05  | S0  | AN  | ID  | СН | AE | PMI | AN 1 | S   |     |   |   |   |     |
|--------|-------|------|------------|-------|-----|----|-----|-----|-----|----|-----|-----|-----|-----|----|----|-----|------|-----|-----|---|---|---|-----|
|        |       | DA   | TA         | •     | •   | •  | • • | •   | •   | ٠  | •   | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • | • | 86  |
|        | c.    | TH   | <b>B</b> I | łIG   | H-  | LA | TIJ | TUD | E   | SH | AL. | LOI | 7 5 | 50U | ND | C  | H   | N    | NEI | LS  | • | • | • | 87  |
| VII.   | CCN   | CLU  | SIC        | ) N S |     | •  | ••• | •   | •   | •  | •   | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • | • | 96  |
|        | A.    | RE   | SUI        | TS    | A   | ND | DI  | SC  | US  | SI | ON  | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • | • | 96  |
|        | Β.    | RE   | coi        | 1ME   | ND  | AT | ION | IS  | A N | D  | AR  | EAS | 5 E | POF | F  | ŪE | RTF | IEI  | R   |     |   |   |   |     |
|        |       | ST   | UDI        | Z     | •   | •  | • • | •   | •   | •  | •   | •   | •   | •   | •  | •  | •   | •    | •   | •   | ٠ | • | • | 97  |
| APPEND | IX A  | :    | INI        | PUT   | P   | AR | AMF | ETE | RS  | F  | OR  | ΤI  | ΗE  | NP  | S  | PI | 3 2 | NI   | D   | ?A0 | T |   |   |     |
|        |       |      | 9 H        | MO    | DE  | LS | •   | •   | •   | •  | •   | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • | • | 99  |
| LIST O | F REI | FER. | ENC        | CES   |     | -  | • • | •   | •   | -  | -   | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • |   | 105 |
| INITIA | L DIS | STR  | IBU        | JTI   | 0 N | L  | ISI |     | •   | •  | •   | •   | •   | •   | •  | •  | •   | •    | •   | •   | • | • |   | 106 |

# LIST OF TABLES

| I   | Input Parameters for the NPS PE and FACT 9H   |
|-----|---|
|     | Models  |
| II  | Dosso and Charman's Sound Velocity Profile at |
|     | 0 Kilometers                                  |
| III | Dosso and Chapman's Sound Velocity Profile at |
|     | 16 Kilometers                                 |
| IV  | Dosso and Chapman's Sound Velocity Profile at |
|     | 20 and 33 Kilcmeters                          |
| V   | High-latitude Sound Velocity Profile for 10   |
|     | June  |
| VI  | High-latitude Sound Velccity Profile for 28   |
|     | June  |

# LIST OF FIGURES

| 2.1 | Typical Mid-latitude Sound Velocity Profile 23   |
|-----|--|
| 2.2 | Sound Velocity Frofile Showing Shallow Sound     |
|     | Channel  |
| 3.1 | Dosso and Chapman's Sound Velocity Profile at 0  |
|     | Km   |
| 3.2 | Dosso and Chapman's Sound Velocity Profile at    |
|     | 16 Km  |
| 3.3 | Dosso and Chapman's Sound Velocity Profile at    |
|     | 20 and 33 Km                                     |
| 3.4 | Propagation Loss vs Range (Dosso and Chapman) 33 |
| 3.5 | Propagation loss for 800 Hz, Absorption Removed  |
|     | (Dosso and Charman)                              |
| 3.6 | Measured Loss vs Frequency for Three-point       |
|     | Range Averages (Dosso and Chapman)               |
| 3.7 | Propagation Loss vs Range for Deep and Shallow   |
|     | Receivers (Dossc and Chapman)                    |
| 3.8 | Relative Gain between Deep and Shallow           |
|     | Receivers (Dosso and Chapman)                    |
| 3.9 | PE Model Results with Observations for 630 and   |
|     | 25 Hz (Dosso and Chapman)                        |
| 4.1 | Transmission Loss vs Range, 2000 Hz (NPS PE      |
|     | Model)   |
| 4.2 | Transmission Loss vs Range, 800 Hz (NPS PE       |
|     | Model)   |
| 4.3 | Transmission Loss vs Range, 250 Hz (NPS PE       |
|     | Model)   |
| 4.4 | Transmission Loss vs Range, 100 Hz (NPS PE       |
|     | Model)   |

| 4.5  | Transmission Loss vs Range, 25 Hz (NPS PE          |
|------|--|
|      | Model)   |
| 4.6  | Transmission Loss for 800 Hz, Absorption           |
|      | Removed (NPS PE Model)                             |
| 4.7  | Transmission Loss vs Frequency (NPS PE Model) 53   |
| 4.8  | Shallow vs Deep Receiver, 630 Hz (NPS PE Model) 54 |
| 4.9  | Shallow vs Deep Receiver, 315 Hz (NPS PE Model) 55 |
| 4.10 | Shallow vs Deep Receiver, 160 Hz (NPS PE Model) 56 |
| 4.11 | Relative Gain between Deep and Shallow             |
|      | Receivers (NPS FE Model)                           |
| 4.12 | Transmission Loss vs Range, 630 Hz (NPS PE         |
|      | Model)   |
| 4.13 | Transmission Loss vs Range, 400 Hz (NPS PE         |
|      | Model)   |
| 4.14 | Transmission Loss vs Range, 250 Hz (NPS PE         |
|      | Model)   |
| 4.15 | Transmission Loss vs Range, 25 Hz (NPS PE          |
|      | Model)   |
| 5.1  | High-latitude Scund Velocity Profile, 10 June 65   |
| 5.2  | High-latitude Scund Velocity Profile, 28 June 66   |
| 5.3  | Transmission Loss vs Frequency, 28 June (NPS PE    |
|      | Model)   |
| 5.4  | Transmission Loss vs Frequency, 10 June (NPS PE    |
|      | Model)   |
| 5.5  | Transmission Loss vs Range, 28 June, 600 Hz        |
|      | (NFS PE Model)                                     |
| 5.6  | Transmission Loss vs Range, 28 June, 700 Hz        |
|      | (NPS PE Model)                                     |
| 5.7  | Transmission Loss vs Range, 28 June, 800 Hz        |
|      | (NPS PE Model)                                     |
| 5.8  | Transmission Loss vs Range, 28 June, 900 Hz        |
|      | (NFS PE Model)                                     |
| 5.9  | Transmission Loss vs Range, 10 June, 700 Hz        |
|      | (NPS FE Mod el)                                    |

| 5.10 | Transmission Loss vs Range, 10 June, 800 Hz            |
|------|--|
|      | (NPS PE Model)   |
| 5.11 | Transmi <del>s</del> sion Loss vs Frequency, Truncated |
|      | Profile (NPS PE Model)                                 |
| 5.12 | Transmission Loss vs Range, Truncated Profile,         |
|      | 700 Hz (NPS PE Model)                                  |
| 5.13 | Transmission Loss vs Range, Truncated Profile,         |
|      | 800 Hz (NPS PE Model)                                  |
| 5.14 | Transmission Loss vs Range, Truncated Profile,         |
|      | 900 Hz (NPS PE Model)                                  |
| 5.15 | Transmission Loss between Surface Layer and            |
|      | SSC, 28 June (NPS PE Model)                            |
| 5.16 | Transmission Loss between Surface Layer and            |
|      | SSC, 10 June (NPS PE Model)                            |
| 5.17 | Transmission Loss between Surface Layer and            |
|      | SSC, Truncated Frofile (NPS PE Model) 81               |
| 5.18 | Relative Gain between Surface Layer and SSC, 28        |
|      | June (NPS PE Model)                                    |
| 5.19 | Relative Gain between Surface Layer and SSC, 10        |
|      | June (NPS PE Mcdel)                                    |
| 5.20 | Relative Gain between Surface Layer and SSC,           |
|      | Truncated Profile (NPS PE Model)                       |
| 6.1  | Transmission Loss vs Frequency, Dosso and              |
|      | Chapman (NPS FACT 9H Model)                            |
| 6.2  | Transmission Loss in the Shallow Sound Channel,        |
|      | Dosso and Chapman (NPS FACT 9H Model) 90               |
| 6.3  | Transmission Loss between SSC and DSC, Dosso           |
|      | and Chapman (NPS FACT 9H Model)                        |
| 6.4  | Relative Gain, Losso and Chapman (NPS FACT 9H          |
|      | Model)   |
| 6.5  | Transmission Loss vs Frequency, 28 June (NPS           |
|      | FACT 9H Model)   |
| 6.6  | Transmission Loss vs Frequency, 10 June (NPS           |
|      | FACT 9H Model)   |

\_

# III. THE DOSSO AND CHAPMAN EXPERIMENT

# A. DATA COLLECTION

Desso and Chapman [Ref. 1] conducted an experiment in sound propagation within and below the shallow sound channel. During summer conditions in the northeast Pacific Ccean off the west coast of Canada, CFAV ENDEAVOUR took up a station and monitored data collection equipment. A single calibrated hydrophone was suspended below the vessel at a depth of 101 meters, approximately the shallow sound channel An array of hydrophones was suspended at 417 meters axis. near the deep sound channel axis. A second vessel, CVAF PARIZEAU, opened range from CFAV ENDEAVOUR, dropping explosive charges every 1.8 km (approximately one nautical mile). The charges were set to detonate at 98 meters, near the shallcw sound channel axis.

CFAV PARIZEAU also measured sound velocity profiles at 16-kilometer intervals over the track (Figures 3.1 through 3.3). Later analysis revealed that the sound channel deepened over the portion of the track between eight and twenty kilometers, so that the sources were not located within the SSC and sound trapping was greatly reduced for sources detonated between those ranges. Section D below discusses steps that Dosso and Chapman took to account for this deepening of the SSC.

The received acoustic energy was measured as 1/3 octave band averages for each shot for both the shallow and deep hydrophones. Dosso and Chapman were able to distinguish bottom-interacting propagation paths by the different arrival times for shots in the first 35 kilometers of the track, and these arrivals were subtracted from the resulting

# REFRODUCED AT GOVERNMENT EXPENSE



Figure 2.2 Sound Velocity Profile Showing Shallow Sound Channel.

والمرجبة فالمتحد والمتحد والمتحد والمحمو



Pigure 2.1 Typical Mid-latitude Sound Velocity Profile.

and below by smooth interfaces between layers with no absorption or leakage should produce losses at about the rate due to\_cylindrical spreading alone. The minimum frequency which will be trapped well in a channel is the cutoff frequency. At frequencies near 1000 Hz, absorption mechanisms become important, and scattering losses also come into play. Therefore it should be possible to find scme optimum frequency for transmission of sound in a channel of given thickness, lying somewhere above the cutoff frequency and below the frequency range where absorption and scattering losses become large. absorption. The degree of attenuation is strongly dependent on the frequency of the sound, with higher frequencies experiencing greater attenuation. Thorp [Ref. 4] developed extensive tables to describe the attenuation of sound as a function of frequency.

Scund can be scattered from rough boundaries at the sea surface or bottom, or from discontinuities at the edges of the layers. Bubbles, marine organisms and suspended particulate matter will also scatter sound [Ref. 3]. Scattering is generally more important for higher frequencies than for lower ones.

Sound energy can also be lost through absorption. Viscosity effects in the interaction of water molecules as the sound wave passes account for one absorption mechanism. Chemical reactions are also important sources of absorptive loss. Of the many chemical constituents of seawater, certain compounds appear to undergo continuous dissociation into ions and reassociation. This relaxation mechanism takes up acoustic energy. The most important absorption mechanism for frequencies near 1000 Hz appears to be the borate-boric acid relaxation mechanism [Ref. 5].

In general, attenuation increases logarithmically with frequency. The attenuation losses due to such mechanisms are so small at low frequencies that the measurements must be made over extremely long ranges to detect any losses. The precision with which the measurements must be made and the inhomogeneities in the ocean further complicate the task. Urick [Ref. 2] provides an excellent discussion of absorption and attenuation.

Two factors are operating with opposing effects on sound being propagated through sound channels. First, attenuation mechanisms tend to cause losses of acoustic energy. Second, the focusing effect of the channel tends to reduce the losses. In the ideal case, a sound channel bounded above formula is given by Kinsler, Frey, Coppens and Sanders [Ref. 3]

$$= \frac{1}{c_0} \approx \frac{2 \times |0^5|}{D^{3/2}} \qquad (egn 2.2)$$

for  $\bigcup$  in meters. This yields a cutoff frequency of about 280 Hz for this channel. All of these calculations agree within useful ranges, since the cutoff frequency does not mark an abrupt end to propagation.

# C. TRANSMISSION LOSS

Several mechanisms act to decrease the energy of an acoustic wave as the wavefront moves farther away from its source. The most obvious loss mechanism is spreading. Once an outwardly propagating wavefront reaches a reasonable distance from a sufficiently small source, the wavefront can be considered for all practical purposes to be spherical. Thus, the energy in the wave is spread out over an area that increases as the square of the range from the source. In decibels, spherical spreading alone would produce a transmission loss (TL) of

 $TL_{SPHER} = 20 \log_{10} R$ (eqn 2.3)

If the sound is scmehow contained so that spreading may only take place horizontally, as is the case when the sound source is inside a channel or duct, the spreading is cylindrical rather than spherical and the loss is given by

 $TL_{CYL} = 10 \log_{10} R$  (egn 2.4)

Other mechanisms cause additional energy to be lost. These attenuation mechanisms include scattering and

# B. ACOUSTIC WAVEGUIDES

Sound channels act as acoustic waveguides. Ihe ray theory of sound propagation predicts that sound can be refracted and trapped in ducts. Trapping depends on the thickness of the duct and the wavelength of the sound: if the wavelength is "too large" to be contained within the vertical dimension of the duct, the sound will propagate Frequencies corresponding to those longer wavelcoorly. engths will propagate poorly, if at all: higher frequencies with shorter wavelengths will propagate much better. Ncrmal mode theory provides a tool for understanding these propagation effects [Ref. 3]. The transition from poor to good propagation is marked by the cutoff frequency. This frequency does not wark an abrupt end to propagation below which sound cannot be transmitted at all: rather it is a lower boundary below which progragation is less effective.

Acoustic propagation in a sound channel is exactly analogous to the propagation of radio waves in a ground-based duct. Urick [Ref. 2] provides an equation from the theory of radio propagation for the maximum wavelength which will "fit" in such a duct. Dosso and Chapman [Ref. 1] use this equation to calculate the cutoff frequency for their 80-meter thick shallow sound channel as about 250 Hz.

Urick gives another equation derived from radio propagation theory to calculate the cutoff frequency: [Ref. 2]

$$\lambda_{max} = 4.7 \times 10^{-3} H^{3/2}$$
 (eqn 2.1)

where  $\lambda_{max}$  is the maximum wavelength of the trapped sound in feet, and H is the thickness of the duct in feet. Converted into metric units and using a sound velocity of 1483 m/s, this formula yields a cutoff frequency of about 243 Hz for Dosso and Chapman's 80-meter channel. A third

A typical sound velocity profile like that of Figure 2.1 [Ref. 3] shows a surface layer of seawater which is subject to the actions of sun, wind and precipitation. This layer but its temperature, salinity and is often well-mixed, thickness may vary greatly from place to place and from day Typically the surface layer shows a constant or to day. slightly increasing sound velocity profile. The surface layer may extend to a depth of several tens of meters. At some point below the surface layer a strong thermal gradient may show up. Temperature and therefore sound velocity decrease sharply with depth, creating a seasonal thermo-Deeper still lies the main thermocline, formed by cline. another strong negative thermal gradient. Below this is the deep isothermal layer, which extends to the sea floor. In this layer salinity is essentially constant, as is tempera-Fressure and velocity increase very nearly linearly ture. with depth. The layers bounded above by the main thermoand below by the increasing velocity gradient cline are (DSC). called the deep sound channel Sound can be trapped in this channel and refracted repeatedly toward the velocity minimum, which is called the DSC axis. This axis may occur at depths ranging frcm several hundred to over 1000 meters.

Certain environmental conditions can cause a sound velocity profile like that shown in Figure 2.2. A combination of winds, high precipitation and low evaporation such as is found in the northeastern Pacific Ocean can lead to the formation of a secondary or shallow sound channel (SSC) just below the seasonal thermocline. Just as sound can be trapped in the DSC, sound can also be trapped in the SSC [Ref. 1].

#### II. <u>THEORY</u>

#### A. SCUND IN THE SEA

The manner in which sound is transmitted through a medium depends on the velocity with which it propagates. Because of the greater density of seawater, sound is transmitted much faster in the ocean than in the air. The velocity of sound at any given point in the ocean is determined by the temperature, salinity and pressure. Since pressure varies linearly with water depth, these two quantities can be treated as interchangeable. Temperature and depth are generally the dominant factors affecting the speed of sound. Thus the velocity of sound in the ocean varies in all dimensions: hcrizontally, vertically and temporally [Ref. 2].

The sound velocity can be measured directly using a velocimeter or indirectly using a bathythermograph (BT) to measure temperature as a function of depth. Numerous researchers have provided empirical formulas for calculating velocity from temperature, salinity and depth [Ref. 3]. In either case the result is a record of the sound velocity as it changes with depth, or sound velocity profile (SVP).

Snell's Law of acoustics is exactly analogous to Snell's Law of optics. When a ray of light or sound passes from one medium into another, the ray is bent or refracted toward the medium in which it travels at the slower speed. The ocean may be thought of as composed of many layers of water, in each of which sound has a different velocity. Where the SVP shows a velocity minimum, sound is refracted toward that depth, resulting in a focusing of energy at that velocity minimum. This depth is often referred to as a sound channel axis. Dosso and Chapman were able to obtain good agreement between their experimental results and the predictions of the model. A full discussion of Dosso and Chapman's experiment is contained in Chapter III.

This study examines the Dosso and Chapman experiment, then attempts to reproduce their results using the Naval Postgraduate School's PE and FACT 9H models. Chapter IV compares these predictions with the Dosso and Chapman results, supporting the use of the two models to predict the optimum frequency for sound propagation within a shallow sound channel. The models are then applied to two sound velocity profiles of interest to the Naval Postgraduate School's Environmental Acoustic Research Group. These profiles were obtained under summer conditions in a deep ocean basin (4000 meters) at high latitude. Chapter V describes the results of the NPS PE model as applied to these profiles. Chapter VI discusses the FACT 9H model and its predictions for the Dosso and Chapman profiles and the high-latitude summer profiles. Chapter VII then summarizes this study's results and conclusions and presents recommendations for further investigation.

The first model, the split-step Parabolic Equation (PE) model, uses a parabolic approximation to the basic wave equation and solves for pressure levels as a function of range. It is considered to be a low-frequency (below 800 Hz) model, since higher frequencies require large amounts of computational time. The PE model, a full-wave solution, is considered a benchmark against which other transmission loss models are tested. It is not commonly used in support of fleet operations due to the large computational times required.

The second model, Fast Asymptotic the Coherent Transmission loss model version 9H (FACT 9H), employs raytracing techniques to predict the amount of acoustic energy arriving at a receiver as a function of range. This model is less rigorous in predicting the effects of different types of boundaries and it does not allow for variations of the sound velocity profile with range. It is simpler and requires less computational time. FACT is generally considered more appropriate than the PE model for frequencies above 800 Hz. The FACT model is widely used in acoustic transmission loss predictions provided to fleet users in the Both the PE model and FACT 9H are available at U. S. Navy. the Naval Postgraduate School, accessed through the IBM 3033 computer.

In 1984 Dosso and Chapman [Ref. 1] reported an experiment on propagation loss that they had conducted in the northeast Pacific Ocean. Sound velocity profiles indicated the presence of a shallow sound channel overlying a deep sound channel. They placed sources of known magnitude in the shallow sound channel, with receivers in the shallow sound channel and the deep sound channel. They measured propagation losses over ranges extending from zero to 35 km for propagation both within the SSC and across the boundary with the DSC. Using a split-step parabolic equation model,

resulting from winds and turbulence which may extend from the surface to depths of several tens of meters. Below the mixed layer a shallcw sound channel (SSC) is formed by a combination of temperature and salinity gradients, resulting in a sound speed minimum (channel axis) at roughly 80 to 200 The lower edge of the SSC is bounded by an area of meters. rapidly increasing scund speed. Below the SSC the combined effects of decreasing temperature and increasing pressure can also result in a second or deep sound channel (DSC) with an axis at about 800 to 1000 meters in mid-latitudes. Sound channels act as acoustic waveguides, trapping certain frequencies and allowing them to propagate especially well, while other frequencies "leak" out of the channel and propagate poorly. A more complete discussion of the theoretical background for this paper is contained in Chapter II.

The various layers and channels discussed above occupy the top several hundred to one thousand meters of the Submarines operate within these depths. oceans. These features of the sound velocity profile strongly affect the propagation of the submarine's acoustic signature, and the active and passive operation of the submarine's sonar equipment and that of its hunters. Antisubmarine warfare (ASW) operators must understand these effects and have some means of predicting them. With reliable predictions operators will be able to select frequencies and modes of operation to maximize the effectiveness of their sonar equipment in detecting and tracking the submarine.

# B. OBJECTIVE

This study seeks to use two acoustic transmission loss models to predict the behavior of sound in typical shallow sound channels. Both models are available at the Naval Postgraduate School (NPS), accessed through the IBM 3033 computer.

# I. INTRODUCTION

#### A. BACKGROUND

Despite technological advances in ship silencing, the acoustic signature produced by a submarine's main propulsion system and auxiliary machinery remains the single most easily exploited tool for detecting, tracking and localizing the submarine. The transmission of sound through the ocean is predictable given a sufficiently well-defined knowledge of the environment, the source and the receiver. The transmission of sound in the sea depends on the sound velocity profile (SVP). Sound velocity in turn depends on the temperature, salinity and depth of the water. Transmission phenomena can become extremely complex, even for relatively simple sound velocity profiles.

Acoustic transmission loss models have been developed for implementation on digital computers. The models generally take one of two approaches: either solving the acoustic wave equation or employing ray-tracing techniques. Both approaches require assumptions, simplifications and approximations. For real situations some models will predict transmission loss more accurately than others depending on the computational technique involved, the method of solution and the extent to which the model accepts real conditions for boundaries at the sea surface, the sea floor and between different water masses.

The situation of interest here is one of the more complicated cases: the shallow sound channel. This situation develops in higher latitudes of the world's oceans, where precipitation is heavy and evaporation is small. A sound velocity profile reveals the presence of a mixed layer

#### ACKNOVLEDGEMENTS

ď

The author wishes to acknowledge the kind assistance of Dr. N. R. Chapman of the Defence Research Establishment Pacific in Victoria, British Columbia, in providing experimental data and background information. The author also wishes to thank Prof. S. W. Yoon and Prof. C. R. Dunlap for their support and patience. energy levels. Bottom interactions could not be isolated from more distant signals. Propagation loss was calculated as known source level minus the received level measured at the hydrophones.

# B. RESULTS AND DISCUSSION

For the shallow sound channel [Ref. 1], measured propagation loss was plotted as a function of range for the 1/3 octave hands. The propagation loss demonstrated strong dependence on range, as expected. An optimum frequency for propagation of about 800 Hz was observed.

Figure 3.4 shows the propagation loss measured by Dosso and Chapman for both source and receiver located within the shallow sound channel. The solid curve represents geometrical spreading loss, calculated from

# $H = |0|_{0.00} (R \cdot R_0)$ (eqn 3.1)

where range R and ocean depth  $R_0$  are measured in meters. Figure 3.4 (a) represents propagation loss below the optimum frequency cf 800 Hz; Figure 3.4 (b) represents propagation loss above 800 Hz. The close agreement between the geometrical loss curve and the 800 Hz data over much of the range is noteworthy.

Figure 3.5 displays the propagation loss within the shallow sound channel for the optimum propagation frequency of 800 Hz, with the effects of chemical absorption removed. Again the solid line represents geometrical spreading for comparison. Note the abrupt increase in losses over the 8-20 km range. Over this range the sound channel axis deepened, so that the sources were no longer within the duct.

Figure 3.6 presents the same data plotted as a function of frequency for three-point range averages centered at 24 and 33 km. The solid circles represent actual measurements: the open circles represent values adjusted upward to remove the effects of chemical absorption. The dotted lines represent the expected lcss from geometrical spreading alone at 800 Hz. This display shows more clearly the optimum frequency of 800 Hz and how closely the losses for this frequency approximate the losses due to qeometrical spreading alone. It was clear that frequencies above and below 800 Hz experienced greater losses. Diffraction or "leakage" from the shallow sound channel accounted for the losses at lower frequencies. High frequencies experienced losses due to chemical absorption mechanisms and scattering.

# C. CCHPARISON BETWEEN SSC AND DSC PROPAGATION

The deep sound channel trapped lower frequencies (longer wavelengths) than the shallow sound channel because the DSC is much thicker. Figure 3.7 demonstrates the effects of receiver depth on propagation loss. The sources were located at 98 meters, near the shallow sound channel axis. One receiver was also near the shallow sound channel axis at 101 meters. The other receiver was positioned at 417 meters, near the deep sound channel axis. At 160 Hz sound leaked easily out of the shallow sound channel but was well trapped within the deep sound channel. At 315 Hz. iust above the cutoff frequency for the shallow sound channel, propagation in the channel improved. At 630 Hz sound was effectively trapped in the shallow sound channel, and propagation loss at the deep receiver was significantly greater than at the shallow receiver.

Dosso and Chapman plotted relative gain between the two receivers according to the relationship

Relative 
$$Gain = T \Box DEEP - T \Box SHALLOW$$
 (eqn 3.2)

Figure 3.8 displays the results for a four-point range average centered at 24 km. The cutoff frequency of 250 Hz is clearly demonstrated. Below 250 Hz the SSC fails to trap the sound effectively, giving larger transmission losses than the DSC and a negative relative gain. Above 250 Hz the SSC traps the sound tetter, producing smaller transmission losses than the DSC and a positive relative gain. Larger propagation losses in the SSC below 25 Hz result from surface decoupling effects.

# D. MODELING PROPAGATION LOSS IN THE SSC

Geometrical spreading is a simple model, but it is not able to predict the frequency and range dependence that Dosso and Chapman observed. A split-step parabolic equation (PE) model was used to calculate propagation loss based on the sound velocity profiles measured at ranges of zero, 16 and 33 km along the track. [Ref. 1]. Attempts to model propagation using only these three profiles, however, were unsatisfactory. The 16 km profile indicated that the axis of the SSC had deepened, so that the sources were no longer contained in the channel. This is reflected in the increased propagation loss over the 5-20 km range in Figure 3.5. The improved propagation at and beyond 20 km indicated to Dosso and Charman that the axis of the SSC must have risen to about 100 meters again. For this reason they used the profile recorded at 33 km for the 20 km range also. **Dosso** and Chapman also truncated their four sound velocity profiles at a depth of 600 meters, introducing an acoustically transparent bottom at that depth [Ref. 7]. This step had the practical effects of limiting the Pourier transform matrix to a manageable size and shortening computational It may also have had some effect on the time somewhat. predicted losses.

With these four sound velocity profiles Dosso and Chapman's model predicted losses with an acceptable degree of accuracy at 25 Hz and 630 Hz (the practical lower and upper limits of their model). But near the cutoff frequency of 250 Hz, the predicted losses were not in such good agreement with observed losses. The model did, however, predict strong dependence on both frequency and range as Dosso and Chapman observed. Figure 3.9 shows the model results compared to actual measurements.

# E. SUMMARY OF DOSSO AND CHAPMAN'S EXPERIMENT

Dosso and Chapman point out that the shallow sound channel behaved like an acoustic waveguide with optimum propagation at 800 Hz, with increased losses at lower frequencies due to diffraction and at higher frequencies due to absorption and scattering [Ref. 1]. The propagation was found to be very sensitive to changes in the environment. The PE model that Dosso and Chapman used was able to account for these range-dependent effects with good agreement with experimental results at low and near-optimum frequencies. intermediate frequencies the model showed range and At frequency dependent effects, but the predicted losses were greater than experimental results indicated. Dosso and Chapman emphasize that more accurate modeling of propagation losses requires a much finer sampling of the environment; that is, sound velocity profiles at much closer intervals than 16 kilometers.



Pigure 3.1 Dosso and Chapman's Sound Velocity Profile at 0 Km.



Figure 3.2 Dosso and Chapman's Sound Velocity Profile at 16 Km.



REPRODUCED AT GOVERNMENT EXPENSE

Figure 3.3 Dosso and Chapman's Sound Velocity Profile at 20 and 33 Km.





.




Figure 3.5 Propagation loss for 800 Hz, Absorption Removed (Dosso and Chapman).



Figure 3.6 Measured Loss vs Frequency for Three-point Range Averages (Dosso and Chapman).



Figure 3.7 Propagation Loss vs Range for Deep and Shallow Receivers (Dosso and Chapman).



Figure 3.8 Relative Gain between Deep and Shallow Receivers (Dosso and Chapman).



Figure 3.9 PE Model Results with Observations for 630 and 25 Hz (Dosso and Chapman).

والمستقد والمستقد

## IV. THE NES PARABOLIC EQUATION MODEL

Dosso and Chapman reported good results [Ref. 1] using their split-step Parabolic Equation (PE) model to predict propagation loss in a range-dependent environment where both a shallow sound channel and a deep sound channel existed. The first step in this study was to attempt to reproduce those results using the PE model available at Naval Fostgraduate School Monterey.

### A. MODEL DESCRIPTION

The split-step Parabolic Equation (PE) acoustic transmission loss model was chosen for study because it produces a numerical solution for an approximation to the wave equation and is generally considered to provide the most accurate tool for predicting transmission loss. It is often used as a benchmark against which to compare the performance of other transmission loss models. It can deal with rangedependent environments (multiple sound velocity profiles) and with some interaction of sound with the sea floor. Its drawbacks are its relatively low-frequency capability, inability to handle all bottom loss conditions, and lack of flexibility in dealing with boundary conditions at the sea surface (the model uses a flat pressure-release boundary which does not account for the effects of wind and waves). This PE model is implemented on the IBM 3033 computer at the Naval Postgraduate School (NPS) and is accessed through an interactive program developed and managed by the school's oceanography department.

The FORTRAN source code for this PE model was written by the Acoustic Environmental Support Detachment (AESD) of the



2.8

REPRODUCED AT GOVERNMENT EXPENSE

Figure 4.7 Transmission Loss vs Frequency (NPS PE Model).



Figure 4.6 Transmission Loss for 800 Hz, Absorption Removed (NPS PE Model).

والمتحر والمراجع والم



Figure 4.5 Transmission Loss vs Range, 25 Hz (NPS PE Model).

# REPRODUCED AT GOVERNMENT EXPENSE



Figure 4.4 Transmission Loss vs Range, 100 Hz (NPS PE Model).



Figure 4.3 Transmission Loss vs Range, 250 Hz (NPS PE Model).



Figure 4.2 Transmission Loss vs Range, 800 Hz (NPS PE Model).



Figure 4.1 Transmission Loss vs Range, 2000 Hz (NPS PE Model).

demonstrated an appropriate cutoff frequency around 250 Hz, but with unexpected reaks at frequencies well below cutoff.

Some of these anomalous results from the NPS PE model may arise from using full-depth sound velocity profiles. Reasoning from ray-tracing theory, a fully absorbing bottom placed at 2500-2900 meters may have allowed sufficient depth for some deep propagation paths to be refracted back toward the receiver. The fully absorbing bottom at 600 meters which Dosso and Chapman used in their modeling may have eliminated propagation by these paths. Interference effects between these paths and the ducted propagation may account for some of the differences between Dosso and Chapman's results and the NPS PE results.

followed by better propagation at longer about 18 km. Their predictions correspond rather well to the ranges. measurements. On the other hand, Figure 4.12 predicts several dB better propagation for 630 Hz than was observed ranges less than 15 km and several dB worse than for observed at ranges beyond 20 km. Again the compensation using the 20 km profile was less successful for the NPS PE model than for Dosso and Chapman's model. The steep drop and failure to recover in the transmission loss curves are even more apparent in Figure 4.13 for 400 Hz and Figure 4.14 for 250 Hz. In Figure 4.15 for 25 Hz the observed values match quite well with predicted values out to about 15 km. At that point the prediction goes wrong again and predicted values fall 10-15 dB below measured values.

### C. DISCUSSION OF NPS PE RESULTS

Discounting the multipath effects on transmission loss which produce extreme fluctuations in transmission loss with both range and frequency, it appears valid to use the NPS Parabolic Equation mcdel to estimate optimum frequency for sound propagation in a shallow sound channel. The plot of transmission loss versus frequency (Figure 4.7) shows an optimum frequency range of 500-700 Hz. This is acceptable comparison with Cosso and Chapman's measured optimum in frequency of 800 Hz for the same set of sound velocity This is also good enough for active and passive profiles. sonar operators to use in selecting the best frequency ranges for their equipment.

The NPS PE model was not, however, a good estimator for absolute levels of transmission loss. The NPS PE curves showed large differences in transmission loss levels when compared to Dosso and Chapman's measurements. For relative gain between deep and shallow receivers the NPS PE model

trapping and leaking are better balanced. There is still a 10 dB better propagation for the 15-17.5 km range when both source and receiver are in the channel. Figure 4.10 demonstrates significant transmission loss for 160 Hz, which is well below cutoff. In this case the deep receiver experiences better propagation by 5-10 dB over almost the entire range, indicating that the shallow sound channel failed to trap this frequency effectively.

It should especially be noted in Figures 4.8 and 4.9 that ancmalous propagation is occurring in the 17-25 km range. This may be due to the change in depth of the shallow sound channel that Dosso and Chapman noted and tried to correct by adding the sound velocity profile at 20 km. This compensation was apparently much less successful with the NPS FE model than with Dosso and Chapman's model.

Figure 4.11 corresponds to Figure 3.8. Relative gain is calculated according to equation 3.2, following Dosso and Chapman's procedure. Their results were good for 24 km. showing a sudden improvement above the 250 Ħz cutoff frequency when both source and receiver were in the SSC. The curve for the NPS PE model at the 24 km range does not produce good results, probably due to the failure of the added profile at 20 km to compensate for the changing depth of the SSC. The 15 km curve, however, is taken before the SSC deepened and indicates better results. The 250 Ηz NPS results, cutoff frequency is clearly indicated. The however, show unexpected peaks at 40-50 Hz and at 100 Hz, where the shallow sound channel receiver should not be doing as well as the deer receiver. Other frequencies below cutoff behave as expected.

Together Figures 4.12 through 4.15 correspond to Figure 3.9, where Dosso and Chapman plotted their PE model predictions along with experimentally measured data. Note that Dosso and Chapman's 630 Hz curve shows a minimum at

The NPS model allows the user to select whether attenuation will be considered. Figure 4.6 represents the NPS PE model prediction for 800 Hz without attenuation. Again the steep drop in transmission occurs between 15 and 20 km. A comparison with Figure 4.2 shows that the two curves are essentially similar, but attenuation accounts for a 1-2 dB greater loss in Figure 4.2.

Dcssc and Chapman's experimental data yielded good results when propagation loss was plotted as a function of frequency for 24 and 33 km (Figure 3.6). Recall that Dosso and Charman measured 1/3 octave band levels and then calculated three-point range averages to obtain each curve. The NPS PE model produces transmission loss predictions for discrete frequencies. To obtain transmission loss for the desired ranges, values were read from the computer-generated PE model graphic output at the appropriate ranges and at one kilometer on either side. The three values for each range were averaged to produce the values used in plotting Figure 4.7. Again multipath interference effects can account for the fluctuations with range and frequency. While an optimum frequency of 800 Hz is easy to read from Figure 3.6, it is more difficult to state an optimum frequency from Figure 4.7. Frequencies in the 500-700 Hz range seem to have propagated best.

Dosso and Chapman compared results from shallow sound channel and deep sound channel receivers in Figure 3.7. Figures 4.8 through 4.10 present the corresponding results from the NPS PE model. As expected for a frequency well above cutoff, the 630 Hz curves (Figure 4.8) show better propagation where both source and receiver were within the shallow sound channel, but much greater loss (up to 10-20 dB) where the receiver was in the deep sound channel. The two curves are in closer agreement for 315 Hz (Figure 4.9) as would be expected for a frequency near cutoff, where

Compare Figures 4.1 through 4.5 with Figure 3.4. The smooth, downward trending curve represents transmission loss due to geometric spreading alone, calculated from equation 3.1. The measured 1/3 octave band levels of Figure 3.4 show signs of smoothing because many frequencies have been added together, lessening the multipath interference effects that become apparent for discrete frequencies [Ref. 1].

It is apparent, however, that frequencies below the cutoff frequency of 250 Hz propagate poorly within the shallow sound channel and that higher frequencies propagate better. An interesting outcome here is that the 2000 Hz experiences less transmission loss than the experimentally determined optimum frequency of 800 Hz at ranges greater than 17.5 km. Note also that the three highest frequencies all show sudden steep increases in transmission loss in the 17-20 km range and that the levels never really recover. This is the range at which Dosso and Chapman noted a change in their sound speed profiles so that their sources were no longer within the shallow sound channel.

Dosso and Chapman observed an increase in transmission loss over roughly the same ranges (Figure 3.4), followed by better propagation at ranges beyond 20 km. They were able to model these results successfully by adding another sound velocity profile at 20 km, using the same profile they had measured at 33 km. With the same input parameters the NPS PE model yielded a much steeper drop and did not indicate a return to levels expected from the experimental data.

Dosso and Chapman's Figure 3.5 compares to Figure 4.6. For Figure 3.5 Dosso and Chapman plotted measured data, with losses due to chemical absorption removed. This figure clearly shows the close correspondence between the measurements for the optimum frequency of 800 Hz and the losses predicted for geometrical spreading alone. The only anomalies arise over the 8-20 km range, as discussed above. solved numerically using the Tappert-Hardin split-step Fourier algorithm to yield a solution for the entire acoustic pressure field as a function of range and depth [Ref. 6].

The PE solution is best where the source and receiver are arranged so that the path between the two makes a small angle with the hcrizcntal. At larger angles, the group and phase velocities of the computed solution become subject to errors and produce inaccurate representations in the interference pattern. This affects the accuracy of the predicted transmission loss for a given range. Computing time increases quickly with frequency. The numerical solution is limited by the practical Fourier transform size, which means that the input environment governs the extent to which the model can handle higher frequencies. For practical purposes the PE model should be used to predict propagation loss for frequencies below 200 Hz along waterborne or shallow bottombounce paths [Ref. 6].

The FE model becomes inappropriate for situations where the bottom slopes steeply and where large sound speed gradients cccur [Ref. 6].

### B. VALIDATION AGAINST DOSSO AND CHAPMAN'S DATA

This study is concerned with waterborne paths and shallow angles. We are not specifically interested in bottom interactions. Even though the frequencies in which we are interested may be as high as 800 Hz [Ref. 1], we are willing to use computational time to examine a full-wave solution. Especially important for comparison with Dosso and Charman's experimental data is the fact that the PE model can utilize a range-dependent environment. The input parameters described in Appendix A are derived from [Ref. 1] and [Bef. 7]. The resulting information and displays show reasonable agreement with Dosso and Chapman's work. Naval Ocean Research and Development Activity (NORDA) during the 1970's. A complete description of the physics and algorithms for this model are given in [Ref. 6]. The wave equation

$$\left[\nabla^{2} + K_{0}^{2} n^{2}(r,z)\right] P(r,z) = 0 \qquad (eqn 4.1)$$

is an elliptic equation which describes acoustic pressure as a function of range r and depth z. It can be approximated by a parabolic partial differential equation of the form

$$\frac{\partial \Psi}{\partial r} = i (A + B) \Psi \qquad (egn 4.2)$$

where

$$A = -\frac{1}{2K_0} \frac{\partial^2}{\partial z^2} \qquad (egn 4.3)$$

and

$$B = \frac{K_{o}}{2} (n^{2} - |) \qquad (eqn 4.4)$$

This solution makes the assumptions that the sound is propagating radially outward from a source in a cylindrically symmetric medium and that the range r is very large compared to the size of the source and the wavelength of the sound: these are the cylindrical symmetry and the far-field assumptions. The source is further considered to be oscillating harmonically at a discrete frequency. The ccean surface is considered to be a flat pressure-release boundary, and the acoustic field vanishes in the bottom at the maximum depth of the Fourier transform [Ref. 6].

The parabolic equation accounts for diffraction and other full-wave effects; it also allows solution for rangedependent environments. The parabolic equation can be











Figure 4.10 Shallow vs Deep Receiver, 160 Hz (NPS PE Model).







Figure 4.12





# REPRODUCED AT GOVERNMENT EXPENSE

Figure 4.13

r





Figure 4.14 Transmission Loss vs Range, 250 Hz (NPS PE Model).



Figure 4.15 Iransmission Loss vs Range, 25 Hz (NPS PE Model).

the optimum frequency prediction somewhat for the 10 June case.

Putting all three cases together and looking for a trend, we can tentatively identify a range of optimum frequencies around 600-900 Hz. The results for these shallow sound channels are not as clear or conclusive as Dosso and Chapman's results, but they should be adequate for the fleet sonar operator to use in setting up search plans.

### B. OPTINUM FREQUENCY FOR PROPAGATION ACROSS THE LAYER

The second part of this investigation involved the same sound velocity profiles with the source still located at 98 meters near the SSC axis, but with the receiver modeled at 20 meters, well within the surface layer. Figures 5.15 through 5.17 show the results.

Figure 5.15 for 28 June shows peaks at 125 and 600 Hz in the transmission loss versus frequency curves for 15, 24 and 33 km. Again the concept of cutoff frequency does not appear to have much meaning in these cases. Figure 5.16 shows peaks at 160-200 Hz and at 700 Hz. For the truncated 10 June profile, Figure 5.17 shows best propagation at 75-100 Hz. There is a peak at 800 Hz, but the transmission loss is greater than at 75-100 Hz.

Figures 5.18 through 5.20 show relative gain for our three cases, calculated according to the equation

Relative Gain =  $TL_{LAYER} - TL_{SSC}$  (eqn 5.1)

These high-latitude summer profiles do not show a cutoff frequency between the SSC and the surface layer. Propagation is always better when both source and receiver are contained within the shallow sound channel than when the source is in the SSC and the receiver is in the surface layer.

# REPRODUCED AT GOVERNMENT EXPENSE



Figure 5.1 High-latitude Sound Velocity Profile, 10 June.



Figure 5.2 High-latitude Sound Velocity Profile, 28 June.

# REPRODUCED AT GOVERNMENT EXPENSE 1000 FREQUENCY (HZ)

(EC) SSOT NOISSIWSNAU Figure 5.3 Transmission Loss Vs Frequency, 28 June (NPS PE Model).

ŚZ

08

9

06

58

02

59

. . . . .





۰.

Figure 5.4 Transmission Loss vs Frequency, 10 June (NPS PE Model).



Figure 5.5 Transmission Loss vs Range, 28 June, 600 Hz (NPS PE Model).



Figure 5.19 Relative Gain between Surface Layer and SSC, 10 June (NPS PE Model).



Figure 5.18 Relative Gain between Surface Layer and SSC, 28 June (NPS PE Model).


Figure 5.17 Transmission Loss between Surface Layer and SSC, Truncated Profile (NPS PE Model).



REPRODUCED AT GOVERNMENT EXPENSE

.....

Figure 5.16 Transmission Loss between Surface Layer and SSC, 10 June (NPS PE Model).



. . . .

1.12

Figure 5.15 Transmission Loss between Surface Layer and SSC, 28 June (NPS PE Model).



Figure 5.14 Transmission Loss vs Range, Truncated Profile, 900 Hz (NPS PE Model).



Figure 5.13 Transmission Loss vs Range, Truncated Profile, 800 Hz (NPS PE Model).



Figure 5.12 Transmission Loss vs Range, Truncated Profile, 700 Hz (NPS PE Model).



Figure 5.11 Iransmission Loss vs Frequency, Truncated Profile (NPS PE Model).



Figure 5.10 Transmission Loss vs Range, 10 June, 300 Hz (NPS PE Model).



Figure 5.9 Transmission Loss vs Range, 10 June, 700 Hz (NPS PE Mod el).



Figure 5.8 Transmission Loss vs Range, 28 June, 900 Hz (NPS PE Model).



Figure 5.7 Transmission Loss vs Range, 28 June, 800 Hz (NPS PE Model).



Figure 5.6 Transmission Loss vs Range, 28 June, 700 Hz (NPS PE Model).

# REPRODUCED AT GOVERNMENT EXPENSE



Figure 5.20 Relative Gain between Surface Layer and SSC, Truncated Profile (NPS PE Model).

### VI. THE NPS FACT 9H MODEL

### A. HODEL DESCRIPTION

The Fast Asymptotic Coherent Transmission loss mcdel. version 9H (FACT 9H), like the split-step Parabolic Equation model, is accessed through the Naval Postgraduate School's FACT currently provides the acoustic IBM 3033 computer. predictions for the Integrated Command ASW Predicticn System s. (ICAPS) on board U. Navy aircraft carriers and ASW Operations Centers (ASWOCs) worldwide. It is also the basis for a number of acoustic products routinely provided by the Fleet Numerical Oceanographic Center, Monterey, to fleet users. Since the FACT model and its products are so widely distributed in the fleet, it is of interest to know how well FACT performs for the shallow sound channel case.

The FACT 9H model as installed at the Naval Postgraduate School was developed for the Naval Ocean Research and Development Activity (NORDA) [Ref. 8]. It uses ray tracing theory with special corrections to improve the treatment of caustics, which would produce calculations indicating excessive acoustic energy at certain ranges if not corrected. Unlike the PE model, FACT 9H accepts only one sound velocity profile, located at range zero. It makes no allowance for bottom topography changing over the length of a track. The user may indicate the absorption characteristics of the bottom, or specify a table of values for bottom loss versus grazing angle.

In addition, a semi-empirical expression is used to account for propagation in a surface duct. In this module the user may indicate the wave height, unlike the NFS PE model which makes no provisions for boundary conditions at

the surface. As a ray-tracing model, FACT 9H is not expected to deal with waveguide phenomena such as diffraction and leakage as successfully as the PE model does. The surface duct module is intended to remedy this problem somewhat and to improve the acoustic prediction in the case of surface ducts. No correction has yet been applied for shallcw sound channels.

The investigation of the FACT 9H model proceeded along essentially the same lines as that of the PE model. The FACT 9H model was first tested against the experimental results of Dosso and Chapman. Then the model was applied to the 10 June and 28 June sound velocity profiles. Input parameters are described in Appendix A.

### B. VALIDATION AGAINST DOSSO AND CHAPMAN'S DATA

Since FACT 9H does not allow for a range-dependent environment or for wave effects like diffraction and leakage, it was not expected to perform very well for the shallow sound channel observed by Dosso and Chapman. Again the first test applied to the FACT 9H output was a plot of transmission loss versus frequency (Figure 6.1). As for the PE model, the levels were obtained by taking three-point range averages centered at 24 km. Since only the zero range sound velocity profile was used, there was no need to be concerned about the effects of the shallow sound channel axis deepening over the eight to twenty kilometer range.

Surprisingly, the transmission loss when both source and receiver were within the SSC showed a gradual decrease and optimum values at 800-900 Hz, consistent with Dosso and Chapman's actual measurements. Over the entire frequency band tested the FACT 9H model predicted losses between 70 and 78 dB, while Dosso and Chapman observed losses between about 80 and 110 dB. The transmission loss in the optimum

frequency range is some 10 dB less than Dosso and Chapman's measurements, but at least the optimum occurred at the proper frequencies. The transmission loss curve for the deep sound channel receiver showed only a fairly consistent increase with higher frequencies.

Figures 6.2 and 6.3 are the FACT 9H transmission loss curves for the three frequencies near optimum. The shallow receiver curves (Figure 6.2) show more fluctuations, probably due to multipath arrivals of sound reflecting from the flat ccean surface. The deep receiver curves (Figure 6.3) are smoothed by the partial absorption of sound in the ocean bottom.

The plot of relative gain (Figure 6.4) reiterates the information in Figure 6.1 in a way that should indicate the presence of a cutoff frequency. We already know that the channel should exhibit a cutoff frequency at about 250 Hz, but there is no evidence for this in Figure 6.4. The shallow receiver always shows better propagation than the deep receiver. This result is not surprising in that the FACT 9H model is not designed to handle such wave effects.

### C. THE HIGH-LATITUDE SHALLOW SOUND CHANNELS

With good predictions for optimum frequency in the Dosso and Charman case, the investigation proceeded to the 10 June and 28 June high-latitude, deep ocean sound velocity profiles. For the 28 June case (Figure 6.5) transmission loss in the shallow scund channel did indeed show a gradual rise and fall. The best frequency, however, was in the vicinity of 400 Hz, much lower than the 600-900 Hz predicted by the PE model (Chapter 5, Section A). As one might expect, transmission losses between the SSC and the surface layer are always significantly greater than when the source and receiver are both contained in the SSC.

As for the 10 June case, FACT 9H results showed a slight but steady increase in transmission loss over the entire frequency range (Figure 6.6). The best frequency was, in 75 Hz. fact, the lowest tested: The transmission loss curve for the receiver located in the surface layer is only a few dB greater than the SSC curve. Recall that the NPS PE model also failed to produce satisfactory results for the 10 June case. Truncating the sound velocity profile at 150 meters with a fully absorbing bottom seemed to improve the PE model prediction somewhat, but Figure 6.7 does not present much of a difference for the FACT 9H model.

Perhaps the 10 June case is a "weaker" shallow sound channel for modeling purposes. Dosso and Chapman's sound velocity profiles show a velocity gradient between 0.1436/s and 0.2071/s between the bottom of the surface layer and the axis of the shallow sound channel. The 28 June sound velocity profile has a velocity gradient of 0.1871/s. The 10 June sound velocity profile, however, has a velocity gradient of only 0.0737/s. There may be a critical value for the velocity gradient between the surface layer and the SSC axis that will produce good results in the models.

For now, however, it does not appear that the FACT 9H model is successful in predicting optimum frequencies for propagation of sound in shallow sound channels. In view of the extensive usage of the FACT model to provide acoustic transmission loss products to fleet operations, this problem warrants further attention.



Figure 6.1 Transmission Loss vs Frequency, Dosso and Chapman (NPS FACT 9H Model).



Figure 6.2 Transmission Loss in the Shallow Sound Channel, Dosso and Chapman (NPS FACT 9H Model).

### REPRODUCED AT GOVERNMENT EXPENSE







Figure 6.4 Relative Gain, Dosso and Chapman (NPS FACT 98 Model).

. . .



\_\_\_\_\_

Figure 6.5 Transmission Loss vs Frequency, 28 June (NPS FACT 98 Model).



Figure 6.6 Transmission loss vs Frequency, 10 June (NPS FACT 98 Model).



· .

Figure 6.7 Transmission Loss vs Frequency, Truncated Profile (NPS FACT 9H Model).

### VII. CONCLUSIONS

### A. RESULTS AND DISCUSSION

Two acoustic transmission loss models were examined to determine how well they predicted the optimum frequency for propagation of sound in shallow sound channels. The splitstep Farabolic Equation (PE) model performed satisfactorily, while the Fast Asymptotic Coherent Transmission (FACT 9H) model was less satisfactory.

The FE model has two advantages: it allows for a rangedependent environment and it is a full-wave approximation for the wave equation. These two factors enable the PE model to deal with wave phenomena like diffraction and The PE model predicted ducting with a degree of success. optimum frequencies cf 600-900 Hz for the shallow sound channels under study, consistent with the 800 Hz actually measured by Dosso and Chapman. The model seemed to produce tetter results when the sound velocity gradient between the overlying surface layer and the shallow sound channel was The 28 June case, where the gradient was pronounced. 0.1371/s, yielded 600-900 Hz for optimum frequency, but the 10 June case, where the gradient was only 0.0737/s, did not The 10 June predicticn was produce an optimum frequency. improved somewhat by introducing a fully absorbing bottom at the lower boundary of the shallow sound channel.

The FACT 9H model has its advantages, too: it is efficient in terms of computational time and it is the Navy's standard acoustic propagation loss model at the time of this writing. As a ray-tracing model, it was not expected to handle situations involving surface ducts or shallow sound channels as successfully as the PE model, even with the

semi-empirical surface duct module built into this version of FACT. The Dosso and Chapman sound velocity profiles resulted in a surprisingly good prediction of 800-900 Hz, which agreed well with the experimental results. The 28 June case, however, predicted an optimum of about 400 Hz; and the 10 June case did not predict any reasonable optimum. Again the strength of the sound velocity gradient may explain these different results.

Of our two choices, the PE model, despite its long computation time, appears to be the better candidate for predicting optimum frequency of propagation in a shallow sound channel. The FACT model, despite its widespread use in the fleet, is not a good predictor for optimum frequency. The predictions for both models seem to be better when there is a large sound velocity gradient between the surface layer and the axis of the shallow sound channel.

### B. RECOMMENDATIONS AND AREAS FOR FURTHER STUDY

The fleet user has no easy access to a Parabolic Equation model to assess optimum frequencies for real-time environmental conditions. While this study predicts an cptimum range of 600-900 Hz where both source and receiver are contained within 80 to 110 meter thick channels, it would be helpful to draw up a table for other sourcereceiver depth combinations and channels of varying thickness.

Several areas merit further investigation. First, this study uses a fully absorbing bottom throughout. This is unrealistic. It would be of interest to assess bottom losses more accurately and determine what difference, if any, this makes in the prediction of optimum frequency. Another area for investigation is the relative strength of shallow sound channels. A strong charnel, where the sound





MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

velocity gradient between the bottom of the surface layer and the axis of the shallow sound channel, appears to trap sound more strongly and to produce a clearer prediction of optimum frequency. It would be helpful to find out how much of a velocity gradient is required to produce an optimum frequency from each of the models, and whether the predicted optimum varies with the strength of the channel.

Finally, other acoustic transmission loss models are available. The implicit finite difference (IFD) PE model is advertised as being able to handle boundary conditions at the ocean bottom more successfully than the split-step PE The IFD model should be investigated. model. The most recent revision of the FACT model, version 10A, is nearly Technical documents [Ref. 9] ready for implementation. indicate that FACT 10A will, among other things, handle ducting situations and boundary conditions better than FACT 9H--this may affect performance for shallow sound channels. A third type of acoustic model is also available--the This model uses a combination of normal mode RAYMCLE model. and ray-tracing techniques and may produce better results than FACI when applied to surface ducts and sound channels. The RAYMODE model has recently been designated as the Navy's new standard acoustic propagation loss model, and its performance should be investigated for as wide a variety of environmental conditions as possible.

## <u>APPENDIX A</u> INFUT PARAMETERS FOR THE NPS PE AND FACT 9H MODELS

Table I describes the input options available to the user through the Naval Postgraduate School's split-step Parabolic Equation (PE) and Fast Asymptotic Coherent Transmission loss (FACT 9H) models. Tables II through VI are the sound velocity profiles used in this study.

| PARAMETERS                                  | PE MODEL                                    | FACT 9H  |
|---|---|--|
| Input units                                 | English<br>or metric                        | English<br>or metric                                 |
| Source depths                               | One   | One  |
| Receiver depths                             | Maximum 20                                  | One  |
| Frequencies                                 | One   | Maximum 6  |
| Maximum range                               | Unlimited                                   | 999 kilometers                                       |
| Range step                                  | Minimum .01 nm<br>or selected by<br>program | Selected by program                                  |
| Number of SVPs                              | Maximum 50                                  | One  |
| Depth levels<br>in SVFs                     | Maximum 50                                  | Maximum 50   |
| Bottom lcss                                 | 1) Fully absorbing                          | 1) Bottom type<br>0 (reflecting)<br>to 9 (absorbing) |
|   | 2) User's loss vs<br>grazing angle table    | 2) User's loss<br>vs grazing angle<br>table          |
|   | 3) User's depth vs<br>attenuation table     | 3) Internal loss<br>vs grazing angle<br>table        |
| Variable<br>Lottom depth                    | Maximum 100 ranges/<br>depths               | No   |
| Correcticn for<br>spherical earth           | Available                                   | Available  |
| Correcticn for<br>for vclume<br>attenuation | Available                                   | Available  |
| Vertical beam<br>size of source             | 1-33 degrees                                | No   |
| Special handling<br>for surface duct        | Not required                                | Yes  |
| Wa <b>v</b> e h <b>e</b> ight               | No  | Yes  |
| Critical angle                              | Not reguired                                | 1) Preset value<br>28.65 degrees                     |
|   |   | 2) User input  |

## TABLE I

.

Input Parameters for the MPS PE and FACT 9H Models

## TABLE II

Dosso and Chapman's Sound Velocity Profile at 0 Kilometers

.

| DEP IH (FT) | C (F1/S) | DEPTH (M) | C (M/S) |
|-------------|----------|-----------|---------|
| 0.          | 4927.82  | 0.        | 1502.00 |
| 45.         | 4927.82  | 14.       | 1502.00 |
| 66.         | 4922.90  | 20.       | 1500.50 |
| 87.         | 4906.50  | 26.       | 1495.50 |
| 115.        | 4890.75  | 35.       | 1490.70 |
| 137.        | 4855.17  | 42.       | 1489.00 |
| 169.        | 4879.92  | 52.       | 1487.40 |
| 198.        | 4873.36  | 60.       | 1485.40 |
| 232.        | 4867.45  | 71.       | 1483.60 |
| 251.        | 4866.47  | 76.       | 1483.30 |
| 273.        | 4865.48  | 83.       | 1483.00 |
| 291.        | 4864.83  | 89.       | 1482.80 |
| 310.        | 4864.83  | 95.       | 1482.80 |
| 325.        | 4864.50  | 99.       | 1482.70 |
| 338.        | 4864.50  | 103.      | 1482.70 |
| 357.        | 4863.52  | 109.      | 1482.40 |
| 369.        | 4863.84  | 112.      | 1482.50 |
| 384.        | 4864.83  | 117.      | 1482.80 |
| 403.        | 4865.48  | 123.      | 1483.00 |
| 433.        | 4866.14  | 132.      | 1483.20 |
| 476.        | 4867.12  | 145.      | 1483.50 |
| 510.        | 4867.12  | 155.      | 1483.50 |
| 543.        | 4866.47  | 166.      | 1483.30 |
| 589.        | 4866.47  | 179.      | 1483.30 |
| 690.        | 4862.20  | 210.      | 1483.00 |
| 779.        | 4859.58  | 238.      | 1481.20 |
| 856.        | 4858.59  | 261.      | 1480.90 |
| 946.        | 4857.61  | 288.      | 1480.60 |
| 1026.       | 4854.66  | 313.      | 1479.70 |
| 1115.       | 4854.00  | 340.      | 1479.50 |
| 1312.       | 4849.41  | 400.      | 1478.10 |
| 1640.       | 4849.08  | 500.      | 1478.00 |
| 1969.       | 4849.73  | 600.      | 1478.20 |
| 2625.       | 4852.36  | 800.      | 1479.00 |
| 3281.       | 4856.62  | 1000.     | 1480.30 |
| 3937.       | 4860.89  | 1200.     | 1481.60 |
| 4921.       | 4870.08  | 1500.     | 1484.40 |
| 6562.       | 4891.07  | 2000.     | 1490.80 |
| 8202.       | 4916.01  | 2500.     | 1498.40 |

## See Figure 3.1.

# TABLE III

Dosso and Chapman's Sound Velocity Profile at 16 Kilometers

| DEPIH (FT)                                | C (F1/S)  | DEPTH (M)                        | C (M∕S)  |
|---|---|----------------------------------|--|
| 0.  | 4923.55   | 0.                               | 1500.70  |
| 16.                                       | 4923.88   | 5.                               | 1500.80  |
| 33.                                       | 4926.51   | 10.                              | 1501.60  |
| 66.                                       | 4924.21   | 20.                              | 15C0.90  |
| 82.                                       | 4924.21   | 25.                              | 15C0.90  |
| 98.                                       | 4898.62   | 30.                              | 1493.10  |
| 131.                                      | 4884.18   | 40.                              | 1488.70  |
| 164.                                      | 4879.26   | 50.                              | 1487.20  |
| 197.                                      | 4877.62   | 60.                              | 1486.70  |
| 230.                                      | 4873.69   | 70.                              | 1485.50  |
| 262.                                      | 4867.12   | 80.                              | 1483.50  |
| 295.                                      | 4864.50   | 90.                              | 1482.70  |
| 328.                                      | 4865.48   | 100.                             | 1483.00  |
| 361.                                      | 4863.84   | 110.                             | 1482.50  |
| 394.                                      | 4863.84   | 120.                             | 1482.90  |
| 427.                                      | 4863.52   | 130.                             | 1482.40  |
| 459.                                      | 4860.89   | 140.                             | 1481.60  |
| 492.                                      | 4860.56   | 150.                             | 1481.50  |
| 525.                                      | 4861.22   | 160.                             | 1481.70  |
| 591.                                      | 4862.86   | 180.                             | 1482.20  |
| 689.                                      | 4861.55   | 210.                             | 1481.80  |
| 787.                                      | 4861.55   | 240.                             | 1481.80  |
| 853.                                      | 4860.23   | 260.                             | 1481.40  |
| 919.                                      | 4859.91   | 280.                             | 1481.30  |
| 984.                                      | 4859.91   | 300.                             | 1481.30  |
| 1050.                                     | 4858.59   | 320 -                            | 1480.90  |
| 1115.                                     | 4858.27   | 340 -                            | 1480.80  |
| 1148.                                     | 4857.61   | 350 -                            | 1480.60  |
| 1181.                                     | 4855.64   | 360 -                            | 1480.00  |
| 1214.                                     | 4853.67   | 370 -                            | 1479.40  |
| 1247.                                     | 4852.69   | 380.                             | 1479.10  |
| 1280.                                     | 4850.72   | 390.                             | 1478.50  |
| 1312.                                     | 4851.37   | 400.                             | 1478.70  |
| 1345.                                     | 4850.39   | 410.                             | 1478.40  |
| 1411.                                     | 4850.39   | 430.                             | 1478.40  |
| 1444.<br>1509.<br>1640.<br>1969.<br>2625. | 4849.73<br>4849.41<br>4850.39<br>485C.72<br>4852.69 | 440 -<br>460 -<br>500 -<br>800 - | 1478.20<br>1478.10<br>1478.40<br>1478.50<br>1478.50<br>1479.10 |
| 3281.                                     | 4856.62   | 1000-                            | 1480.30  |
| 3937.                                     | 4860.89   | 1200-                            | 1481.60  |
| 4921.                                     | 4870.08   | 1500-                            | 1484.40  |
| 6562.                                     | 4891.07   | 2000-                            | 1490.80  |
| 8202.                                     | 4916.01   | 2500-                            | 1498.40  |
| 9514.                                     | 4937.01   | 2900-                            | 1504.80  |

# See Figure 3.2.

### TABLE IV

| DEPIH (FT) | C (F1/S) | DEPTH (M) | C (M/S) |
|------------|----------|-----------|---------|
| 0.         | 4922.57  | 0.        | 1500.40 |
| 33.        | 4921.26  | 10.       | 1500.00 |
| 66.        | 4896.32  | 20.       | 1492.40 |
| 98.        | 4885.82  | 30.       | 1489.20 |
| 131.       | 4878.28  | 40.       | 1486.90 |
| 164.       | 4875.66  | 50.       | 1486.10 |
| 197.       | 4875.33  | 60.       | 1486.00 |
| 230.       | 4873.69  | 70.       | 1485.50 |
| 262.       | 4871.06  | 80.       | 1484.70 |
| 279.       | 4866.47  | 85.       | 1483.30 |
| 295.       | 4864.50  | 90.       | 1482.70 |
| 312.       | 4863.52  | 95.       | 1482.40 |
| 328.       | 4864.17  | 100.      | 1482.60 |
| 344.       | 4863.84  | 105.      | 1482.50 |
| 361.       | 4863.84  | 110.      | 1482.50 |
| 394.       | 4865.16  | 120.      | 1482.90 |
| 427.       | 4864.83  | 130.      | 1482.80 |
| 459.       | 4865.81  | 140.      | 1483.10 |
| 492.       | 4865.48  | 150.      | 1483.00 |
| 558.       | 4865.81  | 170.      | 1483.10 |
| 591.       | 4864.17  | 180.      | 1482.60 |
| 623.       | 4863.52  | 190.      | 1482.40 |
| 656.       | 4860.56  | 200.      | 1481.50 |
| 722.       | 4860.23  | 220.      | 1481.40 |
| 787.       | 4857.61  | 240.      | 1480.60 |
| 853.       | 4856.30  | 260.      | 1480.20 |
| 919.       | 4853.67  | 280.      | 1479.40 |
| 984.       | 4850.72  | 300.      | 1478.50 |
| 1083.      | 4849.73  | 330.      | 1478.20 |
| 1148.      | 4851.05  | 350.      | 1478.60 |
| 1312.      | 4848.75  | 400.      | 1477.90 |
| 1640.      | 4849.08  | 500.      | 1478.00 |
| 1969.      | 4849.41  | 600.      | 1478.10 |
| 2625.      | 4851.70  | 800.      | 1478.80 |
| 3281.      | 4855.97  | 1000.     | 1480.10 |
| 3937.      | 4860.89  | 1200.     | 1481.60 |
| 4921.      | 4870.08  | 1500.     | 1484.40 |
| 6562.      | 4891.07  | 2000.     | 1490.80 |
| 8202.      | 4916.01  | 2500.     | 1498.40 |
| 8858.      | 4927.82  | 2700.     | 1502.00 |

### Dosso and Chapman's Sound Velocity Profile at 20 and 33 Kilometers

### See Figure 3.3.

| Bigh-lati                               | tude Sound   | Velocity Profile fo                    | or 10 June  |
|---|--|--|---|
| DEPIH (FT)                              | C(FI/S)  | DEPTH (M)                              | C(M∕S)  |
| 0.<br>131.<br>164.<br>328.<br>443.      | 4796.59<br>4796.59<br>4780.18<br>4780.18<br>4780.18<br>4773.62 | 0.<br>40.<br>50.<br>100.<br>135.       | 1462.00<br>1462.00<br>1457.00<br>1457.0C<br>1455.00 |
| 492.<br>820.<br>1640.<br>2281.<br>6562. | 4798.23<br>4842.52<br>4824.47<br>4847.11<br>4890.42            | 150.<br>250.<br>500.<br>1000.<br>2000. | 1462.50<br>1476.00<br>1470.50<br>1477.40<br>1490.60 |
| 9843.<br>13123.                         | 4943 <b>.</b> 57<br>4999 <b>.</b> 34                           | 3000-<br>4000-                         | 1506.80<br>1523.80                                  |
|   | See  | Figure 5.1.                            |   |

TABLE V

## TABLE VI

High-latitude Sound Velocity Profile for 28 June

| CEPIH (FT) | C (F1/S) | DEPTH (M) | C (M∕S) |
|------------|----------|-----------|---------|
| 0.         | 4806.43  | 0.        | 1465.00 |
| 115.       | 4804.46  | 35.       | 1464.40 |
| 164.       | 4775.26  | 50.       | 1455.50 |
| 262.       | 4771.65  | 80.       | 1454.40 |
| 328.       | 4765.42  | 100.      | 1452.50 |
| 459.       | 4799.54  | 140.      | 1462.90 |
| 656.       | 4811.68  | 200.      | 1466.60 |
| 1640.      | 4827.43  | 500.      | 1471.40 |
| 3281.      | 4847.11  | 1000.     | 1477.40 |
| 6562.      | 4890.42  | 2000.     | 1490.60 |
| 9843.      | 4943.57  | 3000.     | 1506.80 |
| 13123:     | 4999.34  | 4000.     | 1523.80 |

See Figure 5.2.

#### LIST OF REFERENCES

- 1. Dosso, S. E., and Chapman, N. R., "Acoustic propagaticn in a shallow sound channel in the Northeast Pacific Ocean," <u>Journal of the Acoustical Society of</u> <u>America</u>, v. 75, no. 2, pp. 413-418, February 1984.
- 2. Urick, Robert J., <u>Principles of Underwater Sound</u>, 3d edition, McGraw-Hill Book Company, 1983.
- Kinsler, Lawrence E., Frey, Austin R., Coppens, Alan B., and Sanders, James W., <u>Fundamentals of Acoustics</u>, 3d edition, John Wiley & Sons, 1982.
- 4. Thorp, W. H., "Deep-ocean sound attenuation in the sub- and low kilocycle per-second region," <u>Scientific</u> and <u>Engineering Studies</u>, Y. <u>II</u>, <u>1981</u>: <u>Attenuation of</u> Low Frequency Sound in the Sea, Naval Underwater Systems Center, 1981.
- 5. Mellen, R. H., Simmons, V. P., and Browning, D. G., "Lcw-frequency sound absorption in sea water: A borate-complex relaxation," <u>Scientific and Engineering Studies, V. II, 1981: Attenuation of Low Frequency</u> <u>Sound in the Sea</u>, Naval Underwater Systems Center, 1981.
- Naval Ocean Research and Development Activity Technical Note 12, <u>The AESD Parabolic Equation Model</u>, by H. K. Brock, January, 1978.
- 7. Chapman, N. R., private communication, 21 January 1985.
- 8. Acoustic Environmental Support Detachment, Maury Center Report 109, <u>The FACT Model</u>, by C. W. Spofford, November 1974.
- 9. Naval Ocean Research and Development Agency Report 70, <u>Technical Evaluation of FACT 10A</u>, by R. McGirr, D. White, and C. Bartberger, June 1984.
## INITIAL DISTRIBUTION LIST

|    |   | No. | Copies |
|----|---|-----|--------|
| 1. | Defense Technical Information Center<br>Cameron Station<br>Alexandria, Virginia 22304-6145                                      |     | 2      |
| 2. | Superintendent<br>Attn: Library, Ccde 0142<br>Naval Postgraduate School<br>Mcnterey, Califorria 93943-5100                      |     | 2      |
| 3. | Superintendent<br>Attn: Prof. C. R. Dunlap, Code 68Du<br>Naval Postgraduate School<br>Mcnterey, California 93943-5100           |     | 2      |
| 4. | Superintendent<br>Attn: Dr. S. W. Yoon, Code 61Yo<br>Naval Postgraduate School<br>Mcnterey, Califorria 93943-5100               |     | 5      |
| 5. | Dr. N. R. Chapman<br>Defence Research Establishment Pacific<br>Forces Mail Office<br>Victoria, British Columbia, Canada VOS 1B0 |     | 1      |
| 6. | LCDR W. L. Bradfield-Smith<br>6429 Princeton Drive<br>Alexandria, Virginia 22307  |     | 1      |

106

## END

## FILMED

## 11-85

DTIC