



al al a set a set a set

ANNAL PROPERTY AND A PUBLICA POWER PARAMA

MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

.



PARAMETRIC ANALYSIS OF COMBUSTION OF POROUS MEDIUM

THESIS

Antonio Carlos de Souza Serapiao

December 1985

OTIC FILE COPY

Thesis Advisor:

David Salinas

Approved for public release; distribution is unlimited.

86 2

	REPORT DOCU	MENTATION	PAGE		
a. REPORT SECURITY CLASSIFICATION		1b. RESTRICTIVE	MARKINGS	· · · · · · · · · · · · · · · · · · ·	
- SECURITY CLASSIFICATION AUTHORITY				FREEDET	
		Approved	for publi	c releas	e;
26. DECLASSIFICATION / DOWNGRADING SCHEDULE		distribution is unlimited.			
PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5. MONITORING	ORGANIZATION R	EPORT NUMBER	(5)
a. NAME OF PERFORMING ORGANIZATION	66. OFFICE SYMBOL	7a. NAME OF MO	ONITORING ORGA	NIZATION	
Naval Postgraduate School	(If applicable) Code 69	Naval Postgraduate School			
ADDRESS (City State and ZIP Code)		75 ADDRESS (Cit	v State and ZIP	(ode)	
			<b>,,</b>	,	·
lonterey, California 9394	3-5004	Monterey	, Califorr	nia 93943	-5004
B. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT	T INSTRUMENT ID	ENTIFICATION N	UMBER
c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF F		S	
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT
TITLE (Include Security Classification)					
PARAMETRIC ANALYSIS OF CON	BUSTION OF PO	DROUS MEDI	UM		
2 PERSONAL AUTHOR(S)				<u> </u>	
Serapiao, Antonio Carlos d	le Souza				
laster's thesis	DVERED TO	14. DATE OF REPO December	RT (Year, Month, 1 1985	Day) 15 PAGE	E COUNT 36
6 SUPPLEMENTARY NOTATION				^	
	18. SUBJECT TERMS (C	Continue on reverse	e if necessary and	l identify by blo	ock number)
7 COSATI CODES FIELD GROUP SUB-GROUP	18. SUBJECT TERMS (C	Continue on reverse	e if necessary and	l identify by blo	ock number)
COSATI CODES FIELD GROUP SUB-GROUP	18. SUBJECT TERMS (C Combustion (C	Continue on reverse Df Porous 1	e if necessary and Medium	l identify by blc	ick number)
7 COSATI CODES FIELD GROUP SUB-GROUP	18. SUBJECT TERMS (C Combustion o	Continue on reverse Of Porous 1	e if necessary and Medium	l identify by blo	ock number)
A COMPUTER program for	18. SUBJECT TERMS (C Combustion c and identify by block n a transient	Continue on reverse of Porous 1 umber) one+dimen	e if necessary and Medium sional mat	identify by blo	l model c
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu	18. SUBJECT TERMS (C Combustion c and identify by block n a transient im was used to	Continue on reverse of Porous 1 umber) one+diment o investiga	e if necessary and Medium sional mat ate the ef	identify by blo thematica	l model c several
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behave	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results	Continue on reverse of Porous i umber) one+diment o investiga s show the	e if necessary and Medium sional mat ate the ef effects c	tidentify by blo chematica fects of of medium	l model o several
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu barameters on system behave bermeability and reaction	is. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb	Continue on reverse of Porous i umber) one+diments o investiga s show the oustion.	e if necessary and Medium sional mat ate the ef effects o In additio	thematica fects of f medium on, the e	l model o several thickness
ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction teat input on combustion w	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous 1 umber) one+dimens o investigs s show the oustion. ied. ( ncs	e if necessary and Medium sional mat ate the ef effects c In additic	thematica fects of f medium on, the e	l model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu barameters on system behave bermeability and reaction heat input on combustion w	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous 1 one+diment o investigates show the bustion. ied. ( nCS	Medium Sional matate the effects of In addition	thematica fects of of medium on, the e	l model c several thicknes ffect of
7 COSATI CODES FIELD GROUP SUB-GROUP ABSITRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behave permeability and reaction theat input on combustion w	18. SUBJECT TERMS (C Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous I umber) one≠dimens o investiga s show the oustion. ied. ( ncs	e if necessary and Medium sional mat ate the ef effects o In additio	thematica fects of of medium on, the e	l model ( several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction neat input on combustion w	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous I umber) one+diment o investiga s show the oustion. ied. ( ncs	Medium Sional matate the effects of In addition	thematica fects of of medium on, the e	l model ( several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSJRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction heat input on combustion w	18. SUBJECT TERMS (C Combustion of and identify by block n a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous 1 umber) one+diment o investiga s show the oustion. ied. ( mcs	e if necessary and Medium sional mat ate the ef effects o In additio	thematica fects of of medium	l model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction heat input on combustion w	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous I umber) one+diment o investiga s show the oustion. ied. ( mcs	Medium Sional matate the effects of In addition	tidentify by blo chematica fects of of medium on, the e	l model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behave permeability and reaction heat input on combustion w	is subject terms ( Combustion of and identify by block m a transient in was used to vior. Results order on comb vas also stud:	Continue on reverse of Porous i one+diment o investig s show the oustion.	Medium Sional matate the effects of In addition	thematica fects of of medium on, the e	1 model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behave permeability and reaction heat input on combustion w	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	21. ABSTRACT SE	e if necessary and Medium sional mat ate the ef effects of In addition (S)	thematica fects of of medium on, the e	l model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABS/FRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction heat input on combustion w 0 DISTRIBUTION/AVAILABILITY OF ABSTRACT CONDUCLASSIFIED/UNLIMITED SAME AS F 24 NAME OF RESPONSIBLE INDIVIDUAL	18. SUBJECT TERMS ( Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	21. ABSTRACT SE Unclass 22b TELEPHONE (	e if necessary and Medium sional mat ate the ef effects of In addition 'S CURITY CLASSIFIC ified include Area Code	ATION	l model c several thicknes ffect of
COSATI CODES FIELD GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary A computer program for combustion in porous mediu parameters on system behav permeability and reaction neat input on combustion w D DISTRIBUTION/AVAILABILITY OF ABSTRACT CONCLASSIFIED/UNLIMITED SAME AS F Ta NAME OF RESPONSIBLE INDIVIDUAL David Salinas	18. SUBJECT TERMS (C Combustion of and identify by block m a transient im was used to vior. Results order on comb vas also stud:	21. ABSTRACT SE Unclass 22b TELEPHONE ( (408) 64	e if necessary and Medium sional mat ate the ef effects c In additic 'S CURITY CLASSIFIC ified Include Area Code 6-3426	ATION	1 model c several thicknes ffect of ffect of

### Approved for public release; distribution is unlimited.

### Parametric Analysis of Combustion of Porous Medium

by

### Antonio Carlos de Souza Serapiao Major , Brasilian Air Force B.S., Instituto Tecnologico de Aeronautico , 1977

Submitted in partial fulfillment of the requirements for the degree of

### MASTER OF SCIENCE IN ENGINEERING SCIENCE

from the

NAVAL POSTGRADUATE SCHOOL December 1985

Author: Souza Serapiao Dar as. Approved by: hesis Advisor Dav Paul J. Marto, Chairman, Department of Mechanical Engineering  $\gamma$ iIX Dean of Science and Engineering

### ABSTRACT

A computer program for a transient one-dimensional mathematical model of combustion in porous medium was used to investigate the effects of several parameters on system behavior . Results show the effects of medium thickness , permeability and reaction order on combustion . In addition, the effect of heat input on combustion was also studied .



sion For	
CRA&i TAB nounced	
Dution /	
vailability C	odes
Avail and Special	or
	Sion For CRA&I TAB nounced ication Dution ( Vailability C Avail and Special

3

### TABLE OF CONTENTS

-

1

Ċ,

I.	INT	$\mathbf{RODUCTION}  \dots  \dots  \dots  \dots  \dots  \dots  \dots  \dots  \dots  $
II.	EFFI	ECT OF HEAT INPUT ON COMBUSTION
	A.	INTRODUCTION AND DESCRIPTION
	в.	PROCEDURE
	C.	<b>RESULTS</b>
		1. CASE II-1 SQ = 18000 BTU/ft.sq hr 22
		2. CASE II-2 SQ = 20000 BTU/ft.sq hr 23
		3. CASE II-3 SQ = 30000 BTU/ft.sq hr 28
		4. CASE II-4 SQ = 40000 BTU/ft.sq hr 34
	D.	SUMMARY
		1. Power Relation 40
		2. Relation of Temperature and Oxygen Concentration
		3. Equilibrium Temperature for Combustion 46
III.	EFFI	ECT OF THICKNESS ON COMBUSTION
	A.	INTRODUCTION
	в.	PROCEDURE
	c.	RESULTS 50
		1. CASE III-1Thickness = 0.25 inches 51
		1. CASE III-1Thickness = 0.25 inches512. CASE III-2Thickness = 0.50 inches51
-		<pre>1. CASE III-1 Thickness = 0.25 inches 51 2. CASE III-2 Thickness = 0.50 inches 51 3. CASE III-3 Thickness = 0.75 inches 59</pre>
-		1. CASE III-1Thickness = 0.25 inches2. CASE III-2Thickness = 0.50 inches3. CASE III-3Thickness = 0.75 inches4. CASE III-4Thickness = 1.00 inches
		<pre>1. CASE III-1 Thickness = 0.25 inches 51 2. CASE III-2 Thickness = 0.50 inches 51 3. CASE III-3 Thickness = 0.75 inches 59 4. CASE III-4 Thickness = 1.00 inches 61 5. CASE III-5 Thickness = 2.00 inches 64</pre>
		<pre>1. CASE III-1 Thickness = 0.25 inches 51 2. CASE III-2 Thickness = 0.50 inches 51 3. CASE III-3 Thickness = 0.75 inches 59 4. CASE III-4 Thickness = 1.00 inches 61 5. CASE III-5 Thickness = 2.00 inches 64 6. CASE III-6 Thickness = 4.00 inches 70</pre>
		<pre>1. CASE III-1 Thickness = 0.25 inches 51 2. CASE III-2 Thickness = 0.50 inches 51 3. CASE III-3 Thickness = 0.75 inches 59 4. CASE III-4 Thickness = 1.00 inches 61 5. CASE III-5 Thickness = 2.00 inches 64 6. CASE III-6 Thickness = 4.00 inches 70 7. CASE III-7 Thickness = 6.00 inches 73</pre>
•	D.	1. CASE III-1Thickness = 0.25 inches2. CASE III-2Thickness = 0.50 inches3. CASE III-3Thickness = 0.75 inches4. CASE III-4Thickness = 1.00 inches5. CASE III-5Thickness = 2.00 inches6. CASE III-6Thickness = 4.00 inches7. CASE III-7Thickness = 6.00 inches81
-	D.	1. CASE III-1       Thickness = 0.25 inches       .

IV.	PER	MEABILITY
	Α.	INTRODUCTION
	в.	PROCEDURE
	c.	<b>RESULTS</b>
		1. $CASE IV-1 Permeability = 0.00015 ft2$
		(d=D=0.0025  in)
		2. CASE IV-2 Permeability = 0.00058 ft <sup>2</sup> (d=D=0.0050 in)
		3. $CASE IV_3$ Permeability = 0.00233 ft <sup>2</sup>
		(d=D=0.0100 in)
		4. CASE IV-4 Permeability = 0.00933 ft <sup>2</sup> (d=D=0.0200 in)
	D.	SUMMARY
		1. Power Relation
		2. Combustion Speed
		-
ν.	REA	$CTION ORDER \dots \dots$
	A.	$INTRODUCTION \dots \dots$
	В.	<b>PROCEDURE</b>
	C.	<b>RESULTS</b>
		1. CASE V-1 Reaction Order = 0.25 112
		2. CASE V-2 Reaction Order = 0.50 114
		3. CASE V-3 Reaction Order = 0.75 117
		4. CASE V-4 Reaction Order = 1.00 121
	D.	SUMMARY
		1. Power Relation
VI.	CON	CLUSIONS
LIST O	FRE	FERENCES
INITIA	L DI	STRIBUTION LIST

.

5

+2+2+2+2+2

 $\mathcal{L}$ 

### LIST OF TABLES

I	VARIED PARAMETERS DURING THE PROCESS FOR SQ = 18000 BTU/FT.SQ HR
II	VARIABLE PARAMETERS DURING THE PROCESS FOR SQ = 20000 BTU/FT.SQ HR
III	VARIED PARAMETERS DURING THE PROCESS FOR SQ = 30000 BTU/FT.SQ HR
IV	VARIED PARAMETERS DURING THE PROCESS FOR SQ = 40000 BTU/FT.SQ HR
V	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 0.25 INCHES
VI	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 0.50 INCHES
VII	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 0.75 INCHES
VIII	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 1.00 INCHES
IX	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 2.00 INCHES
X	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 4.00 INCHES
XI	VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 6.00 INCHES
XII	RESULTS FOR ALL THICKNESS CASES
XIII	RESULTS FOR PERMEABILITY
XIV	POWER RELATION RESULTS
XV	COMBUSTION AND EXTINCTION TEMPERATURE FOR REACTION ORDER CASES

6

ъ.Х

## LIST OF FIGURES

2.1	Temperature vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 46 seconds
2.2	Temperature vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds
2.3	Oxygen concentration vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 46 seconds 24
2.4	Oxygen concentration vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds 24
2.5	Reaction rate vs X/L and time for SQ =18000 BTU/ft.sq hr and TQ = 46 seconds
2.6	Reaction rate vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds
2.7	Combustion and extinction carbon temperature for position X/L = 0
2.8	Temperature vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 35 seconds
2.9	Temperature vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 34 seconds
2.10	Oxygen concentration vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 35 seconds 31
2.11	Oxygen concentration vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 34 seconds 31
2.12	Reaction rate vs X/L and time for SQ = $20000$ BTU/ft.sq hr and TQ = 35 seconds
2.13	Reaction rate vs X/L and time for SQ =20000 BTU/ft.sq hr and TQ = 34 seconds $\dots \dots \dots$
2.14	Extinction and combustion carbon temperature for position X/L = 0
2.15	Temperature vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 15 seconds
2.16	Temperature vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 14 seconds
2.17	Oxygen concentration vs X/L and time for SQ = $30000 \text{ BTU/ft.sq}$ hr and TQ = 15 seconds 37
2.18	Oxygen concentration vs X/L and time for SQ = 30000 BTU/ft.sq hr,and TQ = 14 seconds 37
2.19	Reaction rate vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 15 seconds

2.20	Reaction rate vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 14 seconds
2.21	Extinction and combustion carbon temperature for position X/L = 0
2.22	Temperature vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds
2.23	Temperature vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds
2.24	Oxygen concentration vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds
2.25	Oxygen concentration vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds
2.26	Reaction rate vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds
2.27	Reaction rate vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds
2.28	Extinction and combustion carbon temperature for position $X/L = 1$
2.29	Heat flux versus combustion temperature (TQ <sub>c</sub> ) rectangular plot
2.30	Heat flux (SQ) vs combustion temperature(TQ <sub>c</sub> ) Log log plot
3.1	Temperature vs X/L and time for thickness = . 0.25 in Initial carbon temperature = 1100 F 52
3.2	Temperature vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F 52
3.3	Oxygen concentration vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1100 F
3.4	Oxygen concentration vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F
3.5	Reaction rate vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1100 F 54
3.6	Reaction rate vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F 54
3.7	Temperature vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F 56
3.8	Temperature vs X/L and time for thickness = 0.50 in Initial carbon temperature = 950 F 56
3.9	Oxygen concentration vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F
3.10	Oxygen concentration vs X/L and time for thickness = 0.50 in Initial carbon temperature = 950 F

Ŷ

X.

いいいい

Real Providence

3.11	Reaction rate vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F 58
3.12	Reaction rate vs X/L and time for thickness = 0.50 in Initial carbon temperature = 950 F 58
3.13	Temperature vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F 60
3.14	Temperature vs X/L and time for thickness = 0.75 in Initial carbon temperature = 890 F 61
3.15	Oxygen concentration vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F
3.16	Oxygen concentration vs X/L and time for thickness = 0.75 in Initial carbon temperature = 890 F
3.17	Reaction rate vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F 62
3.18	Reaction rate vs X/L and time for thickness = 0.75 in Initial carbon temperature = 890 F 63
3.19	Temperature vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F 65
3.20	Temperature vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F 65
3.21	Oxygen concentration vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F
3.22	Oxygen concentration vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F
3.23	Reaction rate vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F 67
3.24	Reaction rate vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F 67
3.25	Temperature vs X/L and time for thickness = 2.00 in Initial carbon temperature = 760 F 69
3.26	Temperature vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F 70
3.27	Oxygen concentration vs X/L and time for thickness = 2.00 in Initial carbon temperature = 760 F
3.28	Oxygen concentration vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F
3.29	Reaction rate vs X/L and time for thickness = 2.00 in Initial carbon temperature = 760 F 71
3.30	Reaction rate vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F 72

9

adere i se la s

3.31	Temperature vs X/L and time for thickness = 4.00 in Initial carbon temperature = 690 F	•		74
3.32	Temperature vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F	•	•	74
3.33	Oxygen concentration vs X/L and time for thickness = 4.00 in Initial carbon temperature = 690 F	•	•	75
3.34	Oxygen concentration vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F	•	•	75
3.35	Reaction rate vs X/L and time for thickness = 4.00 in Initial carbon temperature = 690 F	•	•	76
3.36	Reaction rate vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F		•	76
3.37	Temperature vs X/L and time for thickness = 6.00 in Initial carbon temperature = 650 F	•	•	78
3.38	Temperature vs X/L and time for thickness = 6.00 in Initial carbon temperature = 640 F	•	•	79
3.39	Oxygen concentration vs X/L and time for thickness = 6.00 in Initial carbon temperature = 650 F	•	•	79
3.40	Oxygen concentration vs X/L and time for thickness = 6.00 in Initial carbon temperature = 640 F	•	•	80
3.41	Reaction rate vs X/L and time for thickness = 6.00 in Initial carbon temperature = 650 F	•	•	80
3.42	Reaction rate vs X/L and time for thickness = 6.00 in Initial carbon temperature = 640 F	•		81
3.43	Thickness versus combustion temperature Retangular plot	•	•	84
3.44	Thickness versus combustion temperature Log-log plot	•		85
3.45	Thickness vs time for oxygen concentration at X/L = 1. to reach zero Retangular plot	•	•	86
3.46	Thickness vs time for oxygen concentration reach zero log-log plot	•	•	87
4.1	Geometry of a typical cell	•		90
4.2	Temperature vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 760 F	•		93
4.3	Temperature vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 750 F	•	•	93
4.4	Oxygen concentration vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 760 F	•		94
4.5	Oxygen comcentration vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 750 F	•	•	94

4.6	Reaction rate vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 760 F	95
4.7	Reaction rate vs X/L and time for permeability = 0.00015 ft <sup>2</sup> initial carbon temperatiure = 750 F	95
4.8	Temperature vs X/L and time for permeability = 0.00058 ft <sup>2</sup> initial carbon temperatiure = 850 F	96
4.9	Temperature vs X/L and time for permeability = 0.00058 ft initial carbon temperatiure = 840 F	97
4.10	Oxygen concentration vs X/L and time for permeability = 0.00058 ft <sup>2</sup> initial carbon temperatiure = 850 F	97
4.11	Oxygen comcentration vs X/L and time for permeability = 0.00058 ft <sup>2</sup> initial carbon temperatiure = 840 F	98
4.12	Reaction rate vs X/L and time for permeability = 0.00058 ft <sup>2</sup> initial carbon temperatiure = 850 F	98
4.13	Reaction rate vs X/L and time for permeability = 0.00058 ft <sup>2</sup> initial carbon temperatiure = 840 F	99
4.14	Cemperature vs X/L and time for permeability = 0.00233 ft initial carbon temperatiure = 980 F . 10	00
4.15	Temperature vs X/L and time for permeability = $0.00233$ ft <sup>2</sup> initial carbon temperatiure = 970 F . 1	00
4.16	Oxygen concentration vs X/L and time for permeability = 0.00233 ft <sup>2</sup> initial carbon temperatiure = 980 F	01
4.17	Oxygen comcentration vs X/L and time for permeability = 0.00233 ft <sup>2</sup> initial carbon temperatiure = 970 F	01
4.18	Reaction rate vs X/L and time for permeability = 0.00233 ft <sup>2</sup> initial carbon temperatiure = 980 F	02
4.19	Reaction rate vs X/L and time for permeability = 0.00233 ft <sup>2</sup> initial carbon temperatiure = 970 F	02
4.20	Permeability versus combustion temperature retangular plot	06
4.21	Permeability versus combustion temperature log log plot	07
4.22	Permeability versus t* Retangular plot 1	10
4.23	Permeability versus t* Log-log plot 1	11
5.1	Temperature vs X/L and time for reaction order = 0.25 Initial carbon cemperature = 980 F 1	14
5.2	Temperature vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F 1	15

5.3	Oxygen concentration vs X/L and time for reaction order = 0.25 Initial carbon temperature = 980 F	115
5.4	Oxygen concentration vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F	116
5.5	Reaction rate vs X/L and time for reaction order = 0.25 Initial carbon temperature = 980 F .	116
5.6	Reaction rate vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F .	117
5.7	Temperature vs X/L and time for reaction order = 0.50 Initial carbon temperature = 850 F	118
5.8	Temperature vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F	118
5.9	Oxygen concentration vs X/L and time for reaction order = 0.50 Initial carbon temperature = 850 F	119
5.10	Oxygen concentration vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F	119
5.11	Reaction rate vs X/L and time for reaction order = 0.50 Initial carbon temperature = 850 F .	120
5.12	Reaction rate vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F .	120
5.13	Temperature vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F	121
5.14	Temperature vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F	122
5.15	Oxygen concentration vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F	122
5.16	Oxygen concentration vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F	123
5.17	Reaction rate vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F .	123
5.18	Reaction rate vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F.	124
5.19	Temperature vs X/L and time for reaction order = 1.00 Initial carbon temperature = 670 F	125
5.20	Temperature vs X/L and time for reaction order = 1.00 Initial carbon temperature = 660 F	126
5.21	Oxygen concentration vs X/L and time for reaction order = 1.00 Initial carbon temperature = 670 F	126
5.22	Oxygen concentration vs X/L and time for reaction order = 1.00 Initial carbon temperature = 660 F	127

Ĭ

5.23	Reaction rate vs X/L and time for reaction rate= 1.00 Initial carbon temperature = 670 F	127
5.24	Reaction rate vs X/L and time for reaction order = 1.00 Initial carbon temperature = 660 F .	128
5.25	Reaction order versus temperature Retangular plot	130
5.26	Reaction order versus temperature Log-log plot .	131
5.27	Reaction order versus temperature Semi log plot .	132

1-1-2-2-

### ACKNOWLEDGEMENTS

I wish to express my sincere appreciation to Dr. David Salinas for his guidance, assistance and encouragement during the pursuit of this study. To my wife and our sons, for the encouragement, patience and understanding, I am deeply grateful.

### I. INTRODUCTION

The goal of this thesis is to study the combustion behavior of porous graphite. The mathematical model developed by VATIKIOTIS (1) is a transient, one-dimensional model of a porous medium consisting of spherical particles, or cylindrical fibers of graphite.

The model covers several aspects : mass transfer, heat transfer, combustion , airflow , and temperature dependency of thermophysical properties. Geometric parameters of the porous medium include porosity (p) and medium thickness (L). The porous medium has interconnected pores which permit air flow through the medium. This air flow was modeled by the continuity equation and Darcy's Law . The porous medium is characterized by a number of parameters including porosity , specific internal area (Z), tortuosity ( $\tau$ ) and permeability (m). These parameters are defined as follows. Given a unit square cell of dimension D, and particle diameter d, we have

$$p = 1 - \pi / 4 (d/D)^2$$
(1.1)

 $z = 1/2 \pi d^2/D^3$  (1.2)

 $\tau = 1.4 \tag{1.3}$ 

 $m = Sp^3/z^2$  (1.4)

Porosity, p, is defined as the ratio of void volume per volume of unit all . The specific internal area, Z, is the

ratio of internal surface area to bulk volume . The tortuosity is defined as the ratio of the length of the flowpath of a fluid particle to the straight line distance.

The particle's size decreases as the carbon is consumed and all geometric properties which depend on particle diameter are functions of time and position . This model considers that the carbon matrix remains rigid as the particle diameter decreases and thus porosity increases with combustion.

The magnitude of REYNOLDS number defines the motion of the fluid which can be molecular , viscous or inertial. In the case of porous media , the flow is dominated by viscous and inertial effects. Darcy's Law for the range of REYNOLD's number where viscous effects dominate is the equation that governs the fluid flow in porous media. Two velocities which distinguish the flow through the medium are filter velocity Q, and pore velocity u. Filter velocity is given by :

$$Q = -m/\mu \left(\frac{\partial P}{\partial x}\right)$$
(1.5)

where u is the viscosity of the fluid and P is the pressure. The pore velocity u is given by :

 $U = Q/p \tag{1.6}$ 

The hypothesis of the Dupuit-Forcheimer assumption is that the local pore velocity is greater than the filter velocity. The actual velocity in a pore is a function of position within the pore. The Dupuit-Forcheimer relation defines an average velocity in a pore.

The model of combustion adopted was the model of N. N. Semenov (2). The relation of reaction rate to temperature and oxygen concentration, and the interaction of heat generation and heat transfer are fundamental to this model. If the heat transfer dominates, extinction will occur. If the heat generation dominates then combustion will result. The reaction rate equation was adopted from Arrhenius's Law for a simple reaction where the rate depends on the concentration of the reactants and not on the products. The heat generated by an exothermal reaction is obtained by multiplying the reaction rate by the heat of combustion .

A study of the curve of heat generation versus temperature presented by Frank-Kamenetskii distinguishes two phases during combustion. During the initial kinetic phase , the rate of reaction and the temperature are lowest. During This phase , there is an excess supply of oxygen. In the kinetic regime the reation rate increases exponentially with increasing temperature. The kinetic regime is followed by the diffusion regime. This phase is distinguished by high temperatures and reaction rates , and the reaction is limited by a lack of oxygen.

It is assumed that the chemical reaction for the combustion process produces carbon monoxide and carbon dioxide. The ratio of the mass rates of carbon monoxide to carbon dioxide depends on the temperature. Increasing temperature results in an increase of this CO to  $CO_2$  ratio.

The model of heat transfer includes three basic mechanisms : convection , conduction and radiation . The heat transfer equation used by VATIKIOTIS (1) also includes a heat generation term due to combustion. All thermophysical properties were treated as temperatures dependent. These properties include viscosity, conductivity and density. Energy balance equations were constructed for control volumes of the porous medium and the air flowing through the porous medium .

A third field equation of the model was obtained by a mass balance of oxygen . This equation includes molecular diffusion, convective transport and a sink term to account for the depletion of oxygen due to combustion.

These equations resulted in a system of coupled, nonlinear transient field equation . These field equations, together with boundary and initial conditions , define the problem. They were solved numerically by using the Galerkin finite element method. Details of the formulation are presented in reference 1 .

### **II. EFFECT OF HEAT INPUT ON COMBUSTION**

### A. INTRODUCTION AND DESCRIPTION

In this section the effect of heat input on the combustion behavior of porous medium was investigated. The porous medium is subjected to a heat source on its surface. Two parameters of main importance are considered: The magnitude of the heat flux of the source to the porous medium (SQ), and the time that the heat flux remains active (TQ).

To do this analysis, all parameters of the system are fixed except the time period of heating (TQ) and the amount of heat flux (SQ).

The purpose of this section is to determine the relation between SQ and TQ which will result in combustion. This is achieved as follows:

For a specific value of heat flux SQ, the program is run with different values of TQ until combustion occurs at  $(TQ)_c$  and extinction occurs at  $(TQ)_e$ , where  $\delta$  is a small time period. Here we took  $\delta$  seconds.

$$TQ_{c} = TQ_{e} + \delta$$
 (2.1)

Four cases of heat flux were studied in this section:

CASE II.1 SQ = 18000 BTU/ft.sq hr CASE II.2 SQ = 20000 BTU/ft.sq hr CASE II.3 SQ = 30000 BTU/ft.sq hr CASE II.4 SQ = 40000 BTU/ft.sq hr

The fixed parameters used in all cases are:

```
Ambient temperature = 80 F
Ambient temperature = 2117 lb/ft.sq
Tortuosty = 1.400
Filament diameter = 0.0004167 ft
```

Thickness of matrix laminate = 0.0004167 ft Thickness of porous medium = 0.02083 ft Gas constant for air = 53.34 lbf ft/lbm R Conductivity of filament = 86 BTU/1bm H.F. Specific heat of filament = 0.703 lbm/Cf Emissivity of filament = 0.90 Shape factor for int.HF.XFER coefficient = 1.00 Characteristc length of medium = 1 inch Heat of reaction = 14090 BTU/CfReaction order = 0.50Stochiometric ratio (fuel/air) = 0.375 Reaction coefficient = 2065000 1bm/Cf H Activation energy coefficient = 28840 deg R Pressure differential across thickness = 50 lb/ft.sq Initial carbon and air temperature = 80 F Initial uniform oxygen concentration = 0.0172 lbm/ft.cu

The equations used in this program permit three sets of boundary conditions that are approximations to physical situations. The boundary conditions selected are the best approximations of a one dimensional model. The set of boundary conditions used in this case are typical of thermal flow reactor without radiation from the boundary surfaces . for the problems of this investigation, the following boundary conditions were used :

- No heat transfer from either end of the porous medium.

dt/dx = 0 at X/L = 0 and X/L = 1 (2.2)

- Danckwerts' boundary conditions : Conditions for the air temperature and oxygen concentration were assumed. This means :

$$K_{a} \partial T_{a} / \partial x = \rho_{a} c_{a} u (T_{a} - T_{\infty}) \qquad X/L = 0 \qquad (2.3)$$

$$\partial T_a / \partial x = 0$$
  $X/L = 1$  (2.4)

$$D_{e} \partial \phi / \partial x = u (\phi - \phi_{\infty}) \qquad X/L = 0 \qquad (2.5)$$

$$(K_e + K_r) \partial T_c / \partial x = -\sigma \varepsilon (T_c^4 - T_{\infty}^4) \qquad X/L = 1 \qquad (2.6)$$

$$K_a \partial T_a / \partial x = \rho \cdot a c_a u (T_a - T_\infty) \qquad X/L = 1 \qquad (2.7)$$

$$\partial T_a / \partial x = 0$$
  $X/L = 1$  (2.8)

$$D_{e} \partial \phi / \partial x = u(\phi - \phi_{\infty}) \qquad X/L = 1 \qquad (2.9)$$

### **B. PROCEDURE**

For each case , the amount of heat flux (SQ) was fixed and several values of shut off time (TQ) were chosen until values of  $TQ_c$  and  $TQ_e$  were found such that :

$$TQ_c \approx TQ_e$$
 (2.10)

 $TQ_{c} = TQ_{e} + \delta$  (2.11)

where  $\delta$  is a small number.

C. RESULTS

The results for each case were obtained in both numerical and graphical form . The behavior of carbon temperature, oxygen concentration and reaction rate for combustion and extinction are shown as surfaces versus time and position The program also calculates the air temperature in the porous medium. However the air temperature surfaces are not shown as they are quite similar , in most cases to carbon temperature.

There are three surface graphics for each heat flux case:

-Carbon temperature versus position and time

-Oxygen concentration versus position and time

-Reaction rate versus position and time

In adition , there are two curves for each heat flux (SQ) , one showing the variation of carbon temperature versus time for combustion and the other showing the variation of carbon temperature for extinction . These is two curves are for the point x/L=0. (i.e. where the air enters the porous medium) .

1. CASE II-1 SQ = 18000 BTU/ft.sq hr

The values for shut off time bounding extinction and combustion are :

for combustion  $TQ_c = 46$  seconds for extinction  $TQ_e = 47$  seconds

During the transient analyses , system parameters varied . for each analysis , the maximum and minimum values of some of these parameters provide some insight into the character of the particular case . These parameters and their values are given in Table I

The graphical results are shown in Figures 2.1 to 2.6

TEMPERATURE SURFACE FROM GRAFIE



Figure 2.1 Temperature vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 46 seconds.

TEMPERATURE SURFACE FROM GRAFIE



Figure 2.2 Temperature vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 2.3 Oxygen concentration vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 46 seconds.

OXYGEN CONC. SURFACE FROM GRAFSE



Figure 2.4 Oxygen concentration vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds.

PERCTION RATE SURFACE FROM GRAFIE



Figure 2.5 Reaction rate vs X/L and time for SQ =18000 BTU/ft.sq hr and TQ = 46 seconds.

PERCTION RATE SUPFACE FROM GRAFSE



Figure 2.6 Reaction rate vs X/L and time for SQ = 18000 BTU/ft.sq hr and TQ = 45 seconds.



# Figure 2.7

Combustion and extinction carbon temperature for position X/L = 0..

VARIED PARAMETERS DURING THE PROCESS FOR SQ = 18000 BTU/FT.SQ HR TABLE I

parameters	extin	ct i on	combu	stion
	maximum	minimum	maximum	minimum
<pre>permeability (ft.sq)(l0-<sup>1 •</sup>)</pre>	2.022	1.617	298.8	1.617
pressure (lb/ft.sq)	2117	2066	2117	2066
pressure gradient (lb/ft.cu)	-1724	- 3809	-716.6	-3384
pore velocity (ft/hr)	6707	4056	8676	2287
Reynolds number	1.477	0.0975	1.477	0.09243
convection coefficient	45.42	40.03	55.67	19.51

### 2. CASE II-2 SQ = 20000 BTU/ft.sq hr

For this case the heat flux duration times for the conditions of extinction and combustion are :

for combustion  $TQ_c = 35$  seconds for extinction  $TQ_e = 34$  seconds

During the transient history of this case several parameters varied. The maximum and minimum of these changing variables are in the Table II . It is necessary to emphasize that these extrema results do not occur at the same time or same position (X/L). They are maximum and minimum values obtained at different times and position during the transient process. These values show the characteristc behavior of this case .

The behavior of carbon temperature , oxygen concentration and reaction rate are shown in Figures 2.8 to 2.13 . These surfaces are an important characteristic of this case because they show the evolution of the combustion process or extinction process for each position during the transient time .

3. CASE II-3 SQ = 30000 BTU/ft.sq hr

The values of heating time that result in combustion and extinction for this value of heat flux are :

> for combustion  $TQ_c = 15$  seconds for extinction  $TQ_e = 14$  seconds

During the transient analysis , some variation of values occured to several parameters. The limits of variation , maximum and minimum values , are shown in Table III . The process of combustion and extinction have particular characteristics that determine the variation of the values

-
H
Щ
B
×.
<u> </u>

0.00000

# VARIABLE PARAMETERS DURING THE PROCESS FOR SQ = 20000 BTU/FT.SQ HR

parameters	extinc	tion	combus	tion
	maximum	minimum	maximum	minimum
<pre>permeability (ft.sq)(l0-'')</pre>	1.913	1.617	3.899	1.617
pressure (lb/ft.sq)	2117	2066	2117	2066
pressure gradient (lb/ft.cu)	-825.5	-3553	-17.65	-3706
pore velocity (ft/hr)	7472	2603	7488	2322
Reynolds number	1.471	0.155	1.477	0.041
convection coefficient	55.67	32.14	57.12	18.63

~~~~~~~~~

TEMPERATURE SURFACE FROM GRAFTE



Figure 2.8 Temperature vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 35 seconds.

TEMPERATURE SURFACE FROM GRAFSE



Figure 2.9 Temperature vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 34 seconds.

OXYGEN CONC. SURFACE FROM GRAFIE



Figure 2.10 Oxygen concentration vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 35 seconds.

DXYGEN CONC. SURFACE FROM GRAFIE



Figure 2.11 Oxygen concentration vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 34 seconds.

REACTION RATE SURFACE FROM GRAFSE



Figure 2.12 Reaction rate vs X/L and time for SQ = 20000 BTU/ft.sq hr and TQ = 35 seconds.

REACTION RATE SURFACE FROM GRAF3E



Figure 2.13 Reaction rate vs X/L and time for SQ =20000 BTU/ft.sq hr and TQ = 34 seconds.



# FOR NUMBER POINT I AND SQ=20000

# Figure 2.14 Extinction and combustion carbon temperature for position X/L = 0..
of these parameters. The maximum and minimum values give a general idea of system behavior . These limiting values do not occur at same position (X/L) or same time .

A better idea of the development of temperature , oxygen concentration and reaction rate can be obtained from Figures 2.15 to 2.20 These surfaces show the values of these parameters for each point (X/L) during the transient time .

Figure 2.14 shows that at X/L = 0. the transient behavior for extinction and combustion are the same until  $TQ_e = 14$  seconds, the time the heat flux is terminated. After this time the temperature for the extinction case decreases to ambient temperature; while for the combustion case, the temperature increases reaching a peak temperature of 3200 F at 28 seconds and thereafter decreases to an equilibrium combustion temperature of about 2500 F after about 50 seconds (see Figure 2.14).

## 4. CASE II-4 SQ = 40000 BTU/ft.sq hr

The heat flux of this case produced combustion and extinction of the porous medium at the following times :

for combustion  $TQ_c = 9$  seconds for extinction  $TQ_e = 8$  seconds

During the transient process , the output of the program showed parameters th at didn't change with time and others that did . The variation of these parameter's values show the development of the combustion and extinction phenomenon for this value of SQ . The maximum and minimum values of several parameters are shown in Table IV . Again these values do not correspond to the same time .

The characteristics of this case , carbon temperature , oxygen concentration and reaction rate , as function TABLE ILI

X.

O Kasaka

VARIED PARAMETERS DURING THE PROCESS FOR SQ = 30000 BTU/FT.SQ HR

| parameters                               | extin             | ction   | combus    | tion    |
|------------------------------------------|-------------------|---------|-----------|---------|
|                                          | <b>พบพ i พ</b> ณฑ | minimum | max i mum | minimum |
| permeability (ft.sq)(10- <sup>10</sup> ) | 2.022             | 1.617   | 2.948     | 1.617   |
| pressure (lb/ft.sq)                      | 2117              | 2066    | 2117      | 2066    |
| <pre>oressure gradient(lb/ft.cu)</pre>   | - 841             | - 4850  | -25.39    | -4859   |
| pere velocity (ft/hr)                    | 9248              | 2475    | 9248      | 1852    |
| keynolds number                          | 1.581             | 0.1932  | 1.477     | 0.037   |
| convection coefficient                   | 58.20             | 31.40   | 57.65     | 20.88   |

TEMPERATURE SURFACE FROM GRAF3E



Figure 2.15 Temperature vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 15 seconds.

TEMPERATURE SURFACE FROM GRAF3E



Figure 2.16 Temperature vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 14 seconds.

## OXYGEN CONC. SURFACE FROM GRAF3E



Figure 2.17 Oxigen concentration vs X/L and time for SQ =30000 BTU/ft.sq hr and TQ = 15 seconds.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 2.18 Oxigen concentration vs X/L and time for SQ = 30000 BTU/ft.sq hr, and TQ = 14 seconds.

REACTION RATE SURFACE FROM GRAF3E



Figure 2.19 Reaction rate vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 15 seconds.

REACTION RATE SURFACE FROM GRAFTE



Figure 2.20 Reaction rate vs X/L and time for SQ = 30000 BTU/ft.sq hr and TQ = 14 seconds.





b



of time and position (X/L) are shown as graphic surfaces in Figures 2.22 to 2.27. These graphical results give an idea about the behavior of each point of the transient history.

For X/L = 0, both the combustion and extinction cases show similar behavior to this time equal to about 8 seconds, when the heat flux is terminated. After this time, for the extinction case, the temperature decreases to ambient temperature. For the combustion case, the temperature at X/L = 0 increased to about 3300 F, and thereafter decreased to around 2500 F (temperature of combustion). Both the extinction and combustion cases achieve new equilibrium temperatures, about 2500 F for the combustion cases and ambient temperature for the extinction cases, after 35 seconds (see Figures 2.28).

D. SUMMARY

Here, some observations are made about the effects of heat flux input and duration of heat flux on the combustion process.

1. Power Relation

For each case , a pair of values  $(SQ, (TQ)_c)$  was obtained . A plot of these point is shown in Figures 2.29 and 2.30 . It is observed that the relation between SQ and TQ of these graphics yields the approximate power relation (equation 2.12) .

## 2. Relation of Temperature and Oxygen Concentration

During the initial heating of the porous medium , the temperature increases while the oxygen is being defleted. After the heat flux is removed , either extinction or combustion will proceed. If extinction occurs , the carbon temperature decreases to ambient temperature while the oxygen is being restored to ambient concentreition .

If combustion occurs ,then the oxygen inside the medium goes to zero and remains there . The only oxygen

## TABLE IV

# VARIED PARAMETERS DURING THE PROCESS FOR SQ = 40000 BTU/FT.SQ HR

| parameters                                        | ext in  | ction   | combu   | stion   |
|---------------------------------------------------|---------|---------|---------|---------|
|                                                   | maximum | minimum | maxinum | minimum |
| <pre>permeability (ft.sq)(10-<sup>10</sup>)</pre> | 2.186   | 1.617   | 307.3   | 1.677   |
| pressure (lb/ft.sq)                               | 2117    | 2066    | 2117    | 2066    |
| pressure gradient (lb/ft.cu)                      | -823.9  | -5705   | -25.79  | - 5705  |
| pore velocity (ft/hr)                             | 8945    | 2061    | 9597    | 1480    |
| Reynolds number                                   | 1.581   | 0.1929  | 1.477   | 0.0365  |
| convection coeffitient                            | 58.00   | 29.33   | 58.00   | 23.19   |

TEMPERATURE SURFACE FROM GRAF3E



Figure 2.22 Temperature vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds.

TEMPERATURE SURFACE FROM GRAFIE



Figure 2.23 Temperature vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds.

A DALALADAL

## DXYGEN CONC. SURFACE FROM GRAFIE



Figure 2.24 Oxygen concentration vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 2.25 Oxigen concentration vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds.

REACTION RATE SURFACE FROM GRAF3E



Figure 2.26 Reaction rate vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 9 seconds.

REACTION RATE SURFACE FROM GRAF3E



Figure 2.27 Reaction rate vs X/L and time for SQ = 40000 BTU/ft.sq hr and TQ = 8 seconds.



FOR NUMBER POINT 1 AND SQ=40000

## Figure 2.28

Second Second



$$TQ_{c} = 3.4 \ 10^{10} / (SQ)^{2} . ^{09}$$
 (2.12)

present is at the entrance at X/L = 0. The temperature continues to increase to a maximum , and thereafter the temperature decreases . Eventually the entire medium would achieve a uniform combustion temperature .

## 3. Equilibrium Temperature for Combustion

In all combustion cases , the behavior was similar . During the initial combustion period , the temperature of the medium at X/L = 0 rose between 2000 F (CASE II-1) to 3400F (CASE II-4) . At this time , on the other side of the medium at X/L = 1. , the temperature of the medium was approximately 1500 F . This during thus early transient stage there is  $a\Delta T$  of 1300 F (for CASE II-1) and 1900 F (for CASE II-4) across the medium . As time proceeds the temperature at X/L = 0 decreased , while at X/L = 1. , the temperature increased . That is , with progressing time , the medium moves towards a uniform temperature . In the present case , this equilibrium temperature of combustion is around 2400 F to 2500 F for all cases .

The mechanism of equilibrium of the temperature during combustion is due to the heat transfer by air . As the air flows through the porous medium it transports the heat from the hot front part of the medium to the cooler back part , until all points of the medium have the same temperature .

SQ VERSUS TQ



Figure 2.29 Heat flux versus combustion temperature  $(TQ_c)$  rectangular plot.



## SQ VERSUS TQ

## III. EFFECT OF THICKNESS ON COMBUSTION

## A. INTRODUCTION

The porous medium has several geometric parameters that can have direct influence on the combustion process. The effect of the thickness parameter on system behavior is analysed in this section. All other parameters are fixed except the thickness of the medium.

The purpose of this section is to determine the relation of the thickness on the minimum temperature to start combustion (i.e., the ignition temperature).

For a specified value of thickness, the program is run with different values of initial temperature. This initial temperature is equal at all points of the medium. The lowest value of initial temperature that results in combustion is the ignition temperature Tc. Extinction occurs at Tc- $\delta$ , where  $\delta$  is a small increment of temperature. The value of  $\delta$ used in this parametric analysis was 10 F.

Seven cases with different thicknesses were studied in this section:

CASE III-1 THICKNESS = 0,25 inches CASE III-2 THICKNESS = 0,50 inches CASE III-3 THICKNESS = 0,75 inches CASE III-4 THICKNESS = 1.00 inches CASE III-5 THICKNESS = 2.00 inches CASE III-6 THICKNESS = 4.00 inches CASE III-7 THICKNESS = 6.00 inches

Each case is characterised by its thickness. The fixed parameters used in all cases are:

- Ambient temperature = 80 F
- Ambient pressure = 2117 lb/ft. sq.
- Tortuosity = 1.400
- Filament diameter = 0.0004167 ft.

- Thickness of matrix laminate = 0.0004167 ft.
- Thickness of porous medium = 0.02083 ft.
- Gas constant for air = 53.34 lbf.ft/lbm.R
- Conductivity of filament = 86 BTU/lbf HF
- Specific heat of filament = 0.703 lbm/cf.
- Emissivity of filament = 0.90
- Shape factor for int.HF.XFER coefficient = 1.00
- Heat of reaction = 14090 BTU/CF
- Reaction order = 0.50
- Stoichiometric ratio (full/air) = 0.375
- Reaction rate coefficient = 2065000 lbm/CF hr
- Activation energy coefficient = 28.840 deg R
- Pressure differential across thickness =  $50 \text{ lb/ft}^3$
- Initial uniform oxygen concentration =  $0.0172 \text{ lbm/ft}^3$

## **B. PROCEDURE**

For each case, the characteristic length of the medium (thickness) was fixed and values of the uniform initial temperature were chosen until the value of temperature for combustion  $(T_c)$  and temperature for extinction  $(T_e)$  were approximately equal  $(T_c \approx T_e)$  or  $(T_c = T_e + 10)$  (F).

C. RESULTS

For each case, the results were obtained in both numerical and graphical form. The behavior of carbon temperature, oxygen concentration and reaction rate for combustion and extinction are shown as surfaces versus time and position.

The numerical results from the program show the variation of several parameter values during the transient analysis. The air temperature inside the porous medium, the griphite temperature and the oxygen concentration are presented at each position (X/L) at intervals of time. Other system properties are also given . These properties characterize the process of combustion and extinction for different thicknesses. The maximum and minimum do not occur at the same point or at the same time.

The graphical results are given in the form of surfaces. These surfaces show the behavior of carbon temperature, oxygen concentration and reaction rate versus time and position (X/L) for the combustion and extinction processes.

1. CASE III-1 Thickness = 0.25 inches

The values of the initial uniform carbon temperature bounding the extinction and combustion processes are:

```
for combustion Tc = 1100 F
for extinction Te = 1090 F
```

The development with time of the behavior of the graphite temperature, oxygen concentration and reaction rate during the combustion and extinction processes are shown in Figures 3.1 to 3.6 The transient parametric analysis provide some insight into the characterers of this particular case. The maximum and minimum values of these parameters are given in Table V .

2. CASE III-2 Thickness = 0.50 inches

The combustion and extinction process, in this case, start with the following uniform carbon temperatures:

> for combustion Tc = 960 F for extinction Te = 950 F

For this case, the graphical results for graphite temperature, oxygen concentration and reaction rate are shown in Figures 3.7 to 3.12. The characteristics of the changing parameters in this case, are shown by the maximum and minimum values in Table VI. TEMPERATURE SURFACE FROM GRAF3E



Figure 3.1 Temperature vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1100 F.

TEMPERATURE SURFACE FROM GRAF3E



Figure 3.2 Temperature vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.3 Oxygen concentration vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1100 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.4 Oxygen concentration vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F.

## REACTION RATE SURFACE FROM GRAF3E



Figure 3.5 Reaction rate vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1100 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 3.6 Reaction rate vs X/L and time for thickness = 0.25 in Initial carbon temperature = 1090 F.

TABLE V

22

1

¥.

A Second Second

**Service** 

| INCHES     |
|------------|
| 0.25       |
| 11         |
| THICKNESS  |
| FOR        |
| PROCESS    |
| THE        |
| DURING     |
| PARAMETERS |
| VARIED     |

| parameters                               | extin   | ction   | compu   | ISTION  |
|------------------------------------------|---------|---------|---------|---------|
|                                          | maximun | minimun | maximun | minimur |
| permeability (ft.sq)(l0- <sup>10</sup> ) | 1.772   | 1.618   | 1.842   | 1.617   |
| pressure (lb/ft.sq)                      | 2117    | 2066    | 2117    | 2066    |
| pressure gradient (lb/ft.cu)             | -935    | - 3807  | - 742   | -4132   |
| pore velocity (ft/hr)                    | 8595    | 2633    | 6654    | 1622    |
| Reynolds number                          | 0.1522  | 0.1357  | 0.202   | 0.065   |
| convection coefficient                   | 56.07   | 31.05   | 42.03   | 29.71   |

## TEMPERATURE SURFACE FROM GRAF3E



Figure 3.7 Temperature vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F.

TEMPERATURE SURFACE FROM GRAFSE



Figure 3.8 Temperature vs X/L and time for thickness = 0.50 in Initial carbon temperature = 950 F.

DXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.9 Oxygen concentration vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F.

OXYGEN CONC. SURFACE FROM GRAFSE



REACTION RATE SURFACE FROM GRAFIE



Figure 3.11 Reaction rate vs X/L and time for thickness = 0.50 in Initial carbon temperature = 960 F.

REACTION RATE SURFACE FROM GRAFTE



Figure 3.12 Reaction rate vs X/L and time for thickness = 0.50 in Initial carbon temperature = 950 F.

TABLE VI

VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 0.50 INCHES

| parameters                                        | extin   | ction   | combu   | stion   |
|---------------------------------------------------|---------|---------|---------|---------|
|                                                   | maximun | minimun | maximun | minimun |
| <pre>permeability (ft.sq)(l0-<sup>10</sup>)</pre> | 1.685   | 1.617   | 1.767   | 1.617   |
| pressure (lb/ft.sq)                               | 2117    | 2066    | 2117    | 2066    |
| <pre>pressure gradient (lb/ft.cu)</pre>           | -492    | -1896   | -325    | -2039   |
| pore velocity (ft/hr)                             | 4431    | 1328    | 3372    | 933     |
| Reynolds number                                   | 0.711   | 0.085   | 0.1575  | 0.0446  |
| convection coefficient                            | 41.07   | 23.62   | 34.04   | 20.78   |

╸┟┶╻╘┑┟┶╏┶╕┟┶┧┟┶┧╞╼┟┶╶┟┶╶┟╸┟╼╶┟┑┟┑┟┑┟┑┟┑┟┑┟┑

## 3. CASE III-3 Thickness = 0.75 inches

During this case the minimum uniform temperature that starts the combustion process and the maximum uniform temperature for extinction are:

> for combustion Tc = 900 F for extinction Te = 890 F

During the transient analysis, the system parameters varied. For this case , the maximum and minimum values of some of these parameters provide some insight into the character of the case. These parameters and their extreme values are given in Table VII .

Figures 3.13 to 3.18 show the graphical results for carbon temperature, oxygen concentration and reaction rate for this case.

TEMPERATURE SURFACE FROM GRAF3E



Figure 3.13 Temperature vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F.

60

X DATA AND ALL AND A

TEMPERATURE SURFACE FROM GRAF3E



Figure 3.14 Temperature vs X/L and time for thickness = 0.75 in Initial carbon temperature = 890 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.15 Oxygen concentration vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.16 Oxygen concentration vs X/L and time for thickness = 0.75 in Initial carbon temperature = 890 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 3.17 Reaction rate vs X/L and time for thickness = 0.75 in Initial carbon temperature = 900 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 3 18 Reaction rate vs X/L and time for thickness = 0.75 in

Ir al carbon temperature = 890 F.

4. CASE III 4 Thickness = 1 00 inches

The program was run with several values of initial uniform graphite temperature. The temperatures bounding combustion and extinction are:

> for combustion Tc = 850 F for extinction Te = 840 F

The variable parameters of this case attain maximum and minimum values as given in Table VIII .

In this case, the graphical results for carbon temperature, oxygen concentration and reaction rate are shown in Figures 3.19 to 3.24.

## TABLE VII

# VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 0.75 INCHES

| parameters                              | extin   | ction   | combu   | stion   |
|-----------------------------------------|---------|---------|---------|---------|
|                                         | maximun | minimun | maximun | minimun |
| <pre>permeability (ft.sq)(l0-1°)</pre>  | 1.733   | 1.617   | 1.863   | 1.617   |
| <pre>pressure (lb/ft.sq)</pre>          | 2117    | 2066    | 2117    | 2066    |
| <pre>pressure gradient (lb/ft.cu)</pre> | -331    | -1309   | -236    | -1257   |
| pore velocity (ft/hr)                   | 2301    | 906     | 2085    | 633     |
| Reynolds number                         | 0.1684  | 0.0623  | 0.1116  | 0.0416  |
| convection coefficient                  | 28.60   | 19.36   | 26.99   | 16.27   |

آهي

## TEMPERATURE SURFACE FROM GRAFIE

10000000 U 2020

X-652-56-9

No. of the State o



Figure 3.19 Temperature vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F.

TEMPERATURE SURFACE FROM GRAFIE



Figure 3.20 Temperature vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F.

OXYGEN CONC. SURFACE FROM GRAFIE



Figure 3.21 Oxygen concentration vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F.

DAYGEN CONC. SURFACE FROM GRAFIE



Figure 3.22 Oxygen concentration vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 3.23 Reaction rate vs X/L and time for thickness = 1.00 in Initial carbon temperature = 850 F.

REACTION RATE SURFACE FROM GRAFIE



Figure 3.24 Reaction rate vs X/L and time for thickness = 1.00 in Initial carbon temperature = 840 F.

## TABLE VIII

100 A

2,5

## VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 1.00 INCHES

| parameters                                        | extin   | ction   | combu   | stion   |
|---------------------------------------------------|---------|---------|---------|---------|
|                                                   | maximun | minimun | maximun | minimun |
| <pre>permeability (ft.sq)(10-<sup>10</sup>)</pre> | 1.911   | 1.617   | 1.874   | 1.617   |
| pressure (lb/ft.sq)                               | 2117    | 2067    | 2117    | 2066    |
| <pre>pressure gradient (lb/ft.cu)</pre>           | - 360   | -1289   | -260    | -1257   |
| pore velocity (ft/hr)                             | 1835    | 715     | 1535    | 686     |
| Reynolds number                                   | 0.2313  | 0.0531  | 0.1108  | 0.0518  |
| convection coefficient                            | 28.04   | 17.27   | 24.09   | 16.99   |

<u></u>

N. 1. 1. 1.

5. CASE III-5 Thickness = 2.00 inches

The combustion and extinction process, in this case, are characterized by the following uniform initial graphite temperatures:

> for combustion Tc = 760 F for extinction Te = 750 F

The graphite temperature and other parameters varied during these processes . The variation of these parameters characterize the system. The maximum and minimum values of these parameters are in Table IX .

The graphical results for carbon temperature, oxygen concentration and reaction rate are shown in Figures 3.25 to 3.30.

TEMPERATURE SURFACE FROM GRAFIE



Figure 3.25 Temperature vs X/L and time for thickness = 2.00 in Initial carbon temperature = 760 F.
### TEMPERATURE SURFACE FROM GRAF3E



Figure 3.26 Temperature vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.27 Oxygen concentration vs X/L and time , for thickness = 2.00 in Initial carbon temperature = 760 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.28 Oxygen concentration vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F.

a sacara

REACTION RATE SURFACE FROM GRAPSE



Figure 3.29 Reaction rate vs X/L and time for thickness = 2.00 in Initial carbon temperature = 760 F.

ALLER DER DER SALTER SALTER SALTER REPORT ALLER SALTER DER SALTER DER GARE ALLER DER GARE DER DER DER DER DER D

### REACTION RATE SURFACE FROM GRAF3E



Figure 3.30 Reaction rate vs X/L and time for thickness = 2.00 in Initial carbon temperature = 750 F.

### 6. CASE III-6 Thickness = 4.00 inches

The minimum value of the initial graphite temperature to start combustion of the porous medium and the maximum value of the initial graphite temperature that results in extinction for this case are:

> for combustion Tc = 690 F for extinction Te = 680 F

Other variable parameters of this case are shown in Table X. The values of these parameters are characteristic of the combustion and extinction processes for this value of thickness.

In this case, the graphical results show the behavior of carbon temperature, oxygen concentration and reaction rate in Figures 3.31 to 3.36

TABLE IX

F.

VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 2.00 INCHES

| parameters                               | extin   | ction   | combu   | stion   |
|------------------------------------------|---------|---------|---------|---------|
|                                          | maximun | minimun | maximun | minimun |
| permeability (ft.sq)(10- <sup>10</sup> ) | 1.748   | 1.617   | 1.822   | 1.617   |
| pressure (lb/ft.sq)                      | 2117    | 2066    | 2117    | 2067    |
| pressure gradient (lb/ft.cu)             | - 136   | -482    | - 88    | - 525   |
| pore velocity (ft/hr)                    | 1004    | 381     | 899     | 346     |
| Reynolds number                          | 0.1025  | 0.0303  | 0.0561  | 0.0206  |
| convection coefficient                   | 19.39   | 12.75   | 17.54   | 12.66   |





Figure 3.31 Temperature vs X/L and time for thickness = 4.00 in Initial carbon temperature = 690 F.

TEMPERATURE SURFACE FROM GRAFTE



Figure 3.32 Temperature vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F.

CATGEN CONC. SUPFACE FROM GRAFIE



Figure 3.33 Oxygen concentration vs X/L and time for thickness = 4.00 in Initial carbon temperature = 690 F.

BYISEN CONC. SURFACE FROM GRAFSE



Figure 3.34 Oxygen concentration vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F.

PERCTION PRIE SUPPRCE FROM GRAFTE

100000000000

2.2.2.2.2.2.2.



Figure 3.35 Reaction rate vs X/L and time for thickness = 4.00 in Initial.carbon temperature = 690 F.

REPOTION RATE SURFACE FROM GRAFSE



Figure 3.36 Reaction rate vs X/L and time for thickness = 4.00 in Initial carbon temperature = 680 F.

# TABLE X

**GROW** 

# VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 4.00 INCHES

| parameters                               | extin   | ction   | combu   | stion   |
|------------------------------------------|---------|---------|---------|---------|
|                                          | maximun | minimun | maximun | minimun |
| permeability (ft.sq)(l0- <sup>14</sup> ) | 1.659   | 1.617   | 1.710   | 1.617   |
| pressure (lb/ft.sq)                      | 2117    | 2067    | 2117    | 2066    |
| pressure gradient (lb/ft.cu)             | - 166   | -241    | - 49    | -242    |
| pore velocity (ft/hr)                    | 444     | 199     | 410     | 136     |
| Reynolds number                          | 0.0371  | 0.0174  | 0.0289  | 0.0124  |
| convection coefficient                   | 12.89   | 9.30    | 12.27   | 7.86    |

(a)

ZRUXXNY:NXXXXXXX

7. CASE III-7 Thickness = 6.00 inches

Below is given the initial uniform carbon temperature for combustion and extinction:

> for combustion Tc = 650 seconds for extinction Te = 640 seconds

The variable parameters for this case are given in Table XI

The Figures 3.37 to 3.42 show the development of carbon temperature, oxygen concentration and reaction rate at each position during the combustion and extinction processes.



Figure 3.37 Temperature vs X/L and time for thickness = 6.00 in Initial carbon temperature = 650 F.

## TEMPERATURE SURFACE FROM GRAF3E



Figure 3.38 Temperature vs X/L and time for thickness = 6.00 in Initial carbon temperature = 640 F.

OXYDEN COND. SURFROE FROM GRAFSE



Figure 3.39 Oxygen concentration vs X/L and time for thickness = 6.00 in Initial carbon temperature = 650 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 3.40 Oxygen concentration vs X/L and time for thickness = 6.00 in

Initial carbon temperature = 640 F. -ERCTION BRIE CUPPACE FROM GRAFTE



### REACTION RATE SURFACE FROM GRAF3E



Figure 3.42 Reaction rate vs X/L and time for thickness = 6.00 in Initial carbon temperature = 640 F.

D. SUMMARY

Here, some observations are made about the effects of thickness on the combustion process.

1. Power Relation

For each case a pair of values (thickness, combustion temperature) was obtained. Four plots of this data are shown in Figures 3.43 to 3.46.

Figures 3.43 and 3.44 show thickness versus combustion temperature , and Figures 3.45 and 3.46 show thickness versus the time it takes for the oxygen concentration at X/L = 1. to reach.

It is observed that the relation between thickness and combustion temperature , figure 3.43 has a form which approximates an exponentially decreasing function.

The log-log plot ( Figure 3.44 ) is close to a linear form, which yields the approximate power relation.

The temperature is in degrees fahrenheit and thickness is in inches .

-149.8 maximun minimun 1.617 2066 66 combustion 1.717 -33.4 2117 292 maximun minimun -160.8 1.617 2067 138 extinction 1.657 -48.8 2117 325 pressure gradient (lb/ft.cu) permeability (ft.sq)(l0-<sup>10</sup>) pore velocity (ft/hr) pressure (lb/ft.sq) parameters

0.0056

0.0201 10.37

0.0126

0.0318

7.75

11.14

convection coefficient

Reynolds number

6.41

VARIED PARAMETERS DURING THE PROCESS FOR THICKNESS = 6.00 INCHES

TABLE XI

 $T = 850 L^{-0} 16554$ 

A comparison of the computer program's results and the formula's results are given in Table III. The maximum difference between the analytical results and the power equation results is less than 3 percent over the range of thickness between 0.25 and 6.00 inches.

This shows that the formula is a good approximation for these cases.

2. <u>Combustion Start Time</u>

During the initial phase of the combustion process, the oxygen concentration at all points of the porous medium continuously decreases to zero. for all cases, the point of the porous medium that first reached zero was X/L = 1. The time it taken for that the oxygen concentration at X/L = 1. to reach zero is important because it is related to the time that combustion starts.

Figure 3.45, shows that this time does not increase linearly with the thickness. The log-log plot of these values, Figure 3.46, shows that this log-log plot is approximately a straight line.

The equation for this line is:

 $T* = 226.8 L^{1}.683$ 

(3.2)

(3.1)

This equation can be used to give an estimate for the time it takes for combustion to start.



# THICKNESS VERSUS TEMPERATURE

Figure 3.43 Thickness versus combustion temperature Retangular plot.



Figure 3.44 Thickness versus combustion temperature Log-log plot.

THICKNESS VERSUS T\* **S** 8 TIME THAT OXYGEN REACH ZERO (S) 8 8 THICKNESS (INCHES)

Figure 3.45

Thickness vs time for oxygen concentration at X/L = 1. to reach zero Retangular plot.

# THICKNESS VERSUS T\*





TABLE XII RESULTS FOR ALL THICKNESS CASES

CANCEL CONTRACTOR

|       |       | extinction  | combust | ion temperature | (F)     |        |
|-------|-------|-------------|---------|-----------------|---------|--------|
|       |       | temperature |         | power           |         |        |
| cases | L(in) | (F)         | program | relation        | % error | t* (s) |
| 1-111 | 0.25  | 1090        | 1100    | 1090            | 2.8     | 22     |
| 111-2 | 0.50  | 950         | 960     | 950             | 0.7     | 68     |
| 111-3 | 0.75  | 890         | 006     | 890             | 0.9     | 136    |
| 111-4 | 1.00  | 840         | 850     | 840             | 0.0     | 225    |
| 111-5 | 2.00  | 750         | 760     | 750             | 0.3     | 748    |
| 9-11I | 4.00  | 680         | 690     | 680             | 2.1     | 2253   |
| 111-7 | 6.00  | 640         | 650     | 640             | 2.8     | 4626   |

and a start a start and a strategy with the start a start and a start a start a start a start a start a start a

### IV. PERMEABILITY

### A. INTRODUCTION

The permeability or hydraulic conductivity of a porous medium is the capacity of air flow through the porous medium. The air provides the oxygen for combustion . On the other hand , air flow provides for convective heat transfer within the medium . Thus air flow provides for heat generation from combustion , as well as heat transfer by convection . The interaction of these two mechanisms determines whether combustion or extinction will occur . If the heat generation of combustion is greater than the heat transfer of convection , then combustion will occur . If the heat transfer mechanism dominates , then extinction will occur . The equation used for permeability in the program is :

$$m = 0.2 p^3 / z^2$$
 (4.1)

Where m is the permeability , p is the porosity and z is the specific internal area . The expressions for porosity and specific internal area are :

$$p = 1 - \pi / 6(d/D)^3$$
(4.2)

$$z = 1/2 \pi (d/D^2)$$
 (4.3)

$$z = 1/2 \pi (d^2/D^3)$$
 (4.4)

The equation 4.3 is for spherical particles and equation 4.4 is for cylindrical particles . Equation 4.1 is the Kozeny

equation for permeability of porous medium . This equation fails for highly porous fibrous media .



Figure 4.1 Geometry of a typical cell.

This equation fails for highly porous fibrous medias .

The tortuosity  $,\tau$ , is the ratio of the length of the flow path for a fluid particle to the straight line distance. The tortuosity depends on the ratio d/D .In this program tortuosity was assumed to have a constant value of 1.4 .

Normally the interior geometry of a porous medium can be inregular and complex . In such cases the internal structure is difficult to discribe analytically . The program used in this investigation models the porous medium as consisting of cylindrical fibers or spherical particles in a regular periodic geometry as shown in Figures 4.1 .

During the combustion process carbon is being continuously consumed and as a result, the internal geometry is changing. The medium becomes more porous as the carbon decreases. Therefore, all properties which depend upon fiber or particle diameter are functions of time and position. The model used in the program assumed that the carbon matrix remains rigid as the particles diameter decreases , and thus , the porosity increases with combustion .

**B. PROCEDURE** 

To study the effects of permeability on combustion , all parameters of the program were maintained constant , except the permeability . In order to change the permeability and keep the porosity constant , it is necessary to keep the (d/D) ratio constant as seen in the equations 4.5 and 4.6 . This is accomplished by setting d/D equal to $\alpha$  . Then the numerator of equation 4.1 remains constant , however the denominator changes because  $d = \alpha D$  and Z gives :

$$Z = 1/2 \pi (\alpha d/D^2) = \text{constant} / D$$
 (4.5)

$$Z = 1/2 \pi (\alpha^2 d^2/D^3) = \text{constant} / D$$
 (4.6)

Thus , the dimensions of d and D were changed proportionally so that the initial ratio (d/D) remained constant in all cases . Thus the porosity remained constant while the permeability was different for each case .

The cases studied in this section are :

CASE IV-1 PERMEABILITY =  $0.00015 \text{ ft}^2 \text{ (d=D=0.0025 in)}$ CASE IV-2 PERMEABILITY =  $0.00058 \text{ ft}^2 \text{ (d=D=0.0050 in)}$ CASE IV-3 PERMEABILITY =  $0.00233 \text{ ft}^2 \text{ (d=D=0.0100 in)}$ CASE IV-4 PERMEABILITY =  $0.00933 \text{ ft}^2 \text{ (d=D=0.0200 in)}$ 

For each values of permeability the program was run with different uniform carbon temperatures for all points (X/L). This procedure was repeated until we obtaind the minimum temperature that results in combustion . This temperature

is called the combustion temperature  $(T_c)$  . Extinction occurs at temperatures below  $T_c$  .

$$T_{c} = T_{e} + \delta \tag{4.7}$$

In this section this difference ( $\delta$  ) was chosen equal at 10 F then :

 $T_c = T_e + 10$  (F) (4.8)

### C. RESULTS

For each case , the program provided the values of the carbon and air temperatures inside the porous medium , as well as other parameters which varied during the combustion process .

1. CASE IV-1 Permeability = 0.00015 ft<sup>2</sup> (d=D=0.0025 in)

For this value of permeability , the maximum carbon temperature that does not result in combustion (extinction temperature) and the minimum temperature that results in combustion (combustion temperature) are :

> for combustion  $T_c = 760$  F for extinction  $T_e = 750$  F

The graphical results are shown in Figures 4.2 to 4.7. These graphical surfaces show the carbon temperature, oxygen concentration and reaction rate at each position and time. The form of these surfaces shows the different behavior of these three parameters during the extinction and combustion processes.

### TEMPERATURE SURFACE FROM GRAF3E



Figure 4.2 Temperature vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperature = 760 F.

### TEMPERATURE SURFACE FROM GRAF3E



Figure 4.3 Temperature vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperature = 750 F.

### OXYGEN CONC. SURFACE FROM GRAF3E



Figure 4.4 Oxygen concentration vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperatiure = 760 F.

DXYGEN CONC. SURFACE FROM GRAFIE



Figure 4.5 Oxygen comcentration vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperatiure = 750 F.

an in the

NEW IX DY XDY NYN AN AN AN AN AN AN AN AN AN

REACTION RATE SURFACE FROM GRAFSE



Figure 4.6 Reaction rate vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperatiure = 760 F.

REACTION RATE SURFACE FROM GRAFSE



Figure 4.7 Reaction rate vs X/L and time for permeability = 0.00015 ft<sup>2</sup> initial carbon temperatiure = 750 F.

| ŀ | AD-A1      | 54 488 | PAR | AMETRI<br>AL POS | C ANA | LYSIS<br>VATE S | OF COM<br>Chool | BUSTIC | DN OF I<br>Rey ca | POROUS<br>A C | NEDIL | IN(U)<br>AO | 2/ | 2 |
|---|------------|--------|-----|------------------|-------|-----------------|-----------------|--------|-------------------|---------------|-------|-------------|----|---|
| Ľ | UNCLAS     | SIFIE  | )   |                  |       |                 |                 |        |                   |               | F/G 2 | 1/2         | NL |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   |            |        |     |                  |       |                 |                 |        |                   |               |       |             |    |   |
|   | - <u>-</u> | _      |     |                  |       |                 |                 |        |                   |               |       |             |    | A |



201

MARIA TILLAND

MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

,8

2. <u>CASE IV-2 Permeability = 0.00058 ft<sup>2</sup> (d=D=0.0050 in)</u> Here the value of permeability is 0.00058 ft<sup>2</sup> which results from a pore diameter of 0.0050 in . For this case the combustion and extinction temperatures are :

for combustion  $T_c = 850 \text{ O F}$ for extinction  $T_e = 840 \text{ O F}$ 

From the numerical output of the program , three graphical surface s were created ; the carbon temperature , oxygen concentration and reaction rate as functions of time and position . These surfaces provide information of the development of these three dependent variables during the combustion and extinction process . These surfaces are shown on Figures 4.8 to 4.13 .

TEMPERATURE SURFACE FROM GRAF3E



Figure 4.8 Temperature vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperature = 850 F.

### TEMPERATURE SURFACE FROM GRAFSE



Figure 4.9 Temperature vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperature = 840 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 4.10 Oxygen concentration vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperatiure = 850 F.

### OXYGEN CONC. SURFACE FROM GRAF3E



Figure 4.11 Oxygen comcentration vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperatiure = 840 F.

### REACTION RATE SURFACE FROM GRAF3E



Figure 4.12 Reaction rate vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperatiure = 850 F.

### REACTION RATE SURFACE FROM GRAF3E



Figure 4.13 Reaction rate vs X/L and time for permeability = 0.00058 ft<sup>2</sup> initial carbon temperatiure = 840 F.

3. <u>CASE IV-3 Permeability = 0.00233 ft<sup>2</sup> (d=D=0.0100 in)</u> For this case the initial permeability is 0.00233  $ft^2$ . With this value of permeability the combustion and extinction temperatures are :

| for | combustion | т <sub>с</sub> | = | 980 | 0.F |
|-----|------------|----------------|---|-----|-----|
| for | extinction | T              | = | 970 | 0.F |

The variation of the dependent variables during the combustion and extinction cases is shown by a numerical output of the program . These results are also shown in three graphical surfaces ; carbon temperature , oxygen concentration and reaction rate on each position (X/L) and time . These graphical results are shown in Figures 4.14 to 4.19

TEMPERATURE SURFACE FROM GRAFSE



Figure 4.14 Temperature vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 980 F.

TEMPERATURE SURFACE FROM GRAFIE



Figure 4.15 Temperature vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 970 F.

OXIGEN CONC. SURFACE FROM GRAFIE



Figure 4.16 Oxygen concentration vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 980 F.

OXYGEN CONC. SURFACE FROM GRAFIE



Figure 4.17 Oxygen comcentration vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 970 F.

### REACTION RATE SURFACE FROM GRAFSE



Figure 4.18 Reaction rate vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 980 F.

REPOTION RATE SURFACE FROM GRAFSE



States - States

Figure 4.19 Reaction rate vs X/L and time for permeability = 0.00233 ft<sup>2</sup> initial carbon temperatiure = 970 F.

4. <u>CASE IV-4 Permeability = 0.00933 ft<sup>2</sup> (d=D=0.0200 in)</u> The combustion and extinction temperatures for this case, with initial permeability equal to 0.00933 ft<sup>2</sup>, are:

> for combustion  $T_c = 1180 \text{ 0.F}$ for extinction  $T_e = 1170 \text{ 0.F}$

for this case , it was not possible to obtain the graphical surfaces due to limitations of the graphical program .

D. SUMMARY

Here , some observations about the effects of permeability on combustion can be understood by looking at all the results at one time . Table XIII contains the results of all cases .

The Table lists the temperatures for extinction and combustion ,the permeability (m) , the dimension of the unit cell (d=D) and time t\* . The t\* time is the time at which the oxygen concentration at a point reaches zero first . That point of the porous medium that first reaches zero oxygen concentration in all these cases is the the position point X/L = 1.

1. Power Relation

The pair of values (permeability , combustion temperature) for each case was plotted on a cartesian graph. An observation of this curve shows that the combustion temperature increases with increasing permeability. Figure 4.20 shows that the combustion temperature increases monotonically and approaches an assindoticptate as permeability increases . The plot of these same points on a log-log graph , Figures 4.21 , shows that its form is not quite a straight line .

It is observed that the relation between combustion temperature  $(T_c)$  and permeability (m) yields the approximate power relation (equation 4.9) :
|           | t* (s)     | 420     | 220     | 83      | 23      |
|-----------|------------|---------|---------|---------|---------|
| ure (o F) | Te         | 750     | 840     | 970     | 1170    |
| temperat  | Τc         | 760     | 850     | 980     | 1180    |
|           | (d=D) (in) | 0.0025  | 0.0050  | 0.0100  | 0.0200  |
|           | m (ft²)    | 0.00015 | 0.00058 | 0.00233 | 0.00933 |
|           |            | IV-1    | IV-2    | IV-3    | 1V-4    |
|           |            | CASE    | CASE    | CASE    | CASE    |

TABLE XIII

RESULTS FOR PERMEABILITY

 $T_c = 1880 \text{ m}^0.105$ 

(4.9)

A comparation of the values of the combustion temperature obtained by the program and by the power relation is presented in Table XIV. This Table shows that the difference between these results fail betweer 1.2 to 3.2 percent. This result shows that the above power relation is a good approximation to estimate the temperature which will start combustion for a given permeability.

2. Combustion Speed

In this section , the question of how permeability affects the time it takes for combustion to begin is addressed . We meassure the rapidilly of the combustion process by the t\* time previously defined . Recall that t\* is the time at which the oxygen first reaches zero at some point in the porous medium . In all cases the position X/L =l is the first point to achieve zero oxygen concentration . The plots of permeability (m) versus t\* , Figures 4.22 and 4.23 , show that t\* decays exponentially with increasing permeability and approaches an assymptotic value of t\* = 0 as m goes to infinity .

A very interesting observation is obtained from the results of Table XIII . It is noted that the  $m_{i+1}/m_i$  (for i = 1,2,3) remains pratically constant (3.84 , 4.01 , 4.00) while the  $t*_{i+1}/t*_i$  ratio takes on the variable values 1/(i+1) (1/1.91 , 1/2.65 , 1/3.56).

An attempt was made to obtain an additional run with the permeability equal to  $0.03733 \text{ ft}^2$ , however the combustion activity was too rapid to achieve meaningful results. Combustion was achieved so rapidly that the gradient were too large for the program to handle.

The permeability is a parameter that has great influence on the combustion process for porous medium .



Figure 4.20 Permeability versus combustion temperature retangular plot.



# PERMEABILITY VERSUS TEMPERATURE



Permeability versus combustion temperature log log plot.

| RESULTS  |  |
|----------|--|
| RELATION |  |
| POWER    |  |

TABLE XIV

ð

4 . . . .

|      |    |   |   | combustion t | emperature (o.F) | difference |
|------|----|---|---|--------------|------------------|------------|
|      |    |   |   | program's    | power relation   | in percent |
| CASE | ١٧ | • | 1 | 760          | 745.8            | 1.9        |
| CASE | ١٧ | I | 2 | 850          | 859.6            | 1.1        |
| CASE | IV | ı | 3 | 980          | 994.8            | 1.5        |
| CASE | lν | I | 4 | 1180         | 1150.8           | 2.5        |



語言語の時間に

Figure 4.22 Permeability versus t\* Retangular plot.



#### V. REACTION ORDER

#### A. INTRODUCTION

The expression for reaction rate for carbon reacting in air used in the program was the expression resulting from the experimental data of Parker and Hotel .

$$R_{c} = A \frac{P_{c_{a}}^{n}}{\sqrt{T_{c}}} \exp\left(\frac{-E}{RT_{c}}\right) \frac{gr-c}{cms}$$
(5.1)

Reaction order is the exponent of the partial pressure of oxygen in the expression of the reaction rate . The program permits the user to select any value for this parameter . In all of the previous chapters , a value of n equal to 0.5 was used . In this chapter we investigate the effect of n on the combustion process .

#### B. PROCEDURE

In this section , all parameters are fixed to their basic values and only the reaction order is changed in each case .

The program was run , for each value of reaction order , with different value of the uniform initial carbon temperature until we obtained the minimum temperature which results in combustion . This temperature is the combustion temperature ( $T_c$ ) . The maximum temperature that results in extinction is the extinction temperature ( $T_e$ ). they differ by an infinitesimal $\delta$  ( $T_c = T_e + \delta$ ). The magnitude of  $\delta$  was chosen equal to 10 F for this study .

In order to study the influence of the reaction order on the combustion process , four different values of this parameter were chosen . These cases are :

| CASE | V-1 | Reaction | Order | Ξ | 0.25 |
|------|-----|----------|-------|---|------|
| CASE | V-2 | Reaction | Order | = | 0.50 |
| CASE | V-3 | Reaction | Order | = | 0.75 |
| CASE | V-4 | Reaction | Order | = | 1.00 |

The fixed parameters used in all cases are : Ambient temperature = 80 F Ambient pressure = 2117 lb/ft.sq Tortuosty = 1.400Filamento diameter = 0.0004167 ft Thickness of matrix laminette = 0.0004167 ft Thickness of porous medium = 0.02083 ft Gas constant for air = 53.34 lbf ft/lbm R Conductivity of filament = 86 BTU/1bm H.F. Specific heat of filament = 0.703 lbm/Cf Emissivity of filament = 0.90 Shape factor for internal HFxFER =1.00 Characteristc length of medium = 1 inchess Heat of reaction = 14090 BTU/Cf Stochiometric ratio (fuel/air) = 0.375 Reaction coefficient = 2065000 lbm/Cf H Activetion energy coefficient = 28840 deg R Pressure differential across thickness = 50 lb/ft.sq Initial uniform oxygen concentration =  $0.172 \text{ lbm/ft}^3$ 

#### C. RESULTS

For each cases the results were obtained in both numerical and graphical form . These results show the variation of some parameters during the combustion and extinction processes . The results obtained for each value of reaction order are presented below

1. CASE V-1 Reaction Order = 0.25

With this value of reaction order , the combustion and extinction processes define the following characteristic temperatures : for combustion  $T_c = 980 \text{ o.F}$ for extinction  $T_e = 970 \text{ o.F}$ 

The analysis of the numerical output of the program shows that some parameters varied during the combustion and extinction processes. The limits of these parameters show the character of the particular kind of process which occured.

The graphical results show three surfaces that represent the evolution of the carbon temperature , oxygen concentration and reaction rate at each position during the transient history . These graphical surfaces are shown in Figures 5.1 to 5.6 .

TEMPERATURE SURFACE FROM GRAFSE



Figure 5.1 Temperature vs X/L and time for reaction order = 0.25 Initial carbon temperature = 980 F.

#### TEMPERATURE SURFACE FROM GRAFSE



Figure 5.2 Temperature vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F.

DX (GEN CONC. SURFACE FROM GRAF3E



Figure 5.3 Oxygen concentration vs X/L and time for reaction order = 0.25 Initial carbon temperature = 980 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.4 Oxygen concentration vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F.

PEACTION RATE SURFACE FROM GRAFSE



Figure 5.5 Reaction rate vs X/L and time for reaction order = 0.25 Initial carbon temperature = 980 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 5.6 Reaction rate vs X/L and time for reaction order = 0.25 Initial carbon temperature = 970 F.

2. CASE V-2 Reaction Order = 0.50

For reaction order equal to 0.50 , the initial uniform carbon temperatures that separate the combustion and extinction processes are :

for combustion  $T_c = 980 F$ for extinction  $T_e = 970 F$ 

The program's numerical output included the values of some parameters that varied during the transient process. The variation of the values characterize the combustion or extinction process. The graphical results are shown in three surfaces: carbon temperature, oxygen concentration and reaction rate versus position (X/L) and time. These graphical surfaces are shown in figures 5.7 to 5.12.

### TEMPERATURE SURFACE FROM GRAF3E



Figure 5.7 Temperature vs X/L and time for reaction order = 0.50 Initial carbon temperature = 850 F.

TEMPERATURE SURFACE FROM GRAFSE



Figure 5.8 Temperature vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F.

### OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.9 Oxygen concentration vs %/L and time for reaction order = 0.50 Initial carbon temperature = 850 F.

DXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.10 Oxygen concentration vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F.

### REACTION RATE SURFACE FROM GRAF3E



Figure 5.11 Reaction rate vs X/L and time for reaction order = 0.50 Initial carbon temperature = 850 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 5.12 Reaction rate vs X/L and time for reaction order = 0.50 Initial carbon temperature = 840 F.

3. CASE V-3 Reaction Order = 0.75

The reaction order was set equal to 0.75 for this case. The combustion and extinction temperatures are:

for combustion Tc = 750 Ffor extinction Te = 740 F

A visualization of the development of the carbon temperature, oxygen concentration and reaction rate at each position and time are shown in the graphical surfaces of Figures 5.13 to 5.18.

TEMPERATURE SURFACE FROM GRAF3E



Figure 5.13 Temperature vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F.

TEMPERATURE SURFACE FROM GRAF3E



Figure 5.14 Temperature vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.15 Oxygen concentration vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F.

OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.16 Oxygen concentration vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F.

REACTION RATE SURFACE FROM GRAFTE



Figure 5.17 Reaction rate vs X/L and time for reaction order = 0.75 Initial carbon temperature = 750 F.

REACTION RATE SURFACE FROM GRAF3E



Figure 5.18 Reaction rate vs X/L and time for reaction order = 0.75 Initial carbon temperature = 740 F.

4. CASE V-4 Reaction Order = 1.00

For this case, the temperature of the combustion and extinction processes are:

for combustion  $T_c = 670 F$ for extinction  $T_e = 660 F$ 

The Figures 5.19 to 5.24 show the behavior of the carbon temperature, oxygen concentration and reaction at each position and time.

D. SUMMARY

1. <u>Power Relation</u>

For each case, a pair of values (reaction order, combustion temperature) was obtained. The points were plotted in cartesian coordinates in Figure 5.25. A log-log plot is shown in Figure 5.26, and a semi log plot is shown in Figure 5.27. It is observed that the relation between

#### TEMPERATURE SURFACE FROM GRAF3E



Figure 5.19 Temperature vs X/L and time for reaction order = 1.00 Initial carbon temperature = 670 F.

reaction order (n) and combustion temperature  $(T_c)$  of figure 5.27 yields the approximate power relation (equation 5.2).

Table 5.25 shows a resume of each case, combustion temperature, extinction temperature and the value of the combustion temperature obtained from Equation 5.2 and the percentage error . An observation of these results leads to the conclusion that this power relation is a good estimation for combustion temperature.

### TEMPERATURE SURFACE FROM GRAF3E





OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.21 Oxygen concentration vs X/L and time for reaction order = 1.00 Initial carbon temperature = 670 F.

## OXYGEN CONC. SURFACE FROM GRAF3E



Figure 5.22 Oxygen concentration vs X/L and time for reaction order = 1.00 Initial carbon temperature = 660 F.

REACTION RATE SURFACE FROM GRAFTE



Figure 5.23 Reaction rate vs X/L and time for reaction rate= 1.00 Initial carbon temperature = 670 F.

126

REACTION RATE SURFACE FROM GRAF3E



Figure 5.24 Reaction rate vs X/L and time for reaction order = 1.00 Initial carbon temperature = 660 F.

 $T_c = 10^{(3.05-0.22n)}$  (F)

(5.2)

## TABLE XV

## COMBUSTION AND EXTINCTION TEMPERATURE FOR REACTION GRDER CASES

## temperatures (<sub>o</sub>F)

|          | extinction | combust | tion     | % error |
|----------|------------|---------|----------|---------|
| reaction | program    | program | power    |         |
| order    | output     | output  | relation |         |
| 0.25     | 970        | 980     | 980      | 0.0     |
| 0.50     | 840        | 850     | 863      | 1.6     |
| 0.75     | 740        | 750     | 760      | 1.4     |
| 1.00     | 670        | 670     | 670      | 0.0     |



Figure 5.25 Reaction order versus temperature Retangular plot.

## **REACTION ORDER VERSUS TEMPERATURE**



Figure 5.26 Reaction order versus temperature Log-log plot.

## **REACTION ORDER VERSUS TEMPERATURE**



Figure 5.27 Reaction order versus temperature Semi log plot.

#### VI. CONCLUSIONS

In each of the previous chapters, the effects of a single parameter on the combustion behavior of a porous medium was investigated. In Chapter 2, we considered the effect of heat flux (SQ) and its duration (TQ) on combustion. In Chapter 3, the effect of medium thickness (L) on behavior was investigated. Chapter 4 was a study of the effect of permeability (m) on system behavior; and finally in Chapter 5, the effect of reaction order (n) was investigated.

The major conclusions from these investigations are:

- The relation between SQ and TQ is not linear, a power relation gives rasonable approximation.
- During the combustion process, for the SQ cases, initially there is a large temperature gradient across the medium with T (X/L = 0.) >> T (X/L = 1.). With passing time, this gradient decreases until there is a uniform combustion temperature over the entire medium. When this occurs, there is no oxygen within the medium, and the medium is continuosly consumed by combustion.
- The relation between thickness and combustion tempera ture is not linear . Increasing the thickness results in decreasing of combustion temperature. If the thickness increased with a constant rate c ( $L_{i+1}/l_i =$ c) the time that marks the start of combustion is not constant , it increases with increasing thickness ( i.e.  $t_{i+1}^*/t_i^* = b(L)$ ) where b depends upon the thickness .

- The relation between permeability and minimum combus tion temperature is not linear.

- An increase of the permeability shows that the combus tion temperature increases to an asymptotic limit.

- Permeability has a significant influence on the speed of the combustion process. When the permeability is increased, the time that marks the start of the combustion process decreases. For large values of permeability, the combustion may occur in a fraction of a second.

- If the permeability is increased with a constant rate  $c(m_{i+1} = c m_i)$ , the time that measures the start of combustion decreases .
- The relation between reaction order (n) and combustion temperature (Tc) is not linear.
- An observation of the graphical surfaces, for all cases of this investigation, shows a similar form for combustion and extinction cases. a11 For a11 combustion cases, it was noted that the oxygen within the porous medium being consumed with passing time. The first point at which the oxygen is depleted is always X/L = 1. With passing time the point with smaller X/L reach zero oxygen, until all points have zero oxygen. At this time the only oxygen is at the interface of the porous medium and the ambient environment. At this time the combustion process becomes a surface recession phenomena. At the same time the oxygen is being depleted the temperature is increasing. Eventually when all the interior oxygen has been consumed, there is a temperature gradient across the medium with  $T_{c}(X/L=0) > T_{c}(X/L=1)$ .

This thesis concludes with two recomendations . First , it is recommended that additional parameter studies he conducted . For example , it would be useful to determine the effects of pressure differential , conductivity , and other thermophysical properties on combustion . Another recommendation is to attempt to obtain a relation between combustion temperature and several parameters .

### LIST OF REFERENCES

- Vatikiotis, C. S., <u>A Combustion and Heat Tranfer Model</u> <u>for Porous Media</u>, Phd.Dissertation, Naval Posgraduate School, Monterey, California, 1982.
- 2. Semenov, N. N., <u>Chemical Kinetics and Chain Reaction</u>, Clarendon Press, Oxford, 1935.

## IN TIAL DISTRIBUTION LIST

.

A CONTRACT OF A CONTRACT OF

ì

|    |                                                                                                                                                  | No.   | Copies |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------|
| 1. | Departamento de Pesquisa e Desenvolvimento<br>Ministerio da Aeronautica<br>Brasilia , Brazil                                                     |       | 2      |
| 2. | Centro Tecnico Aeroespacial<br>Ministerio da Aeronautica<br>Sao Jose dos Campos , SP , Brazil 12200                                              |       | 2      |
| 3. | Major Antonio C. S. Serapiao , Brazilien air<br>Centro Tecnico Aeroespacial<br>Sao Jose dos Campos , SP , Brazil 12200                           | force | 3      |
| 4. | Associate Professor David Salinas , Code 69Zc<br>Department of Mechanical Engineering<br>Naval Posgraduate School<br>Monterey , California 93940 |       | 3      |
| 5. | Library , Code 0142<br>Naval Posgraduate School<br>Monterey , California 93943                                                                   |       | 1      |
| 6. | Departament Chairman , Code 69<br>Departament of Mechanical Engineering<br>Naval Posgraduate School<br>Monterey , California 93943               |       | 1      |
| 7. | Defense Technical Information Center<br>Cameron Station<br>Alexandria , Virginia 22304-6145                                                      |       | 2      |

135

