ND	ND-R167 171 OPTIMUM ACCELERATION FACTORS FOR ITERATIVE SOLUTIONS OF 1/1 LINER AND MON-LI. (U) TEXAS UNIV AT AUSTIN DEPT OF													
UN	CLAS	SIFIE) <u>G</u> S	DULIK	RAVIC	ET A	L. 30	DEC 8	<u>.</u>		F/G 1	.2/1	NL.	_
•														
										-				



MICROCOP

CHART



Interim Scientific Report : December 1, 1984 - November 30, 1985

(Grant AFSOR - 85 - 0052)

OPTIMUM ACCELERATION FACTORS FOR ITERATIVE SOLUTIONS OF

LINEAR AND NON-LINEAR SYSTEMS

Principal Investigator :

Dr. George S. Dulikravich, Assistant Professor Department of Aerospace Engineering and Engineering Mechanics Tel. (512) 471-4178

Co-Investigator :

Dr. David M. Young, Jr., Professor Department of Mathematics Director, Center for Numerical Analysis Tel. (512) 471-7711

Project Monitor :

OTIC FILE COPY

Capt. John P. Thomas, Jr. USAF Program Manager, Computational Mathematics Directorate of Mathematical and Information Science, AFOSR/NM Bolling AFB, D.C. 20332 Tel. (202) 767-5026



The University of Texas at Austin

Austin, Texas 78712 - 1085

December 30, 1985

00

1

Approved for public release; distribution unlimited.

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC) NOTICE OF TRANSMITTION TO DITC This technical of problem of the standard and is List of Contents proved for schule of the standard and is Distribution at calimited. MATTHEW J. KERTER Chief, Technical Information Division

Com	oined Summ	nary	1
A.	Report of	f the Group Headed by Dr. G.S. Dulikravich	
	A.1	Abstract	1
	A.2	Research Objectives and the Statement of Work	2
	A.3	Status of Research	2
	A.3.1	Introduction	3
	A.3.2	Theoretical Aspects	5
	A.3.2.1	Optimization of the Euler Scheme for Linear Problems	5
	A.3.2.2	Multi-Step Minimum Residual Method for Linear Problems	8
	A.3.2.3	Optimization of the Euler Scheme for Nonlinear Problems -	10
	A.3.2.4	The Generalized Nonlinear Minimum Residual Method	13
	A.3.3	Numerical Examples	15
	A.3.3.1	Burgers' Equation	16
	A.3.3.2	The Heat Conduction Equation	19
	A.3.4	Conclusion Remarks	22
	A.3.5	References	23
	A.4	List of Publications	38
	A.5	List of Professional Personnel	38
	A.6	Interactions (Coupling Activities)	38
	A.7	New Discoveries, Inventions and Patent Disclosures	40
	A.8	Additional Information for Evaluation of the Progress	40
Β.	Report o	f the Group Headed by Dr. D.M. Young, Jr.	
	B.1	Abstract	41

B.2 Research Objectives and the Statement of Work ------ 41

ii

B.3	Status of Research	42
B.4	List of Publications	42
B.5	List of Professional Personnel	42
B.6	Interactions (Coupling Activities)	43
B.7	New Discoveries, Inventions and Patent Disclosures	43
B.8	Additional Information for Evaluation of the Progress	43

Accession For NTIS GRAZI DTIC TAB Unannounced Justific Lien By Distribution / Avadulo Liegeneiles 1.701 (\mathbf{r}_{i}) 4 dy stal Dist QUALITY

. . .

.

COMBINED SUMMARY

Two different approaches to the acceleration of iterative algorithms for the numerical solution of differential systems have been developed. General form of the non-linear minimal residual method has been analytically determined and numerically confirmed for linear and non-linear problems. The method was applied to multi-step algorithms for effectively determining optimal values of each of the acceleration parameters at each time step. It was found that both the rate of iterative convergence and the smoothness of the iterative convergence can be substantially augmented by the use of these multiple optimal acceleration parameters.

The second approach involves a composite adaptive method which is based on variational techniques. An automatic procedure for determining splitting parameters needed in the iterative solution of large sparse linear systems was developed. It was then complemented with the generalized conjugate gradient acceleration procedures and successfully applied in the symmetric successive overrelaxation method and in the shifted incomplete Cholesky method.

A. Report of the Group Headed by Dr. G.S. Dulikravich

A.1 Abstract

A generalized non-linear minimal residual (GNLMR) method based on the time-dependent approach and multi-step algorithm has been developed to accelerate iterative methods for solving linear and non-linear problems. Both theoretical studies and numerical experiments show the monotone convergence behavior of the GNLMR method. It is found that the rate of convergence and the smoothness of convergence for iterative methods can be improved by the optimized multi-step algorithm.

A.2 Research Objectives and the Statement of Work

The NLMR method developed originally by S. R. Kennon is capable of accelerating iterative methods for the solutions of linear and non-linear problems. This method can be considered as a time-dependent technique with variable time step size. The basic idea of this method is based on the sequential minimization of the global residual. A relaxation factor is introduced to minimize the L_2 norm of the residual at each iteration. This iteration-dependent optimal relaxation factor drives the iterative solution to convergence. In order to obtain a smooth convergence history, several options are available to this acceleration procedure. For instance, each three regular iterations can be followed by two accelerated iterations.

Recently, this method has been generalized by Huang, Kennon and Dulikravich by using time-dependent method and multi-step algorithm. Both theoretical studies and numerical experiments proved the monotone convergence behavior of this method. With the multi-step algorithm, it was found that the rate of convergence and the smoothness of convergence of the NLMR method can be improved even further.

Since the limitation on the time step size and the optimal value of the time step size can analytically be determined with the GNLMR method, it is believed that Euler and Navier-Stokes equations of gasdynamics can be efficiently solved using the GNLMR method.

A.3 Status of the Research

A.3.1 Introduction

The time-dependent technique proposed by Moretti and Abbett [1] in the mid-1960's was the first successful method to solve problems governed by equations of mixed type. The steady state solution was obtained by starting with the unsteady equation, and marching the solution along the time coordinate until convergence was achieved. Nowadays, the time-dependent method is widely used in computational fluid dynamics for the solution of the steady state Euler and Navier-Stokes equations [2], [3], [4].

It is interesting to note that most iterative methods for the solution of steady state problems can be shown to be equivalent to methods for solving time-dependent problems of either parabolic or hyperbolic type [5], [6]. The relaxation factor used in accelerating an iterative method to obtain the converged solution plays the same role as the time step size in advancing the transient solution to the steady state solution for a time-dependent problem. This approach offers several advantages.

For example, the mechanism of an acceleration scheme can be unveiled and an optimal value of relaxation factor (optimal time step size) could be analytically determined. If accurate time evolution is required for an unsteady problem, the time step size should be small to guarantee both the stability and the accuracy of the solution. Consequently, very often a compromise must be made beetween the computer time requirements and the accuracy of the solution of such computation provided the method is stable. Since the limitation on the time step size can be analytically determined using the GNLMR method, a satisfactory compromise can be achieved. If transient behavior is of no interest to us, it is convenient to interpret the physical time as the artificial time or to reformulate the governing equations in terms of certain artificial time. Then the GNLMR method can be applied to determine the optimal value of the time step size (optimal relaxation factor) to minimize the time steps (number of iterations) for obtaining the steady state converged solution.

The NLMR method developed by Kennon [7], [8], [9], actually can be considered as a time-dependent method with variable time step size. The NLMR method is based on the sequential minimization of the global residual. A relaxation factor is introduced to minimize the L_2 norm of the residual at each iteration. This iteration-dependent optimal relaxation factor drives the iterative solutions to convergence. In order to obtain a smooth convergence history, several options are available to this acceleration procedure. For instance, each three regular smoothing iterations are followed by two accelerated iterations [7]. Marchuk [6] has proved that under certain conditions, the variational optimization process will produce the highest convergence rate for iterative method, and the norm of the residual will form a monotone decreasing sequence with iteration. Marchuk [6] also pointed out that the convergence speed of the minimum residual method can be even further improved by using single-iteration, two-step minimum residual method.

The main objective of the present study is to extend Marchuk's idea to generalize the NLMR method using the time-dependent approach and the single-iteration, multi-step algorithm. The applications of the GNLMR method are demonstrated by two numerical examples: one dimensional Burgers' equation and the two dimensional heat conduction equation. Several interesting problems originating from this method such as integration by sampling, the concept of grid-dependent relaxation factor, and the determination of the global minimum are also discussed.

A.3.2 Theoretical Aspects

A.3.2.1 Optimization of the Euler Scheme for Linear Problems

Let us first consider a well-posed linear initial value problem

$$\partial \phi / \partial \tau = L \phi - F$$
 in Ω (1)

$$\phi = \phi_{\mathsf{B}} \qquad \text{on} \quad \partial\Omega \qquad (2)$$

$$\phi = \phi_0 \qquad \text{at } \tau = \tau_0 \qquad (3)$$

Applying the Euler one-step, time-consistent, explicit scheme, the finite difference equation of (1) can be written as :

$$\phi^{t+1} = \phi^t + \Delta \tau (\ell \phi^t - f)$$
(4)

where

£ denotes the scheme-dependent difference analog of L,

f is the discrete analog of F and

t denotes the time level.

Most linear stability analyses of the scheme represented by equation (4) do not consider the effects of boundary conditions, thus resulting in overly restrictive and even incorrect conclusions. For example, H. D. Thompson, <u>et al.</u> [10], proved that the cell Reynolds number restriction for convection-diffusion problems derived from linear stability analysis is a commonly accepted misconception. Moreover, the numerical experiments performed by S. R. Kennon [7], [8], [9], using the NLMR method showed that the usual Courant-Friedrichs-Lewy (CFL) number limitation for both linear and nonlinear problems can be significantly exceeded. It should be pointed out that, although Thompson <u>et al.</u> clarified the misconception of cell Reynolds number limitation for <u>linear</u> convection-diffusion problems, their results did not give the best value of time step size for accelerating the scheme. The NLMR method provided a simple analytic way to determine the optimal acceleration factors for both linear and nonlinear problems. However, the elementary time steps used for obtaining the corrections still follow the CFL number limitation concluded from the linear analysis.

Assuming that coding of a numerical scheme will not cause too much difficulty, stability, convergence speed (computer time) and accuracy of the solution are three major factors to be compromised in optimizing the numerical scheme. We now present an easy and analytic formulation which allows us to make this compromise effectively.

Let the exact solution of $L\phi - F = 0$ be denoted as ϕ

Define

$$\boldsymbol{\xi}^{\mathsf{t}} = \boldsymbol{\phi}^{\mathsf{t}} - \boldsymbol{\phi}^{\mathsf{t}} \tag{5}$$

$$r^{t} = \ell \phi^{t} - f \tag{6}$$

as the error and residual vectors at time level t, respectively. Hence, the time evolution of both error and residual vectors satisfy the following equations :

$$r^{t} = \ell \xi^{t} \tag{7}$$

$$r^{t+1} = r^{t} + \Delta \tau (\ell r^{t}) \tag{8}$$

$$\boldsymbol{\xi}^{t+1} = \boldsymbol{\xi}^{t} + \Delta \tau(\boldsymbol{\ell} \boldsymbol{\xi}^{t}) \tag{9}$$

The residual and the error norms at time step t+1 can be expressed as

$$\|r^{t+1}\|^2 = \|r^t\|^2 + 2\Delta\tau(r^t, \ell r^t) + (\Delta\tau)^2 \|\ell r^t\|^2$$
(10)

$$\|\xi^{t+1}\|^2 = \|\xi^t\|^2 + 2\Delta\tau(\xi^t, \, \varrho\xi^t) + (\Delta\tau)^2 \|\varrho\xi^t\|^2$$
(11)

Define the rate of convergence Γ and rate of damping Λ by

$$\mathbf{r} = -\log(\|\mathbf{r}^{t+1}\| / \|\mathbf{r}^{t}\|)$$
(12)

$$\Lambda = -\log(\|\xi^{t+1}\| / \|\xi^{t}\|)$$
(13)

The convergence and stability of scheme (4) requires that both Γ and Λ are greater than zero. However, the Lax equivalence theorem [11] states that <u>for linear initial value problems</u>, stability is the sufficient and necessary condition for convergence. Thus, the limitation on $\Delta \tau$ can be obtained by solving the inequalities :

$$\Delta \tau > 0$$
 and $||r^{t+1}||^2 < ||r^t||^2$ (14)

The solution of the above inequalities can easily be obtained as :

$$0 < \Delta \tau < -2(r^{t}, \ell r^{t}) / ||\ell r^{t}||^{2}$$
(15)

It should be noted that equation (15) addresses only stability and not the accuracy of the solution. Nevertheless, if time-accurate solution is required (with a specified accuracy), equation (15) provides the free choice of $\Delta \tau$ to meet both stability and the desired accuracy conditions. On the other hand, if time evolution is not important, $\Delta \tau$ can be chosen as large as possible to minimize the number of time steps for obtaining the steady state solution. The optimal value of $\Delta \tau$ can be determined by maximizing the convergence rate Γ and the result is

$$(\Delta \tau)_{opt} = - (r^t, \ell r^t) / ||\ell r^t||^2$$
 (16)

Thus, for steady state solution of equation (1), the optimized scheme

$$\phi^{t+1} = \phi^{t} + (\Delta \tau)_{opt} (\ell \phi^{t} - f)$$
 (17)

will produce the highest rate of convergence. The monotone convergence behavior of the optimized scheme can be best illustrated pictorially by figure 9 and figure 10. As for the stopping criteria, the L_2 norm or L_2 norm of the residual at new time level are commonly used in determining if the steady state solution is obtained. However, by examining equations (8) and (10), it is interesting to note that $\Delta \tau$ will approach zero as the converged solution is achieved. This provides us with a new criteria for stopping the iterative process.

A.3.2.2 M 'ti-Step Minimum Residual Method for Linear Problems

The method described in the previous section can be used to optimize the single-iteration, one step scheme. However, the speed of convergence of scheme (17) can be improved even further by multi-step algorithm.

Assume that M steps are used to iterate at each time level. Using the Einstein summation convention where repeated subscripts are summed, the multi-step algorithm for equation (1) is then defined as follows :

$$\phi^{t+1} = \phi^t + \omega_m \delta_m \quad ; \quad m = 1 \sim M \tag{18}$$

where

$$\delta_1 = \ell \phi^t - f$$

$$\delta_m = \ell^{m-1}(\delta_1) \quad ; \quad m > 1$$
(19)

are the residual vectors at step m, and ω_m are the relaxation factors to be determined by minimizing the L₂ norm of the residual at time level (t+1). If the previous definitions of error vector and residual vector are used, the following equations can easily be verified :

$$r^{t} = \ell \xi^{t}$$
(20)

$$r^{t+1} = r^{t} + \omega_{m} \ell \delta_{m} \tag{21}$$

$$\xi^{t+1} = \xi^{t} + \omega_{m} \delta_{m}$$
 (22)

The L_2 norm of the residual at time level t+1 can be expressed as

$$\|r^{t+1}\|^{2} = \|r^{t}\|^{2} + 2\omega_{m}(r^{t}, \ell\delta_{m}) + (\ell\delta_{m}, \ell\delta_{n})\omega_{m}\omega_{n} ; m, n = 1 \sim M$$
(23)

In order to get the highest rate of convergence, clearly, ω_m are the solutions of the following system of linear equations :

$$\partial \Gamma / \partial \omega_{\rm m} = 0$$
 or $(r^{\rm t}, \ell \delta_{\rm m}) + (\ell \delta_{\rm m}, \ell \delta_{\rm n}) \omega_{\rm n} = 0$ (24)

Multiplying equation (24) by $\boldsymbol{\omega}_{m}$, it follows that

$$(r^{t}, \ell \delta_{m})\omega_{m} + (\ell \delta_{m}, \ell \delta_{n})\omega_{m}\omega_{n} = 0$$
 (25)

Subtracting equation (25) from equation (23) and using equation (24) results in

$$\|r^{t+1}\|^{2} - \|r^{t}\|^{2} = (r^{t}, \ell \delta_{m})\omega_{m} = -(\ell \delta_{m}, \ell \delta_{n})\omega_{m}\omega_{n}$$
$$= -\int_{\Omega} (\omega_{m}\ell \delta_{m})^{2} d\Omega < 0$$
(26)

Thus, the residual norms for the multi-step minimum residual method also shows a monotone convergence behavior which guarantees the stability of the iterative scheme and produces the highest rate of its convergence.

A.3.2.3 Optimization of the Euler Scheme for Nonlinear Problems

For clarity, we consider two-dimensional problems and equations in conservative form only. The extension to the N-dimensional problems and non-conservative equations is then straightforward.

The conservative form of the governing equations for most engineering problems can be written as :

$$\partial \phi / \partial \tau = L_v N^v (\phi, \phi_x, \phi_v) - F$$
 (27)

where

$$L_1 = \partial/\partial x$$
, $L_2 = \partial/\partial y$ (28)

and N^{ν} is the nonlinear differential operator in x_{ν} coordinates. Using the Euler one-step, time-consistent, explicit scheme, the finite difference form of equation (27) can be written as :

 $\phi^{t+1} = \phi^{t} + \Delta \tau [\ell_{y} N^{v} (\phi^{t}, \phi^{t}_{x}, \phi^{t}_{y}) - f]$ (29)

or

$$\phi^{t+1} = \phi^{t} + \Delta \tau r^{t} \tag{30}$$

where

$$r^{t} = \ell_{y} N^{v}(\phi^{t}, \phi^{t}_{x}, \phi^{t}_{y}) - f \qquad (31)$$

is defined as the residual at time level t .

Therefore, the residual at time level t+1 can be expressed as

$$r^{t+1} = \ell_v N^v (\phi^{t+1}, \phi^{t+1}_x, \phi^{t+1}_y) - f$$
 (32)

After expanding the nonlinear operator $N^{\boldsymbol{\nu}}$ into Taylor series, it follows that

$$r^{t+1} = \ell_{v} \{ N^{v}(\phi^{t}, \phi^{t}_{X}, \phi^{t}_{Y})$$

+
$$[(\partial N^{v}/\phi^{t})r^{t} + (\partial N^{v}/\partial \phi^{t}_{X})(r^{t})_{X} + (\partial N^{v}/\partial \phi^{t}_{Y})(r^{t})_{Y}] \Delta \tau \quad (33)$$

+
$$O(\Delta \tau^{2}) \} - f$$

In summary,

$$r^{t+1} = r^t + a_m (\Delta \tau)^m \tag{34}$$

where

$$a_{1} = \ell_{v} [(\partial N^{v} / \phi^{t}) r^{t} + (\partial N^{v} / \partial \phi^{t}_{x}) (r^{t})_{x} + (\partial N^{v} / \partial \phi^{t}_{y}) (r^{t})_{y}]$$
(35)

and the coefficients of higher order terms a_2 , a_3 , a_4 , ... can be determined by direct Taylor series expansion. Equation (34) indicates that the residual at time level t+1 is a polynomial (hereinafter called residual polynomial [7] or RP) of the time step size. The total number of terms in the residual polynomial (34) depends on the degree of nonlinearity of the operator N^v.

If N^{ν} is polynomial in its arguments then the Taylor series truncates and becomes exact. Thus, the L₂ norm of the residual at time level t+1 can be expressed as

$$\|r^{t+1}\|^{2} = \|r^{t}\|^{2} + 2(r^{t}, a_{m})(\Delta \tau)^{m} + (a_{m}, a_{n})(\Delta \tau)^{m}(\Delta \tau)^{n} ; m, n \ge 1$$
(36)

Equation (36) implies that the residual norm at time step t+1 is a positive polynomial (hereinafter called minimizing polynomial [7] or MP) of the time step size (to be determined). Thus, the stability of scheme (29) will be guaranteed provided that $\Delta \tau$ is chosen as the optimizer of the minimizing polynomial (36) such that $\|r^{t+1}\|$ is an infimum (global minimum). However, the determination of the optimizer needs special numerical techniques [14]. The rate of convergence depends on the relative difficulty in finding the optimizer. To reduce this difficulty, the linearized operator of N^V may be applied. If N^V is truncated to the first order of $\Delta \tau$ (linearized operator), the approximate residual vector is

$$(r^{t+1}) = r^{t} + a_{1}\Delta \tau$$
 (37)

Then, the approximate MP is

$$\|r^{t+1}\|^{2} = \|r^{t}\|^{2} + 2(a_{1}, r^{t})\Delta\tau + (a_{1}, a_{1})(\Delta\tau)^{2}$$
(38)

The optimizer of the above equation can be easily found. It should be noted that equations (36) and (38) have the same, but negative slope at $\Delta \tau = 0$. Figures 3 and 4 give the best illustration for the effects of the linearization on the convergence rate.

A.3.2.4 The Generalized Nonlinear Minimum Residual Method

The GNLMR method actually is the application of the methods described in the previous sections. Let us consider the problems governed by equation (27) and assumme that M steps are used at each time level t. The multi-step algorithm for nonlinear problems is defined as

$$\phi^{t+1} = \phi^{t} + \omega_{m} \delta_{m} + O(\omega_{m}^{2}) ; m = 1 \sim M$$
 (39)

where repeated indices are summed. The residual at step m is defined as

$$\delta_{1} = \epsilon_{y} N^{v} (\phi^{t}, \phi^{t}_{x}, \phi^{t}_{y}) - f$$
(40)

$$\delta_{m} = \ell_{v} \left[(\partial N^{v} / \partial \phi^{t}) \delta_{m-1} + (\partial N^{v} / \partial \phi^{t}_{x}) (\delta_{m-1})_{x} + (\partial N^{v} / \partial \phi^{t}_{y}) (\delta_{m-1})_{y} \right]$$
(41)

The coefficients of the higher order terms of ω_m can be obtained by Taylor's series expansion. If only linear terms of ω_m are retained, the residual polynomial (RP) at time step t+1 can be expressed by Taylor's series expansion as

$$r^{t+1} = \epsilon_{v} N^{v} (\phi^{t+1}, \phi^{t+1}_{x}, \phi^{t+1}_{y}) - f$$

$$= \epsilon_{v} N^{v} [\phi^{t} + \omega_{m} \delta_{m}, \phi^{t}_{x} + \omega_{m} (\delta_{m})_{x}, \phi^{t}_{y} + \omega_{m} (\delta_{m})_{y}] - f$$

$$= r^{t} + \epsilon_{v} ([(\partial N^{v} / \partial \phi^{t}) \delta_{m} + (\partial N^{v} / \partial \phi^{t}_{x}) (\delta_{m})_{x} (\partial N^{v} / \partial \phi^{t}_{y}) (\delta_{m})_{y}] \omega_{m}$$

$$+ \tilde{\upsilon} (\omega_{m} / \tilde{J}) \qquad (42)$$

13.

Therefore, the minimizing polynomial (MP) at time step t+1 can be determined as

$$\|r^{t+1}\|^2 = \|r^t\|^2 + g(\omega_m)$$
(43)

where $g(\omega_m)$ is a polynomial in ω_m . For a highly nonlinear differential equation, g will be a complicated multi-variable polynomial that depends on the steps we used and the degree of the nonlinearity of the differential operator N^{ν}. Thus, a fast and accurate method to determine the optimizer of MP is required for the GNLMR method to guarantee the highest rate of convergence. If the linearized operator of N^{ν} is applied to reduce the difficulty of finding the global minimum, the approximate optimizer of (43) can be determined by the method described in Section 2.2.

Since the coefficients in the MP are obtained by integrating the residuals over the whole domain, the GNLMR method requires a large amount of computer storage to save the residuals from each step m. This is also the common problem for all the conjugate-gradient type methods [12]. For new generation of supercomputers storage may not cause too much problem [12]. However, if storage restriction does exist, an integration by sampling could be considered. Nevertheless, several problems accompany this idea [13]. Since a statistical sampling procedure can be used to get the random data for integration, the question of error incurred by the sampling should be addressed. If the error caused by sampling approximation can be determined, it should be possible to design an optimal sampling procedure to minimize the error.

الأسكنية مستعلمه الم

The problem of finding the global minimum (infimum) or the global maximum (supremum) for a function of several variables is a basic problem in global optimization theory. In the GNLMR method, the optimal relaxation factors are actually the optimizer of the MP. The relative difficulty to find the optimizer depends on the degree of non-linearity of the governing differential equations and the steps we used for the multi-step algorithm. As pointed out by H. Ratschek and J. Rokne [14], interval method is the only among all the existing methods that guarantee always the location of the global extremum with arbitrary accuracy. Since the interval method is basically iterative, it will require considerable computer time to get the accurate result for a multi-variable polynomial of higher order. The highest rate of convergence of GNLMR method will be guaranteed if the optimizer of MP can be efficiently determined.

Since boundary conditions can be applied exactly in the regions that are neighboring to the boundary, it is obvious that during the process of relaxation, the iterative solutions in those region are more accurate than the regions that are far away from the boundary. This implies that the relaxation factor should vary from one subregion to another, or even from point to point since the subregions or points where residuals are large definitely need more correction.

A.3.3 Numerical Examples

Two numerical test cases are used to demonstrate the applications of the GNLMR method : one-dimensional Burgers's equation and two-dimensional heat conduction equation. Both test cases were computed using non-accelerated method where time step size satisfies the CFL limitation. In addition, three accelerated computations were performed with M=1, 2, 3 where M is the number of steps used in the multi-step algorithm. It should be pointed out that when applying the GNLMR method, it is not necessary to specify the time step to obtain the residuals at each step. However, in order to compare the relative speed of convergence between the GNLMR method and the non-accelerated method, a time step size that satisfies the CFL limitation is used in calculating the residual at each step for both cases. Moreover, the effect of linearization to the rate of convergence is investigated by solving both exact and approximate MPs for M=1 in the case of Burgers's equation. Comparisons are based on the accuracy of the solution and the actual computer time required.

A.3.3.1 Burgers' Equation

According to the notations defined in the Section 2, the one-dimensional, viscous Burgers' equation can be written as

$$\partial \phi / \partial \tau = L_X N(\phi, \phi_X)$$

 $N(\phi, \phi_y) = -\phi^2/2 + v\phi_X$ (44)

and v is the viscosity coefficient. In this example, v = 0.07 is used. The initial and the boundary conditions are chosen as follows

$$\phi(1, \tau) = 0$$

 $\phi(0, \tau) = 1$ (45)
 $\phi(x, 0) = 1-x$

The FTCS scheme is applied to discretize equation (44) as

where

$$\phi^{t+1} = \phi^{t} + \Delta \tau \{-[(\phi^{t}_{i+1})^{2} - (\phi^{t}_{i-1})^{2}]/4\Delta x + v(\phi^{t}_{i+1} - 2\phi^{t}_{i} + \phi^{t}_{i-1})/\Delta x^{2}\}$$
(46)

where i denotes the ith grid point in the total of 41. The exact RP for M=1 can be expressed as

$$RP = r^{t+1} = r^{t} + a_{1}\Delta\tau + a_{2}(\Delta\tau)^{2}$$
(47)

where

$$a_{1} = \frac{\partial}{\partial x} (-\phi^{t} r^{t} + v r^{t}_{x})$$

$$a_{2} = -0.5 \frac{\partial}{\partial x} (r^{t})^{2}$$
(48)

The optimal value of $\Delta\tau$ is chosen as the optimizer of the exact MP

$$MP = \|r^{t+1}\|^2 = A_0 + A_1 \Delta \tau + A_2 (\Delta \tau)^2 + A_3 (\Delta \tau)^3 + A_4 (\Delta \tau)^4$$
(49)

where

$$A_{0} = ||r^{t}||^{2} , \quad A_{1} = 2(r^{t}, a_{1})$$

$$A_{2} = (a_{1}, a_{1}) + 2(r^{t}, a_{2})$$

$$A_{3} = 2(a_{1}, a_{2}) , \quad A_{4} = (a_{2}, a_{2})$$
(50)

If linearized operator of N and M steps are used, the residual polynomial is truncated up to its first order as

$$RP = r^{t+1} = r^t + a_m \omega_m$$

where

$$a_{m} = \partial/\partial x \left[-\phi^{t} \delta_{m} + v(\delta_{m})_{x}\right]$$
 (51)

and δ_m can be determined from equations (40)-(41).

The minimizing polynomial MP is then

$$MP = \|r^{t+1}\|^2 = \|r^t\|^2 + 2(r^t, a_m)\omega_m + (a_m, a_n)\omega_m\omega_n$$

Thus, the optimal relaxations ω_m can be easily determined by solving the following system of linear equations.

$$A_{mn}\omega_n = b_m$$

where

$$A_{mn} = (a_m, a_n)$$

$$b_m = -(r^t, a_m)$$
(52)

and A_{mn} is a symmetric matrix of order M.

Figure 1 shows the exact steady state solution and the numerical solutions after 100 iterations. It is obvious that the GNLMR method gives the most accurate results. The computer time costs of 100 iterations for each case are shown in figure 2. It indicates that the GNLMR method needs more computer time per iteration. This depends on the number of steps that were used in the multi-step algorithm and whether a linearized or exact MP was solved. However, if a desired accuracy is specified, the GNLMR method needs fewer iterations to achieve the accuracy requirement as shown in figure 3. Therefore, the overall judgement of the efficiency of the GNLMR method should be based on the computer time rather than number of iterations required to obtain a solution with a specified ac-Figure 4 does prove the efficiency gained by using the GNLMR curacy. method. The variations of the relaxation factors with respect to time (or iteration) show that a sudden change in their magnitudes occurred just before converged solution is reached as shown in figures 5, 6 and 7. It is interesting to note that all the relaxation factors reduce to zero as converged solution is obtained. Since the relaxation factor is equivalent to the time step size in our formulations, this phenomena can be interpreted as that the time marching will stop once the steady state solution is obtained. This provides an alternative criteria for stopping the iterative process in the GNLMR method.

It must be mentioned that according to figures 3 and 4, both the rate of convergence and smoothness of convergence of the NLMR method can be improved even further by the multi-step algorithm. Moreover, figures 3 and 4 show a peculiarity that during the first few tens of iterations solution converges very slowly and then suddenly accelerate to its maximum rate. The converged solution is then reached almost immediately following the maximum rate interval. This behavior is entirely different for linear problems as mentioned by Marchuk [6]. For a positive definite matrix (a linear operator), the convergence rate during the initial iterations is much higher than the asymptotic rate of convergence if the method of minimum residual is applied. Hence, in practice it is not necessary to solve the exact MP for a nonlinear problem; the linearized MP can be used and still guarantee a high rate of convergence as shown in figures 2, 3 and 4.

A.3.3.2 The Heat Conduction Equation

The unsteady heat conduction equation is given by

$$\partial \phi / \partial \tau = L \phi$$
, $L = \alpha (\partial^2 / \partial x^2 + \partial^2 / \partial y^2)$ (53)

where α is the thermal diffusivity.

A rectangular uniform grid having 21x21 grid points was used for this example. The initial and boundary conditions are as follows

$$\phi(x, y, 0) = 100$$

$$\phi(0, y, \tau) = 100 \times COS(2\pi y/H) , \quad \phi(W, y, \tau) = 100 \quad (54)$$

$$\phi(x, 0, \tau) = 100 , \quad \phi(x, H, \tau) = 100$$

Applying FTCS scheme, equation (53) discretizes into

$$\phi^{t+1} = \phi^t + \Delta \tau r^t$$

where

$$r^{t} = \alpha [(\phi^{t}_{i+1,j} - 2\phi^{t}_{i,j} + \phi^{t}_{i-1,j})/\Delta x^{2}]$$
$$(\phi^{t}_{i,j+1} - 2\phi^{t}_{i,j} + \phi^{t}_{i,j-1})/\Delta y^{2} + (55)$$

Here i,j denote the grid point at ($i\Delta x$, $j\Delta y$) The residual polynomial is given by equation (21) as

$$r^{t+1} = r^t + \omega_m^{\ell \delta} m$$

The minimizing polynomial is given by equation (23) as

$$MP = \|r^{t+1}\|^2 = \|r^t\|^2 + 2(r^t, \ell \delta_m)\omega_m + (\ell \delta_m, \ell \delta_n)\omega_m\omega_n$$

The optimal relaxation factors ω_m are the solution of the following linear system of equations.

 $A_{mn}\omega_n = b_m$

where

$$A_{mn} = (\ell \delta_{m}, \ell \delta_{n})$$

$$b_{m} = -(r^{t}, \ell \delta_{m})$$
(56)



and A_{mn} is a symmetric matrix of order M.

The numerical results are summarized by figures 8 to 13. As indicated in figure 8, the computer time required per iteration for the GNLMR method is longer than for the non-accelerated method. However, figure 9 shows that if the maximum number of iterations is limited to 80, the accuracy that can be obtained by the GNLMR method is better than that of the non-accelerated method. If a fixed computer time is specified, figure 10 clearly shows that the GNLMR method will produce the best solution. Figures 11 to 13 show the variations of the optimal relaxation factors versus number of iterations. Figures 9 and 10 confirm that using the multi-step algorithm improves both the smoothness and the rate of convergence for the NLMR method. If the GNLMR method is applied to a linear problem, it is interesting to note that the rate of convergence during the initial few iterations is much higher than the asymptotic rate of convergence as indicated by figures 9 and 10.

It should be pointed out that the linear version of the GNLMR method is similar to the generalized minimum residual GMRES method developed by Saad and Schultz [15] to solve non-symmetric linear systems of equations. This method was recently modified by Wigton et. al. [12] to solve non-linear problems in gas dynamics using Newton's iteration method. Since Gram-Schmidt orthogonalization procedures are applied to orthogonalize the search directions at each iteration in the GMRES method, this method demands a large number of arithmetic operations and a large computer memory. Moreover, as pointed out by Marchuk [6], the implementation of the orthogonalization algorithm with respect to high-order matrices usually results after a few tens of iterations in a numerical instability because of nonlinearity. This implies that the maximum number

~ 1

of steps which can be used in one iteration for the multi-step algorithm is practically limited to a moderate finite number.

A.3.4 Conclusion Remarks

The GNLMR method and its applications were presented. The accelerating mechanism and the monotone convergence behavior of the GNLMR method has been proved by theoretical studies and the numerical experiments. It was found that both the rate and the smoothness of convergence of the NLMR method can be improved even further by the optimized multi-step algorithm. Both numerical test cases confirmed that all the optimal relaxation factors vanish as converged solution is achieved thus providing a new stopping criteria for the iterative process. The numerical results also proved that linearization of a nonlinear operator in the GNLMR method reduces the problems of determining the optimizer of the MP. This linearization still guarantees a high rate of convergence. Hence, the GNLMR method can be simplified in practical problems when iteratively solving nonlinear partial differential equations.

A.3.5 References

- Moretti, G. and M. Abbett, "A Time-Dependent Computational Method for Blunt Body Flows", AIAA J. Vol. 4, No. 12, 1966, pp. 2136-2141.
- Ni, Ron-Ho, "A Multiple-Grid Scheme for Solving the Euler Equations", AIAA J. vol. 20, NO. 11, 1981, pp. 1565-1571.
- MacCormack, R. W., "Current Status of Numerical Solutions of the Navier-Stokes Equations", AIAA Paper 85-0032, January 1985.
- Shang, J. S. and Scherr, S. J., "Navier-Stokes Solution of the Flows Field Around a Complete Aircraft", AIAA Paper 85-1509, July 1985.
- Garabedian, P. R., "Estimation of the Relaxation Factor for Small Mesh Size", Mathematical Tables and Other Aids to Computation, Vol. 10, 1956.
- Marchuk, G. I., <u>Method of Numerical Mathematics</u>, 2nd ed., Spring-Verlog, New York, 1982.
- Kennon, S. R., <u>Novel Approaches to Grid Generation, Inverse Design</u> <u>and Acceleration of Iterative Schemes</u> Master Thesis, Department of Aerospace Engineering and Engineering Mechanics, The University of Texas at Austin, 1984.
- Kennon, S. R., "Optimal Acceleration Factors for Iterative Solution of Linear and Nonlinear Differential Systems", AIAA Paper 85-0162, January 1985.
- Kennon, S. R., "Optimal Acceleration Factors for Iterative Solution of Linear and Nonlinear Differential Systems", Computer Methods in Applied Mechanics and Engineering, 47 (1984) 357-367, North-Holland.
- Thompson, H. Doyle, Webb, B. W. and Hoffman, J. D., "The Cell Reynolds Number Myth", International Journal for Numerical Methods in Fluids, Vol. 5, 305-310 (1985).

- 11. Richtmyer, R. D. and Morton, K. W., <u>Difference Methods for</u> <u>Initial-Value Problems</u>, 2nd ed., Interscience Publishers, New York, 1967.
- 12. Wigton, L. B., Yu, N. J. and Young, D. P., "GMRES Acceleration of Computayional Fluid Dynamics Codes", AIAA Paper 85-1494, July 1985.
- Davis, P. F. and Rabinowitz, P., <u>Methods of Numerical Integration</u>, 2nd ed., Academic Press, Inc. 1984.
- 14. Ratschek, H. and Rokne, J., <u>Computer Methods for the Range of Func-</u> <u>tions</u>, Ellis Horwood Ltd., England, 1984.
- 15. Saad, Y and Schultz, M. H., "GMRES: A Generalized Minimal Residual Algorithm for Solving Nonsymmetric Linear Systems", Research Report YALEU/DCS/RR-254, August 24, 1983.



Figure 1. Exact and Numerical Solutions of Burgers's Equation



Figure 2. Computer Time Versus Number of Iterations



Figure 3. Number of Iteration Versus the Residual Norm



Figure 4. Computer Time Versus the Residual Norm



Figure 5. Number of Iteration Versus Optimal Relaxation Factor(ω 1)



Figure 6. Number of Iteration Versus Optimal Relaxation Factors



Figure 7. Number of Iteration Versus Optimal Relaxation Factors



Figure 8. Computer Time Versus Number of Iterations

È



Figure 9. Number of Iteration Versus the Residual Norm



Figure 10. Computer Time Versus the Residual Norm



Figure 11. Number of Iteration Versus Optimal Relaxation Factor(ω 1)



B

.

Figure 12. Number of Iteration Versus Optimal Relaxation Factors



Figure 13. Number of Iteration Versus Optimal Relaxation Factors

A.4 List of Publications

- Kennon, S. R. and Dulikravich , G. S., "Optimal Acceleration Factors for Iterative Solution of Linear and Nonlinear Differential Systems", Computer Methods in Applied Mechanics and Engineering, 47, (1984), pp. 357-367.
- Kennon, S. R., "Optimal Acceleration Factors for Iterative Solution of Linear and Nonlinear Differential Systems", AIAA Paper 85-0162, January 1985.
- Kennon, S. R., Jespersen, D. C. and Dulikravich, G. S., "Direct Solution of Polynomial Systems of Equations with Applications to Euler Equations", AIAA Paper 86-0554, January 1986.
- 4. Huang, C. Y., Kennon, S. R. and Dulikravich, G. S., "Generalized Non-Linear Minimal Residual (GNLMR) Method for Iterative Algorithms", submitted to the Journal of Computational and Applied Mathematics.

A.5 List of Professional Personnel

Dr. George S. Dulikravich --- Assistant Professor, ASE/EM Department Stephen R. Kennon --- Ph.D Candidate in ASE/EM Department Chung-Yuan Huang --- Ph.D Candidate in ASE/EM Department

A.6 Interactions (Coupling Activities)

Papers presented at technical meetings :

 "Optimal Acceleration Factors for Iterative Solution of Linear and Non-Linear Differential Systems" by S. R. Kennon has been presented at the AIAA 23rd Aerospace Sciences Meeting, Reno, Nevada, January 14-17, 1985. "Direct Solution of Polynomial Systems of Equations With Applications to Euler Equations", will be presented by S. R. Kennon at AIAA 24th Aerospace Sciences Meeting, Reno, Nevada, January 6-9, 1986.

Consultative and Advisory Functions :

Dr. G. S. Dulikravich delivered the following invited lectures that included the optimal acceleration factor theory :

- -- Mech. Eng. Dept., U. of California, Davis, CA, Jan. 1985.
- -- Mech. Eng. Dept., Rice Univ., Houston, TX, Jan. 1985.
- -- General Electric Co., Evandale, OH, April 1985.
- -- Aerospace Eng. Dept., U. of Texas, Arlington, TX, May 1985.
- -- Mech. Eng. Dept., Old Dominion Univ., Norfolk, VA, May 1985
- -- Allison Gas Turbines, Indianapolis, IN, July 1985.
- -- Mech. Eng. Dept., U. of Texas, Austin, TX, Oct. 1985.
- -- Aerospace Eng. Dept., Pennsylvania State U., Univ. Park, PA, Nov. 1985.
- -- Mech. Eng. and Material Sciences Dept., Duke U., Durham, NC, Dec. 1985.

Mr. S. R. Kennon delivered the following invited lectures that included the optimal acceleration factor theory :

- -- Dept. of Mathematics, U. of Texas, Austin, TX, March 1985.
- -- Computational Fluid Dynamics Branch, NASA Ames Research Center, Field, CA, August 1985.
- -- Computational Aerodynamics Branch, Lockheed California Co., Burbank, CA, August 1985.

A mini-grant was obtained from the Computational Fluid Dynamics Branch at NASA Ames Research Center (\$7,000 + 5 hours of CRAY X-MP computer time) that gave an opportunity to Mr. S. R. Kennon to visit there last summer for six weeks and to develop the basic algorithm for his latest AIAA paper on polynomial systems of equations for fast iterative algorithms.

A.7 New Discoveries, Inventions or Patent Disclosures No contribution.

A.8 Additional Information for Evaluation of the Progress

Work in progress is oriented towards accelerating implicit iterative methods for the Euler and Navier-Stokes equations of gasdynamics. Future work will include (a) accelerating the solution of the Euler and Navier-Stokes equations and (b) further exploitation of the polynomial properties of the Euler and Navier-Stokes equations by applying classical algebraic polynomial elimination theory.

The immediate task is an application of the generalized non-linear minimal residual method to the finite-volume Runge-Kutta time-stepping scheme of Jameson. This scheme uses multiple time steps that are presently limited by the linear stability analysis. It is expected that our method of multiple optimal acceleration factors can accelerate this popular scheme and enhance its stability. B. Report of the Group Headed by Dr. D.M. Young, Jr.

B.1 Abstract

A composite adaptive procedure, based on the use of variational techniques, has been developed for the automatic determination of splitting parameters for accelerated iterative procedures. Examples include the symmetric SOR method and the shifted incomplete Cholesky method, each with conjugate gradient acceleration.

B.2 Research Objectives and the Statement of Work

Mr. Mai, working with Professor Young, has been developing and testing "composite" adaptive procedures for speeding up the convergence of certain iterative algorithms for solving large sparse linear systems of the type arising in the numerical solution of partial differential equations. The iterative algorithms considered include a basic iterative method combined with the acceleration procedure, such as Chebyshev acceleration or conjugate gradient acceleration. The effective application of these algorithms may require the choice of "splitting parameters" associated with the acceleration procedure.

In the past these parameters have been determined adaptively, but the determination of the splitting parameters has been done separately from the determination of the acceleration parameters. A "composite" adaptive procedure is designed to determine both sets of parameters simultaneously. The procedures used are based on the application of certain variational principles combined with the solution of certain nonlinear optimization problems. Preliminary testing has been done on generalized conjugate gradient acceleration procedures applied to the symmetric suc-

B.6 Interactions (Coupling Activities)

Ľ

It is planned to describe the work in a paper to be presented at the International Conference on Vector and Parallel Computing, Leon, Norway, June 2-6, 1986.

- B.7 New Discoveries, Inventions and Patent Disclosures No contribution
- B.8 Additional Information for Evaluation of the Progress No contribution

			ANA 14	0111	-		
CURITY CLASSIFICATION OF THIS PAGE							
	REPORT DOCUME	INTATION PAGE					
1. REPORT SECURITY CLASSIFICATION		16. RESTRICTIVE M	ARKINGS				
ANCLASSIFIED		3. DISTRIBUTION/AVAILABILITY OF REPORT					
		Approved for public release; distribution					
20. DECLASSIFICATION/DOWNGRADING SCHED	ULE	unlimited.					
4. PERFORMING ORGANIZATION REPORT NUM	BER(S)	5. MONITORING ORGANIZATION REPORT NUMBERISI AFOSR - TR - 86 - 0221					
64 NAME OF PERFORMING ORGANIZATION	BD. OFFICE SYMBOL	74. NAME OF MONIT	ORING ORGANI	ZATION			
The University of Texas at Austin	(II applicable)	Air Force Office of Scientific Research			earch		
6c. ADDRESS (City, State and ZIP Code)		76. ADDRESS (City.	State and ZIP Cod	e)			
Dept. of Aerospace Eng. & Eng. 1	Mechanics	Directorate	of Mathema	tical & Info	rmation		
Ine University of Texas at Aust Austin, Texas 78712-1085	in	Sciences, Bo	IIING AFB 1	UC 20332			
AL NAME OF FUNDING/SPONSORING	Bb. OFFICE SYMBOL	9. PROCUREMENT	NSTRUMENT ID	ENTIFICATION NU	MBER		
AFOSR	NM	17000	5 0050		ť		
ADDRESS (City, State and ZIP Code)		AFUSK-8	<u>2-0052</u>				
		PROGRAM	PROJECT	TASK	WORK UNIT		
Bolling AFB DC 20332		ELEMENT NO.	2304	NO. A3	NO.		
11. TITLE (Include Security Classification) OPTIMIM ACCELERATION FACTORS FOR		TIONS OF LINE					
12. PERSONAL AUTHORIS)	A TIERATIVE SOLU	TIONS OF LINE	AK AND NON-	LINEAR SYST	CMS		
Dr. George S. Dulikrav	ich						
13 TYPE OF REPORT 13b. TIME CO	DVERED	14. DATE OF REPOI	T (Yr., No., Dey)	15. PAGE CO	DUNT		
16. SUPPLEMENTARY NOTATION		1909	· //L	43			
17 COSATI CODES	18. SUBJECT TERMS (C	ontinue on reverse if no	tcessery and identi	fy by block number	,		
FIELD GROUP SUB. GR							
19. ABSTRACT Co A generalized	non-linear min	imal residual	(GNLMR) m	ethod based	07		
	annual and a						
the time-dependent	approach and mu	ilti~step algo	rithm has	been develop	ped		
to accelerate itera	ative methods f	or solving li	near and no	n-linear pro	-do		
lems. Both theor	etical studies	and numerica	l experime	ents show t	the		
monotone convergenc	e behavior of t	he GNLMR moth	nd. It te	found that	he		
rate of convergence	e and the smo	athness of a	10 13	for the state			
			ouvergence	for iterati	94		
methods can be impr	oved by the opt	imized multi-	step algori	thm.			
20. DISTRIBUTION AVAILABILITY OF ABSTRA	.T	21. ABSTRACT SEC	URITY CLASSIFI	CATION			
UNCLASSIFIED. LINLIMITED T SAME AS APT	UNGLACCIPIED						
22. NAME OF RESPONSIBLE INDIVIDUAL	226. TELEPHONE NUMBER 226. OFFICE SYMBOL						
Captain John P. Thomas		(Include Area Co (202) 767-50	26	IM			
DO FORM 1473 83 APR	EDITION OF 1 JAN 22						

ſ

-

1

<u>} - 1</u>

EDITION OF 1 JAN 73 IS OBSOLETE.

UNCLASSIFIED UNCLASSIFIED

