

AD-A167 222

PUBLIC WORKS CENTER GUAM FLEET MOORINGS UNDERWATER  
INSPECTION REPORT(U) NAVAL FACILITIES ENGINEERING  
COMMAND WASHINGTON DC CHESAPEAKE DIV SEP 83


1/1


UNCLASSIFIED

CHES/NAVFAC-FPO-1-83(32)

F/G 13/2

NL





MICROCOPY

CHART

FPO  
8332



AD-A167 222

NTIC FILE COPY

DTIC  
ELECTE  
APR 3 0 1986  
S D  
D

**PUBLIC WORKS  
CENTER  
GUAM  
FLEET MOORINGS  
UNDERWATER  
INSPECTION  
REPORT**

**DISTRIBUTION STATEMENT A**

Approved for public release;  
Distribution Unlimited

**SEPTEMBER 1983**

OCEAN ENGINEERING  
AND CONSTRUCTION PROJECT OFFICE  
CHESAPEAKE DIVISION  
NAVAL FACILITIES ENGINEERING COMMAND  
WASHINGTON, D.C. 20374

FPO-1-83 (32)

\*Original contains color  
plates: All DTIC reproductions  
will be in black and  
white\*

86 4 22 064

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

AD-A167222

1a. REPORT SECURITY CLASSIFICATION  
Unclassified

1b. RESTRICTIVE MARKINGS

2a. SECURITY CLASSIFICATION AUTHORITY

3. DISTRIBUTION AVAILABILITY OF REP.  
Approved for public release;  
distribution is unlimited

2b. DECLASSIFICATION/DOWNGRADING SCHEDULE

4. PERFORMING ORGANIZATION REPORT NUMBER  
FPO-1-83(32)

5. MONITORING ORGANIZATION REPORT #

6a. NAME OF PERFORM. ORG. 6b. OFFICE SYM  
Ocean Engineering  
& Construction  
Project Office  
CHESNAVFACENGCOM

7a. NAME OF MONITORING ORGANIZATION

6c. ADDRESS (City, State, and Zip Code)  
BLDG. 212, Washington Navy Yard  
Washington, D.C. 20374-2121

7b. ADDRESS (City, State, and Zip )

8a. NAME OF FUNDING ORG. 8b. OFFICE SYM

9. PROCUREMENT INSTRUMENT INDENT #

8c. ADDRESS (City, State & Zip)

10. SOURCE OF FUNDING NUMBERS

PROGRAM	PROJECT	TASK	WORK UNIT
ELEMENT #	#	#	ACCESS #

11. TITLE (Including Security Classification)

Public Works Center Guam Fleet Moorings Underwater Inspection Report

12. PERSONAL AUTHOR(S)

13a. TYPE OF REPORT

13b. TIME COVERED  
FROM TO

14. DATE OF REP. (YYMMDD)  
83-09

15. PAGES  
72

16. SUPPLEMENTARY NOTATION

17. COSATI CODES  
FIELD GROUP SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if nec.)  
Mooring inspection, Underwater inspection,  
Fleet moorings, Public Works Center Guam

19. ABSTRACT (Continue on reverse if necessary & identify by block number)  
This report contains results of the inspection of 22 fleet moorings operated and maintained by the Public Works Center, Guam. A CHESNAVFACENGCOM-assigned Engineer-in-Charge and divers from Underwater Construction Team Two conducted the inspection from 6-14 June 1983. (Con't)

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT  
SAME AS RPT.

21. ABSTRACT SECURITY CLASSIFICATION

22a. NAME OF RESPONSIBLE INDIVIDUAL  
Jacqueline B. Riley  
DD FORM 1473, 84MAR

22b. TELEPHONE 22c. OFFICE SYMBOL  
202-433-3881

SECURITY CLASSIFICATION OF THIS PAGE

BLOCK 19 (Con't)

Of the 22 moorings inspected, 19 were found to be in satisfactory condition, and 3 were found to be in fair condition with 1 of these recommended for overhaul. Specific comments concerning each of these moorings and recommendations for future actions are included in this report.

### Abstract

This report contains results of the inspection of 22 fleet moorings operated and maintained by the Public Works Center, Guam. A CHESNAVFACENGCOM-assigned Engineer-in-Charge and divers from Underwater Construction Team Two conducted the inspection from 6-14 June 1983.

➤ Of the 22 moorings inspected, 19 were found to be in satisfactory condition, and 3 were found to be in fair condition with 1 of these recommended for overhaul. Specific comments concerning each of these moorings and recommendations for future actions are included within this report.

## TABLE OF CONTENTS

Paragraph		Page
	ABSTRACT.....	i
1.0	INTRODUCTION .....	1
1.1	Background .....	1
1.2	General Mooring History .....	1
2.0	INSPECTION PROCEDURES .....	1
2.1	Inspection Objectives .....	1
2.2	Buoy .....	6
2.3	Riser .....	6
2.4	Ground Ring .....	6
2.5	Ground Legs .....	6
2.6	Anchors .....	9
3.0	INSPECTION SUMMARY .....	9
4.0	MOORING INSPECTION COMMENTS AND RECOMMENDATIONS .....	11
Annex		
A	FLEET MOORING INSPECTION RESULTS .....	A-1
B	PHOTOGRAPHS .....	B-1
C	REFERENCES .....	C-1

Accession For	
NTIS	<input checked="" type="checkbox"/>
CRA&I	<input type="checkbox"/>
DTIC	<input type="checkbox"/>
TAB	<input type="checkbox"/>
Unannounced	
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail a d / or Special
A-1	



## PWC GUAM FLEET MOORINGS INSPECTION REPORT

### 1.0 INTRODUCTION

1.1 Background. Under the COMNAVFACENGCOM Fleet Mooring Maintenance (FMM) Program, CHESNAVFACENGCOM has been assigned the responsibility to plan and conduct periodic diver inspections of all fleet moorings worldwide. In carrying out this responsibility, CHESNAVFACENGCOM designated an Engineer-in-Charge (EIC) to provide inspection planning and onsite technical direction for the underwater inspection of fleet moorings located in Apra Harbor near the Public Works Center Guam. The actual underwater portion of the inspection was performed by divers of Underwater Construction Team Two (UCT TWO). The inspection was conducted 6-14 June 1983.

1.2 General Mooring History. PWC Guam currently operates and maintains 22 fleet moorings. They consist of one AA-, one CC-, one A-, thirteen B-, five D-, and one E-class moorings. Figure 1 shows the overall geographic positions of these moorings located in Apra Harbor, Guam, while Figures 2 and 3 are enlargements of portions of Apra Harbor and show the positions of the fleet moorings located in the outer and inner harbors, respectively.


The latest maintenance data summary concerning these moorings was prepared by PWC Guam in April 1983. Table I is a copy of this summary.

### 2.0 INSPECTION PROCEDURES

2.1 Inspection Objectives. ↓ The purpose of the mooring inspections was to determine the general physical condition of the buoys and chain assemblies and, when possible, to verify or update existing as-built and maintenance records. Divers inspected only a portion of the submerged buoy hull and chain assemblies in order to compile a general description of the mooring's condition. The existence of fairly consistent measurements during this inspection provides a good indication of the mooring's overall condition. It should be kept in mind that periodic underwater inspections are intended as an expedient and relatively inexpensive supplement to accurate maintenance records. As such, they cannot fully substitute for a complete inspection involving recovery of the mooring and the measurement and evaluation of each component.







PWC GUAM FLEET MOORINGS LOCATIONS






FIGURE 2. OUTER HARBOR MOORING LOCATIONS




FIGURE 3. INNER HARBOR  
MOORING LOCATIONS

**LEGEND**

CORAL

**TABLE 1**  
**PWC GUAM FLEET MOORINGS**

Mooring Number	Mooring Class	Water Depth (Ft)	Date Installed	Date Last Overhaul	Reported Condition	Date Next Overhaul	Type Ships Moored
951	AAT	130	12/59	6/82	FAIR	6/88	AS-19
701	BR	125	4/59	1/81	GOOD	1/86	AFS-7
702	AR	150	6/57	2/82	GOOD	2/85	AFDL-21
703	BR	140	6/57	2/82	GOOD	2/87	-
704	ER	125	10/69	1973	POOR	4/84	-
501	BR	160	7/57	3/82	GOOD	3/87	-
25W	BR	36	4/53	2/81	GOOD	2/86	22 Cape Class
25E	BR	36	4/53	2/81	GOOD	2/86	YTB
26E	BR	32	9/53	3/82	GOOD	3/87	YTB
26W	BR	32	9/53	3/82	GOOD	3/87	SWOB
27E	BR	37	9/53	4/82	GOOD	4/87	-
27W	BR	32	9/53	4/82	GOOD	4/87	30 Balsam Class
28E	BR	36	9/53	9/82	GOOD	9/87	YFN, YC
28W	BR	36	9/53	9/82	GOOD	9/87	YPD
22	BR	70	9/53	8/82	GOOD	8/87	YON
22/23	BR	58	9/53	8/82	GOOD	8/87	-
12/13	DR	105	-	7/82	GOOD	7/87	-
13	DR	97	-	7/82	GOOD	7/87	-
14	DR	97	10/53	6/82	GOOD	6/87	YC
15/16	DR	97	10/53	9/82	GOOD	9/87	YTB
17	DR	69	9/53	5/82	GOOD	5/87	YON

NOTE: Mooring historical data provided by PWC GUAM, April 1983.

Chain wire diameter measurements are used to evaluate the condition of a mooring. After cleaning to bare metal, a selective sampling of the wire diameter of chain links and connecting hardware was taken in order to determine the amount of deterioration due to corrosion and wear. "Single link" measurements were taken where chain was slack to detect corrosion loss. "Double link" measurements were taken where two links connected under tension to detect the combined effects of corrosion and wear. Chain links and other components which measured 90 percent or greater of original wire diameter are considered to be in "good" condition; measurement between 80 percent and 90 percent of original diameter is considered "fair" condition and is cause for the mooring to be downgraded in classification; any measurement less than 80 percent is considered "poor" and is cause for the mooring to be declared unsatisfactory for fleet use.

Standard underwater inspection procedures do not call for the inspection of any part of the mooring which has been buried or which is below a water depth of 130 feet if scuba gear is used. Ground legs and risers were observed only to the point at which they became buried; no attempt was made to locate and inspect anchors or other mooring materials which were not readily visible. For clarification, schematic drawings of typical riser and telephone type moorings are shown in Figures 4 and 5 respectively.

## 2.2 Buoy.

2.2.1 Buoy Topside. Each buoy was inspected to determine its general condition. The buoy markings were checked for conformance to those noted in applicable charts. Physical damage such as holes, dents, or listing was described. The fiberglass was inspected for cracks, wear, peeling, or rust-bleeding. Hatches, openings, and penetrations were examined and worn material and rust were reported.

The buoy fenders and chafing rails were checked for integrity and secure connection to the buoy. Buoy top jewelry was measured with calipers to find the overall outside dimensions and areas of most severe reduction in wire size.

2.2.2 Buoy Lower Portion. Divers inspected the buoy below the waterline. The thickness of marine growth was recorded, 1-foot-square areas were selected and cleared of growth without damaging the fiberglass, and the condition of the fiberglass was noted.

2.3 Riser. To determine chain wear, each riser chain was inspected by taking three consecutive double link measurements, using precut gauges and/or calipers, at both ends and at the center of the riser. To determine original chain size, divers took single link caliper measurements of the wire diameter. Divers also documented the type of hardware connecting the riser chain to the sinker.

2.4 Ground Ring. When visible, the ground ring was examined for general and localized wear. Caliper measurements were made of the wire size in the region of most severe wear and across the inner diameter.

2.5 Ground Legs. To determine chain wear, three consecutive double link measurements were made at both ends and at the center of each leg until the chain was




FIGURE 4. TYPICAL RISER-TYPE MOORING






FIGURE 5. TYPICAL TELEPHONE-TYPE MOORING

buried in the seafloor. Where a segment of chain was resting on the bottom and was not in tension, single link measurements were taken instead of double link measurements. To determine original chain size, divers took single link caliper measurements of its wire diameter.

2.6 Anchors. No anchors were sighted during the course of the inspection.

### 3.0 INSPECTION SUMMARY

An in-depth discussion of the inspection results is presented in Annex A. Annex B contains photographs, and Annex C contains a copy of the preliminary report of the results of the inspection.

The data gathered during the inspection indicates the following:

- o Of the 22 moorings inspected, 20 are in satisfactory condition for continued use at their current mooring classification level. Although usable, the other two require some maintenance rework. Table I presents the status of the PWC Guam fleet moorings.
- o The riser chain of Mooring 704 is badly pitted and its buoy is in need of repairs.
- o Although its components and assemblies are in good condition, the riser chain of Mooring 22 is entwined with about 40 feet of extraneous 2-inch wire rope.
- o The material condition of Mooring 12/13 is good, but the orientation of its ground legs is questionable. Magnetic bearings of these three legs from the ground ring were found to be 029, 031, and 215 degrees.
- o The top jewelry of Mooring 17 includes a shackle with a measured wire diameter of 1 1/2 inches. This is undersized for a class D mooring, which requires the wire size of all components to be a minimum of 2 inches.
- o Buoy 28E is badly rusted, has a bent and rusted chafing rail, and has sustained some collision damage.

TABLE I

## INSPECTION SUMMARY

MOORING NUMBER	MOORING CLASS	CONDITION			REMARKS
		GOOD	FAIR	POOR	
EC-2	CCR (MOD)	✓			Oversize riser chain (2 3/4-inch) Riser badly pitted. Mooring needs to be overhauled.
951	AAT	✓			
701	BR	✓			
704	ER		✓		
702	AR	✓			Riser only inspected to a depth of 100 feet
703	BR	✓			
22	BR	✓			About 40 feet of 2-inch wire rope is entwined with riser chain
22/23	BR	✓			Riser only inspected to a depth of 100 feet
501	BR	✓			
25E	BR	✓			Buoy has a 2-foot-wide, 2-inch-deep dent in hull
25W	BR	✓			
26E	BR	✓			
26W	BR	✓			
27E	BR	✓			
27W	BR	✓			Orientation of the ground legs is questionable
12/13	DR	✓			
13	DR	✓			
14	DR	✓			
15/16	DR	✓			
17	DR	✓			Divers only inspected mooring to the ground ring. Undersized shackle used in top hardware.
28E	BR		✓		
28W	BR	✓			Buoy needs refurbishment
TOTALS		20	2	0	

- o The ground legs of half of the mooring systems (11 of 22) were completely buried in the bottom and inaccessible for inspection.
- o None of the buoys or risers have cathodic protection systems. Although the ground legs of Mooring 27W are purported to have a cathodic protection system, the legs are buried and the presence of such a system could not be verified.

#### 4.0 COMMENTS/RECOMMENDATIONS

As a result of an analysis of the data collected during the inspection, the following comments/recommendations are pertinent:

- o In view of the deep pitting of its riser and the fact that Mooring 704 was previously downgraded from a class A to a class E mooring, recommend that this mooring be overhauled at the earliest opportunity.
- o The wire rope entwined in the riser of Mooring 22 should be removed.
- o The orientation of the legs of Mooring 12/13 should be checked during the next scheduled overhaul, and if necessary, the ground legs and anchors reinstalled in their designed locations.
- o The undersized shackle in the top jewelry of Buoy 17 should be removed at the earliest possible time.
- o Due to the generally poor condition of its exterior, Buoy 28E should be refurbished.

## ANNEX A

### MOORING INSPECTION RESULTS

This Annex contains for each mooring:

- o A summation of the inspection data obtained by the CHESNAVFACENGCOM EIC and UCT TWO divers, and
- o a diver data reporting form.

## INSPECTION RESULTS

### MOORING EC-2

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 40-inch freeboard. The bottom is covered with about 1 inch of marine growth and the top deck plate is rusted; otherwise the buoy is in good condition.

#### Riser

The riser is 3 1/2-inch chain. All double link measurements were greater than 90 percent of the chain's original wire diameter. There is moderate to heavy marine growth on the riser. A few feet of riser rests on the bottom before the chain enters the bottom.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a modified class CC mooring.

MODRING NO: EC-2 CLASS: CCR (MOD) LOCATION: PNC GUAM LAT: 13° 25' 54.7" N LONG: 144° 40' 10.4" E

WATER DEPTH: 38' ANCHOR SIZE/TYPE: 25K STOCKLESS BUOY TYPE: 12' x 9' 6"

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK ☐ D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT
		NEW	SINGLE LINK %			DOUBLE LINK %			
			90+	80+	80-	90+	80+	80-	
BUOY HARDWARE									
"F" SHACKLE W/LOGS		3 1/2"	✓						DRUM BUOY WITH HAWSE PIPE. 34'
SHACKLE PIN		3 3/4"	✓						FREEBOARD, 1" GROWTH ON BOTTOM.
PEAR LINK		3 1/2"	✓						BUOY TOP PLATE RUSTED. BUOY IN GOOD CONDITION.
RISER	NEAR BUOY	3 1/2"				✓✓✓			MOD TO HEAVY GROWTH. SWIVEL IN
	MIDDLE	↓				✓✓✓			GOOD CONDITION. D.L. CALIPER 7"
	NEAR GRID RG					✓✓✓			38' SOME CHAIN ON BOTTOM PRIOR TO RISER ENTERING HUD
GROUND RING									
GROUND LEG NO. A	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. B	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. C	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. D	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								

DATE: 10 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: TRUCANOW/BRADSHAW

## INSPECTION RESULTS

### MOORING 951

#### Buoy

This is a 17-foot-diameter telephone-type buoy. The buoy is fiberglass coated and has a 17-inch freeboard. Due to this relatively low freeboard, the fender is partially submerged. The buoy bottom is covered with only a light coating of marine growth and is in good condition.

#### Ground Legs

The mooring contains three pairs of ground legs (six legs). Each pair of legs is connected to the buoy by a spider plate and a single short length of chain to one of three buoy padeyes. Each leg consists of 2 3/4-inch chain and all single and double link measurements were greater than 90 percent of the original chain diameter. The three spider plates are in good condition. At 100 feet, the lowest depth to which the divers descended, leg E was observed to be about 10 feet above leg F.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class AA mooring.



NI = not inspected, inaccessible

**$D = \text{depth}$**

50

## Visibility –

**ROCK**

**CORAL**

CLAY

11

☒

□

**Personnel**

iii

[illegible]

14 JUNE 83  
ENGINEER IN CHARGE: A. J. DODSON  
DIVERS: DEMMING/REIST

CHESLEY FACENGCOM REPORT FPR-1-83(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT,"


**MILITARY, NO.**

**ANCHOR SIZE/TYPE:**

**НОСК**

**CORAL**

CLAY



**SANI**

**MODIUM I YPE.**

[illegible]

DATE 14 JUNE 83 ENGINEER IN CHARGE A J. DODSON DIVERS: DENNING REIST

CN: SURVACE NGC(OM REPORT FPR-1-83(32). "PWC GUAM FLEET MOIRING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 701

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepole. The buoy is painted with standard colors and has a 45-inch freeboard. The bottom has a one-half inch coating of marine growth. There is no rusting, and the buoy appears to be in good condition.

#### Riser

The riser consists of 2 3/4-inch chain which is one-half inch larger than required for a class B mooring. All single and double link measurements were greater than 90 percent of the chain's original wire diameter. The chain was inspected and measured to a water depth of 120 feet.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MIDDING NO. 701 CLASS BR LOCATION: PWC GUAM LAT. 13° 26' 51" N LONG. 144° 37' 48.5" E  
 WATER DEPTH 157' ANCHOR SIZE/TYPE: 9K STATO BUOY TYPE: 12' x 6' DEVM

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 50' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT
		NEW	SINGLE LINK %		DOUBLE LINK %		D		
			90+	80+	80-	90+		80+	
BUOY HARDWARE									
CHAIN		3"							FREEBOARD 45" LIGHT (1/2") GROWTH
DETACHABLE LINK		3"							ON BOTTOM. NO BUOY RUST
PEAR LINK		4 3/8"							
DETACHABLE LINK		3 1/4"							
RISER	NEAR BUOY	2 3/4"	✓		✓			8'	S.L. 2 3/8" D.L. 5 1/16"
	MIDDLE	↓	✓		✓			80'	
	NEAR GROUND		✓		✓			120'	
GROUND RING									
GROUND LEG NO. A	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. B	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. C	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. D	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								

DATE 13 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: HARDING

## INSPECTION RESULTS

### MOORING 704

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 40-inch freeboard. The chafing rail is bent and badly rusted in some areas. The bottom of the buoy is covered with 2 to 3 inches of marine growth. The fender is in good condition.

#### Riser

The riser consists of 2 3/4-inch chain, which is much larger than the 1 3/4-inch chain required for a class E mooring. Although single and double link measurements indicated that the chain links were about 90 percent of their original size, there were many areas of severe pitting, with some as large as 2 inches wide and an eighth of an inch deep. This pitting reduced the available wire diameter of the chain to between 80 and 90 percent of its original diameter.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

Due to anchor system problems, this mooring was downgraded from a class A to a class E mooring by PWC Guam personnel. In addition, a measurement between 80 and 90 percent of any mooring component is normally cause for a mooring to be downgraded to the next lower class of mooring. However, in this case, the larger-than-required original wire diameter of the riser chain allows this mooring to be still capable of withstanding class E mooring loads. However, it recommended that this mooring not be subjected to loads in excess of E class load limits as defined in NAVFACENGCOM Design Manual 26. It is further recommended that this mooring be overhauled and its riser chain replaced at the earliest practical time.

MOORING NO. 704 CLASS ER LOCATION: PWC GUAM LAT: 13° 26' 54.5" N LONG: 144° 38' 44.8" E

WATER DEPTH: 125' ANCHOR SIZE/TYPE: 9K STATO BUOY TYPE: 13' x 6' DEUM W/HANSEPIAE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK ☐ VISIBILITY 20' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION						COMMENT
		NEW	SINGLE LINK %		DOUBLE LINK %		D	
			90+	80+	80-	90+		
BUOY HARDWARE								40" FREEBOARD. 2-3" growth
PEAR LINK		2 1/2"						on bottom. FENDER OK. CHAFING
'F SHACKLE W/LUGS		3 1/8"						RAIL BENT AND RUSTED BADLY
								IN SOME AREAS
		3 3/4"						CHAIN MEASURED AT 2 1/2."
NEAR BUOY			✓			✓	10'	LARGE AREAS OF SEVERE
MIDDLE			✓			✓	45'	PITTING - SOME 1/8" DEEP BY
NEAR GRD RG		↓	✓			✓	95"	2" DIAMETER
GROUND RING								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								

DATE 14 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: NELSON / SCHEDER

## INSPECTION RESULTS

### MOORING 702

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 36-inch freeboard. The top deck plate is heavily rusted, and the bottom is covered with a thick marine growth. The fender is in good condition.

#### Riser

The riser consists of 2 3/4-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class A mooring.

MOORING NO. 702 CLASS AR LOCATION PWC GUAM LAT: 13°-27'-31.1" N LONG: 144°-38'-08.1" E  
 WATER DEPTH 150' ANCHOR SIZE/TYPE: 9K/STATO BUOY TYPE: 12'x6' DRUM W/HAUSEPIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 50' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT
		NEW	SINGLE LINK %			DOUBLE LINK %			
			90+	80+	80-	90+	80+	80-	
BUOY HARDWARE									FREE BOARD 36" FEEDER GARD.
"F" SHACKLE W/LUGS		3/4"							HEAVY RUST ON TOP DECK PLATING
FEAR LINK		3/8"							BUOY BOTTOM COVERED WITH HEAVY MARINE GROWTH.

DATE 14 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: HARDING / TUCANAW



## INSPECTION RESULTS

### MOORING 703

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with hawsepipe. The buoy is painted with standard colors and has a 34-inch freeboard. The lower hull is covered with about 2 1/2 inches of soft marine growth. Overall, the buoy is in good condition.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A swivel was observed at 15 feet.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

BOTTOM TYPE. ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK

Visibility 20' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT		
		NEW	SINGLE LINK %			DOUBLE LINK %				D	
			90+	80+	80-	90+	80+	80-			
BODY HARDWARE											
DETACHABLE LINK		3"									FREEBOARD 34", 2 1/2" GROWTH
5" SHACKLE W/LUGS		3"									ON BOTTOM, FENDER OK. SWIVEL
PEAR LINK		3 3/8"									AT 15'
		2 1/2"	✓			✓				7'	SWIVEL NOTED AT 15'
NEAR BODY											
MIDDLE		↓	✓			✓				45'	
NEAR GRD RG		↓	✓			✓				95'	
GROUND RING											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											
UPPER END											
MIDDLE											
ENTERS BOTTOM											

DATE: 14 JUNE 83 ENGINEER IN CHARGE: A. J. DADSON DIVERS: NELSON / SCHEUREN

CUESNAVFACENCOM REPORT FPH-1-83(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 22

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 42-inch freeboard. The buoy has only a light marine growth (one-quarter inch) on its bottom. Buoy is in good condition.

#### Riser

Riser is 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's initial wire size. From just below the buoy, about 40 feet of 2-inch wire rope is tightly entwined with the riser chain. The riser enters the bottom at a water depth of 70 feet.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MOUNTING NO. 22 CLASS BR LOCATION: PWC GUAM LAT: 13° 26' 37.7" N LONG: 144° 39' 50.6" E  
 WATER DEPTH 70' ANCHOR SIZE/TYPE: 20K STOCKLESS BUOY TYPE: 12' x 6' DEEP W/HANDSE PI PE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 30' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT	
		NEW	SINGLE LINK %			DOUBLE LINK %				D
			90+	80+	80-	90+	80+	80-		
BUOY HARDWARE										
PEAR LINK		3 1/4"								FREEBOARD 42" FEELER OK.
DETACHABLE LINK		3 3/16"								LIGHT GROWTH (1/4") ON BOTTOM.
CHAIN		2 3/8"								
HULL		2 1/2"	✓				✓			40' OF 2" WIRE ROPE TIGHTLY
		↓	✓				✓			ENTWINED WITH CHAIN.
		↓	✓				✓			
GROUND RING										
GROUND LEG NO A										
GROUND LEG NO B										
GROUND LEG NO C										
GROUND LEG NO D										

DATE 11 JUNE 83 ENGINEER IN CHARGE A J. DODSON DIVELER SCHEUREN / RIESE

## INSPECTION RESULTS

### MOORING 22/23

#### Buoy

This is a 10-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 32-inch freeboard. The buoy is in good condition.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A swivel was observed to be in good condition at a water depth of 15 feet, and a 4 1/2-inch ground ring was located at a depth of 40 feet.

#### Ground Legs

The upper 50 feet or so of three ground legs were visible. All legs were 2 1/2-inch chain and all measurements taken were larger than 90 percent of the original diameters. At their attachment to the ground ring, two of the legs are side-by-side.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

WATER DEPTH: 58 ANCHOR SIZE/TYPE: 20K STACKLESS BUOY TYPE: 10' x 6.5' DRUM

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK

Visibility 6-50 D = depth NI = not inspected inaccessible

[illegible]

DATE: 11 JUNE 83 ENGINEER IN CHARGE: A. J. DEDSON DIVERS: NELSON / HARDING

CIN SNAVFACFNGCOM REPORT FPR-1-A3(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 501

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 36-inch freeboard. The bottom of the buoy has only a light coating of marine growth. Overall, the buoy is in good condition.

#### Riser

The riser consists of 2 1/2-inch chain and all measurements were larger than 90 percent of the chain's original wire size. The chain was only inspected to a water depth of 100 feet.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK  
 Visibility 40' D = depth  
 NI = not inspected, inaccessible

DATE: 14 JUNE 83 ENGINEER IN CHARGE: A. J. DODSON DIVERS: HARDING / TIZUCANOW



## INSPECTION RESULTS

### MOORING 25E

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 35-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 3/4-inch-diameter ground ring was found on the bottom at a water depth of 42 feet.

#### Ground Legs

The upper few links of three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.



## INSPECTION RESULTS

### MOORING 25W

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 35-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 1/2-inch diameter ground ring was found on the bottom at a water depth of 41 feet.

#### Ground Legs

The upper few links of three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MOORING NO.: 25 W CLASS: BR LOCATION: PINE GUAN LAT: \_\_\_\_\_ LONG: \_\_\_\_\_  
WATER DEPTH: 41' ANCHOR SIZE/TY: 20K STOCKLESS BUOY TYPE: 12' x 6' DECK W/H MOOSEPITE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK  
 Visibility 5' D = depth NI = not inspected, inaccessible

[illegible]

DATE: 10 JUNE 83 ENGINEER IN CHARGE: A. J. DODSON DIVERS: TORRENS/WELSON

CUESIAVAFACOM REPORT FPR-1-83(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 26E

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 45-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 1/2-inch-diameter ground ring was found on the bottom at a water depth of 37 feet.

#### Ground Legs

The upper few links of three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MARKING NO: 26E CLASS BR LOCATION PWC GUAM LAT: 13°25'-46.2" N LONG: 144°-46'-14.1" E  
 WATER DEPTH: 38' ANCHOR SIZE/TYPE: 20K STOCKLESS BUOY TYPE 12' X 6' DRUM NO 10/HAKKEPPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK ☐ VISIBILITY 10' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT	
		NEW	SINGLE LINK %			DOUBLE LINK %		D		
			90+	80+	80-	90+	80+			80-
BUOY HARDWARE										
CHAIN LINK		3"	✓							FREEBOARD 45" FENDER GOOD
SHACKLE		3 3/4"	✓							GROWTH 1/2"-1"
PEAR LINK		4"	✓							
FISHER										
	NEAR BUOY	2 1/2"	✓				✓			<10'
	MIDDLE	↓	✓				✓			20'
GROUND RING										
	NEAR GRID RG	↓	✓				✓			37'
		4 1/2"	✓							37'
GROUND LEG NO. A		2 1/2"	✓				✓			38'
	UPPER END									
	MIDDLE									
ENTERS BOTTOM										
GROUND LEG NO. B		2 1/2"	✓				✓			38'
	UPPER END									
	MIDDLE									
ENTERS BOTTOM										
GROUND LEG NO. C		2 1/2"	✓				✓			38'
	UPPER END									
	MIDDLE									
ENTERS BOTTOM										
GROUND LEG NO. D										
	UPPER END									
	MIDDLE									
ENTERS BOTTOM										

DATE 10 JUNE 83 ENGINEER IN CHARGE: A. J. DODSON DIVERS: NELSON/TORRENS

## INSPECTION RESULTS

### MOORING 26W

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 45-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 9/16-inch diameter ground ring was found on the bottom at a water depth of 38 feet.

#### Ground Legs

About 10 feet of each of the three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MOONING NO. 26W CLASS BR LOCATION PWC GUAM AT 13-25-46.2" N LONG 144-40-14.1 E

WATER DEPTH: 38' ANCHOR SIZE/TYPE: 20K STOCKLESS BUOY TYPE: 12 X 6' DRUM WITH HARKEN PIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 10 D = depth NI = not inspected, inaccessible

[illegible]

DATE 10 JUNE 83 NAME IN CHARGE: A. J. DODSON DIVERS: AUSTIN/SCHENKEN  
CHESNAVACOM REPORT FPR-1-83(32), "PNC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."



## INSPECTION RESULTS

### MOORING 27E

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 38-inch freeboard. The buoy hull has a 2-foot-wide, 2-inch-deep dent just below the fender. However, there is no rust and the fiberglass covering the dent is still intact. There is only a light coating of marine growth (one-quarter inch) on the buoy's bottom.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 1/2-inch diameter ground ring was found near the bottom at a water depth of 30 feet.

#### Ground Legs

The upper few links of three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

WATER DEPTH: 31' ANCHOR SIZE/TYPE: 20 K STOCKLESS BUOY TYPE: 12'x6' DRUM WITH ANCHOR PIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK

Visibility 2' D = depth NI = not inspected, inaccessible

[illegible]

DATE: 10 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: DEHNING/REIST

CHESNAVFACEGCOM REPORT FPR-1-83(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 27W

#### Buoy

This is a 12-foot-diameter fiberglass-coated drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 37-inch freeboard. There is some rust on the chafing rail but the general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 3-inch-diameter ground ring was found near the bottom at a water depth of 38 feet.

#### Ground Legs

The upper few feet of each of three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

☐ SAND    ☒ MUD    ☐ CLAY    ☐ CORAL    ☐ ROCK  
 BOTTOM TYPE:    Visibility 5-20'    D = depth    NI = not inspected, inaccessible

DATE: 10 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: BRADSHAW / TZUCANOW

CUE'SNAVFACEGCOM REPORT FPR-1-83(32). "PAC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 12/13

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 18-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 -inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 1/2-inch diameter ground ring was found on the bottom at a water depth of 98 feet.

#### Ground Legs

The upper 10 feet of each of the three ground legs were visible before the chain entered the bottom. All three legs were 2 -inch chain and all measurements were larger than 90 percent of the original wire diameter. The leg bearings are 029, 031, and 215 degrees, although a 120-degree separation of the ground legs is desired.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class D mooring. However, the orientation of the ground legs should be checked during the next overhaul and these legs reinstalled if required.

MOORING NO. 12/13 CLASS DR LOCATION PWC GUAM LAT: 13°26'41"N LONG: 144°39'02"E  
 WATER DEPTH: 98' ANCHOR SIZE/TYPE: 20K STOCKLESS BUOY TYPE: 9'x6' DRUM W/HAWSEPIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 40' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION							COMMENT
		NEW	SINGLE LINK %			DOUBLE LINK %			
			90+	80+	80-	90+	80+	80-	
BUOY HARDWARE									
PEAR LINK		3/4"							FREE BOARD 18" FEUDER GOOD
" F" SHACKLE W/LUGS		2 1/8"							1" GROWTH ON BOTTOM
(PIN) SHACKLE		2 1/8"							
RISER		2"	✓			✓			8'
		2"	✓			✓			45'
	NEAR GRD RG	2"	✓			✓			92'
GROUND RING		4 1/2"							98' 24" DIAMETER
	UPPER END	2"	✓			✓			98' BEARING 039°M
MIDDLE									
ENTERS BOTTOM									
GROUND LEG NO. A		2"	✓			✓			98' BEARING 031°M
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. B		2"	✓			✓			98' BEARING 215°M
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. C		2"	✓			✓			98' BEARING 215°M
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. D									EACH LEG VISIBLE FOR ABOUT 10' ON BOTTOM. LEGS VERY TALL
	UPPER END								
	MIDDLE								
ENTERS BOTTOM									

DATE 13 JUNE 83 ENGINEER IN CHARGE: A.J. Dodson DIVERS: TEUCANOW/SCHUELEN

CHESNAVAFACNGCOM REPORT FPR-1-83(32), "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

## INSPECTION RESULTS

### MOORING 13

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 32-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 1/2-inch-diameter ground ring was found on the bottom at a water depth of 105 feet.

#### Ground Legs

The upper few links of three ground legs were measured with calipers. All three legs were 2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class D mooring.

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 20' D = depth NI = not inspected inaccessible

[illegible]

DATE: 13 JUNE 83 ENGINEER IN CHARGE: A.J. DODSON DIVERS: DEAMING / TORREWS

CHE SHAVACENCOM REPORT FPR-1-H3(32). "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT,"\*



## INSPECTION RESULTS

### MOORING 14

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a hawsepole. The buoy is painted with standard colors and has a 30-inch freeboard. There is a 1- to 3-inch marine growth on its bottom. Overall, this buoy is in good condition.

#### Riser

The riser consists of 2-inch chain. All measurements taken were larger than 90 percent of the chain's original wire size. The riser vertically enters the bottom at a water depth of 97 feet.

#### Ground Ring/Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class D mooring.



## INSPECTION RESULTS

### MOORING 15/16

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 27-inch freeboard. Except for some light marine growth on the bottom, the buoy is in good condition.

#### Riser

The riser consists of 2-inch chain. Single and double link measurements were all greater than 90 percent of the chain's original wire size. The riser enters the bottom at a depth of 97 feet.

#### Ground Ring/Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class D mooring.

MOORING NO. 15/16 CLASS DR LOCATION: PWC GUAM LAT: 13° 26' 49.7" N LONG: 144° 39' 08.4" E  
 WATER DEPTH: 97 ANCHOR SIZE/TYPE: 20K STACKLESS BUOY TYPE: 9' x 6' DEEP W/ HAWSEPIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 15' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION						COMMENT
		NEW	SINGLE LINK %		DOUBLE LINK %		D	
			90+	80+	80-	90+		
BUOY HARDWARE								
DETACHABLE LINK		3 1/2"						27" FREE BOARD. LIGHT GROWTH ON
DETACHABLE LINK		2"	✓					BOTTOM
PEAR LINK		2 3/8"	✓					
RISE	NEAR BUOY	2"	✓			✓		5.L 1 7/8" D.L 3 3/4" C10'
	MIDDLE	↓	✓			✓		D.L 3 3/4" 60'
	NEAR GRD RG		✓			✓		D.L 3 3/4" 99'
GROUND RING								
GROUND LEG NO. A	UPPER END							
	MIDDLE							
	ENTERS BOTTOM							
GROUND LEG NO. B	UPPER END							
	MIDDLE							
	ENTERS BOTTOM							
GROUND LEG NO. C	UPPER END							
	MIDDLE							
	ENTERS BOTTOM							
GROUND LEG NO. D	UPPER END							
	MIDDLE							
	ENTERS BOTTOM							

## INSPECTION RESULTS

### MOORING 17

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy has a 20-inch freeboard and has a light coating of marine growth on the hardware. A 1 1/2-inch shackle in the top jewelry is attached to a lug of a larger 2 5/8-inch shackle. Overall the buoy is in good condition.

#### Riser

The riser consists of 2-inch chain. Single and double link measurements were all greater than 90 percent of the chain's initial wire diameter. A 4 1/2-inch wire size ground ring was located at a water depth of 81 feet. The bottom was estimated to be about 15 feet below the ground ring.

#### Ground Leg/Anchors

Not inspected.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class D mooring. However, since all components of a class D mooring should have, as a minimum, a wire size of 2 inches, recommend that the 1 1/2-inch shackle be removed from the top jewelry to preclude a vessel inadvertently mooring to an undersized component.

MOORING NO. 17 CLASS DR LOCATION APC GUAM LAT: 13° 26' 53.4" N LONG: 144° 39' 02.2" E  
 WATER DEPTH 96' ANCHOR SIZE/TYPE 20K STOCKLESS BUOY TYPE 9x6 DECK W HOUSE PIPE

BOTTOM TYPE ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 15' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION						COMMENT	
		NEW	SINGLE LINK %		DOUBLE LINK %		D		
			90+	80+	80-	90+			80+
BUOY HARDWARE									
"F" SHACKLE W/LIPS		2 3/8"							20" FREEBOARD. FENDER GOOD.
SHACKLE PIN		3"							1/2" GROWTH ON BOTTOM
PEAR LINK		2 9/16"							
SHACKLE		1 1/2"	(ATTACHED TO LOG OF LARGE SHACKLE)						
RISER		2	✓			✓		< 10'	
		↓	✓			✓		45'	
	NEAR GRID RG	✓				✓		80'	SWIVEL AT 63'
GROUND RING		4 1/2"						81'	DIVERS ONLY WENT TO GROUND
GROUND LEG NO. A	UPPER END								RING, DID NOT MEASURE LEG
	MIDDLE								CHAIN DIAMETERS. HOWEVER, DID
	ENTERS BOTTOM								GET LEG BEARINGS:
GROUND LEG NO. B	UPPER END								LEG A 120° H
	MIDDLE								↓ B 260° H
	ENTERS BOTTOM								↓ C 310° H
GROUND LEG NO. C	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								
GROUND LEG NO. D	UPPER END								
	MIDDLE								
	ENTERS BOTTOM								

DATE 13 JUNE 83 ENGINEER IN CHARGE AJ DODSON DIVERS DEMING/TORRENS

## INSPECTION RESULTS

### MOORING 28E

#### Buoy

This is a 9-foot-diameter fiberglass-coated drum-type buoy with a tension bar. The buoy is painted with standard colors and has a 19-inch freeboard. The top plate and top jewelry are badly rusted, and the chafing rail is bent. The buoy has been slightly damaged and has a one-half-inch-deep dent through the fiberglass. The dent is heavily rusted, the fiberglass is chipped, and the metal below the chipped area is deteriorating.

#### Riser

The riser consists of 2 1/2-inch chain. Single and double link measurements were all larger than 90 percent of the chain's initial wire size. The riser vertically enters the bottom at a water depth of 32 feet.

#### Ground Legs/Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring. However, the buoy is in need of refurbishment.

MOORING NO. 28E CLASS: BR LOCATION: PWC GUAM LAT: 13°-35'-34.6" N LONG: 144°-40'-10" E  
 WATER DEPTH: 32' ANCHOR SIZE/TYPE: 20K STOKLESS BUOY TYPE: 9'x6' DRUM W/ HAWSE PIPE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK Visibility 10' D = depth NI = not inspected, inaccessible

COMPONENTS	NI	CONDITION						COMMENT
		NEW	SINGLE LINK %		DOUBLE LINK %		D	
BUOY HARDWARE			90+	80+	90+	80+	80-	
"F" SHACKLE W/ LOGS		3/8"						19" FREEBOARD, TOP PLATE BADLY
PIN SHACKLE		2 3/4"						RUSTED. CHAFING RAIL BENT, BUOY
PEAR LINK		3 3/4"						DAMAGED. HAS 1 1/2" DENT WITH
								CORRODING METAL SHORING
		2 1/3"	✓		✓			< 10'
NEAR BUOY								
MIDDLE			✓		✓			16'
NEAR GRID RG			✓		✓			32'
GROUND RING								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								
ENTERS BOTTOM								
UPPER END								
MIDDLE								



## INSPECTION RESULTS

### MOORING 28W

#### Buoy

This is a 12-foot-diameter drum-type buoy with a hawsepipe. The buoy is painted with standard colors and has a 34-inch freeboard. The general condition of the buoy is good.

#### Riser

The riser consists of 2 1/2-inch chain. All single and double link measurements were larger than 90 percent of the chain's original wire size. A 4 5/8-inch diameter ground ring was found near the bottom at a water depth of 30 feet.

#### Ground Legs

The upper 10 feet of the three ground legs were visible before the chain entered the bottom. All three legs were 2 1/2-inch chain and all measurements were larger than 90 percent of the original wire diameter.

#### Anchors

Not visible for inspection.

#### Recommendation

This mooring is in satisfactory condition for continued use as a class B mooring.

MOUNTING NO: 28W CLASS: BR LOCATION: PWC GUAM LAT: 13°-25'-34.9" N LONG: 144°-40'-04.6" E  
 WATER DEPTH: 36' ANCHOR SIZE/TYPE: 20K STACKLESS BUOY TYPE: 12'x6' DEPH W/HAIRSEAPIE

BOTTOM TYPE: ☐ SAND ☒ MUD ☐ CLAY ☐ CORAL ☐ ROCK ☐ D = depth. NI = not inspected, inaccessible  
 Visibility 10'

COMPONENTS	NI	CONDITION							COMMENT	
		NEW	SINGLE LINK %			DOUBLE LINK %				D
			90+	80+	80-	90+	80+	80-		
BUOY HARDWARE										
SPIDER		3"								34" FREEBOARD. FEUDED GOOD.
SPIDER SPIDER		3"								1/2" MARINE GROWTH
2 PEAR		2 1/2"								
U/W DETACHABLE		3 3/8"								
FISHER		2 1/2"	✓				✓			<10'
		↓	✓				✓			20'
		↓	✓				✓			30'
GROUND RING		4 5/8"								30'
		2 1/2"	✓				✓			31'
GROUND LEG NO. A		2 1/2"	✓							
ENTERS BOTTOM		2 1/2"	✓				✓			36'
UPPER END		2 1/2"	✓				✓			31'
MIDDLE										
ENTERS BOTTOM		2 1/2"	✓				✓			36'
UPPER END		2 1/2"	✓				✓			
MIDDLE										
ENTERS BOTTOM		2 1/2"	✓				✓			31'
UPPER END		2 1/2"	✓				✓			
MIDDLE										
ENTERS BOTTOM		2 1/2"	✓				✓			36'
UPPER END										
MIDDLE										
ENTERS BOTTOM										
UPPER END										
MIDDLE										
ENTERS BOTTOM										


DATE: 12 JUNE 83 ENGINEER IN CHARGE: AJ DODSON DIVERS: AUSTIN/SCHUEREN  
 CROSS REFERENCE REPORT FPR-1-83(32), "PWC GUAM FLEET MOORING UNDERWATER INSPECTION REPORT."

**ANNEX B**

**PHOTOGRAPHS**



**Marine Growth on the Bottom of Buoy 701.  
This is Typical of the Condition of Most Buoy Hulls**



**Damaged Fender and Upper Hull of Buoy 27E**



**Heavy Rusting of Top Deck and Jewelry of Buoy 28E**




**Ground Ring of Mooring 22/23.**

**Note that Two Legs are Together at Their Attachment to the Ring**



**Swivel in the Riser of Mooring 15/16**



**Typical Good Condition of Recently Overhauled Buoys**

ANNEX C

REFERENCES

UNCLASSIFIED

01 01

RR

UUUU

1981200

FROM CHESNAVFACENGCOM WASHINGTON DC

TO PWC GUAM

INFO COMNAVFACENGCOM ALEXANDRIA VA

PACNAVFACENGCOM PEARL HARBOR HI

UNCLAS //N11000//

SUBJ: FLEET MOORING INSPECTION

1. A CHESNAVFACENGCOM/UCT TWO UNDERWATER INSPECTION OF THE 22 FLEET MOORINGS LOCATED AT GUAM WAS CONDUCTED DURING THE PERIOD 6-14 JUNE 1983. THIS IS A PRELIMINARY REPORT OF THE INSPECTION RESULTS.

FINDINGS ARE AS FOLLOWS:

A. MOORINGS 951, 701, 702, 703, 22, 22/23, 501, 25E, 25W, 26E, 26W, 27E, 27W, 12/13, 13, 14, 15/16, 17, 28E, 28W, EC-2: GOOD CONDITION.

B. MOORING 704: RECOMMEND OVERHAUL AS PLANNED TO UP GRADE MOORING TO ORIGINAL CLASS A.

2. CHESNAVFACENGCOM POINT OF CONTACT IS MR. J. MCLAUGHLIN AT AUTOVON 288-3881 OR (202) 433-3881.

D STP

J. MCLAUGHLIN

FP0-1C7

Rsh

15 JULY 83

33881

*James E. M. Laughlin*

COPY TO:

09/00; 0161; DAILY

FP0-1EA(PDC); FP0-1EA

FP0-1EA5; FP0-1C7

FP0-1C..FP0-10P2

E. B. SPONZER, HD, OCEAN ENGR &

PROJ OFFICE (A)

UNCLASSIFIED

DD FORM 1732 OCA





I4	0	97	10/53	6/82	GOOD	6/87	YC
15/I6	0	97	10/53	9/82	GOOD	9/87	YTB
17	0	69	9/53	5/82	GOOD	5/87	YON

2. FOR PARA 2.E: THERE IS NO ANTICIPATED MOORING USAGE DURING THE INSPECTION PERIOD IN JUNE 1983, UNLESS TYPHOON PREPARATIONS ARE NEEDED.

4. INFO REQUIRED BY PARAGRAPHS 2.B, 2.C AND 2.D TO BE MAILED  
25 APRIL 1983.  
BT

220001Z APR 83  
PNC GUAM

C-4

[illegible]

# ROUTINE

R 132054Z APR 83

FM CHESNAVFAENGCOM WASHINGTON DC

TO PWC GUAM

INFO COMNAVFACENGCOM ALEXANDRIA VA  
COMCDPAC PEARL HARBOR HI  
COM THREE ONE NCR PORT HUENEME CA

PACNAVFACENGCOM PEARL HARBOR HI  
COM THREE ZERO NCR GUAM  
UCT TWO

BT  
UNCLAS //N11000//

**SUBJ: FLEET MOORING INSPECTIONS**

1. AS PART OF THE COMNAVFACENGCOM FLEET MOORING MAINTENANCE (FMM) PROGRAM, CHESNAVFACENGCOM, WITH DIVER SUPPORT FROM UCT TWO, PLANS TO CONDUCT AN UNDERWATER INSPECTION OF THE 20 MOORINGS OPERATED AND MAINTAINED BY PNC GUAM DURING JUNE 1983. AVAILABLE INFORMATION INDICATES 3 CLASS A MOORINGS IN 125-150 FEET OF WATER, 10 CLASS B MOORINGS IN 32-160 FEET OF WATER AND 7 CLASS D MOORINGS IN 32-105 FEET OF WATER. INSPECTION WILL RESULT IN SPECIFIC CONDITION ANALYSES AND RECOMMENDATIONS BY MOORING AND WILL ENHANCE THE PROGRAMMING OF FUNDS FOR FLEET MOORING MATERIAL SUPPORT.

2. THE FLEET MOORING INSPECTION TEAM WILL CONSIST OF A CHESDIV ENGINEER-IN-CHARGE (EIC) AND A DET FROM UCT TWO. IN ORDER TO PREPARE A DETAILED INSPECTION PLAN, THE FOLLOWING INFORMATION IS REQUIRED PER MOORING:

A. MAINTENANCE HISTORY - WHEN INSTALLED, WHEN INSPECTED, WHEN OVERHAULED, LAST REPORTED CONDITION, ETC.

8. COPIES OF AVAILABLE MOORING DESIGN CALCULATIONS AND DRAWINGS.

C. COPIES OF "AS-BUILT" MATERIALS LIST.

D. FACILITY MAP SHOWING LOCATION OF ALL MOORINGS WITH SPECIFIC LOCATIONS FOR THOSE CURRENTLY IN USE.

E. ANTICIPATED MOORING USAGE DURING THE INSPECTION PERIOD -  
TYPES OF SHIPS.

F. PLANNED REPAIRS AND OVERHAULS - PARTICULARLY THOSE BEFORE THIS INSPECTION.

**G. TYPES OR CLASSES OF SHIPS USING MOORING.**

H. WHETHER CATHODIC PROTECTION SYSTEMS ARE INSTALLED AND TYPE

DLVR:CHESNAVFACEGCOM WASHINGTON DC(9)...ORIG

RTD:007.-000/CUPIES:0009

593518/103  
CSN:RXOY70509

1 OF 2 M1 0468 103/23:42Z 132054Z APR 83  
CHESNAVFACENGCOM WASHINGTON DC

UU  
U U N C L A S S I F I E D U  
UU





UUUUUUU 1UUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUU  
U U N C L A S S I F I E D U  
UU

A. CINCPACFLT PEARL HARBOR HI 260654Z JUN 82

1. REF A REQUESTED NOMINATIONS OF PROJECTS FOR UCT TWO ACCOMPLISHMENT FY83-85. FROM THE RESPONSES TO REF A THE FOLLOWING PROJECTS ARE TASKED FOR ACCOMPLISHMENT IN FY83:

- A. CENTERVILLE BEACH (CLASSIFIED)
- B. ARCTIC WEST (CLASSIFIED)
- C. BARKING SANDS, HI, CABLE LANDING AND REPAIRS
- D. WPNSTA SEAL BEACH, DEMOLISH ANAHEIM BAY BRIDGE
- E. NSD SUBIC, PILE REPAIR POL PIER
- F. NSD SUBIC, PILE REPAIR MARINE TERMINAL PIER PHASE I (REPAIR ALL SEVERE AND MAJOR DAMAGE)
- G. NAVSHIPREPFAC SUBIC, INSPECT ALAYA WHARF
- H. FLEET MOORING INSPECTION - PACIFIC DATA BASE (PEARL HARBOR HI, GUAM, YOKOSUKA, Iwakuni, SASEBO, INDIAN ISLAND WA, BREMERTON WA)
- I. NAVMAG LUALUALEI, INSPECT AMMO PIERS W1-5
- J. UNDERWATER INSPECTION PROGRAM (NSC SAN DIEGO)
- K. SUBASE, BANGOR WA, UNDERWATER INSPECTION
- L. TRIREFAC BANGOR WA, UNDERWATER MSF RANGE REPAIR
- M. DEGAUSSING RANGE SURVEY, SAN FRANCISCO CA
- N. NAVPHIBASE CORONADO SAN DIEGO CA, PIER INSPECTIONS

2. THE FOLLOWING PROJECTS ARE TASKED AS FILL IN WORK FOR FY83:

- A. UNDERWATER INSPECTION PROGRAM (NAVSTA PEARL HARBOR)
- B. NAVUSEAWAKENGSTA KEYPORT WA, INDIAN IS PHASE TWO MOORING
- C. NSD GUAM, REPAIRS TO SIERRA WHARF GUAM. REQUIRES COORDINATION WITH ON SITE NMCB FOR ACCOMPLISHMENT.

THE FOLLOWING PROJECTS ARE TENTATIVELY TASKED FOR ACCOMPLISHMENT AS INDICATED:

- A. FY-84
  - (1) ARCTIC WEST (CLASSIFIED)
  - (2) NAVSHIPREPFAC GUAM, REPAIRS TO LIMA WHARF
  - (3) FLEET MOORING INSPECTION - PACIFIC DATA BASE 9SUBIC BAY, NSF DIEGO GARCIA, PNC SAN DIEGO, NAVSTA SAN DIEGO, WPNSTA SEAL BEACH, NAVSTA LONG BEACH)
  - (4) NSD SUBIC, WATERFRONT FACILITIES INSPECTION
  - (5) NSD SUBIC, MONOBUOY FUEL LINE REPAIRS
  - (6) DEGAUSSING RANGE SAN FRANCISCO, RANGE INSTALLATION
  - (7) UNDERWATER INSPECTION PROGRAM CNAVSHIPY PEARL HARBOR, NSC PEARL HARBOR, SUBASE PEARL HARBOR)
  - (8) SCARF REPAIR/INSPECTION
  - (9) BARKING SANDS, UNDERWATER RANGE REPAIRS
  - (10) NSD SUBIC, PILE REPAIR MARINE TERMINAL PIER PHASE 2

114776/235  
RXDY00304

2 OF 3 M1 0308

235/23:21Z 210331Z AUG 82  
CINCPACFLT PEARL HARBOR HI

UU  
U U N C L A S S I F I E D U  
UU

UNCLASSIFIED  
UNCLASSIFIED

(REPAIRS TO MODERATE AND MINOR DAMAGE)

B. FY-85

- (1) ARCTIC WEST (CLASSIFIED)
- (2) BARKING SANDS, UNDERWATER RANGE WORK
- (3) FLEET MOORING INSPECTION - PACIFIC DATA BASE (PEARL HARBOR HI, GUAM, JAPAN, PUGET SOUND WA)
- (4) UNDERWATER INSPECTION PROGRAM (HARE ISLAND WA)
- (5) SUBASE PEARL, MCON P-088, REPAIR AND EXTEND SEABALL  
THIS PROJECT WILL REQUIRE SEPARATE TASKING OF AN  
RNMCS, CBU, OR OTHER ORGANIZATION AS "PRIME  
CONTRACTOR" FOR PILE DRIVING AND TOPSIDE ZONE, WITH  
VET ACCOMPLISHING IN WATER SUPPORT.

147 6/23  
S :RXC 003

1 04 1 01 0300 03:02:11Z 210112 AUG 82  
LINCAPAC, PEARL HARBOR HI

UNCLASSIFIED  
UNCLASSIFIED

END

FILMED

6-86

DTIC