























MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS - 1963 - A



T4



AR-004-046

.

ARL-AERO-PROP-R-168

AD-A171 058

Ø



DEPARTMENT OF DEFENCE DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION AERONAUTICAL RESEARCH LABORATORIES

MELBOURNE, VICTORIA

AERO PROPULSION REPORT 168

INVESTIGATION OF BLADE VIBRATION

T55-L-11C COMPRESSOR STAGES 1 AND 2

by

N. S. SWANSSON

Approved for Pubic Release

onc file copy



C COMMONWEALTH OF AUSTRALIA 1985

SEPTEMBER 1985

86 8 10 085

AR-004-046

DEPARTMENT OF DEFENCE DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION AERONAUTICAL RESEARCH LABORATORIES

AERO PROPULSION REPORT 168

INVESTIGATION OF BLADE VIBRATION

T55-L-11C COMPRESSOR STAGES 1 AND 2

by

N. S. SWANSSON

SUMMARY

A vibration survey of the first and second stage compressor blades on the T55-L-11C engine was conducted following the manufacturer's warning that the proposed fitting of locally designed intake screens might lead to blade vibration problems. Vibration tests and a simple analysis indicated a possible resonance region. Special statistical methods for small samples were used to fully define tolerance limits for this region and establish confidence levels in the limits.

Operators were initially advised to restrict operation in the potential resonance region. Subsequent intake flow tests demonstrated that the screens generated no abnormal excitation, so the restrictions could be discontinued.



© COMMONWEALTH OF AUSTRALIA 1985

CONTENTS

REFERENCES

A CARE A CONTRACTOR A LAN A CARE

10 miles

DISTRIBUTION

DOCUMENT CONTROL DATA

Access	ion For		_
NTIS DTIC 1 Unanno Justif	GRA&I AB unced ication		OUNU Notes 1
By Distr:	bution/		
Ava1	ability Cod	93	
Dist	Avail and/or Special		
A-1			



Page No.

1

1

1

1

3

3

3

4

6

6

6

7

1. INTRODUCTION

The first and second stage compressor blades on the Lycoming T55-L-11C engine installed in the Boeing Vertol CH-47C Chinook helicopter are liable to foreign object damage (FOD) due to ingested debris. During certain types of operations such as over gravel surfaces, the level of FOD experienced by the RAAF was such as to significantly reduce the operational availability of the helicopter.

To alleviate the FOD and other problems, the engine manufacturers proposed a modification, replacing the original first and second stage compressor blades with a more robust design having a wider chord. While this modification offered a long term solution, pending its implementation the RAAF proposed to cover the standard engine intake screens (which are of relatively coarse mesh) with a fine mesh fibreglass overlay.

Since the proposal to fit overlay screens originated locally, the RAAF asked ARL to investigate the effects of fitting screens on various aspects of engine performance and operation, particularly since the engine manufacturer had warned of a possible problem with "second order" blade vibration [1].

Simple investigations verified that fitting screens would have only minor effects upon engine performance. But as no detailed blade vibration data were available from the engine manufacturer, investigations were initiated both to measure the effect of the screens on vibration excitation due to flow distortion at the compressor intake [2], and to measure blade vibration and response characteristics.

2. TESTS AND RESULTS - ORIGINAL DESIGN BLADES

It was originally expected that the vibration investigation would comprise simple static measurements of natural frequencies, which would then be adjusted for effects of rotation. But the scatter found in frequency values indicated that a greater depth of statistical analysis was called for, in order to have adequate confidence in predictions which would be based on scatter limits.

2.1 Testing

Natural frequencies of blades were determined by measuring resonant frequencies, as the blades were excited through a range of frequencies using an electro magnetic vibrator. Blades were held in a fixture designed to simulate the constraint in a rotating engine, where centrifugal force firmly wedges the blade base into its mating dovetail slot. Peak vibration amplitudes were determined using a non-contacting capacitive displacement pick-up, and mode shapes were observed using stroboscopic illumination, with the stroboscope triggered by a slow motion generating device. Results for a sample group of blades, including mean frequencies and standard deviation estimates, are given in Table 1.

2.2 Effect of Rotation

As the compressor rotates, centrifugal forces tend to straighten the blade, effectively increasing its stiffness and hence its natural frequency. The quantitative effect of centrifugal stiffening can be determined using a Southwell type formula, which is exact for a linear vibrating system

TABLE 1

Natural Frequencies T55 Compressor — Original Blades

	Stage Blades		Stage 2 Blades	
Mode	Mean Frequency Hz	Standard Deviation	Mean Frequency Hz	Standard Deviation
lst Bending	267·2	2.95	288	3 · 13
2nd Bending	1110	21.9	1006	17.2
1st Torsion	1597	9 ·87	2052	12.75
3rd Bending	2753	22.5	2436	19.7
4th Bending			4560	52
2nd Torsion	4267	64 • 4	4872	71
	1			

having multiple restoring forces. For a rotating blade it has the form:

CONTRACT CONTRACT CONTRACT STATUS STATUS

$$f^2 = f_0^2 + SN^2 \tag{2.1}$$

where f is natural frequency, f_0 frequency at zero rotational speed and N the speed. If the mode shape of the blade can be determined, the Southwell coefficient S can be calculated exactly. The shape of practical blades makes exact quantitative determination of the coefficient by either experiment or analysis very difficult, but data are available to estimate values. The value of S for each mode is a function of blade geometry; the relevant parameters are aspect ratio, radius/length ratio, taper, twist and setting angle. Data in [4] for untwisted rectangular plates were used to find approximate values for S which are given in Table 2. Comparison with data in [5] and [6] indicates that the effect of neglecting taper and twist should not be serious. Radius ratio and setting angle are used explicitly in determining S; data were interpolated for applicable aspect ratios. Because the system is not quite linear, the value of S is slightly influenced by the ratio of rotational to natural frequency.

TABLE 2

Southwell Coefficients

T55 (Compressor	– Origin al	Blades
-------	------------	--------------------	--------

	Stage 1	Stage 2
Aspect Ratio	3	4.3
Radius Ratio	1.15	0.92
Setting Angle	47 · 2°	48 · 3°
Mode	Southwell	Coefficient
1st Bending	2.424	2.05
2nd Bending	15.9	13.9
1st Torsion	2.63	2.25
3rd Bending	45·2	39.6
4th Bending		60
a 1 m ·	10.6	17.1

2.3 Frequency Scatter

となるのであると、人気になっていた。

Small samples (about 5-6) of each type of blade were supplied to A.R.L. for testing: measured blade frequencies exhibited significant scatter. Even if the frequency values are assumed to have a normal distribution, the small sample sizes meant that special methods were required to estimate scatter limits with their associated probability levels, the appropriate methods being those dealing with tolerance limits. Discussion of tolerance limits, and an outline of their derivation is a substantial topic and is considered in the following section.

3. LIMITS OF FREQUENCY SCATTER

3.1 Tolerance Limits

Tolerance limits need to be established when it is required to find or to control the proportion of a population having values of a particular variable within (or without) a specified range. For a variable such as the strength of a component, a single sided limit is relevant since the statistic of concern is the proportion of the population having less than a specified strength. With vibration frequency values, either upper or lower limits may define critical resonance conditions so a two-sided tolerance limit is applicable.

Two-sided tolerance limits are defined as the limits v_1 , v_2 of the population variable x_1 , within which a proportion p of the population is expected to lie. As in the present problem, statistics of population variables frequently are not known, and must be inferred from measurements on small samples. If a large series of samples were to be taken, the varying limits x_1 , v_2 deduced statistically from each individual sample would encompass a proportion at least p of the population in a fraction γ of the samples. It is then concluded that the limits v_1 , v_2 predicted using a single sample have a probability γ of including a proportion at least p of the population.

For known forms of probability distribution, values for tolerance limits can be derived. For a normal distribution, whose limits are symmetrical, details are given in [9]. If the distribution is not normal, results have the same form but the variable limits are changed to some extent. Non parametric methods, not requiring any knowledge of the probability distribution, can also be used; such distribution free methods are relatively inefficient in the sense that significantly larger sample sizes are required to predict limits with comparable certainty, or to predict limit ranges at the same probability level.

3.2 Derivation of Tolerance Limits

Tolerance limits for a normally distributed population of mean value μ , variance σ^2 are derived by considering the properties of a sample of size N drawn from this population. The central limit theorem asserts that sample mean \bar{x} is normally distributed with mean μ , variance σ^2/N . The sample standard deviation estimate s has a nearly normal distribution with mean σ , variance $\sigma^2/2$ (N-1). The statistic $\bar{x} \pm ks$ combines the distributions of \bar{x} and s, and by integrating its distribution there can be found the probability γ that $\bar{x} \pm ks$ will encompass the same proportion p of the population as $\mu \pm k_p \sigma$ (k_p is the normal deviate for proportion p). This integration must be performed numerically. Since there are four variables, three of them independent, multi-dimensional interpolation (direct or inverse) may be needed to secure desired results in some cases.

A more convenient form of result is obtained by a Maclaurin series approximation as outlined in [10]. Since only the proportion of the distribution covered by a specified interval is of concern, the population may without loss of generality be standardised with mean $\mu = 0$, variance $\sigma^2 = 1$, having a standard normal distribution function:

$$f(x)=\frac{1}{\sqrt{2\pi}}e^{-\frac{1}{2}x^2}$$

Defining A by:

SANDARY SELVING ACCORD

るというである

$$A = \int \frac{\bar{x} + ks}{\bar{x} - ks} f(x) \, dx$$

Probability Pr is required such that:

$$\Pr\{A \mid p\} = \gamma \tag{3.1}$$

Define r independently of k by:

$$p = \int_{\bar{x}-r}^{\bar{x}+r} f(x) \, dx$$

Because A increases monotonically with ks, the inequality $A \cdot p$ is equivalent to $ks \cdot r$. Since the distributions of \bar{x} and s are independent then:

$$Pr\{A = p : \bar{x}\} = Pr\{ks = r : \bar{x}\}$$

$$= Pr\{(N-1)s^2 = (N-1)\left(\frac{r}{k}\right)^2 : \bar{x}\}$$

 $(N-1)s^2$ has a value distributed as χ^2 for N-1 degrees of freedom so:

$$Pr\{A = p \mid \bar{x}\} = Pr\{X_{N-1}^2 \mid (N-1)\left(\frac{r}{\bar{k}}\right)^2 \mid \bar{x}\}$$

$$(3.2)$$

To obtain the unconditional probability $Pr\{A \mid p\}$, $Pr\{A \mid p \mid \bar{x}\}$ is approximated by the first two terms of a Maclaurin series, noting that odd powers vanish because of symmetry:

$$Pr\{A > p \mid \bar{x}\} = Pr\{A > p \mid 0\} + \frac{\bar{x}^2}{2!} Pr''\{A > p \mid 0\} \dots$$
(3.3)

As indicated \bar{x} has a normal distribution function:

$$f(\bar{x}) = \sqrt{\frac{\bar{N}}{2\pi}} e^{-\frac{1}{2}Nx^2}$$

Total probability is found by integrating over this distribution:

$$Pr\{A \rightarrow p\} = \int_{-\infty}^{\infty} (Pr\{A > p \mid 0\} + \frac{\bar{x}^2}{2!}Pr''\{A > p \mid 0\} \dots)f(\bar{x}) d\bar{x}$$

The conditional probability terms $Pr\{A = p \mid 0\}$ and $Pr''\{A = p \mid 0\}$ within the integral are constant, so integrating $f(\bar{x})$ and its second moment:

$$Pr\{A \rightarrow p\} = Pr\{A \rightarrow p \mid 0\} + \frac{1}{2N}Pr''\{A \rightarrow p \mid 0\} \dots$$
(3.4)

Putting $\bar{x} = 1/\sqrt{N}$ in (3.3):

$$Pr\left\{A - p \mid \frac{1}{\sqrt{N}}\right\} = Pr\{A - p \mid 0\} + \frac{1}{2N}Pr''\{A > p \mid 0\} \dots$$

Comparing with (3.4) gives:

$$Pr\{A \to p\} \approx Pr\left\{A \to p \mid \frac{1}{\sqrt{N}}\right\}$$
(3.5)

Substituting $\bar{x} = 1/\sqrt{N}$ in (3.2):

$$\gamma \approx \Pr\{A \mid p\} = \Pr\{X_{N-1}^2 \mid (N-1)\binom{r}{k}^2 \mid \frac{1}{\sqrt{N}}\}$$
(3.6)

Corresponding values of r and k_p with $\bar{x} = 1/\sqrt{N}$ are found by equating the population fractions of the standard distribution with central and non-central limits (Fig. 1):

$$\int_{-\overline{x}-r}^{\overline{x}+r} f(x) \, dx = \int_{-\overline{k}p}^{\overline{k}p} f(x) \, dx = p$$
(3.7)

Which as Fig. 1 shows is the same as equating the tail areas:

$$= \int \frac{\bar{x} - r}{k_{\rm p}} f(x) \, dx = \int \frac{\bar{x} + r}{k_{\rm p}} f(x) \, dx$$

The integration limits are close together, so the value of f(x) at the upper limits can be approximated by:

$$f(x+h) = f(x)+hf'(x) = (1-hx)f(x)$$

since for the standard normal distribution f'(x) = x f(x). The integrals are estimated by the trapezoidal rule, and neglecting higher order terms, after manipulation there is obtained:

$$r = k_p(1 + \bar{x}^2/2) = k_p(1 + 1/2N)$$
(3.8)

(the latter after substituting $\bar{x} = 1/\sqrt{N}$). When this is used in (3.6) the final result becomes:

$$k = k_{\rm p} \sqrt{\frac{N-1}{x_{\rm y}^2}} \left(1 + 1/2N\right) \tag{3.9}$$

where the value χ_{γ}^2 is exceeded with probability γ in a χ^2 distribution with N-1 degrees of freedom.

Equation (3.9) requires only readily available tables or computer algorithms for normal and χ^2 distributions. [9] verifies that despite the approximations entailed, results of (3.6) are nearly exact (even for values as small as N = 2, if p and γ are high). Comparison of solutions of (3.7) and (3.8) indicates that (3.9) is of similar accuracy if $N \ge 4$.

As an example of the application of (3.9), consider a sample of size N = 6, probability $\gamma = 0.95$, and population fraction p = 0.98 (excludes 1°_{0} extremes). For N = 1 = 5 degrees of freedom χ^{2} exceeds 1.15 at $\gamma = 0.95$, and $k_{p} = 2.326$ at p = 0.98.

$$k = 2.326 \sqrt{\frac{5}{1.15}} \left(1 + \frac{1}{12}\right) = 5.25$$

k is tabulated as a function of N, p and γ in [8]. Figure 2 shows γ vs. p for constant N = 5, and Figs 3, 4 and 5 show k vs. N for various combinations of γ and n. In these plots it is seen that with large sample sizes, k asymptotically approaches Gaussian values $k_{\rm p}$.

3.3 Properties of Frequency Data

The numerical values given in the figures apply to a normally distributed population. As noted, for other distributions numerical values of tolerance limits are changed, but generally not to a serious degree. Some of the effects of probability in the current tests can be suggested from prior knowledge.

Production control of geometric tolerances on blade dimensions would tend to reduce scatter below that of a normal distribution. Geometrical dimensions have a distribution with truncated extreme values, since blades are rejected when dimensions are outside allowable limits. Assuming that various geometrical size variations are independent of one another, and that they add together to affect the blade frequency, the central limit theorem indicates that this cumulative effect (natural frequency) will have a distribution tending more toward Gaussian than the individual contributing effects (geometrical sizes). Even though this tendency accurately represents the central features of shape of the natural frequency distribution, if the number of individual contributing effects is fairly small it will not be accurate at the extreme values which are of concern, and their distribution will remain substantially truncated relative to the Gaussian.

It is also vital to accurate estimation that the sample be random. Bias in the sample selection (e.g. if blades are all drawn from a batch which differs significantly from the population) produces correspondingly biased results, so careful sampling is important. Sampling bias results in a undirectional shift of both range limits, and truncated tolerance distributions a reduction in width of the scatter, so their combined effects tend to cancel one another at one extreme of the range, and to be unduly conservative at the other (i.e. actual scatter limits will be less than estimate).

4. EVALUATION OF RESULTS --- ORIGINAL BLADES

4.1 Campbell Diagrams --- Construction

Interpretation of results is facilitated by presenting data in Campbell diagrams, plotting natural frequency limits vs. rotational speed. To esumate the extent of frequency scatter, a deviation multiplier k in the tolerance limits f + ks was chosen to give a 95% probability of en-

compassing at least 98% of the population (i.e. all except 1% extreme values). For the sample sizes used this gave k values in the region 5-6, and frequency limits based on this criterion are given in Table 3. Figure 2 shows that for the given sample size and chosen deviation multiplier, a greater population proportion is included with lower probability or a lesser proportion with higher probability.

TABLE 3

Frequency Tolerance Limits T55 Compressor — Original Blades

	Frequency Hz Stage 1 Blades Stage 2 Blades			Blades
Mode	Lower	Upper	Lower	Upper
1st Bending	252.4	282	272	304
2nd Bending	1000	1220	920	1092
1st Torsion	1548	1646	1988	2106
3rd Bending	2640	2866	2337	2535
4th Bending		-	4300	4820
2nd Torsion	3945	4589	4517	5227

The frequency scatter limits in Table 3, together with the Southwell coefficients in Table 2 were used in equation (2.1) to produce Campbell diagrams for first and second stage blades, shown in Figs 6 and 7 respectively. The straight lines through the origin indicate the exciting frequency produced when the blade experiences 1, 2, 3, etc. pulses during one revolution.

4.2 Discussion

The plots confirm that the "second order" vibration problem previously mentioned, refers to a possible resonance condition when the blade frequency in the 4st bending mode coincides with excitation at twice engine speed. This will occur in the range 60.78°_{\circ} maximum engine speed (18720 rpm) for first stage or 60.75°_{\circ} maximum rpm for second stage blades. Pending detailed investigation of the magnitude of the second order aerodynamic component, the RAAF was advised to avoid as far as possible operating the engine in the critical speed range [2]. Since the engine power output is relatively low at these speeds, it was fortunately possible to adopt these limitations without hampering the operational effectiveness of the helicopter.

Subsequent detailed investigation of the flow conditions at the compressor inlet showed that with the overlay screens fitted, flow distortion which would generate second order excitation was less than with the standard manufacturer approved screens [3], so the operating restriction could be removed.



FIG. 1 CENTRAL AND NON-CENTRAL LIMITS WITH NORMAL DISTRIBUTION

i.e.



Population fraction p

FIG. 2 TOLERANCE LIMITS

Probability $^{\delta} = 0.9$



AND AND AND AND AND

FIG. 3 TOLERANCE LIMITS

10



FIG. 4 TOLERANCE LIMITS

57250

Ż

Research State



FIG. 5 TOLERANCE LIMITS





FIG. 7 T55 COMPRESSOR ORIGINAL BLADES - STAGE 2

5. WIDE CHORD BLADES

To improve engine performance and alleviate other operating problems including FOD, the engine manufacturer has produced blades of modified design for first and second stages of the compressor. The new design eliminates inlet guide vanes, and provides rotor blades which are mechanically more robust having a considerably wider chord, so they are referred to by this distinguishing feature.

The RAAF propose in due course to fit wide chord blades and this will alleviate the FOD and eliminate any associated vibration problem.

Comprehensive design validation checks were conducted by the manufacturers on the wide chord blades, and they supplied data on vibrational stresses in blades in service, as well as natural frequency data and Campbell diagrams. However to complement the earlier tests and verify the validity of test methods, frequencies were measured on a small sample of blades supplied through the RAAF. Results of frequency measurements for the wide chord blades are given in Table 4, estimated Southwell coefficients are given in Table 5, and frequency tolerance limits are given in Table 6, with Campbell diagrams plotted in Figs 8 and 9.

TABLE 4

Natural Frequencies T55 Compressor — Wide Chord Blades

	Stage 1 Blades		Stage 2	Blades
Mode	Mean Frequency Hz	Standard Deviation	Mean Frequency Hz	Standard Deviation
1st Bending	530	6.09	506	5.17
2nd Bending		_	1800	23.9
1st Edgewise	1819	7.5		
lst Torsion	2265	25 · 2	2628	26 · 3
3rd Bending			5245	77+5
2nd Torsion	5220	36-4	6085	110+5
Chordwise	7380	108		

TABLE 5

Southwell Coefficients T55 Compressor — Wide Chord Blades

	Stage 1	Stage 2
Aspect Ratio Radius Ratio Setting Angle	2·0 1·17 54°	2 · 73 1 · 46 52°
Mode	Southwell	Coefficient
1st Bending 2nd Bending 1st Edgewise 1st Torsion 3rd Bending 2nd Torsion Chordwise	2·35 2·66 2·45 17·9 8·12	$ \begin{array}{r} 2 \cdot 83 \\ 18 \cdot 55 \\ \hline 2 \cdot 96 \\ 52 \cdot 5 \\ 22 \cdot 3 \\ \hline \end{array} $

TABLE 6

Frequency Tolerance Limits T55 Compressor — Wide Chord Blades

	Frequency Hz		ency Hz		
	Stage Blades		. Stage 2 Blades		
MODE	Lower	Upper	Lower	Upper	
lst Bending	495	566	475	537	
2nd Bending	-		1657	1943	
1st Edgewise	1774	1864			
1st Torsion	2113	2417	2470	2786	
3rd Bending			4780	5710	
2nd Torsion	5002	5438	5422	6748	
Chordwise	6732	8028		 	

16



FIG. 8 T55 COMPRESSOR WIDE CHORD BLADES - STAGE 1



1

1 9 1 1 1

FIG. 9 T55 COMPRESSOR WIDE CHORD BLADES --- STAGE 2

18

Summarising these results, the wide chord blades are substantially stiffer with lowest natural frequencies nearly twice those of the original blades. Consequently any possible resonance condition with intake strut disturbances, and with stator wake disturbances, has been eliminated.

Agreement of these results and manufacturer data was very good for lower modes but some discrepancies occurred with the higher modes. These may be due to limitations of the manufacturer's vibration model, or in the experimental techniques employed in this investigation. Difficulties in the experimental area occur in producing the proper conditions of constraint, and in providing appropriate excitation for high modes (a single point excitation was used); an alternative exciter location, or multi-point excitation may have been required for some modes.

The mode designated "Chordwise" in the Stage 1 Blades (Table 3) differs from all other beam type modes encountered. Motion in this mode is mainly normal to the midsurface of the blade so the centre line of the blade section changes shape. Such plate or shell type modes are characteristic of low aspect ratio blades [7].

6 CONCLUSIONS

Tests on first and second stage compressor blades of the T55 engine confirmed that there was a potential resonance condition with second order excitation, and the extent of the resonant speed region was defined. Pending fuller investigation, operation of this region was restricted. Later investigation of inlet flow distortion showed that second order excitation, when fitted with locally designed intake screens, was less than with manufacturer approved equipment, so that no local operating restrictions were necessary.

Scatter in measured frequency values indicated that a frequency tolerance band needed to be established to adequately define the extent of any possible resonance region. As data were derived from small samples the available but infrequently used tolerance limit theory was applied, which provides an estimate of tolerance limits for a given population proportion, and corresponding probabilities. Larger sized samples provide a closer estimate, either as narrower limits, higher population proportion or higher probability, so it is desirable to consider sample size when designing the experiment.

Tests on modified wide chord blades agreed well with the manufacturers design validation data, confirming the validity of experimental techniques used. Since design specifications now require that all new equipment and components should be supported by such data, the need for tests such as reported here should only occur with equipment designed to earlier standard, and is likely to diminish in future.

REFERENCES

- [1] TN006768 from AUSTAIR Washington 8 June 1976.
- [2] C2/03 of 22 June 1976.
- [3] M2/451 of 13 November 1978.
- [4] DOKAINISH, M. A., and RAWTANI, S. (1971).—Vibration Analysis of Rotating Cantilever Plates. Intern. Journ. for Numerical Methods in Engineering, Vol. 3, 1971.
- [5] HENRY, R., and LALANNE, M. (1974).—Vibration Analysis of Rotating Compressor Blades. Trans. ASME Journ. of Engineering for Industry, August 1974.
- [6] BOSSAK, M. A. J., and ZIENKIEWCZ, O. C. (1973).—Free Vibration of Initially Stressed Solids with Particular Reference to Centrifugal Force Effects in Rotating Machinery. Journal of Strain Analysis, Vol. 8, No. 4, 1973.
- [7] PETRICONE, R., and SISTO, F. (1971).—Vibration Characteristics of Low Aspect Ratio Compressor Blades. Trans. ASME Journ. of Engineering for Power, January 1971.
- [8] HALD, A.—Statistical Theory with Engineering Applications. John Wiley, 1952.
- [9] WALD, A., and WOLFOWITZ, J. (1946).—Tolerance Limits for a Normal Distribution. Annals of Mathematical Statistics, Vol. 17, 1946.
- [10] KENDALL, M. G., and STUART, A.—Advanced Theory of Statistics, Vol. 2, Inference and Relationship. Charles Griffin, London, 1973.

DISTRIBUTION

AUSTRALIA

DEPARTMENT OF DEFENCE

Defence Central

Chief Defence Scientist Deputy Chief Defence Scientist Superintendent, Science and Program Administration Controller, External Relations, Projects and Analytical Studies Defence Science Adviser (UK) (Doc. Data sheet only) Counsellor, Defence Science (USA) (Doc. Data sheet only) Defence Science Representative (Bangkok) Defence Central Library Document Exchange Centre, DISB (18 copies) Joint Intelligence Organisation Librarian H Block, Victoria Barracks, Melbourne

Aeronautical Research Laboratories

Director Library Superintendent—Aero Propulsion Divisional File—Aero Propulsion G. Merrington Author: N. Swansson

Materials Research Laboratories

Director/Library

Defence Research Centre

Library

Navy Office

Navy Scientific Adviser RAN Aircraft Maintenance and Flight Trials Unit Directorate of Naval Aircraft Engineering Superintendent, Aircraft Maintenance and Repair

Army Office

Scientific Adviser—Army

Air Force Office

Air Force Scientific Adviser Aircraft Research and Development Unit Scientific Flight Group Library Technical Division Library Director General Aircraft Engineering—Air Force Director General Operational Requirements—Air Force HQ Operational Command (SMAINTSO) HQ Support Command (SLENGO) RAAF Academy, Point Cook

Government Aircraft Factories

Manager Library

DEPARTMENT OF AVIATION

Library

STATUTORY AND STATE AUTHORITIES AND INDUSTRY

Trans-Australia Airlines, Library Qantas Airways Limited SEC of Vic., Herman Research Laboratory, Library Ansett Airlines of Australia, Library Commonwealth Aircraft Corporation, Library Hawker de Havilland Aust. Pty. Ltd., Bankstown, Library Rolls Royce of Australia Pty, Ltd., Mr C. G. A. Bailey

Universities and Colleges

Adelaide	Barr Smith Library
	Professor of Mechanical Engineering
Flinders	Library
La Trobe	Library
Melbourne	Engineering Library
Monash	Hargrave Library
Newcastle	Library
New England	Library
Sydney	Engineering Library
NSW	Physical Sciences Library
	Professor R. A. A. Bryant, Mechanical Engineering
Queensland	Library
Tasmania	Engineering Library
Western Australia	Library
	Associate Professor J. A. Cole, Mechanical Engineering
RMIT	Library

CANADA

International Civil Aviation Organization, Library NRC

Aeronautical & Mechanical Engineering Library Division of Mechanical Engineering, Director

Universities and Colleges

Toronto Institute for Aerospace Studies

CZECHOSLOVAKIA

Aeronautical Research and Test Institute (Prague), Head

FRANCE

ONERA, Library

INDIA

Defence Ministry, Aero Development Establishment, Library Gas Turbine Research Establishment, Director Hindustan Aeronautics Ltd., Library National Aeronautical Laboratory, Information Centre

ISRAEL

Technion-Israel Institute of Technology Professor J. Singer Dr I. T. Bar-Itzhack

JAPAN

National Aerospace Laboratory Institute of Space and Astronautical Science, Library

NETHERLANDS

National Aerospace Laboratory (NLR), Library

NEW ZEALAND

Defence Scientific Establishment, Library RNZAF, Vice Consul (Defence Liaison)

Universities

Canterbury

Library Professor D. Stevenson, Mechanical Engineering

SWEDEN

Aeronautical Research Institute, Library Swedish National Defence Research Institute (FOA)

UNITED KINGDOM

Ministry of Defence. Research, Materials and Collaboration CAARC. Secretary
Royal Aircraft Establishment Bedford. Library
Pyestock North, Director
Admiralty Research Establishment
St Leonard's Hill, Superintendent
National Engineering Laboratory, Library
British Library, Lending Division
GEC Gas Turbines Ltd., Managing Director
Ricardo & Company Engineers (1927) Ltd., Manager
Rolls-Royce Ltd., Aero Division Bristol, Library
British Aerospace
Kingston-upon-Thames, Library
Hatfield-Chester Division, Library British Hovercraft Corporation Ltd., Library Short Brothers Ltd., Technical Library

Universities and Colleges

Bristol Bristol Cambridge

London Nottingham Southampton Strathclyde Cranfield Inst. of Technology Imperial College Engineering Library Library, Engineering Department Whittle Library Professor G. J. Hancock, Aero Engineering Science Library Library Library

UNITED STATES OF AMERICA

NASA Scientific and Technical Information Facility Boeing Vertol United Technologies Corporation. Library Lockheed-California Company Lockheed Missiles and Space Company Lockheed Georgia McDonnell Aircraft Company, Library Avco Lycoming

Aeronautics Library

Universities and Colleges

Florida	Aero Engineering Department
	Professor D. C. Drucker
Johns Hopkins	Professor S. Corrsin. Engineering
Iowa State	Dr G. K. Serovy. Mechanical Engineering
lowa	Professor R. I. Stephens
Princeton	Professor G. L. Mellor, Mechanics
Massachusetts Inst.	
of Technology	MIT Libraries

SPARES (10 copies)

TOTAL (139 copies)

DOCUMENT CONTROL DATA

1. a. AR No.	1. b. Establishment No.	2. Document Date	3. Task No.
AR004046	ARL-AERO-PROP-R-168	September 1985	DST 82/041
4. Title		5. Security	6. No. Pages
INVESTIGATI	ON OF BLADE VIBRATION	a. document	22
T55-L-11C CO	MPRESSOR STAGES 1 AND 2	b. title c. abstract	7. No. Refs
		σ σ	9
O Australia)	——————————————————————————————————————		<u> </u>
N. S. Swansson		9. Downgrading instruc	tions
10. Corporate Auth Aeronautical R	or and Address esearch Laboratories	11. Authority (as appro)	oriate) c. Downgrading
P.O. Box 4331,	Melbourne Vic., 3001.	b. Security	d. Approval
12. Secondary Diet	ibution (of this document)	1	
Approved for p	ublic release		
Overseas enquirers Branch, Departmen	outside stated limitations should be referred to of Defence, Campbell Park, CANBERRA, A	through ASDIS, Defence	Information Services
13. a. This docume	nt may be ANNOUNCED in catalogues and aw	areness services available to	
No limitations			
13. b. Citation for a	other purposes (i.e, casual announcement) may	be (select) unrestricted (or) as for 13 a.
14. Descriptors		· · ·	15. COSATI Group
Vibration	Tolerances (Statistics)		21050
Resonant frequ	ency	2	20110
Forced vibratio	n		
Compressor bla	des		
16. Abstract			
A vibration sur	vey of the first and second stage comp	pressor blades on the	T55-L-11C engine
was conducted f	ollowing the manufacturer's warning th	at the proposed fitting	of locally designed
intake screens i	night lead to blade vibration problems ible surgering service Security and the	. Fibration tests and	a simple analysis
to fully define to	wie resonance region. Special statistic oberance limits for this region and actual	ai mernous jor small blish confidence levels	sampics were used in the limits
Onerators	were initially advised to restrict over	ation in the notential	resonance region

Subsequent intake flow tests demonstrated that the screens generated no abnormal excitation, so the restrictions could be discontinued. This page is to be used to record information which is required by the Establishment for its own use but which will not be added to the DISTIS data base unless specifically requested.

16. Abstract (Contd)

...

「上市はないという」ともあるがあるので、「日本の人物ないの

ries, Melbourne	
19. Cost Code 47 7455	20. Type of Report and Period Cover
	ries, Melbourne

