

AD-A171 154

OPTIMAL REPLACEMENT AGE IN AN IMPERFECT INSPECTION


1/1

MODEL(U) FLORIDA STATE UNIV TALLAHASSEE DEPT OF  
STATISTICS D C HERGE ET AL JUN 86 FSU-STATISTICS-N729  
ARO-23699.4-MA F49620-85-C-0007 F/C 15/3

UNCLASSIFIED

NL

END  
DATE  
FILMED  
0886  
DT-



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

ARO 23699.4-mA

(2)

OPTIMAL REPLACEMENT AGE IN AN  
IMPERFECT INSPECTION MODEL

By

Donna C. Herge, Frank Proschan\*  
and Jayaram Sethuramant

AD-A171 154

FSU-Statistics Report No. M729  
AFOSR Technical Report No. 86-190  
USARO Technical Report No. D-88

June, 1986

The Florida State University  
Department of Statistics  
Tallahassee, Florida 32306-3033

DTIC  
SELECTED  
AUG 26 1986  
S D

400 2 15

\*Research supported by the Air Force Office of Scientific Research under  
Grant Number F49620-85-C-0007.

†Research supported by the U.S. Army Research Office under Grant Number  
DAAL 03-86-K-0094.

The U.S. Government is authorized to reproduce and distribute reprints for  
Government purposes notwithstanding any copyright notation thereon.

Key Words and phrases: Renewal-reward process; imperfect inspection;  
age replacement policy.

DTIC FILE COPY

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited

86 8 20 057

A

Optimal Replacement Age in an  
Imperfect Inspection Model

by

Donna C. Herge, Frank Proschan  
and Jayaram Sethuraman

ABSTRACT

A device is maintained under an age replacement policy. The status of the device (functioning or failed) is known only by inspection at some fixed interval  $k$ . With probability  $q$ , an inspection error may be made, and a functioning unit will be declared to have failed and be replaced by a new unit. On the contrary, when a failed unit is inspected, it is assumed that no inspection error will be made. Assuming that the cost of replacing a failed unit (actually failed or believed failed) is greater than the cost of replacing a functioning unit, we show that we can obtain an optimum replacement age which minimizes  $L(T)$ , the long-run expected cost per unit of time. We find a lower bound for the optimal replacement age and obtain asymptotic and monotonicity properties for  $L(T)$ .

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

I  
CLASSIFIED

## 1. INTRODUCTION

Most of the recent work on maintenance models takes into account additional real-world factors like "minimal" or "imperfect" repair actions. Another relevant factor, imperfect inspection, has not been considered extensively in the literature.

Brown and Proschan (1983) propose several different imperfect maintenance and imperfect inspection models in [3] and study properties of the distribution of the mean time between perfect repairs in [4]. Fontenot and Proschan (1984) then develop optimal policies for several maintenance models based on the imperfect repair model in [4].

The objective of this paper is to develop an optimal replacement policy for an imperfect inspection model. Derman and Sacks (1960) solved the problem of choosing an optimal replacement rule for deteriorating equipment when the amount of deterioration is observed periodically. Perfect inspection was assumed. Barlow, Hunter, and Proschan (1963) showed how to obtain optimum inspection schedules for a broad class of failure distributions in [1]. For an unknown failure distribution, Derman (1961) obtained the minimax schedule assuming that failure has probability  $p > 0$  of being detected by an inspection, and in the absence of failure the unit is replaced at some specified time  $T$ . More recently, Taylor (1975), assuming a cumulative damage model for system failure, found an optimal replacement strategy that minimizes the long-run expected cost per unit of time.

In this paper we are concerned with a device subject to an age replacement policy. We assume that all repair (replacement) actions are perfect and repair time is negligible. The state (functioning or failed) of the device is determined by periodic inspection at a specified interval  $k$ . The failure of a unit remains undetected until the unit is actually inspected. Due to an inspection error

occurring with probability  $q$ , a functioning unit is declared to have failed and is replaced by a new unit. On the contrary, when a failed unit is inspected, no error in inspection occurs.

An inspection error may be due to human error or malfunction of a detection device. Inspection policies are frequently used for safety or security devices. One example is a fire extinguisher which is checked periodically. If the pressure gauge malfunctions, it may erroneously indicate the extinguisher is empty and so the extinguisher is unnecessarily replaced.

It is apparent that an age replacement policy is inappropriate if the underlying failure rate is decreasing. Thus we will assume that the failure rate  $r(t) = f(t)[\bar{F}(t)]^{-1}$  is increasing. We assume that the life distribution  $F$  of the device is absolutely continuous with density  $f$  and  $F(0) = 0$ .

We use the notation  $\bar{F} = 1 - F$ ,  $\bar{F}_i = \bar{F}(i)$ , and  $r_i = r(i)$ .

## 2. FORMULATION AND SOLUTION OF MODEL.

A device has life length  $X$  with distribution  $F$ . The device is installed at time 0, and is inspected at successive times  $k, 2k, \dots$ . When the device is functioning, the probability of no error in inspection is  $p = 1 - q$ . The device is replaced by a new unit at age  $T$ , which is a positive integer multiple of  $k$ , or at the first inspection following failure, whichever comes first. This process is continued indefinitely. Clearly the process renews itself at times of replacement.

The probability that the device is replaced after time  $t = ik$  is  $P[Y > ik] = \bar{F}_{ik} p^i$  for  $i = 0, 1, 2, \dots$ , since the device must survive to time  $ik$  and pass  $i$  inspections. Thus  $Y$  is the observed life length of the device. Note that

$EY = k \sum_{i=0}^{\infty} \bar{F}_{ik} p^i$ . Let  $Z$  be the elapsed time between replacements; then  
 $Z = \min\{Y, T\}$ .

Let  $c_1$  be the cost of an unscheduled replacement (actual or believed failure) and  $c_2$  be the cost of a scheduled (age) replacement. Assume  $c_1 < c_2$ . Our objective is to find the replacement age  $T$  which minimizes  $L(T)$ , the long-run expected cost per unit of time. In Theorem 2.1 we give a formula for  $L(T)$  and in Theorem 2.2 we describe the optimal value of  $T$ . These results are analogous to those found by Fontenot and Proschan (1984) for a modified age replacement model with imperfect repair.

Theorem 2.1

$$L(T) = \frac{c_1 - (c_1 - c_2) \bar{F}_{T-k} p^{\frac{T}{k}-1}}{k \sum_{i=0}^{\frac{T}{k}-1} \bar{F}_{ik} p^i} .$$

Proof: The times of replacement are renewal times in a renewal-reward process whose interarrival distribution is that of  $Z = \min\{Y, T\}$ . From renewal theory, we have that

$$L(T) = \frac{C(T)}{D(T)} ,$$

where  $C(T)$  is the expected cost per renewal cycle and  $D(T)$  is the expected duration of a renewal cycle. Denote the distribution function of  $Y$  by  $G$ . Then

$$\bar{G}(t) = P\{Y > t\} = \bar{F}_{(i-1)k} p^{i-1} \quad \text{for } (i-1)k \leq t < ik \\ \text{and } i = 1, 2, \dots$$

Then the expected length of a cycle is

$$\begin{aligned}
 D(T) = E(Z) &= \int_0^T \bar{G}(t) dt = \sum_{i=1}^{T/k} \int_{(i-1)k}^{ik} \bar{G}(t) dt \\
 &= \sum_{i=1}^{T/k} \bar{F}_{(i-1)k} p^{i-1} \int_{(i-1)k}^{ik} dt = k \sum_{i=0}^{T/k-1} \bar{F}_{ik} p^i.
 \end{aligned}$$

With probability  $\bar{F}_{T-k} p^{T/k-1}$ , the device is replaced after time  $T-k$  and a cost of  $c_2$  is incurred. Otherwise, it is replaced at or before time  $T-k$  and a cost of  $c_1$  is incurred. Therefore the expected cost per cycle is

$$C(T) = c_1(1 - \bar{F}_{T-k} p^{T/k-1}) + c_2 \bar{F}_{T-k} p^{T/k-1}. \quad \square$$

Theorem 2.2. In addition to the assumptions about  $F$  in Section 1, assume that  $r$  is differentiable. Then

$$a. \quad L^*(T) = \bar{F}_{T-k} p^{T/k-1} \left[ k \sum_{i=0}^{T/k-1} \bar{F}_{ik} p^i \right]^{-2} H(T), \quad \text{where}$$

$$H(T) = (c_1 - c_2) \left[ (kr_{T-k} - \log p) \sum_{i=0}^{T/k-1} \bar{F}_{ik} p^i + \bar{F}_{T-k} p^{T/k-1} \right] - c_1.$$

b. An optimal replacement age  $T^*$  exists ( $T^*$  may be infinite) and  $T^* = k$  if and only if  $p \leq \exp\left(\frac{c_2}{c_2 - c_1} + kr_0\right)$ .

c.  $T^*$  is finite if and only if  $r_\infty > \frac{c_1}{(c_1 - c_2)EY} + \frac{1}{k} \log p$ .

d.  $\frac{EY}{k} < \frac{c_1}{c_2}$  implies that  $T^* < \infty$ .

e. A lower bound for  $T^*$  is  $\frac{c_2}{c_1} EY$ .



Proof: a. Differentiate.

b. Given  $c_1 > c_2$  note that  $H$  is increasing since  $r$  is increasing and

$$H'(T) = (c_1 - c_2) k r_{T-k}' \sum_{i=0}^{T-k-1} \bar{F}_{ik} p^i.$$

Then  $T^* = k \Leftrightarrow L$  is increasing  $\Leftrightarrow H(k) \geq 0 \Leftrightarrow (c_1 - c_2)(kr_0 - \log p + 1) - c_1 \geq 0$   
 $\Leftrightarrow p \leq \exp\left(\frac{c_2}{c_2 - c_1} + kr_0\right).$

If  $p > \exp\left(\frac{c_2}{c_2 - c_1} + kr_0\right)$ , then  $H(k) < 0$ . Thus if we can find

$T_0 = \min\{T: H(T) \geq 0\}$ , then  $L'$  is negative on  $(0, T_0 - k)$  and positive on  $(T_0, \infty)$ .

So we choose  $T^*$  such that  $L(T^*) = \min\{L(T_0 - k), L(T_0)\}$ . Otherwise, if there is no  $T$  such that  $H(T) \geq 0$ , then  $L$  is decreasing and  $T^* = \infty$ .

c. The inequality involving  $r_\infty$  implies  $\lim_{T \rightarrow \infty} H(T) > 0$ . Thus the equation

$T_0 = \min\{T: H(T) \geq 0\}$  has a finite solution.

d. Note that  $L(T^*) \leq L(k) = \frac{c_2}{k}$ . If  $T^* = \infty$ , then  $L(T^*) = \frac{c_1}{EY} \leq \frac{c_2}{k}$ . By the contrapositive,  $\frac{EY}{k} < \frac{c_1}{c_2}$  implies that  $T^* < \infty$ .

e. It is easy to show that  $L(T) \geq \frac{c_2}{T}$ . Thus  $(LT)$  must cross  $L(\infty) = \frac{c_1}{EY}$  (if it crosses at all) to the right of the value at which  $\frac{c_2}{T}$  crosses  $\frac{c_1}{EY}$ ; this value is  $T = \frac{c_2}{c_1} EY$ . Therefore, we should schedule replacement at an age greater than  $\frac{c_2}{c_1} EY$ .  $\square$

### 3. Asymptotic and monotonicity properties of $L(T)$ .

If we let  $p = 1$ , we get a desired asymptotic result for  $L(T)$  as the length of the inspection interval,  $k$ , goes to zero. In this case our model reduces to the simple age replacement model for which the optimization problem was solved by Barlow and Proschan (1965), pp. 85 - 90. Since the denominator of  $L(T)$  is a

Riemann sum, it converges to the integral form given in Barlow and Proschan (1965) p. 88, if  $\bar{F}$  is Riemann integrable.

$$\lim_{k \rightarrow 0} L(T) = \lim_{k \rightarrow 0} \frac{c_2 + (c_1 - c_2) F_{T-k}}{\frac{T}{k} - 1} = \frac{c_2 + (c_1 - c_2) F_T}{\int_0^T \bar{F}(x) dx}.$$

If  $0 < p < 1$  we will show that  $L(T) \rightarrow \infty$  as  $k \rightarrow 0$ . This result is expected since more frequent inspections will lead to more units being erroneously replaced.

Case 1. If  $T = k$ , then  $\lim_{k \rightarrow 0} L(k) = \lim_{k \rightarrow 0} \frac{c_2}{k} = \infty$ .

Case 2. If  $T = \infty$ , then  $\lim_{k \rightarrow 0} L(\infty) = \lim_{k \rightarrow 0} \frac{c_1}{EY} = \lim_{k \rightarrow 0} \frac{c_1}{k \sum_{i=0}^{\infty} \bar{F}_{ik} p^i} > \lim_{k \rightarrow 0} \frac{c_1}{k \sum_{i=0}^{\infty} p^i}$

$$= \lim_{k \rightarrow 0} \frac{c_1}{k \left( \frac{1}{1-p} \right)} = \infty.$$

Case 3. If  $k < T < \infty$ , then  $\lim_{k \rightarrow 0} \frac{c_1 - (c_1 - c_2) \bar{F}_{T-k} p^{\frac{T}{k} - 1}}{\frac{T}{k} - 1} > \lim_{k \rightarrow 0} \frac{c_1 - (c_1 - c_2) p^{\frac{T}{k} - 1}}{\frac{T}{k} - 1}$

$$= \lim_{k \rightarrow 0} \frac{c_1 - (c_1 - c_2) p^{\frac{T}{k} - 1}}{k \left( \frac{1-p^{T/k}}{1-p} \right)} = \infty.$$

For a particular value  $p_1$  of  $p$ , we denote  $L_{p_1}(T) = \left[ \frac{c_1 - (c_1 - c_2) \bar{F}_{T-k} p_1^{\frac{T}{k} - 1}}{\frac{T}{k} - 1} \right] / k \sum_{i=0}^{\frac{T}{k} - 1} \bar{F}_{ik} p_1^i$ . Then it is easily seen that  $L_p(T)$  increases as  $p \rightarrow 0$  as follows.

a. Note that  $\bar{F}_{ik} p_1^i \leq \bar{F}_{ik} p_2^i$  for  $p_1 < p_2$ ,  $i = 0, 1, \dots, \frac{T}{k} - 1$ .

Thus  $1/[k \sum_{i=0}^{\frac{T}{k}-1} \bar{F}_{ik} p_1^i] \geq 1/[k \sum_{i=0}^{\frac{T}{k}-1} \bar{F}_{ik} p_2^i]$  for  $T=k, 2k, \dots$ . When  $T > k$ , we have strict inequality above.

b. Note that  $\bar{F}_{T-k} p_1^{\frac{T}{k}-1} \leq \bar{F}_{T-k} p_2^{\frac{T}{k}-1}$  for  $p_1 < p_2$  and  $T=k, 2k, \dots$ . When  $T > k$  we have strict inequality. Thus  $c_1 - (c_1 - c_2) \bar{F}_{T-k} p_1^{\frac{T}{k}-1} \geq c_1 - (c_1 - c_2) \bar{F}_{T-k} p_2^{\frac{T}{k}-1}$ .

From a and b we have  $L_{p_1}(T) = L_{p_2}(T)$  for  $T=k$  and  $L_{p_1}(T) > L_{p_2}(T)$  for  $p_1 < p_2$  and  $T=2k, 3k, \dots$ . This is intuitively reasonable since more mistakes in inspection lead to an increase in unnecessary replacements. This can be seen in Figure 4.10 in the next section. Clearly  $\lim_{p \rightarrow 0} L_p(T) = c_1/k$ .

Since  $L_p(T)$  is a decreasing function of  $p$ , we obtain a sharp lower bound for  $L(T)$  by taking the limit as  $p$  increases to 1. Thus

$$L(T) \geq \lim_{p \rightarrow 1} L_p(T) = \frac{c_1 - (c_1 - c_2) \bar{F}_{T-k}}{\frac{T}{k} - 1} = L_1(T) .$$

$$k \sum_{i=0}^{\frac{T}{k}-1} \bar{F}_{ik}$$

This bound is shown in Figure 4.10.

We denote the optimal value of  $T$  for a particular  $p$  as  $T_p^*$ . Then the optimal long-run expected cost per unit of time is  $L_p(T_p^*) = \min_T L_p(T)$ . Since for all  $T$  we have  $L_{p_1}(T) \geq L_{p_2}(T)$  for  $p_1 < p_2$ , it follows that  $L_{p_1}(T_p^*) = \min_T L_{p_1}(T) \geq \min_T L_{p_2}(T) = L_{p_2}(T_p^*)$ . Thus  $L_p(T_p^*)$  is also a decreasing function of  $p$ . This can be seen in figure 4.10.

#### 4. APPLICATIONS

Our model makes sense only for a failure rate which is increasing. We see from Theorem 2.1 that the denominator of  $L(T)$  is a sum which can be explicitly solved for an exponential distribution  $F$ . Although it is clear that the optimal

policy is to replace only at failure times, because replacing an exponential component by a new component does not change the residual life, we will show that Theorem 2.2 confirms that  $T^* = \infty$ . Let  $\bar{F}(x) = e^{-\lambda x}$ ,  $\lambda > 0$ , and  $k = 1$ .

Then  $EY = \sum_{i=0}^{\infty} \left(\frac{p}{e^\lambda}\right)^i = \frac{1}{1-p/e^\lambda}$ . Setting  $L'(T) = 0$  and solving for  $T$  we get

$$T = 1 + \log \left[ \frac{\left(\frac{c_1}{c_1 - c_2}\right) \left(1 - \frac{p}{e^\lambda}\right) + \log \frac{p}{e^\lambda}}{1 + \frac{p}{e^\lambda} \left(\log \frac{p}{e^\lambda} - 1\right)} \right] / \log \frac{p}{e^\lambda}.$$

Note that  $1 + \frac{p}{e^\lambda} (\log \frac{p}{e^\lambda} - 1) > 0$  since it reduces to the form  $\log x < x - 1$ , which is true for  $x = \frac{e^\lambda}{p} > 1$ . Thus for  $T$  to exist, we need  $\left(\frac{c_1}{c_1 - c_2}\right) \left(1 - \frac{p}{e^\lambda}\right) + \log \frac{p}{e^\lambda} > 0$ , which implies  $\frac{c_1}{c_1 - c_2} > \frac{\lambda - \log p}{1 - p/e^\lambda}$ , which in turn implies  $r_\infty = \lambda < \frac{c_1}{(c_1 - c_2)EY} + \log p$ .

Thus from Theorem 2.2c. we see that  $T^* = \infty$ .

Next we will consider an application of our model to the truncated normal distribution so that we can compare our results to those in Example 1, p. 90, of Barlow and Proschan (1965). "Example 1. Many types of electron tubes used in commercial airline communication equipment and elsewhere tend to have a truncated normal failure distribution (Aeronautical Radio, Inc., 1958). A certain tube used in commercial equipment has a truncated normal failure distribution with a mean life of 9080 hours and a standard deviation  $\sigma$  of 3027. Suppose  $c_1 = \$1100$  and  $c_2 = \$100$ , so that  $c_1/c_2 = 11$ ."

The density  $f(x)$  of the truncated normal distribution may be written as

$$f(x) = \begin{cases} \frac{1}{b\sigma} \psi\left(\frac{x-\mu}{\sigma}\right), & x \geq 0 \\ 0 & \text{otherwise,} \end{cases}$$

where  $\psi(x) = \frac{1}{\sqrt{2\pi}} e^{-x^2/2}$  and  $b = \frac{1}{\sigma} \int_0^{\infty} \psi\left(\frac{x-\mu}{\sigma}\right) dx$ . From  $L'(T) = 0$  we get

$$(2.1) \quad (kr_{T-k} - \log p) \sum_{i=0}^{\frac{T}{k}-1} \bar{F}_{ik} p^i + \bar{F}_{T-k} p^{\frac{T}{k}-1} = \frac{c_1}{c_1 - c_2}.$$

Making the change of variable  $y_0 = \frac{T-k-\mu}{\sigma}$  and defining  $r_N(x) = \frac{\psi(x)}{\int_x^{\infty} \psi(t) dt}$ , we have from (2.1) for a truncated normal distribution  $F$ ,

$$(2.2) \quad K(y_0) = \left(\frac{k}{\sigma} r_N(y_0) - \log p\right) \sum_{i=0}^{\frac{T}{k}-1} p^i \int_{\frac{ik-\mu}{\sigma}}^{\frac{\sigma y_0 + \mu}{\sigma}} \psi(v) dv + p^{\frac{T}{k}-1} \int_{y_0}^{\infty} \psi(v) dv$$

$$= \frac{bc_1}{c_1 - c_2} = b + \frac{bc_2}{c_1 - c_2}.$$

If  $\frac{\mu}{\sigma} \geq 3$ , then  $f(x)$  is very close to the density of a normal distribution with mean  $\mu$  and standard deviation  $\sigma$ .

In Example 1, Barlow and Proschan estimate  $b$  by 1 and use a graph of  $K(y_0) = K(y_0) + b$  for  $\frac{\mu}{\sigma} = 3$  to find  $y_0$ . To obtain more accurate results for comparison with our model, we compute  $b = .9987$  and  $K(y_0) = \frac{bc_2}{c_1 - c_2} = .09987$ . Then  $y_0 = -1.63$  and the optimal replacement age is 4146 hours with an associated minimum cost of  $L(4146) = \$0.036$ .

For our model we consider several examples with various values for  $k$ , the length of the inspection interval, and  $p$ , the the probability of no error in inspecting a functioning unit. Note that for the truncated normal distribution,  $r_{\infty} = \infty$ , so that we know by Theorem 2.2c. that  $T^*$  is finite. Using (2.2) we wish to find the value of  $T$  such that  $K\left(\frac{T-k-\mu}{\sigma}\right)$  is nearest to  $K(y_0) = \frac{bc_1}{c_1 - c_2} = 1.0986$ .

Example 2:  $k = 1000$ ,  $p = .95$ .

Using (2.2) we compute the following values:

T	y	K(y)
1000	-3.00	1.050
2000	-2.67	1.051
3000	-2.34	1.060
4000	-2.01	1.088
5000	-1.68	1.149

FIGURE 4.1: Values of  $K(y)$  for  $k = 1000$ ,  $p = .95$ .




FIGURE 4.1: Values of  $L(T)$  for  $k = 1000$ ,  $p = .95$ .

We see from Figure 4.1 that  $T^* = 4000$  is the optimal value, which gives us the minimum cost  $L(T^*) = \$.0710$  as shown in Figure 4.2. We compute  $EY = 7629$ . Recall from the proof of Theorem 2.2e that  $c_1/EY = .144$  is the horizontal asymptote for  $L(T)$ . Also  $\frac{c_2}{c_1} EY = 694$  is a lower bound for  $T^*$ .

We see from Figure 4.3 that  $T^* = 4000$  is the optimal value and  $L(T^*) = \$.1271$  shown in Figure 4.4. We compute  $EY = 5979$ . Then  $\frac{c_2}{c_1} EY = 544$  is a lower bound for  $T^*$ . Notice in Figure 3.4 that  $\frac{c_2}{k} > \frac{c_1}{EY}$ , thus the implication in Theorem 2.2d cannot be reversed.

Comparing Examples 2 and 3, it is clear that more frequent inspections result in a higher optimal cost  $L(T^*)$ .

We see from Figure 4.5 that the graph of  $K(y)$  does not cross  $K(y_0) = 1.0986$ . Thus there is no solution to  $L'(T) = 0$ , so that  $L' > 0$ , and the cost is strictly increasing, as shown in Figure 4.6. Then the minimum cost is  $\$.10 = L(1000)$  at  $T^* = k$ . This is the expected result from Theorem 2.2b since  $.5 = p \leq \exp\left(\frac{c_2}{c_2 - c_1} + kr_0\right) = \exp[-.1 + 1000(.0000015)] \approx .9062$ . Since  $EY = 1980$ ,  $\frac{c_2}{c_1} EY = 180$  is a lower bound for  $T^*$ .

Just as in Example 4 we see from Figure 4.7 that  $K$  does not cross  $K(y_0) = 1.0986$ , so that cost is strictly increasing and  $T^* = k$  as expected from Theorem 2.2b since  $.5 = p \leq \exp\left(\frac{c_2}{c_2 - c_1} + kr_0\right) = \exp[-.1 + 500(.0000015)] \approx .9055$ .

A lower bound for  $T^*$  is  $\frac{c_2}{c_1} EY = \frac{100}{1100} (998) = 91$ .

Example 3:  $k = 500, p = .95$

T	y	K(y)
3500	-2.01	1.0700
4000	-1.84	1.0916
4500	-1.68	1.1205
5000	-1.51	1.1605

FIGURE 4.3: Values of  $K(y)$  for  $k = 500, p = .95$ .




FIGURE 4.4: Values of  $L(T)$  for  $k = 500, p = .95$ .



Example 4:  $k = 1000, p = .5$

T	y	K(y)
1000	-3.00	1.6923
2000	-2.67	1.5410
3000	-2.34	1.4710
4000	-2.01	1.4490
5000	-1.68	1.4590
6000	-1.35	1.4969

FIGURE 4.5: Values of  $K(y)$  for  $k = 1000, p = .5$ .




FIGURE 4.6: Values of  $L(T)$  for  $k = 1000, p = .5$ .

Example 5:  $k = 500, p = .5$

T	y	K(y)
500	-3.00	1.6915
1000	-2.83	1.5384
1500	-2.67	1.4630
2000	-2.50	1.4260
2500	-2.34	1.4096
3000	-2.17	1.4040
3500	-2.01	1.4042
4000	-1.84	1.4089
4500	-1.68	1.4164

FIGURE 4.7: Values of  $K(y)$  for  $k = 500, p = .5$ .




FIGURE 4.8: Values of  $L(T)$  for  $k = 500, p = .5$ .

We summarize the results as follows:

EXAMPLE	p	k	$\frac{c_2}{c_1} EY_p$	$T_p^*$	$EY_p$	$L_p(T_p^*)$
1	1.00	0	$\frac{c_2}{c_1} \mu = 825$	4146	$\mu = 9080$	\$.036
2	.95	1000	694	4000	7629	\$.071
3	.95	500	544	4000	5979	\$.127
4	.50	1000	180	1000	1980	\$.100
5	.50	500	91	500	998	\$.200

Table 4.9: Summary of Examples.

Asymptotic and monotonicity properties of  $L_p(T)$  are shown in Figure 4.10 for  $k = 1000$ . Optimal values  $L_p(T_p^*)$  are circled. For  $p = .5, .7, \text{ and } .9$  we have  $T_p^* = k = 1000$ . Clearly  $L_p(T_p^*)$  and  $L_p(T)$  are decreasing in  $p$ .  $L_1(T)$  is a sharp lower bound. Horizontal asymptotes are labeled  $L_p(\infty)$ . Lines connecting values of  $L_p(T)$  for a given value of  $p$  were drawn to illustrate the trend of  $L_p(T)$  as  $T \rightarrow \infty$ .




FIGURE 4.10: Asymptotic and monotonicity properties of  $L_p(T)$  for an inspection interval  $k = 1000$  hours, for a truncated normal life distribution.

### References

- [1] Barlow, R.E., Hunter, L.C., and Proschan, F. (1963). Optimum Checking Procedures. J. Soc. Indust. Appl. Math. 11, 1078 - 1095.
- [2] Barlow, R.E. and Proschan, F. (1965). Mathematical Theory of Reliability. John Wiley and Sons, Inc.
- [3] Brown, M. and Proschan, F. (1983). Imperfect Maintenance. IMS Lecture Notes 2, 179 - 188.
- [4] Brown, M. and Proschan, F. (1983). Imperfect Repair. J. Appl. Prob. 20, 851 - 859.
- [5] Derman, C. (1961). On Minimax Surveillance Schedules. Naval Research Logistics Quarterly, 8, 415 - 419.
- [6] Derman, C. and J. Sacks (1960). Replacement of Periodically Inspected Equipment. Naval Research Logistics Quarterly 7, 597 - 607.
- [7] Fontenot, R.A. and Proschan, F. (1984). Some Imperfect Maintenance Models. Reliability Theory and Models, ed. Abdel-Hameed, Çinlar, and Quinn. Academic Press, Inc., 83 - 101.
- [8] Taylor, H.M. (1975). Optimal Replacement Under Additive Damage and Other Failure Models. Naval Research Logistics Quarterly 22, 1 - 18.

ADA171154

REPORT DOCUMENTATION PAGE				
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY NA		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for Public Release, Distribution Unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE NA				
4. PERFORMING ORGANIZATION REPORT NUMBER(S) FSU M 729 USARO D-88 AFOSR 86-190		5. MONITORING ORGANIZATION REPORT NUMBER(S) ARO 23699-4-MA		
6a. NAME OF PERFORMING ORGANIZATION Florida State University	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION AFOSR-NM, USARO		
6c. ADDRESS (City, State and ZIP Code) Department of Statistics Tallahassee, Florida 32306-3035		7b. ADDRESS (City, State and ZIP Code) USARO-Durham AFOSR P.O. Box 12211 Bldg. 410 Research Triangle PK Bolling AFB, DC 20332-6448 N.C. 27709		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR, USARO	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER AFOSR USARO F49620-85-C-0007; DAAL03-86-K-0094		
8c. ADDRESS (City, State and ZIP Code) AFOSR USARO-Durham Bldg. 410 P.O. box 12211 Bolling AFB, DC 20532 N. Carolina 27709		10. SOURCE OF FUNDING NOS.		
		PROGRAM ELEMENT NO. 6.1102F	PROJECT NO. 2304	TASK NO.
				WORK UNIT NO.
11. TITLE (Include Security Classifications) Optimal Replacement Age in an Imperfect Inspection Model				
12. PERSONAL AUTHOR(S) D.C. Herge, F. Froshan, and J. Sethuraman				
13a. TYPE OF REPORT Technical	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Yr., Mo., Day) June, 1986	15. PAGE COUNT 17	
16. SUPPLEMENTARY NOTATION				
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB. GR.		
			Renewal-reward process; imperfect inspections; age replacement policy.	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)  A device is maintained under an age replacement policy. The status of the device (functioning or failed) is known only by inspection at some fixed interval $k$ . With probability $q$ , an inspection error may be made, and a functioning unit will be declared to have failed and be replaced by a new unit. On the contrary, when a failed unit is inspected, it is assumed that no inspection error will be made. Assuming that the cost of replacing a failed unit (actually failed or believed failed) is greater than the cost of replacing a functioning unit, we show that we can obtain an optimum replacement age which minimizes $L(T)$ , the long-run expected cost per unit of time. We find a lower bound for the optimal replacement age and obtain asymptotic and monotonicity properties for $L(T)$ .				
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS <input type="checkbox"/>		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL Frank Proshan/Jayaram Sethuraman		22b. TELEPHONE NUMBER (Include Area Code) (904) 644-3218	22c. OFFICE SYMBOL AFOSR/NM USARO	

ATE  
LMED  
=8