



「大きないの」

.

1.2.2.2.1

THE REPORT OF THE PARTY OF THE



ENVIRONMENTAL IMPACT RESEARCH PROGRAM

TECHNICAL REPORT EL-86-8

GALLINACEOUS GUZZLERS

Section 5.4.1, US ARMY CORPS OF ENGINEERS WILDLIFE RESOURCES MANAGEMENT MANUAL

by

Ted Johnson

Washington Department of Game Walla Walla, Washington 99362

and

Ruth A. (Wilson) Jacobs

US Army Engineer District, Portland PO Box 2946, Portland, Oregon 97208-2946



106

106

26

Approved For Public Release, Distribution Unlimited

Prepared for DEPARTMENT OF THE ARMY US Army Corps of Engineers Washington, DC 20314-1000 Under EIRP Work Unit 31631 Destroy this report when no longer needed. Do not return it to the originator.

.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products. Unclassified SECURITY CLASSIFICATION OF THIS PAGE

.

AD-A11437

| | TION PAGE | | | OMB No: 0704-0188 Exp: Date: Jun 30, 198 |
|--|--|--|---|--|
| a REPORT SECURITY CLASSIFICATION Unclassified | 16 RESTRICTIVE | MARKINGS | · · · · · · | |
| 2a SECURITY CLASSIFICATION AUTHORITY | 3 DISTRIBUTION | V / AVAILABILIT | Y OF REPORT | |
| | Approve | d for publ | ic release | e; distributio |
| | unlimit | | | _, |
| PERFORMING ORGANIZATION REPORT NUMBER(S) | 5 MONITORING | ORGANIZATIO | N REPORT NUN | ABER(S) |
| | Technic | al Report | EL-86-8 | |
| a NAME OF PERFORMING ORGANIZATION 66. OFFICE SYMI | | IONITORING O | RGANIZATION | |
| Washington Department of Game; (If applicable USAED, Portland | COMUNED | mental Lab | oratory | |
| c. ADDRESS (City, State, and ZIP Code) | 7b. ADDRESS (C | | | |
| Walla Walla, WA 99362 | PO Box | 631 | | |
| PO Box 2946, Portland, OR 97208 | | | sippi 391 | 180-0631 |
| Ba. NAME OF FUNDING/SPONSORING Bb. OFFICE SYMI ORGANIZATION (If applicable | | IT INSTRUMENT | DENTIFICATIO | ON NUMBER |
| US Army Corps of Engineers | | | | |
| c. ADDRESS (City, State, and ZIP Code) | 10. SOURCE OF | FUNDING NUN | IBERS | WORK UNIT |
| Washington, DC 20314-1000 | ELEMENT NO. | NO. | NO. | ACCESSION N |
| | | 1 | | EIRP 316 |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) 3a TYPE OF REPORT 13b TIME COVERED Final report FROM TO | 14 DATE OF REP July | 1986 | | PAGE COUNT 23 |
| | 14 DATE OF REP July | 1986 | | 23 |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) 13. TYPE OF REPORT Final report 13. TIME COVERED FROM TO 14. SUPPLEMENTARY NOTATION Available from National Technical Informat VA 22161. 15. SUBJECT TE 18. SUBJECT TE | 14 DATE OF REP July | 1986 85 Port Ro rse if necessary | yal Road, | 23 Springfield, y block number) |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) 13a TYPE OF REPORT Final report 13b TIME COVERED FROM TO 16 SUPPLEMENTARY NOTATION Available from National Technical Informat VA 22161. 17 COSATI CODES FIELD GROUP SUB-GROUP Guzzler Gallinac | 14 DATE OF REP July ion Service, 528 RMS (Continue on rever ceous guzzler | 1986 85 Port Ro rse if necessary Wild | yal Road, | 23 Springfield, |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) Jarvee OF REPORT Final report SUPPLEMENTARY NOTATION Available from National Technical Informat VA 22161. TO COSATI CODES FIELD GROUP SUB-GROUP SUB-GROUP SUB-GROUP A management techniques report on ga of the US Army Corps of Engineers Wildling prepared as a guide to assist Corps biol implementing artificial watering systems factor. Topics covered include habitat co lation, fencing, maintenance, personnel evaluation. The gallinaceous guzzler is a permane habitat conditions for wildlife in arid and formica), Gambel's quail (C. gambelii), chukar), ring-necked pheasant (Phasianus co | 14 DATE OF REP July 10n Service, 528 RMS (Continue on rever ceous guzzler Nock number) 111naceous guzz fe Resources Ma logists and res for wildlife w considerations, and costs, ent self-filling d semiarid region ords such as Ca scaled quail (<i>plchicus</i>), and m | 1986 35 Port Ro 35 Port Ro Wild: (Cont lers is pr nagement is ource man. there wate design and cautions g watering ons. The alifornia (C. squame. | yal Road, and identify b life water tinued) covided as Manual. T agers in a r supply d constru- and lim device us technique quail (<i>Ca</i> <i>ita</i>), chuid dove (<i>Zena</i> | 23 Springfield, y block number) ing devices Section 5.4. The report wa developing an is a limitin ction, instal itations, an sed to improv is appropriat <i>lipepla cali</i> kar (Alectori |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) Ja TYPE OF REPORT Final report 6 SUPPLEMENTARY NOTATION Available from National Technical Informat VA 22161. 7 COSATI CODES FIELD GROUP 9 ABSTRACT (Continue on reverse if necessary and identify by the A management techniques report on ga. of the US Army Corps of Engineers Wildling prepared as a guide to assist Corps biol implementing artificial watering systems factor. Topics covered include habitat co lation, fencing, maintenance, personnel evaluation. The gallinaceous guzzler is a permane habitat conditions for wildlife in arid and formica), Gambel's quail (C. gambelii), chukar), ring-necked pheasant (Phasianus co | 14 DATE OF REP July 10n Service, 528 RMS (Continue on rever ceous guzzler Nock number) 111naceous guzz fe Resources Ma logists and res for wildlife w considerations, and costs, ent self-filling d semiarid region birds such as Ca scaled quail (<i>olchicus</i>), and m | 1986 35 Port Ro 35 Port Ro Wild: (Cont lers is pr nagement is ource man. there wate design and cautions g watering ons. The alifornia (C. squame. | yal Road, and identify by life water tinued) covided as Manual. T agers in a r supply id constru- and lim device us technique quail (<i>Ca</i> <i>sta</i>), chuk dove (<i>Zena</i> | 23 Springfield, y block number) ing devices Section 5.4. The report wa developing an is a limitin ction, instal itations, an sed to improv is appropriat <i>llipepla cali</i> kar (<i>Alectori</i> |
| Johnson, Ted, and Jacobs, Ruth A. (Wilson) Jarype OF REPORT Final report Supplementary NOTATION Available from National Technical Informat VA 22161. COSATI CODES FIELD GROUP SUB-GROUP SUB-GROUP SUB-GROUP A management techniques report on ga of the US Army Corps of Engineers Wildling prepared as a guide to assist Corps biol implementing artificial watering systems factor. Topics covered include habitat co lation, fencing, maintenance, personnel evaluation. The gallinaceous guzzler is a permane habitat conditions for wildlife in arid and for habitat management programs for game b formica), Gambel's quail (C. gambelii), chukar), ring-necked pheasant (Phasianus co | 14 DATE OF REP July 10n Service, 528 RMS (Continue on rever ceous guzzler Nock number) 111naceous guzz fe Resources Ma logists and res for wildlife w considerations, and costs, ent self-filling d semiarid region birds such as Ca scaled quail (<i>olchicus</i>), and m | 1986 35 Port Ro se if necessary Wildi (Consi- lers is pro- nagement in ource man- there water design and cautions g watering ons. The alifornia (C. squame hourning of ECURITY CLASS classified | yal Road, and identify by life water tinued) rovided as Manual. T agers in a r supply id constru- and lim device us technique quail (<i>Ca</i> <i>ita</i>), chui dove (<i>Zena</i> | 23 Springfield, y block number) ing devices Section 5.4. The report wa developing an is a limitin ction, instal itations, an sed to improv is appropriat llipepla cali car (Alectori ida macroura) |

1.00

V

1 . 6 . . .

 $(-,t)^{\alpha}$

18. SUBJECT TERMS (Continued).

Water management Cistern Upland game birds Gallinaceous birds

Habitat development Habitat management Wildlife management Management practices and techniques

19. ABSTRACT (Continued).

>as well as game mammals and certain nongame species. The guzzler described in this report is used extensively by the Washington State Department of Game and the US Army Engineer District, Walla Walla, and consists basically of a fiberglass cistern and a galvanized metal collecting apron. Details are given on the design, construction, installation, and maintenance of the guzzler, and specification drawings and lists of materials required are provided. Guidelines are presented on the application of guzzlers as part of a broader habitat management program in which food, cover, and water conditions are improved and properly interspersed.

| Accession For |
|---------------------|
| NTIS GRAZI |
| DTIC TAB |
| Upang supped 🛛 🔲 |
| Justification |
| By |
| Distribution/ |
| Availar liter Jodes |
| Aveil snd/or |
| Dist Special |
| A-1 |

07,_C '0₀,

PREFACE

This work was sponsored by the Office, Chief of Engineers (OCE), US Army, as part of the Environmental Impact Research Program (EIRP), Work Unit 31631, entitled Management of Corps Lands for Wildlife Resource Improvement. The Technical Monitors for the study were Dr. John Bushman and Mr. Earl Eiker, OCE, and Mr. Dave Mathis, Water Resources Support Center.

This report was prepared by Mr. Ted Johnson, Washington Department of Game, Walla Walla, Wash., and Ms. Ruth A. (Wilson) Jacobs, US Army Engineer District, Portland, Portland, Oreg., under an Interagency Agreement with the US Army Engineer Waterways Experiment Station (WES). Mr. Chester O. Martin, Team Leader, Wildlife Resources Team, Wetlands and Terrestrial Habitat Group (WTHG), Environmental Laboratory (EL), WES, was principal investigator for the work unit. The authors wish to express appreciation to District biologists of the US Army Engineer Division, North Pacific (NPD), for their contributions and review of this report. Mr. E. Paul Peloquin, Division Wildlife Biologist, NPD, was instrumental in providing guidance and review. Design and construction specifications were provided by Mr. Blaise Gradine, US Army Engineer District, Walla Walla. The authors' experience and input from Mr. James R. Kosciuk and Mr. Lonnie E. Mettler, US Army Engineer District, Walla Walla, were the sources of information on costs and man-hours. Technical review was also provided by Mr. Martin, WTHG; Dr. Wilma A. Mitchell, WTHG; and Mr. Larry R. Marcy, Texas A&M University.

The report was prepared under the general supervision of Dr. Hanley K. Smith, Chief, WTHG, EL; Dr. Conrad J. Kirby, Chief, Environmental Resources Division, EL; and Dr. John Harrison, Chief, EL. Dr. Robert T. Saucier, WES, was Program Manager, EIRP. The report was edited by Ms. Jessica S. Ruff of the WES Publications and Graphic Arts Division (PGAD). Drawings were prepared by Mr. John R. Harris, Scientific Illustrations Section, PGAD, under the supervision of Mr. Aubrey W. Stephens, Jr.

At the time of publication, COL Allen F. Grum, USA, was Director of WES, and Dr. Robert W. Whalin was Technical Director.

This report should be cited as follows:

Johnson, Ted, and Jacobs, Ruth A. (Wilson). 1986. "Gallinaceous Guzzlers: Section 5.4.1, US Army Corps of Engineers Wildlife Resources Management Manual," Technical Report EL-86-8, prepared by the Washington Department of Game, Walla Walla, Wash., and US Army Engineer District, Portland, Portland, Oreg., for the US Army Engineer Waterways Experiment Station, Vicksburg, Miss.

NOTE TO READER

This report is designated as Section 5.4.1 in Chapter 5 -- MANAGEMENT PRACTICES AND TECHNIQUES, Part 5.4 -- WATER DEVELOPMENTS, of the US ARMY CORPS OF ENGINEERS WILDLIFE RESOURCES MANAGEMENT MANUAL. Each section of the manual is published as a separate Technical Report but is designed for use as a unit of the manual. For best retrieval, this report should be filed according to section number within Chapter 5.

GALLINACEOUS GUZZLERS

Section 5.4.1, US ARMY CORPS OF ENGINEERS WILDLIFE RESOURCES MANAGEMENT MANUAL

| HABITAT CONSIDERATIONS | 4 | MAINTENANCE |
|-------------------------|----|-----------------------------|
| DESIGN AND CONSTRUCTION | 5 | PERSONNEL AND COSTS 13 |
| The Cistern | 5 | CAUTIONS AND LIMITATIONS 14 |
| Collecting Apron | 8 | EVALUATION 14 |
| INSTALLATION | 11 | LITERATURE CITED |
| FENCING | 12 | APPENDIX |
| | | |

The gallinaceous guzzler is a permanent self-filling watering device used to improve habitat conditions for animals in arid and semiarid regions. The first guzzler was developed by Ben Glading, California Department of Fish and Game, for use by California quail (*Callipepla californica*); thus, the device was christened "Glading's Gallinaceous Guzzler" (Glading 1947, Edminster 1954). Since its conception the device has gained wide acceptance, and its application has broadened to include management for many other game birds such as Gambel's and scaled quail (*C. gambelii* and *C. squamata*), chukar (*Alectoris chukar*), ring-necked pheasant (*Phasianus colchicus*), and mourning dove (*Zenaida macroura*), as well as game mammals and certain nongame species (Galbreath and Moreland 1953, Edminster 1954, Yoakum et al. 1980).

The guzzler described in this report is used extensively by the Washington State Department of Game and the U.S. Army Engineer (USAE) District, Walla Walla, and consists basically of a fiberglass cistern and a galvanized metal collecting apron (Fig. 1); it is designed primarily for bird use but may also provide water for small mammals. Depending on availability of materials and labor, other designs or materials may be preferred. Refer to USDA Forest Service (1969) and Yoakum et al. (1980) for alternate designs.



Figure 1. Gallinaceous guzzler installed for game bird use (photo compliments of Ted Johnson, Washington Department of Game)

HABITAT CONSIDERATIONS

The success of a habitat management program involving installation of a gallinaceous guzzler depends on (1) the condition of water, food, and cover within the managed area, and (2) the behavioral or physiological characteristics of a species that govern its use of an open water supply. If there is adequate food and cover, provision of water may he all that is needed to entice animals to occupy an area or to enhance production or survival of existing populations. If conditions are inadequate, a guzzler may be provided as part of a "guzzler complex" in which food, cover, and water conditions are improved.

Several basic principles should be considered when assessing the adequacy of existing habitat to meet an animal's needs or when planning habitat improvements: (1) food and water supplies should generally be close to cover; (2) several smaller areas that supply all of an animal's needs are usually better than one large area; and (3) a diversity of plant species and growth forms attracts a greater variety of animals and provides more consistent food and cover for the target species (Burger 1973). These concepts should be considered when including guzzlers as part of a management program. Appropriate vegetation and distances between food, cover, and water will vary regionally and according to target species.

The appendix at the end of this section provides basic information on water requirements, movement patterns relative to water, and use of guzzlers for the scaled quail, Gambel's quail, California quail, mountain quail (*Oreortyx pictus*), gray partridge (*Perdix perdix*), chukar, ring-necked pheasant, blue grouse (*Dendragapus obscurus*), sage grouse (*Centracercus urophasianus*), and turkey (*Meleagris gallopavo*). The information given in the table is intended only as a summary and does not apply to all situations; therefore, regional game specialists should be consulted for site-specific requirements.

DESIGN AND CONSTRUCTION

The guzzler described in detail below has 2 major features: (1) a concave cistern set in the ground, and (2) a double-section apron with inner sloping surfaces that sits above the cistern on wooden supports and collects precipitation for the cistern. Animals gain access to the water through an opening in the cistern and walk down to the water's edge via a ramp attached to the cistern's lid. The guzzler is functional, durable, easily constructed and installed, highly resistant to damage by livestock and big game animals, and requires little maintenance.

The Cistern

The guzzler cistern is prefabricated commercially and consists of a fiberglass tank and a removable reinforced fiberglass lid and ramp. Most companies that manufacture fiberglass products should be able to construct the cistern by following the plans and specifications provided in Figures 2-4.

<u>Cistern tank</u>. The tank is a concave bowl constructed entirely of fiberglass. Specifications provided in Figure 2 are for a 500-gal tank, but larger or smaller tanks can be constructed by modifying the design. Larger capacity tanks may be desirable to make water available for other uses such as fighting range fires, irrigating plantings, or providing drinking water for big game. Dimensions and thickness of the fiberglass parts shall be no less than 3/16 in. in thickness and $\pm 1/2$ in. in any dimension. The form of fiberglass



casting to be used is hand-laid matting; casting the fiberglass with a chopper gun instead of hand-laid matting is cheaper but is not recommended because the fiberglass application is not uniform, air pockets may form, and the overall construction is weaker.



Figure 2. Construction details for commercially inbricated fiberglass cistern tank for a gallinaceous guzzler (after USACE 1979)





Nations

.

Figure 3. Construction details for commercially fabricated cistern lid and ramp for a gallinaceous guzzler (after USACE 1979)

10.100



Figure 4. Construction detail for guzzler tank and lid connection (after USACE 1979)

Lid and ramp. The lid covers the tank and provides access to water stored within the tank via an attached ramp. The lid is also prefabricated of fiberglass, with the color and form of casting usually the same as the tank (Fig. 3). Encapsuled wood or thickened fiberglass parts are included for strength to minimize damage if large animals walk across the lid. The lid fits snugly to the top of the tank (Fig. 4) and can be removed for cleaning and repairs.

<u>Cistern molds</u>. Most fiberglass companies can manufacture the cistern molds by following specifications provided in Figures 3 and 4. In the USAE Division, North Pacific, the forms are owned by the Government but are stored at a local fiberglass company. The forms are thereby available to USAE Districts or cooperating agencies that order cisterns from that company. Similar arrangements could be made by other USAE Districts and Divisions on a regional basis for availability and storage of molds. Fiberglass manufacturers should be advised that curing cisterns at too rapid a rate, which can occur with high ambient temperatures, may damage the molds and products.

Collecting Apron

The collecting apron is made of sheets of corrugated galvanized metal roofing nailed to a set of wooden frames (Fig. 5, Table 1). The lumber should be stained with wood preservative to prevent splitting and dry-rot. The frames are 4 ft wide and made of $2- \times 4-in$. lumber nailed together at the corners. Framing anchors are attached to the corners of each frame to hold 90-deg angles and prevent joint expansion. The frames can be prefabricated



Table 1. Materials needed to build 1 gallinaceous guzzler collecting apron. Lengths of 2- × 4-in. lumber for sides of frame and roofing will vary depending on rainfall and size of cistern

| Item | Quantity |
|--|---------------|
| Lumber | |
| $4- \times 4$ -in. $\times 4$ -ft pressure-treated wooden post | 8 |
| or 4-ft round cedar post split in half | 4 or 8 halves |
| $2- \times 4-in. \times 8-ft$ lumber | 4 |
| $2- \times 4-in. \times 4-ft$ lumber | 10 |
| Roofing | |
| 28-ga corrugated galvanized roofing, | 4 sections, |
| 26 in. wide | 8 ft long |
| Hardware | |
| #16 galvanized nails | 50 |
| Galvanized roofing nails | 60 |
| $1/2- \times 5-1/2$ -in. galvanized bolts | 8 |
| 1/2-ir. galvanized flat washer | 16 |
| 1/2-in. galvanized lock washer | 8 |
| 4-in. \times 4-ft strip 1/4-in. mesh hardware cloth | 1 |
| Galvanized framing anchors | 8 |
| Wood preservative | lqt |

and transported to the installation site intact. They are then bolted to wooden posts and oriented opposite each other above the cistern. The long axis of each frame is perpendicular to the long axis of the ramp, and the inside surfaces of the apron sections slope downward toward the ramp.

Two sheets of corrugated roofing, each 26 in. wide, are fastened to each frame to form the collecting surface. Thus, 4 sections of roofing are needed for each guzzler unit. Water flows from the apron sections onto the ramp and down into the tank. With this design, the apron also shades the cistern; additional sections can be added near a guzzler to provide shade for animals coming to drink.

The length of each apron section is a function of the area of collection surface needed to fill the cistern. The required surface area is a function of both the minimum annual precipitation expected at the installation site and the water capacity of the cistern. The area of a collecting surface can be calculated as follows (Yoakum et al. 1980):

Capacity of cistern (gal) × 1.6 Area (sq ft) = Minimum level of rainfall (in.)

For example, a 500-gal cistern in an area with a minimum of 13 in. of rainfall would need a collecting surface approximately 62 sq ft. This surface area could be achieved with two 8- by 4-ft rectangular apron sections, an 8-ft square apron, or a circular apron with a diameter of 9 ft. Appropriate lengths of the 4-ft-wide corrugated roofing sections previously described are listed in Table 2. Information on precipitation levels is available in the U.S. Department of Commerce publication "Climates of the States." A separate publication is available for each State and can be ordered from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Reported levels of precipitation include rainfall and melted snowfall.

INSTALLATION

To install the cistern, first excavate a hole for inserting the tank; this may be done manually or with a backhoe. Compact and shape the soil on the sides and bottom of the hole to provide maximum support and contact area for the floor and walls of the cistern. In rocky areas the hole should be overexcavated and backfilled with sand or silt. The cistern is set into the hole, and any remaining space around the cistern's outside walls is filled with soil. The ground around the guzzler should be sloped to prevent silt and debris from being washed into the cistern. When the cistern is in place, the rim of the tank should be level and not more than 1 in. above the adjoining ground so that the lid will fit tightly over the tank. The lid is then placed over the top of the cistern.

The apron is situated above the cistern as shown in Figure 5. The steps below should be followed for ease of installation:

- Hold prefabricated frame over cistern and mark locations of posts. The frames should be centered above the ramp opening with 2 in. of clearance between sections.
- (2) Dig holes and position posts nearest cistern to a depth that will allow 1 ft of clearance between the cistern lid and bottom of each frame.
- (3) Dig holes and position posts farthest from cistern to a depth that will create a 5% slope to the apron surfaces.
- (4) Drill holes for bolting frame to posts.
- (5) Bolt frames to posts; use flat and lock washers.



| Minimum Annual Precipitation, in. | Length, ft* | Potential Annual Water Yield, gal |
|--------------------------------------|-------------|--------------------------------------|
| 1 | 100 | 490 |
| 2 | 50 | 490 |
| 3 | 34 | 500 |
| 4 | 26 | 510 |
| 5 | 20 | 500 |
| 6 | 13 | 530 |
| 7 | 14 | 480 |
| 7 | 16 | 550 |
| 8 | 12 | 470 |
| 8 | 14 | 550 |
| 9 | 12 | 530 |
| 10 | 10 | 490 |
| 11 | 10 | 540 |
| 11 | 8 | 430 |
| 12 | 10 | 590 |
| 12 | 8 | 470 |
| 13 | 8 | 510 |
| 14 | 8 | 550 |
| 15 | 8 | 590 |
| 16 | 8 | 630 |
| 17 | 6 | 500 |
| 18 | 6 | 530 |
| 19 | 6 | 560 |

Table 2. Suggested lengths of wooden frames and corrugated roofing for a set of collecting aprons to achieve annual water yields under various levels of minimum annual precipitation (modified from Washington Department of Game (unpublished data) and Yoakum et al. 1980)

Four sheets of roofing of equal length are used for a set of collecting aprons.

(6) Nail a strip of hardware cloth between sections of the apron.

(7) Nail sheets of galvanized roofing to frames.

Guzzlers are installed before the major rainfall period to ensure proper filling. Where heavy freezing occurs it may be desirable to install apron supporting posts that extend below the frost line so frost heave will not disturb the apron.

FENCING

Guzzlers are often fenced to minimize damage caused by livestock or big game animals walking on the cistern or rubbing the apron supports. Fencing can also protect native vegetation or plantings around a guzzlei from overgrazing (Emlen and Glading 1945). Fences should have gates to allow access for maintenance, and fence posts should be pointed to discourage perching by avian predators (USDA Forest Service 1969). Refer to Part 5.2 of this manual, Fences and Crossings, for specifications on a variety of fence designs.

MAINTENANCE

Guzzlers should be checked at least once a year. Debris such as sticks or leaves can be removed from the cistern via the ramp or by lifting the lid. A pump or siphon can be used to remove algae or silt. Fiberglass mat and epoxy resin can be used to patch holes in the cistern. Vegetation around the opening of the ramp should be cut back so that the ramp opening is not obscured. The collection surface can be increased by adding apron sections. With proper care, guzzlers can have an average life expectancy of 30 to 40 years.

PERSONNEL AND COSTS

The list of materials in Table 1 can be used to compute current costs of a guzzler. Cost of prefabricated cisterns (tanks and lids) purchased by the Yakima Firing Center, Washington, in 1981 was \$650 per unit (U.S. Army 1981). Reusable molds for fabricating cisterns were purchased in 1978 by the U.S. Army Engineer District, Walla Walla, for \$580 per unit.

From 3 to 17 man-hours are needed for guzzler construction and installation (not including time for commercial fabrication of the cistern and for travel to and from the installation site). The breakdown of the effort is: (1) 0.5 hour for constructing a set of wooden apron frames, (2) 0.25 hour for measuring and cutting corrugated roofing, (3) 0.25 hour for digging the hole if a backhoe is used, or 3 to 12 man-hours (i.e., 2 people each working 1.5 to 6 hours) if the hole is dug by hand, and (4) 2 to 4 hours for installation of the apron and cistern (2 people each working 1 to 2 hours). Fencing and plantings are an additional investment that must be calculated separately. Inspection and repair of a guzzler excluding fencing, plantings, and travel time will require from 0.5 to 4 man-hours.

CAUTIONS AND LIMITATIONS

Guzzlers should not be located in washes or gullies because of possibilities of flooding or siltation, and hard ground should be avoided as much as possible. The opening of a cistern should face opposite to prevailing winds and in a direction that minimizes exposure of the water to sunlight. Also, the collecting apron should not be overhung by branches that could interfere with interception of water and drainage.

As discussed earlier, food, water, and cover conditions must be evaluated at a site prior to guzzler installation. Campbell (1960) reported a situation where guzzlers were placed in areas of summer precipitation in New Mexico to improve conditions for production of Gambel's and scaled quail. However, broods dispersed to feed on succulent vegetation available in the summer and did not require open water to survive. On the average, only slightly over half the guzzlers were used by quail, and use was limited. Consequently, an expensive program was not justified in terms of increased production of young (Campbell 1960). This example is not provided to discourage consideration of use of a guzzler; rather, it is meant to emphasize the importance of evaluating an animal's needs and the ability of existing habitat to meet these needs before embarking on a program of guzzler installation.

Stocking programs are generally unnecessary to establish populations around a guzzler unless the desired species is absent and prevented from occupying the installation site due to existing barriers (Emlen and Glading 1945, Leopold 1977). For example, California quail 1 to 2 miles from a guzzler will find and use the water supply, although up to 3 years may be needed to attain maximum use (Edminster 1954). Despite attempts to improve habitat conditions, populations may be limited by terrain features or climatic extremes (MacGregor 1953) or by behavioral traits of a species, such as wide dispersion patterns. If such limitations occur, the decision to continue a guzzler program should be based on benefits to all species in an area, rather than those originally targeted for management.

EVALUATION

Guzzlers should be evaluated to determine animal use and impact on populations of target species. Direct observations of numbers and species, including animal sign. around the guzzler will provide basic information on



use. Determining impacts on population growth of target species may be difficult because the presence of animals at a guzzler site could reflect a concentration of surrounding populations rather than increases in a local population (Hungerford 1960).

Data collected on population or production levels within the managed area (the maximum radius of an animal's movement from the guzzler site) will determine whether specific management goals or mitigation requirements are being met; these data should be compared to a control area beyond the radius of movement. Relative or absolute data derived from variable circular plot censusing, flush or call counts, or nest searches (Overton 1971, Reynolds et al. 1980) can be used for this level of evaluation.

LITERATURE CITED

Burger, G. V. 1973. Practical Wildlife Management. Winchester Press, New York. 218 pp.

Campbell, H. 1960. An evaluation of gallinaceous guzzlers for quail in New Mexico. J. Wildl. Manage. 24:21-26.

, D. K. Martin, P. E. Ferkovick, and B. K. Harris. 1973. Effects of hunting and some other environmental factors on scaled quail in New Mexico. Wildl. Monogr. 34. 49 pp.

Dalke, P. D., D. B. Pyrah, D. C. Stanton, J. E. Crawford, and E. F. Schlatterer. 1963. Ecology, productivity and management of sage grouse in Idaho. J. Wildl. Manage. 27:811-841.

- Edminster, F. C. 1954. American Game Birds of Field and Forest. Charles Scribner and Sons, New York. 490 pp.
- Emlen, J. T., Jr., and B. Glading. 1945. Increasing valley quail in California. Calif. Agric. Exp. Sta. Bull. 695. 56 pp.

Galbreath, D. S., and R. Moreland. 1953. The chukar partridge in Washington. Wash. Dep. Biol. Bull. 11. 54 pp.

- Glading, B. 1947. Game watering devices for the arid Southwest. Trans. N. Am. Wildl. Conf. 12:286-292.
- Hannon, S. J., L. G. Sopuck, and F. C. Zwickel. 1982. Spring movements of female blue grouse: Fvidence for socially induced delayed breeding in yearlings. Auk 99:687-694.
- Hanson, L. E., and D. R. Progulske. 1973. Movements and cover preferences of pheasants in South Dakota. J. Wildl. Manage. 37:454-461.

Hart, C. M., B. Glading, and H. T. Harper. 1956. The pheasant in California. Pages 90-158 In D. L. Allen, ed. Pheasants in North America. Stackpole Co. and Wildl. Manage. Inst., Harrisburg, Pa., and Washington, D.C. 490 pp.

- Hungeriord, C. R. 1960. Water requirements of Gambel's quail. Trans. N. Am. Wildl. Conf. 25:231-240.
- Johnsgard, P. A. 1973. Grouse and quail of North America. Univ. Nebr. Press, Lincoln. 553 pp.
- Korschgen, L. J. 1967. Feeding habits and food. Pages 137-198 In O. H. Hewitt, ed. The Wild Turkey and Its Management. The Wildl. Soc., Washington, D.C. 589 pp.

Kuck, T. L., R. B. Dahlgren, and D. R. Progulske. 1970. Movements and behaviors of hen pheasants during the nesting season. J. Wildl. Manage. 34:626-630.

Lauckhart, J. B., and J. W. McKean. 1956. Chinese pheasants in the Northwest. Pages 43-89 In D. L. Allen, ed. Pheasants in North America. Stackpole Co. and Wildl. Manage. Inst., Harrisburg, Pa., and Washington, D.C. 490 pp.

Leopold, A. S. 1977. The California Quail. Univ. Calif. Press, Berkeley. 281 pp. MacGregor, W. G. 1953. An evaluation of California quail management. Proc. Annu. Conf. West. Assoc. State Game and Fish Comm. 33:157-160.

- Mackie, R. J., and H. K. Buechner. 1963. The reproductive cycle of the chukar. J. Wildl. Manage. 27:246-260.
- Oliver, W. H. 1969. Riparian lands--key habitat for upland birds. Wash. Dep. Game Bull. 21:3-5.
- Overton, W. S. 1971. Estimating the number of animals in wildlife populations. Pages 403-455 In R. H. Giles, ed. Wildlife Management Techniques, 3rd ed. The Wildl. Soc., Washington, D.C. 633 pp.
- Porter, R. D. 1950. The hungarian partridge in Utah. J. Wildl. Manage. 19:93-109.
- Reynolds, R. T., J. M. Scott, and R. A. Nussbaum. 1980. A variable circular plot method for estimating bird numbers. Condor 82:309-313.
- Schemnitz, S. D. 1961. Ecology of the scaled quail in the Oklahoma panhandle. Wildl. Monogr. 8:1-47.
- USACE. 1979. Design memorandum for wildlife habitat development, Supplement no. 1, Lower Snake River Project. U.S. Army Engineer District, Walla Walla, Wash.
- U.S. Army. 1981. Wildlife cisterns with fence protection. Unit price schedule, exhibit G to grazing lease for the Yakima Firing Center, Selah, Washington. Fort Lewis, Wash.
- USDA Forest Service. 1969. Wildlife habitat improvement handbook. USDA For. Serv. Handb., FSH 2609.11.
- Yoakum, J., W. P. Dasmann, H. R. Sanderson, C. M. Nixon, and H. S. Crawford. 1980. Habitat improvement techniques. Pages 329-403 In S. D. Schemnitz, ed. Wildlife Management Techniques Manual. 4th ed. The Wildl. Soc., Washington, D.C. 686 pp.



1







e

.

APPENDIX

Generalized Information on Needs for Open Water, Movement Patterns, and Use of

Guzzlers for 10 Species of Gallinaceous Birds

| Species | Need for Open Water | Movements* | Information Specific to Guzzlers | References |
|----------------------|--|---|--|--|
| SCALED QUAIL | Controversial; succulent vegetation, when suffic- iently abundant, probably supplies needs | Movement to water depen- dent on abundance of suc- culent plants; reported to range 0.25 to 15 m1 from water | Spacing intervals of 1.0 mi or more recommended; fence minimum of 0.5 acre (better 10-15 acres) with mostly grassy cover in fenced areas | Edminster 1954, Schemnitz 1961, Campbell et al. 1973 |
| GAMBEL'S QUAIL | May require open water when succulent vegetation unavailable | Probably moves 1 m1 or less to water in absence of succulent foods | <pre>4- to 5-m1 spacing intervals recom- mended but coveys probably stay within 1 m1 of water when succulent foods scarce; fence as for scaled quall but provide bushy cover</pre> | MacGregor 1953, Fdminster 1954, Johnsgard 1973 |
| CALI FORNIA QUAIL | May require open water when succulent vegetation unavailable | Young broods probably stay within 0.25 mi and adults within 0.5-1.0 mi of water in absence of succulent foods | Water supplies spaced at intervals of 1 mi or less recommended; brushy cover around guzzler needed and usually gained with fencing when rainfall sufficient | Emlen & Glading 1945, Edmin- ster 1954, Leopold 1977 |
| MOUNTAIN QUAIL | May require open water when succulent vegetation unavailable | Probably remains within l mi of water when suc- culent foods scarce or absent | <pre>1- to 2-mi spacing intervals recom- mended; brushy cover around guzzler important; mainly needed on low- altitude summer range; fence as for Gambel's quail</pre> | MacGregor 1953, Edminster 1954, Johnsgard 1973 |
| GRAY PARTRIDGE | Open water probably not essential; usually suffic- ient supplies associated with food and cover | No major shifts between seasons; usually moves less than 0.25 mi, rarely up to 1 mi from water | Seldom nested over 0.1 m1 from guz- zlers placed near intermittently dry water-courses in Washington; 0.5-mi spacing interval used near Lower Snake River, Wash. | Porter 1950, Oliver 1969, Johnsgard 1973, USACE 1979 |
| CHUKAR | Availability of open water during dry season influ- ences distribution | Generally within 0.5 to 1.0 mi of open water when succulent food limited; may travel 2-3 mi to reach water | 0.5-mi spacing interval used near Lower Snake River, Wash., with most nesting within 0.1 mi of guzzler; rocky slopes or brush needed near guzzler for escape cover or shade | Galbreath & Moreland 1953, Mackie & Buechner 1963, Oliver 1969, USACE 1979 |
| | | (Continued) | nued) | |

Information emphasizes movement relative to water supplies when possible.

10.000

11113

3.12.19

| R ING-NECKED PHEASANT | Need for Open Water | Movements* | Information Specific to Guzzlers | References |
|--------------------------|--|---|---|---|
| | Usually sufficient supplies associated with food and cover; may be inadequate supplies if land use prac- tices exclude irrigation during dry season | Females can move up to l mi during breeding season; young broods probably remain within 0.1 mi of nest sites | 0-5 mi spacing interval used near Lower Snake River, Wash. | Hart et al. 1956, Lauckhart and McKean 1956, Kuck et al. 1970, Hanson & Progulske 1973, USACE 1979 |
| GROUSE | Availability of open water probably limits movement of broods when succulent foods absent | Seasonal movements alti- tudinal; females with broods and territorial males move little; during prelaying and laying periods, adult females generally move less than 0.25 mi | May be beneficial on drier summer ranges; no specifics on spacing found | Johnsgard 1973, Hannon et al. 1982, USACE 1979 |
| GROUSE | Open water used when and where available; can sur- vive temporarily on succu- lent vegetation and dew; good habitat has good water supply | Seasonal (often alti- tudinal movements from breeding to wintering grounds; females and broods can move 13-27 mi to rearing areas | Observed using guzzlers installed for other species | Edminster 1954, Dalke et al. 1963, Johnsgard 1973 |
| TURKEY | Open water necessary during warmer months; dew and suc- culent foods can supply some of needs | Typically moves to water daily; movement of 0.5- 1.0 mi not unusual | No information found on guzzler installation specifically for wild turkey | Edminster 1954, Korschgen 1967 |
| á | | | | |

-

NO.

2

* 10 1

