

AD-A175 045

ADA COMPILER VALIDATION SUMMARY REPORT: ALSYS ALSYCOM
003 VERSION 111 GOUPEL G40(U) BUREAU D'ORIENTATION DE
LA NORMALISATION EN INFORMATIQUE LE C.. 23 APR 86..I
ADA-86.2


1/1

UNCLASSIFIED

F/G 9/2

NL

END



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963-A

UNCLASSIFIED

AD-A175 045

2

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		CONDITIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Ada Compiler Validation Summary Report: Alsys Alsy COMP 003 Version 1.1.1 GROUPIX G40		5. TYPE OF REPORT & PERIOD COVERED April 1986 to April 1987
7. AUTHOR(s) BNI Domaine de Volceau ROCQUENCOURT B.P.- 105-78153 LE CHESNAY CEDEX, FRANCE		6. PERFORMING ORG. REPORT NUMBER Ada 86.2
9. PERFORMING ORGANIZATION AND ADDRESS BNI		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Ada Joint Programming Office United States Department of Defense Washington, D.C. 20301-3081		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) BNI Domaine de Volceau ROCQUENCOURT B.P. 105-78153 LE CHESNAY CEDEX, FRANCE		12. REPORT DATE 23 April 1986
		13. NUMBER OF PAGES 54
		15. SECURITY CLASS (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20. If different from Report) UNCLASSIFIED		
18. SUPPLEMENTARY NOTES		
19. KEYWORDS (Continue on reverse side if necessary and identify by block number) Ada Programming language, Ada Compiler Validation Summary Report, Ada Compiler Validation Capability, ACVC, Validation Testing, Ada Validation Office, AVO, Ada Validation Facility, AVF, ANSI/MIL-STD-1815A, Ada Joint Program Office, AJPO		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) See Attached.		

DTIC
SELECTED
DEC 12 1986
E

DTIC FILE COPY

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73 S/N 0102-LF-014-6601

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

05/22/86

Validation Summary Report

ADA 86.2

Ada COMPILER VALIDATION SUMMARY REPORT:

Alsys
AlsyCOMP_003, version 1.1.1
GOUPI L G40

Completion of On-Site Validation:
23 April 1986

Prepared By:
BNI
Domaine de Voluceau ROCQUENCOURT
B.P.105 - 78153 LE CHESNAY CEDEX
FRANCE

Prepared For:
Ada Joint Program Office
United States Department of Defense
Washington, D.C.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



Ada is a registered trademark of the United States Government
(Ada Joint Program Office)

86 12 11 083 86 4853

Validation Summary Report

05/22/86

++++++
+
+ Place NTIS form here +
+
++++++

05/22/86

Validation Summary Report


Ada Compiler Validation Summary Report:

Compiler name : AIsyCOMP_003, version 1.1.1


Host Computer	Target Computer
GOUPIL G40	GOUPIL G40
under	under
MS/DOS Version 3.1	MS/DOS Version 3.1

Testing Completed 23 April 1986 Using ACVC 1.7


This report has been reviewed and approved:



Ada Validation Facility (AVF)
BNI
Nicolas Malagardis represented by Jacqueline Sidi
Domaine de Voluceau ROCQUENCOURT
B.P.105 - 78153 LE CHESNAY CEDEX
FRANCE



Ada Validation Office (AVO)
John F. Kramer, Jr
Institute for Defense Analyses
Alexandria, VA



Ada Joint Program Office (AJPO)
Virginia L. Castor
Director
Washington, D.C.

Ada is a registered trademark of the United States Government
(Ada Joint Program Office)

EXECUTIVE SUMMARY

This Validation Summary Report presents the results and conclusions of testing performed on the AlsyCOMP_003, version 1.1.1. Standardized tests serve as input to an Ada compiler, producing results which are evaluated by the validation team. This summary briefly states the highlights of the AlsyCOMP_003, version 1.1.1 validation.

On-site testing was completed by 23 April 1986 at Alsys at La Celle Saint-Cloud, France under the auspices of the BNI (AVF), according to Ada Validation Office policies and procedures. The AlsyCOMP_003, version 1.1.1 is hosted on GOUPIL G40 operating under MS/DOS Version 3.1. The suite of tests known as the Ada Compiler Validation Capability (ACVC), Version 1.7, was used. The ACVC is used to validate conformance of a compiler to ANSI/MIL-STD-1815A Ada. The purpose of testing is to ensure that a compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent but permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, or during execution.

The results of validation are summarized in the following table.

RESULT	TEST CLASS						TOTAL
	A	B	C	D	E	J	
Passed	68	820	1014	12	9	21	1944
Failed	0	0	0	0	0	0	0
Inapplicable	0	4	306	5	2	2	319
Anomalous	0	0	0	0	0	0	0
Withdrawn	0	4	12	0	0	0	16
TOTAL	68	828	1332	17	11	23	2279

Ada is a registered trademark of the United States Government
(Ada Joint Program Office)

Tests found to contain errors were withdrawn from Version 1.7 of the Ada Compiler Validation Capability (ACVC). When validation was completed, the following tests had been withdrawn:

C35904A	C41404A	C48008A
C4A014A	B4A010C	B83A06B
C92005A	C940ACA	CA1003B
BA2001E	CA3005A..D (4 tests)	BC3204C
CE2107E		

Some tests demonstrate that language features are not supported by an implementation. For this implementation the tests determined the following.

. SHORT_FLOAT is not supported:

B86001CP C34001F C35702A

. LONG_FLOAT is not supported:

B86001CQ C34001G C35702B

. Representation clauses for noncontiguous enumeration representations are not supported:

C55B16

. No other integer type other than INTEGER, SHORT_INTEGER, AND LONG_INTEGER is supported:

B86001DT

. The package SYSTEM is used by package TEXT_IO:

C86001F

. The 'SIZE clause is not supported:

C87B62A

. The 'STORAGE_SIZE clause is not supported:

C87B62B

. The 'SMALL clause is not supported:

C87B62C

. Generic package bodies can be compiled in separate compilation files, but before any corresponding generic instantiation:

CA2009C BC3205D

. Generic subprogram bodies can be compiled in, but before any corresponding generic instantiation:

CA2009F

. Pragma INLINE is not supported for procedures:

LA3004A EA3004C CA3004E

. Pragma INLINE is not supported for functions:

LA3004B EA3004D CA3004F

. No more than one internal file can be associated with the same external file, if one of the internal files is used for writing :

CE2107B CE2107C CE2107D
CE2111D CE3111B CE3111C
CE3114B CE3111D CE3111E

. An external file associated with more than one internal file cannot be reset for writing:

CE2111H CE3115A

. An external file associated with more than one internal file cannot be deleted:

CE2110B

. The compiler's capacity with respect to levels of loop nesting is at least 17 levels, but less than 31:

D55A03E..H (4 tests)

. The compiler's capacity with respect to the levels of block nesting is less than 65:

D56001B

. The library tasks were aborted when the main program terminated.

C94004A..C (3 tests)

AlsyCOMP_003, version 1.1.1 05/22/86 Validation Summary Report

ACVC Version 1.7 was taken on-site via magnetic tape to Alsys at La Celle Saint-Cloud, France. The tape was loaded, and all tests, except the withdrawn tests and any executable tests which make use of a floating point precision greater than SYSTEM.MAX_DIGITS, were compiled on GOUPIL G40. Class A, C, D, and E tests were executed on GOUPIL G40.

On completion of testing, all results were analyzed for failed Class A, C, D, or E programs, and all Class B and L compilation results were individually analyzed.

The ACVC, Version 1.7, contains 2279 tests of which 1944 were applicable to AlsyCOMP_003, version 1.1.1. No anomalies were found in the testing of this compiler. Testing demonstrated that all applicable tests were passed by this compiler. The AVF concluded that the results show acceptable compliance to ANSI/MIL-STD-1815A Ada.

1- INTRODUCTION	
1.1- PURPOSE OF THIS VALIDATION SUMMARY REPORT.....	1-1
1.2- USE OF THIS VALIDATION SUMMARY REPORT.....	1-2
1.3- REFERENCES.....	1-3
1.4- DEFINITION OF TERMS.....	1-3
1.5- CONFIGURATION.....	1-5
2- TEST RESULTS	
2.1- ACVC Test Classes.....	2-1
2.1.1- Class A Tests.....	2-3
2.1.2- Class B Tests.....	2-4
2.1.3- Class C Tests.....	2-5
2.1.4- Class D Tests.....	2-6
2.1.5- Class E Tests.....	2-7
2.1.6- Class L Tests.....	2-8
2.1.7- Support Units.....	2-9
2.2- WITHDRAWN TESTS.....	2-9
2.3- INAPPLICABLE TESTS.....	2-11
2.4- IMPLEMENTATION CHARACTERISTICS.....	2-13
3- COMPILER ANOMALIES AND NONCONFORMANCES	
3.1- ANOMALIES.....	3-1
3.2- NONCONFORMANCES.....	3-1
4- ADDITIONAL TESTING INFORMATION	
4.1- PRE-VALIDATION.....	4-1
4.2- TEST SITE.....	4-1
4.3- TEST TAPE INFORMATION.....	4-1
4.4- TESTING LOGISTICS.....	4-2
5- SUMMARY AND CONCLUSIONS	
Appendix A - COMPLIANCE STATEMENT	
Appendix B - TEST PARAMETERS	
Appendix C - COMMAND SCRIPTS	
Appendix D - TEST NAMING	

CHAPTER 1

INTRODUCTION

The Validation Summary Report describes how an Ada compiler conforms to the language standard. This report explains all technical terms used within and thoroughly reports the Ada Compiler Validation Capability (ACVC) test results. Ada compilers must be written according to the language specification as given in the ANSI/MIL-STD-1815A Ada. All implementation-defined features must be included for the compiler to conform to the Standard. Following the guidelines of the Standard ensures continuity between compilers. That is, the entire Standard must be implemented, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Standard, it must be understood that some differences do exist between implementations. ANSI/MIL-STD-1815A permits some implementation dependencies, e.g., the maximum length of identifiers, the maximum values of integer types, etc. These implementation-dependent features limit the portability of programs between compilers. Other differences between compilers are due to limitations imposed on a compiler by the operating system and by the hardware. All of these dependencies are given in the report.

Validation summary reports are written according to a standardized format. Compiler users can, therefore, more easily compare the reports from several compilers when selecting a compiler for a given task. The validation report can be completed mostly from the test results produced during validation testing. Additional testing information is given at the end of the report and states problems and details which are unique for a specific compiler. The format of the validation report limits variance between reports, enhances readability of the report, and accelerates report readiness.

1.1- PURPOSE OF THIS VALIDATION SUMMARY REPORT

The Validation Summary Report documents the results of the testing performed on an Ada compiler. Testing was carried out for the following purposes:

- . To identify any language constructs supported by the translator that do not conform to the Ada Standard

Validation Summary Report 05/22/86 AIsyCOMP_003, version 1.1.1

- . To identify any unsupported language constructs required by the Ada Standard
- . To describe the implementation-dependent behavior allowed by the Ada Standard

Testing of this compiler was conducted under the supervision of BNI according to policies and procedures established by the Ada Validation Office (AVO). Testing was completed by 23 April 1986 at AIsys at La Celle Saint-Cloud, France.

1.2- USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the Ada Validation Office may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. §552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that any statement or statements set forth in this report are accurate or complete, or that the subject compiler has no nonconformances to the Ada Standard other than those presented. This report is not intended for the purpose of publicizing the findings summarized herein.

Questions regarding this report or the validation tests should be directed to:

Ada Validation Office
Institute for Defense Analyses
1801 N. Beauregard
Alexandria VA 22311

and to:

BNI
Domaine de Voluceau ROCQUENCOURT
B.P.105 - 78153 LE CHESNAY CEDEX
FRANCE

1.3- REFERENCES

- . Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, Feb 1983.
- . Ada Validation Organization : Policies and Procedures, T.H. Probert, June 1982, The MITRE Corporation MTR-82W00103.
- . Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., Dec 1984.

1.4- DEFINITION OF TERMS

Anomaly	A test result that, given pre-validation analysis, is not expected during formal validation but is judged allowable under the circumstances.
ACVC	The Ada Compiler Validation Capability. A set of programs that evaluates the conformance of a compiler to the Ada language specification, ANSI/MIL-STD-1815A.
Ada Standard	ANSI/MIL-STD-1815A, February 1983.
Applicant	The agency requesting validation.
AVF	The BNI. In the context of this report, the AVF is responsible for conducting compiler validations according to established policies and procedures.
AVO	The Ada Validation Office. In the context of this report, the AVO is responsible for setting policies and procedures for compiler validations.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	A test for which the compiler generates a result that demonstrates nonconformance to the Ada Standard.
Host	The computer on which the compiler resides.

Inapplicable test A test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.

Passed test A test for which a compiler generates the expected result.

Target The computer for which a compiler generates code.

Test A program that evaluates the conformance of a compiler to a language specification. In the context of this report, the term is used to designate a single ACVC test. The text of a program may be the text of one or more compilations.

Withdrawn test A test that has an invalid test objective, fails to meet its test objective, or contains illegal use of the language.

1.5- CONFIGURATION

The candidate compilation system for this validation was tested under the configuration:

Compiler: AlsyCOMP_003, version 1.1.1

Test Suite: Ada Compiler Validation Capability, Version 1.7

Host Computer:

Machine(s): GOUPIL G40

Operating System: MS/DOS Version 3.1

Memory Size: augmented to 4 Megabytes

Target Computer:

Machine(s): GOUPIL G40

Operating System: MS/DOS Version 3.1

Memory Size: augmented to 4 Megabytes

One GOUPIL G40 with the above configuration was used to process the ACVC tests.

CHAPTER 2

TEST RESULTS

2.1- ACVC Test Classes

Conformance to ANSI/MIL-STD-1815A is measured using the Ada Compiler Validation Capability (ACVC). The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. Legal programs are compiled and executed while illegal programs are just compiled. Support packages are used to report the results of the legal programs. A compiler must correctly process each of the tests in the suite and demonstrate conformance to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. Tests that are found to contain errors are withdrawn from the ACVC. Detailed test results are listed in the Appendix D. The results of validation testing are summarized in the following table:

RESULT	TEST CLASS						TOTAL
	A	B	C	D	E	L	
Passed	68	820	1014	12	9	21	1944
Failed	0	0	0	0	0	0	0
Inapplicable	0	4	306	5	2	2	319
Anomalous	0	0	0	0	0	0	0
Withdrawn	0	4	12	0	0	0	16
TOTAL	68	828	1332	17	11	23	2279

A total of 1985 tests were processed during this validation attempt. The 16 withdrawn tests in Version 1.7 were not processed, nor were 278 Class C tests that were inapplicable because they use floating point types having digits that exceed the maximum value for the implementation. All other tests were processed.

Some conventions are followed in the ACVC to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic 55 character set, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be

Validation Summary Report 05/22/86 AlsyCOMP_003, version 1.1.1

supported in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values. The values used for this validation are listed in Appendix B.

2.1.1- Class A Tests

Class A tests check that legal Ada programs can be successfully compiled and executed. However, no checks are performed during execution to see if the test objective has been met. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a message indicating that it has passed. If a Class A test cannot be compiled and executed because of its size, then the test is split into a set of smaller subtests that can be processed. Splits were required for 2 tests:

AE2101A

AE2101F

The following table shows that all applicable Class A tests were passed:

RESULT	CHAPTER													TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14		
Passed	15	9	0	5	2	12	13	3	0	0	0	9	68	
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0	
Inapplicable	0	0	0	0	0	0	0	0	0	0	0	0	0	
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0	
Withdrawn	0	0	0	0	0	0	0	0	0	0	0	0	0	
TOTAL	15	9	0	5	2	12	13	3	0	0	0	9	68	

2.1.2- Class B Tests

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined manually to verify that every syntax or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler. If one or more errors are not detected, then a version of the test is created that contains only the undetected errors. The resulting "split" is compiled and examined. The splitting process continues until all errors are detected by the compiler. Splits were required for 12 tests:

B32202A	B33006A	B37004A
B43201D	B61012A	B62001B
B91004A	BA1101B	BC3009A
BC3009C	BC3204D	BC3205E

The following table shows that all applicable Class B tests were passed:

RESULT	CHAPTER												TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14	
Passed	39	86	86	113	73	67	48	87	36	8	159	18	820
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0
Inapplicable	0	0	0	0	0	0	3	0	0	0	1	0	4
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0
Withdrawn	0	0	1	0	0	0	1	0	1	0	1	0	4
TOTAL	39	86	87	113	73	67	52	87	37	8	161	18	828

2.1.3- Class C Tests

Class C tests check that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASS/FAIL message indicating the result when it is executed. If a Class C test cannot be compiled because it exceeds the compiler's capacity, then the test is split into smaller subtests until all are compiled and executed. Splits were required for 6 tests:

C23003G..J (4 tests)

C23006E

C23006G

The following table shows that all applicable Class C tests were passed:

RESULT	CHAPTER														TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14			
Passed	37	90	162	118	82	18	93	106	40	20	56	192	1014		
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0		
Inapplicable	23	119	140	1	0	0	4	3	4	0	0	12	306		
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0		
Withdrawn	0	1	3	0	0	0	0	2	5	0	0	1	12		
TOTAL	60	210	305	119	82	18	97	111	49	20	56	205	1332		

2.1.4- Class D Tests

Class D tests check the compilation and execution capacities of a compiler. Since there are no requirements placed on a compiler by the Ada Standard for the number of identifiers permitted in a compilation, the number of units in a library, the number of nested loops in a subprogram body, and so on, a compiler may refuse to compile a Class D test. Each Class D test is self-checking and produces a PASS/FAIL message indicating the result when it is executed. If a Class D test fails to compile because the capacity of the compiler is exceeded, then the test is classified as inapplicable.

The following table shows that all applicable Class D tests were passed:

RESULT	CHAPTER													TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14		
Passed	1	0	4	4	3	0	0	0	0	0	0	0	0	12
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Inapplicable	0	0	0	5	0	0	0	0	0	0	0	0	0	5
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Withdrawn	0	0	0	0	0	0	0	0	0	0	0	0	0	0
TOTAL	1	0	4	9	3	0	0	0	0	0	0	0	0	17

Capacities measured by the Class D tests are detailed in section 2.4, IMPLEMENTATION CHARACTERISTICS.

2.1.5- Class E Tests

Class E tests provide information about the compiler in those areas in which the Ada Standard permits implementations to differ. Each Class E test is executable and produces messages that indicate how the Ada Standard is interpreted. However, in some cases the Ada Standard permits a compiler to detect a condition either at compile time or at execution time, and thus a Class E test may correctly fail to execute. A Class E test is passed if it fails to compile and appropriate error messages are issued, or if it executes properly and produces a message that it has passed. If a Class E test cannot be compiled and executed because of its size, then the test is split into a set of smaller subtests that can be processed. No splits were required.

The following table shows that all applicable Class E tests were passed:

RESULT	CHAPTER													
	2	3	4	5	6	7	8	9	10	11	12	14	TOTAL	
Passed	1	3	2	1	1	0	0	0	0	0	0	1	9	
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0	
Inapplicable	0	0	0	0	0	0	0	0	2	0	0	0	2	
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0	
Withdrawn	0	0	0	0	0	0	0	0	0	0	0	0	0	
TOTAL	1	3	2	1	1	0	0	0	2	0	0	1	11	

Information obtained from the Class E tests is detailed in section 2.4, IMPLEMENTATION CHARACTERISTICS.

2.1.6- Class L Tests

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time and the test does not execute.

The following table shows that all applicable Class L tests were passed:

RESULT	CHAPTER												
	2	3	4	5	6	7	8	9	10	11	12	14	TOTAL
Passed	0	0	0	0	0	0	0	0	21	0	0	0	21
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0
Inapplicable	0	0	0	0	0	0	0	0	2	0	0	0	2
Anomalous	0	0	0	0	0	0	0	0	0	0	0	0	0
Withdrawn	0	0	0	0	0	0	0	0	0	0	0	0	0
TOTAL	0	0	0	0	0	0	0	0	23	0	0	0	23

2.1.7- Support Units

Three packages support the self-checking features of Class C tests: REPORT, CHECK_FILE, and VAR_STRINGS. The REPORT package provides the mechanism by which executable tests report results. It also provides a set of identity functions that are used to defeat some compiler optimization strategies to cause computations to be made by the target computer instead of the by the compiler on the host computer. The CHECK_FILE package is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The VAR_STRINGS package defines types and subprograms for manipulating varying-length character strings. The operation of these three packages is checked by a set of executable tests. These tests produce messages that are examined manually to verify that the packages are operating correctly. If these packages are not operating correctly, then validation is not attempted.

An applicant is permitted to substitute the body of package REPORT with an equivalent one if for some reason the original version provided by the ACVC cannot be executed on the target computer. Package REPORT was not modified for this validation.

All support package specifications and bodies were compiled and were demonstrated to be operating correctly.

2.2- WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. When testing was performed, the following 16 tests had been withdrawn for the reasons indicated:

C35904A:

The elaboration of subtype declarations SFX3 & SFX4 may raise NUMERIC_ERROR vs. CONSTRAINT_ERROR.

C41404A: The values of 'LAST and 'LENGTH in the "if" statements from line 74 to the end of the test are incorrect.

C48008A:

This test requires that the evaluation of default initial values not occur if an exception is raised by an allocator. However, the LMC has ruled that such a requirement is incorrect (AI-00397).

B4A010C:

The object_declaration in line 18 follows a subprogram body of the same declarative part.

C4A014A:

The number declarations in lines 19-22 are not correct, because conversions are not static.

B83A06B:

The Ada Standards 8.3(17) and AI_00330 permit the label LAB_ENUMERAL of line 80 to be considered a homograph of the enumeration literal in line 25.

C92005A:

At line 40, "/"= for type PACK.BIG_INT is not visible without a "use" clause for package PACK.

C940ACA:

This test assumes that allocated task TT1 will run prior to the main program, and thus assign SPYNUMB the value checked for by the main program; however, such an execution order is not required by the Ada Standard, so the test is erroneous.

CA1003B:

This test requires all of the legal compilation units of a file containing some illegal units to be compiled and executed. But according to AI-00255, such a file may be rejected as a whole.

BA2001E:

The Ada Standards 10.2(5) states that "simple names of all subunits that have the same ancestor library unit must be distinct identifiers." This test checks for the above condition when stubs are declared; but it is not clear that the check must be made then, as opposed to when the subunit is compiled.

CA3005A..D:(4 tests)

There exists no valid elaboration order for these tests.

BC3204C:

The file BC3204C4 should contain the body for BC3204C0—as indicated in line 25 of BC3204C3M.

CE2107E:

TEMP_HAS_NAME must be given an initial value of TRUE.

2.3- INAPPLICABLE TESTS

Some tests use features of the Ada language that the Ada Standard does not require a compiler to support; thus these tests may be inapplicable to a particular compiler. Others may depend on the result of another test that is either inapplicable or withdrawn. For this validation attempt, 319 tests were inapplicable for the reasons indicated:

B86001DT (1 test)

This test is inapplicable because this implementation has no predefined type other than INTEGER, FLOAT, SHORT_INTEGER, SHORT_FLOAT, LONG_INTEGER, LONG_FLOAT and DURATION.

C24113C..Y

C35705C..Y

C35706C..Y

C35707C..Y

C35708C..Y

C35802C..Y

C45241C..Y

C45321C..Y

C45421C..Y

C45424C..Y

C45521C..Z

C45621C..Z (10*23 + 2*24 = 278 tests)

These tests are inapplicable because this implementation limits digits to 6.

B86001CP

C34001F

C35702A (1+3 = 3 tests)

These tests are inapplicable because this implementation does not support SHORT_FLOAT.

B86001CQ

C34001G

C35702B (1+3 = 3 tests)

These tests are inapplicable because this implementation does not support LONG_FLOAT.

C55816A

C87862A..C (1+3 = 4 tests)

These tests are inapplicable because this implementation does not support representation clauses.

C86001F (1 test)

This test is inapplicable because package SYSTEM is used by TEXT_10.

BC3205D

CA2009C

CA2009F (1*3 = 3 tests)

These tests are inapplicable because this implementation does not support instantiating missing generic bodies.

CA3004E..F

EA3004C..D

LA3004A..B (3*2 = 6 tests)

These tests are inapplicable because this implementation does not support pragma INLINE. These tests ignore the pragma and are processed correctly.

CE2107B..D

CE2110B

CE2111D

CE2111H

CE3111B..E

CE3114B

CE3115A (3+1+1+1+4+1+1 = 12 tests)

These tests are inapplicable because this implementation does not support the sharing of external file by several internal files when one of the external file is opened for writing.

D55A03E..H (4 tests)

These tests are inapplicable because the compiler's capacity with respect to levels of loop nesting is at least 17 levels, but less than 31.

056001B

This test is inapplicable because the compiler's capacity with respect to the levels of block nesting is less than 65.

C94004A..C (3 tests)

These tests are inapplicable because the library tasks were aborted when the main program terminated.

2.4- IMPLEMENTATION CHARACTERISTICS

One of the purposes of validation is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, inapplicable tests in other classes also characterize an implementation. This compiler is characterized by the following interpretations of the Ada Standard:

- . Non-graphic characters.

Non-graphic characters are defined in the ASCII character set but are not permitted in the texts of Ada programs. The compiler correctly recognizes these characters as illegal in Ada compilations. The characters are printed in the output listing.

- . Capacities.

The compiler correctly processes compilations containing loop statements nested to at least 17 levels (but less than 31), procedures nested to at least 17 levels (but less than 31), and 723 variables.

- . Universal integer calculations.

An implementation is allowed to reject universal integer calculations having values that exceed SYSTEM.MAX_INT. This implementation does not reject such calculations and processes them correctly.

- . Predefined types.

This implementation supports the predefined types SHORT_INTEGER, INTEGER, LONG_INTEGER, FLOAT and DURATION. It does not support any other predefined numeric types.

- . Based literals.

An implementation is allowed to reject a based literal with value exceeding SYSTEM.MAX_INT during compilation or it may raise NUMERIC_ERROR during execution. This compiler raises NUMERIC_ERROR during execution.

. Array types.

An implementation is allowed to raise NUMERIC_ERROR for an array having a 'LENGTH that exceeds STANDARD.INTEGER'LAST and/or SYSTEM.MAX_INT. When an array type is declared with an index range exceeding INTEGER values and with a component that is a null BOOLEAN array, this compiler does not raise any exception.

When an array type is declared with an index range exceeding SYSTEM.MAX_INT values and with a component that is a null BOOLEAN array, this compiler raises NUMERIC_ERROR.

A packed BOOLEAN array of length INTEGER_LAST+3 does not raise any exception. A packed two-dimensional BOOLEAN array with INTEGER_LAST+3 components does not raise any exception.

NOTE : this compiler does not support pragma PACK.

A null array with one dimension of length exceeding INTEGER'LAST does not raises NUMERIC_ERROR.

In assigning one-dimensional array types, the entire expression is evaluated before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype.

In assigning two-dimensional array types, the entire expression is NOT evaluated before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype.

. Discriminated types.

In assigning record types with discriminants, the entire expression is evaluated before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype.

An incompletely declared type with discriminants may be used in an access type definition and constrained either there or in later subtype indications.

. Aggregates.

When evaluating the choices of a multi-dimensional aggregate the order in which choices are evaluated and index subtype checks are made depends upon the aggregate itself.

When evaluating an aggregate containing subaggregates, all choices are evaluated before being checked for identical bounds.

. Functions.

The declaration of a parameterless function with the same profile as an enumeration literal in the same immediate scope is rejected by the implementation.

. Representation clauses.

'SMALL length clauses are not supported.

Enumeration representation clauses are not supported.

. Tasks.

A task object's storage size is not allowed to change after the task is activated.

. Generics.

When given a separately compiled generic declaration, some illegal instantiations, and a body, the compiler ignores the body because it is not in the same compilation as its declaration and it is compiled after the instantiations. It issues a warning for each instantiation, stating that a null body is assumed.

. Package CALENDAR.

TIME_OF and SPLIT are inverses when SECONDS is a non-model number.

. Pragmas.

Pragma INLINE is not supported for procedures. It is not supported for functions.

. Input/output.

Package SEQUENTIAL_IO can be instantiated with unconstrained array types and record types with discriminants. Package DIRECT_IO can be instantiated with unconstrained array types and record types with discriminants without defaults. However any call to OPEN or CREATE of such instances will raise an exception.

More than one internal file can be associated with each external file for sequential I/O for reading only. An external file associated with more than one internal file cannot be deleted.

More than one internal file can be associated with each external file for direct I/O for reading only. An external file associated with more than one internal file cannot be deleted.

More than one internal file can be associated with each external file for text I/O for reading only. An external file associated with more than one internal file cannot be deleted.

An existing text file can be opened in OUT_FILE mode, can be created in OUT_FILE mode, and can be created in IN_FILE mode.

Dynamic creation and resetting of a sequential file is allowed.

Temporary sequential files are given a name. Temporary direct files are given a name. Temporary files given names are not deleted when they are closed.

CHAPTER 3

COMPILER ANOMALIES AND NONCONFORMANCES

3.1-- ANOMALIES

An anomaly is a test result that, given the pre-validation analysis, was not expected during formal validation but which is judged allowable by the AVF and the AVO under the circumstances of the validation. No anomalies were detected in this validation attempt.

3.2-- NONCONFORMANCES

Any discrepancy between expected test results and actual test results is considered to be a nonconformance. No nonconformances were detected in this validation attempt.

CHAPTER 4

ADDITIONAL TESTING INFORMATION

4.1- PRE-VALIDATION

Prior to validation, a set of test results for ACVC 1.7 produced by AIsyCOMP_003, version 1.1.1 was submitted to BNI by the applicant for pre-validation review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests.

4.2- TEST SITE

Tests were compiled and executed at AIsys at La Celle Saint-Cloud, France.

4.3- TEST TAPE INFORMATION

A test tape containing ACVC Version 1.7 was taken on-site by the validation team. This tape contained all tests applicable to this validation as well as all tests inapplicable to this validation except for any Class C tests that require floating-point precision exceeding the maximum value supported by the implementation. Tests that were withdrawn from ACVC 1.7 were not written to the tape. Tests that make use of values that are specific to an implementation were customized before being written to the tape. Any split tests were also included on the test tape so that no editing of these test files was necessary when the validation team arrived on-site.

The format of the test tape was the same as the ACVC distribution tapes. The files were mounted on a VAX. They were transferred from the VAX by an ETHERNET local area network to four IBM PC/ATs and subsequently transferred on floppy disks.

4.4- TESTING LOGISTICS

Processing of the tests was begun using command scripts provided by Alsys. The text of these scripts are given in Appendix C.

The compiler supports various options that control its operation. The compiler was tested with the following option settings.

For tests from class C the following was used :

Alsys ADA Library Manager Version 1.00 (c)Copyright Alsys 1986

```

NEW (LIBRARY => ,
     OPTIONS => (OVERWRITE   => NO,
                 TARGET_KIND => I286_REAL,
                 TASKING     => YES));

COMPILE (SOURCE => ,
         LIBRARY => "adalib",
         DISPLAY => (LIST_FILE      => NO,
                   RECAP          => NO,
                   WARNING        => NO,
                   BANNER         => NO,
                   TEXT           => NO,
                   DETAIL         => NO,
                   ASSEMBLY       => NO),
         FORMAT => (LINE_LENGTH    => 79,
                   PAGE_LENGTH    => 45),
         OPTIONS => (ERRORS        => 999,
                   LEVEL          => CODE,
                   CHECKS         => YES,
                   STACK_CHECK    => YES,
                   GENERIC_STUBS  => NO));

BIND (PROGRAM => ,
     LIBRARY  => "adalib",
     DISPLAY  => (BIND_MAP        => NO,
                 LINK_MAP        => NO,
                 WARNING         => YES,
                 UNITS           => NO,
                 ELABORATION     => NO),
     OPTIONS  => (LEVEL           => LINK,
                 EXECUTION_MODE  => LIBRARY_DEFAULT,
                 OUTPUT_NAMES    => no_value,
                 MAIN_STACK      => 64,
                 TASK_STACK      => 8,
                 INITIAL_HEAP    => 64,
                 HEAP_INCREMENT  => 64,
                 STACK_TRACE     => YES,
                 FAST_TIMER      => NO,
                 RUNTIME_OPTIONS => NO),
     INTERFACED => (OBJECT_MODULES => no_value,
                   SEARCH_LIBRARIES => no_value));

```

Alsys PC AT Ada Version 1.00
 (C)Copyright Alsys 1986. All rights reserved.

For tests from classes A, B, D, E and L, the following was used :

Alsys ADA Library Manager Version 1.00 (c)Copyright Alsys 1986

```

NEW (LIBRARY => ,
     OPTIONS => (OVERWRITE => NO,
                 TARGET_KIND => I286_REAL,
                 TASKING => YES));

COMPILE (SOURCE => ,
         LIBRARY => "\acvc\adalib",
         DISPLAY => (LIST_FILE => NO,
                    RECAP => NO,
                    WARNING => YES,
                    BANNER => YES,
                    TEXT => YES,
                    DETAIL => YES,
                    ASSEMBLY => NO),
         FORMAT => (LINE_LENGTH => 79,
                    PAGE_LENGTH => 45),
         OPTIONS => (ERRORS => 999,
                    LEVEL => CODE,
                    CHECKS => YES,
                    STACK_CHECK => YES,
                    GENERIC_STUBS => NO));

-- BIND_MAP=YES for L TEST ONLY

BIND (PROGRAM => ,
      LIBRARY => "\acvc\adalib",
      DISPLAY => (BIND_MAP => NO,
                 LINK_MAP => NO,
                 WARNING => YES,
                 UNITS => NO,
                 ELABORATION => NO),
      OPTIONS => (LEVEL => LINK,
                  EXECUTION_MODE => LIBRARY_DEFAULT,
                  OUTPUT_NAMES => no_value,
                  MAIN_STACK => 64,
                  TASK_STACK => 8,
                  INITIAL_HEAP => 64,
                  HEAP_INCREMENT => 64,
                  STACK_TRACE => YES,
                  FAST_TIMER => NO,
                  RUNTIME_OPTIONS => NO),
      INTERFACED => (OBJECT_MODULES => no_value,
                     SEARCH_LIBRARIES => no_value));
    
```

Alsys PC AT Ada Version 1.00
 (C)Copyright Alsys 1986. All rights reserved.

The procedure used for the validation of the GOUPIL G40 was done on one machine. An overview of this procedure follows :

All the ACVC sources were copied on floppy diskettes, each floppy containing one chapter. This set of floppies was then used as a master ACVC set .

The entire directory structure (with adaworld scripts in appropriate directories) was then created .

All these preliminary tasks being done, the procedure for validating an ACVC chapter was then :

- copy the master diskette containing the ACVC sources for the chapter into the corresponding subdirectory on the machine.

- invoke the adaworld script for this chapter

- when the execution of the script was finished (and then the execution of the ACVC chapter), copy the contents of the subdirectories lst (for compilation listings) and res (for execution result) on a transfer diskette, and send back the contents of that diskette on the VAX on which all results where accumulated .
The task of uploading from diskettes to the VAX was done using four IBM PC/ATs connected to the VAX via an ETHERNET local area network.

- finally the ACVC sources and all results for the chapter were deleted from the machine before starting the next chapter, so as not to run out of disk space.

This procedure was repeated for every ACVC chapter.

CHAPTER 5

SUMMARY AND CONCLUSIONS

The BNI identified 1985 of the 2279 tests in ACVC Version 1.7 to be processed during the validation of AIsyCOMP_003, version 1.1.1. Excluded were 278 tests requiring too great a floating-point precision, and the 16 withdrawn tests. 41 tests were determined to be inapplicable after they were processed. The remaining 1944 tests were passed by the compiler.

The BNI concludes that these results demonstrate acceptable conformance to the Ada Standard.

APPENDIX A

COMPLIANCE STATEMENT

The only allowed implementation dependencies correspond to implementation-dependent pragmas and attributes, to certain machine-dependent conventions as mentioned in Chapter 13 of MIL-STD-1815A, and to certain allowed restrictions on representation classes. The implementation-dependent characteristics of the AlsyCOMP_003, version 1.1.1 are described in the following sections which discuss topics one through eight as stated in Appendix F of the Ada Language Reference Manual (ANSI/MIL-STD-1815A).

(1) Implementation-Dependent Pragmas

```
Pragma INTERFACE (language_name, subprogram_name);  
Pragma INTERFACE_NAME (subprogram_name, string_literal);
```

(2) Implementation-Dependent Attributes

None.

(3) Package SYSTEM

The specification for package SYSTEM is

package SYSTEM is

type ADDRESS is access STRING ;
type NAME is (I_80x86) ;

SYSTEM_NAME : constant NAME := I_80x86 ;
STORAGE_UNIT : constant := 8 ;
MEMORY_SIZE : constant := 640 * 1024 ;

— System-Dependent Named Numbers:

MIN_INT : constant := -(2**31) ;
MAX_INT : constant := 2**31 - 1 ;
MAX_DIGITS : constant := 6 ;
MAX_MANTISSA : constant := 31 ;
FINE_DELTA : constant := 2#1.0#E-31 ;
TICK : constant := 1.0 / 18.2 ;

— Other System-Dependent Declarations

subtype PRIORITY is INTEGER range 1..10 ;

...
end SYSTEM;

(4) Representation Clause Restrictions

Representation clauses specify how the types of the language are to be mapped onto the underlying machine. The following are restrictions on representation clauses.

Address Clause

Not supported.

Length Clause

Not supported.

Enumeration Representation Clause

Not supported.

Record Representation Clause

Not supported.

(5) Conventions

The following conventions are used for an implementation-generated name denoting implementation-dependent components.

There are no implementation-generated names.

(6) Address Clauses

Address clauses are not supported.

(7) Unchecked Conversions

The following are restrictions on unchecked conversions, including those depending on the respective sizes of objects of the source and target.

Unchecked conversions are allowed between any types which are implemented on the same physical size.

(8) Input-Output Packages

The following are implementation-dependent characteristics of the input-output packages.

SEQUENTIAL_IO Package

SEQUENTIAL_IO is defined as specified in the Standard. However SEQUENTIAL_IO is not supported for unconstrained types. The instantiation is accepted, but any call to OPEN or CREATE will raise USE_ERROR.

DIRECT_IO Package

DIRECT_IO is defined as specified in the Standard with COUNT defined as follows :

type COUNT is range 0 .. 2_147_483_647 ;

However DIRECT_IO is not supported for unconstrained types. The instantiation is accepted, but any call to OPEN or CREATE will raise USE_ERROR.

TEXT_IO Package

type COUNT is range 0 .. 2_147_483_647 ;

subtype FFIELD is INTEGER range 0 .. 255 ;

LOW_LEVEL_IO

Not supported.

(9) Package STANDARD

type INTEGER is range -32768..32767 ;

type SHORT_INTEGER is range -128..127 ;

type LONG_INTEGER is
range -2_147_483_648..2_147_483_647 ;

— no other predefined integer types

type FLOAT is digits 6 range

-2#1.111_1111_1111_1111_1111_1111#E+127

.. 2#1.111_1111_1111_1111_1111_1111#E+127 ;

— type SHORT_FLOAT is not implemented ;

— type LONG_FLOAT is not implemented ;

— no other predefined floating point types

type DURATION is delta

0.001 range -86_400.0 .. 86_400.0 ;

— no predefined types other than those required by the Standard.

(10) File Names

File names make no use of conventions except those of the operating system.

Name and Meaning	Value
------------------	-------

\$EXTENDED_ASCII_CHARS

A string literal containing all the ASCII characters with printable graphics that are not in the basic 55 Ada character set.

"abcdefghijklmnopqrstuvwxyz!\$%&'()*~"

\$NON_ASCII_CHAR_TYPE

An enumerated type definition for a character type whose literals are the identifier NON_NULL and all non-ASCII characters with printable graphics.

(NON_NULL)

\$BLANKS

Blanks of length MAX_IN_LEN - 20

\$MAX_DIGITS

Maximum digits supported for floating point types.

6

\$NAME

A name of a predefined numeric type other than FLOAT, INTEGER, SHORT_FLOAT, SHORT_INTEGER, LONG_FLOAT, LONG_INTEGER, or DURATION. AlsyCOMP_003 supports no other type, so an arbitrary name was used.

LONG_LONG_INTEGER

\$INTEGER_FIRST

The universal integer literal expression whose value is INTEGER'FIRST.

-32768

<u>Name and Meaning</u>	<u>Value</u>
-------------------------	--------------

\$INTEGER_LAST

The universal integer literal expression whose value is INTEGER'LAST.

32767

\$MAX_INT

The universal integer expression whose value is SYSTEM.MAX_INT

2147483647

\$LESS_THAN_DURATION

A universal real value that lies between DURATION'BASE'FIRST and DURATION'FIRST or any value in the range of DURATION.

-100_000.0

\$GREATER_THAN_DURATION

A universal real value that lies between DURATION'BASE'LAST and DURATION'LAST or any value in the range of DURATION.

100_000.0

\$LESS_THAN_DURATION_BASE_FIRST

The universal real value that is less than DURATION'BASE'FIRST.

-33_554_433.0

\$GREATER_THAN_DURATION_BASE_LAST

The universal real value that is greater than DURATION'BASE'LAST.

33_554_434.0

\$COUNT_LAST

Value of COUNT'LAST in TEXT_IO package.

2147483647

\$FIELD_LAST

Value of FIELD'LAST in TEXT_IO package.

255

Name and Meaning	Value
------------------	-------

<p>\$FILE_NAME_WITH_BAD_CHARS An illegal external file name that either contains invalid characters or is too long.</p>	
---	--

X}}|@/\$~Y

<p>\$FILE_NAME_WITH_WILD_CARD_CHAR An external file name that either contains a wild card character or is too long.</p>	
---	--

XYZ*

<p>\$ILLEGAL_EXTERNAL_FILE_NAME1 Illegal external file name.</p>	
--	--

BAD-CHARACTER**

<p>\$ILLEGAL_EXTERNAL_FILE_NAME2 Illegal external file names.</p>	
---	--

MUCH-TOO-LONG-NAME-FOR-A-FILE

AleyCOMP_003, version 1.1.1

05/22/86

Validation Summary Report

APPENDIX C

COMMAND SCRIPTS

File : DO_A.ADW

invoke acvc_env.adw, Y

```
--
compile      a21001a.ada, list=lst\a21001a.lst
bind        a21001a
system.execute a21001a
--
compile      a22002a.ada, list=lst\a22002a.lst
bind        a22002a
system.execute a22002a
--
compile      a22006b.ada, list=lst\a22006b.lst
bind        a22006b
system.execute a22006b
--
compile      a26004a.exp, list=lst\a26004a.lst
bind        a26004a
system.execute a26004a
--
compile      a29002a.ada, list=lst\a29002a.lst
bind        a29002a
system.execute a29002a
--
compile      a29002b.ada, list=lst\a29002b.lst
bind        a29002b
system.execute a29002b
--
compile      a29002c.ada, list=lst\a29002c.lst
bind        a29002c
system.execute a29002c
--
compile      a29002d.ada, list=lst\a29002d.lst
bind        a29002d
system.execute a29002d
--
compile      a29002e.ada, list=lst\a29002e.lst
bind        a29002e
system.execute a29002e
--
compile      a29002f.ada, list=lst\a29002f.lst
bind        a29002f
system.execute a29002f
--
compile      a29002g.ada, list=lst\a29002g.lst
bind        a29002g
system.execute a29002g
--
compile      a29002h.ada, list=lst\a29002h.lst
bind        a29002h
system.execute a29002h
--
compile      a29002i.ada, list=lst\a29002i.lst
bind        a29002i
system.execute a29002i
--
compile      a29002j.ada, list=lst\a29002j.lst
bind        a29002j
system.execute a29002j
--
compile      a2a031a.ada, list=lst\a2a031a.lst
```

```
bind a2a021a
system.execute a2a011a
--
compile a32203b.ada, list=lst\a32203b.lst
bind a32203b
system.execute a32203b
--
compile a32203c.ada, list=lst\a32203c.lst
bind a32203c
system.execute a32203c
--
compile a32203d.ada, list=lst\a32203d.lst
bind a32203d
system.execute a32203d
--
compile a34008b.ada, list=lst\a34008b.lst
bind a34008b
system.execute a34008b
--
compile a38106d.ada, list=lst\a38106d.lst
bind a38106d
system.execute a38106d
--
compile a38106e.ada, list=lst\a38106e.lst
bind a38106e
system.execute a38106e
--
compile a38199a.ada, list=lst\a38199a.lst
bind a38199a
system.execute a38199a
--
compile a38199b.ada, list=lst\a38199b.lst
bind a38199b
system.execute a38199b
--
compile a38199c0.ada, list=lst\a38199c0.lst
compile a38199c1.ada, list=lst\a38199c1.lst
compile a38199c2.ada, list=lst\a38199c2.lst
bind a38199c1m
system.execute a38199c1m
--
compile a54b01a.ada, list=lst\a54b01a.lst
bind a54b01a
system.execute a54b01a
--
compile a54b02a.ada, list=lst\a54b02a.lst
bind a54b02a
system.execute a54b02a
--
compile a55b12a.ada, list=lst\a55b12a.lst
bind a55b12a
system.execute a55b12a
--
compile a55b13a.ada, list=lst\a55b13a.lst
bind a55b13a
system.execute a55b13a
--
compile a55b14a.ada, list=lst\a55b14a.lst
bind a55b14a
system.execute a55b14a
```

```
--  
compile      a62006d.ada, list=lst\a62006d.lst  
bind        a62006d  
system.execute a62006d  
--  
compile      a63202a.ada, list=lst\a63202a.lst  
bind        a63202a  
system.execute a63202a  
--  
compile      a71002a.ada, list=lst\a71002a.lst  
bind        a71002a  
system.execute a71002a  
--  
compile      a71004a.ada, list=lst\a71004a.lst  
bind        a71004a  
system.execute a71004a  
--  
compile      a72001a.ada, list=lst\a72001a.lst  
bind        a72001a  
system.execute a72001a  
--  
compile      a73001i.ada, list=lst\a73001i.lst  
bind        a73001i  
system.execute a73001i  
--  
compile      a73001j.ada, list=lst\a73001j.lst  
bind        a73001j  
system.execute a73001j  
--  
compile      a74006a.ada, list=lst\a74006a.lst  
bind        a74006a  
system.execute a74006a  
--  
compile      a74105b.ada, list=lst\a74105b.lst  
bind        a74105b  
system.execute a74105b  
--  
compile      a74106a.ada, list=lst\a74106a.lst  
bind        a74106a  
system.execute a74106a  
--  
compile      a74106b.ada, list=lst\a74106b.lst  
bind        a74106b  
system.execute a74106b  
--  
compile      a74106c.ada, list=lst\a74106c.lst  
bind        a74106c  
system.execute a74106c  
--  
compile      a74205e.ada, list=lst\a74205e.lst  
bind        a74205e  
system.execute a74205e  
--  
compile      a74205f.ada, list=lst\a74205f.lst  
bind        a74205f  
system.execute a74205f  
--  
compile      a83a02a.ada, list=lst\a83a02a.lst  
bind        a83a02a  
system.execute a83a02a
```

```
--
compile      a83a02b.ada, list=lst\a83a02b.lst
bind        a83a02b
system.execute a83a02b
--
compile      a83a06a.ada, list=lst\a83a06a.lst
bind        a83a06a
system.execute a83a06a
--
compile      a83c01c.ada, list=lst\a83c01c.lst
bind        a83c01c
system.execute a83c01c
--
compile      a83c01d.ada, list=lst\a83c01d.lst
bind        a83c01d
system.execute a83c01d
--
compile      a83c01e.ada, list=lst\a83c01e.lst
bind        a83c01e
system.execute a83c01e
--
compile      a83c01f.ada, list=lst\a83c01f.lst
bind        a83c01f
system.execute a83c01f
--
compile      a83c01g.ada, list=lst\a83c01g.lst
bind        a83c01g
system.execute a83c01g
--
compile      a83c01h.ada, list=lst\a83c01h.lst
bind        a83c01h
system.execute a83c01h
--
compile      a83c01i.ada, list=lst\a83c01i.lst
bind        a83c01i
system.execute a83c01i
--
compile a83c01j.ada, list=lst\a83c01j.lst
bind        a83c01j
system.execute a83c01j
--
compile a85007d.ada, list=lst\a85007d.lst
bind        a85007d
system.execute a85007d
--
compile a85013b.ada, list=lst\a85013b.lst
bind        a85013b
system.execute a85013b
--
compile a91002m.ada, list=lst\a91002m.lst
bind        a91002m
system.execute a91002m
--
compile a95005a.ada, list=lst\a95005a.lst
bind        a95005a
system.execute a95005a
--
compile a97106a.ada, list=lst\a97106a.lst
bind        a97106a
system.execute a97106a
```

```
--
compile ae2101a.ada, list=lst\ae2101a.lst
bind ae2101a
system.execute ae2101a
--
compile ae2101b.ada, list=lst\ae2101b.lst
bind ae2101b
system.execute ae2101b
--
compile ae2101c.dep, list=lst\ae2101c.lst
bind ae2101c
system.execute ae2101c
--
compile ae2101d.ada, list=lst\ae2101d.lst
bind ae2101d
system.execute ae2101d
--
compile ae2101f.ada, list=lst\ae2101f.lst
bind ae2101f
system.execute ae2101f
--
compile ae2101h.dep, list=lst\ae2101h.lst
bind ae2101h
system.execute ae2101h
--
compile ae2101s.ada, list=lst\ae2101s.lst
bind ae2101s
system.execute ae2101s
--
compile ae2101t.ada, list=lst\ae2101t.lst
bind ae2101t
system.execute ae2101t
--
compile ae2101u.ada, list=lst\ae2101u.lst
bind ae2101u
system.execute ae2101u
--
compile ae2101v.ada, list=lst\ae2101v.lst
bind ae2101v
system.execute ae2101v
--
compile ae3101a.ada, list=lst\ae3101a.lst
bind ae3101a
system.execute ae3101a
--
compile ae3702a.ada, list=lst\ae3702a.lst
bind ae3702a
system.execute ae3702a
--
compile ae3709a.ada, list=lst\ae3709a.lst
bind ae3709a
system.execute ae3709a
```

File : ACVC_ENV.ADW

```
default.system stay_resident=no
default.compile library      = \acvc\adalib,
  banner                    = yes,
  text                      = yes,
  line_length               = 79,
  error                     = 999
default.bind lib=\acvc\adalib
lib.new \acvc\adalib,task, overwrite
```

File : EXECUTE.BAT

```
echo on
%1 > res\%1.res
erase %1.obj
erase %1.exe
erase %1.lnk
```

APPENDIX D

TEST NAMING

Each test name indicates the class of the test and which test objective in the ACVC Implementers' Guide applies to the test.

Each test has a name that identifies the section of the Ada Standard addressed by the test objective. The name of a test is interpreted according to the table below, where the first column indicates the character position in the name and the second column, the meaning of that position:

POS	MEANING
1	Test class: A, B, C, D, E, L.
2	Implementers' Guide chapter number (in hexadecimal).
3	Implementers' Guide section number within a chapter (in Hexadecimal)
4	Implementers' Guide subsection number (in hexadecimal)
5-6	Implementers' Guide Test Objective number (in decimal)
7	Test sequence letter
8	[Optional] Compilation sequence digit or letter
9	[Optional] Main program designator in the case of a test having multiple compilation units.

Characters 8 and 9 are only present for tests that consist of several separately compiled units. A series of separately compiled units is counted as one test for reporting purposes. The eighth character indicates the order in which the units are to be compiled, with unit 0 being compiled first. The ninth character is only present for a file containing a main program for a test comprising multiple files and is always M.

A file name ending with the extension .TST indicates that the test depends on one or more of the implementation-dependent parameters listed in Appendix B. A file name ending with .DEP indicates that the test is not necessarily applicable to all implementations because it depends upon the support of language features that a compiler may legally not implement.

A test may comprise several separate compilation units contained in two or more files; the names of such files are indented under the name of the test. The letter "M" indicates which of these files contains the main procedure."

END OF DOCUMENT

END

DATE
FILMED

2-87