ŀ	ND-81	rg 606	LAS	ER CLA	DDING	OF NG RESIST	AND N	CUS IL	VYS FO	R INPR	OVED AT UN		1/3	
	UNCLAS	SSIFIE	D J M	AZUNDE	RET	AL. JA	N 87 A	FOSR-1	12 ENG. 12-87-1	9441	F/G 1	1/6	NL.	
			* 5 a											
										**			1	
	A - M 2		8 8				Θ							
-														
ĉ	<u></u>													



We we want the second secon

CANAL CONTRACTOR CONTRACTOR CONTRACTOR



Annual Report (January 1986 through January 1987)

606

AD-A179

LASER CLADDING OF Mg AND Nb ALLOYS FOR IMPROVED ENVIRONMENTAL RESISTANCE

Approx of for public release: faction at on unlimited.

Contract No. AFOSR 86-0034 submitted to Air Force Office of Scientific Research **Building 410** ATTN: Dr. A. Rosenstein **Bolling Air Force Base** Washington, DC 20332

submitted by

J. MAZUMDER, Principal Investigator, J. SINGH, Research Associate, and

S. RAJA, Graduate Research Assistant

Laser Aided Materials Processing Laboratory Department of Mechanical and Industrial Engineering University of Illinois at Urbana-Champaign Urbana, IL 61801

DTIC ELECTE APR 2 7 1987 П

REPORT DOCUMENTATION PAGE a Report SECURITY CLASSIFICATION to REPORT SECURITY CLASSIFICATION AUTORNITY a Report SECURITY CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION AUTORNITY a OCCUSENT CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION AUTORNITY b OCCUSENT CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION AUTORNITY b OCCUSENT CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION AUTORNITY b OCCUSENT CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION b OCCUSENT CLASSIFICATION AUTORNITY b SECURITY CLASSIFICATION b OCCUSENT CLASSIFICATION b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b SECURITY INFORMACTION NUMBER b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL b OFFICE STUDOL	CURITY CLA			والأوين مورد متحرب معروف الكائلي				
				REPORT DOCUM	INTATION PAG	E		
Inclassified to Authom to Schebout > Distriction (Authom to Schebout) Approved for public release; distribution unlisted, distribution unlisted, dis	A REPORT S	ECURITY CLA	SIFICATION		ID. RESTRICTIVE N	ARKINGS		
Appreved for public release; distribution unitatized; Image: Anomalia of an ison and an anomalia of anomalia of an anomalia of anomalia of an anomalia of an anomalia of anomania of anomalia of an anomalia of anomalia of an anomalia	linclas	SIFIED	ION AUTHORITY		3 DISTRIBUTION	VAILABILITY OF	FREPORT	
DECLASSINGLATION DOWNGRAPHOLE distribution unlistica distribution distribution unlistica distribution dist	-				ADDFOV	ed for muhlte	TALAASA .	
Image and an isotron with a second and	DECLASS	FICATION/DO	WIGRADING SCHE		distri	bution unlim	1104.	
A Add GF FERTORMING ORGANIZATION B. OFFICE SYMBOL Is NAME OF MONITORING ORGANIZATION INTUESILY OF Illinois Iffeedeable: AFOSE Intversity of Illinois Iffeedeable: AFOSE Intversity of Illinois Iffeedeable: AFOSE Intversity of Illinois Iffeedeable: Iffeedeable: Intversity of Illinois Officials Industrial Iffeedeable: Intversity of Illinois Officials Industrial Iffeedeable: Intversity Officials Industrial Iffeedeable: Iffeedeable: Name of Function Iffeedeable: Iffeedeable: Iffeedeable: Same as 24 NE Officials Industrial Iffeedeable: Iffeedeable: Same as 24 NE Iffeedeable: Iffeedeable: Iffeedeable: Iffeedeable: Same as 24 NE Iffeedeable: Iffeedeable: Iffeedeable: Iffeedeable: Same as 24 NE Ne Affeedeable: Iffeedeable: Iffeedeable: Same as 24 NE Ne Affeedeable: Iffeedeable: Iffeedeable:	PERFORM	NG ORGANIZA	TION REPORT NUN	18E A (\$)	S. MONITORING OF	SR-TH- E	37-04	4 1
The spectrum of fillinois AFOSE AFOSE The appresent of Section definition is an approximate of Section for the section for the section is an approximate of Section for the sectin for the section for the section for the sec	A NAME OF	PERFORMING	ORGANIZATION	B. OFFICE SYMBOL	TA NAME OF MONI	TORING ORGANI	ZATION	
bit ADDRESS (Cir, Same and 210 Const. Department of Nechanical & Industrial Ingineer Urbana. Illinois 61801 Name of Jacobias (Cir, Same and 210 Const. Namodias (Cir, Same and 210 Const. <td< td=""><td>Univer</td><td>sity of</td><td>Illinois</td><td></td><td>AFOSR</td><td></td><td></td><td></td></td<>	Univer	sity of	Illinois		AFOSR			
Importance of Accounter of Accounter of Thouser and the second account of Accounter of Acco	ADDRESS	City State and	ZIP Code :	ا منه محرف برابرو ا	75. ADDRESS (City	Siem and ZIP Cod	10 /	
Bolling AFB. DC 20332-0448 Bolling AFB. DC 20332-0448 Name of Photomosocomonic in Section Sympton Same as 7.4 NE ADDMESSION Section of Sile of Si	- Depa rt - Engine	nent of . er	geenanical	a industrial	t that t	N.		
Bandani String Banda	<u>Urbana</u>	. Illino	is 61801		Bolling	AFB, DC	20332-6448	3
Same as 74 NE AFGS Q. Sec. (0.54) > ADDRESS (Cir Sinu and EIP Comp. NE Nonce of subscience of the substrate melts and subscience of the subscrate of the subscrate of the subscrate of subscience of subscience of the subscrate of the subscrate of subscience of the subscrate of the subsc	DRGANIZ	FUNDING/SPC	MECRING	B. OFFICE SYMBOL (If applicable)	9. PROCUREMENT	INSTRUMENT (D	ENTIFICATION N	
ADDMENS (Cir) Sinn and 21P Comp. is Source of Function Mode Same is 7b is Source of Function Marketimer Lasser - Lindding of CollColl No No No & Ab Alloys for Improved Lavisonment (GIIColl 230+ All No & Ab Alloys for Improved Lavisonment (GIIColl 230+ All No & Ab Alloys for Improved Lavisonment (GIIColl 230+ All 12 MESONAL AUTHORS 13b Time Coverso (GIIColl 230+ All 13 Tree of Report 13b Time Coverso (GIIColl 230+ All 13 Tree of Report 13b Time Coverso (GIIColl 230+ All 14 Long Coverso 14b Date Coverso 14b Date Coverso 15b Pace Count 14 Coverson 14b Date Coverso 14b Date Coverso 15b Pace Count 15 BUB/LEMENTARY NOTATION 14b Date Coverso 14b Date Coverso 15b Date Coverso 15 Costar cools 14b Subject Trends Consult on Harder Coverso 15b Date Coverso 15b Date Coverso 16 Bub/LEMENTARY NOTATION 14b Date Coverso 15b Date Coverso 15b Date Coverso 16 Bub/LEMENTARY NOTATION 14b Date Coverso 15b Date Coverso 15b Date Coverso <td>_Same_a</td> <td>s 7a</td> <td></td> <td>N E</td> <td>AFCISR-1</td> <td>ñe-0034</td> <td></td> <td></td>	_Same_a	s 7a		N E	AFCISR-1	ñe-0034		
Same as 7b PROACT Take No PROACT Take No 11 Mo A Allows for Improved Lavitonmen (1)(2) 230 All No No A Allows for Improved Lavitonmen (1)(2) 230 All No No A Allows for Improved Lavitonmen (1)(2) 230 All No No A Allows for Improved Lavitonmen (1)(2) 230 All No 12 PREOR (1) Estimate covered (1)(2) (1)(2) (1)(2) (1)(2) 13 Tree of Reform (1) Estimate covered (1)(2) (1)(2) (1)(2) (1)(2) 13 Tree of Reform (1) Estimate covered (1)(2) (1)(2) (1)(2) (1)(2) 13 The present status of Laviton the formation of the status of laviton the formation of the status of laviton the formation of the present project grant laviton the been discussed. (1) (1)(2) (1)(2) (1)(2) (1)(2) 14 Estimate of the lavit formation of the status of the sta		City State and	ZIP Code)		10. SOURCE OF FL	NDING NOS	······································	
Same as 7b (110.3) 230. Al IN TYLE House Benuty Comments Laser cladding of Me A Nb Alloys for Improved Environment (110.3) 230. Al In A Nb Alloys for Improved Environment (110.3) 230. Al In Construction Is Viel Covered Environment (110.3) 230. Al In Construction Is Viel Covered Environment (110.3) 230. Al In Construction Is Viel Covered Environment (110.3) (110.3) (110.3) In Construction Is Under Vieland (110.3) (110.3) (110.3) (110.3) In the present status of laser cladding of We and Niobium has been surveyed. I potential of clading Zirconium onto the been discussed. In the present project zirconium has been cladded onto magnetime by preplaced power cladding technique. The laser beam encounters the power tirst place on the substrate. A very thin layer on the top of the substrate melts and results in a cladding of minimum dilution. (110.3) (110.3) (110.3) Isolation absorbered. The Structural characterization of the clad region was evaluated in a 3.5 percent Ma solution at room temperature. Substantial improvement in certoster resistant as been observed. The structural characterization of the clad region was evaluated in a 3.5 percent Ma solution at room temperature. Substantial improvement in certoster resistant as been observed. The structural characterization of the clad region was evaluated in a 3.5 percent Ma solution acerefect at the Coveren					PROGRAM	TOLORS	TASK	NORK UNIT
In the deside Security Chamber on Laser Cladding of No. A No. Allows for Improved Lavisonmen (allCA) In . Standar Inproved Lavisonmen In . Standar Isb Time Coverage Isb Tree of REPORT Isb Time Coverage Isb Time Coverage Isb Time Coverage Isb Tree of REPORT Isb Time Coverage Isb Time Coverage Isb Time Coverage	с					,30+	41	
Me A Nh Alloys for Improved Lavisonment 12. MacContaction 12. MacContaction 12. MacContaction 12. MacContaction 12. MacContaction 13. The coverage 13. The coverage 13. The coverage 13. The coverage 14. Date of account of the coverage 15. Contact on account of the coverage 14. Date of account of the coverage 15. Contact on account of the coverage 16. Contact on account of the coverage 17. Contact on account of the coverage 18. Contact on account of the coverage 19. Contact on account of the coverage 10. Group 10. The present status of laser cladding of (Mg) and Niebium has been surveyed. I potential of cladding, directact on the coverage 10. The present project zironium has been cladded onto magnesium by preplaced gowder cladding technique. The laser beam encounters the powder tirst place on the substrate melts and tectrosion resistance substrate account of the substrate melts and tectrosion resistance account the clad region was evoluated in a 3-b percent Ma solution accounters the powder to cladding of minimum dilution. 10. Corresten of the coverage 10. Coverage 11. The present state of the zr-clad region was evoluated in a 3-b percent Ma solution at room tector metroscopy. LDAS analysis has been done to identify of astract	<u></u>		Name Bastien		- (61031 -		· · · ·	
The cost of cost of cost of cost of the substrate of the substrate of the substrate of the substrate. A very thin layer on the top of the substrate melts and results in a cladding of minimum dilution. Correstion properties of the Zr-clad region was evaluated in a 3.5 percent Massion of the clad region was been done to cladd region was been done to cladd region was been done to cladding of minimum dilution. Correstion properties of the Zr-clad region was evaluated in a 3.5 percent Massion of the clad region was been done to cladd region was been done to clade region was clade region was been done to clade region was been done to clade region was been done to clade region was clade region was been done to clade region was been done to clade region was clade region was been done to clade region was	<u>Me A A</u> 12. PERSONA 134. TVPE OF <u>Annual</u> 16. SUPPLEN	ALLOYS LAUTHORIS) LZIERCE FREPORT	136 TIME FROM	er cladding ol ved Environmer COVERED Jan 86 to Jan 8	14 DATE OF REPO	DRT Yr Mo Der	I IS PAGE	
ABSTRACT Communications and denny by Maximum Market	Mo A N 12. PERSONA 13. TVPE OF Annual 16. SUPPLEN	ALLOYS LAUTHOR(S) LZUEGEE REPORT	IS TIME	er cladding ol ved Environmet COVERED Jan 86 to Jan 8	14 DATE OF REPO	DRT Yr No Dey	IS PAGE	
Addite of the status of laser cladding of (Mg) and Niobium has been surveyed. I potential of claddia, Zirconium onto Machesium and litanium onto Niobium for improving chyironmental resistance have been discussed. In the present project zironium has been cladded onto magnesium by preplaced powder cladding technique. The laser beam encounters the powder first place on the substrate. A very thin layer on the top of the substrate melts and results in a cladding of minimum dilution. Cerrosion properties of the Zr-clad region was evaluated in a 3.5 percent Masselution at room temperature. Substantial improvement in cerrosion resistant has been done to identify the phases observed in clectron miroscopy. EDAS analysis has been done to identify the phases observed in clectron miroscopy. I source to the identify the phases observed in clectron miroscopy. I source the identify the phases observed in clectron miroscopy. I source the identify the phases observed in clectron miroscopy. I source the identification of the phases observed in clectron miroscopy. I source the identification is and the phase observed in clectron miroscopy. I source the identification of the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in clectron miroscopy. I source the identification is the phase observed in cleater of the identification is the phase observed in cleater of the identification is the phase observed in cleater of the identhe identification is the phase of the iden	Mo A N 12. PERSONA 13. TYPE OF Annual 16. SUPPLEN 17. FIELD	ALLOYS LAUTHORIS REPORT REPORT	136. TIME 136. TIME #ROM	er cladding ol ved Environmel Covered Jan 86 to Jan 8	Continue on reverse of	DRT Yr Mo Dey	I IS PAGE	
The present status of laser cladding of (Mg) and Niobium has been surveyed. I potential of claddia, Zirconium onto Marnesium and Litanium onto Niobium for improving environmental resistance have been discussed. In the present project zironium has been cladded onto magnesium by preplaced power cladding technique. The laser beam encounters the powder first place on the substrate. A very thin layer on the top of the substrate melts and results in a cladding of minimum dilution. Cerrosion properties of the Zr-clad region was evaluated in a 3.5 percent Ma solution at room temperature. Substantial improvement in cerrosion resistan nas been observed. The structural characterization of the clad region was done by optical and electron miroscopy. EDAS analysis has been done to identify the phases observed in clectron miroscopy. The sub- cate of the substrate of the class of the class of the clade region was done by optical and electron miroscopy. EDAS analysis has been done to identify the phases observed in clectron miroscopy. The super- tice of the super- center of the phases of the class of the class of the super- dentified of the phases observed in clectron miroscopy. The super- tice of the super- tice of the super- ter of the phases of the super- ter of the phase of the top of the super- ter of the phase of the top of the super- ter of the phase of the top of the top of the super- ter of the phase of the top of the top of the top of the term of the phase of the top of the top of the top of the top of the term of the top of the term of the top of the term of the top of	Mo A N 12. PERSONA 13. TVPE OF Annual 16. SUPPLEN 17. FIELD	COSATI CC	136 TIME 136 TIME PROM ATION 0065 SUB: GR	er cladding ol yed Environmet COVERED Jan 86 to Jan 8	Continue on reverse of	necemary and ident	ary by black numb	
38. DISTRIBUTION/AVAILABILITY OF ABSTRACT 21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED/UNLIMITED I SAME AS RPT I DT CUSERS I 21. ABSTRACT SECURITY CLASSIFICATION 234. NAME OF RESPONSIBLE INDIVIDUAL 225. TELEPHONE NUMBER Include Area Code/ Include Area Code/ Inclu	Me A A 12. PERSONA Dr Min 13. TVPE OF Annual 10. SUPPLEN 17. PIELO	CT Continue of	TOT IMPROV 136. TIME FROM ATION DOES SUE GR	er cladding ol yed Environmen COVERED Jan 85 to Jan 8 IE SUBJECT TERMS	Con Baue on reverse of	necessary and ident	ary by block numb	COUNT COUNT COUNT
UNCLASSIFIED/UNLIMITED I SAME AS APT I DT CUSERS I 22. NAME OF RESPONSIBLE INDIVIDUAL Dr. A. Rosenstein 22. TELEPHONE NUMBER Include Ame Coder 767-4933	Me A N 12. PERSON 13. TVPE OF Annual 13. TVPE OF Annual 14. SUPLEN 15. PELO 17. PELO 17. PELO 17. PELO 18. PELO 19. PELO 19	COSATIC GROUP CCOSATIC GROUP CT Continue of Called of a claddin substra ts in a c sion prop ion at re ch obset ov optic.	Tion Improv Tib Time FROM ATION A	covered Jan 86 to Jan 8 Jan 80 to Jan 80 to Jan 8 Jan 80 to Jan 80	Consaw on rewrond Consaw on rewrond Magnesium at verbeen disc een cladded beam encout on the top of tion. egion was ev ntial improv aracterizat v. i.DAS and ron minoscop	iobium has necessry and dam iobium has nd litaniu ussed. onto magn nters the of the sub coluated i cement in ion of the alvsis has ov. 1	been sur monte Ni esium by powder ti strate me n a 3.5 p corrosion clad reg been don	count count objum for proplaced rst place its and ercent Ma resistan ion was c to
22. NAME OF RESPONSIBLE INDIVIDUAL 22. TELEPHONE NUMBER Include Ame Code: 767-4933 22. OFFICE SYMBOL	Me A N 12. PERSON 13. TYPE OF Annual 13. TYPE OF Annual 14. SUPLEN 15. SUPLEN 17. FILD 17. FILD 10. SUPLEN 10. SUPL	CT Continue of cosoft co gRoup CT Continue of cosoft of co present substra ts in a co sion prop ion at ro con obset by optic.	Tion Improv IDE TIME FROM ATION A	er cladding ol ved Environmel Covered Jan 86 to Jan 8 Jan 8 Jan 80 to Jan 8 Jan 8 Ja	Continue on murre of Continue on murre of May nessium ar verbeen disc een cladded beam encour on the top of tion. egion was evo ntial improviant aracterization v. EDAS and ron miroscop	iobium has necessory and deal iobium has nd litaniu ussed. onto magn aters the of the sub coluated i coment in ion of the alssis has py. 1	been sur monte Ni esium by powder ti strate me n a 3.5 p corrosion clad reg been don	COUNT COUNT 2 bium for obium for proplaced rst place its and orcent Mas cresistan ion was c to
	Me A N 12. PERSONA Dr Not 13. TVPE OF Annual 13. TVPE OF Annual 14. SUPPLEN 17. PIELO PIELO PIELO In the powdet result Cerres Selut nas be dene f ident 24. DISTRIC	COSATICC GROUP COSATICC GROUP CT Continue of Cosent st cial of c cing envi present cial of c cing envi present cial of c cing envi present cial of c cing envi present cing envi present con obset ov optic. ity the p	I or Improv I JE TIME FROM ATION	covered Jan Sbrojan S Jan S Jan Sbrojan S Jan S Jan Sbrojan S Jan S Jan Sbrojan S Jan Jan S Jan S Jan S Jan Jan Jan Jan Jan Jan Jan Jan Jan Jan	Container on rearrant Container on rearrant of (Mg) and Nat Magnesium at verbeen disc een cladded beam encout on the top of tion, egion was ev nical improv aracterization s. EDAS and ron minoscop	iobium has nd litaniu ussed. onto magn nters the of the sub coluated i coment in ion of the alvsis has pv. k sup	been sur monte Ni esium by powder ti strate me clad reg been don	veved. To objum for proplaced rst place its and ercent Mar resistan ion was c to

Laser Cladding of Mg and Nb Alloys for Improved Environmental Resistance

ŝ

5

3

A.

N

 \overline{C}

S. Raja, J. Singh, and J. Mazumder Laser Aided Materials Processing Laboratory Department of Mechanical and Industrial Engineering University of Illinois at Urbana-Champaign 1206 West Green Street Urbana, IL 61801



212222014

Constant and

Accesion 1 or		٩
NTIS COART DelC ING No 2000 - 200 DelC ING		• • • •
	• ••••	•
 		•
A-1		

TABLE OF CONTENTS

X.

Ż

ŝ

<u>k</u>

5

0

Ŋ

い い

ž

 $\boldsymbol{\lambda}_{i}^{*}$

	Pa	Ige
SUMMA	RYii	i
Ι.	INTRODUCTION	1
п.	EXPERIMENTAL PROCEDURE	6
ΙΙΙ.	RESULTS AND DISCUSSION. 3.1 Magnesium-Zirconium Alloy. 3.1.1 Optical Microscopy. 3.1.2 Electron Microscopy. 3.1.2.a Amorphous Phase. 3.1.2.b Martensite Phase. 3.1.2.c Precipitates. 3.1.3 Corrosion Properties of Laser Cladding of Zr onto Mg. 3.2 Niobium-Titanium Alloy.	9 9 9 9 9 9 1 1 1 2
IV.	FUTURE WORK	4
FIGUR	ES1	6
TABLE	S	2
REFER	ENCES	4

Υ.

1

iii

SUMMARY

-

S

3

2

.

The present status of laser cladding of Mg and Niobium has been surveyed. The potential of cladding Zirconium onto Magnesium and Titanium onto Niobium for improving environmental resistance have been discussed.

In the present project zirconium has been cladded onto magnesium by preplaced powder cladding technique. The laser beam encounters the powder first placed on the substrate. A very thin layer on the top of the substrate melts and results in a cladding of minimum dilution.

Corrosion properties of the Zr-clad region was evaluated in a 3.5 percent NaCl solution at room temperature. Substantial improvement in corrosion resistance has been observed. The structural characterization of the clad region was done by optical and electron microscopy. EDAX analysis has been done to identify the phases observed in electron microscopy.

Also titanium has been cladded onto Niobium. DTA thermal analysis of the clad region was done to study the = to ß transformation of the Ti-clad region. Variation in the solubility of Nb in Ti clad with laser processing conditions was observed. Corresponding electron microprobe analysis of the Ti-clad region revealed the extent of solubility of Nb in Ti. Structural characterization of the Ti clad region was done by optical microscopy.

The insitu cladding using screw feeder has been proposed and discussed.

I. INTRODUCTION

×.

ò

ž

Ŕ

E

2 2

5

3

1

Much emphasis has been made on laser cladding to modify the surface chemistry of materials to improve properties like wear resistance, corrosion and high temperature oxidation resistance.

Laser cladding is a material processing technique in which a metal or alloy of different composition is deposited onto the substrate. The substrate is locally melted by using laser beam to produce metallurgical bonding. The metal deposited onto the substrate and only thin layer of the top surface of the substrate are melted by the laser beam on account of high power density available from the focused laser beam. The localized heat source of laser with low specific energy input in conjunction with very short laser-material interaction time keep the substrate at low temperature and make the substrate as an intimate heat sink. The novel microstructure results from the high cooling rate. The best cladding is considered to be the one with minimum dilution of the clad layer on the substrate with a thin layer of interface between them.

The processing variables that influence the laser surface cladding are: power of the laser beau, beam diameter, spatial distribution, traverse speed, the chemistry of the substrate, and focusing conditions [1].

Under controlled cladding conditions, a laser beam melts a very thin surface layer of the substrate. This thin liquid layer mixes with the liquid cladding alloy and subsequently solidifies to form a metallic bonding between the cladding and substrate. A scheme has to be developed to choose the best combination of the processing variables for a particular application.

From the literature, it has been found out that laser surface alloying and laser cladding have been done by using either of the following methods to deposit the metal onto the substrate.

1) sputter-deposition [2]

Ĭ,

Ì

Š.

Z

Ŕ

*

22

electro deposition of thin film [3]

3) spraying or coating the metallic powder [4]

4) gas-borne injection of powder into the laser interaction zone [5].

Selective improvement of properties by material processing and subsequent microstructural studies have been done by using different techniques [6,7,8,9] such as rapid solidification process (RSP), laser alloying, plasma spraying and electron beam rapid quenching (EBRQ) process. The final microstructure obtained by this technique depends mainly upon heat and mass transfer, fluid flow and cooling rate.

Studies have been done on the microstructure and corrosion properties of laser irradiated Mg-Zn alloy [10]. In laser beads deposited on Mg-5.3% Zn-0.6% Zr alloy the microstructure was finely dendritic. Due to high cooling and growth rates the material was very homogeneous. Corrosion studies have revealed that corrosion rate of rapidly solidified Mg-Zn alloy immersed in a 3.5% NaCl aqueous solution is higher than that in a slowly solidified specimen. This increase in corrosion resistance has been attributed to the formation of finely distributed interdendritic nonequilibrium Mg-Zn₂ phase.

Irradiation with a CO_2 laser at 40 w/mm² refined the microstructure of the Mg-Li alloy to a depth of 1.5 mm and raised its corrosion resistance [11]. In the laser affected zone, the alloy has a homogeneous fine-grained microstructure with an average grain size up to 2 um. The corrosion resistance of this Mg-Li alloy in a 3% NaCl solution was shown to increase by a factor of 30 after irradiating the surface by a pulsed laser and by more than an order of magnitude following irradiation by a continuous wave laser. The increase in corrosion resistance has been attributed to the grain refinement and absence of structural defects.

The main aim of the present investigation is to study: (1) the corrosion properties of cladding of Zr onto the Mg substrate, and (2) high temperature oxidation resistance of laser clad Nb alloys. To the best of the authors' knowledge, the corrosion studies of laser clad Mg-Zr system and Nb alloys have not been reported in the literature.

3

E

۱. ۲.

5

ŝ

÷,

À

.

5

It is reported that the structural refinement, achievement of nonequilibrium phases and extremely homogeneous amorphous alloys concomitant of very high cooling rate prevailing under laser processing conditions improve the oxidation and corrosion properties considerably. The rationale for choosing Zr as the cladding metal for Nb is to generate these phases which are proven resistant to corrosion and oxidation in several alloy systems such as Nb-Ti-Zr [12], Nb-Zr [13], Nb-Mo-Zr [14], and Nb-Ti-Al-Zr [15].

Studies of laser-alloyed zirconium-containing surface layers have been reported [16]. Thin films of Zr on Fe, Ni, Al, V, and Ti have been alloyed with the substrate metals using the pulse laser.

The recent review [17] of the current state of the art of coating systems classifies the coatings available under two headings: "metallic coatings" and "ceramic thermal barrier coatings". Among the coating techniques laser cladding has unique potentials: production of extremely homogeneous amorphous alloy phases on account of rapid cooling rate prevailing under laser-material processing conditions, less loss of materials, feasibility of controlling alloy chemistry, minimized dilutions, minimized distortion and minimized post processing machining [18].

Laser cladding of Nb with Ti is carried out in this experiment. In the literature there are no reports dealing with the oxidation behavior of laser cladded Nb alloys. A sizeable body of the literature deals with high temperature oxidation properties of surface coated Nb-alloys. In these cases

surface coating has been done by diffusion using liquid metal as transport medium. The diffusion coating has been subsequently oxidized to produce transient oxide layer which is found to improve the oxidation resistance. In the diffusion coating of Nb, liquid Na was used as transport medium [2] since it is immune to corrosion in this medium. The kinetics of diffusion coating is very slow and almost 10 to 12 hours dipping has to be done at temperatures as high as 1200 to 1300°C. This coating was followed by rapid cooling to develop finer microstructure which results in improved oxidation resistance.

Some of the Nb alloys which have been studied and experimented with heat resistant coatings are given below; it is important to note that in all these cases, the coating has been done by diffusion in liquid metal medium.

1. Nb - 1 at % Zr [19]

- 2. Nb 10, 20, 30 wt%, Ti [20]
- 3. Nb A1 [21]

Ċ,

Ş

シンシン

۲.

- 4. Nb 5W 3 Mo 1 Zr 0.02 C [22]
- 5. Nb 5% Mo 1% Zr [23]
- 6. Nb 40% Ti 3-7% Al, 0.06% C [24]

It has been reported that the Nb-alloy substrates given above have been alloyed or coated with either of the following alloying elements.

- 1. A1, Zr, Cr, Mo [25]
- 2. Mo-B-Si [26]
- 3. S1-T1 [22]
- 4. Cr-Si-Ti, Mo [27]
- 5. Zr, V [28]
- 6. Ti, Ta [29]
- 7. Cr, V [30]

8. Re, V, Pt, Si, Cr [31]

9. Ti, Al [32]

S

5

Ś

ř

Ŋ

N

.

Perrin [20] has studied the influence of Ti content on oxidation of Nb-Ti alloys. Ti is found to form protective oxide layer and oxygen diffusion is the preponderant mechanism of oxidation. Ti has been increased in Nb from 10 to 30 wt% and oxidation test has been carried out in air at 400 to 1300°C. Depth of oxygen penetration decreased with increase in Ti content. Above 700°C, Ti addition in Nb gave parabolic oxidation rate which implies the protective nature of oxide scale.

5

Pure Nb has poor oxidation resistance [33] above 300°C and appreciable high temperature strength (Table 3). But the alloys with Ti, as in the case of pure Ti, hardly oxidize at all up to 800°C. There has been a considerable decrease in the constant of parabolic oxidation rate at 1000°C. Also there was a change in the type of oxidation rate at 1200°C, it changed from linear to parabolic. Introduction of Ti into Nb caused a considerable improvement in the scale resistance which increased with increasing Ti content.

The oxidation of Nb base alloys has been studied by several authors [34-37] and among these alloys, the Nb-Ti alloys exhibit improved oxidation resistance [20]. In this regard, another aim of the present investigation is laser cladding of Ti onto Nb substrate and evaluation of oxidation properties of the clad.

II. EXPERIMENTAL PROCEDURE

3

, . .

4

Ş

The experimental set-up for laser cladding is shown in Fig. 1. It consists of a stainless steel chamber. Ar gas was used to maintain an inert atmosphere inside the chamber at a pressure 20 ps: inside the chamber. It provided shielding of the substrate which minimized the surface contamination and prevent oxidation of Mg which is pyrophoric. The plasma formation at the laser-substrate interaction point was also suppressed by the Ar atmosphere and above atmospheric pressure.

The cladding treatments were carried out using a continuous wave CO_2 laser with 1.5 kW. In the present investigation, laser was operated at 800-1000 W in the TEM*₀₀ mode (Gaussian distribution). The cladding was performed with an underfocused beam of 1.5 to 3 mm diameter. Mg specimens (63.5 mm thick) were traversed relative to the laser beam at the speed of 20 to 50 inches per minute.

Zr powder used was 99.99% pure with particle size 20 _m supplied by Johnson Matthey, AESAR. Zr powder was directly applied on to the Mg specimen and compacted to prevent loose packing.

The formation of cracks due to thermal shock by rapid heating and cooling rates during laser processing was prevented by preheating the Mg substrate by laser interaction.

Ti has been cladded onto Nb using a 10 kW CW CO_2 laser. Prior to cladding the Ti powder (99.9 percent pure, supplied by Johnson Matthey, AESAR) was annealed in a temperature controlled tubular furnace for about 16 hours to get rid of moisture. The cladding was carried out by placing the powder on the Nb cylindrical specimen (20 mm height, 12.57 mm dia.) prior to laser-metal interaction.

The laser cladding process variables used are in the following range:

Laser power: 4 to 8 kW Laser beam d'ameter: 3 mm

.

. .

Scanning speed: 20 to 50 ipm (inches per minute)

For the optical microscope observation, an etchant of 3% HNO₃ in methanol was used for Mg-Zr clad, and an etchant of 5 ml HNO₃, 2.5 ml HF and 17.5 ml water was used for Nb-Ti clad. The optical microscope used was LEITZ.

Microstructural investigations of clad specimens were carried out by optical and Electron Microprobe Analysis (EPMA) and electron microscopy. Samples for transmission electron microscopy were sectioned in the laser clad region. After mechanically thinning the samples, discs of 3 mm diameter were punched from the clad region. Specimens for TEM observations were prepared by dimpling followed by ion-beam thinning technique by using Ar ion-beam at an angle of 12' to the surface in a cold chamber to avoid phase transformation of metastable phases due to heat developed during ion bombardment. The TEM samples were observed using philips EM 430 microscope (attached with EDAX), operated at 300 kV.

The corrosion studies of Mg alloys were carried out in EG&G PARK corrosion testing system (Fig. 2). Sections from the clad region parallel to the clad/substrate interface were cut and exposed to 3.5% NaCl solution. Potentio dynamic and corrosion potential testings were carried out at room temperature.

The differential thermal analysis (DTA) of the Nb-Ti clad region was carried out using Perkin-Elmer 1700 Differential Thermal analyzer. The sampling for DTA was done as follows: thin sections of the clad region were cut normal to the clad/substrate interface using Buehler ISOMET low speed diamond saw. The samples were subsequently cleaned using acetone and dichloroethane.

7

The thermal analysis was carried out with the following experimental variables:

T_{min} : 100°C T_{max} : 1500°C Heating Rate 40°C/min Cooling Rate 40°C/min.

Č

Ş

5

2

X

52

5

3

Ż

Ş

В

 $\mathbf{\overline{N}}$

Ar was used for the cooling curve determination at the flow rate of 30 cc/min.

8

III. RESULTS AND DISCUSSION

3.1 Magnesium-Zirconium Alloy

3

ý

2

K

Ś

5

3.1.1 Optical Microscopy

The general microstructura' survey of the laser clad region by optical microscopy revealed two distinct phases (Fig. 3a and 3b).

The clad region is divided into two parts (Fig. 3a): the lower zone shows duplex microstructure of two phases and the upper zone shows homogeneous microstructure. The electron microprobe analysis of laser clad/substrate region is shown in Fig. 4. The width of the lower zone, which is adjacent to the clad/substrate interface, is approximately 200 Lm.

The optical micrograph near the interface at a higher magnification (Fig. 3b) shows the two phases. The microprobe analysis in the bottom zone shows the depletion of Mg at a point where Zr is enriched and vice versa. This suggests two phases one rich in Mg and another rich in Zr exist near the interface. By contrast and the microanalysis, the bright phase was found to be rich in Zr.

3.1.2 Electron Microscopy

The general microstructural survey of the laser clad region by transmission electron microscopy (TEM) revealed several phases: amorphous, crystalline, precipitates, and matrix with high density of dislocations.

3.1.2.a Amorphous Phase

In a thin foil prepared from the clad region it was observed in the TEM that an amorphous region was contiguous to a crystalline region. This is shown in the bright field (BF) micrograph in Fig. 5a. Figure 5b shows the selected area diffraction pattern (SAD) from the region marked 'A' in Fig. 5a and the diffused rings shows that region 'A' is amorphous. Figure 5c shows the SAD pattern from regions marked 'B' and 'C' and consist of diffuse rings due to amorphous phase and diffraction spots due to crystalline phase in these regions.

S

Ś

Š

Š

Ś

Ś

r

2

The X-ray microanalysis of the amorphous phase is shown in Fig. 6. The quantitative microanalysis from amorphous phase (region A) revealed that this phase contains 85.56 wt% Zr and 14.439 wt% Mg.

The X-ray microanalysis of the region B is shown in Fig. 7. The quantitative analysis done for the EDAX spectrum from this region revealed that this region contains equal amount of Zr (50.56 wt%) and Mg (49.431 wt%).

The X-ray microanalysis of the region marked C is shown in Fig. 8. The quantitative analysis done for the EDAX spectrum from this region revealed that this region is rich in Mg (74.464 wt%) and depleted in Zr (25.536 wt%).

From the electron microscopic investigation in conjunction with X-ray microanalysis, an amorphous phase rich in Zr and an interface containing equal amount of Zr and Mg and an adjacent region rich in Mg were found. The amount of Mg increases as one move from the amorphous phase towards the interface.

Similar findings have also been observed in Cu-Zr system [38]. Amorphous surface layer 30 to 70 μ m thick in the alloy Cu-43 at % Zr by laser radiation under suitable condition has been reported in the literature. It is reported that, even on melting treatment at larger areas by overlapping pulse irradiation, the glassy structure may be retained in the topmost structure.

Capelli [39] has pointed out the attainment of amorphous alloys by laser glazing. The extremely rapid cooling rates of thin molten zones formed by laser interaction have produced a variety of novel, extremely homogeneous microstructure, including amorphous alloys.

10

いていた。

3.1.2.b Martensite Phase

2

K

3

ř

ř.

S

3

1

:5

 \overline{C}

As mentioned above, in the clad region, martensitic phase has been found in TEM study. The bright field micrograph of martensitic phase is shown in Fig. 9a.

The dark field micrograph formed by one of the Bragg reflections from the martensitic phase is shown in Fig. 9b. This shows lath type martensites. The dark field image formed by one of the matrix reflections is shown in Fig. 9c. This shows heavily dislocated matrix.

The diffraction pattern in Fig. 9d shows the diffraction spots from the matrix as well as martensite. The streaking effect along one direction is observed.

3.1.2.c Precipitates

Figure 10a shows the bright field image of precipitates and strain contrast due to the shear imposed by the precipitates. The dark field image of the precipitate formed by one of the reflections from the precipitate is shown in Fig. 10b. The average size of the precipitate was found to be 0.02 μ m and found to be uniformly distributed. Figure 10c shows the diffraction pattern, from the precipitate region.

3.1.3 Corrosion Properties of Laser Cladding of Zr onto Mg

The corrosion properties of the laser clad and pure Mg have been evaluated.

Figure 11a shows the optical micrograph of laser clad region. The microstructure reveals the Zr rich phase and Mg rich phase.

0.545455310.742440.543

The results from corrosion potential test and potentio dynamic test have been shown in Figs. 12a and 12b, respectively for pure Mg and in Figs. 13a and 13b, respectively for clad region.

The results from these corrosion studies have been summarized and compared with other metal and alloy systems in Table 2.

The formation of homogeneous amorphous phase enriched in Zirconium is manifested in increase in the corrosion potential.

3.2 Niobium-Titanium Alloy

The α to β transformation of Ti has been studied by using differential thermal analysis, optical microscopy and electronprobe microanalysis. The optical micrographs in Figs. 14 and 15 show the widmanstatten structure of α and β transformation of the Ti clad for the parameters, 8 kW and 20 ipm. Figures 16 and 17 show the optical micrograph of Ti clad for the parameters, 6 kW and 20 ipm.

The DTA-heating curve of Ti clad region (6 KW, 20 ipm) is shown in Fig. 18. There is no appreciable shift in the \propto to β transformation temperature of the clad from that of pure Ti. The transformation occur around 860°C. The corresponding EPMA-analysis of this clad region is shown in Fig. 19 and the amount of Nb dissolved in the Ti clad near the interface is found to be seven weight percent.

The DTA-heating curve of Ti clad region (8 kW, 20 ipm) is shown in Fig. 20. The appreciable shift in the α to β transformation temperature towards lower temperature range suggests the increase in the amount of Nb in the Ti clad region. The corresponding EPMA analysis of this clad, as shown in Fig. 21, shows the increase in the amount of Nb dissolved in the clad to 10 weight percent.

5

j,

Ś

ES3

ř

5

 \hat{S}

S.

٧.

According to the equilibrium phase diagram of Nb-Ti system, as shown in Fig. 22, the increased amount of Nb in the Ti clad region is due to extended solid solubility. Transmission electron microscopy has to be done to analyze the phases present in the clad.

2222222222

IV. FUTURE WORK

The method employed to deposit the metal onto the substrate and the type of laser-metal interaction affect the extent of mixing (mass transport) and the resultant cooling rate (heat transport). This in turn influence the overall composition and microstructure of the laser clad material. On account of rapid solidification conditions prevailing in the laser cladding technique, usually fine microstructure, increased solid solubilities of alloying elements, nonequilibrium crystalline and amorphous phases and achievement of high point defects have been observed and reported widely in the literature.

Ň

3

5

No.

У

The cladding of Zr onto Nb by insitu cladding technique has been proposed. A screw feeder to deliver the zr powder into the laser zone has been developed (Fig. 23). The laser beam encounters both the substrate and the powder delivered from the screw feeder simultaneously. The result is change in heat and mass transfer conditions from normal cladding technique by preplacing the powder onto the substrate before laser metal interaction. The change in microstructure and the corrosion resistant properties have to be studied.

The addition of Zr improves the oxidation properties of Nb alloys by forming ZrO_2 particles dispersed in the matrix. In case of an alloy Nb-1% Zr prepared in the ingot metallurgy route, low temperature saturation of the alloy with oxygen favors the formation of ZrO_2 particles. This work emphasizes the increased diffusion mobility of Zr atoms in Nb at 900°C.

It has been observed, in the Nb-Zr alloy, that Zr on rapid cooling gives rise to martensitic type of transformations [12].

In this regard, laser cladding of Zr onto Nb using insitu powder feeding technique has been proposed. A screw feeder has been designed to deliver the metallic powder into the laser interaction zone on the substrate directly.

4

8

R

7

ž

ŕ

r, S

?

X

 $\mathbf{\bar{N}}$

A CONTRACTOR

Printing Duning Differen MA

2222222

Sizza Sizza da Standa Zezzeta Statista Kaata da Sizza



Ľ

Ż

Ņ

3

Ś

î

ø

N •••

Ň

₹,

And a second second

Fig. 1 Experimental Setup for Cladding

والعالم والعالمي







Ş

ļ

N N

¢.

3

ŝ

2

 \mathbf{N}





c SAD Pattern from Crystalline Amorphous Interface

 \mathcal{F}_{i}^{*}



UNDER SERVICE ALE PERSONNE ENVIRENCE



9c DF Electron Micrograph Formed by one of the Matrix Reflections

٠

9d Diffraction Pattern from Matrix and Martensite Phase







Fig. 11 Optical Micrograph of Ir Laser Cladded onto Mg - The Clad Region

_ **.**



Fig. 12a corrosion Potential Plot of Pure Mg

8

10

Ň

3

ŕ

Ĩ

ŝ

Ñ

ド

 \overline{C}



ι.



7

2 2 2

Ż

ž

٨.

1

13ь Potentiodynamic Plot of Laser Clad Region 26

PURCHARGE REPAIRS REPUBLICE RECEIPTION RECEIPTION REPUBLICE



Ľ

5

j,

Ś

Ţ

-

È

Š,

Ś

¥•

3

S

3

<u>o bobstickje kristickje kritickje kristickje bistickje bistickje bistickje bistickje bistickje bistickje bisti</u>

Figs. 14 and 15 Optical Mircograph of Clad Region of Ti Laser Cladded onto Nb at 8 kW, 20 ipm (inches per minute)



n L

8

Ņ

2

ř

ij

1. 1. 1.

or Le

35



<u>berthe were structure. Etable in structure structure structure structure structure structure structure structures structure</u>

Figs. 16 and 17 Optical Micrograph of Clad Region of Tillaser Cladded onto Nb at 6 kW, 20 ipm



Ň

J

2

N.

2

ř

.

.

۶. ۲.

٣.

• •





Fig. 21 EPMA - Curve of Ti/Interface/Nb - 8 kW, 20 ipm

29



AND THE PURCHASE RECEIPTER SAMPLES SECTORS. SHA

and the state of the state of the

Fig. 22 Equilibrium Phase Diagram of Nb-Ti

3

نه



JECCOLORS -

44444444 AAAAAAA

C. L

0222222220



.

Ż

.

.

and the second of the second second

a Possional Represents Posserval Dooroom ES

<u>228.2220 BESERVER PERSESSE SCORE EXCERT</u>

Table 1 Composition of Amorphous and Crystalline Regions of Fig. 5

	Composition	in weight %
Region	Mg	Zr
A-amorphous	15.367	84.634
B-interface	49.431	50 . 569
C-crystalline	74.464	25.536

Table 2Corrosion Evaluation of Zr Laser Cladded onto
Mg and Comparison with other Alloy Systems

3.5%-NaCl
E-Corrosion
-0.647
-0.674
-0.733
-1.335
-1.526
-1.455

Table 3 High Temperature Strength of Nb Alloys UTS (MNm^{-2})

Alloy	1,100°C	1,320°C	1,540°C	1,7 6 0°C
Superalloys	245/350			
Niobium alloys	350	168	119	
Molybdenum alloys	630	385	252	182
Tantalum allovs	5 6 0	364	210	105
Tungsten alloys	700	420	280	210
Chromium alloys	315	119		

Table 4 Laser Cladding Process Parameters

Power		Ti Cladded onto N Beam Diameter	lb Scanning Speed
4	kW	3 mm	20 ipm
6	kW	3 mm	50 ipm
6	kW	3 mm	20 ipm
8	kW	3 mm	20 ipm

シゾンユ

1991 1997 1

NAME OF TAXABLE PARTY.

Ý.

.

21

REFERENCE S

- 1. Mukherjee, K., and J. Mazumder, "Laser Processing of Materials," Conference Proceedings, TMS, AIME, 1985.
- Weinman, L. S., Devault, J. N., Moore, P., "Applications of Lasers in Materials Processing," <u>American Society for Metals</u>, Metals Park, OH, pp. 245-257, April 1979.
- 3. Molian, P. A., Scr. Metall. Vol. 17, No. 11, pp. 1311-1314, 1983.
- 4. Walker, A., West, D. F. F., Steen, W. M., <u>Met. Technol.</u>, Vol. 11, No. 9, pp. 399-404, 1984.
- 5. Weerasinghe, V. M., Steen W. M., "Transport Phenomena in Materials Processing," <u>American Society of Mechanical Engineers</u>, pp. 15-23, 1983.
- Inoue, A., Iwadochi, T., Minemura, T., and Masumato, T., <u>Trans. J. I. M.</u>, Vol. 22, p. 197, 1981.
- Messler, R. W., Ansell, G. S., and Lizunov, V. I., <u>Trans. ASME</u>, Vol. 62, p. 213, 1981.
- 8. Molian, P. A., Wang, P. J., Khan, K. H., and Wood, W. E., in the Material Research Society Proceedings of "Rapidly Solidified Amorphous and Crystalline Alloys," ed. B. H. Rear, B. C. Griessen, M. Cohen, North Holland Publishing Company, Vol. 8, p. 511, 1981.
- 9. Rayment, J. J., and Thomas, G., ibid, p. 547.

2

Ś

¥,

Ş,

.

Ľ

Ì.

Ň

Š.

N 15

- 10. Kattamis, T. Z., "Solidification Microstructure of Laser Processed Alloys and its Impact on Some Properties," <u>Lasers in Metallurgy, Met. Soc. AIME</u>, pp. 1-10, 1981.
- 11. Kalimullin, R. K. H., Kuzhevnikov, Y. Y., "Structure and Corrosion Resistance of Nb-Li Base Alloy after Laser Treatment," <u>Mat. Sci. Neat</u> <u>Treat</u> (USSR), Vol. 27, No. 3/4, pp. 272-274, 1985.
- 12. Lyutyi, E. M., Gomozov, L. I., Eliseena, O. I., <u>Fi. Khim. Mekh. Mater.</u>, Vol. 2, pp. 122-124, 1985.
- 13. Domashevskaya, E. P., Metallorzika, Vol. 17, No. 37, pp. 31-36, 1985.
- 14. Korotaev, et al., Fiz, A.D., Met. Metalloved, Vol. 54, p. 6, 1982.
- Troitskii, B. S., Zakharov, A. M., Vergasova, L. C., Vlasov, P. N., Izr,
 V. U. Z. <u>Tsvetn. Metall.</u>, Vol. 6, pp. 71-74, 1981.
- 16. Draper, et al., C. W., "Laser and Electrons Beam Interactions with Solids," Elsevier Science Publications, pp. 419-424, 1981.
- 17. Goward, G. W., "Overview Protective Coatings--Purpose, Role and Design," MTS, Vol. 2, No. 3, pp. 194-200, 1986.

- Bill, R., Appleton, Bruce Sartwell, Paul, S. Peercy, Robert Schaefer, and Richard Osgood, Materials Science and Engineering, Vol. 20, p. 23, 1985.
- 19. Domashevskaya, E. P., Metallofizika, Vol. 7, No. 3, pp. 31-36, 1985.

ŀ

.

E

ľ

Ŀ

.

-

.

ĥ

ļ

74 |_

N

- 20. Christian Perrin, Titanium 80 Science and Technology, Proc., 4th International Conference on Ti, Vol. 4.
- 21. Oshima, M., et al., Solid State Communication, Vol. 46, No. 11, pp. 815-818, 1983.
- 22. Maksimovich, et al., Fiz. Khim, Mekh. Meter. Vol. 4, pp. 82-86, 1984.
- 23. Korotaev, et al., AD., Fiz. Met. Metalloved., Vol. 54, No. 6, 1982.
- 24. Troitskii, et al., B. S., Izv. V. U. Z. Tsvetn. Metall., Vol. 6, pp. 71-74, 1981.
- 25. Lyutyi, et al., E. M., Fiz. Khim. Mekh. Mater., Vol. 2, pp. 122-124, 1985.
- 26. Kozlov, et al., A. T., IZV. Akad. Naul, SSSR, Met. Vol. 3, pp. 182-186, 1985.
- 27. Belov, et al., A. F., Izv. Akad. Nauk, SSSR, Met., Vol. 5, pp. 92-97, 1982.
- 28. Troitskii, et al., BS., Sov. Nonferrous Met. Res., Vol. 9, No. 6, pp. 500-503, 1981.
- 29. Voitovich, et al., RV., Russ. Met., Vol. 1, pp. 183-187, 1979.
- 30. Fedotov, Ak., IZV. Akad, Nauk. SSSR, Met., Vol. 5, pp. 248-252, 1979.
- 31. Shatinskii, et al., VF., Prot. Met. (USSST), Vol. 15, No. 3, pp. 301-303, 1979.
- 32. Vasileva, et al., E. V., Tr Moskov Vyshh Etkh Univ NE Bauman, Vol. 214, pp. 63-67, 1976.
- 33. Critical Materials in the Electrical and Electronics Industry. The Inst. of Metallurgists, pp. 35.
- 34. Kofstad, P., et al., Technical Scientific Note, Vol. 3, 1960.
- 35. Argent, B. B., et al., J. Less-Common Metals, Vol. 2, Nos. 2-4, p. 181, 1960.
- 36. Felten, E. J., J. Less Common Metals, Vol. 17, p. 207, 1969.
- 37. Smith, R., J. Less-Common Metals, Vol. 2, 1960.
- 38. Pfeiffer, I., Hack, S., Z. Metallkd., Vol. 72, No. 1, pp. 36-42, 1981.

Ľ 36 8 39. Capelli, P. G., "Laser Surface Alloying," Agard, Naho, (LS-106), pp. 13, March 1980. ļ, -: 4 ٠ . . • -•

-

26665555

المتعاملة والمتلك المستحد المست

A COLOR A COLOR STATEMENT OF THE PARTY OF TH

