



ち こうころれる ない

and a strate of

A SUBSCRIPTION OF SUBSCRIPTION

۱¢

MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

000026000000

NOOD CONTRACTOR

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS
REFORT DOCUMENTATIO	2. GOVT ACCESSION NO	BEFORE COMPLETING FORM
DRO 19769 1LEC	N/A	
TITLE (and Subtilia)	N/A	S. TYPE OF REPORT & PERIOD COVERS
AN ANALYTICAL METHOD OF NON-GRAY	THREE-DIMENSIONAL	
RADIATION HEAT TRANSFER IN SPRAY	COMBUSTION	
		6. PERFORMING ORG. REPORT NUMBE"
AUTHOR(.)		6. CONTRACT OR GRANT NUMBER(+)
		DAAC20 92 K 0042
S. L. Chang and K. I. Knee		DAA029-03-K-0042
PERFORMING ORGANIZATION NAME AND ADDRES	<u></u>	10. PROGRAM ELEMENT PROJECT TASK
Mechanical & Aerospace Engineering Dept. Rutgers, The State University of New Jersey		AREA & WORK UNIT NUMBERS
P.O. Box 909, Piscataway, NJ 088	55-0909	
CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
U. S. Army Research Office Post Office Box 12211		13. NUMBER OF PAGES
Research Triangle Park, NC 27709		8
. MONITORING AGENCY NAME & ADDRESS(I dillon	ent from Controlling Office)	15. SECURITY CLASS. (of this report)
		Unclassified
		15. DECLASSIFICATION/DOWNGRADING SCHEDULE
DICTORDITION CTATEMENT (of the Boost		
. DISTRIBUTION STATEMENT (of the abstract entere	d in Block 20, if different in	om Report)
NA		
		and the second
SUPPLEMENTARY NOTES		
		this warent and
The view opinions and/or find	inne containad i-	LIIIS LEPULL ALE
The view, opinions, and/or find (those of the author(s) and show	ings contained in ld not be constru	ed as an official
The view, opinions, and/or find those of the author(s) and shou pepartment of the Army position	ings contained in ld not be constru , policy, or deci	ed as an official sion, unless so
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentati	ings contained in ld not be constru , policy, or deci on md identify by block number	ed as an official sion, unless so
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentati KEY WORDS (Continue on reverse side if necessary Analytical Solution, 37D Radiati	ings contained in ld not be constru , policy, or deci on <i>identify by block number</i> on, Computation, (ed as an official sion, unless so ptically Thin, Optically
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentati NET WORDS (Continue on reverse edge if necessary Analytical Solution, 37D Radiati Thick, Species Distribution, Bla	ings contained in ld not be constru , policy, or deci on didentify by block number on, Computation, (ackbody Radiation	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentati</u> NEY WORDS (Continue on reverse side if necessary Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fue	ings contained in ld not be constru , policy, or deci on, computation, con ckbody Radiation els, fuel spi	ed as an official sion, unless so Optically Thin, Optically Function, Inverse Error
The view, opinions, and/or find those of the author(s) and shou pepartment of the Army position <u>designated by other documentation</u> Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fu	ings contained in ld not be constru , policy, or deci on on, Computation, Computation, Computation els, fuel spi	ed as an official sion, unless so Optically Thin, Optically Function, Inverse Error
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentari</u> NEY WORDS (Continue on reverse eigent necessary Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fue	ings contained in ld not be constru , policy, or deci on, computation, con ickbody Radiation els, fuel spr ad identify by block number)	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentari Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fix	ings contained in ld not be constru , policy, or deci on, computation, con ickbody Radiation els, fuel spr ion heat transfer	ed as an official sion, unless so Optically Thin, Optically Function, Inverse Error any
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentation</u> Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fu	ings contained in 1d not be constru , policy, or deci on, computation, con ckbody Radiation els, fuels, in heat transfer the present paper	ed as an official sion, unless so optically Thin, Optically Function, Inverse Error in a combustor having fuel . When the distribution
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentati</u> NEY WORDS (Continue on reverse side if necessary Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fu A computational study of radiati spray combustion is reported in of radiatively participating spe or an exponential distribution i	ings contained in ld not be constru , policy, or deci on, computation, con ckbody Radiation els, fuel spr ind identify by block number ind identify by block number identify b	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error in a combustor having fuel . When the distribution either a normal distribution of cylindrical coordinates
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentari Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fue A computational study of radiati spray combustion is reported in of radiatively participating spe or an exponential distribution i with respect to a referenced loc	ings contained in ld not be constru- , policy, or deci- on, Computation, Construction, Computation, Computation, Computation, Construction, Construction	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error in a combustor having fuel . When the distribution either a normal distribution of cylindrical coordinates form, F = f exp (-20-b+2-c32);
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentation</u> Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fu Accomputational study of radiati spray combustion is reported in of radiatively participating spe or an exponential distribution i with respect to a referenced loc where f, a, b, and c are distribution	ings contained in ld not be constru , policy, or deci on, Computation, C ickbody Radiation els, fuels, to heat transfer the present paper cies is known in n any direction c sation, e.g., in a pution constants f	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error when the distribution either a normal distribution of cylindrical coordinates form, F = f exp (-ap-b+2-c22), for individual species, the
The view, opinions, and/or find those of the author(s) and shou Department of the Army position designated by other documentari Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fix A computational study of radiati spray combustion is reported in of radiatively participating spe or an exponential distribution i with respect to a referenced loc where f, a, b, and c are distrib governing equation of radiation	ings contained in ld not be constru- , policy, or deci- on, Computation, Construction, Computation, Computation, Computation, Constants, fuel spin els, fuel spin els, fuel spin end identify by block number) fon heat transfer the present paper cies is known in n any direction co- sation, e.g., in a pution constants for heat transfer wit	ed as an official sion, unless so petically Thin, Optically Function, Inverse Error
The view, opinions, and/or find those of the author(s) and shou Department of the Army position <u>designated by other documentari</u> Analytical Solution, 37D Radiati Thick, Species Distribution, Bla Function Combustors, fue Accomputational study of radiati spray combustion is reported in of radiatively participating spe or an exponential distribution i with respect to a referenced loc where f, a, b, and c are distrib governing equation of radiation	ings contained in ld not be constru , policy, or deci on, Computation, C ckbody Radiation els, fuel spr d Identify by block number on heat transfer the present paper cies is known in n any direction c cation, e.g., in a bution constants f heat transfer wit	ed as an official sion, unless so ptically Thin, Optically Function, Inverse Error any in a combustor having fuel . When the distribution either a normal distribution of cylindrical coordinates a form, $F = f \exp \left(\frac{-2e^{-bt^2} - cz^2}{r^2}\right)$, for individual species, the chout scattering in such a

__UNCLASSIFIED

conto

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

System can be solved with relative ease by using the herein reported method. Several results from the present authors' work are explained that are employed for implementing the solution: a new coordinate transformation method to find the species distribution along individual optical paths centered at any chosen location in the combustor; a new formula for the adiabatic flame temperature in a logarithmic function expressed in terms of relevant variables; a new integral function facilitating solutions for various radiation equations; a new inverse error function enabling some exact solution of the governing equation of radiation heat transfer, etc.

An exact solution is found for both optically thin and thick media. And a numerical solution is offered for optically medially thin medium. The present analytical method is applied to radiation heat transfer in a direct injection-type diesel engine combustion chamber. Some representative results are discussed that have been obtained from a parametric analysis of its radiation heat transfer.

Keyword-

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

86-WA/HT-17 THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS 345 E. 47 St., New York, N.Y. 10017 An Analytical Method of Non-Gray Three-Dimensional **Radiation Heat Transfer in Spray Combustion** S. L. CHANG K. T. RHEE Department of Mechanical and Aerospace Engineering **Rutgers University** New Brunswick, New Jersey 08903 Jati: COD tribution/ 1.11ab1115# -

E

h

T

a

Т

ρ.

ABSTRACT

100 C 20 C 20

A computational study of radiation heat transfer in a combustor having fuel spray combustion is reported in the present paper. When the distribution of radiatively participating species is known in either a normal distribution or an exponential distribution in any direction of cylindrical coordinates with respect to a referenced location, e.g., in a form, F = f exp ($az-bz^2-cz^2$), where f, a, b, and c are distribution constants for individual species, the governing equation of radiation heat transfer without scattering in such a system can be solved with relative ease by using the herein reported method. Several results from the present authors' work are explained that are employed for implementing the solution: a new coordinate transformation method to find the species distribution along individual optical paths centered at any chosen location in the combustor; a new formula for the adiabatic flame temperature in a logarithmic function expressed in terms of relevant variables; a new integral function facilitating solutions for various radiation equations; a new inverse error function enabling some exact solution of the governing equation of radiation heat transfer, etc.

An exact solution is found for both optically thin and thick media. And a numerical solution is offered for optically medially thin medium. The present analytical method is applied to radiation heat transfer in a direct injection-type diesel engine combustion chamber. Some representative results are discussed that have been obtained from a parametric analysis of its radiation heat transfer.

Nomenclature

a Species distribution constant or

- b Species distribution constant
- Species distribution constant or speed of light

- Plank radiation function Species distribution constant
- Plank's constant
- Radiation Intensity
- Boltzman constant
- Radiation heat flux
- Optical path
- Radius of cylinder
- Temperature
- . .
- ϕ , z Components in cylindrical coordinate r.

Avail and

Special

30 228

- θ , ζ Components in spherical coordinate
- Volume absorptance
- λ Wavelength
- Optical depth
- o Stefan-Boltzman constant

Subscripts

- a Adiabatic
- b Blackbody
- Detector
- l ith subrange in r-domain
- j jth subrange in λ -domain
- λ Spectral
- 0 Foot of the optical path

INTRODUCTION

When an equation of radiative heat transfer is solved for predicting the heat flux incident upon various locations over the surface of a combustor having flame plumes, several difficult problems are encountered. In order to briefly review the difficulties, a combustor having a jet flame is considered as shown in Fig. 1. The heat flux through an optical path (r, θ, ζ) centered at location D may be calculated by solving the governing equation of radiation neglecting scattering effect,

Presented at the Winter Annual Meeting Anaheim, California — December 7-12, 1986

$$\begin{array}{c} & & \\ \mathsf{q}_{\theta\zeta} = \int \mathbf{I}_{\lambda}(0) \, \cos\theta \, \mathrm{d}\lambda \qquad (1) \\ & 0 \end{array}$$

when the spectral radiation intensity, $\boldsymbol{I}_{\boldsymbol{\lambda}}(\boldsymbol{r})$ is represented as

$$I_{\lambda}(r) = \int_{r}^{r_{0}} \frac{\kappa_{\lambda}(r')}{\pi} e_{b\lambda} \exp(-\int_{r}^{r} \kappa_{\lambda}(r'') dr'') dr' \quad (2)$$

where κ_{λ} is the spectral volume absorptance at (r,θ,ζ) and e_{λ} is the spectral blackbody radiation. The total radiation flux on location D, then, is calculated by integrating $q_{\theta\xi}$ over the entire hemispherical volume faced by the location. Among the main difficulties in implementing the above computation are that κ_{λ} can be determined only when the distributions of radiatively participating species and temperature are known along the individual optical paths and that I_{λ} is spectrum-dependent.



Fig. 1 A Combustor with Jet Flames.

Star A Maria

In order to obtain a better solution of Eq. (1), some new methods were proposed for overcoming the abovementioned difficulties when the authors computed radiation heat transfer in a direct injection-type diesel engine: a coordinate transformation technique to find the species distribution along individual optical paths when the distribution is given with respect to a chosen location, e.g., the injection nozzle hole [1]; a computation method of finding the spectral volume absorptances of soot and gas for their mixtures [1,2] by using reported results [3,4,5] and new analytical and numerical methods of solving Eq. (1), which are considered in the present paper. This paper, therefore, may partially serve as a summary report of the authors' modeling study of radiation heat transfer in a combustor having flame jets, in addition to reporting new analytical solutions of the radiation heat transfer equation.

Elaborating on the species distribution in the combustion chamber, it was found to be conveniently described by an equation in cylindrical coordinates with respect to the injection nozzle [1] when the distribution is known in either a normal (or a skewed normal) or an exponential form in all directions of the cylindrical coordinate system, e.g., in a form,

$F = f \exp(-a\rho - b\phi^2 - cz^2)$

where F represents either fuel/air ratio or soot concentration or CO_{2} or $H_{2}O$ concentration; f, a, b and c are constants to be separately determined for each medium by either experimental or theoretical means. The expression is considered as to reasonably well describe the species distribution of non-axisymmetric plumes in view of some reported results from both theoretical and experimental studies [6,7]. The new expression offers various advantages, e.g., the expression can be used to describe the spray plume in swirl motion by including its effect in the ϕ direction and it facilitates the sought solution of Eq. (1) [1]. When the species distribution with respect to a referenced position in the combustor is known, the species distribution along the optical path, r, of any chosen direction (r, θ, ζ) and location D (ρ_d, ϕ_d, z_d) may be found as [1].

$$r_{o} = r_{d} \exp(-[(r-r_{o})/r_{w}]^{2}$$
 (4)

where f_d , r_o and r_a are functionally related to θ , ζ , ρ_d , ϕ_d , z_d , f, a, b, and c. This distribution equation, then, may be used for determining the volume absorptance according to the reported methods [3,4,5] as

$$\kappa_{0} = \kappa_{1} \exp(-c_{1}(r-r_{1})^{2})$$
 (5)

The temperature distribution, T, needed in the above equation and e_{bl} for Eq. (1) may be determined by using the distribution of burned fuel/air ratio, ω , from Eq. (3). This can be achieved by using our new formula for the adiabatic flame temperature [8],

$$T = T_0 + T_1 \ln \omega + T_2 (\ln \omega)^2$$
 (6)

where T , T, and T are functionally related to the reaction pressure, the initial mixture temperature and the number of carbon atoms of the fuel molecule. Even with the above rearrangement and simplification of terms in Eq. (1), its solution was not readily found until some new mathematical techniques were employed as explained next.

ANALYTICAL AND NUMERICAL SOLUTIONS

The solution of Eq. (1) may be considered for the following three cases: (1) the optically thin medium; (2) optically thick medium and (3) optically medially thick medium. The solution for each case will be explained upon further simplifying the governing equation as follows. Introducing new terms,

$$\kappa_{o} = \kappa_{\lambda} \cdot \lambda [3,9], \quad x = hc/k\lambda T \text{ and } a = \frac{kT}{hc} \int_{0}^{r} \kappa_{o} dr,$$

where h is Planck's constant, c the speed of light and k the Boltzmann constant, Eq. (1) can be rewritten for directional radiation intensity as,

$$I_{\theta\zeta} = q_{\theta\zeta}/\cos\theta,$$

$$I_{\theta\zeta} = \int_{0}^{r_{0}} \kappa_{0} \int_{0}^{r} \frac{1}{\lambda} e_{b\lambda} e^{-\frac{1}{\lambda}} \int_{0}^{r} \kappa_{0} dr$$

$$= \frac{15}{\pi^{3}} \frac{\sigma}{hc} \int_{0}^{r_{0}} \kappa_{0} T^{5} \int_{0}^{r} \frac{x^{4}e^{-ax}}{e^{x}-1} dx dr.$$

1

(3)

During the process of simplifying the above equation, the authors discovered a new useful integration function [10],

S. Carlos and the

$$\int_{1}^{x_{2}} \frac{e^{-ax_{x}m}}{e^{x_{-1}}} dx = F(m,a,x_{1}) - F(m,a,x_{2}), \quad (7)$$

$$F(m,a,x) = \sum_{\substack{x \in 1 \\ \Sigma \\ n=1}}^{x_{1}} \{e^{-(n+a)x} \sum_{\substack{x \in 1 \\ \Sigma \\ i=0}}^{m} [\frac{\Gamma(m+1)}{\Gamma(m-i+1)} (n+a)^{-i-1}x^{m-i}]\},$$
where $\Gamma(m+1) = m!$

Note that Eq. (7) can also be used for determining a solution in closed form of the black body radiation function, $F_{0-\lambda T}$ [11],

$$F_{0-\lambda T} = \int_{0}^{\lambda T} \frac{E_{b\lambda}(T)}{\sigma T^4} d(\lambda T)$$

= $\frac{15}{\pi^5} \int_{n-1}^{\infty} \left[\frac{e^{-nx}}{n} \left(x^3 + \frac{3x^2}{n} + \frac{6x}{n^2} + \frac{6}{n^3} \right) \right].$

From Eq. (7), since one can find

 $\int_{0}^{\infty} \frac{x^{4} e^{-ax}}{e^{x}-1} dx = \sum_{n=1}^{\infty} \frac{4!}{(n+a)^{5}},$

the governing equation is simplified as

$$I_{\theta\zeta} = \frac{360}{\pi^3} \frac{\sigma k}{nc} \sum_{n=1}^{\infty} \frac{1}{n^5} \int_0^{r_0} \frac{\kappa_0 T^3}{(1+a/n)^5} dr$$

With the definition of the optical depth, $\tau = \int_1^{r} \kappa_0 dr$,

the equation may be rewritten in a tidier form,

$$I_{\theta\zeta} = \frac{360 \text{ ok}}{\pi^5 \text{ hc}} \sum_{n=1}^{t} \frac{1}{n^5} \int_{0}^{\tau_0} \frac{T^5}{(1 \frac{k t \tau}{n hc})^5} d\tau \qquad (8)$$

٥

Note that κ in the equation is assumed constant with respect to λ , which appears valid when soot generated radiation dominates [19]. The solution of this equation is considered for the previously mentioned three cases as follows.

<u>OPTICALLY THIN MEDIUM</u>: When τ approaches zero, i.e., in the optically thin limit, an exact solution for Eq. (8) was found. In this case, Eq. (8) becomes

$$\frac{360 \text{ or }}{\pi^3 \text{hc}} = \frac{1}{\pi^3 \text{hc}} \frac{1}{n^5} \int_{0}^{\tau} \sigma T^5 (1 - \frac{5 \text{kT} \tau}{n \text{hc}}) d\tau \qquad (9)$$

For finding the solution of the above equation, since T is functionally related to the optical depth, τ , and the burned fuel/air ratio, ω , and since ω may be found

as
$$w = w_e e^{-r^2}$$
 from Eq. (4), Eq. (6) may be written as

$$T * T_{0} * T_{1} (ln w_{1} - \overline{r}^{2}) * T_{2} (ln w_{1} - \overline{r}^{2})^{2}$$

+ $T_{3} - T_{4} \overline{r}^{2} * T_{2} \overline{r}^{4}$ (10)

here,
$$T_3 = T_0 + T_1 \ln \omega_1 + T_2 (\ln \omega_1)^2$$
 and
 $T_1 = T_1 + 2T_2 \ln(\omega_1)$.

In addition, for obtaining the solution of Eq. (8), it was necessary to find the relationship between τ and r. From definition and Eq. (5), the optical depth, τ , is rewritten as

$$\tau = \kappa_{1} \int_{0}^{r} e^{-c_{1}(r-r_{1})^{2}} dr$$

$$= \frac{\kappa_{1}}{2} \sqrt{\frac{\pi}{c_{1}}} \{ erf [\sqrt{c_{1}}(r-r_{1})] + erf (\sqrt{c_{1}} r_{1}) \}$$

or, erf
$$[\sqrt{c_1}(r-r_1)] = \frac{2\pi}{\kappa_1} \sqrt{\frac{c_1}{\pi}} \tau - \operatorname{erf}(\sqrt{c_1}r_1).$$
 (11)

In view of Eq. (10) and for further simplifying Eq. (11), a variable transformation was employed to obtain

$$\overline{r} = \sqrt{c_1} (r - r_1),$$

$$\overline{\tau} = \frac{2}{\kappa_1} \sqrt{\frac{c_1}{\pi}} [\tau - \frac{\kappa_1}{2} \sqrt{\frac{\pi}{c_1}} \operatorname{erf} (\sqrt{c_1} r_1)]$$

$$= d_1 [\tau - \tau_1]. \qquad (12)$$

Then Eq. (11) may be written as

erf
$$(\overline{r}) = \overline{\tau}$$

or, $\overline{r} = erf^{-1}(\overline{\tau})$ (13)

where, erf^{-1} represents the inverse error function, whose exact solution is found as follows (the details of its derivation are explained in the Appendix):

$$\overline{r} = erf^{-1}(\overline{\tau}) = \frac{\sqrt{\pi}}{2}(\overline{\tau} + \frac{\pi}{2.3!}\overline{\tau}^3 + \frac{7\pi^2}{4.5!}\overline{\tau}^5 + \dots)$$
(14)

Next, the above equation is introduced into Eq. (10) to find

$$T = T_{3} - \frac{T_{4}\pi}{4} (\overline{\tau} + \frac{\pi}{2 \cdot 3!} \overline{\tau}^{3} + \frac{7\pi^{2}}{4 \cdot 5!} \overline{\tau}^{5} + \dots)^{2} + \frac{T_{2}\pi^{2}}{16} (\overline{\tau} + \frac{\pi}{2 \cdot 3!} \overline{\tau}^{3} + \frac{7\pi^{2}}{4 \cdot 5!} \overline{\tau}^{5} + \dots)^{4} = T_{3} - \frac{\pi}{4} T_{4} \overline{\tau}^{2} + (-\frac{\pi^{2}T_{4}}{4 \cdot 3!} + \frac{\pi^{2}}{16} T_{2}) \overline{\tau}^{4} = T_{4} - T_{4} \overline{\tau}^{2} + T_{4} \overline{\tau}^{4} \qquad (15)$$

where, $T_5 = \frac{\pi}{4} T_4$ and $T_6 = (-\frac{\pi^2 T_4}{4.3!} + \frac{\pi^2}{16} T_2)$.

From Eq. (15), one may also find the following in order to use them in Eq. (9):

$$T^5 = T_3^5 - 5T_3^4 T_5 \overline{\tau}^2 + (10T_3^3 T_5^2 + 5T_3^4 T_6) \overline{\tau}^4,$$

 $T^6 = T_3^6 - 6T_3^5 T_5 \overline{\tau}^2 + (15T_3^4 T_5^2 + 6T_3^5 T_6) \overline{\tau}^4.$

Finally, the above equations and Eq. (12) are introduced into Eq. (9), with a change of variables $\left(\frac{1}{2} \right)$

$$\tau = d_1(\tau - \tau_1)$$
 and $d\tau = 1/d_1 d\tau$, to obtain

$$I_{\theta\zeta} = \frac{360 \text{ ok}}{\pi^5 \text{ hc}} \sum_{n=1}^{2} \frac{1}{n^5} \int_{-d_1 \tau_1}^{d_1 (\tau_0 - \tau_1)} \frac{1}{n^5} \frac{1}{n^4 \tau_1} \left[(\tau_3^{-5} - \frac{5k\tau_1 T_3^{-6}}{nhc}) - \frac{5kTT_3^{-6}}{nhcd_1} \tau \right]$$

$$+ \left(\frac{30kT_1 T_3^{-5} T_5}{nhc} - 5 T_3^{-4} T_5 \right) \tau^2 + \frac{30kTT_3^{-5} T_5}{nhcd_1} \tau^3$$

$$+ \left(10T_3^{-3} T_5^{-2} + 5 T_3^{-4} T_6 \right)$$

$$- \frac{75k\tau_1 T_3^{-4} T_5^{-2}}{nhc} + \frac{30k\tau_1 T_3^{-5} T_6}{nhc} \tau^4$$

$$- \frac{5kT}{nhc} \left(15 T_3 T_5^{-2} + 6 T_3^{-5} T_6 \right) \tau^5 \right] d\tau \qquad (16)$$

Consequently, Eq. (16) can be used for finding an exact solution of the equation of radiation for an optic 'ly thin medium in a combustor with flame plumes as,

$$I_{\theta \zeta} = \frac{360 \text{ dk}}{\pi^{3} \text{ hc}} \sum_{n=1}^{4} \frac{1}{n^{5} d_{1}} \left[(T_{3}^{5} - \frac{5k\tau_{1}T_{3}^{6}}{nhc}) d_{1}\tau_{0} - \frac{5kTT_{3}^{6}}{2nhcd_{1}} (d_{1}^{2}(\tau_{0} - \tau_{1})^{2} - d_{1}^{2}\tau_{1}^{2}) + (\frac{10kT_{1}T_{3}^{5}T_{5}}{nhc} - \frac{5}{3}T_{3}^{4}T_{5}) (d_{1}^{3}(\tau_{0} - \tau_{1})^{3} - d_{1}^{3}\tau_{1}^{3}) + (\frac{10kT_{1}T_{3}^{5}T_{5}}{2nhcd_{1}} (d_{1}^{4} (\tau_{0} - \tau_{1})^{4} - d_{1}^{4}\tau_{1}^{4}) + \frac{15\kappa\tau_{3}^{5}T_{5}}{2nhcd_{1}} (d_{1}^{4} (\tau_{0} - \tau_{1})^{4} - d_{1}^{4}\tau_{1}^{4}) + \frac{15\kappa\tau_{1}T_{3}^{5}T_{5}}{2nhcd_{1}} (d_{1}^{4} (\tau_{0} - \tau_{1})^{4} - d_{1}^{4}\tau_{1}^{4}) + \frac{15\kappa\tau_{1}T_{3}^{5}T_{5}}{2nhcd_{1}} (d_{1}^{4} (\tau_{0} - \tau_{1})^{4} - d_{1}^{4}\tau_{1}^{4}) + \frac{15\kappa\tau_{1}T_{3}^{5}T_{5}}{nhc} + \frac{6\kappa\tau_{1}T_{3}^{5}T_{5}}{nhc} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + T_{3}^{4}T_{5}^{2} + T_{3}^{5}T_{5} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}{2}T_{5}^{2} + \frac{5\kappa\tau_{1}}}{2}T_{5}^{2} + \frac{5$$

<u>Optically thick medium</u>: An exact solution can also be found in an optically thick medium: assuming the volume absorptance κ is 0 for $r < r_0$, and κ_0 for $r_0 < r < r_0 + \epsilon$, one can rewrite Eq. (2) as

$$I_{\theta\xi} = \int_{0}^{r_{0}+\varepsilon} \frac{\kappa}{\pi} e_{b} \exp \left(-\int_{0}^{r} \kappa dr^{*}\right) dr^{*}$$

This equation is further solved to find the result,

$$I_{\theta\xi} = \int_{0}^{r_{0}+\varepsilon} \frac{\kappa_{o}}{\pi} e_{b} \exp\left(-\int_{0}^{r_{1}} \kappa_{o} dr^{*}\right) dr^{*}$$
$$= \frac{\kappa_{o}e}{\pi} \int_{0}^{r_{0}+\varepsilon} \exp\left(-\kappa_{o}(r^{*}-r_{0})\right) dr^{*}$$
$$= \frac{\sigma T^{4}}{\pi} [1-e^{-\tau}] \qquad (18)$$

Optically medially thin medium: When the system holds an optically medially thin (or thick) medium, Eq. (2) cannot analytically be solved as the above discussed cases; rather, a numerical method was employed for it. Without going into the details of its derivation, but by knowing that the volume absorptance <(r) can be found from Eq. (5), the following result was used for the solution.

$$I_{\theta\zeta} = \frac{15}{\pi^{3}} \frac{dk}{hc} \int_{0}^{r_{0}} (\int_{-\kappa_{0}}^{\kappa_{0}} T^{5} (\frac{x^{4}e^{-ax}}{e^{x}-1} dx) dr$$
$$= \frac{15}{\pi^{3}} \frac{dk}{hc} \int_{i=1}^{r_{1}} \int_{1-1}^{r_{1}} \int_{j=1}^{J} \int_{0}^{\kappa_{0}} T^{5}[F(4,a,x_{j-1})]$$
$$= F(4,a,x_{j})] dr$$

where, $\kappa_{0,1}$ is the volume absorptance defined in the ith subrange of r-domain and the jth subrange of λ^- domain. Then,

$$I_{\theta\zeta} = \frac{15 \text{ ok}}{\pi^{2} \text{ hc}} \frac{M}{\Sigma} \int_{i=1}^{\tau_{1}} \sum_{j=1}^{J} T^{5}[F(4,a,x_{j-1}) - F(4,a,x_{j})] d\tau_{ij}$$
(19)

where, $d\tau_1 = \kappa_{011}$ dr. The numerical results of Eq. (19) were obtained using Caussian integration method.

RESULTS AND CONCLUSION

The present computational method enables an extensive parametric study of radiation heat transfer in a combustor with flame jets [2]. Since this paper is to primarily report the analytical methods of computation by using the authors' several new findings reported elsewhere [1, 2, 8, 10, 11], only some representative results obtained for a direct injection-type diesel engine are presented here.

Note that since our computer program to numerically implement Eq. (1) was developed prior to finding the exact solutions that are reported here and since some comparison between the results obtained using the program and those using the exact solutions was satisfactory, the results discussed next were mainly obtained using our available computer program. In the computation, in order to be consistent and to have better mutual comparisons, the same computational conditions employed for the previous results are considered here. The numerical values of f in Eq.(3) were for soot, H_00 , CO_0 and fuel/air ratio 8 x 10 0.01, 0.01 and 1.0, respectively; the distribution constants, a, b, and c were, for these species, 0.6, 2.36 and 2.0, accordingly. Note again that these constants and the distribution made in each coordinate of Eq. (3) can be determined by computational or experimental methods, or arbitrarily chosen for parametric studies. The engine details for the computation were: the chamber surface temperature, 500⁰K; the number of spray plumes, 4; the piston radius, R = 4.92 cm; the combustion chamber bowl radius, 3.44 cm; the compression ratio, 23; the engine speed, 1000 rpm; the surface spectral emissivity, 0.95; the fuel composition, $C_{1,6}H_{2,4}$; the time of computation in a cycle, 40 degrees after top dead center. The results are shown in normalized forms: normalized radiation heat transfer, Q/oT, where T is 2400 γKand σ is the Stefan-Boltzmann constant; normalized directional intensity, $I_{\theta \gamma}/\pi\sigma T$; normalized spectral radiation heat transfer, $Q_{\chi}/\sigma T$.

1000



Fig. 2 Directional Radiation Heat Flux Incident on Cylinder Head Surface in Radial Direction.

The radiation heat transfer through a solid angle incident on the cylinder head, are shown in Fig. 2. When there are four flame jets in the combustion chamber, radiation heat transfer flux incident on the locations along the radial direction varies depending upon the direction in the hemispherical volume of integration. The schematic drawing in the figure shows the spherical coordinates identifying the direction of solid angles. Note that, for cases $\theta = 60^{\circ}$ and 76.7°, neat transfer on r/R < 0.1 is largely from plume #1 and that beyond r/R = 0.1 from both plumes #1 and #2. The directional radiation intensity, I , was combined with the spectral emissivity of the chamber wall, $c_1 = 0.95$.



Fig. 3 Radiation Heat Transfer through Cylindrical Head.

to obtain radiation heat transfer through the cylinder head by integrating as, Q = $\int I_{\theta \zeta} \cos \theta \sin \theta \, d\theta \, d\zeta$ (Fig. 3). The net heat transfer computed with inclusion of wall emission at 500K, reflection from the opposite-side walls are represented by "Net"; those obtained excluding the reflection are denoted by "No reflection"; and the heat flux incident on the surface without including the wall effect are shown by "Spray plume". Explaining the results, the rapid reduction in heat transfer around r/R = 0.7 is caused by the presence of the piston bowl. The double hump in the plot may be surprising. In order to clarify this, an additional computation made for solid angle of zenith angle, $\theta = 39.7^{\circ}$, at various azimuthal angles and locations on the cylinder head, is shown in Fig. 4. From the results, one finds that while the radiation heat flux incident on locations around the nozzle (r/R - 0) is from all of the four plumes, the flux on those near r/R = 0.1 is from one plume, i.e., the nearest



Fig. 4 Directional Intensity of Radiation Incident on Cylinder Head through Various Directions of Solid Angle.

plume to the location. If the computation is made for a single plume, the heat transfer should have asymptotically been approaching zero at r/R = 0. This trend is qualitatively compared with the experimental results obtained by using a single plume [12].

Since the distribution constants being used for Eq. (3) in the present analysis were chosen based on an in-cylinder soot measurement [13], it seems of interest to compute radiative heat transfer contril sted by in-cylinder soot and gaseous species, i.e., mainly CO₂ and H₂O. Fig. 5 shows their spectrum-resolved radiation

STATES STATES

12222

i N

C C



Fig. 5 Radiation Heat Transfer Contributed by Soot and Gaseous Species and their Combination.

heat transfer smoothed over individual wave bands in normalized form, Q_/dT, with respect to normalized wave number, 6 µm/Å. It appears clear that thermal radiation transmission caused by the presence of soot almost dominates the entire radiation process and the radiation by gaseous species is very small. The great portion of radiation by gas found around 6µm/ λ = 1.8 is explained by the strong emission bands of H₂O at λ = 2.7µm and CO₂ at λ = 2.7 and 4.3 µm. Since the spectral absorptance of a surface can be incorporated with results like those in Fig. 5, the analysis may be made for combustors having various surface coatings with known spectral emissivity.

The main issue associated with the use of the present analytical method of radiation heat transfer may be justification of the species distribution described by Eq. (3). Since the distribution widely varies depending upon the fuel injector and combustor condition, it is difficult to exactly describe the variations by a single equation. Reported results suggest, however, the individual species distribution may be simplified by using an exponential or normal (or skewed normal) distribution in each coordinate component of a cylindrical system, e.g., Eq. (3). It is found in the present study that the radiation heat analysis is greatly simplified when the distribution is made in such a form without resorting to the rather complex zonal method or the use of the geometric factors. Further, the use of the present method readily enables a parametric analysis of radiation heat transfer, e.g., the selection of an injector suitable for a chosen combustor system.

ACKNOWLEDGEMENT

The present study has been sponsored by the U.S. Army Research Office, Contract No. DAAG 29-83-K-0043 (Scientific Program Officer, Dr. David M. Mann).

REFERENCES

1. Chang, S. L. and Rhee, K. T., "Coordinate Transformation Method for Radiation Heat Transfer Prediction in Soot Laden Combustion Products," being reviewed for publication.

2. Chang, S. L., Yang, X. L. and Rhee, K. T., "A Parametric Analysis of Radiation Heat Transfer in Direct Injection Diesel Combustion," International Symposium on Diagnostics and Modeling in Reciprocating Engines, September 4-6, 1985, Tokyo, Japan. ままらいとうない。 ゆんぶんしん がまたの たいしょん シャーボ

3. Dalzell, W. H. and Sarofim, A. F., "Optical Constants of Soot and Their Application to Heat Flux Calculation," J. of Heat Transfer, Trans. of ASME, Vol. 91, pp. 100-104, 1969.

4. Lee, S. C. and Tien, C. L., "Optical Constants of Soot in Hydrocarbon Flame," 18th Symposium (Int'1) on Combustion, The Combustion Institute, pp. 1159-1165, 1981.

5. Edward, D. K. and Balakrishnan, A., "Thermal Radiation by Combustion Gases," Int'l J. of Heat Mass Transfer, Vol. 16, p. 25~40, 1973.

6. Takeuchi, K., Senda, J. and Shikuja, M., "Transient characteristics of Fuel Atomization and Droplet Size Distribution in Diesel Fuel Spray," SAE Paper 830449, 1983.

7. Kuo, T. W., Yu, R. C. and Shahed, S. M., "A Numerical Study of the Transient Evaporating Spray Mixing Process in the Diesel Environment," SAE Paper-831735, 1983.

8. Rhee, K. T. and Chang, S. L., "Empirical Equations for Adiabatic Flame Temperatures for Some Fuel-Air Combustion Systems," Combustion Science and Technology, Vol. 44, pp. 75-88, 1985.

9. Grosshandler, W. L. and Modak, A., "Radiation from Nonhomogeneous Combustion Products," 18th Symposium (Int'1) on Combustion, The Combustion Institute, pp. 601-609, 1981.

10. Chang, S. L. and Rhee, K. T., "A Useful Integral Function and Its Application in Thermal Radiation Calculations," International Communication of Heat and Mass Transfer, Vol. 10, No. 4, pp. 329-333, 1983.

11. Chang, S. L. and Rhee, K. T., "Blackbody Radiation Functions," International Communication of Heat and Mass Transfer, Vol. 11, pp. 451-455, 1984.

12. Tsuboi, T., Fukushima, M., Sato, T. and Oguri, T., "Thermal Radiation During Spray Combustion Behind Reflected Shock Waves," International Symposium on Diagnostics and Modeling in Reciprocating Engines, September 4-6, 1985, Tokyo, Japan.

13. Kittleson, D. B., Du, C. J. and Pipho, M., "Total Cylinder Sampling from a Diesel Engine: Part II -Particulate Measurement", SAE Paper 830243, 1983.

14. Papoulis, A., Probability, Random Variables, and

Stochastic Processes, McGraw Hill Book Co., New York, 1965.

15. Schneider, P. J., <u>Conduction Heat Transfer</u>, Addison-Wesley Publishing Co. Inc., Reading, Mass., 1955.

16. Abramowitz, M. and Stegun, I. A., <u>Handbook of</u> <u>Mathematical Functions</u>, National Bureau of <u>Standards</u>, <u>Applied Mathematic Series-55</u>, U. S. Government Printing Office, Washington, D.C., 1964.

Appendix:

AN INVERSE ERROR FUNCTION

-1

The error function, erf(x), although defined in several ways, is essentially equivalent to the following expression:

$$\operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_{0}^{x} e^{-t^{2}} dt = \frac{2}{\sqrt{\pi}} \int_{n=0}^{\infty} (-1)^{n} \frac{x^{2n+1}}{n!(2n+1)} (A-1)$$

The equation is the integral of the so-called Gaussian or normal function and occurs frequently in the study of the general theory of probability [14], the analysis of transient heat flow in a semi-infinite solid [15], and the computation of radiation heat transfer with radiatively participating media [10], etc. For meeting the needs of such studies, the error function, its derivatives and integrals have been tabulated [16]. As found in the text, it was needed to obtain the inverse form of the error function, i.e., in Eq. (A-1), the value of x for a corresponding erf(x). The following derivation shows a new inverse error function in closed form:

When the error function, erf(x), is set equal to y, i.e., y = erf(x), its inverse form may be expressed, for the convenience of discussion,

$$x = erf'(y) \tag{A-2}$$

or,

 $x = fre(y). \tag{A-3}$

By Taylor's expansion method, the inverse error function can be expressed as

$$x = \sum_{n=0}^{\infty} \frac{x^{(n)}(0)}{n!} y^{n}$$
 (A-4)

where, $x^{(n)}(0)$ is the nth derivative of x with respect to y at y = 0. In order to find $x^{(n)}(0)$, the following steps are taken.

$$x'(y) = \frac{dx}{dy} - (\frac{dy}{dx})^{-1}$$
$$= \left\{ \frac{d}{dx} \left[\frac{2}{\sqrt{\pi}} \int_{0}^{x} e^{-t^{2}} dt \right] \right\}^{-1}$$
$$= \frac{\sqrt{\pi}}{2} e^{x^{2}},$$

$$x^{(1)}(y) = \frac{d}{dy} [x^{(1)}(y)] = \frac{d}{dx} [x^{(1)}(y)] [\frac{dy}{dx}]^{-1}$$

$$= \frac{\pi}{2} x e^{-2x^{2}},$$

$$x^{(3)}(y) = \frac{d}{dy} [x^{(1)}(y)] = \frac{d}{dx} [x^{(1)}(y)] [\frac{dy}{dx}]^{-1}$$

$$= [\frac{\pi}{2} (1 + 4x^{2}) e^{2x^{2}}] [\frac{\sqrt{\pi}}{2} e^{x^{2}}]$$

$$= \frac{\pi^{3/2}}{4} (1 + 4x^{2}) e^{3x^{2}},$$

$$x^{(4)}(y) = \frac{\pi^{2}}{4} (7x + 12x^{3}) e^{4x^{2}},$$

$$x^{(5)}(y) = \frac{\pi^{5/2}}{8} (7 + 92x^{2} + 96x^{4}) e^{5x^{2}}$$

$$x^{(6)}(y) = \frac{\pi^{3}}{8} (127x + 652x^{3} + 480x^{5}) e^{6x^{2}}$$

$$x^{(7)}(y) = \frac{\pi^{7/2}}{16} (127 + 3480x^{2} + 10224x^{4} + 5760x^{6}) e^{7x^{2}}, etc.$$

Consequently, one can rewrite Eq. (4) as

$$x = fre(y) = \frac{\sqrt{\pi}}{2} (y + \frac{\pi}{2.3!} y^3 + \frac{7\pi^2}{4.5!} y^5 + \frac{127\pi^3}{8.7!} y^7 + \dots). \qquad (A-5)$$

A close investigation of the above results indicates that a term $\left[\frac{dy}{dx}\right]^{-1}$ is repeated in each derivative and that the even derivatives become zero at y = 0. This leads to writing Eq. (5), the inverse error function, in a tidier form,

$$fre(y) = \sum_{n=0}^{\infty} f_n(0) \left(\frac{\sqrt{\pi}}{2} y\right)^{2n+1} / (2n+1)! \quad |y| < 1 \quad (A-6)$$

where, f (0) is obtained from the reciprocally defined function, f n(t), expressed as

$$f_{0}(t) = 1, \text{ and}$$

$$f_{n+1}(t) = f_{n}^{*}(t) + 2(4n + 3) \times f_{n}^{*}(t)$$

$$+ 2[2n+1 + 4(2n+1)(n+1)x^{2}] f_{n}(t).$$

$$(n = 0, 1, 2, ...)$$

Among the analytical properties of the new inverse error function are

fre(0) = 0

fre(-y) = -fre(y), and

fre(1) = =.

In addition, the convergence of Eq. (6) is demonstrated in Figure A-1.



Fig. A-1 Inverse Error Function and its Convergence.

