~	AD-A17	79 976	TOM	IOGRAPI R AIRI A CA	HIC RE	CONSTR (U) S ARRESS	UCTION PECTRO	OF T	HREE-D ELOPHE MAR 87	IMENSI NT LAG	ONAL I S INC 7-229	FLON Costa 1-13F	2	1
	UNCLAS	SIFIE	D ARC	-1947:	L. 4-EG	DAAG2	9-83-0	-0012			F78 2	2074	NL	
			4 0	.c)			Ļ							
									<u></u>	- <u>†</u>				
			<b>3</b> 4 1											
		_												

\*\*\*\*\*\*\*\*\*



MICROCOPY RESOLUTION TEST CHART NATIONAL HOLD CONTANT HOLD HOLD

	76 416 1/	LE CODY	<u> </u>			
	JRT DOCUN	IENTATION'	PAGE			
Unclassified		16. RESTRICTIVE	MARKINGS			
SECURITY CLASSIFICATION AUTHORY EL	ECTE	3. DISTRIBUTION	AVAILABILITY O	F REPORT		
b. DECLASSIFICATION / DOWNGRAD	NE 0 4 1987	Approve distrib	d for public ution unlim:	release; ited.		
PERFORMING ORGANIZATION REPORT JUNE	R(S)	5. MONITORING	ORGANIZATION R	EPORT NUMBE	R(S)	
SDL No. 87-2284-13F		ARO 1	9471.4-EG			
. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF M	ONITORING ORGA	NIZATION		
SPECTRON DEVELOPMENT LABS		U. S. #	Army Researc	h Office		
ADDRESS (City, State, and ZIP Code)	· · · · · · · · · · · · · · · · · · ·	7b. ADDRESS (Cit	ty, State, and ZIP	Code)		
3535 Hyland Avenue, Suite 102		P. O. H	Box 12211			
		Researd	n Triangle	Park, NC	27709-2211	
NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMEN	T INSTRUMENT ID	ENTIFICATION	NUMBER	
U. S. Army Research Office		DAAG29-83-C-0012				
ADDRESS (City, State, and ZIP Code)		10 SOURCE OF	FUNDING NUMBER	RS		
P. O. Box 12211 Research Triangle Park, NC 2	7709-2211	PROGRAM ELEMENT NO	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO	
Dariush Modarress, Hung Tan, a	nd James D. Trol	inger				
Darlush Modarress, Hung Tan, a         Ba. TYPE OF REPORT         Final         5 SUPPLEMENTARY NOTATION         The view,         of, the author(s) and should no         Solliev, or decision, unless so	nd James D. Trol OVERED 15/83 TO11/14/86 opinions and/or t be construed a	inger 14 DATE OF REPC 18 March findings co s an officia	DRT (Year, Month, 1987 Dontained in 11 Departmen	Day) 15 PA( 3) this repo	GE COUNT 0 rt are those Army position	
Jariush Modarress, Hung Tan, a         Ja. TYPE OF REPORT         Final         Supplementary NOTATION         The view,         of the author(s) and should no         pollogy of the cision, unless so         7         COSATI CODES         FIELD         GROUP         SUB-GROUP         4         ABSTRACT (Continue on reverse if necessary)	nd James D. Trol OVERED 15/83 TO11/14/86 opinions and/or t be construed as designated by 18. SUBJECT TERMS (C Tomography, Three-Dimens	inger 14 DATE OF REPC 18 March findings co s an officia ther document continue on reverse Holography, ional umber)	DAT (Year, Month, 1987 Dontained in al Departmen Station We if necessary an Transonic,	Day) 15 PA 3 this repo this repo the first of the discontify by the Fringe Dig	GE COUNT O rt are those Army position Nock number) gitization,	
Dariush Modarress, Hung Tan, a         3a. TYPE OF REPORT       13b. TIME ( Final         3a. TYPE OF REPORT       13b. TIME ( FROM 3/         6 SUPPLEMENTARY NOTATION       The view,         of the author(s) and should no       The view,         of the author (s) and should no       The view,         of the author (s) and should no       The view,         of the author (s) and should no       The view,         of the density       Application of holograph         is investigated.       Data in the         obtained by AVRADCOM at NASA       field. An automated fringe a         repair the fringe patterns.       input data to the reconstruct         method of least squares solut       were obtained tor the density         An important feature of the t       (sav 20 x 20), it was possibil         surrounding important feature       greater detail. This feature         was determined.	nd James D. Trol OVERED 15/83 TO11/14/86 opinions and/or t be construed at designated by 18. SUBJECT TERMS (C Tomography, Three-Dimens and identify by block n ic tomography to form of interfe Ames were used t nalysis capabili The binary image ion code. A new ion was develope and velocity fi echnique was fou e to repeatedly is of the flow an was used and th	inger 14 DATE OF REPC 18 March findings co s an officia Ther document fortinge on reverse Holography, ional umber) the flow an rograms obta o reconstruct ty was devel s of the interpret ART code ba d for tomographic development and to be that use the same d, hence, rogenetics of the interpret the same the same d, hence, rogenetics of the interpret the same d hence d henc	DAT (Year, Month, 1987 Datained in al Departmen fration Transonic, round the ti ained at for ct the three loped to dig terferograms ased on the raphic recon ous heights at with limi e code and z econstruct to of the shock	Dey) 15 PAG 3 this repo at of the d dentify by t Fringe Dig ty differ differentiation di differentiation diffe	GE COUNT O rt are those Army position Nock number) gitization, volving airfo ent angles nal density lter and d as the refinement . Solutions blade. ution regions ield in r the wing	
Dariush Modarress, Hung Tan, a         3a. TYPE OF REPORT       13b. TIME ( Final         5 SUPPLEMENTARY NOTATION       The view,         of the author(s) and should no         bollow       Daries so         7       COSATI CODES         FIELD       GROUP         9 ABSTRACT (Continue on reverse if necessary         →       Application of holograph         is investigated.       Data in the         obtained by AVRADCOM at NASA         field.       An automated fringe a         repair the fringe patterns.         input data to the reconstruct         method of least squares solut         were obtained for the density         An important feature of the t         (sav 20 x 20), it was possibl         surrounding important feature         was determined.         0 DistRigution/AvailaBility OF ABSTRACT         20 NCLASS/FIED/INUMITED       SAME AS	nd James D. Trol OVERED 15/83 TO11/14/86 opinions and/or t be construed at designated by a 18 SUBJECT TERMS (C Tomography, Three-Dimens and identify by block in ic tomography to form of interfe Ames were used t nalysis capabili The binary image ion code. A new ion was develope and velocity fi echnique was fou e to repeatedly is of the flow an was used and th	inger 14 DATE OF REPC 18 March findings co s an officia Ther Journer continue on revers the flow an rograms obta o reconstruct ty was devel s of the init ART code ba d for tomoge eld at varion nd to be that use the same d, hence, roge 21 ABSTRACT S	DAT (Year, Month, 1987 Dontained in al Departmen tration Transonic, Transonic, round the ti ained at for ct the three loped to dig terferograms ased on the raphic recon bus heights at with limit e code and z econstruct to of the shock ECURITY CLASSIFIC	Dey) 15 PA 3 this repo this repo the of the didentify by the Fringe Dig pof a rev ty different different ty different different ty different ty different ty different ty different to mension different ter the solution above the ted resolution the flow f the wave ove CATION	GE COUNT O rt are those Army position Nock number) gitization, volving airfo ent angles nal density lter and d as the refinement . Solutions blade. ution regions ield in r the wing	
Dariush Modarress, Hung Tan, a         3a. TYPE OF REPORT         Final         13b. TIME OF REPORT         Final         5 SUPPLEMENTARY NOTATION         Of the author(s) and should no         of the author (s) and should no         of the author (continue on reverse if necessary         Application of holograph         is investigated. Data in the         obtained by AVRADCOM at NASA         field. An automated fringe a         repair the fringe patterns.         input data to the reconstruct         method of least squares solut         were obtained for the density         An important feature of the t         (sav 20 x 20), it was possibl         surrounding	nd James D. Trol OVERED 15/83 TO11/14/86 opinions and/or t be construed at designated by a 18. SUBJECT TERMS (C Tomography, Three-Dimens and identify by block n ic tomography to form of interfe Ames were used t nalysis capabili The binary image ion code. A new ion was develope and velocity fi echnique was fou e to repeatedly s of the flow an was used and th	inger 14 DATE OF REPC 18 March findings co s an officia fortinue on reverse Holography, ional umber) the flow an rograms obta o reconstruct ty was devel s of the inter ART code ba d for tomographic eld at varian nd to be that use the same d, hence, roge 21 ABSTRACT S CHART	DAT (Year, Month, 1987 Datained in al Departmen in arison ration transonic, round the ti ained at for ct the three loped to dig terferograms ased on the raphic recon- bus heights at with limit e code and z econstruct to be code and z econstruct to at with shock ECURITY CLASSIFIC nelassified (include Area Cod	Day) 15 PAG 3 this repo at of the didentify by t Fringe Dig p of a rev ty differ -dimension itize, fil were used iterative istruction above the ted resolu- toom into the flow f wave ove CATION Tel 22c OFFICI	GE COUNT O rt are those Army position Nock number) gitization, volving airfo ent angles nal density lter and d as the refinement . Solutions blade. ution regions ield in r the wing	

.

. ......

# TOMOGRAPHIC RECONSTRUCTION OF

THREE-DIMENSIONAL FLOW OVER AIRFOILS

FINAL REPORT

Prepared by:

D. Modarress, H. Tan, and J. D. Trolinger SPECTRON Development Laboratories, Inc. 3535 Hyland Avenue, Suite 102 Costa Mesa, California 92626-1439

SDL No. 87-2284-13F

18 March 1987

Prepared for:

U.S. Army Research Offices

Contract No. DAAG29-83-C-0012

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED



Ľ

3

X

2

Ņ

Ņ

3

NY N

Ņ

**[**]

SPECTRON DEVELOPMENT LABORATORIES, INC.

1.1.1.1.1.1.1.1.1

# 87 4 30 224

#### TABLE OF CONTENTS

4.4 .

.

Ě

ŝ

家村

Ś

S.

.

3

2

S.

.

1.0	STATEMENT OF THE PROBLEM STUDIED 1
2.0	SUMMARY OF THE MOST IMPORTANT RESULTS
3.0	LIST OF PUBLICATIONS 14
4.0	LIST OF PARTICIPATING SCIENTIFIC PERSONNEL
5.0	REFERENCES



-i-



Page

87228413TC/64

# LIST OF FIGURES

Ľ

Ş

Ň

ž

ž

5

, N

2

j,

Y.

Ŕ

•

Figure		Page
1	Basic Holographic Interferometry System	• 17
2	Holographic Interferometer, $\theta = 176.5^{\circ}$	. 17
3	Fringe Digitization Hardware	. 18
4	Fringe number distribution along line AB	. 19
5	Numerically generated density and refractive index distribution	20
6	Reconstructed field of refractive index (Case 1)	. 21
7	Residual and conversion errors vs. iteration number for different projection ray numbers, data file errors, and total view angles	. 22
8	Reconstructed density field for different heights above blade chord line	. 23
9	Density ratio profile	. 24
10	Presentation of air density distribution at Z = 0.5" above a rotating NACA 0012 airfoil	. 25
11	Reconstructed Velocity Contours	. 26

# LIST OF TABLES

Table				<u> </u>	age
1	The	Numerical	Test	Matrix	13

87228413TC/64

-i i -

#### 1.0 STATEMENT OF THE PROBLEM STUDIED

ŝ

ž

Ş

5

X

~/

Application of holographic tomography to the flow around the tip of a revolving airfoil was investigated. Data in the form of interferograms obtained at different angles obtained by AVRADCOM at NASA Ames were used to reconstruct the three-dimensional density field. The data were obtained for the flow around a rotating NACA0012 airfoil at a tip mach number of 0.9 (See Figure 1). Each interferogram represented the integrated map of the optical path along a given orientation relative to the wing. A total of forty interferograms were used. A typical interferogram is shown in Figure 2. The final objective of the work was to reconstruct the density field around the tip of the rotating blade.

The work consisted of three stages:

- a) Digitization of the interferograms in the phase maps.
- b) Reconstruction of the set of integrated phase maps into a three-dimensional map of index of refraction.

c) Development of the density or mach number maps.

Each stage of the work is briefly described here:

87-2284-13/64

## a) Interferogram Digitization:

6

3

S

Ì

2

R

3

÷,

X

57

In the course of this project, a semi-manual and an automated technique for digitization of interferograms were developed. The hardware for the manual digitization consisted of a Tektronix 4112 display terminal and a graphic tablet connected to a VAX11/780. An efficient, menu-driven program for digitization of the interferograms was constructed. This technique was initially used for the digitization of the interferograms.

An automated image analyzing system was later developed. The hardware consisted of an IBM/AT personal computer, a video camera and a frame grabber. It had a 512 x 512 pixel resolution which could digitize at 30 frames per second rate. The fringe digitization hardware is shown in Figure 2.

The software consisted of three major sets of programs. The first set of the processing software included most of the standard "textbook" image processing procedures! such as image averaging, filtering, enhancement, zooming, mirror imaging for the axisymmetric problem along with Sobel or Robert edge operators. This set of programs was supported by a commercially available image processing software product.

-2-

The second program set was developed to determine fringe center-line coordinates according to the local gray scale distribution. This program was able to detect fringes with relatively poor visibility and with variable background gray scale.

The last program was the fringe detection algorithm which transformed the individual fringe line information into a phase map for the entire pixels. This was achieved by surface spline interpolation technique<sup>2</sup>, an efficient technique to interpolate between sparse or nonuniformly spaced data points. It solves the equation for elastic deformation of a plate and assumes continuity of the function and its derivatives.

## b) Tomographic Reconstruction

1. S. S.

Š.

Q

22

R

谷

3

ý

Ň

X

X

A new ART code based on the iterative refinement method of least squares solution for tomographic interferometry was developed. Three dimensional field of the refractive index was reconstructed from the optical path data recorded on the interferograms.

The integral optical length for negligible ray curvature is expressed by the Radon transformation<sup>3</sup>:

and a start a start and a start a start

-3-

$$\ell(P,\theta) = \int_{-\infty}^{+\infty} n(x,y) \delta[P-x\cos(\theta)-y\sin(\theta)] dxdy \qquad (1)$$

5

N.

1

Ŕ

7

ų

X

where  $\delta$  is the Dirac delta-function, and the parameters P and  $\theta$  define the position and the orientation of the ray. The interferograms provide data on the optical pathlength,  $\ell(P, \theta, z_0)$ , along the ray S. The reconstruction problem is to obtain the map of  $n(x, y, z_0)$  from a number of angular projections. A common procedure for obtaining the reconstructed map is matrix inversion. A square grid is superimposed over the density field and the refractive index within each element (pixel) is assumed to be constant. The Radon transformation reduces to a set of discrete equations:

$$\sum_{i=1}^{m} \sum_{j=1}^{m} w_{ij}(P,\Theta) n_{ij} = t(P,\Theta)$$
(2)

The weight factor,  $w_{ij}$ , are determined from geometric relations. Equation (2) is evaluated for N independent rays, resulting in N linear equations. N should be larger or at least equal to the number of pixels, P. The overdeterminate system of linear algebraic equations can be generated and, in principle, solved for the unknown coefficients,  $n_{ij}(z_0)$ .

87-2284-13/64

-4-

Tomographic reconstruction of the phase object was achieved with a modified version of a well documented Algebraic Reconstruction Technique (ART). The linear equations (equation 2) were iteratively solved. Method of conjugate gradient<sup>4</sup> was used to maximize the rate of convergance. A more catailed account of the technique is given in Reference 5.

## c) Data Reduction

ř

2

)

Ŗ

2

3

3

8

7

1

A simplifying and common assumption made throughout this program has been that the effects of refractive index gradient on the beam propagation is negligible. This allowed the use of two dimensional reconstruction codes for solving for the phase map along horizontal planes. The reconstructed data consisted of the density field at any one elevation above the airfoil chord line. For perfect gas, and assuming constant static pressures for each side of the shockwave, the density data may be reduced to a velocity or mach number map.

Due to the courseness of the calculation grids (20 x 20, or 100 x 100), the position and the strength of the shock may not directly be deduced from the tomographic reconstruction results. A method was developed to extract shock position and shock strength directly from the discontinuities observed in the interferograms.

-5-

87-2284-13/64

The reconstructed density field around the leading edge of the rotating blade at different heights above the rotor blade, however, showed the existence of a shock wave extending beyond the blade<sup>6</sup>. Determination of the location and the strength of the shock wave using the existing codes were not possible. Radon transformation in theory can only be applied to a continuous field<sup>3</sup>. Using an adaptive selection technique on the original interferogram data, it was possible to reconstruct the discontinuities in the phase map.

N.

3

X

It was noted that a number of the interferograms showed discontinuous fringe patterns, representing the passage of rays through the shock wave. The regions of the interferogram where the fringe number distribution underwent a rapid change constituted the input data for the reconstruction of the shock waves.

Figure 4 shows the fringe number distribution across a shock wave. The data of Figure 2 were obtained by generating a high resolution image (150 pixels per inch) of the fringe discontinuity region. In contract, the reconstruction of the entire field of interest were achieved with a resolution of 10 pixels per inch.

87-2284-13/64

-6-

Reconstruction of the shape of the shock wave and the shock strength was based on the assumption of isotropy for the two regions before and after the shock wave (denoted as the "+" and "-" regions). The relation between the flow Mach number, M, and the index of refraction,  $N = n - n_{\odot}$  can be written as

f

0

0

9

. .

12

ŝ

$$M_{+}/M_{\pm} = (1 + C_{1}N_{+}/M_{\pm}^{2})/(1 - (-1) C_{1}N_{+})^{1/2}$$
(3)

where  $C_1$  is a constant. The normal shock assumptions and Gladstone-Dale formula relating the refractive index with the gas density can be used to relate the upstream Mach number to the refractive indices across the shock wave.

$$\frac{1 - C_1 N_{-}}{1 - C_1 N_{+}} = \frac{6M_{+}^2}{M_{+}^2 + 5}$$
(4)

Discontinuous fringe patterns may only be achieved for rays parallel to the shock wave for any finite length. The optical path difference between rays 1 and 2 is determined by

$$C_{2}(I_{1} - N_{1}) = \Delta F$$
(5)

where  $L_S$  is the length of the shock wave element parallel to the rays, AF is the fringe number difference at tringe discontinuity regions (see Figure 3), and Co is a constant.

87-2284-13 164

An iterative algorithm was developed. Four unknowns,  $M_+$ ,  $N_+$ ,  $N_-$ , and  $L_S$  for each "shock wave zone" was calculated to satisfy the equations (3) to (5) and a fourth condition on the continuity of refractive indices around the shock wave in both regions.

٢

3

•

ŕ

....

Ŕ

7

2

**.** 4

## 2.0 SUMMARY OF THE MOST IMPORTANT RESULTS

5

Š,

Ņ

Š

ķ.

5

ž

17

a) Numerical Experimentation:

To evaluate the developed tomographic reconstruction code, a numerically generated density ratio field shown in Figure 5.0 was used as an input for the numerical test. It represents the calculated density distribution over the tip region of the rotor blade in a plane above the blade<sup>7</sup>. The data of integral optical length difference as a function of ray parameter  $\theta$  and P was generated from Equation (2). The errors associated with the optical length measurement, encountered in the real tomography, were artificially added to the data file. Fringe round-off errors of  $\pm 0.5$ ,  $\pm 0.05$  and  $\pm 0.005$  were used here. Parametric study of the reconstruction code was achieved for different ranges of view angle and equation numbers.

The numerical test matrix is given in Table 1. Figure 6 shows the development of the reconstructed field  $x_{ij,rec}$  with iteration number for Case 1.  $\epsilon_T$  is defined as the average of the square of the inversion errors.

Convergence rate of the algorithm and the corresponding reconstruction errors as functions of input data errors, the projection ray numbers and the view angles were investigated

-9-

87-2284-13/64

and the results are given in Figure 7. The following conclusions may be drawn from the numerical experimentation:

- The convergence rate is increased as the projection ray number, N, is increased (Figure 7a). The corresponding inversion error for sufficient number of iterations is, in general, independent of N. (Figure 7d).
- The norm of the residual vector, R, in all cases, unconditionally converges to a limit which is a strong function of the input data error (Figure 7b). The resulting error for the first few iterations is independent of the input data error (Figure 7e). However, for more accurate input data, additional iterations result in more accurate solutions. This underlines the importance of the accuracy of the data set. It also proposes a guideline for determining the optimum number of iterations based on the rate of change of the residual.
- Finally, limited viewing angles (>  $30^{\circ}$ ) do not have a significant effect on the convergence rate or the accuracy of the reconstructed data (Figures 7e and 7f). Acceptable results were obtained for total view angles of  $30^{\circ}$ . Care must be taken to ensure that sufficient information is recorded on the interferograms, when the view angle limitations are imposed. In the present case, the projection

-10-

87-2284-13/64

Ř

£

8

ž

ŕ

ŝ

.

5

8

S.

ŝ

angles were taken to be symmetric about the axis of the blade (90° to the chord line).

b) Reconstruction of the density and velocity field.

S

Ś

3

X

8

1.4

The reconstructed density field around the leading edge of the rotating blade for heights z = 1.3, 2.5, 3.8 and 5.1 cm for a 7.5 cm chord and blade aspect ratio of 13.7 is shown in Figure 8. In each case a 20 x 20 pixel with dimensions of 10 mm by 20 mm was used. The programs were run on an IBM PC. The run time for each iteration was approximately 3 minutes, and the results are shown after 3 to 6 iterations.

The results show the existence of the shock wave extending beyond the blade. The magnitude of the maximum density ratio represents the strength of the shock wave for increasing height from the blade surface. More detailed evaluation of the flow field requires more refined mesh dimensions. The reconstructed data at z = 1.3 and 7.8 cm exhibit less noise than the middle stations. This may be attributed to the error in the input data.

The distribution of the density ratio at three longitudinal positions x/B = 0.94, 0.98, and 1.02 are shown in Figure 9. The data in all cases exhibit less than adequate sharpness in the position of the shock wave. This is also attributed to

-11-

87-2284-13/64

the courseness of the reconstruction grid. Due to limited memory map, further refinement of the grid on the same microprocessor was not possible.

Ñ

2

ŝ

5

ž

Š

R

Figure 10 shows similar results in a form of constant density lines for z = 0.5". To transform the density field into the velocity field, accurate location of the shock wave was needed which was determined from the fringe discontinuity locations. Figure 11 shows the map of constant velocity contours. The location of the shock wave is shown as the line of discontinuity in the velocity contours.

CASE	FRINGE NUMBER ROUND OFF ERROR	VIEW ANGLE (degree)	NUMBER OF VIEWS	NUMBER OF Points per view
1	0.005	0 180	61	20
2	0.005	090	61	20
3	0.005	0 180	31	20
4	0.050	0 180	61	20
5	0.050	0 180	31	20
6	0.500	0 180	61	20
7	0.500	0 180	31	20
8	0.005	-75 75	31	20
9	0.005	-60 60	31	20
10	0.005	-45 45	31	20
11	0.005	-30 30	31	20
12	0.005	-15 15	31	20
13	0.050	-75 75	31	20
14	Q.050	-60 60	31	20
15	0.050	-45 45	31	20
16	0.050	-30 30	31	20
17	0.050	-15 •• 15	31	20

# TABLE 1. THE NUMERICAL TEST MATRIX

7

C

Š

8

#### 3.0 LIST OF PUBLICATIONS

R

Š.

5

ŝ

ίà.

33

X

8

5-1 **5**7 Tomographic Reconstruction of Three-Dimensional Flow Over Air Foils, by D. Modarress, H. Tan, and J. D. Trolinger, AIAA 85-0479, January 1985.

Algebraic Reconstruction Technique Code for Tomographic Interferometry, by H. Tan, and D. Modarress, <u>Optical Engineering</u>, Vol. 24, No. 3, May-June 1985.

An Automated Holographic Interferometry Data Reduction System, by H. Tan, J. D. Trolinger, and D. Modarress, Presented at the SPIE Meeting, San Diego, 1986.

Application of Tomography in 3-D Transonic Flows, by D. Modarress, and H. Tan, to be presented at the AIAA 19th Fluid Dynamics, Plasma Dynamics, Laser Conference, June 1987.

#### 4.0 LIST OF PARTICIPATING SCIENTIFIC PERSONNEL

3

ĺ.

Ì

X

Ņ

8

Š

Y,

þ

8

11

Dr. Jim D. Trolinger R&D Director and Chief Scientist Spectron Development Laboratories

Dr. Dariush Modarress Fluid Mechanics Group Leader Spectron Development Laboratories

Dr. Hung Tan Senior Scientist Spectron Development Laboratories

1.5

#### 5.0 REFERENCES

8

5

2

ķ

. . .

Ŗ

 $\hat{\lambda}$ 

Δ

5

- 1. Rosenfeld, A., and A. C. Kak, "Digital Picture Processing," Academic Press, Inc., London (1982).
- 2. Harder, R. L., and R. N. Desmarais, "Interpolation Using Surface Splines," J. Aircraft, 9(2), 189, 1972.
- 3. Deans, S. R., The Radon Transform and some of its Applications, Cap. 1, Wiley, New York (1979).
- 4. Reid, J. K., "Large Sparse Sets of Linear Equations", J. K. Reid, ed., Academic Press, New York (1971).
- Tan, H., and Modarress, D., "Algebraic Reconstruction Technique for Tomographic Interferometry," <u>Optical Engineering</u>, Vol. 24, No. 3, May - June 1985.
- 6. Modarress, D., Tan, H., Trolinger, J. D., Yu, Y., "Tomographic Reconstruction of Three-Dimensional Flow Over Airfoils", AIAA-85-0479 (1985).
- 7. Caradonna, F., "The Transonic Flow about a Helicopter Rotor," Ph.D. Dissertation, Stanford University, 1978.



ľ,

8

8

ŝ

13 13 13

33

Ċ,

53

5

in N

٠;

Figure 1. Basic Holographic Interferometry System.







Figure 3. Fringe Digitization Hardware

**%** 

a second a s





Figure 4. Fringe number distribution along line AB (of Figure 2)



**(b)** 

Š

Q

2

é

*.*---

Ś

È

Figure 5. Numercially generated density and refractive index distribution (Ref. 7).



-\_!-



Residual and conversion errors vs. iteration number for different pr jection ray numbers (a & d); data file errors (b & c); and total view angles (c & f). Inside numbers correspond to case numbers of Table 1. is are

1. 2.

يحددون 

Ĭ.

•



87-2284-13



Ě

Ŋ

Ř

Š

ř

Į į

N.

B

8

1.2.2

8

...

2

Figure 9. Density ratio profile (B=Blade length, C=Chord length)

-24-



Figure 10. Presentation of air density distribution at  $Z = 0.5^{\circ}$ above a rotating NACA 0012 airfoil.



)

Figure 11. Reconstructed Velocity Contours

87-2284-13

