UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE 1a. REPORT SECURITY CLASSIFICATION 16 RESTRICTIVE MARKINGS UNCLASSIFIED . SECURITY CLASSIFICATION AUTHORITY 3 DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; 2b. DECLASSIFICATION / DOWNGRADING SCHEDULE distribution is unlimited 5 MONITORING ORGANIZATION REPORT NUMBER(S) 4 PERFORMING ORGANIZATION REPORT NUMBER(S) CR 87-05 CR 87-05 7a. NAME OF MONITORING ORGANIZATION 6a. NAME OF PERFORMING ORGANIZATION 6b. OFFICE SYMBOL Science Applications Naval Environmental Prediction (If applicable) Research Facility International Corp. 7b. ADDRESS (City, State, and ZIP Code) 6c. ADDRESS (City, State, and ZIP Code) 205 Montecito Avenue Monterey, CA 93943-5006 Monterey, CA 93940 8b. OFFICE SYMBOL 9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER 8a. NAME OF FUNDING / SPONSORING ORGANIZATION Commander. (If applicable) N00228-84-D-3187 Naval Oceanography Command **10. SOURCE OF FUNDING NUMBERS** 8c. ADDRESS (City, State, and ZIP Code) WORK UNIT PROGRAM PROJECT TASK ELEMENT NO ACCESSION NO. NO. NO. NSTL, MS 39529-5000 DN656794 11. TITLE (Include Security Classification) Severe Weather Guide - Mediterranean Ports - 5. Cagliari (U) 12. PERSONAL AUTHOR(S) Englebretson, Ronald E. (LCDR, USN, Ret.) and Gilmore, Richard D. (CDR, USN, Ret.) 14. DATE OF REPORT (Year, Month, Dav) 15. PAGE COUNT 13a. TYPE OF REPORT Final 13b. TIME COVERED FROM 9/13/84 TO 11/1/86 1988, March 64 16. SUPPLEMENTARY NOTATION Funding Source: 0 & M, N-1 18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 17. COSATI CODES SUB-GROUP FIELD GROUP Storm haven Mediterranean meteorology 04 02 Mediterranean oceanography Cagliari port 19. ABSTRACT (Continue on reverse if necessary and identify by block number) This handbook for the port of Cagliari, one in a series of severe weather guides for Mediterranean ports, provides decision-making guidance for ship captains whose vessels are threatened by actual or forecast strong winds, high seas, restricted visibility or thunderstorms in the port vicinity. Causes and effects of such hazardous conditions are discussed. Precautionary or evasive actions are suggested for various vessel situations.

discussed. Precautionary or evasive actions are suggested for various vessel situations. The handbook is organized in four sections for ready reference: general guidance on handbook content and use; a quick-look captain's summary; a more detailed review of general information on environmental conditions; and an appendix that ptovides oceanographic information.

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT	RPT. DTIC USERS	21. ABSTRACT SECURITY CLASSIFICAT UNCLASSIFIED	ION
22a. NAME OF RESPONSIBLE INDIVIDUAL Perryman, Dennis C., contract	monitor	22b. TELEPHONE (Include Area Code) (408) 647–4709	22c. OFFICE SYMBOL 0&M,N-1
DD FORM 1473, 84 MAR 83 A	PR edition may be used un	til exhausted.	ASSIEICATION OF THIS PAGE

All other editions are obsolete.

NIT CLASSIFICATION OF THIS PA

AN (1) AD-A199 387 (2) 040200 FG (\Box) CA (5) SCIENCE APPLICATIONS INTERNATIONAL CORP MONTEREY CA T1 (6) Severe Weather Guide - Mediterranean Ports. 5. Cagliari. TC (8) (U) DN (9) Final rept. 13 Sep 84-1 Nov 86, Englebretson, Ronald E. AU (1Ø) AU (10) Gilmore, Richard D. RD (11) Mar 1988 PG (12) 660 CT (15) NØØ228-84-D-3187 RN (18) NEPRE-CR-87-05 RC (20) Unclassified report NO (21) See also Number 6. AD-A199 386. DE (23) *PORTS, (FACILITIÉS), DECISION MAKING, HANDBOOKS, HAZARDS, LIMITATIONS, MEDITERRANEAN SEA, OCEANOGRAPHIC DATA, THUNDERSTORMS. VISIBILITY, WIND, DC (24) (U) AB (27) This handbook for the port of Cagliari, one in a series of severe weather guides for Mediterranean ports. provides decision-making guidance for ship captains whose vessels are threatened by actual or forecast strong winds, high seas, restricted visibility or thunderstorms in the port vicinity. Causes and effects of such hazardous conditions are discussed. Precautionary or evasive actions are suggested for various vessel situations. The handbook is organized in four sections for ready reference: general/guidance on handbook content and use; a duick-look captain's summary; a more detailed review of deneral information on environmental conditions; and an appendix that provides oceanographic information. (fr) AC (28) (U) (33) Ø1 Di. SE (34) F CC (35) 417277

##

Naval Environmental Prediction Research Facility Monterey, CA 93943-5006





SEVERE WEATHER GUIDE MEDITERRANEAN PORTS

5. CAGLIARI

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED

QUALIFIED REQUESTORS MAY OBTAIN ADDITIONAL COPIES FROM THE DEFENSE TECHNICAL INFORMATION CENTER. ALL OTHERS SHOULD APPLY TO THE NATIONAL TECHNICAL INFORMATION SERVICE.

CONTENTS

Fore	eword			• •	• •			•		•			•	•			•	iii
Pref	face .			• •		•			•	•		•	٠	•	•	•	•	v
Reco	ord of	F Change	25			•								•			-	vii
1.	Gener	al Guid	lance						•	•			•					1-1
	1.1	Design						-	-			•					-	1-1
		1.1.1	Object	tives			н ,н		÷.			-					-	1-1
		1.1.2	Approa	ach				-										1-1
		1.1.3	Organi	izati	on										-		-	1-2
	1.2	Content	s of S	Speci	fic	Ha	rbc	ir 5	Stu	ıdi	es						-	1-3
				•														
2.	Cant	ain's S	umma	rv														2-1
	cupt	u		,														_
3.	Gener	al Info	ormatio	חכ														3-1
	3.1	Geogra	phic Lo	ocati	an			-							_			3-1
	3.2	Dualit;	ative F	Evalu	atic	- - הי	 of	Har	- -bo)r-	as	al	Hav	ver	1			3-4
	रर	Current	e and	Tide	_			. rea							•	•	-	3-4
	3.3 7 A	Uicibil		TUE		r.	* •	•	•	•			•		•	-	•	3-5
	J.4 7 E	VISIOI	LILY .			•		•	•	•	• •	•	•	•	•	•	-	3-0 7.5
	3.3	Hazaroo	ous cor	10111	ons	•		-	۳	•	• •	-	•	•		•	•	3-0 7 0
	J.6	Harbor	Prote		· ·		• •	•	•	•	• •	•	-	•	•		-	3-7
		3.6.1	Winds	and	Weat	he	r .		•	•		-	-	•	٠	•		3-10
		3.6.2	Waves		• •	•	•	•	•				*	•			•	3-10
		3.6.3	Wave I	Data	Uses	s ai	nd	Cor	nsi	de	rat	:10	ns	•	-	•	•	3-17
	3.7	Protect	tive/M	itiga	ting	M	eas	ure	25	*	• •		•	•	•	•	•	3-17
		3.7.1	Moving	; to	New	An	che	raç	je	•	• •		•	•	•	•	•	3-17
		3.7.2	Sortie	e/Rem	ain	in	Pc	irt	•		•	•	•	•	•	*	•	3-18
		3.7.3	Schedu	uling		•			•	•	•	•	•	•		•	•	3-18
	3.8	Local	Indica	ators	of	Ha	zar	dou	IS	We	ath	ner	Co	onc	ti t	ic	ns	3-18
	2																	
Refe	erence	25															-	3-25

Appendix A -- General Purpose Oceanographic Information . A-1

FOREWORD

This handbook on Mediterranean Ports was developed as part of an ongoing effort at the Naval Environmental Prediction Research Facility to create products for direct application to Fleet operations. The research was conducted in response to Commander Naval Oceanography Command (CNOC) requirements validated by the Chief of Naval Operations (CNO).

As mentioned in the preface, the Mediterranean region is unique in that several areas exist where local winds can cause dangerous operating conditions. This handbook will provide the ship's captain with assistance in making decisions regarding the disposition of his ship when heavy winds and seas are encountered or forecast at various port locations.

Readers are urged to submit comments, suggestions for changes, deletions and/or additions to NOCC, Rota with a copy to the oceanographer, COMSIXTHFLT. They will then be passed on to the Naval Environmental Prediction Research Facility for review and incorporation as appropriate. This document will be a dynamic one, changing and improving as more and better information is obtained.

> M. G. SALINAS Commander, U.S. Navy

The following is a tentative prioritized list of Mediterranean Ports to be evaluated during the five-year period 1988-92, with ports grouped by expected year of the port study's publication. This list is subject to change as dictated by circumstances and periodic review.

1988 NO. PORT	1990	PORT
1 GAETA, ITALY		BENIDORM, SPAIN
2 NAPLES, ITALY		ROTA, SPAIN
3 CATANIA, ITALY		TANGIER, MOROCCO
4 AUGUSTA BAY, ITALY		PORT SAID, EGYPT
5 CAGLIARI, ITALY		ALEXANDRIA, EGYPT
6 LA MADDALENA, ITALY		ALGIERS, ALGERIA
7 MARSEILLE, FRANCE		TUNIS, TUNISIA
8 TOULON, FRANCE		GULF HAMMAMET, TUNISIA
9 VILLEFRANCHE, FRANCE		GULF OF GABES, TUNISIA
10 MALAGA, SPAIN		SOUDA BAY, CRETE
11 NICE, FRANCE		
12 CANNES, FRANCE	1991	PORT
13 MONACO		
14 ASHDOD, ISRAEL		PIRAEUS, GREECE
15 HAIFA, ISRAEL		KALAMATA, GREECE
BARCELONA, SPAIN		THESSALONIKI, GREECE
PALMA, SPAIN		CORFU, GREECE
IBIZA, SPAIN		KITHIRA, GREECE
POLLENSA BAY, SPAIN		VALETTA, MALTA
VALENCIA, SPAIN		LARNACA, CYPRUS
CARTAGENA, SPAIN		
GENOA, ITALY	1992	PORT
LIVORNO, ITALY		
SAN REMO, ITALY		ANTALYA, TURKEY
LA SPEZIA, ITALY		ISKENDERUN, TURKEY
VENICE, ITALY		IZMIR, TURKEY
TRIESTE, ITALY		ISTANBUL, TURKEY
		GOLCUK, TURKEY
1989 PORT		GULF OF SOLLUM
	-	
SPLIT, YUGOSLAVIA		
DUBROVNIK, YUGOSLAVIA		
TARANTO, ITALY		
PALERMO, ITALY		
MESSINA, ITALY		
TAORMINA, ITALY		
PORTO TORRES, ITALY		

PREFACE

Environmental phenomena such as strong winds, high waves, restrictions to visibility and thunderstorms can be hazardous to critical Fleet operations. The cause and effect of several of these phenomena are unique to the Mediterranean region and some prior knowledge of their characteristics would be helpful to ship's captains. The intent of this publication is to provide guidance to the captains for assistance in decision making.

The Mediterranean Sea region is an area where complicated topographical features influence weather patterns. Katabatic winds will flow through restricted mountain gaps or valleys and, as a result of the venturi effect, strengthen to storm intensity in a short period of time. As these winds exit and flow over port regions and coastal areas, anchored ships with large 'sail areas' may be blown aground. Also, hazardous sea state conditions are created, posing a danger for small boats ferrying personnel to and from port. At the same time, adjacent areas may be relatively calm. A glance at current weather charts may not always reveal the causes for these local effects which vary drastically from point to point.

Because of the irregular coast line and numerous islands in the Mediterranean, swell can be refracted around such barriers and come from directions which vary greatly with the wind. Anchored ships may experience winds and seas from one direction and swell from a different direction. These conditions can be extremely hazardous for tendered vessels. Moderate to heavy swell may also propagate outward in advance of a storm resulting in uncomfortable and sometimes dangerous conditions, especially during tending, refueling and boating operations.

This handbook addresses the various weather conditions, their local cause and effect and suggests some evasive action to be taken if necessary. Most of the major ports in the Mediterranean will be covered in the handbook. A priority list, established by the Sixth Fleet, exists for the port studies conducted and this list will be followed as closely as possible in terms of scheduling publications.

RECORD OF CHANGES

CHANGE NUMBER	DATE OF CHANGE	DATE ENTERED	PAGE NUMBER	ENTERED BY
		-		

vii

1. GENERAL GUIDANCE

1.1 DESIGN

This handbook is designed to provide ship captains with a ready reference on hazardous weather and wave conditions in selected Mediterranean harbors. Section 2, the captain's summary, is an abbreviated version of section 3, the general information section intended for staff planners and meteorologists. Once section 3 has been read, it is not necessary to read section 2.

1.1.1 Objectives

The basic objective is to provide ship captains with a concise reference of hazards to ship activities that are caused by environmental conditions in various Mediterranean harbors, and to offer suggestions for precautionary and/or evasive actions. A secondary objective is to provide adequate background information on such hazards so that operational forecasters, or other interested parties, can quickly gain the local knowledge that is necessary to ensure high quality forecasts.

1.1.2 Approach

Information on harbor conditions and hazards was accumulated in the following manner:

- A. A literature search for reference material was performed.
- B. Cruise reports were reviewed.
- C. Navy personnel with current or previous area experience were interviewed.
- D. A preliminary report was developed which included questions on various local conditions in specific harbors.

$$1 - 1$$

- E. Port/harbor visits were made by NEPRF personnel; considerable information was obtained through interviews with local pilots, tug masters, etc; and local reference material was obtained (See section 3 references).
- F. The cumulative information was reviewed, combined, and condensed for harbor studies.

1.1.3 Organization

The Handbook contains two sections for each harbor. The first section summarizes harbor conditions and is intended for use as a quick reference by ship captains, navigators, inport/at sea OOD's, and other interested personnel. This section contains:

- A. a brief narrative summary of environmental hazards,
- B. a table display of vessel location/situation, potential environmental hazard, effect-precautionary/evasion actions, and advance indicators of potential environmental hazards,
- C. local wind wave conditions, and
- D. tables depicting the wave conditions resulting from propagation of deep water swell into the harbor.

The swell propagation information includes percent occurrence, average duration, and the period of maximum wave energy within height ranges of greater than 3.3 feet and greater than 6.6 feet. The details on the generation of sea and swell information are provided in Appendix A.

The second section contains additional details and background information on seasonal hazardous conditions. This section is directed to personnel who have a need for additional insights on environmental hazards and related weather events.

1.2. CONTENTS OF SPECIFIC HARBOR STUDIES

This handbook specifically addresses potential wind and wave related hazards to ships operating in various Mediterranean ports utilized by the U.S. Navy. It does not contain general purpose climatology and/or comprehensive forecast rules for weather conditions of a more benign nature.

The contents are intended for use in both previsit planning and in situ problem solving by either mariners or environmentalists. Potential hazards related to both weather and waves are addressed. The oceanographic information includes some rather unique information relating to deep water swell propagating into harbor shallow water areas.

Emphasis is placed on the hazards related to wind, wind waves, and the propagation of deep water swell the harbor areas. Various vessel into locations/situations are considered, including moored, nesting, anchored, arriving/departing, and small boat operations. The potential problems and suggested precautionary/evasive actions for various combinations of environmental threats and vessel location/situation are provided. Local indicators of environmental hazards and possible evasion techniques are summarized for various scenarios.

CAUTIONARY NOTE: In September 1985 Hurricane Gloria raked the Norfolk, VA area while several US Navy ships were anchored on the muddy bottom of Chesapeake Bay. One important fact was revealed during this incident: Most all ships frigate size and larger dragged anchor, some more than others, in winds of over 50 knots. As winds and waves increased, ships 'fell into' the wave troughs, BROADSIDE TO THE WIND and become difficult or impossible to control.

This was a rare instance in which several ships of recent design were exposed to the same storm and much effort was put into the documentation of lessons learned. Chief among these was the suggestion to evade at sea rather than remain anchored at port whenever winds of such intensity were forecast.

2. CAPTAIN'S SUMMARY

<u>Cagliari Harbor</u> is located on the south coast of the Italian island of Sardinia on the northwest side of the Gulf of Cagliari (Golfo di Cagliari), (Figure 2-1).



Figure 2-1. Ports of Italy, Sicily, and Sardinia.

2-3

Two anchorage areas have been selected for Cagliari (Figure 2-3). <u>Point 1</u> is 4-5 n mi southeast of the enclosed harbors, bearing 170° from Scogtio Sant'Elia. <u>Point 2</u> is about 8 n mi due south of the enclosed harbors east of Sarroch.

The designated anchorages are exposed to winds and waves of the open sea. Strong <u>southeasterly winds</u> of force 7 (28 to 33 kt) pose the greatest threat to anchored vessels due to the long fetch and associated high swell. Strong <u>northwesterly winds</u> of force 7 (28 to 33 kt with gusts to 70 kt) can cause vessels to drag anchor, but the short fetch to the northwest limits wave problems to small craft operations.

Tanker crews at Sarroch sometimes call the weather office at the Cagliari Airport to check on the local weather forecast when they start to feel swell motion in the anchorage. The onset of such swell motion is an indicator of impending southeasterly winds since the long-period swell often travels faster than the wind field that generated it, and arrives ahead of the winds.

<u>Tides</u> are slight, about 1 ft (0.3 m) maximum. <u>Currents</u> are generally wind driven, set with the wind, and are weak. However, with strong northwest winds a 4 to 5 kt east current has been reported off Isola Dei Cavoli (Figure 2-3).

Specific <u>hazardous atmospheric conditions</u>, vessel situations, and suggested precautionary/evasion action scenarios are summarized in <u>Table 2-1</u>. Hazards for both inport and at anchorage are addressed.

HAZARDOUS CONDITION	INDICATORS OF POTENTIAL HAZARD	VESSEL LOCATION/ SITUATION AFFECTED	EFFECT - PRECAUTIONARY/EVASIVE ACTIONS
 NW'ly wind - Primary cause is Mistral from Gulf of Lion. Strongest wind at Cagliari, it funnels to Port area through Campidano Valley. Strongest in late winter/early spring, wind velocities may reach 30-35 kts with gusts to 60-70 kts. Neakest in summer. 	Advance warning * Approximately 24 hours after mistral starts in Bulf of Lion. * Approximately 5 to 7 hours after orographically induced cumulus clouds are observed over the mountains west of the Port. <u>Duration</u> * Predominant wind at Cagliari - 170 days per year. * Strong winds will persist as long as Mistral conditions last.	 (1) <u>Moored</u>. (2) <u>Anchored</u>. (3) <u>Arriving/departing</u>. (4) <u>Small boat operations</u>. 	 (a) Wind may tend to force vessels off moorings.
 SE'ly wind/seas - Caused by Scirocco or Iow fransiting south of Sardinia. Produces worst swell at anchorages. Most common during autuan. Swell reflects off breakwater to west of harbor, causing chop near harbor entrance. May be accompanied by rain turned red by sand and dust in atmosphere. 	Advance Warning * Bood visibility between the Port and Sarroch anchorage provides 24-hour warning. * The sun "turning white" during winter indicates SE winds and rain will occur within 24 hours. • Cloud buildup on mountains west of Sarroch indicates possible forthcoming Se winds Seas. • Long period swell felt in tankers at anchorage off Sarroch are an indicator of impending southeasterly winds. Duration • Occurs about 60 days per year at Cagliari. • Strong winds usually last 24 to 36 hours before changing to NW.	 (1) <u>Moored</u>. (2) <u>Anchored</u>. (3) <u>Arriving/departing</u>. (4) <u>Small boat operations</u>. 	 (a) Inner harbor is affected only by wind, which may tend to force vessels off moorings. * Lines may need to be doubled. (b) Swell affects only outer harbor entrance and waters outside Nuovo Molo di Levante. * Minimal effect in inner harbor. (a) Force of wind/swell may cause vessels to drag anchor. * Two anchors may be required. * Strong event may require evasion to the protected waters of the Gulf of Palaes (Bolf de Palaes), about 40 n ei W of Capitari. (a) Evolutions should be completed prior to wind onset or delayed until winds abate. * Winds will affect ship handling in inner harbor. * Swell may make anchoring inadvisable. (a) Winds/seas create hazardous boating conditions in harbor entrance and outside Nuovo Nolo di Levante. * Boating to/from anchorage may be curtailed. * Boating in inner harbor enimaally affected.
 Tropical cyclones - Although uncommon, tropical cyclones have been observed in the Mediterranean basin. Most likely in late summer/autumn but may occur in any month. Storm track is difficult to forecast accurately. Mariners must give wide berth to forecast track. 	Advance warning * High, thin clouds in cyclonically spiralling, gradually thickening bands. * Unexplained long-period swell approaching from the southern semicircle.	 (1) <u>Moored</u>. (2) <u>Anchored</u>. (3) <u>Arriving/departing</u>. (4) <u>Small boat operations</u>. 	 (a) Vessels should put to sea and evade storm. (a) Vessels should put to sea and evade storm. (a) Vessels should put to sea or stay at sea and evade storm. (a) Curtail all seall boat operations prior on onset of wind. * Hoist small craft out of the water and secure well above high tide line, or * If on ship, hoist small craft out of the water and secure on deck.

TABLE 2-1. Summary of hazardous environmental conditions for the Port of Cagliari, Italy.

2~5

Table 2-2 provides the height ratio and direction of <u>shallow water waves</u> to expect at points 1 and 2 (Figure 2-3) <u>when the deep water wave conditions are</u> <u>known</u>.

The Cagliari Point 1 conditions are found by entering Table 2-2 with the forecast or known deep water wave direction and period. The height is determined by multiplying the deep water height (8 ft) by the ratio of shallow to deep height (.4).

Example: Use of Table 2-2 for Cagliari Point 1. Deep water wave forecast as provided by a forecast center or a reported/observed deep water wave condition: 8 feet, 10 seconds, from 210°. The expected wave condition at Cagliari. Point 1 as determined from Table 2-2: 3 feet, 10 seconds, from 180°.

<u>NOTE</u>: Wave periods are a conservative property and remain constant when waves move from deep to shallow water, but speed, height, and steepness change. Table 2-2. Shallow water wave directions and relative height conditions versus deep water period and direction (see Figure 2-3 for location of points).

FORMAT: Shallow Water Direction Wave Height Ratio: (Shallow Water/Deep Water)

CAGLIARI POINT 1:							
Period (sec)	6	8	10	12	14	16	1
Deep Water	Shallo	w Water	-				ļ
<u>Direction</u>	Direct	ion and	d Heigh	t Rati	0		ł
1 070° 1	100°	105°	110°	110°	115°	120°	ł
	.7	.6	.7	.4	.4	. 4	-
120°	120°	120°	120°	125°	125°	125°	1
	.9	-8	-8	.7	.6	.6	-
150°	150°	150°	145°	140°	140°	140°	1
	• 7	.8	• /	• /	. 6	.6	1
180°	180°	175°	170°	160°	160°	150°	-
	• 7	-8	.0	.0	• /	.8	1
1 210°	190°	190°	180°	170°	165°	160°	;
	.6	.5	. 4	د.	د.	• 2	1
1 240°	180°	180°	180°	175°	170°	165°	ł
1	.2	.2	.3	.3	. 4	.3	;

CAGLIARI POINT 2:

:	Period (sec)	6	8	10	12	14	16
1	Deep Water {	Shall	ow Water	-			1
:	Direction	Direct	tion and	d Heigh	t Rati	0	
;	090° i	090°	090°	095°	100°	100°	100° ¦
:	;	.9	.8	.7	.5	.5	.5 :
ł	1						1
1	120° I	120°	120°	120°	120°	120°	120° ;
;	;	1.0	.9	.9	.8	.8	.8 1
1	;						1
;	150° i	150°	150°	145°	140°	140°	135° ;
:	1	1.0	.9	.8	.7	.8	.8 !
;	ţ						1
1	180° I	180°	175°	170°	160°	155°	150° ¦
1		1.0	.8	.8	.6	.5	.5 ;
1							ł
:	210°	210°	200°	190*	185°	180°	160° ¦
1		.7	.5	. 4	.5	.5	.3 (
1							1
1	240°	180°	180°	205°	180°	170°	170°
1		.2	.2	.2	.2	.3	.4

The <u>local wind generated wave conditions</u> for the anchorage area identified as point 1 (Figure 2-3) are given in <u>Table 2-3</u>. All heights refer to the significant wave height (average of the highest 1/3 waves). Enter the local wind speed and direction in this table to obtain the minimum duration in hours required to develop the indicated fetch limited sea height and period. The time to reach fetch limited height is based on an initial flat ocean. When starting from a pre-existing wave height, the time to fetch limited height will be shorter.

Table 2-3. Gulf of Cagliari Point 1. Local wind waves for fetch limited conditions related to Point 1 (based on JONSWAP model).

Direction and\	n Loca Spea	al Wind ed (kt)			
Fetch \					
Length `	18	24	30	36	42
l(n mi)				1	
1	1			}	
I SW	2-3/4	3/4	3-4/4	4-5/4-5	5-6/5 ;
12 n mi	2	2	1-2	2	2 1
1		1			
I NW	<2 ft	2/3	3/4	3-4/4	4/4 1
17 n mi	f	1	1	1	1 1
1	5			;	1
N	1 <2 ft	<2 ft	2/3	2-3/3	3/3
<u>4 n mi</u>			1	<u> 1</u>	<u>1</u> ;
1	1		l	:	
ΙE	2/3-4	3/3-4	3-4/4	4/4-5	5/5
10 n mi	1-2	2	2	1-2	1-2
1				;	1
I SE*	3/4	3-4/4-5	4/5	4-5/5	6/5 ;
16 n mi	3	2	2	2	2 1

<u>Format:</u> height (feet)/period (seconds) time (hours) to reach fetch limited height

* Southwest flow over the open sea backs to southeast over the Gulf of Cagliari. The maximum fetch resulting from such a wind pattern would be about 16 n mi. Wind waves would be generated over that distance and combine with the deep water swell which changes from southwest to south over the Gulf (see Table 2-2). 1 Example: To the northwest (315°) there is about a 7 ; fetch (Figure 2-3). Given a northwest n mi wind at 36 kt, the sea will have reached 3-4 ! ł feet with a period of 4 seconds within 1 hour. 1 Wind waves will not grow beyond this condition { 1 unless the wind speed increases or the direction ! changes to one over a longer fetch length. If 1 the wind waves are superimposed on deep water ; combined height may change in l swell. the response to changing swell conditions. Wind : wave directions are assumed to be the same as { the wind direction.

<u>Combined Wave heights</u> are obtained by finding the square root of the sum of the squares of the swell and wind wave heights.

Example: Swell 10 ft, wind wave 5 ft.

$$\sqrt{10^2 + 5^2} = \sqrt{100 + 25} = \sqrt{125} \approx 11.2 \text{ ft}$$

Note: Increase over larger height is small. If both heights were equal, combined height would increase by a factor of 1.4. If one is half of the other, as in the example, increase over the larger of the two is by a factor of 1.12.

<u>Climatological factors of shallow water waves</u>, as described by percent occurrence, average duration, and period of maximum energy (period at which the most energy is focused for a given height), are given in <u>Table 2-4</u>. See Appendix A for discussion of wave spectrum and energy distribution. These data are provided by season for two ranges of heights: greater than 3.3 feet and greater than 6.6 feet. Table 2-4. Shallow water climatology as determined from deep water wave propagation. Percent occurrence, average duration or persistence, and wave period of maximum energy for wave height ranges of greater than 3.3 feet and greater than 6.6 feet by climatological season.

CAGLIARI POINT 1:	WINTER	SPRING	SUMMER	AUTUMN I
! >3.3 feet	NOV-APR	MAY	JUN-SEP	OCT I
Occurrence (%)	20	10	7	11
Average Duration (hrs)	13	13	10	10
Period Max Energy(sec)	12	8	8	8
l >6.6 feet	NOV-APR	MAY	JUN-SEP I	OCT
 Occurrence (%) 	5	2	1	1
Average Duration (hrs)	8	6	8 1	8 ;
 Period Max Energy(sec) 	12	12	12	12*
CAGLIARI POINT 2:	WINTER	SPRING	SUMMER !	AUTUMN I
1 <u>>3.3 feet</u>	NOV-APR	MAY	JUN-SEP!	OCT I
 Occurrence (%) 	20	10	7	13
Average Duration (hrs)	13	11	12	11 :
 Period Max Energy(sec) 	9-10	8-9	8	8
<u>>6.6 feet</u>	NOV-APR	MAY	JUN-SEP!	0CT ;
Occurrence (%)	3	2	1	1
Average Duration (hrs)	9	8	6	9
Period Max Energy(sec)	10	12	12	9-10

* The 12 second period shows a sharp peak in the wave climatology energy values. This indicates that for wave heights over 6.6 feet, waves with a 12 second period have a high frequency of occurrence. This pattern is known as "short crested conditions" (see page A-3 of Appendix A for explanation of "short crested conditions").

SEASONAL SUMMARY OF HAZARDOUS WEATHER CONDITIONS

WINTER (November thru February):

- * Frequent (especially February) strong northwesterlies due to Mistral, generally 30-35 kt gusting to 60-70 kt.
- * Mistral causes high waves at anchorage, moderate chop in harbor.
- * High waves in harbor caused by strong southeasterlies due to Scirocco or low in Strait of Sicily.
- * Dangerous wind chill infrequent but can occur when cold temperature combines with strong wind.

SPRING (March thru May):

- * Early spring conditions are like winter.
- * Sea breeze occurs on warmest days.

SUMMER (June thru September):

* Sea breeze daily occurrence.

AUTUMN (October):

- * Short transition season with winter weather returning by end of month.
- * Scirocco common in autumn and rain associated with it may be red due to dust/sand transported from Africa.

NOTE: For more detailed information on hazardous weather conditions see previous Summary Table in this section and Hazardous Weather Summary in Section 3. This section expands on the material in the Captain's Summary. Figures and Tables are repeated with a continuation of numbering. Paragraph 3.5 provides a general discussion of hazards and Table 3-5 provides a summary of hazards and actions by season.

3.1 <u>Geographic Location</u>

The Port of Cagliari is located at 39°13'N 09°07'E on the south coast of the Italian island of Sardinia on the northwest side of the Gulf of Cagliari (Golfo di.Cagliari), (Figure 3-1).





The <u>Gulf of Cagliari</u> is exposed to winds and waves from the southeast quadrant and to northwest winds funneled through the Campidano Valley (Figure 3-2). Vessels desiring to avoid strong northwesterly winds can move east around Cape Carbonara and northward beyond Cape Ferrato. The Gulf of Palmas (Golfo di Palmas), located about 40 n mi west of Cagliari, offers good protection from southeasterly winds and waves.



Figure 3-2. Gulf of Cagliari

The <u>Port of Cagliari</u> consists of inner and outer harbors. The artificial outer harbor is protected by two extensive breakwaters: Nuovo Molo di Ponente which forms and protects the west side of the harbor, and Nuovo Molo di Levante which forms and protects the south side (Figure 3-3). The inner harbor is protected by Vecchio Molo di Levante and Molo Sebaudo. Cagliari is the largest commercial port on Sardinia and the capital of the island.



Figure 3-3. Port of Cagliari

3.2 Qualitative Evaluation of the Port of Cagliari

The Port of Cagliari is situated at the southeast end of the Campidano Valley, a long rift in the mountainous terrain of Sardinia. Elevations of the terrain bordering the valley range from 2,000 to 3,500 ft (610 to 1,067 m) on the northeast side to over 4,000 ft (1,219 m) on the southwest side. The configuration of the valley is largely responsible for the prevailing northwesterly winds (170 days per year) at Cagliari, and serves as a funnel to direct strong Mistral winds to the Port.

The inner harbor is sheltered and considered safe. The outer harbor is well protected, but southeasterly swell reflects off of the face of a breakwater which protects a new industrial harbor (no U.S. military ships allowed) located west of the primary harbor, and enters the outer harbor. The reflected swell is not a significant bother to ships but can create problems for small boats going to or from the anchorage. The bottom of the harbor offers moderate holding ground.

While smaller vessels utilize the protected waters inside the breakwaters, large vessels must anchor out. The primary anchorage (Point 1) is located on radial 170° about 2 to 3 n mi from Scoglio Sant' Elia (Figure 3-3) in a depth of 82 to 98 ft (25 to 30 m). Holding is generally good on a sand bottom. Commercial tankers anchor (Point 2) near Sarroch south of 39°04'N from the coast to 09°10'E in depths of 115 to 131 ft (35 to 40 m). Both anchorages are exposed to southeasterly wind and waves. Anchorage can be taken in 60 ft (18.3 m) of water with good holding ground in Rada di Cagliari (U. S. Navy, 1983).

3.3 Currents and Tides

Currents near Cagliari are wind driven and mostly weak. The current sets east with a northwest wind and

west with a southeast wind. A strong northwest wind is reported to cause a 4 to 5 kt current off of Isola Dei Cavoli (Figure 3-3). According to U. S. Navy, 1983, an east current, "particularly noticeable with winds from the northwest quadrant and after heavy rain carries sea weed into the harbor." Tides are slight, with a spring rise of only about 1 ft (30 cm). The tidal rise doesn't exceed 2 ft even when augmented by onshore winds.

3.4 Visibility

Visibility conditions at Cagliari are rarely bad, but are best under northwesterly flow and worst under southeasterly flow. When occurring, restricted visibility is most common during early morning hours.

3.5 Hazardous Conditions

A seasonal summary of known environmental hazards that may be encountered in the Port of Cagliari follows.

A. Winter (November through February)

The winter season brings frequent strong northwesterly winds to the Port of Cagliari as Mistral winds blow from the Gulf of Lion across the western Mediterranean Sea to Sardinia. Most frequent in February (Brody and Nestor, 1980), the winds reach the Port as 30 to 35 kt northwesterlies with gusts as strong as 60 to 70 kt. The winds cause only minor problems in the harbor, but anchor dragging is possible for anchored vessels. Because the wind is offshore, the fetch is severely limited and the effect on the sea surface is limited to a The chop can, however, affect small craft chop. operations in the harbor and jeopardize small boat runs to and from the anchorage. The wind is strongest when a low pressure system moves across the Gulf of Genoa.

Strong southeasterly winds (to 30 kt) pose a greater hazard to the Port of Cagliari. They can be caused by a Scirocco or a low pressure system in the Strait of Sicily but, in either case, because of the long

fetch area, can generate southeasterly swell which propagates to and adversely affects the Port. The swell is highest near Sarroch, but also affects the anchorage south of Scoolio Sant' Elia. Southeasterly swell tends to reflect off of the face of the breakwater which protects the east side of the new commercial port and enters the outer harbor of the primary port area through the west-facing harbor entrance. The reflected waves create hazardous conditions for small boats. When the winds are caused by a low in the Strait of Sicily, they may be accompanied by rain and thunderstorms produced by orographic lifting over the mountains of Sardinia. Southeasterly winds occur about 60 days per year, usually lasting about 24 to 36 hours before returning to northwesterly, except that a strong Scirocco event may last longer.

There are generally no other strong wind effects at Cagliari. Southwesterly winds turn to southeast as they cross the Gulf of Cagliari, and usually cause no problems at the Port. The harbor is protected from southwesterly swell.

Visibility is mostly good during winter, with fog occurring occasionally during early morning hours early in the season.

Precipitation is common during winter as it is the wettest season of the year at Cagliari.

Winter temperatures normally range from about 43°F (6°C) to 57°F (14°C). The extreme range for the season, based on a 20-year record, spans 25°F (-4°C) to 72°F (22°C). While the temperatures do not appear cold by many standards, the wind chill (temperature combined with wind) can adversely affect personnel working on weather decks without proper protection. (Table 3-1 can be used to determine wind chill for various temperature and wind combinations.)

Table 3-1. Wind Chill. The cooling power of the wind expressed as "Equivalent Chill Temperature" and the danger of freezing exposed flesh (adapted from Miller and Thompson, 1970).

	_										
Wind S	Speed	Coo	ling	Pow	er a	f W:	ind (expro	esse	d as	
		ĽEg	"Equivalent Chill Temperature"								
Knots	MPH	-	Temperature (°F)								
Calm	Calm	50	45	40	35	30	25	20	15	10	
Equivalent Chill Temperature								2			
3-6	5	48	43	37	32	27	22	16	11	6	
7-10	10	40	34	28	22	16	10	4	-2	-9	
11-15	15	36	29	22	16	9	2	-5	-11	-18	
16-19	20	32	25	18	11	4	-3	-10	-17	-25	
20-23	25	30	23	16	8	0	-7	-15	-22	-29	
24-28	30	28	21	13	6	-2	-11	-18	-25	-33	
29-32	35	27	19	11	4	-4	-12	-20	-27	-35	
33-36	40	. 26	18	10	2	-6	-13	-21	-29	-37	

B. <u>Spring (March through May)</u>

Early spring environmental conditions are similar to those of winter. Northwesterly winds continue to predominate but strong winds become less frequent after mid-season. Southeasterly winds occur with diminishing frequency as the season progresses, as low pressure systems track farther north and Scirocco events become less common.

Sea breezes start to occur during afternoons on warm days, but seldom exceed southeasterly 7 to 10 kt and pose no significant problem to harbor operations.

Spring temperatures start to moderate from those of winter, with temperatures normally ranging from about 50° F (10°C) to 66° F (19°C). Based on a 20-year record, the extreme range from the season is approximately 28°F (-2°C) to 86° F (30°C).

Precipitation amount and frequency gradually decrease as summer approaches.

C. Summer (June through September)

Summer weather at Cagliari brings few hazardous weather events. Northwesterly winds still predominate but are overcome during afternoon hours as the sea breeze mechanism takes effect. The southeasterly sea breeze starts about 1100L, seldom exceeds 7 to 10 kt, and is strongest between 1600L and 1700L. The sea breeze is

usually not a problem to mariners. There is no land breeze at night.

Since summer Sciroccos are uncommon, and the storm track that brings low pressure systems south of Sardinia during the winter is displaced northward during the summer, strong southeasterly winds and associated waves are not usually a problem from June through September.

Summer temperatures normally range from about 64°F (18°C) to 82°F (28°C).

Summer is the driest season of the year, with July being the month of least precipitation.

D. Autumn (October)

The autumn season is short at Cagliari, as the transition from the summer weather regime to winter is quite abrupt. Strong northwesterly winds become more common by the end of the month as Mistral conditions return to the western Mediterranean Sea. Funneled to the Port through the Campidano Valley, the winds reach the Port as northwest 30 to 35 kt with gusts as strong as 60 to 70 kt. The winds cause only minor problems in the harbor, but anchor dragging is possible for vessels anchored in the harbor or south of Scoolio Sant' Elia. Because the wind is offshore, the fetch is severely limited and the effect on the sea surface is limited to a chop. The chop can, however, affect small craft operations in the harbor and jeopardize small boat runs to and from the anchorage. The wind is strongest when a low pressure system moves across the Gulf of Genoa.

Scirocco conditions commonly occur in autumn, and low pressure systems once again pass south of Sardinia as the storm track is displaced southward as the season progresses. Both events cause southeasterly flow to impact Cagliari harbor operations. Although the winds seldom exceed 30 kt and have a normal duration of only 24 to 36 hours, the long fetch southeast of Cagliari allows a significant swell to be generated. Section 3.5A contains a discussion of the effect of the southeasterly winds at Cagliari.

Autumn visibility is generally good, but early morning fog occasionally restricts visibility.

Temperatures begin to decrease from the warm values of summer. The normal daily range is approximately 57°F (14°C) to 73°F (23°C), but a 20-year record shows an extreme range of about 32°F (0°C) to 102°F (39°C).

October brings a sharp increase in precipitation, from that of the relatively dry summer months, as extratropical storm systems and their associated frontal systems transit the area. Scirocco events also bring warm rain, which may have a red color due to the sand and dust being transported northward from Africa.

E. Tropical Storm Season

Storms having tropical cyclone characteristics with fully developed eyes have been observed on at least three occasions in the Mediterranean basin: 23-26 September 1969, 22-28 January 1982, and 26-30 September 1983. On the latter occasion the storm moved northwest from the Gulf of Gabes (on the southeast coast of Tunisia), through the Strait of Sicily, <u>along the east</u> <u>coast of Sardinia</u>, and into the Gulf of Genoa. Winds of 100 kt were observed near the eye while Cagliari reported winds of 60 kts. The potential for another storm of this type to strike Cagliari is real and the meteorologist must be aware of the possibility.

3.6 Harbor Protection

While parts of the Port of Cagliari are well protected from specific hazardous conditions, there is exposure to others. The following sections address the various conditions and their effects on harbor operations.

With one major exception, the topography of Sardinia protects the port area from most winds from west-southwest clockwise through east. The exception is wind that blows from the northwest through the Campidano Valley. Cagliari lies at the southeast end of the valley, and wind, usually of Mistral origin, funnels uninterrupted to the port. The major impact on harbor operations is primarily limited to small craft operations to and from the anchorage south of Scoglio Sant' Elia and to anchored vessels due to the possibility of anchor dragging.

Winds from east-southeast clockwise through southwest are unimpeded by any terrain effects and arrive at Cagliari with little change in their open sea direction or velocity except that southwesterly winds reach the harbor as southeast due to the configuration of the terrain around the port area. The direct effects of the wind alone may cause anchor dragging and curtailment of small boat operations outside the breakwaters surrounding the outer harbor. Rain and/or occasional thunderstorms may accompany southeasterly winds but have little impact on harbor operations.

3.6.2 Waves

The breakwater enclosed inner and outer harbors of the Port of Cagliari are well protected from significant wave action from all directions. The strong northwesterly wind which is funneled to the Port area through the Campidano Valley creates a chop, but the chop impacts only small boat operations. A southeasterly wind generate a sea and swell that is potentially сал hazardous to vessels in the roadstead, but the impact inside the breakwaters is limited to waves which reflect off of the face of the breakwater (Molo Settentrionale) that protects the eastern side of the new commercial

harbor being constructed west of the original harbor. The reflected waves pass through the harbor entrance and create difficult conditions for small boat operations within the harbor. The anchorages outside the breakwaters are exposed to the full force of the southeasterly swell.

Table 3-2 provides the shallow water wave conditions at the two designated points when deep water swell enters the harbor.

1	Example: Use of Table 3-2.
(
!	For a <u>deep water</u> wave condition of:
1	
1	10 feet, 12 seconds, from 210°
ł	
;	The approximate shallow water wave conditions :
;	are:
ł	
;	Point 1: 3 feet, 12 seconds, from 170° ;
ł	Point 2: 5 feet, 12 seconds, from 185°
!	

Table 3-2. Shallow water wave directions and relative height conditions versus deep water period and direction (see Figure 3-3 for location of the points).

FORMAT: Shallow Water Direction Wave Height Ratio: (Shallow Water/Deep Water)

CAGLIARI POINT 1:

!	Period (sec)	1	6	8	10	12	14	16
ł	Deep Water	1	Shallow	w Water				1
1	Direction	;	Directi	ion and	Height	Ratio	3	1
1	090°	3	100°	105°	110°	110°	115°	120° ;
1		1	.7	.6	.7	. 4	.4	.4 1
i i		ł						1
ł	120°	ł	120°	120°	120°	125°	125°	125°
ł		8 3	.9	.8	.8	.7	.6	.6 1
1		;						1
1	150°	1	150°	150°	145°	140°	140°	140° ;
ł		ł	.9	.8	.7	.7	. 6	.6 ;
;		3						1
1	180°	ł	180°	175°	170°	160°	160°	150° (
;		1	.9	.8	. 6	.6	.7	.8 :
1		ł						1
;	210°	1	190°	190°	180°	170°	165°	160° ¦
1		ł	.6	.5	.4	.3	.3	.2 1
;		9 3						ł
1	240°	ł	180°	180°	180°	175°	170°	165°
1		1	.2	.2	.3	.3	.4	.3 1

CAGLIARI POINT 2:

1	Period (sec)		6	8	10	12	14	16
1	Deep Water	1	Shallow	Water				1
!	Direction	-	Directi	on and	Height	Ratic)	1
ł	090°	1	090°	090°	095°	100°	100°	100°;
1		1	.9	.8	.7	.5	.5	.5 1
:		ł						1
;	120°	ł	120°	120°	120°	120°	120°	120°
1		1	1.0	.9	.9	.8	.8	.8 /
1		1						1
1	150°	2	150°	150°	145°	140°	140°	135°
1			1.0	. 9	.8	.7	.8	.8 1
;		ţ						1
1	180°	ł	180°	175°	170°	160°	155°	150° ¦
;		1	1.0	.8	.8	.6	.5	.5 1
ł		1						1
;	210°	ł	210°	200°	190°	185°	180°	160° ;
1		l.	.7	.5	. 4	.5	.5	.3 (
;		1						- 1
1	240°	1	180°	180°	205°	180°	170°	170° ¦
;		1	.2	.2	.2	.2	.3	.4 :

Situation specific shallow water wave conditions resulting from deep water wave propagation are given in Table 3-2 while the seasonal climatology of wave conditions in the harbor resulting from the propagation of deep water waves into the harbor are given in Table 3-3. If the actual or forecast deep water wave conditions are known, the expected conditions at the two specified harbor anchorage areas can be determined from Table 3-2. The mean duration of the condition, based on the shallow water wave heights, can be obtained from Table 3-3.

Example: Use	of Tables 3-2 and	<u>3-3</u> .
The forecast (winter case	for <u>wave condition</u>) <u>outside the harbo</u>	s tomorrow
4	teet, 12 seconds, t	
Expected <u>sha</u>	llow water conditio	<u>ns</u> and <u>duration</u> : I
	Point 1	Point 2
height	5-6 feet	5-6 feet
period	12 seconds	12 seconds
direction	from 160°	from 160°
duration	13 hours	13 hours
		1

Interpretation of the information from Tables 3-2 and 3-3 provide guidance on the local wave conditions expected tomorrow at the various harbor points. The duration values are mean values for the specified height range and season. Knowledge of the <u>current synoptic</u> <u>pattern</u> and <u>forecast/expected duration should be used</u> when available.

Possible applications to small boat operations are; selection of the mother ships anchorage point and/or areas of small boat work. The condition duration information provides insight as to how long before a change can be expected. The local wave direction information could be of use in selecting anchorage configuration and related small boat operations.

Table 3-3. Shallow water climatology as determined from deep water wave propagation. Percent occurrence, average duration or persistence, and wave period of maximum energy for wave height ranges of greater than 3.3 feet and greater than 6.6 feet by climatological season.

CAGLIARI POINT 1:	WINTER	SPRING	SUMMER	AUTUMN
<u>>3.3 feet</u>	I NOV-APR	I MAY	JUN-SEP	OCT
l Occurrence (%)	20	10	7	11
Average Duration (hrs)	13	13	10	10
Period Max Energy(sec)	12	: : 8	8	8
: <u>>6.6 feet</u>	I NOV-APR	MAY	JUN-SEP	OCT
 Occurrence (%) 	1 5	2	1	1
Average Duration (hrs)	8	6	8 1	8 ;
 Period Max Energy(sec) 	12	12	12	12*
CAGLIARI POINT 2:	WINTER	SPRING	SUMMER	AUTUMN :
: <u>>3.3 feet</u>	I NOV-APR	MAY	JUN-SEP!	OCT I
 Occurrence (%) 	 20	10	7	13
Average Duration (hrs)	13	11	12	11
: Period Max Energy(sec) 	9-10	8-9	8 1	8
>6.6 feet	I NOV-APR I	MAY I	JUN-SEP !	OCT
l Occurrence (%)		2	1	1 1
Average Duration (hrs)	9	8	6 1	9 ¦
 Period Max Energy(sec) 		12	12	9-10

* The 12 second period shows a sharp peak in the wave climatology energy values. This indicates that for heights over 6.6 feet, waves with a 12 second period have a high frequency of occurrence. This pattern is known as "short crested conditions" (see page A-3 of Appendix A for explanation of "short crested conditions"). Local wind wave conditions are provided in Table 3-4 for Cagliari point 1. The specified fetch lengths are specifically for point 1. The time to reach the fetch limited height assumes an initial flat ocean. With a pre-existing wave height, the times are shorter.

Table 3-4. Gulf of Cagliari point 1. Local wind waves for fetch limited conditions related to point 1 (based on JONSWAP model).

Direction and\	Loca Spee	al Wind ed (kt)			
Fetch \					
Length \	18	24	30	36	42
(n mi)				1	
1				1	
I SW I	2-3/4	3/4	3-4/4	4-5/4-5	5-6/5
; 12 n mi	2	2	1-2	1 2	2 1
			ł	1	1
I NW I	<2 ft	2/3	3/4	: 3-4/4	4/4 1
7 n mi	1	1	1	; 1	1 1
; ;	1			1	1
IN I	<2 ft	<2 ft	2/3	1 2-3/3	1 3/3 1
; 4 n mi ;			: 1	1	1
	1		1	1	1
IE I	2/3-4	3/3-4	3-4/4	4/4-5	1 5/5 1
10 n mi	1-2	2	2	: 1-2	i 1-2 i
			1	1 1	{ }
I SE*	3/4	3-4/4-5	4/5	1 4-5/5	6/5
16 n mi	3	2	1 2	1 2	<u> 2 </u>

Format: height (feet)/period (seconds) time (hours) to reach fetch limited height

* Southwest flow over the open sea backs to southeast over the Gulf of Cagliari. The maximum fetch resulting from such a wind pattern would be about 16 n mi. Wind waves would be generated over that distance and combine with the deep water swell which changes from southwest to south over the Gulf (see Table 3-3).

Example: Small boat wave forecasts (based on the assumption that swell is not a limiting condition). Forecast for Tomorrow: Wind Waves ł Time (Forecast) (Table 3-4)ł prior to 0700 LST ł light and variable < 1 ft 0700 to 1200 Ł SW 8-10 kt < 4 ft; 1200 to 1500 1 SW 22-26 kt 3 ft at 4 sec 1 by 1400 1500 to 2000 NW 28-32 kt 3 ft at 4 sec by 1600-1700 2000 to 2200 1 NW 14-18 kt less than 2 ft by 2100 Interpretation: Assuming that the limiting factor is Ł ! waves greater than 3 feet, small boat operations would ! ! become marginal by 1400 and remain so until 2000-2100. }

Combined wave heights are computed by finding the square root of the sum of the squares of the wind wave and swell heights. For example, if the wind waves were 3 ft and the swell 8 ft the combined height would be about 8.5 ft.

$$\sqrt{3^2 + 8^2} = \sqrt{9 + 64} = \sqrt{73} \approx 8.5$$

Note that the increased height is relatively small. Even if the two wave types were of equal height the combined heights are only 1.4 times the equal height. In cases where one or the other heights are twice that of the other, the combined height will only increase over the larger of the two by 1.12 times (10 ft swell and 5 ft wind wave combined results in 11.2 ft height).

3.6.3 Wave data uses and considerations

Local wind waves build up quite rapidly and also decrease rapidly when winds subside. The period and therefore length of wind waves is generally short relative to the period and length of waves propagated into the harbor (see Appendix A). The shorter period and length result in wind waves being characterized by choppy conditions. When wind waves are superimposed on deep water waves propagated into shallow water, the waves can become quite complex and confused. Under such conditions, when more than one source of waves is influencing a location, tending or joint operations can be hazardous even if the individual wave train heights are not significantly high. Vessels of various lengths may respond in different motions to the different wave lengths The information on wave periods, present. provided in various tables, should be considered when forecasts are made for joint operations of various length vessels.

Wind waves will seldom be a problem for the ships. Under strong northwest flow wind waves may make small boat operations somewhat hazardous from either anchorage point. Vessels should anchor in as close as possible to reduce the offshore fetch length. The strong winds will present a greater threat than the wind waves and may require ships to sortie.

3.7 Protective and Mitigating Measures

3.7.1 Moving to new anchorage

Vessels desiring to avoid strong northwesterly winds can move east around Cape Carbonara and north along the east coast of Sardinia to the north of Cape Ferrato. Ships are advised to leave the anchorage and move to open sea when heavy southeast swell is occurring or forecast.

The Gulf of Palmas (Golfo di Palmas), located about 40 n mi west of Cagliari, offers good protection

from any north wind (usually not a problem at Cagliari), and southeasterly winds and swell.

3.7.2 Sortie/remain in port

Vessels moored in the protected area inside the breakwaters should not find it necessary to sortie under any situation short of a tropical cyclone. Units should remain at their piers, doubling lines where necessary.

All vessels should put to sea and evade the storm if a tropical cyclone is forecast to affect Cagliari.

3.7.3 <u>Scheduling</u>

On average, wind velocities will be lighter during early morning hours than during the late afternoon. If possible, evolutions such as arriving, departing, or changing berths should be scheduled to avoid peak wind hours.

3.8 Local indicators of Hazardous Weather Conditions

Strong winds from the northwest and southeast, and heavy swell from the southeast pose the greatest threats to the Port of Cagliari.

Northwesterly Wind - Since most of the strong northwesterly winds at Cagliari are caused by Mistral winds originating in the Gulf of Lion, they should be anticipated at Cagliari about 24 hours after a strong Mistral has commenced in that area. A 5 to 7 hour advance warning of strong northwest flow is indicated whenever orographically induced clouds build on the mountains west of the port.

<u>Scirocco/Southeasterly Wind and Swell</u> - Scirocco winds occur mainly during autumn. A 24-hour advance warning of an impending Scirocco is provided when the typical hazy atmosphere becomes clear and the visibility between the harbor at Cagliari and the anchorage at Sarroch is unlimited. Also, a mass of clouds on the

mountains near Sarroch is an indication of southeasterly flow and impending southeasterly winds and swell. During winter, a Scirocco with rain is indicated in 24-hours if the sun "turns white."

Tanker crews at Sarroch sometimes call the weather office at the Cagliari Airport to check on the local weather forecast when they start to feel swell motion in the anchorage. The onset of such swell motion is an indicator of impending southeasterly winds since the long-period swell often travels faster than the wind field that generated it, and arrives ahead of the winds.

Southeasterly wind and swell is also caused by low pressure systems which transit eastward south of Sardinia, so they should be anticipated anytime a low moves eastward between Sardinia and the North African coast.

TABLE 3-5 .	Potential	problem	situations	at	Port	of	Cagliari	- ALL	SEASONS	
-------------	-----------	---------	------------	----	------	----	----------	-------	---------	--

VESSEL LOCATION/SITUATION	POTENTIAL HAZARD	EFFECT - PRECAUTIONARY/EVASIVE ACTIONS	ADVANCE INDICATORS AND OTHER INFORMATION ABOUT POTENTIAL HAZARD
1. <u>Moored</u> . Winter Spring Uncommon Summer Autumn	a. Strong northwesterly wind - Usually resulting from a Histral, with the winds funneled through the Campidano Valley. Decreasing intensity and frequency April through September. A strong event may have 30-35 kts with gusts to 60-70 kts, most likely in late winter and early spring but possible by the end of October. Because of a near zero fetch length, wind raises only a chop in the harbor and anchorage. Wind can create difficult ship handling in inner harbor due to restricted room and slow headway.	a. Remain at mooring, doubling mooring lines if a strong event is forecast. Secure loose gear. Minimize personnel exposure on weather decks.	a. Northwester)y winds should be anticipated about 24-hours after a Mistral has started in the Gulf of Lion, with the velocity of the wind dependent on the Mistral strength. Mistral frequency and intensity decrease April Through September. A buildup of orographically induced cualus clouds over the mountains west of the port indicates the onset of northwesterly winds at Cagliari in 5-7 hours.
Winter Spring Uncommon Summer Autumn	b. Southeasterly winds/seas - Caused by a Scirocco or low pressure system passing south of Sardinia, phenomena least common in summer increasing frequency starting in October. Winds to 30 kts may last for 24-36 hours and raise a swell which is hazardous for ships in the anchorages, with the worse effects felt at the Sarroch Anchorage. Incoming or departing vessels may experience ship handling problems in the inner harbor.	b. Remain at mooring, doubling mooring lines if strong winds are forecast. Secure loose gear. Minimize personnel exposure on weather decks. Swell should not impact inner harbor operations.	b. A 24-hour advance warning of Scirocco winds is indicated when haze clears and good visibility prevails between Cagliari and the Sarroch anchorage. A buildup of clouds on the mountains west of Sarroch is an indication of southeasterly flow and possible forthcosing strong southeasterly winds and seas. Tanker crews from vessels in the Sarroch anchorage sometimes telephone the weather office at Cagliari Airport when they start to feel swell motion. Since long period swell often their faith at the sind field that generated the swell, the calls provide warning of impending strong southeasterly winds.
Winter Spring Summer Autuwn	c. <u>Tropical cyclone</u> - Not a common phenomena in the Mediterranean region, but when occurring, have a strong likelihood of occurring in late summer or autumn. Two of three storms recorded since 1969 have occurred in late September, with one having maximum winds of 100 kts and causing sustained 60 kt winds at Cagliari.	c. Because of the potential for destruction, mariners should make every effort to avoid being placed in the path of a tropical cyclone. Vessels should put to sea and take evasive action at the first indication that a tropical cyclone may strike or pass close to Cagliari.	c. There is little advance indication of the formation of a tropical cyclone in the Mediterranean. Close monitoring of satellite images and synoptic reports is necessary for early detection. An approaching tropical cyclone may be indicated by noting high, thin clouds in cyclonically spiralling, gradually thickening bands, or unexplained long-period swell approaching from the southern semicircle.
2. <u>Anchored</u> . Winter Spring Uncommon Summer Autumn	a. Strong northwesterly wind - Usually resulfing from a Mistral, with the winds funneled through the Caspidano Valley, Decreasing intensity and frequency April through September. A strong event may have 30-35 kts with gusts to 60-70 kts, most likely in late winter and early spring but possible by the end of October. Because of a near zero fetch length, wind raises only a chop in the harbor and anchorage. Wind can create difficult ship handling in inner harbor due to restricted room and slow headway.	a. Remain at anchorage, deploying two anchors if necessary to avoid anchor dragging. If a very strong event makes reasining at the anchorage inadvisable, moving to the east side of Sardinia north of Cape Ferrato will provide protection from the winds.	a. Northwesterly winds should be anticipated about 24-hours after a Histral has started in the Gulf of Lion, with the velocity of the wind dependent on the Histral strength. Histral frequency and intensity decrease April Through September. A buildup of orographically induced coundus clouds over the auontains west of the port indicates the onset of northwesterly winds at Cagliari in 5-7 hours.
Winter Spring Uncommon Summer Autumn	b. Southeasterly winds/seas - Caused by a Scirocco or low pressure system passing south of Sardinia, phenomena least common in summer increasing frequency starting in October. Winds to 30 kts may last for 24-36 hours and raise a swell which is hazardous for ships in the anchorages, with the worse effects feit at the Sarroch Anchorage. Incoming or departing vessels may experience ship handling problems in the inner harbor.	b. Leaving the anchorage is recommended if a strong event is forecast. The Gulf of Palmas (Bolfo di Palmas), approximately 40 n mi west of Cagliari, provides good protection from southeasterly winds and seas.	b. A 24-hour advance warning of Scirocco winds is indicated when haze clears and good visibility prevails between Cagliari and the Sarroch anchorage. A buildug of clouds on the mountains west of Sarroch is an indication of southeasterily flow and possible forthcosing strong southeasterly winds and seas. Tanker crews from vessels in the Sarroch anchorage sometimes telephone the weather office at Cagliari Airport when they start to feel swell motion. Since long period swell often travels faster than the wind field that generated the swell, the calls provide warning of impending strong southeasterly winds.
Winter Spring Summer Autumn	c. <u>Tropical cyclone</u> - Not a common phenomena in the Mediterranean region, but when occurring, have a strong likelihood of occurring in late summer or autuan. Two of three storas recorded since 1969 have occurred in late September, with one having maximum winds of 100 kts and causing sustained 60 kt winds at Canliari.	c. Because of the potential for destruction, mariners should make every effort to avoid being placed in the path of a tropical cyclone. Vessels should put to sea and take evasive action at the first indication that a tropical cyclone may strike or pass close to Cagliari.	c. There is little advance indication of the formation of a tropical cyclone in the Mediterranean. Close anoitoring of satellite images and synoptic reports is necessary for early detection. An approaching tropical cyclone may be indicated by noting high, thin clouds in cyclonically spiralling, gradually thickening bands, or unexplained long-period smell approaching from the southern semicircle.

TABLE	3-5.	(Continued)

VESSEL LOCATION/SITUATION	POTENTIAL HAZARD	EFFECT - PRECAUTIONARY/EVASIVE ACTIONS	ADVANCE INDICATORS AND OTHER INFORMATION ABOUT POTENTIAL HAZARD
3. <u>Arriving/departing</u> . Winter Spring Uncommon Summer Autumn	a. Strong northwesterly wind - Usually resulting from a Mistral, with the winds funneled through the Caspidano Valley. Decreasing intensity and frequency April through September. A strong event may have 30-35 kts with gusts to 60-70 kts, most likely in late winter and early spring but possible by the end of October. Because of a near zero fetch length, wind raises only a chop in the harbor and anchorage. Wind can create difficult ship handling in inner harbor due to restricted room and slow headway.	a. Due to restricted maneuvering room and slow headway in the harbor, vessels inbound to the inner harbor should consider remaining outside the harbor arem if strong winds are blowing. Outbound vessels should revise departure plans as necessary to avoid the strongest winds.	a. Northwesterly winds should be anticipated about 24-hours after a Mistral has started in the Gulf of Lion, with the velocity of the wind dependent on the Mistral strength. Mistral frequency and intensity decrease April Through September. A buildup of orographically induced cumulus clouds over the bountains west of the port indicates the onset of northwesterly winds at Cagliari in 5-7 hours.
Winter Spring Uncommon Summer Autumn	b. <u>Southeasterly winds/seas</u> - Caused by a Scirocco or low pressure system passing south of Sardinia, phenomena least common in Summer increasing frequency starting in October. Winds to 30 kts may last for 24-36 hours and raise a swell which is hazardous for ships in the anchorages, with the worse effects felt at the Sarroch Anchorage. Incoming or departing vessels may experience ship handling problems in the inner harbor.	b. Strong southeasterly winds may cause ship handling problems in the inner harbor due to restricted maneuvering room and slow headway. Vessels outside the southern breakwater (Nuovo Molo di Levante) will be exposed to the full force of the wind and swell. Since strong southeasterly winds seldom last longer than 24-36 hours, vessels are advised to remain in port/at sea and delay departure/arrival until conditions abate.	b. A 24-hour advance warning of Scirocco winds is indicated when haze clears and good visibility prevails between Cagliari and the Sarroch anchorage. A buildup of clouds on the mountains west of Sarroch is an indication of southeasterly flow and possible forthrowing strong southeasterly winds and seas. Tanker crews from vessels in the Sarroch anchorage sometimes telephone the weather office at Cagliari Airport when they start to feel swell motion. Since long period swell often travels faster than the wind field that generated the swell, the calls provide warning of impending strong southeasterly winds.
Winter Spring Summer Autumn	c. <u>Tropical cyclone</u> - Not a common phenomena in the Medilerranean region, but when occurring have a strong likelihood of occurring in late summer or autumn. Two of three storms recorded since 1954 have occurred in late September, with one having maximum winds of 100 kts and causing sustained 60 kt winds at Cagliari.	c. Because of the potential for destruction, mariners should make every effort to avoid being placed in the path of a tropical cyclome. Vessels should put to sea and take evasive action at the first indication that a tropical cyclone may strike or pass close to Cagliari.	c. There is little advance indication of the formation of a tropical cyclone in the Mediterranean. Close monitoring of satellite (mages and synoptic reports is necessary for early detection. An approaching tropical cyclone may be indicated by noting high, thin clouds in cyclonically spiralling, gradually thickening bands, or unexplained long-period swell approaching from the southern semicircle.
4. <u>Small boat operations</u> . Winter Spring Uncommon Summer Autumn	a. Strong northwesterly wind - Usually resulting from a Mistral, with the winds funneled through the Campidano Valley. Decreasing intensity and frequency April through September. A strong event may have 30-35 kts with gusts to 60-70 kts, most likely in late winter and early spring but possible by the end of October. Because of a near zero fetch length, wind raises only a chop in the harbor and anchorage. Wind can create difficult ship handling in inner harbor due to restricted room and slow headway.	a. Small craft should encounter little difficulty in the inner and most of the outer harbor in all but the strongest winds. Boats operating near the outer harbor entrance and outside the breakwaters may have to curtail operations due to the chop raised by the wind.	a. Northwesterly winds should be anticipated about 24-hours after a Mistral has started in the Gulf of Lion, with the velocity of the wind dependent on the Mistral strength. Mistral frequency and intensity decrease April Through September. A buildup of orographically induced cualus clouds over the mountains west of the port indicates the onset of northwesterly winds at Cagliari in S-7 hours.
Winter Spring Uncommon Summer Autumn	b. <u>Southeasterly winds/seas</u> - Caused by a Scirocco or low pressure system passing south of Sardinia, phenomena least common in summer increasing frequency starting in October. Winds to 30 kts may last for 24-36 hours and raise a swell which is hazardous for ships in the anchorages, with the worse effects felt at the Sarroch Anchorage. Incoming or departing vessels may experience ship handling problems in the inner harbor.	b. Small craft in the inner and most of the outer harbor should be essentially unaffected by the direct effect of winds and seas. Boats operating outside the waters protected by the breakwaters and going to/from the anchorages may have to curtail operations until the seas abate. Wave reflection off of the face of the breakwater protecting the east side of the new commercial port may create a chop morth of Nuovo Molo di Levante that could make small boat operation hazardous in the outer harbor entrance.	b. A 24-hour advance warning of Scirocco winds is indicated when haze clears and good visibility prevails between Cagliari and the Sarroch anchorage. A buildup of clouds on the mountains west of Sarroch is an indication of southeasterly flow and possible forthcoming strong southeasterly winds and seas. Tanker crews from vessels in the Sarroch anchorage sometimes telephone the weather office at Cagliari Airport when they start to feel swell action. Since long period swell often travels faster than the wind field that generated the swell, the calls provide warning of impending strong southeasterly winds.
Winter Spring Scamer Autuen	C. <u>Tropical cyclone</u> - Not a common phenomena in the Mediferranean region, but when occurring, have a strong likelihood of occurring in late summer or autumn. Two of three stores recorded since 1964 have occurred in late September, with one having maximum winds of 100 kts and causing sustained 60 kt winds at Cagliari.	c. All small boat operations should cease at the approach of the tropical cyclone. Small craft should be hoisted out of the water and secured on deck or, in the case of shore based boats, well above the high tide line.	c. There is little advance indication of the formation of a tropical cyclone in the Mediterranean. Close monitoring of satellite images and synoptic reports is necessary for early detection. An approaching tropical cyclone may be indicated by noting high, thin clouds in cyclonically spiralling, gradually thickening bands, or unexplained iong-period swell approaching from the southern semicircle.

REFERENCES

Brody, L. R. and M. J. R. Nestor, 1980: <u>Regional</u> <u>Forecasting Aids for the Mediterranean Basin</u>, NAVENVPREDRSCHFAC Technical report TR 80-10. Naval Environmental Prediction Research Facility, Monterey, CA 93941.

Miller, A. and J. C. Thompson, 1970: <u>Elements of</u> <u>Meteorology</u>. Merrill Publishing Co., Columbus, Ohio.

U.S. Navy, 1983: <u>Sailing Directions for the Western</u> <u>Mediterranean</u>, Publication 131, DMAHTC.

PORT VISIT INFORMATION

JUNE 1985. NEPRF meteorologists R. Fett and R. Picard met with Port Captain CAPT Battaglia and Italian Weather Service meteorologists MAJ Ielo and CAPT Torchiani to obtain much of the information included in this port evaluation.

General Purpose Oceanographic Information

This section provides general information on wave forecasting and wave climatology as used in this study. The forecasting material is not harbor specific. The in paragraphs A.1 and A.2 was extracted from material H.O. Pub. No. 603, Practical Methods for Observing and Forecasting Ocean Waves (Pierson, Neumann, and James, The information on fully arisen wave conditions 1955). (A.3) and wave conditions within the fetch region (A.4) is based on the JONSWAP model. This model was developed from measurements of wind wave growth over the North Sea in 1973. The JONSWAP model considered is more appropriate for an enclosed sea where residual wave activity is minimal and the onset and end of locally forced wind events occur rapidly (Thornton, 1986), and where waves are fetch limited and growing (Hasselmann, et al., 1976). Enclosed sea, rapid onset/subsiding local winds, and fetch limited waves are more representative of the Mediterranean waves and winds than the conditions of the North Atlantic from which data was used for the Pierson and Moskowitz (P-M) Spectra (Neumann and Pierson 1966). The P-M model refined the original spectra of H.O. 603, which over developed wave heights.

The primary difference in the results of the JONSWAP and P-M models is that it takes the JONSWAP model longer to reach a given height or fully developed seas. part this reflects the different starting wave In conditions. Because the propagation of waves from surrounding areas into semi-enclosed seas, bays, harbors, etc. is limited, there is little residual wave action following periods of locally light/calm winds and the sea surface is nearly flat. A local wind developed wave growth is therefore slower than wave growth in the open ocean where some residual wave action is generally always present. This slower wave development is a built in bias in the formulation of the JONSWAP model which is based on data collected in an enclosed sea.

A.1 Definitions

Waves that are being generated by local winds are called "SEA". Waves that have traveled out of the generating area are known as "SWELL". Seas are chaotic in period, height and direction while swell approaches a simple sine wave pattern as its distance from the generating area increases. An in-between state exists for a few hundred miles outside the generating area and is a condition that reflects parts of both of the above definitions. In the Mediterranean area, because its fetches and open sea expanses are limited, SEA or IN- BETWEEN conditions will prevail. The "SIGNIFICANT WAVE HEIGHT" is defined as the average value of the heights of the one-third highest waves. PERIOD and WAVE LENGTH refer to the time between passage of, and distances between, two successive crests on the sea surface. The FREQUENCY is the reciprocal of the period (f = 1/T) therefore as the period increases the frequency decreases. Waves result from the transfer of energy from the wind to the sea surface. The area over which the wind blows is known as the FETCH, and the length of time that the wind has blown is the DURATION. The characteristics of waves (height, length, and period) depend on the duration, fetch, and velocity of the wind. There is a continuous generation of small short waves from the time the wind starts until it stops. With continual transfer of energy from the wind to the sea surface the waves grow with the older waves leading the growth and spreading the energy over a greater range of frequencies. Throughout the growth cycle a SPECTRUM of ocean waves is being developed.

Wave characteristics are best described by means of their range of frequencies and directions or their spectrum and the shape of the spectrum. If the spectrum of the waves covers a wide range of frequencies and directions (known as short-crested conditions), SEA conditions prevail. If the spectrum covers a narrow range of frequencies and directions (long crested conditions), SWELL conditions prevail. The wave spectrum depends on the duration of the wind, length of the fetch, and on the wind velocity. At a given wind speed and given state of wave development, each spectrum has a band frequencies where most of the total energy of is concentrated. As the wind speed increases the range of significant frequencies extends more and more toward lower frequencies (longer periods). The frequency of maximum energy is given in equation 1.1 where v is the wind speed in knots.

$$f_{max} = \frac{2.476}{v}$$
 (1.1)

The wave energy, being a function of height squared, increases rapidly as the wind speed increases and the maximum energy band shifts to lower frequencies. This results in the new developing smaller waves (higher frequencies) becoming less significant in the energy spectrum as well as to the observer. As larger waves develop an observer will pay less and less attention to the small waves. At the low frequency (high period) end the energy drops off rapidly, the longest waves are relatively low and extremely flat, and therefore also masked by the high energy frequencies. The result is that 5% of the upper frequencies and 3% of the lower frequencies can be cut-off and only the remaining

frequencies are considered as the <u>"significant part of</u> <u>the wave spectrum</u>. The resulting range of significant frequencies or periods are used in defining a fully arisen sea. For a fully arisen sea the approximate average period for a given wind speed can be determined from equation (1.2).

$$T = 0.285v$$
 (1.2)

Where v is wind speed in knots and T is period in seconds. The approximate average wave length in a fully arisen sea is given by equation (1.3).

 $\bar{L} = 3.41 \, \bar{T}^2$ (1.3)

Where L is average wave length in feet and \overline{T} is average period in seconds.

The approximate average wave length of a fully arisen sea can also be expressed as:

$$L = .67"L"$$
 (1.4)

where "L" = $5.12T^2$, the wave length for the classic sine wave.

A.3 Fully Arisen Sea Conditions

For each wind speed there are minimum fetch (n mi) and duration (hr) values required for a fully arisen sea to exist. Table A-1 lists minimum fetch and duration values for selected wind speeds, values of significant wave (average of the highest 1/3 waves) period and height, and wave length of the average wave during developing and fully arisen seas. The minimum duration time assumes a start from a flat sea. When pre-existing lower waves exist the time to fetch limited height will be shorter. Therefore the table duration time represents the maximum duration required.

Table A-1. Fully Arisen Deep Water Sea Conditions Based on the JONSWAP Model.

	Wind Speed (kt)	1	Minim Fetch (n mi	um /D)	urat (hr	ion ; s) ;	Siç Pe) Wa erio (sec	ve d/H)	(H1/3) leight (ft)	1	Wave Len Developi	gth ng/l //	(ft) ¹ . Fully Arisen	21
<u>i</u>		1									1	L X (.5)	/L	X (.67):
5	10	ł	28	/	4	- I		4	1	2		41	1	55	<u> </u>
1	15	1	55	1	6	1		6	1	4	1	92	',	123	1
1	20	ł	110	1	8			8	1	8	;	140	' ,	120	1
	75	,	110	Ϊ,				-		0		104	1	220	i
	20	i	100	/	11	1		- 9	/	12	1	208	1	278	!
1	30		210	1	13	1		11	1	16	ł	310		415	-
	75	1	710	,	4 -					10		210	/	413	i
1	55	,	310	/	12	i		13		22		433	1	580	-1
1	40	1	410	1	17	1		15	1	30	1	574	1	770	
									· · ·	~~			/	112	- i -

NOTES:

- ¹ Depths throughout fetch and travel zone must be greater than 1/2 the wave length, otherwise shoaling and refraction take place and the deep water characteristics of waves are modified.
- ² For the classic sine wave the wave length (L) equals 5.12 times the period (T) squared (L = $5.12T^2$). As waves develop and mature to fully developed waves and then propagate out of the fetch area as swell their wave lengths approach the classic sine wave length. Therefore the wave lengths of developing waves are less than those of fully developed waves which in turn are less than the length of the resulting swell. The factor of .5 (developing) and .67 (fully developed) reflect this relationship.

A.4 Wave Conditions Within The Fetch Region

Waves produced by local winds are referred to as <u>SEA</u>. In harbors the local sea or wind waves may create hazardous conditions for certain operations. Generally within harbors the fetch lengths will be short and therefore the growth of local wind waves will be fetch limited. This implies that there are locally determined upper limits of wave height and period for each wind velocity. Significant changes in speed or direction will result in generation of a new wave group with a new set of height and period limits. Once a fetch limited sea reaches its upper limits no further growth will occur unless the wind speed increases.

Table A-2 provides upper limits of period and height for given wind speeds over some selected fetch lengths. The duration in hours required to reach these upper limits (assuming a start from calm and flat sea conditions) is also provided for each combination of fetch length and wind speed. Some possible uses of Table A-2 information are:

- If the only waves in the area are locally generated wind waves, the Table can be used to forecast the upper limit of sea conditions for combinations of given wind speeds and fetch length.
- 2) If deep water swell is influencing the local area in addition to locally generated wind waves, then the Table can be used to determine the wind waves that will combine with the swell. Shallow water swell conditions are influenced by local bathymetry (refraction and shoaling) and will be addressed in each specific harbor study.
- Given a wind speed over a known fetch length the maximum significant wave conditions and time needed to reach this condition can be determined.

Table A-2. Fetch Limited Wind Wave Conditions and Time Required to Reach These Limits (Based on JONSWAP Model). Enter the table with wind speed and fetch length to determine the significant wave height and period, and time duration needed for wind waves to reach these limiting factors. All of the fetch/speed combinations are fetch limited except the 100 n mi fetch and 18 kt speed.

Fetch \	Wind Speed	(kt)			ł
Length \	18	24	1 30 1	36	42
(n mi)			1		
;				1	1
10	2/3-4	3/3-4	3-4/4	4/4-5	5/5
1	1-2	2	1 2 1	1-2	1-2
			}		
1 20 1	3/4-5	4/4-5	1 5/5 I	6/5-6	7/5-6
1	2-3	3	1 3 1	3-4	3 1
1			1		
1 30 1	3-4/5	5/5-6	6/6 1	7/6	8/6-7 ;
1	3	4	3-4	3-4	3
			1		
1 40 1	4-5/5-6	5/6	6-7/6-7	8/7	9-10/7-8 ;
<u> </u>	4-5	4	4 (4	: 3-4 ;
			1		1
100	5/6-71	9/8	11/9	13/9	15-16/9-10
1	5-6	8	<u> 7 </u>	7	7

Format: height (feet)/period (seconds) duration required (hours)

¹ 18 kt winds are not fetch limited over a 100 n mi fetch.

An example of expected wave conditions based on Table A-2 follows: WIND FORECAST OR CONDITION

> An offshore wind of about 24 kt with a fetch limit of 20 n mi (ship is 20 n mi from the coast) is forecast or has been occurring.

SEA FORECAST OR CONDITION

From Table A-2: If the wind condition is forecast to last, or has been occurring, for at least 3 hours:

Expect sea conditions of 4 feet at 4-5 second period to develop or exist. If the condition lasts less than 3 hours the seas will be lower. If the condition lasts beyond 3 hours the sea will not grow beyond that developed at the end of about 3 hours unless there is an increase in wind speed or a change in the direction that results in a longer fetch.

The wave climatology used in these harbor studies based on 11 years of Mediterranean SOWM output. is The MED-SOWM is discussed in Volume II of the U.S. Nava1 Oceanography Command Numerical Environmental Products <u>Manual (1986). A deep water MED-SOWM grid point</u> was as representative of the deep water selected wave conditions outside each harbor. The deep water waves were then propagated into the shallow water areas. Using linear wave theory and wave refraction computations the shallow water climatology was derived from the modified deep water wave conditions. This climatology does not include the local wind generated seas. This omission, by design, is accounted for by removing all wave data for periods less than 6 seconds in the climatology. These shorter period waves are typically dominated by locally generated wind waves.

A.6 Propagation of Deep Water Swell Into Shallow Water Areas

When deep water swell moves into shallow water the wave patterns are modified, i.e., the wave heights and directions typically change, but the wave period remains constant. Several changes may take place including shoaling as the wave feels the ocean bottom, refraction as the wave crest adjusts to the bathymetry pattern, changing so that the crest becomes more parallel to the bathymetry contours, friction with the bottom sediments, interaction with currents, and adjustments caused by water temperature gradients. In this work, only shoaling and refraction effects are considered. Consideration of the other factors are beyond the resources available for this study and, furthermore, they. are considered less significant in the harbors of this study than the refraction and shoaling factors.

To determine the conditions of the deep water waves in the shallow water areas the deep water

first obtained from the Navy's conditions were operational MED-SOWM wave model. The bathymetry for the harbor/area of interest was extracted from available charts and digitized for computer use. Figure A-1 is a sample plot of bathymetry as used in this project. A ray path refraction/shoaling program was run for selected combinations of deep water wave direction and period. The selection was based on the near deep water wave Each study harbor exposure. area climatology and requires a number of ray path computations. Typically there are 3 or 4 directions (at 30° increments) and 5 or 6 periods (at 2 second intervals) of concern for each area of study. This results in 15 to 24 plots per area/harbor. To reduce this to a manageable format for quick reference, specific locations within each study area were selected and the information was summarized and is presented in the specific harbor studies in tabular form.



Figure A-1. Example plot of bathymetry (Naples harbor) as used in this project. For plotting purposes only, contours are at 50 fathom intervals from an initial 10 fathoms to 110 fathoms, and at 100 fathom intervals thereafter. The larger size numbers identify specific anchorage areas addressed in the harbor study.

Hasselmann, K. D., D. B. Ross, P. Muller, and W. Sell, 1976: A parametric wave prediction model. <u>J. Physical</u> <u>Oceanography</u>, Vol. 6, pp. 208-228.

Neumann, G., and W. J. Pierson Jr., 1966: <u>Principles of</u> <u>Physical Oceanography</u>. Prentice-Hall, Englewood Cliffs.

Pierson, W. J. Jr., G. Neumann, and R. W. James, 1955: <u>Practical Methods for Observing and Forecasting Ocean</u> <u>Waves</u>, H. O. Pub. No. 603.

Thornton, E. B., 1986: <u>Unpublished lecture notes for</u> <u>DC 3610, Waves and Surf Forecasting</u>. Naval Postgraduate School, Monterey, CA.

U. S. Naval Oceanography Command, 1986: <u>Vol. II of the</u> <u>U. S. Naval Oceanography Command Numerical Environmental</u> <u>Products Manual</u>. SNDL

21A1	CINCLANTFLT
21A3	CINCUSNAVEUR
22A1	COMSECONDFLT
22A3	COMSIXTHFLT
23B3	Special Force Commander EUR
24A1	Naval Air Force Commander LANT
24D1	Surface Force Commander LANT
24E	Mine Warfare Command
24G1	Submarine Force Commander LANT
26001	Special Warfare Group LANT
28A1	Carrier Group LANT (2)
28B1	Cruiser-Destroyer Group LANT (2)
28D1	Destroyer Squadron LANT (2)
28J1	Service Group and Squadron LANT (2)
28K1	Submarine Group and Squadron LANT
28L1	Amphibious Squadron LANT (2)
29A1	Guided Missile Cruiser LANT
29Bl	Aircraft Carrier LANT
29D1	Destroyer LANT (DD 931/945 Class)
29El	Destroyer LANT (DD 963 Class)
29Fl	Guided Missile Destroyer LANT
29G1	Guided Missile Frigate (LANT)
2911	Frigate LANT (FF 1098)
29J1	Frigate LANT (FF 1040/1051 Class)
29K1	Frigate LANT (FF 1052/1077 Class)
29L1	Frigate LANT (FF 10/8/109/ Class)
29N1	Submarine LANT (SSN)
290	Submarine LANT SSBN
29RL	Sattleship Lant (2) Swided Missile Erisete LAND (EEC 7)
29AAL	Guided Missile Frigate LANI (FFG /)
	Amphibious Command Ship (ANT (2)
21AL	Amphibious Command Ship LANI (2)
2101	Amphibious Cargo Ship LANI
3101	Amphibious Assault Ship LANT (2)
2111	Dock Landing Ship LANT
31.11	Dock Landing Ship LANT
3101	Tank Landing Ship LANT
32A1	Destrover Tender LANT
3201	Ammunition Ship LANT
3261	Combat Store Ship LANT
32H1	Fast Combat Support Ship LANT
32N1	Oiler LANT
3201	Replenishment Oiler LANT
3251	Repair Ship LANT
32X1	Salvage Ship LANT
32DD1	Submarine Tender LANT
32EE1	Submarine Rescue Ship LANT
32KK	Miscellaneous Command Ship
32001	Salvage and Rescue Ship LANT
32TT	Auxiliary Aircraft Landing Training Ship

Dist-1

42N1	Air Anti-Submarine Squadron VS LANT
42P1	Patrol Wing and Squadron LANT
42BB1	Helicopter Anti-Submarine Squadron HS LANT
42CC1	Helicopter Anti-Submarine Squadron Light HSL LANT
C4Ø	Monterey, Naples, Sigonella and Souda Bay only
FD2	Oceanographic Office - COMNAVOCEANCOM
FD3	Fleet Numerical Oceanography Center - FNOC
FD4	Oceanography Center - NAVEASTOCEANCEN
FD5	Oceanography Command Center - COMNAVOCEANCOM

copy to:

21A2	CINCPACFLT
22A2	Fleet Commander PAC
24F	Logistics Command
24H1	Fleet Training Command LANT
28A2	Carrier Group PAC (2)
29B2	Aircraft Carrier PAC (2)
29R2	Battleships PAC (2)
31A2	Amphibious Command Ship PAC (2)
31H2	Amphibious Assault Ship PAC (2)
FA2	Fleet Intelligence Center
FC14	Air Station NAVEUR
FD1	Oceanography Command
USDAO	France, Israel, Italy and Spain

Stocked:

NAVPUBFORMCEN (50 copies)

Dist-2

NAVENVPREDRSCHFAC SUPPLEMENTARY DISTRIBUTION

COMMANDING GENERAL (G4) FLEET MARINE FORCE, ATLANTIC ATTN: NSAP SCIENCE ADVISOR NORFOLK, VA 23511 USCINCLANT NAVAL BASE NORFOLK, VA 23511

USCINCENT ATTN: WEATHER DIV. (CCJ3-W) MACDILL AFB, FL 33608-7001

OFFICE OF NAVAL RESEARCH CODE 1122AT, ATMOS. SCIENCES ARLINGTON, VA 22217-5000 ROOM 5E731, THE PENTAGON WASHINGTON, DC 20350

ASST. SEC. OF THE NAVY (R&D)

ASST. FOR ENV. SCIENCES

OFFICE OF NAVAL RESEARCH ENV. SCI. PROGRAM, CODE 112 ARLINGTON, VA 22217-5000

OFFICE OF NAVAL RESEARCH ATTN: HEAD, OCEAN SCIENCES DIV CODE 1122 ARLINGTON, VA 22217-5000

OFFICE OF NAVAL TECHNOLOGY ONR (CODE 22) 800 N. QUINCY ST. ARLINGTON, VA 22217-5000

CHIEF OF NAVAL OPERATIONS NAVY DEPT. OP-986G WASHINGTON, DC 20350

CHIEF OF NAVAL OPERATIONS OP-953 NAVY DEPARTMENT WASHINGTON, DC 20350 OFFICE OF NAVAL RESEARCH CODE 1122 PO, PHYSICAL OCEANO. ARLINGTON, VA 22217-5000

CHIEF OF NAVAL OPERATIONS (OP-006) U.S. NAVAL OBSERVATORY WASHINGTON, DC 20390

CHIEF OF NAVAL OPERATIONS U.S. NAVAL OBSERVATORY DR. RECHNITZER, OP-952F 34TH & MASS AVE. WASHINGTON, DC 20390

COMMANDANT OF THE MARINE CORPS HDQ, U.S. MARINE CORPS WASHINGTON, DC 20380 COMMANDER IN CHIEF U.S. CENTRAL COMMAND MACDILL AFB, FL 33608

CHIEF OF NAVAL RESEARCH (2) LIBRARY SERVICES, CODE 784 BALLSTON TOWER #1 800 QUINCY ST. ARLINGTON, VA 22217-5000

OFFICE OF NAVAL RESEARCH ATTN: PROGRAM MANAGER, 1122CS ARLINGTON, VA 22217-5000

OFFICE OF NAVAL RESEARCH CODE 1122 MM, MARINE METEO. ARLINGTON, VA 22217-5000

CHIEF OF NAVAL OPERATIONS NAVY DEPT., OP-622C WASHINGTON, DC 20350

CHIEF OF NAVAL OPERATIONS OP-952D U.S. NAVAL OBSERVATORY WASHINGTON, DC 20390

DIRECTOR NATIONAL SECURITY AGENCY ATTN: LIBRARY (2C029) FT. MEADE, MD 20755

OJCS/J3/ESDOFFICER IN CHARGEOFFICER IN CHARGETHE PENTAGON, ROOM 2B887NAVOCEANCOMDETU.S. NAVOCEANCOMDETWASHINGTON, DC 20301-5000NAVAL STATIONBOX 16CHARLESTON, SC 29408-6475FPO NEW YORK 09593-5000

OFFICER IN CHARGE NAVOCEANCOMDET NAVAL EDUCATION & TRNG CENTER NEWPORT, RI 02841-5000

OFFICE OF NAVAL RESEARCH SCRIPPS INSTITUTION OF OCEANOGRAPHY LA JOLLA, CA 92037

COMMANDER NAVAL OCEANOGRAPHY COMMAND NSTL, MS 39529-5000

CHAIRMAN OCEANOGRAPHY DEPT. U.S. NAVAL ACADEMY ANNAPOLIS, MD 21402

LIBRARY NAVAL POSTGRADUATE SCHOOL MONTEREY, CA 93943-5002

COMSPAWARSYSCOM ATTN: CAPT. R. PLANTE CODE 3213, NAVY DEPT. WASHINGTON, DC 20363-5100

DIRECTOR NAVSURFWEACEN, WHITE OAKS NAVY SCIENCE ASSIST. PROGRAM SILVER SPRING, MD 20903-5000

3350TH TECH. TRNG GROUP TTGU/2/STOP 623 CHANUTE AFB, IL 61868 OFFICER IN CHARGE U.S. NAVOCEANCOMDET APO NEW YORK 09406-5000

COMMANDING OFFICER NAVAL OCEAN RSCH & DEV ACT NSTL, MS 39529-5004

COMNAVOCEANCOM ATTN: CODE N5 NSTL, MS 39529-5000

DIRECTOR OF RESEARCH U.S. NAVAL ACADEMY ANNAPOLIS, MD 21402

PRESIDENT NAVAL WAR COLLEGE GEOPHYS. OFFICER, NAVOPS DEPT. NEWPORT, RI 02841

COMMANDER, D.W. TAYLOR NAVAL SHIP RSCH. & DEV. CENTER SURFACE SHIP DYNAMICS BRANCH ATTN: S. BALES BETHESDA, MD 20084-5000

COMMANDING GENERAL FLEET MARINE FORCE, LANT (G4) ATTN: NSAP SCIENCE ADVISOR NORFOLK, VA 23511

OFFICER IN CHARGE SERVICE SCHOOL COMMAND DET. CHANUTE/STOP 62 CHANUTE AFB, IL 61868 COMMANDING OFFICER NAVAL RESEARCH LAB ATTN: LIBRARY, CODE 2620 WASHINGTON, DC 20390

COMMANDING OFFICER FLEET INTELLIGENCE CENTER (EUROPE & ATLANTIC) NORFOLK, VA 23511

SUPERINTENDENT LIBRARY REPORTS U.S. NAVAL ACADEMY ANNAPOLIS, MD 21402

NAVAL POSTGRADUATE SCHOOL OCEANOGRAPHY DEPT. MONTEREY, CA 93943-5000

COMMANDER NAVAL SAFETY CENTER NAVAL AIR STATION NORFOLK, VA 23511

COMMANDER NAVSURFWEACEN, CODE R42 DR. B. KATZ, WHITE OAKS LAB SILVER SPRING, MD 20903-5000

USAFETAC/TS SCOTT AFB, IL 62225

COMMANDING OFFICER U.S. ARMY RESEARCH OFFICE ATTN: GEOPHYSICS DIV. P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709 COMMANDER COASTAL ENGINEERING RSCH CEN KINGMAN BLDG. FT. BELVOIR, VA 22060

DIRECTOR, ENV. & LIFE SCI. OFFICE OF UNDERSECRETARY OF DEFENSE FOR RSCH & ENG E&LS RM. 3D129, THE PENTAGON WASHINGTON, DC 20505

COMMANDANT

DEFENSE LOGISTICS STUDIES INFORMATION EXCHANGE ARMY LOGISTICS MANAGEMENT CENTER FORT LEE, VA 23801

COMMANDING OFFICER USCG RESTRACEN YORKTOWN, VA 23690

FEDERAL COORD. FOR METEORO. SERVS. & SUP. RSCH. (OFCM) 11426 ROCKVILLE PIKE SUITE 300 ROCKVILLE, MD 20852

NOAA RSCH FACILITIES CENTER P.O. BOX 520197 MIAMI, FL 33152 DIRECTOR LIBRARY, TECH. INFO. CEN. ARMY ENG. WATERWAYS STN. VICKSBURG, MS 39180

CENTRAL INTELLIGENCE AGENCY ATTN: OCR STANDARD DIST. WASHINGTON, DC 20505

COMMANDANT U.S. COAST GUARD WASHINGTON, DC 20226

COMMANDING OFFICER USCG RSCH & DEV. CENTER GROTON, CT 06340

NATIONAL CLIMATIC CENTER ATTN: L. PRESTON D542X2 FEDERAL BLDG. - LIBRARY ASHEVILLE, NC 28801

DIRECTOR ATLANTIC MARINE CENTER COAST & GEODETIC SURVEY, NOAA 439 W. YORK ST. NORFOLK, VA 23510

HEAD OFFICE OF OCEANO. & LIMNOLOGY SMITHSONIAN INSTITUTION WASHINGTON, DC 20560 SCRIPPS INSTITUTION OF OCEANOGRAPHY, LIBRARY DOCUMENTS/REPORTS SECTION LA JOLLA, CA 92037

SCIENCE APPLICATIONS INTERNATIONAL CORP. (SAIC) 205 MONTECITO AVE. MONTEREY, CA 93940 OCEANROUTES, INC. 680 W. MAUDE AVE. SUNNYVALE, CA 94086-3518 DIRECTOR (12) DEFENSE TECH. INFORMATION CENTER, CAMERON STATION ALEXANDRIA, VA 22314

DIRECTOR, TECH. INFORMATION DEFENSE ADV. RSCH PROJECTS 1400 WILSON BLVD. ARLINGTON, VA 22209

CHIEF, MARINE SCI. SECTION U.S. COAST GUARD ACADEMY NEW LONDON, CT 06320

OCEANOGRAPHIC SERVICES DIV. NOAA 6010 EXECUTIVE BLVD. ROCKVILLE, MD 20852

DIRECTOR NATIONAL OCEANO. DATA CENTER E/OC23, NOAA WASHINGTON, DC 20235

CHIEF, INTERNATIONAL AFFAIRS NATIONAL WEATHER SERVICE 8060 13TH STREET SILVER SPRING, MD 20910

WOODS HOLE OCEANO. INST. DOCUMENT LIBRARY LO-206 WOODS HOLE, MA 02543

MR. W. G. SCHRAMM/WWW WORLD METEOROLOGICAL ORGANIZATION CASE POSTALE #5, CH-1211 GENEVA, SWITZERLAND DIRECTOR, INSTITUTE OF PHYSICAL OCEANOGRAPHY HARALDSGADE 6 2200 COPENHAGEN N. DENMARK

MINISTRY OF DEFENCE NAVY DEPARTMENT ADMIRALTY RESEARCH LAB TEDDINGTON, MIDDX ENGLAND

METEOROLOGIE NATIONALE SMM/DOCUMENTATION 2, AVENUE RAPP 75340 PARIS CEDEX 07 FRANCE

DIRECTION DE LA METEOROLOGIE ATTN: J. DETTWILLER, MN/RE 77 RUE DE SEVRES 92106 BOULOGNE-BILLANCOURT CEDEX, FRANCE

INSTITUT FUR MEERESKUNDE DER UNIVERSITAT HAMBURG HEIMHUDERSTRASSE 71 2000 HAMBURG 13 FEDERAL REPUBLIC OF GERMANY

CONSIGLIO NAZIONALE DELLE RICERCHE ISTITUTO TALASSOGRAFICO DI TRIESTE, VIALE R. GESSI 2 34123 TRIESTE, ITALY DIRECTOR OF NAVAL OCEANO. & METEOROLOGY MINISTRY OF DEFENCE OLD WAR OFFICE BLDG. LONDON, S.W.1. ENGLAND

COMMANDER IN CHIEF FLEET ATTN: STAFF METEOROLOGIST & OCEANOGRAPHY OFFICER NORTHWOOD, MIDDLESEX HA6 3HP ENGLAND

SERVICE HYDROGRAPHIQUE ET OCEANOGRAPHIQUE DE LA MARINE ESTABLISSEMENT PRINCIPAL RUE DU CHATELLIER, B.P. 426 29275 - BREST CEDEX, FRANCE

OZEANOGRAPHISCHE FORSCHUNGSANTALT BUNDESWEHR LORNSENSTRASSE 7, KIEL FEDERAL REPUBLIC OF GERMANY

DIRECTOR, DEUTSCHES HYDROGRAPHISCHES INSTITUT TAUSCHSTELLE, POSTFACH 220 D2000 HAMBURG 4 FEDERAL REPUBLIC OF GERMANY

DIRECTOR, SACLANT ASW RESEARCH CENTRE VIALE SAN BARTOLOMEO, 400 I-19026 LA SPEZIA, ITALY THE BRITISH LIBRARY SCIENCE REFERENCE LIBRARY (A) 25 SOUTHAMPTON BLDGS. CHANCERY LANE LONDON WC2A 1AW

LIBRARY, INSTITUTE OF OCEANOGRAPHIC SCIENCES ATTN: DIRECTOR WORMLEY, GODALMING SURRY GU8 5UB, ENGLAND

METEOROLOGIE NATIONALE 1 QUAI BRANLY 75, PARIS (7) FRANCE

INSTITUT FUR MEERESKUNDE AN DER UNIVERSITAT KIEL DUSTERNBROOKER WEG 20 23 KIEL FEDERAL REPUBLIC OF GERMANY

ISTITUTO UNIVERSITARIO NAVALE FACILTA DI SCIENZE NAUTICHE ISTITUTO DI METEOROLOGIA E OCEANOGRAFIA, 80133 NAPOLI – VIA AMM, ACTON, 38 ITALY

