DTC_ELE_COPY

AD-A199 717

OBJECTIVE ANALYSIS OF THE GULF STREAM THERMAL FRONT: METHODS AND ACCURACY



by

Karen L. Tracey Amy I. Friedlander D. Randolph Watts

University of Rhode Island Graduate School of Oceanography Narragansett, R.I. 02882

GSO Technical Report 87-2 December 1987



82

Approved for public release; Distribution Unlimited OBJECTIVE ANALYSIS

OF THE

GULF STREAM THERMAL FRONT:

METHODS AND ACCURACY

bу

Karen L. Tracey Amy I. Friedlander D. Randolph Watts

Graduate School of Oceanography University of Rhode Island Narragansett, Rhode Island 02882

GSO Technical Report No. 87-2

December, 1987

This research program has been sponsored by the National Science Foundation under grants OCE82-01222 and OCE85-17746 and by the Office of Naval Research under contract N00014-81-C-0062.

ABSTRACT

The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time-averaged mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, $ho_{
m um}$, which is based on four years of inverted echo sounder data collected in the same region of the Gulf Stream. Variations in the selection of the standard deviation field and decimation time have little effect on the output OA maps.

We determine the accuracy of the output OA maps by comparing them with independent measurements of the thermal field. Two cases are evaluated: standard maps and high temporal resolution maps, with decimation times of 2 days and 1 day, respectively. Standard deviations (STD) between the standard maps at the 15% estimated error level and the on For XETs (AXBTs) are determined to be 47-53 m. The comparisons of the high A&I temporal resolution maps at the 20% error level with the XBTs (AXBTs) give STD differences of 47 m.

> DTIC COPY



60

DTIC

DOPY NSPECTER

iii

2. ۳.

iv

ŝ

TABLE OF CONTENTS

Abstract	:	iii
List of	Tables	vii
List or	Figures	viii
Section	1. Int:	roduction 1
1.1	Backgro	ound
1.2	Specia	1 Application to the Gulf Stream Frontal Zone
1.3	Purpos	e of this Report
	•	•
Section	2. Des	cription of the Data 6
2.1	IES Mea	asurements
2.2	AXBT M	easurements
2.3	XBT Me	asurements
Section	3. Tes	ts for Robustness of the Objective Analysis Method 12
3.1	Genera	1 Information for All Tests
	3.1.1	Standard maps
	3.1.2	The OA map evaluations
	3.1.3	Naming conventions
	012.0	
3.2	Mean F	ield Selection
	3.2.1	Description of the test
	3.2.2	Description of the AXBT and IES OA maps
	3.2.3	Internal consistency 24
	3.2.4	Comparison of the AXBT OA maps
	3.2.5	Comparison of the TES OA maps 28
	3.2.6	Intercomparison of the AVET and IES OA mans 29
	01210	incercomparison of the ANDI and ind or maps
3.3	Standa	rd Deviation Field Selection
	3.3.1	Description of the test
	3.3.2	Description of the AXBT and IES OA maps
	3.3.3	Internal consistency
	3.3.4	Comparison of the AXBT OA maps
	3.3.5	Comparison of the TES OA maps
	3.3.6	Intercomparison of the AXBT and IES OA maps
3.4	Correla	ation Function Selection
	3.4.1	Description of the test
	3.4.2	Description of the AXET and IES OA maps 41
	3.4.3	Internal consistency
	3.4.4	Comparison of the AXBT OA maps
	3.4.5	Comparison of the IES OA maps
	3.4.6	Intercomparison of the AXBT and IES OA maps 50

v

Page

K- -

<u>Page</u>

3.5Decimation Time Selection503.5.1Description of the test503.5.2Description of the IES OA maps503.5.3Internal consistency503.5.4Comparison of the IES OA maps503.5.5Intercomparison of the AXET and IES OA maps50) 3 3 7 7
3.6 Summary of Results	9
Section 4. Tests of the IES OA Maps Against Independent Data 62	2
4.1 General Information624.1.1 Motivation for the test634.1.2 Distribution of the data644.1.3 Description of the test74	2 2 4 0
4.2 Comparison of the IES OA maps with XBT and AXBT Data: Case A ($\delta t = 2 d$)	2 2 6
4.3 Comparison of the IES OA maps with XBT and AXBT Data: Case B ($\delta t = 1 d$)	0 0 0
4.4 Accounting for the RMS differences	6
4.5 Summary of Results 8	9
Section 5. Conclusions	2
Acknowledgements	4
References	5
Appendix. Determination of the Correlation Function	7

LIST OF TABLES

Table 3.1	OA map abbreviations and the associated control parameters	13
Table 3.2	AXET OA maps evaluated at AXET sites for three mean fields	25
Table 3.3	IES OA maps evaluated at IES sites for three mean fields	25
Table 3.4	Differences between AXBT OA maps generated using three mean fields	27
Table 3.5	Differences between IES OA maps generated using three mean fields	27
Table 3.6	Intercomparisons of AXET and IES OA maps using three mean fields	29
Table 3.7	AXBT OA maps evaluated at AXBT sites for two standard deviation fields	35
Table 3.8	IES OA maps evaluated at IES sites for two standard deviation fields	35
Table 3.9	Differences between OA maps generated using two standard deviation fields	37
Table 3.10	Intercomparisons of AXBT and IES OA maps using two standard deviation fields	37
Table 3.11	AXBT OA maps evaluated at AXBT sites for three correlation functions	47
Table 3.12	IES OA maps evaluated at IES sites for three correlation functions	47
Table 3.13	Differences between AXBT OA maps generated using three correlation functions	49
Table 3.14	Differences between IES OA maps generated using three correlation functions	49
Table 3.15	Intercomparisons of AXET and IES OA maps using three correlation functions	51
Table 3.16	IES OA maps evaluated at IES sites for four decimation times	56
Table 3.17	Differences between IES OA maps generated using four decimation times	56
Table 3.18	Intercomparisons of AXBT and IES OA maps using four decimation times	58

LIST OF FIGURES

Figure 2.	.1	Map of IES array and timeline of XET and AXET surveys	7
Figure 3.	.1	Temporal and instantaneous mean fields	17
Figure 3.	.2	AXBT OA maps for survey 4 (12 June 1984) produced using three different mean fields	19
Figure 3.	.3	IES OA maps for survey 4 produced using three different mean fields	20
Figure 3.	.4	AXET CA maps for survey 5 (17 October 1984) produced using three different mean fields	21
Figure 3.	.5	IES OA maps for survey 5 produced using three different mean fields	22
Figure 3.	.6	Temporal and instantaneous standard deviation fields	31
Figure 3.	.7	AXBT and IES OA maps for survey 4 produced using two different standard deviation fields	32
Figure 3.	. 8	AXET and IES OA maps for survey 5, produced using two different standard deviation fields	34
Figure 3.	.9	Three correlation functions for time lags of 0-4 days	40
Figure 3.	.10	AXBT OA maps for survey 4, produced using three different correlation functions	42
Figure 3.	.11	IES OA maps for survey 4 produced using three different correlation functions	43
Figure 3	.12	AXBT OA maps for survey 5, produced using three different correlation functions	44
Figure 3	.13	IES OA maps for survey 5, produced using three different correlation functions	45
Figure 3	.14	IES OA maps for survey 4, produced using four different decimation times	54
Figure 3.	.15	IES OA maps for survey 5, produced using four different decimation times	55
Figure 4.	.1	The estimated error fields on 19 January 1985 for two decimation times for cases A and B	63

<u>Page</u>

Figure 4.2	Locations of the XBTs used
Figure 4.3	Number of comparisons made between IES OA maps and XBTs and AXBTs for cases A and B 67
Figure 4.4	Locations of the AXBT drop sites
Figure 4.5	Comparison of Z_{12} from XBTs with Z_{12} from IES OA maps at the 15% error level for case A 73
Figure 4.6	Comparison of Z_{12} from XBTs with Z_{12} from IES OA maps at the 35% error level for case A 74
Figure 4.7	Differences between IES OA maps and XBTs at five levels of estimated error for case A 75
Figure 4.8	Comparison of Z_{12} from AXBTs with Z_{12} from IES OA maps at the 15% error level for case A 77
Figure 4.9	Comparison of Z_{12} from AXBTs with Z_{12} from IES OA maps at the 35% error level for case A 78
Figure 4.10	Differences between IES OA maps and AXBTs at five levels of estimated error for case A 79
Figure 4.11	Comparison of Z_{12} from XBTs with Z_{12} from IES OA maps at the 20% error level for case B 81
Figure 4.12	Comparison of Z_{12} from XBTs with Z_{12} from IES OA maps at the 35% error level for case B 82
Figure 4.13	Differences between IES OA maps and XBTs at five levels of estimated error for case B 83
Figure 4.14	Comparison of Z_{12} from AXBTs with Z_{12} from IES OA maps at the 20% error level for case B 84
Figure 4.15	Comparison of Z_{12} from AXBTs with Z_{12} from IES OA maps at the 35% error level for case B 85
Figure 4.16	Differences between IES OA maps and AXBTs at five levels of estimated error for case B 87
Figure A.1	Plot of all IES pair separations (x',y') 99
Figure A.2	Correlation functions for cross-stream, along-stream, and diagonal IES pairs versus distance
Figure A.3	Idealized and observed correlation functions $\rho(x',y',t')$, contoured in plan view for time lags of 0, 2, 4, 6, 8, and 10 days

<u>Page</u>

SECTION 1. INTRODUCTION

1

1.1 Background

Objective analysis (OA) is a technique that statistically determines the optimal estimate of a quantity from a limited number of measurements of that quantity. The optimal estimate is the one, of all possible linear estimates, that has the least error. The optimal estimate is determined from the observations by knowing the space-time correlation function of the quantity being estimated. The first use of objective analysis was in meteorology when Gandin (1965) analyzed atmospheric pressure and wind fields. The technique was later introduced to oceanography by Bretherton <u>et al</u>. (1976), who demonstrated its use with simulated temperature and velocity data. Additionally, Freeland and Gould (1976) applied the method to velocity measurements obtained in the MODE region to produce stream function maps.

Several generalizations to the OA technique are presented in Carter (1983) and Carter and Robinson (1987). They extended its application to include spatial anisotropy by defining the correlations as functions of both x and y distances. Additionally, they introduced correlation functions that were dependent on the time lag as well. This allowed estimates of the field to be obtained from data collected over long periods of time.

In these applications, a necessary condition for performing objective analysis on the oceanographic data sets is that the fields being estimated must have homogenous statistics; that is, the mean must be zero and the variance must be uniform throughout. To satisfy these requirements, typically the technique could be applied only to data obtained from mid-ocean regions, areas that were away from strong boundary currents.

Watts and Tracey (1985; hereafter referred to as WT85) extended the use of the OA method to frontal regions, where the homogenous statistics are not found. They overcame this difficulty by preconditioning the input data prior to performing the objective analysis (described below). This report documents a series of tests on the consistency and accuracy of our objective analysis work on the Gulf Stream.

1.2 Special Application to the Gulf Stream Frontal Zone

We have performed objective analyses on a set of inverted echo sounder (IES) observations taken in the Gulf Stream region near Cape Hatteras, NC (Section 2). For example, in WT85 and in three data reports (Tracey et al., 1985; Tracey and Watts, 1986b; and Friedlander et al., 1986) we have produced a series of maps of the 12° C isotherm depth (Z_{12}) at daily intervals, in which each map consisted of a full grid of points at regular (20-km) spacing.

To estimate the value at each output grid point, the OA mapping technique selects from all the available data within a specified maximum ime lag (T) and maximum radial distance (R), the number of points (N)

which had the highest correlations (ρ). By using an assumed noise level (E), smoothing is permitted and the method is not required to fit all the observations exactly. For example, the output maps shown in WT85 result from specifying N = 9, T = ±4 days, R = 120 km, and E = 0.05.

Since the measurements were made in a frontal region, we must always precondition the data. First, the mean field is removed from the observations, and the resulting perturbation field is then normalized by the standard deviation. In this way, the perturbation field has

homogeneous statistics and is appropriate for objective analysis. Both the mean and standard deviation are restored to the output field after running the OA, thus mapping the Gulf Stream Z_{12} field. In WT85, the "mean field" that was removed approximated the instantaneous crossstream profile, in that it sloped steeply through the main portion of the thermocline. The standard deviation field was defined as the first derivative of the mean field, scaled to agree in magnitude with the observed variance. Both of these fields are shown below in Section 3.

A crucial input to the OA mapping technique is the correlation function. The Appendix to this report describes how the correlation function was determined empirically from nearly 5 years of measurements obtained in our study region of the Gulf Stream. An important result of this work is that after the mean field is removed from the observations, the resulting correlation function is isotropic. We typically use an analytic correlation function that was obtained by fitting a decaying (temporal and spatial) cosine function to the observed correlations. This function is shown in Section 3. This report compares results from other functions as well.

Additionally, the input time series of Z_{12} measurements had a sampling interval of one day. However, in our earlier mapping work we subsampled these input data at two-day intervals to use more independent measurements.

The OA technique also produces error estimates of the output Z_{12} field. The error associated with each output grid point depends only on the locations, in ~pace and time, of the input data and the correlation function; it is independent of the measurements themselves. We have used these estimated error fields to mask out regions of the Z_{12} maps where the map quality is predicted to be poor (estimated errors

≥15-20%). Examples of these error fields are presented in Section 4.
1.3 Purpose of this Report

It is evident that the choices for the OA control parameters used by WT85 are not the only ones possible. For example, where WT85 used the instantaneous Gulf Stream profile to approximate the mean field, a temporally averaged thermocline profile might also have been used. Is the objective mapping technique robust to variations in these choices? Do the OA maps accurately represent the "true" field? In this report, we document the effects of varying the control parameters on the output maps. Then we determine the accuracy of these OA maps by comparing them with other independent measurements of the Gulf Stream thermocline field.

An array of inverted echo sounders was deployed in the Gulf Stream northeast of Cape Hatteras from July 1982 through May 1985 in order to monitor changes in the path of the current. In previous investigations (Watts and Rossby, 1977; Watts and Johns, 1982), IESs have been shown to be reliable instruments for monitoring the thermal structure of the water column with high temporal resolution. However, the instruments have been located at only a limited number of sites and were separated by relatively large distances (60-65 km). Since observations which provide both high temporal and spatial resolution are desired, the method of objective analysis was employed on the three-year-long set of IES data to produce daily maps of the Gulf Stream thermocline depth field on a highly resolved horizontal grid. The mapped region (Figure 2.1) extended 240 km across the Gulf Stream and 460 km downstream, with grid point spacings of 20 km.

The IES OA maps are tested against concurrent measurements of the Gulf Stream thermocline depth field obtained using ship- and

aircraft-deployed expendable bathythermographs (XBTs and AXBTs, respectively). The IES, XBT, and AXBT data are described in Section 2.

In Section 3, we test the robustness of the OA technique to variations in the selection of (a) mean field, (b) standard deviation field, (c) correlation function, and (d) subsampling interval of the input time series. For these tests, objective maps have been produced for both the IES and AXBT data. First we check the output maps for internal consistency by comparing them with the actual observations. Then we examine the differences between the OA maps produced with different choices of the above parameters, repeating these comparisons for a representative selection of maps.

In Section 4, we further test the accuracy of the IES OA maps by comparing them with independent measurements of the thermocline depth field. The Z_{12} s are extracted from over 500 XBT and AXBT records taken in the Gulf Stream frontal region throughout the three-year period. We also determined the Z_{12} from the corresponding objective maps, using a linear interpolation scheme whenever an XBT or AXBT site did not correspond to an output grid point. The differences between these observed and estimated values were calculated and these were subsequently compared at different levels of estimated mapping errors.

Finally, in Section 5, we present a summary of the important conclusions.

SECTION 2. DESCRIPTION OF THE DATA

2.1 IES Measurements

For the period July 1982 through May 1985, thermocline depth records of the Gulf Stream downstream of Cape Hatteras were collected using inverted echo sounders. The array, shown in Figure 2.1, was configured such that the lines of instruments were approximately normal to the historical mean axis of the current. The IESs were deployed on various subsets of the lines during several deployments throughout the three-year period. Typically, the instruments were placed about 60 km apart across the Gulf Stream and 65 km apart downstream. The number of IESs in the water at any given time varied from 8 to 20 (Figure 2.1), depending on the deployment and recovery schedules.

Using the techniques described in Watts and Johns (1982) and Tracey and Watts (1986a), the travel times measured by the IESs were scaled to thermocline depths. For many practical purposes the main thermocline depth can be represented by the depth of an individual isotherm. We have chosen the 12°C isotherm since it is situated near the highest temperature gradient of the main thermocline. In this report, we refer to the main thermocline depth and the depth of the 12°C isotherm (Z_{12}) interchangeably. The Z_{12} measurements for each instrument were smoothed using a 40-hour low-pass filter to remove the tidal and internal wave signals.

Objective maps of the thermocline field in the array area were produced from these Z_{12} records at daily intervals for July 1982 to May 1985. The boxed region in Figure 2.1, oriented 064°T, is the 240 km by 460 km region which has been mapped. Two complete sets of maps were generated. The first set of maps (case A) was produced using the







Figure 2.1 Map of IES array (top) and timeline of XBT and AXBT surveys (bottom). IES locations are shown by the solid circles and squares; the box outlines the 240 km by 460 km region mapped by objective analysis. The number of IESs deployed in the study area between July 1982 and May 1985 are indicated on the timeline. The dates of the XBT shipboard surveys and AXBT flight surveys are indicated by the arrows below the timeline.

special objective analysis (OA) techniques described in Section 1.2, together with the control parameters listed below (Section 3.1.1) for the "standard" maps. The second set (case B) was produced using different control parameters (described in Section 4.1.1), which gave higher temporal resolution. The complete set of case A IES OA maps for the three-year period is documented in three data reports (Tracey <u>et</u> <u>al.</u>, 1985; Tracey and Watts, 1986b; and Friedlander <u>et al.</u>, 1986).

In Section 3 of this report, the IES OA maps produced for 12 June and 17 October 1984 are used for the sensitivity tests of the mapping technique to the choices of control parameters. These two dates were selected because they coincided with two of the seven AXBT surveys (described below) that were conducted in the same region, and because the Gulf Stream path on these two dates typified two different cases.

In June 1984, the Gulf Stream flowed along a relatively straight path through the center of the IES array. At that time, we were conducting a cruise in the array area to recover and redeploy the instruments. Since some of the IESs were out of the water during that period, no real-time Z₁, measurements were available at those sites for 12 June. Thus, it was necessary to use time-lagged data in order to map the complete area. As a result, the estimated error fields associated with the IES CA maps for this day are slightly larger than those obtained when real-time measurements were available at all sites. The fourth AXET survey was conducted on this day.

In contrast, on 17 October, the path of the Gulf Stream through the study area was arched by the passage of a meander. The strong thermal front associated with the Gulf Stream was located far to the north and almost out of the region mapped by the IES array. Since all the instruments were in the water at that time, the estimated error fields

associated with the IES OA maps are representative of those obtained during the three-year period. The fifth AXET survey was conducted on this day. However, since the drop sites are typically concentrated in the frontal region, the spatial overlap between the AXET survey and the IES array is limited.

In Section 4, the accuracy of both the case A ("standard") and case B (high temporal resolution) IES OA maps are assessed by comparing them with concurrent Z_{12} measurements obtained from XBT and AXBT (described below) probes deployed in the same region of the Gulf Stream. The Z_{12} value was determined from each IES OA map for exactly the same location as the XBT or AXBT drop site. When the drop site was not located at an output grid point, the Z_{12} value was found by linear interpolation.

Of the daily IES OA maps, the one that was closest in time to the probe launch was used for the comparison. Since the flight time required to complete an AXBT survey was usually less than eight hours, only one IES OA map was needed for comparison with each survey. However, several maps were needed for the comparisons with the XBT measurements, since ship surveys take several days to complete.

2.2 AXBT Measurements

During 1984, John Bane (University of North Carolina) flew seven AXBT survey flights mapping areas of the Gulf Stream thermal field from Cape Hatteras to $65^{\circ}W$. For six of these, there was sufficient overlap in the coverage to allow us to compare the Z_{12} measurements with those obtained from the IESs.

The AXBT probes, manufactured by Sippican Corporation, measured the temperature structure to a depth of 760 m. The depth of the 12° C isotherm was extracted from each record; the deepest Z_{12} was used when

there were shallower temperature inversions. All probes dropped in regions where the water was too cold (Slope Water) or too warm (Sargasso Sea) to have Z_{12} values were excluded from the tests described in Sections 3 and 4.

Of the six flights, the first four were conducted during June 1984. These occurred on 1, 4, 6, and 12 June. The fifth and sixth surveys were flown on 17 October and 13 November 1984. These survey flights are indicated on the timeline in Figure 2.1. Approximately 100 probes were launched per flight, with spacings of about 18 km cross stream and 55 km downstream. Since the primary purpose was to resolve the thermal front associated with the Gulf Stream, the survey region changed with each flight, depending on the location of the current. As a result, the survey region did not always coincide completely with the region mapped by the IES array.

In Section 3, the Z_{12} measurements determined for the AXBTs were used to generate objective maps for 12 June and 17 October using the same techniques as those used to produce the IES OA maps. However, because the surveys were conducted intermittently, the AXBT OA maps were produced without using time-lagged measurements. In order to compare them with the IES OA maps for the same dates, the AXBT OA maps encompass the same region as shown in Figure 2.1. Although many of the AXBT drop sites were actually outside this region, all Z_{12} measurements obtained on a given survey were used to produce the map.

The data from all six of the AXBT surveys are used in Section 4. As described above, the thermocline depths were determined from the IES OA maps at the same locations as the AXBT drop sites. For this comparison, we excluded all probes that were outside the boxed region

shown in Figure 2.1 to avoid excessive extrapolation outside the IES array.

2.3 XBT Measurements

Five research cruises were conducted to the study area between July 1982 and May 1985 (Figure 2.1). Four of these took place aboard the R/V ENDEAVOR: EN087 (5-25 July 1982), EN106 (22-30 September 1983), EN118 (1-18 June 1984), and EN124 (11-20 January 1985). The remaining cruise was aboard the R/V COLUMBUS ISELIN (C8304, 16-27 April 1983).

In all, nearly 300 XBT probes were launched during that time period. There were three main goals for the surveys: (a) to calibrate the IES measurements, (b) to map short segments of the path of the Gulf Stream, and (c) to determine the cross-stream structure of the thermocline.

All XBTs were T-7 probes manufactured by Sippican Corporation; they measured the temperature structure down to 800 m. The depth of the 12°C isotherm was extracted for each probe in the same manner as described above for the AXBTs.

These data are used in Section 4 of this report to test the accuracy of the IES OA maps. Since the XBT surveys were often concentrated near the IES sites, essentially the only probes excluded from this study were those dropped in regions where the waters were either too warm or too cold to obtain Z_{12} values.

SECTION 3. TESTS FOR ROBUSTNESS OF THE OBJECTIVE ANALYSIS METHOD

3.1 General Information for All Tests

In this section we report the results of several tests conducted on the objective analysis method in which we varied the selection of several control parameters. We produced OA maps (Table 3.1) of both the IES and AXBT data for two dates, 12 June and 17 October 1984. The Gulf Stream paths on these two dates were considered to be representative of its positions during 1984-1985. In June, the Gulf Stream was flowing along a relatively straight path through the center of the IES array. By contrast, during October a large meander deflected the Gulf Stream to the north and nearly out of the IES array.

3.1.1 Standard maps

In order to compare the results from the various tests, we produced a set of OA maps, which we considered to be accurate representations of the true fields, to be used as the 'standard maps' against which other maps would be tested. One IES OA map and one AXBT OA map were generated for each of the two dates analyzed. These four maps were used in each of the tests described in the following sections.

Each of these standard OA maps (Table 3.1) was made using the following set of control parameters: (a) the temporal mean field, Z_T (described in Section 3.2); (b) the Gaussian-shaped standard deviation field, σ_T (Section 3.3); (c) the analytic correlation function, ρ_{WT} (Section 3.4); and (d) a decimation time of 2 days (Section 3.5). Additionally, each standard map was produced using a maximum radial distance R = 120 km and an assumed noise level E = 0.05. The IES OA maps were generated using N = 9 points and maximum time lag T = ±4 days. However, due to the closer station spacing, the AXBT OA maps were

Standard 14T IES 12 Jun Temporal Gaussian WT Analytic 2 Maps AT IES 17 0tt Temporal Gaussian WT Analytic 2 9 Maps AT AET IES 17 0tt Temporal Gaussian WT Analytic 2 9 Maps AT AET IES 17 0tt Constant WT Analytic 2 9 Idd IES 17 0tt Constant WT Analytic 2 9 Idd IES 17 0tt Temporal Gaussian WT Analytic 2 9 Idd IES 17 0tt Temporal Constant WT Analytic 2 9 Standard ISC IES 17 0tt Temporal Constant WT Analytic 2 9 Standard ISC IES 17 0tt Temporal Constant WT Analytic 2 9 Standard ISC IES 17 0tt Temporal Constant WT Analytic 2 9 Standard ISC IES IT Cot Temporal	Map Type	Ma p Number	Data Type	Date (1984)	Mean Field	Standard Deviation Field	Correlation Function	Decimation Time (days)	*N	rt days)
Standard 157 125 17 125 17 125 17 1000 7emporat Gaussian 7f Analytic 2 9 A57 XXB7 17 Oct Temporal Gaussian VT Analytic 2 9 141 155 155 153 17 Oct Temporal Gaussian VT Analytic 2 9 145 155 155 17 Oct Temporal Constant VT Analytic 2 9 145 155 157 155 17 Oct Temporal Constant VT Analytic 2 9 155 158 17 Oct Temporal Constant VT Analytic 2 9 Standard 155 158 17 Oct Temporal Constant VT Analytic 2 9 Standard AdS XXBT 17 Oct Temporal Constant VT Analytic 2 9 Standard ASS XXBT 17 Oct Temporal		14T	IES	12 Jun	Temporal	Gaussian	WT Analytic	00	σι	4
Idd Iss 12 Jun Constant VT Analytic 2 9 Idt IES 12 Jun Temporal Constant VT Analytic 2 9 Idts IES 12 Jun Temporal Constant VT Analytic 2 9 Idts IES 17 Oct Constant VT Analytic 2 9 Standard ISC IES 17 Oct Constant VT Analytic 2 9 Standard ISC IES 17 Oct Constant VT Analytic 2 9 Standard ISC IES 17 Oct Temporal Constant VT Analytic 2 9 Privation Add XBF 17 Oct Temporal Constant VT Analytic 2 9 AdS XBF 17 Oct Temporal Constant VT Analytic 2 9 AdS XBF 17 Oct Temporal Constant VT Analytic 2 9 AdS XBF 17 Oct Temporal Gaussian WT Analytic <	Standard Maps	15T A4T A5T	IES AXBT AXBT	17 Oct 12 Jun 17 Oct	Temporal Temporal Temporal	Gaussian Gaussian Gaussian	WT Analytic WT Analytic WT Analytic	N O O	ი ა ა	* 0 0
Term Temporation Constant Wr Analytic 2 9 Rean and 15C TES 17 Oct Constant Wr Analytic 2 9 Standard 15C TES 17 Oct Constant Constant Wr Analytic 2 9 Standard 15C TES 17 Oct Constant Constant Wr Analytic 2 9 Pields Adf AKB 12 Jun Constant Constant Wr Analytic 2 9 Advis AKB 17 Oct Constant Constant Wr Analytic 0 6 Advis AKB 17 Oct Constant Constant Wr Analytic 0 6 Advis AKB 17 Oct Temporal Constant Wr Analytic 0 6 Advis AKB 17 Oct Temporal Gaussian Bapirical 0 6 Advis AKB 17 Oct Temporal Gaussian Bapirical 2 9 Advis 17 Oct Temporal Gaussian Bapir		14C 14T	IES	12 Jun	Constant Tectantaneous	Constant Derivative	WT Analytic WT Analytic	N (б б	ৰ ব
Rean and 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170 170		14CS 14CS	IES 1	12 Jun 12 Jun	Temporal Constant	Constant Constant	WT Analytic WT Analytic	100		• ব ব
StandardISCSIES17 OctTemporalConstantWT Analytic29PeviationA4CAXBT12 JunInstanteneousConstantWT Analytic06A5CAXBT12 JunTemporalConstantWT Analytic06A5CAXBT17 OctTemporalConstantWT Analytic06A5CAXBT17 OctTemporalConstantWT Analytic06A5CAXBT17 OctTemporalConstantWT Analytic06A5CAXBT17 OctTemporalConstantWT Analytic06A5CAXBT17 OctTemporalConstantWT Analytic06A5CAXBT17 OctTemporalGaussianBMpirical29IABNIES12 JunTemporalGaussianBMpirical29IABNISS17 OctTemporalGaussianBMpirical29FunctionA4BRAXBT12 JunTemporalGaussianBMpirical29FunctionA4BRAXBT12 JunTemporalGaussianBMpirical29FunctionA4BRAXBT12 JunTemporalGaussianBMpirical29FunctionA4BRAXBT12 JunTemporalGaussianBMpirical06FunctionA4BRAXBT17 OctTemporalGaussian <td>Mean and</td> <td>151</td> <td>IES</td> <td>17 Oct</td> <td>Luistantaneous</td> <td>Derivative</td> <td>WT Analytic</td> <td>4 (2) (</td> <td>5</td> <td>* 4</td>	Mean and	151	IES	17 Oct	Luistantaneous	Derivative	WT Analytic	4 (2) (5	* 4
FieldsAIAXBT12 JunInstantaneousDerivativeWT Analytic06AGCSAXBT12 JunTemporalConstantWT Analytic06AGSAXBT17 OctConstantWT Analytic06A5AXBT17 OctConstantWT Analytic06A5AXBT17 OctConstantWT Analytic06A5AXBT17 OctTemporalConstantWT Analytic06A5AXBT17 OctTemporalGaussianBmpirical2914HNIES12 JunTemporalGaussianBmpirical2915HNIES17 OctTemporalGaussianBmpirical2915HNIES17 OctTemporalGaussianBMpirical2916HNIES17 OctTemporalGaussianBMpirical2917 OctTemporalGaussianBM Analytic29AHNAXBT17 OctTemporalGaussianBM Analytic06A5HNAXBT17 OctTemporalGaussianBM Analytic06A5HNAXBT17 OctTemporalGaussianBM Analytic06A5HNAXBT17 OctTemporalGaussianBM Analytic06A5HNA3BT17 OctTemporalGaussianWT Analytic06141	Standard Deviation	I5CS A4C	IES AXBT	17 Oct 12 Jun	Temporal Constant	Constant Constant	WT Analytic WT Analytic	0 0	ია	40
AFG AKBT 17 Oct Constant VT Analytic 0 6 A51 AKBT 17 Oct Instantaneous Derivative VT Analytic 0 6 A5Cs AKBT 17 Oct Temporal Constant VT Analytic 0 6 A5Cs AKBT 17 Oct Temporal Constant VT Analytic 0 6 A5Cs AKBT 17 Oct Temporal Gaussian Empirical 2 9 14HK IES 17 Oct Temporal Gaussian Empirical 2 9 I4HK IES 17 Oct Temporal Gaussian Empirical 2 9 IAHK IES 17 Oct Temporal Gaussian Empirical 2 9 Function A4EK AXBT 12 Jun Temporal Gaussian Empirical 0 6 A5EMP AXBT 17 Oct Temporal Gaussian Empirical 0 6 A5EMP AXBT 17 Oct Temporal Gaussian HA Analytic </td <td>Fields</td> <td>A4I A4CS</td> <td>AXBT ▲XBT</td> <td>12 Jun 12 Jun</td> <td>Instantaneous Temporal</td> <td>Derivative Constant</td> <td>WT Analytic WT Analytic</td> <td>00</td> <td>ي م</td> <td>0 0</td>	Fields	A4I A4CS	AXBT ▲XBT	12 Jun 12 Jun	Instantaneous Temporal	Derivative Constant	WT Analytic WT Analytic	00	ي م	0 0
A51 AXBT 17 Oct Instantaneous Derivative WT Analytic 0 6 A5C AXBT 17 Oct Temporal Constant WT Analytic 0 6 I4ENP IES 12 Jun Temporal Gaussian Empirical 2 9 I4HN IES 17 Oct Temporal Gaussian Empirical 2 9 I5ENP IES 17 Oct Temporal Gaussian Empirical 2 9 Correlation I5HN IES 17 Oct Temporal Gaussian Empirical 2 9 Correlation I5HN ABMP 17 Oct Temporal Gaussian Empirical 2 9 Correlation ABMP AND 12 Jun Temporal Gaussian Empirical 2 9 Correlation A5HN AND 12 Jun Temporal Gaussian Empirical 2 9 A6HN AND 17 Oct Temporal Gaussian HM Analytic 2 9 A5HN A		A5C	AXBT	17 Oct	Constant	Constant	WT Analytic	00	· ب د	
I4EMPIES12 JunTemporalGaussianEmpirical29IAHMIES12 JunTemporalGaussianHM Analytic29I5EMPIES17 OctTemporalGaussianEmpirical29I5EMPIES17 OctTemporalGaussianEmpirical29CorrelationI5HMIES17 OctTemporalGaussianEmpirical29FunctionA4EMPAKBT12 JunTemporalGaussianEmpirical29A4HMAXBT12 JunTemporalGaussianEmpirical06A5EMPAXBT17 OctTemporalGaussianHM Analytic29A5HMAXBT17 OctTemporalGaussianHM Analytic29A5HMAXBT17 OctTemporalGaussianHM Analytic06A5HMAXBT17 OctTemporalGaussianHM Analytic06A5HMAXBT17 OctTemporalGaussianHM Analytic06A5HMAXBT17 OctTemporalGaussianHM Analytic06A5HMAXBT17 OctTemporalGaussianWT Analytic06FunctionI44DIES12 JunTemporalGaussianWT Analytic17TimeI51DIES12 JunTemporalGaussianWT Analytic17<		A5I A5CS	AXBT AXBT	17 Oct 17 Oct	Instantaneous Temporal	Derlvative Constant	WT Analytic WT Analytic	00	مە	00
14thLES12 JunTemporalGaussianAddition14thLES12 JunFunction15HKIES17 OctTemporalGaussianEmpirical29FunctionA4HKAXBT12 JunTemporalGaussianEmpirical29A4HKAXBT12 JunTemporalGaussianEmpirical29A5HKAXBT17 OctTemporalGaussianEmpirical06A5HKAXBT17 OctTemporalGaussianHM Analytic06A5HKAXBT17 OctTemporalGaussianHM Analytic06A5HKAXBT17 OctTemporalGaussianHM Analytic06A5HKAXBT17 OctTemporalGaussianHM Analytic17A5HKAXBT17 OctTemporalGaussianWT Analytic17A5HK12 JunTemporalGaussianWT Analytic17A5HK12 JunTemporalGaussianWT Analytic17A5HK12 JunTemporalGaussianWT Analytic17A5HK151DIES12 JunTemporalGaussianWT Analytic17Time151DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49Time <td></td> <td>I 4EMP</td> <td>IES</td> <td>12 Jun</td> <td>Temporal</td> <td>Gaussian</td> <td>Empirical</td> <td>~ ~</td> <td>бо</td> <td>4 4</td>		I 4EMP	IES	12 Jun	Temporal	Gaussian	Empirical	~ ~	б о	4 4
CorrelationI5HMIES17 OctTemporalGaussianHM Analytic29FunctionA4HMAXBT12 JunTemporalGaussianEmpirical06A4HMAXBT12 JunTemporalGaussianEmpirical06A5EMPAXBT17 OctTemporalGaussianEmpirical06A5EMPAXBT17 OctTemporalGaussianEmpirical06A5HMAXBT17 OctTemporalGaussianEmpirical06A5HMAXBT17 OctTemporalGaussianHM Analytic17A5HMAXBT17 OctTemporalGaussianWT Analytic17A5HMIss12 JunTemporalGaussianWT Analytic17A5HMIss12 JunTemporalGaussianWT Analytic17Time151DIES17 OctTemporalGaussianWT Analytic17Time151DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49		14HR I5EMP	IES	17 Oct	Temporal Temporal	Gaussian Gaussian	Empirical	N (N	ה ע	4
A4HKAXBT12 JunTemporalGaussianHMAnalytic06A5EMPAXBT17 OctTemporalGaussianHMAnalytic06A5HMAXBT17 OctTemporalGaussianHMAnalytic06A5HMAXBT17 OctTemporalGaussianHMAnalytic06A5HMAXBT17 OctTemporalGaussianWTAnalytic06141DIES12 JunTemporalGaussianWTAnalytic17DecimationI44DIES12 JunTemporalGaussianWTAnalytic49DecimationI48DIES17 OctTemporalGaussianWTAnalytic17TimeI51DIES17 OctTemporalGaussianWTAnalytic17TimeI54DIES17 OctTemporalGaussianWTAnalytic49ToolISIES17 OctTemporalGaussianWTAnalytic49ToolISIES17 OctTemporalGaussianWTAnalytic49TimeI54DIES17 OctTemporalGaussianWTAnalytic49IISIESI7 OctTemporalGaussianWTAnalytic49	Correlation Function	I 5HM A4EMP	IES AXBT	17 Oct 12 Jun	Temporal Temporal	Gaussian Gaussian	HM Analytic Empirical	0 0	69	40
A5EMPAXBT17 OctTemporalGaussianEmpirical06A5HMAXBT17 OctTemporalGaussianHM Analytic06141DIES12 JunTemporalGaussianWT Analytic17144DIES12 JunTemporalGaussianWT Analytic17Decimation148DIES12 JunTemporalGaussianWT Analytic49Time151DIES17 OctTemporalGaussianWT Analytic811Time154DIES17 OctTemporalGaussianWT Analytic17Time154DIES17 OctTemporalGaussianWT Analytic17Time154DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49Time154DIES17 OctTemporalGaussianWT Analytic49		A4HM	AXBT	12 Jun	Temporal	Gaussian	HM Analytic	0	9	0
I41DIES12 JunTemporalGaussianWTAnalytic17I44DIES12 JunTemporalGaussianWTAnalytic49DecimationI48DIES12 JunTemporalGaussianWTAnalytic811TimeI51DIES17 OctTemporalGaussianWTAnalytic17TimeI54DIES17 OctTemporalGaussianWTAnalytic17ToolIES17 OctTemporalGaussianWTAnalytic49		A5EMP A5HM	AXBT AXBT	17 Oct 17 Oct	Temporal Temporal	Gausslan Gausslan	Empirical HM Analytic	0 0	وو	00
I44D IES 12 Jun Temporal Gaussian WT Analytic 4 9 Decimation I48D IES 12 Jun Temporal Gaussian WT Analytic 8 11 Time I51D IES 17 Oct Temporal Gaussian WT Analytic 1 7 Time I54D IES 17 Oct Temporal Gaussian WT Analytic 1 7 Time I54D IES 17 Oct Temporal Gaussian WT Analytic 4 9 Tool Tool Tool Tool Tool Tool 1 1		I41D	IES	12 Ju n	Temporal	Gaussian	WT Analytic	1	٢	-
Time I51D IES 17 Oct Temporal Gaussian WT Analytic 1 7 I54D IES 17 Oct Temporal Gaussian WT Analytic 4 9 I54D IES 17 Oct Temporal Gaussian WT Analytic 4 9	Decimation	I44D I48D	IES IES	12 Jun 12 Jun	Temporal Temporal	Gaussian Gaussian	WT Analytic WT Analytic	4 00	9	∞ ∞
I54D IES 17 Oct Temporal Gaussian WT Analytic 4 9 read the internation Connection WT Analytic 6 11	Time	151D	IES	17 Oct	Temporal	Gaussian	WT Analytic	I	7	,
		154D 158D	IES	17 Oct	Temporal Temporal	Gaussian Gaussian	WT Analytic WT Analytic	4α	6 [[ωα

OA map abbreviations and the associated control parameters. The maximum radial distance of R = 120 km and the assumed noise level of E = 0.05 are used for all of the objective maps listed. Table 3.1

•

* N is number of points. t r ic mavimum time lad

/

produced using N = 6. Since the AXET survey flights were conducted intermittently, the AXET OA maps were produced by specifying T = 0 days (no time lag).

In the following tests, other IES OA and AXBT OA maps for the same two days were produced by varying just one of these parameters at a time, keeping all of the others the same.

3.1.2 The OA map evaluations

For each test described below, we performed several comparisons in order to assess the sensitivity of the OA method to the parameter choices. An "internal consistency" check was performed in which the IES and AXBT OA maps were evaluated at the instrument sites, and then compared with the actual observations. Since both spatial and temporal smoothing were permitted, the estimated values did not need to agree exactly with the measurements. However, we expected the mapped fields to differ minimally from the input data at these sites.

Secondly, we compared pairs of OA maps by determining the differences between the estimated values at grid points. We limited the comparisons to include only those grid points for which the OA error field was predicted to be small (<15%). (The full estimated error field for a representative date is shown in Figure 4.1.) In the figures shown below, grid points which have been excluded from the analyses (predicted errors \geq 15%) are shaded by the crosshatchings. For each test, we compare IES OA maps against other IES OA maps produced using different choices of the one parameter being tested. We repeat the same analyses for the AXET OA maps. Subsequently, we intercompare the IES and AXET OA maps produced using the same parameter choices.

The differences, ΔZ , between the estimated values at grid points are calculated as:

$$\Delta Z = (OA Field 2) - (OA Field 1)$$

The first column in Tables 3.2-3.18 show the two OA maps being compared. For the internal consistency checks, OA Field 2 is replaced with the observations (abbreviated as OBS). The mean, range, and root-mean-square (RMS) differences of those grid points comparisons (NPTS) are listed in the tables, where

range = max(
$$\Delta Z$$
) - min(ΔZ)
mean = $\frac{\Sigma(\Delta Z)}{NPTS}$
RMS = $\left[\frac{\Sigma(\Delta Z)^2}{NPTS}\right]^{1/2}$

Additionally, we report the residual RMS (STD), which was determined as:

$$STD = [(RMS)^{2} - (Mean)^{2}]^{1/2}$$

3.1.3 Naming conventions

The IES and AXBT OA map numbers used in this report were formulated in the following way. The first letter, 'I' or 'A', indicates whether the map is derived from IES or AXBT data, respectively. Then a number (4 or 5) indicates the date of the map (the fourth AXBT survey was conducted on 12 June 1984; thus, the number '4' has been selected as the code for both the IES and AXBT maps for this day. Likewise, the fifth AXBT survey was made on 17 October 1984, and '5' has been used as its code number). The remaining symbols indicate the choices of the various parameters being tested. The abbreviations are listed in Table 3.1 along with the control parameters used to generate the maps.

/

3.2 Mean Field Selection

3.2.1 Description of the test

We chose to test the OA method sensitivity by using three different 'mean fields'. These three fields were: (a) a broad sloping profile, which represented the time-averaged thermocline, (b) a steeply sloping profile, which approximated the instantaneous thermocline running straight down the middle of the array, and (c) a constant mean throughout the entire mapping region.

To represent the time-averaged mean field, $Z_T(x,y)$, a third order polynomial was fitted to the mean Z_{12} values observed at the IES sites during the June 1984 to May 1985 deployment period (Tracey <u>et al</u>., 1985). The functional form of the polynomial was:

 $Z_{T}(x,y) = B_{0} + B_{1}x + B_{2}y + B_{11}x^{2} + B_{12}xy + B_{22}y^{2} + B_{111}x^{3} + B_{112}x^{2}y + B_{122}xy^{2} + B_{222}y^{3}$

where (x,y) is the position in kilometers from the origin at $36^{\circ}00'N$, 73°30'W and the x axis is along $064^{\circ}T$. B₀ is 5.997880E+02, B₁ is 6.122714E-01, B₂ is -3.145789E+00, B₁₁ is -1.427472E-03, B₁₂ is 5.780502E-03, B₂₂ is -7.886405E-03, B₁₁₁ is -3.748734E-07, B₁₁₂ is -1.383396E-05, B₁₂₂ is 5.646291E-06, and B₂₂₂ is 2.626524E-05. Figure 3.1 shows this 'temporal mean' field in plan view.

The 'instantaneous mean' field, Z_I , was approximated by an asymmetric tanh-like function of cross-stream distance y of the form:

$$Z_{I}(y) = Z_{I} + \left[\frac{Z_{B} - Z_{A}}{1 + \frac{1}{D}}\right] \left[\frac{\frac{-2(y-C)}{1 - e}}{\frac{1 - e}{A}}\right]$$

where Z_i is 350 m, Z_A is 100 m, Z_B is 850 m, D is 2.0, A is 40 km, and C is 25 km, determined from observational results. It should be noted that Z_I does not vary in the downstream direction and is identical to



Temporal

Instantaneous



Figure 3.1 The temporal mean field, Z_{T} (top), and the instantaneous mean field, Z_{T} (bottom), are contoured in plan view. Contours indicate the depth of the 12°C isotherm (Z_{12}), with dashed contours indicating depths shallower than 500 m. The contour interval is 50 m. The frames, corresponding to the boxed region of Figure 2.1, have been rotated so that the long sides lie across the page.

the mean field used in WT85. This instantaneous mean field is also shown in Figure 3.1.

The third mean field used in this test is typical of the mean fields removed in traditional applications of objective analysis (c.f., Carter, 1983). We defined the third mean field as $Z_{C} = 400$ m. It is unlike the temporal and instantaneous means, which slope down across the mapping region, in that it is constant throughout the entire area.

Associated with each of these mean fields is a different standard deviation field (σ). Since these σ fields are defined as functions of the mean fields, they were varied during this test as well. However, as will be shown in Section 3.3, the choice of σ alone has minimal effect on the output fields; thus, the comparisons presented here are primarily affected by the choice of mean field, not σ .

3.2.2 Description of the AXBT and IES OA maps

The AXBT and IES OA maps for 12 June are shown in Figures 3.2 and 3.3, respectively. The corresponding maps for 17 October are shown in Figures 3.4 and 3.5. In each figure, the three maps were produced from identical set of observations and the standard control parameters, except for the choices of mean fields (and their associated standard deviation fields).

The overall impression of the output maps produced by removing the various mean fields is that they are somewhat different from one another. However, their similarities, especially in the <u>interpolated</u> regions (between the instrument sites), are apparent on closer examination. In general, both the shape of the Gulf Stream path and the steepness of the thermocline are similar for maps constructed from the same observations (c.f., Figure 3.2). The obvious exceptions are maps ASI (Figure 3.4) and ISI (Figure 3.5), for which the combined usage of



righte 3.2 AABI OA maps for survey 4 (12 June 1984) produced using three different mean fields: temporal (A4T), instantaneous (A4I), and constant (A4C). The Z_{12} field is contoured at 50 m intervals, and depths shallower than 500 m are dashed. Hatching indicates regions where the estimated errors are $\geq 15\%$; these regions have been excluded from the comparisons.



Figure 3.3 IES OA maps for survey 4 (12 June 1984) produced using three different mean fields: temporal (I4T), instantaneous (I4I), and constant (I4C). Contours and hatching are the same as in Figure 3.2.



Figure 3.4 AXBT OA maps as in Figure 3.2 except for survey 5 (17 October 1984).



Figure 3.5 IES OA maps as in Figure 3.3 except for survey 5 (17 October 1984).

the instantaneous mean field (Z_I) with the Gulf Stream in a northern location results in a steepening of the thermocline and an 'overshoot' in estimating its depth on the offshore side.

The largest differences between the output maps occur in the <u>extrapolated</u> areas, outside the instrument sites. Much of this area has been masked out (indicated by hatching), because the objectively estimated error field is high. However, one of the main purposes for using the OA method is to estimate the field throughout a broader geographic region extending beyond the IES sites. Hence, we wish to test how well the OA method works in the extrapolated but low-estimatederror region. Additionally, the interpolated areas are affected to some extent by these extrapolated fields. Therefore, we examine the full region of low estimated error. In the following discussions, we describe some of these differences, which result from the different mean fields.

As mentioned above, the usage of the Z_I can result in an overestimation ('overshoot') of the thermocline depth. Whereas the overshoot occurs in the extrapolated area of the densely sampled AXET map (A5I in Figure 3.4), it also occurs within the interpolated region of the IES map (I5I in Figure 3.5), where there was a large distance separating the instrument sites. Although the loss of one IES in the middle of the array appears to be an important factor in the occurrence of the overshoot, WT85 observed similar overshoot3 during February 1984 with a full array of instruments. In I5I, the overshoot appears as an isolated pool of deep water. The Gulf Stream path must deviate around this pool in order for the output map to agree with the input measurements. Except for these overshoots, the extrapolated areas

appear to be typical of the Gulf Stream region, even resolving the nearby rings.

A characteristic of the OA method is that the estimated output field, away from the input measurements, will return to the mean field. Clear examples of this are the OA maps A4C, A5C, I4C, and I5C, produced using the constant mean field, $Z_{\rm C}$. The contours of constant 12°C isotherm depth thus form unrealistic closed features in the thermal structure. These isolated pools are pronounced along the northern edge of the mapped region in I5I (Figure 3.5). The thermocline depth is grossly underestimated on the offshore side of the Gulf Stream. Additionally, the cold-core Gulf Stream ring is not resolved in the maps for 12 June (A4C and I4C). As a result, the usefulness of the OA maps produced using $Z_{\rm C}$ is limited because the accurate region of extrapolation is minimal.

The OA maps A4T, A5T, I4T, and I5T produced using the temporal mean field, Z_T , appear to give the most accurate representation of the true temperature structure. Neither the overshoots nor the closed thermal features introduced by Z_I and Z_C are present in these maps. [However, the OA maps shown in Tracey and Watts (1986b) for February 1984 do show some smaller-scale (≤ 100 m) overshoots.] Also, the thermocline asymptotically reaches reasonable depths in the extrapolated regions.

3.2.3 Internal consistency

The comparisons of the AXBT OA maps, evaluated at all the observation sites, with the actual observations at those sites are given in Table 3.2. Similar comparisons are reported in Table 3.3 for the IES OA maps.

Regardless of which mean field was used, the agreements between the estimated and observed values are good. (Recall that since smoothing is

OBS-OA	Range*	Mean**	RMS†	NPTS++
OBS-A4I	57	0	12	61
OBS-A4C	79	0	16	61
OBS-A4T	46	-1	11	61
OBS-A5I	102	-1	15	73
OBS-A5C	60	0	11	73
OBS-A5T	53	0	10	73

Table 3.2AXBT OA Maps Evaluated at AXBT Sitesfor the Three Choices of Mean Fields

* Range =
$$\max(Z_{OBS} - Z_{OA}) - \min(Z_{OBS} - Z_{OA})$$

** Mean =
$$\frac{\sum (Z_{OBS} - Z_{OA})}{NPTS}$$

+ RMS =
$$\frac{\sum (Z - Z)^{2}}{OBS OA}$$

NPTS] 1/2

†† NPTS = Number of comparison points

Table 3.3	IES	OA Mag	os Evalua	ated	at	IES	Sites	for
	the	Three	Choices	of I	Mean	Fie	elds#	

OBS-OA	Range	Mean	RMS	NPTS
OBS-141	26	2		15
OBS-I4C	43	-3	10	15
OBS-I4T	32	2	8	15
0 BS- 151	49	-3	10	18
0 BS- 15C	82	-5	8	18
OBS-I5T	26	1	7	18

* Parameters defined as in Table 3.2

•

permitted, the estimated values need not agree exactly with the measurements.) The RMS differences of ≤ 15 m are comparable in size to the measurement errors of the instrumentation.

The best agreements between OA maps and observations (RMS 7-11 m) are obtained with the maps produced using the temporal mean thermocline field, $Z_{\rm T}$. For both AXBT and IES measurements on both survey dates, the instantaneous and constant thermocline fields, $Z_{\rm I}$ and $Z_{\rm C}$, produced OA maps with slightly greater range and RMS differences. Hence the $Z_{\rm T}$ mean field gives the best internal consistency.

3.2.4 Comparison of the AXBT OA maps

The three AXBT OA maps for each day are compared in Table 3.4. Differences are calculated at all mapped grid points within the 15% estimated error contour. Within this expanded region, interpolated and extrapolated from the measurement sites, the range and standard deviation (STD) are roughly 2 to 4 times greater than the range and RMS listed in Table 3.2, which were at the measurement sites only. (The RMS is the same as the STD in the earlier case, where the mean difference was essentially zero.) The largest differences generally occur at the outer boundary of the extrapolated field.

The maps produced using Z_T and Z_C are the most similar in that the range and STD values are the smallest. For these two AXBT surveys, the signs of the mean differences are negative, indicating that maps produced using Z_I are slightly deeper than the others. These results confirm the visual impressions of these maps, in which the thermocline slope appeared much steeper when Z_I was used. (However, mean differences less than about STD/5, or ~10 m, are not statistically significant.) When the Gulf Stream was located to the north (survey 5), the STD values of about 60 m are double those obtained when it flowed

OA2-OA1	Range*	Mean**	RMS†	STD ++	NPTS®
A4C-A4I	192	-7	33	32	152
A4T-A4I	151	-4	25	25	152
A4T-A4C	109	3	15	15	152
A5C-A5I	399	-11	64	63	159
AST-ASI	392	-10	61	60	159
A5T-A5C	97	1	16	16	159
* Kange = 1	$\frac{\sum_{OA_2} - \sum_{OA_2}}{\sum_{OA_2} - \sum_{OA_3}}$	$(A_1) - \min(1)$	^z oa _z - ^z oa	,) 1	
† RMS =	$\Sigma(z - z)$ OA, OA, NPTS)*]1/2			
†† RES = [(RMS) ² - (MEA	N)"] ^{1/2}			

Table 3.4Differences Between AXBT OA Maps GeneratedUsing Three Choices of Mean Fields

⁰ NPTS = Number of comparison points

Table	3.5	Differences	Between	IES OA	Maps	Generated
		Using Three	Choices	of Mear	Fie:	lds*

0A2-0A1	Range	Mean	RMS	STD	NPTS
I4C-I4I	235	5	33	33	180
I4T-I4I	154	-3	29	28	180
14T-14C	95	-9	22	20	180
15C-151	413	-4	67	66	177
I5T-I5I	368	-20	60	56	177
15T-15C	137	-16	28	23	177

* Parameters defined in Table 3.4

•
through the middle of the mapping region (survey 4). These larger differences for maps produced using Z_I are the result of an overshoot in estimating the thermocline depth on the southern side of the Gulf Stream.

3.2.5 Comparison of the IES OA maps

The IES OA maps for each day are compared in Table 3.5, at all grid points within the region where the estimated error is <15%. The results of these comparisons are very similar to those obtained for the AXBT OA maps in Section 3.2.4. Generally the maps produced using Z_T and Z_C are the most similar, whereas those produced using Z_C and Z_I are the most different. For each survey the range of the differences between Z_T and Z_T is more than double the range of the Z_T and Z_C differences.

3.2.6 Intercomparison of the AXBT and IES OA maps

The AXET and IES OA maps, produced using identical mean fields, are compared in Table 3.6. Differences were calculated at all grid points within the intersection of their regions of estimated error <15%. The maps produced using Z_T consistently have the smallest ranges and STD values, indicating that they are the most similar. When the Gulf Stream flowed through the middle of the mapping region (survey 4), the largest differences between the maps were obtained using Z_C . However, when the Gulf Stream was far to the north (survey 5), the overshoots, obtained using Z_I , produced even bigger discrepancies between the AXET OA and IES OA maps.

3.3 Standard Deviation Field Selection

3.3.1 Description of the test

The observed standard deviations (σ) of the IES Z₁₂ measurements varied systematically, depending on the proximity of the instrument sites to the mean Gulf Stream location. Higher variance was located

0A ₂ -0A ₁	Range	Mean	RMS	STD	NPTS
A4I-I4I	228	12	37	37	100
A4C-I4C	232	0	50	50	100
A4T-I4T	195	8	36	35	100
A5I-I5I	343	-5	59	58	100
A5C-15C	220	-31	54	44	100
A5T-15T	149	-15	42	39	100

Table 3.6 Intercomparisons of the AXBT OA and IES OA Maps Using Three Choices of Mean Fields*

* Parameters defined in Table 3.4

ł

near the mean Gulf Stream center as a result of the steep thermocline slope in that region. Lower values were found both to the north and to the south, where the thermocline slope was reduced.

We represented the observed standard deviations with two different approximations. Both of these were defined as functions of the mean field depth; thus, each had to be applied to the data with its associated mean field. The first of these, $\sigma_{\rm T}$, was described by a Gaussian function of the form:

$$\sigma_{T}(x,y) = A + B \exp \left[\frac{Z_{T}(x,y) - Z_{e}}{C}\right]^{2}$$

where A is 50 m, B is (200 m - A), $Z_T(x,y)$ is the temporal mean thermocline depth at location (x,y), Z_{\bullet} is 470 m, and C is 200 m. This function was chosen to be representative of all the IES records obtained in the Gulf Stream. For the second approximation, we chose the same functional form used by WT85 in which the field σ_I was taken to be the first derivative of the mean field Z_I , scaled to agree in magnitude with the observed values. Both σ_T and σ_I are shown in Figure 3.6 in plan view.

Since $\sigma_{\rm T}$ and $\sigma_{\rm I}$ are functions of the mean field depths, it was difficult to define a test that could adequately determine the robustness of the OA method to their selection only. Thus, in order to assess the effects of σ variations, we defined a third, very different, constant standard deviation field, $\sigma_{\rm CS} = 100$ m, to be independent of the mean depth. Objective maps of the AXBT and IES data were then prepared using the temporal mean field, $Z_{\rm T}$, and either $\sigma_{\rm T}$ or $\sigma_{\rm CS}$.

3.3.2 Description of the AXBT and IES OA maps

The AXBT and IES OA maps for survey 4 (12 June 1984) are shown in Figure 3.7. The corresponding maps for survey 5 (17 October 1984) are



Instantaneous



Figure 3.6 The temporal standard deviation field, $\sigma_{\rm T}$ (top), and the instantaneous standard deviation field, $\sigma_{\rm T}$ (bottom), are shown in plan view. The contour interval is 25 m, with the dashed contours indicating standard deviations of less than 150 m RMS.



1

temporal (A4T and I4T) and constant (A4CS and I4CS). Contours and hatching are Figure 3.7 AXBT (left) and IES (right) OA maps for survey 4 (12 June 1984), produced using two different standard deviation fields: temporal (A4T and 14T) and constant (A4CS and 14CS). Contours and hatching at the same as in Figure 3.2. shown in Figure 3.8. Each figure displays the maps produced using the two σ field choices.

Unlike the maps produced with the different mean field selections (Figure 3.3-5), the overall impression of the corresponding OA maps for the two surveys (Figures 3.7-8) is that they are very similar. The distinctions between them occur primarily in the small-scale features, such as the smoothness of the Z_{12} contours and the presence or absence of isolated pools of water.

The slope of the thermocline tends to be more linear in the maps produced using $\sigma_{\rm CS}$ (OA maps A4CS, A5CS, I4CS, and I5CS in Figures 3.7 and 3.8), as seen from the more uniform spacing of their Z₁₂ contours. The linearity is most apparent along the upper edges of the mapping regions. For example, a comparison of the IES OA maps for survey 5 (Figure 3.8) reveals that the thermocline in I5CS is shallower than that in I5T when the depth is less than 300 m. Conversely, the thermocline in I5T is shallower for depths greater than 300 m.

3.3.3 Internal consistency

The AXBT OA maps evaluated at the AXBT sites are compared with the AXBT observations themselves in Table 3.7. The corresponding values for the IES OA maps and IES observations are listed in Table 3.8.

The estimated and observed values agree very well, with RMS differences of about 10 m. This is true no matter which standard deviation field was used. The range and RMS values for the AXBT comparisons are larger than those for the IES comparisons; however, this discrepancy is probably due to the fact that four times as many AXBT sites as IES sites were evaluated.



OBS-OA	Range	Mean	RMS	NPTS
OBS-A4CS	63	0	14	61
OBS-A4T	46	-1	11	61
OBS-A5CS	49	0	10	73
O BS-A5T	53	0	10	73

Table 3.7 AXBT OA Maps Evaluated at AXBT sites for Two Choices of Standard Deviation Fields*

* Parameters defined in Table 3.2

Table	3.8	IES	0A	Maps	Eva	aluated	at	IES	sites	for	
		Two	Cho	pices	of	Standar	rd I	Devia	ition	Field	is*

0 BS -0 A	Range	Mean	RMS	NPTS
OBS-14CS	37	3	9	15
OBS-14T	32	2	8	15
OBS-15CS	27	1	6	18
OBS-15T	26	1	7	18

* Parameters defined in Table 3.2

A

· * - - -

3.3.4 Comparison of the AXBT OA maps

The AXET OA maps produced for each day are compared in Table 3.9a. The STD differences between the maps produced using $\sigma_{\rm T}$ and $\sigma_{\rm CS}$ are small (13 m), indicating that the maps are quite similar. The ranges (56 and 92 m, respectively) are roughly factors of two to four times smaller than those encountered when the mean field was varied (Table 3.4). This implies that the OA method is not as sensitive to the σ field selection as it is to the choice of mean field.

The biggest differences occur in the upper left portion of the mapped region, where the station spacing is somewhat larger (Figures 3.7 and 3.8). Typically, the thermocline depths there are slightly shallower for the maps produced using σ_c .

3.3.5 Comparison of the IES OA maps

Table 3.9b lists the differences between the IES OA maps produced using the two σ field choices. There is good agreement between the output maps since the STD values are not very large (less than 15 m). Additionally, the STD and range values are considerably less than those obtained with variations in the mean field (cf. IST-ISI in Table 3.5).

The statistics in Table 3.9 indicate that there are bigger differences between the maps for survey 4 than between those for survey 5. Maps I4CS and I4T (Figure 3.7) differ primarily along the northern edge of the region.

3.3.6 Intercomparison of the AXBT and IES OA maps

The AXBT and IES OA maps, produced using the same standard deviation fields, are compared in Table 3.10. The maps produced using $\sigma_{\rm T}$ tend to have slightly smaller STD and range values, indicating that they are more similar than the maps using $\sigma_{\rm CS}$. However, since the values for $\sigma_{\rm CS}$

OA ₂ -OA ₁	Range	Mean	RMS	STD	NPTS
a) AXBT OA	Maps				
A4T-A4CS A5T-A5CS	56 92	-1 -2	13 13	13 13	152 159
b) IES OA	Maps				
14T-14CS 15T-15CS	88 92	5 -3	15 11	14 10	180 177

Table 3.9Differences Between OA Maps Generated Using
Two Choices of Standard Deviation Fields*

* Parameters defined in Table 3.4

Table 3.10 Intercomparisons of the AXBT and IES OA Maps Using Two Choices of Standard Deviation Fields*

0A2-0A1	Range	Mean	RMS	STD	NPTS
A4CS-14CS	254	-19	47	43	100
A4T-14T	195	8	36	35	100
A5CS-15CS	158	-11	40	39	100
A5T-15T	149	-15	42	39	100

* Parameters defined in Table 3.4

•

are not substantially different, the OA method is apparently not very sensitive to the choice of standard deviation field.

Since the standard deviation field is used to normalize the data prior to applying the OA method (and also to renormalize afterwards), the regions that have the largest perturbations are most affected by the choice of σ . Typically, large perturbations occur either when the output map differs substantially from the mean field or in the extrapolated portions of the output map. For example, in survey 4 (Figure 3.7), the Gulf Stream followed a relatively straight path through the center of the IES array, whereas the mean field (Z_T in Figure 3.1) was arched. Hence, the resulting perturbations are large. As can be seen in Figure 3.7, the thermocline depth in the OA maps from the IES data is shallower where it is extrapolated to the upper edge of the mapped region than it is for the AXBT data, where the survey was centered. This difference is slightly exaggerated for the maps produced using σ_{CS} .

3.4 Correlation Function Selection

3.4.1 Description of the test

Three space-time correlation functions (ρ) were selected for this test of the OA method. Two of these were presented in WT85 and the third was adapted from the autocorrelations given in Halliwell and Mooers (1983).

WT85 determined an empirical correlation function $(\rho_{\rm EMP})$ from the set of Gulf Stream IES measurements made between 1979 and 1984. A complete explanation of the method used to calculate $\rho_{\rm EMP}$ is given in the Appendix of this report. Briefly, the instruments were grouped into cross-stream, along-stream, and diagonal pairs and the correlations of each group were calculated separately. The correlation function at zero

time lag was found to be isotropic. Figure 3.9 shows $\rho_{\rm EMP}$ in plan view for time lags out to 4 days.

The observed correlations were also approximated by an analytic function of the form:

 $\rho_{\rm WT} = F_0 \exp(-t^*/T_0) \exp(-r/A) \cos(\pi r/2B)$ where $F_0 = 1.0$, t' is the lag time, $T_0 = 9.3$ days, $r^z = (x^*-ct^*)^z + y^{*2}$, x' and y' are the spatial separations, c = 12 km/day, A = 391 km, and B = 171 km. This function was chosen such that the temporal decay rate of the central peak was similar to the observed values and that the spatial decay rate was the same as that observed for zero time lag. Figure 3.9 shows $\rho_{\rm WT}$ in plan view for the same time lags as for $\rho_{\rm EMP}$.

For the third correlation function, we selected one that was determined independently of our data, yet was still appropriate for the Gulf Stream region. Halliwell and Mooers (1983) presented space-time correlations for propagating meanders that were calculated from measurements of the Gulf Stream surface thermal front. We assigned to the function $\rho_{\rm HM}$ the same analytic form as $\rho_{\rm WT}$ but specified the parameters from those given in Halliwell and Mooers (1983). The function $\rho_{\rm HM}$, shown in Figure 3.9. results from defining $F_{\rm O} = 0.8$, $T_{\rm O} =$ 18.3 days, c = 7 km/day, A = 300 km, and B = 125 km.

For the previous tests of the OA method (Sections 3.2 and 3.3), we limited the OA map comparisons to include only those grid points for which the estimated errors were <15%. However, larger estimated error fields (described below) are produced for $\rho_{\rm EMP}$ and $\rho_{\rm HM}$; consequently, the number of grid points lying within this specified error limit is reduced. Thus, for this test, we extended our comparisons to include grid points with estimated errors of <35%. All hatched regions (shaded



Figure 3.9 Three correlation functions, ρ_{WP} (left), ρ_{WT} (center), and ρ_{HP} (right), contoured in plan view for time lags of 0, 2, and 4 d. For negative time lags, note that ρ 1s 1mplicitly given by the symmetry relation $\rho(-x, -y, -t) = \rho(x, y, t)$. The contour interval 1s 0.1 and negative contours are dashed. Areas with hatching indicate $\rho \ge 0.7$; dotted areas indicate 0.7 $\ge \rho \ge 0.4$.

by a single set of parallel lines) in Figures 3.10-13 have errors $\geq 15\%$; the crosshatching indicates that the errors exceed 35%.

3.4.2 Description of the AXBT and IES OA maps

The AXBT and IES OA maps for survey 4 (12 June) are shown in Figures 3.10 and 3.11, respectively. The corresponding maps for survey 5 (17 October) are shown in Figure 3.12 and 3.13. Each figure displays the three maps produced using the three different choices of ρ .

The most striking feature of the maps is the difference in the sizes of the two estimated error fields. The error fields for maps A4HM, A5HM, I4HM, and I5HM, all produced using $\rho_{\rm HM}$, are the largest, with errors greater than 15% predicted throughout the entire mapping region. The error fields associated with $\rho_{\rm EMP}$ and $\rho_{\rm WT}$ are the most similar in size, yet the differences between them are apparent in the IES OA maps (Figure 3.11 and 3.13), where the spacing between instruments sites is coarser. The smallest estimated error fields are obtained with $\rho_{\rm WT}$.

The large estimated error fields associated with $\rho_{\rm HM}$ are to be expected because the central peak of $\rho_{\rm HM}$ at zero time lag reaches only 0.8. Additionally, both the faster spatial decay rate and the slower temporal decay rate of the central peak may contribute to the larger errors, particularly for the sparse spatial and dense temporal sampling from the IES array.

One reason that $\rho_{\rm EMP}$ is associated with a larger error field than $\rho_{\rm WT}$ is that the shape of $\rho_{\rm EMP}$ is not as smooth as that of the analytic function (Figure 3.9). Another reason is that the central peak of $\rho_{\rm EMP}$ broadens at greater time lags (Figure 3.9). Thus, the input data would appear to be less independent to the OA method, resulting in a larger estimated error field.



Figure 3.10 AXBT OA maps for survey 4 (12 June 1984), produced using three different correlation functions: $\rho_{\rm WT}$ (A4T), $\rho_{\rm EMP}$ (A4EMP), and $\rho_{\rm HM}$ (A4HM). Areas with hatching correspond to regions of $\geq 15\%$ estimated error and the crosshatching designates areas where the estimated errors exceed 35%. Z₁₂ contours and contour interval are the same as in Figure 3.2.





ł

۰.



.....

Figure 3.12 AXET OA maps as in Figure 3.10 except for survey 5 (17 October 1984).



Figure 3.13 IES OA maps as in Figure 3.11 except for survey 5 (17 October 1984).

The rest of this report uses $\rho_{\rm WT}$ as the standard correlation function because it was an analytic function with good qualities (i.e., positive definite correlation matrix) that was a close fit to data from the same type of instruments in the same geographic region. Tests against independent data in Section 4 confirm that the error fields generated from $\rho_{\rm wr}$ produce good estimates of the true errors.

Aside from the estimated error fields, the OA maps of the Z_{12} field produced with the different ρ choices look very similar. The biggest differences occur along the upper edges of the mapped regions in Figures 3.10-13. Another distinction between the output maps in Figure 3.11 is the shape of the cold-core eddy entering the area at the southwest. In I4EMP, the shape is almost rectangular, extending about 265 km along stream and only about 60 km cross stream. However, in I4HM, the eddy is more circular, with a length-to-width ratio of nearly 1. The Z_{12} field in that corner is mapped mainly from the two southernmost IESs, and the differences between the maps arise from the propagation characteristics of the different ρ fields.

3.4.3 Internal consistency

Table 3.11 lists the comparisons between the AXBT OA maps and the input measurements. Similar comparisons are reported in Table 3.12 for the IES OA maps. The resulting errors at all the input sites were small despite the differences in the sizes of the error fields. The number of input points (NPTS) compared remained the same for the three choices of correlation function.

As was seen in Figure 3.9 and Section 3.4.1, the correlation function $\rho_{\rm HM}$ is smaller than either $\rho_{\rm EMP}$ or $\rho_{\rm WT}$; this results in less smoothing in the objective analyses. The input data that are far away, both spatially and temporally, from the output grid point do not

OBS-OA	Range	Mean	RMS	NPTS
OBS-A4HM	21	-1	5	61
OBS-A4EMP	40	-1	9	61
OBS-A4T	46	-1	11	61
OBS-A5HM	22	0	4	73
OBS-A5EMP	43	0	8	73
OBS-A5T	53	0	10	73

Table 3.11 AXBT OA Maps Evaluated at AXBT sites for Three Choices of Correlation Functions*

* Parameters defined in Table 3.2

Table 3.12 IES OA Maps Evaluated at IES sites for Three Choices of Correlation Functions*

OBS-OA	Range	Mean	RMS	NPTS
OBS-14HM	16	0	4	15
OBS-I4EMP	26	-1	7	15
OBS-I4T	32	2	8	15
OBS-15HM	10	o	3	18
OBS-15EMP	28	2	7	18
OBS-15T	26	ī	7	18

* Parameters defined in Table 3.2

contribute significantly to the estimation at that point. Thus, the best agreements between the OA maps and the observations are obtained with the maps produced using $\rho_{\rm HM}$. However, since all the RMS values in Tables 3.11 and 3.12 are less than 11 m, there is good agreement between the estimated and observed Z_{12} values regardless of the choice of correlation function.

3.4.4 Comparison of the AXBT OA maps

Since the estimated error fields associated with $\rho_{\rm HM}$ exceeded 15%, only the AXBT OA maps produced with $\rho_{\rm WT}$ and $\rho_{\rm EMP}$ are compared in Table 3.13a for that error level. However, the three AXBT OA maps for each day are compared in Table 3.13b for all output grid points within the 35% estimated error regions.

At the 35% level, the STD values are small, about 12 m, indicating that the output maps of Z_{is} are not strongly affected by the choice of correlation function. These STD values are smaller than those in Table 3.4, suggesting that the output maps are influenced more by the choice of mean field than by ρ .

Although the range and STD values at the 35% error level for A5T-A5EMP are the largest, the number of grid points (NPTS) used for the comparisons is almost double those of the other two comparisons. For the map comparisons for survey 4, the NPTS for A4T-A4EMP is 50% larger than the others, yet the range and STD values are of comparable size. Thus, the fields generated from $\rho_{\rm WT}$ and $\rho_{\rm EMP}$ are the most similar, and the biggest differences occur between those produced with $\rho_{\rm EMP}$ and $\rho_{\rm HM}$.

3.4.5 Comparison of the IES OA maps

The comparisons of the IES OA maps for each day are given in Table 3.14. As described above for the AXBT OA maps, the IES OA maps produced using $\rho_{\rm HM}$ could not be evaluated at the 15% level due to their large

Range	Mean	RMS	STD	NPTS
son of regio	ons of less	than 15% ei	ror	
57	0	8	8	137
98	-1	12	12	135
on of region	ns of less t	han 35% eri	ror	
66	-1	11	11	122
60	-1	11	11	122
72	1	10	10	185
75	2	13	13	108
		٩	٩	108
56	1	,	,	
	son of region 57 98 on of region 66 60 72	kange near son of regions of less 57 0 98 -1 on of regions of less t 66 -1 60 -1 72 1	$\frac{1}{57} \qquad 0 \qquad 8$ $98 \qquad -1 \qquad 12$ on of regions of less than 35% err $66 \qquad -1 \qquad 11$ $60 \qquad -1 \qquad 11$ $72 \qquad 1 \qquad 10$	kinge heat kins Site son of regions of less than 15% error 57 0 8 8 98 -1 12 12 12 on of regions of less than 35% error 66 -1 11 11 60 -1 11 11 10 10 72 1 10 10 12 12

Table 3.13 Differences Between AXBT OA Maps Generated Using Three Choices of Correlation Functions*

Using Three Choices of Correlation Functions*

0A ₂ -0A ₁	Range	Mean	RMS	STD	NPTS
a) Comparison	of regions	of less	than 15% err	or	
I4T-I4EMP	180	5	27	27	88
I5T-I5EMP	78	1	14	14	94
b) Comparison	of regions	of less	than 35% err	or	
I4EMP-I4HM	47	11	31	29	123
I4T-I4HM	71	5	13	12	123
I4T-I4EMP	214	3	25	25	237
I5EMP-I5HM	44	2	13	13	121
IST-I5HM	72	0	10	10	121
IST-ISEMP	118	0	17	17	227

* Parameters defined in Table 3.4

error fields. At the 35% error level, the STD differences range from 10-29 m. These are smaller than those given in Table 3.5 for the mean field selection, indicating that the choice for ρ is not as critical.

The smallest STD values were obtained for the comparisons of IES OA maps produced using $\rho_{\rm WT}$ and $\rho_{\rm HM}$; thus, these maps are the most similar.

3.4.6 Intercomparison of the AXET and IES OA maps

The differences between the sizes of the error fields result in large differences in the number of grid points available for the AXBT OA and IES OA map comparisons (Table 3.15). At the 15% error limit, the full mapped areas produced by $\rho_{\rm HM}$ were excluded. Also, twice as many grid points were used for the maps produced from $\rho_{\rm WT}$ as for those maps produced using $\rho_{\rm EMP}$. Even at the 35% error level, there is a large difference in NPTS for all three different choices of correlation function.

At both error levels, the RMS, STD and range values for $\rho_{\rm WT}$ are roughly as good as or better than the values for the other two ρ choices. Thus, $\rho_{\rm WT}$ maps a larger region with less error. Although the RMS differences at the 35% error level for $\rho_{\rm WT}$ and $\rho_{\rm EMP}$ are also comparable in size to those obtained for the mean field selection (Table 3.6), the mapping areas being compared are substantially greater.

3.5 Decimation Time Selection

3.5.1 Description of the test

Observations from N input points are used to estimate the value at a single output grid point. They are selected from the input data based on their correlations (ρ). Those with the highest ρ are chosen since they result in the smallest estimated errors for the output value. Higher correlations are obtained for the data with the smallest separation distances, either spatial or temporal, from the output grid

OA ₂ -OA ₁	Range	Mean	RMS	STD	NPTS
a) Intercomp	arison of	regions of	less than	15% error	
A4EMP-14EMP	228	16	53	50	42
A4T-I4T	195	8	36	35	100
A5EMP-I5EMP	123	-1	32	32	50
A5T-15T	149	-15	42	39	100
b) Intercomp	arison of	regions of	less than	35% error	
A4HM-I4HM	224	4	31	31	85
A4EMP-I4EMP	350	6	50	50	153
A4T-I4T	278	l	44	44	180
A5HM-15HM	156	-12	40	38	49
A5EMP-I5EMP	186	-10	43	42	162
A5T-I5T	197	-12	45	43	188

Table 3.15Intercomparisons of the AXBT and IES OA MapsUsing Three Choices of Correlation Functions*

* Parameters defined in Table 3.4

points (Figure 3.9). However, these observations are also correlated with each other, and hence do not contribute completely independent degrees of freedom to the estimates at the output grid points (i.e., the error estimates must be larger). Thus, a balance must be obtained in which the input data are separated far enough from each other to be relatively independent, yet not so far from the output point that they no longer supply adequate information for estimating its value.

In this test of the OA method, we assess the importance of the choice of separation time. Because the IES data consist of time series of daily Z_{12} measurements at fixed locations, we can test the effects of temporal separation by subsampling at different intervals. For this test, we chose decimation times (δ t) of 1, 4, and 8 d in addition to the 2 d interval used to produce the standard maps. The IES output maps are compared to the standard AXBT OA maps for which all the sampling occurred within a few hours on one flight. (Since the AXBT surveys were intermittent, no corresponding test could be conducted for those data.)

In conjunction with the δt variations, it was also necessary to adjust the number of input values (N) and the maximum time lag (T). In order to determine the most appropriate values, we tested several different combinations of N and T with each choice of δt . We chose the maximum N for a given T for which the OA mapping, which depends upon inverting the matrix of correlations, remained stable. If the determinant of this matrix becomes too small, the matrix is singular and the mapping quality would become poor. For the maps produced using the longer decimation times (4 and 8 d), T was changed from ± 4 d to ± 8 d. Additionally, for maps I48D and I58D, N was increased to eleven points. For the maps produced using $\delta t = 1$ d, N was reduced to seven and T was changed to ± 1 d. These selections are summarized in Table 3.1.

3.5.2 Description of the IES OA maps

The IES OA maps for survey 4 (12 June) produced with the four choices of δt are shown in Figure 3.14. Those for survey 5 (17 October) are displayed in Figure 3.15. In general, the output maps are very similar. The major features, such as the cold-core ring (Figure 3.14) and the shape of the Gulf Stream path, are resolved in all of the maps.

The maps differ from one another, however, in that the contours of Z_{12} become progressively smoother as δt increases. For example, the fine-scale structure is more evident in I51D, produced using $\delta t = 1$ d, than in I58D, where $\delta t = 8$ d. The size of the cold-core eddy (Figure 3.14) is also affected by the choice of δt . The eddy appears almost circular in I41D, with a radius of about 100 km. As δt increases, the dimensions of the eddy enlarge. In maps I4T and I44D, the eddy extends 280 km downstream and 200 m in depth. In I48D, the increased smoothing diffuses the cross-stream thermal gradients. Thus, fewer Z_{12} contours close and the eddy actually appears smaller.

As in the test of the correlation function selection (Section 3.4), the most obvious differences between these maps occur with their estimated errors. However, the differences between the sizes of the error fields are not as great all chose obtained in that previous methodology test. The smallest error fields are associated with the standard maps, I4T and I5T, for which $\delta t = 2$ d. The largest errors are obtained when $\delta t = 8$ d. The two intermediate error fields, associated with maps produced using $\delta t = 1$ d (I41D and I51D) and $\delta t = 4$ d (I44D and I54D), are comparable in size.

3.5.3 Internal consistency

Table 3.16 lists the comparisons between the actual observations and the estimated outputs of the IES OA maps evaluated at the measurement





Figure 3.15 IES OA maps as in Figure 3.14 except for survey 5 (17 October 1984).

OBS-OA	Range	Mean	RMS	NPTS
	26			·····
085-141D	26	1	/	15
OBS-I4T	32	2	8	15
OBS-I44D	47	0	12	15
OBS-I48D	48	0	12	15
OBS-I51D	18	1	5	18
OBS-I5T	26	1	7	18
0 BS- 154D	23	2	7	18
OBS-158D	35	2	10	18

Table 3.16	IES	OA Ma	aps Eval	uate	d at	IES S	ites
	for	Four	Choices	of	Decin	ation	Times*

* Parameters defined in Table 3.2

Table 3.17 Differences Between IES OA Maps Generated Using Four Choices of Decimation Times*

OA2-OA1	Range	Mean	rms	STD	NPTS
 14T-141D 14T-144D	105	-4 1	18	18	150
14T-148D	73	-1	16	15	92
15T-151D 15T-154D 15T-158D	47 47 72	0 1 2	8 9 16	8 9 15	158 166 146

* Parameters defined in Table 3.4

....

sites. As expected, both the range and RMS values increase as δt becomes larger; the comparisons of instantaneous observations with estimated outputs should worsen as more and more averaging is done. For $\delta t = 1$ d, the range (18-26 m) and RMS (5-7 m) of the differences are smaller than those obtained for any of the previous tests of the OA methodology. The corresponding values for the remaining three δt selections are also among the smallest. Thus, there is excellent agreement between the observed and the estimated values for all the decimation intervals.

3.5.4 Comparison of the IES OA maps

The IES OA maps for both surveys are compared in Table 3.17. The STD values (8-18 m) are small and nearly uniform. However, the standard maps (I4T and I5T) and those produced using $\delta t = 4$ d are the most similar in that the STD values are consistently smaller.

Additionally, the range and STD values in Table 3.17 are also among the smallest obtained for any of the OA methodology tests. Thus the choice of δt does not strongly affect the estimated output maps. However, it is important to note that this type of comparison does not reveal if there has been a loss of high-frequency signals, which may be of scientific interest, as δt increases. Because the best agreement with the observations is obtained for the maps produced using $\delta t = 1$ d, there is an indication of some signal loss at the larger decimation intervals.

3.5.5 Intercomparison of the AXBT and IES OA maps

Table 3.18 compares the IES OA maps with the standard AXBT OA maps (Figures 3.10 and 3.12) for the same survey dates. The range and STD are essentially the same for all comparisons, indicating that there is

$OA_2 - OA_1$	Range	Mean	RMS	STD	NPTS
A4T-I41D	159	8	32	31	87
A4T-I4T	195	8	36	35	100
A4T-144D	183	8	32	31	74
A4T-148D	132	6	32	31	41
A5T-151D	158	-18	43	39	91
A5T-15T	149	-15	42	39	100
A5T-154D	149	-11	40	39	92
A5T-158D	155	-13	42	40	82

- - ----

Table 3.18 Intercomparisons of the AXBT and IES CA Maps Using Four Choices of Decimation Times*

* Parameters defined in Table 3.4

-

 \mathbf{x}

very little difference between the IES OA maps generated with different decimation times.

The differences in the sizes of the error fields result in a wide range in the number of grid points used in the intercomparisons. NPTS ranges from ~40 for I48D to 100 for the standard maps. Since it is desirable to map accurately the largest area possible, decimation times of either 1 d or 2 d appear to be good choices.

3.6 Summary of Results

We have examined the robustness of the objective mapping technique to the choices of four control parameters: (a) the mean field, (b) the standard deviation field, (c) the correlation function, and (d) the decimation time. Output maps of both IES and AXBT data were produced by varying just one of these control parameters at a time, keeping all others the same.

For each test, we checked the internal consistency of the output maps by evaluating them at all the observation sites and comparing them with the actual observations at those sites. In all cases, the RMS differences were ≤ 15 m, which are comparable to the measurement errors of the instrumentation. Thus, the output maps agreed well with the observations, regardless of the choice of control parameter.

The OA mapping technique was most sensitive to the mean field selection. We produced output maps using: (a) a time-averaged mean field, (b) an instantaneous mean field, and (c) a constant mean field. Of these three, both the instantaneous and constant mean fields introduced unrealistic thermal structures (overshoots and circular features) to the extrapolated areas of the output maps, whereas the time-averaged mean field did not. Additionally, the IES OA maps produced using the temporal mean field gave the best internal

consistency (RMS differences of 8-10 m) and the best intercomparisons with the AXBT OA maps (STD differences of 35-40 m). Thus, the most accurate representation of the true temperature structure was obtained for the maps produced using the temporal mean field.

The choice of the space-time correlation function had the most pronounced effect on the estimated error fields associated with the output maps. The largest estimated error fields were obtained with the independently derived analytic function, $\rho_{\rm HM}$, based on surface observations of the Guli Stream thermal front (Halliwell and Mooers, 1983). The analytic function, $\rho_{\rm WT}$, based on four years of IES data from the same region of the Gulf Stream, gave the smallest error fields. The estimated error fields associated with the maps produced using an empirical function, $\rho_{\rm EMP}$, were intermediate between these other two. All of the AXBT and IES OA maps agreed well ($\leq 10 \text{ m RMS}$) with the observations, no matter which correlation function was used.

Intercomparisons of the AXBT OA and IES OA maps were made for two levels of estimated error (15 and 35%). Although fairly uniform RMS values (35-45 m) were obtained for all three correlation functions, the analytic function $\rho_{\rm WT}$ is considered to be the best choice because it mapped the largest area with the least error. Also, the error fields generated from $\rho_{\rm WT}$ were shown to produce good estimates of the true errors.

Since only slight changes in the thermocline slope were observed, variations in the standard deviation field selection produced virtually no differences between the output maps. Thus, the OA method is apparently not very sensitive to the choice of σ . We have chosen $\sigma_{\rm T}$ because it is most similar to the observed standard deviation field, and

ъÛ

should produce the most accurate output maps of the true thermocline depth field.

Variations in the selection of the decimation time, δt , produced only minor differences in the output maps of the thermocline depth field. The output maps prepared by varying δt gave the best agreement with the observations, with RMS differences as low as 5 m. Comparing the IES OA maps with the AXBT OA maps also gave small STD values (30-40 m). These values are considerably smaller than those when the mean field was varied (35-60 m STD).

The decimation time selection may be more critical than these results indicate, however. At larger δ t intervals, increased smoothing occurs, which may result in the loss of the high-frequency perturbations. Since there is little difference between the output maps of the thermocline depth field, it is desirable to choose δ t such that these fluctuations may be resolved. We have selected both δ t = 1 d (high temporal resolution) and δ t = 2 d ("standard") because smoothing is kept to a minimum. Also, the estimated errors associated with both of these selections are low; thus, the output Z₁₂ maps produced have the largest areas of accurate mapping.

61

SECTION 4. TESTS OF THE IES OA MAPS AGAINST INDEPENDENT DATA

4.1 General Information

4.1.1 Motivation for the test

The principal purpose of this section of the report is to compare the IES OA maps with independent but concurrent measurements of Z_{12} from XBTs and AXBTs. We examine the results of these comparisons in order to determine the accuracy of the mapped Z_{12} , fields.

Two cases are presented here. Two sets of OA maps have been produced, in which different amounts of temporal smoothing were used in calculating the output Z_{12} values. For case A, the OA maps were produced using the standard map parameters (in particular, the decimation time was $\delta t = 2$ d and the maximum time lag was $T = \pm 4$ d) described in Section 3 of this report. These same parameters were used to produce the OA maps shown in the data reports by Tracey and Watts (1986b), Tracey <u>et al</u>. (1985), and Friedlander <u>et al</u>. (1986). The second set of OA maps (case B) were produced with a higher temporal resolution ($\delta t = 1$ d and $T = \pm 1$ d) and, therefore, less averaging was performed. We compare XBT and AXBT Z_{12} values with both sets of maps to determine the map accuracy and to assess the effects of different amounts of temporal smoothing.

In addition to the daily maps of the Z_{12} field, estimated error fields were also produced daily by the OA technique. Each error field is a statistical measure (percent standard deviation) of how well the Z_{12} field has been estimated from the input data. Figure 4.1 (top) shows the case A (standard map parameters) error field for a representative date (19 January 1985). The mapped area corresponds to



Figure 4.1 The error fields (% standard deviation) on 19 January 1985 for two decimation times: case A (top; $\sigma t = 2$ d), with dashed contours indicating <15% error; and case B (bottom; $\sigma t = 1$ d), with dashed contours indicating <20% error. Contour intervals are 5%.
the boxed area of Figure 2.1. The estimated errors are low ($\leq 5\%$) near the IES measurement sites and increase with distance from those sites. Figure 4.1 (bottom) shows the error field, for the same date, associated with the Z₁₂ map produced using the higher temporal resolution parameters (case B). Note that the estimated errors are slightly larger for case B than case A.

The OA technique is used to estimate the Gulf Stream Z_{12} field over a large continuous area by extrapolating outside the IES array. The error fields have been used qualitatively to mask out extrapolated areas of the Z_{12} fields where the map quality is predicted to be poor. For example, WT85 subjectively chose to mask out all extrapolated regions where the errors were $\geq 15\%$. That error level was chosen because it combined low predicted errors with a large mapping area that extended beyond the instrument sites. We would now like to select, objectively, the largest area of accurate mapping by comparing the OA maps against independent measurements of the Z_{12} field. These comparisons are made first for the standard maps (Section 4.2) and then for the high temporal resolution maps (Section 4.3).

4.1.2 Distribution of the data

On five cruises in the study area during 1982 to 1985, a total of 402 XBTs were laken. Of these, XBTs taken outside the boxed region of Figure 2.1 were not used in this test. Additionally, XBTs were also excluded if they were located in regions where the water was either too warm or too cold to measure Z_{iz} . Finally, XBTs taken in the mapping region with \geq 35% error are excluded.

Thus, of the 402 XBTs taken over the three-year period, 295 of them were used in comparison with the standard IES OA maps. The locations of the XBTs used are shown in Figure 4.2, where the outer box is the same as



Figure 4.2 Locations of the 295 XBTs used, superimposed for all five cruises during the study period.

SITES OF XBTS

that outlined in Figure 2.1. Since the primary purpose of the XBT surveys was to calibrate the IESs, the XBT drop sites were concentrated near the instrument sites. Eighty-nine percent (262) of the 295 XBTs taken within the standard map (case A) region delineated by the 35% error limit also occurred within the region of $\leq 15\%$ error. In Figure 4.3a, the histograms show that the number of XBTs used in this test increased by eleven percent as the standard map estimated error increased from 15 to 35%.

For the high temporal resolution map (case B) comparisons, there were a total of 284 XBTs that satisfied the criteria. The histograms (Figure 4.3c) illustrate that the drop sites are concentrated near the IES sites, with eighty-six percent (245) of the XBTs falling within the map region delineated by the 15% error limit.

A total of 512 AXBTs were dropped on six flights between 1 June and 13 November 1984. Of these, 195 met the same criteria described above for the XBTs and were used in the standard map (case A) comparisons. For the high temporal resolution map (case B) comparisons, 164 AXBTs met the criteria. The probe drop-sites are shown in Figure 4.4.

The survey flights were centered on the Gulf Stream thermal front position; thus, they did not always coincide with the fixed IES array. During several of the survey flights, the Gulf Stream path was located to the north of the IES array due to the presence of a large-amplitude meander. The AXBT sites were also shifted northward, and were concentrated along the upper edge of the mapped region. Consequently, the AXBTs were more evenly distributed throughout the mapping regions delineated by the 10 to 35% error levels.

Of the 195 AXETs available for the standard map (case A) comparisons, 80 probes were in the region between the 15% and 35% error



Figure 4.3 The number of comparisons made at five levels of estimated error. For case A ($\sigma t = 2 d$), comparison is between IES OA maps and (a) XBTs for each cruise and (b) AXBTs for each flight. For case B ($\sigma t = 1 d$), comparison is between IES OA maps and (c) XBTs for each cruise and (d) AXBTs for each flight.

Ì



Figure 4.3, continued.

SITES OF AXBTS

		×	*	*	**************************************	*	×₩×	;
×	×x ¥×	₩ ₩	X	(W _X X	XXX	7 7 7	x X X	×
XX	X	% X	\$ ≵ ×	*	×	×	XXXX	×
ž	×	* × ×	×	×			× ×	*
x	×	×					×	×
	x	×						×
				·····				

Figure 4.4 Locations of the AXBT drop sites, superimposed for all six flights during the study period.

Ì

levels and 115 probes were in the region of $\leq 15\%$ error (Figure 4.3b). For the high temporal resolution map (case B) comparisons, 71 probes were in the region between 15% and 35% error levels and 93 probes were in the region of $\leq 15\%$ error (Figure 4.3d).

4.1.3 Description of the test

First, the depth of the 12°C isotherm was extracted from each of the XBTs and AXBTs. If temperature inversions (associated with lowersalinity Slope Water) resulted in the occurrence of more than one Z_{12} value, the deepest one was chosen.

Next, the estimated Z_{12} values were determined from the IES OA maps for the same locations as the probe drop sites. For any XBT or AXBT site not located at a grid point, the Z_{12} value was determined by linear interpolation. Since the IES OA maps were produced for 1200 GMT on each day from July 1982 to May 1985, the Z_{12} value was extracted from the map that was closest in time to the probe launch. For case A, the output maps for the three-year period were produced using the standard map parameters described in Section 3. For case B, the high temporal resolution maps were produced specifying $\delta t = 1$ d and $T = \pm 1$ d, retaining all other standard map parameters.

The estimated Z_{12} values from the IES OA maps were plotted against the observed XBT Z_{12} values from all five cruises. Two plots were produced, one for all XBTs occurring within the map region delineated by the 35% error level, and the other for only these XBTs within either the 15% error level (case A, standard maps) or 20% error level (case B, high temporal resolution maps).

The differences, ΔZ , between the Z₁₂ values from the IES OA maps and the XBTs were calculated as:

 $\Delta Z = (OA Z_{12}) - (XBT Z_{12})$

For each cruise, the mean and root-mean-square differences (RMS) of the number of comparisons (NPTS) were determined as:

mean =
$$\frac{\Sigma(\Delta Z)}{NPTS}$$

RMS = $\left[\frac{\Sigma(\Delta Z^2)}{NPTS}\right]^{1/2}$

The ΔZ differences were divided into groups, according to the locations of the XBTs within geographic regions delineated by five levels of OA map error. For this analysis, we used the 10, 15, 20, 25, and 35% error levels. Then the RMS differences of each group were calculated separately.

The mean and RMS calculations were repeated for the comparisons of the IES OA maps with the AXBTs. To determine ΔZ , the XBT Z_{12} values in the above equation were replaced with AXBT Z_{12} values.

Additionally, the navigation systems on the ship and aircraft are different. Thus, systematic offsets could occur in the locations of the AXET drop sites relative to the IES array location. These navigation offsets would differ from flight to flight. To determine if these offsets occurred on any of the six surveys, the standard deviations (STD) for all five error levels were calculated as:

 $STD = [(RMS)^{2} - (Mean)^{2}]^{1/2}$

If the position of the aircraft had actually been shifted to the north of the array, the Z_{12} values from the AXBTs would be shallower than those from the IESs and the mean ΔZ would be positive. Conversely, if the aircraft had been offset to the south, the mean ΔZ would be negative. To eliminate these biases, the mean ΔZ for each flight was removed from the Z_{12} values of the IES OA maps. These residual OA Z_{12} values were then plotted against the Z_{12} values of the AXBTs at the 15 and 35% error levels for the standard maps (case A) and at the 20 and 35% error levels for the high temporal resolution maps (case B).

To check for possible navigation offsets between ship cruises, the standard deviations (STD) were also determined for the XBTs. We expected these offsets to be negligible since the IESs were deployed by the same ships that dropped the XBTs.

4.2 Comparison of the IES OA maps with XBT and AXBT Data: Case A ($\delta t = 2 d$)

4.2.1 Results of the XBT comparison

For each XBT located within the mapping region delimited by the 15% error level, the depth of the 12° C isotherm is plotted against the OA Z₁₂ estimate (Figure 4.5). The scatter about the line of perfect agreement represents a RMS difference of 47 m. Figure 4.6 shows the same comparison of Z₁₂ values but extended to include all XBTs within the 35% estimated map error level. A RMS difference of 50 m was calculated for all 295 XBTs at the 35% map error level. These RMS differences are relatively small, indicating that there is good agreement between the estimated and observed Z₁₂ values.

The RMS differences at the 10, 15, 20, 25 and 35% map error levels are plotted by cruise in Figure 4.7. This figure illustrates that as we extrapolate farther away from the IES sites (i.e., extending out to areas of increased estimated mapping error), the RMS differences worsen. On three cruises (C8304, EN106 and EN118), the RMS differences were relatively constant as the estimated map error increased. However, the RMS differences for two cruises, EN087 and EN124, increased sharply before levelling off. The RMS differences were also calculated for the combined XBTs from all five cruises (Figure 4.7, right). In Figure 4.7, the combined RMS results increase uniformly from 44 m to 50 m as the estimated map error increased from 10% to 35%. This overall increase in



Figure 4.5 Comparison of the Z_{12} from XBTs versus the Z_{12} from 1ES OA maps within the region where mapping error is <15 % for case A ($\delta t = 2 d$). The solid line represents the line of perfect agreement.



DEPTH TO 12 DEGREE ISOTHERM - OA VS XBT

Figure 4.6 Same as Figure 4.5 except within the <35% error region.



Figure 4.7 The RMS difference (*) and STD difference (+) for Z_{12} values from IES OA maps compared with Z_{12} values from XBTs within five levels of estimated error for case A ($\delta t = 2$ d) for five cruises individually and for all five cruises combined.

1

-5

the RMS differences is small because the distribution of the XBTs (discussed in Section 4.1.2) biases the data toward the low mapping error region.

The corresponding STD values at the 15% and 35% error levels are also plotted in Figure 4.7. They are very similar to the RMS values, indicating that no biases were introduced due to navigation offsets on any of the cruises.

4.2.2 kesults of the AXBT comparison

The depth of the 12°C isotherm of each AXBT within the region of the 15% error limit is plotted against the residual estimated CA Z_{12} value in Figure 4.8. A STD of 53 m was calculated for those AXBTS within the 15% error level. Figure 4.9 shows the same comparison of Z_{12} values but including all AXBTS within the 35% estimated map error level. A STD of 68 m was calculated for the IES OA map and AXBT comparison at the 35% error level.

The navigation offsets between the ship and the aircraft are apparent in Figure 4.10. Both the RMS and STD differences for each flight are plotted at the five map error levels (from 10 to 35%). The navigational offsets (about 2 km cross stream) are apparent as the differences between the curves for the flights on June 1, June 6 and November 13. The two curves are almost identical for the other three flights, indicating that no offsets occurred.

The STD differences were composited for all six flights. They increase from 39 m at the 10% estimated map error level to 68 m at the 35% estimated error level. The rapid increase in STD differences from 39 m to 53 m to 66 m as the mapping area was extended to include the regions of 10% to 15% to 20% estimated error, respectively, suggests the need to limit the extent of extrapolation beyond the IES sites.



77

DEPTH TO 12 DEGREE ISOTHERM - RESIDUAL OA VS AXBT

Figure 4.8 Same as Figure 4.5 except for ADDIS.



DEPTH TO TE DEGREE ISOTHERM - RESIDUAL OA VS AXBT

Figure 4.9 Same as Figure 4.6 except for AXBTs.



Figure 4.10 Same as Figure 4.7 except for AXBTs for six flights individually and for all six flights combined.

4.3 Comparison of the IES OA maps with XBT and AXBT Data: Case B ($\delta t = 1$ a)

4.3.1 Results of the XBT comparison

For each XBT located within the map region delimited by the 20% error level, the depth of the 12° C isotherm is plotted against the OA Z_{12} estimate in Figure 4.11. The scatter represents a RMS difference of 47 m. Figure 4.12 shows the same Z_{12} comparison but includes all XBTs within the 35% estimated map error level with a corresponding RMS difference of 50 m.

The RMS differences are plotted in Figure 4.13 by cruise for estimated map error levels ranging from 10% to 35%. EN106 had almost a constant RMS difference as the estimated map error increased. For C8304 and EN118 there was a sharp rise in RMS difference and then a leveling off as map error levels increased further. Two cruises (EN087 and EN124) had a steady RMS increase as map error levels increased. The combined RMS differences for all 5 cruises increase uniformly from 40 m to 50 m as the map error increased from 10% to 35%.

The corresponding STD values are also plotted in Figure 4.13. There is little difference from RMS values, again indicating that no navigational biases were introduced.

4.3.2 Results of the AXBT comparison

The depth of the 12°C isotherm at each AXBT site is plotted against the residual estimated OA Z_{12} value for all AXBTs within the region of the 20% and 35% error limits in Figure 4.14 and Figure 4.15, respectively. The STD differences increase from 47 m at the 20% error level to 74 m at the 35% error level. The range of these results exceeds that for the standard map comparisons (case A) in which a minimum STD of 53 m and a maximum STD of 68 m were obtained at the 15% and 35% error levels, respectively. The range for case B is greater due



DEPTH TO 12 DEGREE ISOTHERM - OA VS XBT

Figure 4.11 Same as in Figure 4.5 except for case B ($\delta t = 1 d$) and <20% error.



DEPTH TO 12 DEGREE ISOTHERM - OA VS XBT

Figure 4.12 Same as Figure 4.6 except for case B.



Figure 4.13 Same as Figure 4.7 except for case B.



DEPTH TO 12 DEGREE ISOTHERM - RESIDUAL OA VS AXBT

Figure 4.14 Same as Figure 4.5 except for AXBTs and case B ($\delta t = 1 d$) at the 20% error level.



DEPTH TO 12 DEGREE ISOTHERM - RESIDUAL OA VS AXBT



to the redistribution of some AXBTs within the five error levels. As the error fields increased in size from case A to case B, some of the AXBT drop-sites shifted into map regions with higher estimated errors.

The navigational offsets between the ship and aircraft are apparent also in Figure 4.16, where the RMS and STD differences for error levels ranging from 10% to 35% are plotted for each flight. The differences between the two curves for 1 June, 6 June, 17 October, and 13 November indicate such an offset. The two curves for the 4 June and 12 June flights are almost identical, indicating no navigational bias.

The composite STD values for all six flights increases from 34 m at the 10% estimated map error level to 74 m at the 35% error level. As in the comparison with the standard maps, there is a rapid increase in STD differences as the mapping area was extended from regions of 10 to 35% estimated error.

4.4 Accounting for the RMS differences

Finally, we attempt to account for all the factors contributing to the observed RMS (40-50 m) and STD (34-74 m) differences between the IES OA maps and the XBTs and AXETs found in both cases A and B. Three sources of error contribute to these differences: (a) the XBT and AXET probes, (b) the inverted echo sounders, and (c) the objective analysis method.

Sippican Corporation reports a depth accuracy for the XBTs of 5 m plus 2% of the depth, which, when combined with a 0.2°C temperature accuracy, yields an $\epsilon_{\rm XBT} = 15$ m RMS XBT error in Z_{12} for an average Gulf Stream Z_{12} of 400-500 m. The accuracy of the deep AXBTs was determined to be 11 m, resulting from the combination of a 0.2°C temperature accuracy and ± 5 m depth accuracy (Boyd, 1986).



ς.

Figure 4.16 Same as Figure 4.7 except for AXBTs and case B.

Tracey and Watts (1986a) report a Z_{12} accuracy of $\epsilon_{IES} = 25 \text{ m}$ RMS for the IESs. This was obtained by directly comparing the Z_{12} values measured by IESs with those of XBTs dropped right at the IES sites. This difference results from the differences in the types of measurements made by the two instruments. The IES Z_{12} value is an integrated measurement, throughout the full water column, and as such is not sensitive to small-scale vertical features such as internal waves. The XBT, however, records the instantaneous Z_{12} which results from fluctuations on all vertical scales. Typically, the comparison of an integral measurement with a point measurement produces some disagreement.

In general, any amount of interpolation will cause the output values to differ from the input measurements. Two different amounts of temporal smoothing were used to produce the OA maps for cases A and B. The output Z_{12} values were estimated from several (N = 9) input values within separation distances R = 120 m and lag times of T = ±4 d for the standard maps with decimation time $\delta t = 2 d$ (case A). For the high temporal resolution maps (case B), lag times were changed to T = ±1 d, the decimation time was reduced to $\delta t = 1 d$, and N was decreased to seven input values. In both cases, the OA method tends to smooth the small-scale horizontal and temporal fluctuations in the Z₁₂ field. The amount by which the outputs differ from the inputs can be estimated by:

$$\epsilon_{OA} = e^{1/2} \star o$$

where e is the error at the output grid point estimated by the OA method and σ is the standard deviation of Z_{12} at that point. Assuming a typical value for σ in the Gulf Stream of 100 m (Figure 3.6) within the map region of 15% estimated error, we obtain $\epsilon_{OA} = 38$ m. The value of

 ϵ_{OA} ranges from 32 m at the 10% error level within the IES array to 59 m at the 35% map error level in the outer fringes of the OA maps.

The total expected RMS difference between the IES OA maps and the XBTs and AXBTs is the square root of the sum of the squares of these three uncorrelated contributers $(\epsilon_{XBT}^2 + \epsilon_{IES}^2 + \epsilon_{OA}^2)^{-1/2}$. Using ϵ_{OA} = 38 m for the 15% error level, we obtain an expected error of 48 m. The expected RMS difference ranges from 42 m for the 10% error level to 67 m at the 35% error level. These expected errors are close to the observed RMS and STD differences between the Z₁₂ values of the IES OA maps (for both cases A and B) and the XBTs (40-50 m) and the AXBTs (34-74 m). Although the XBT RMS difference of 50 m for the 35% error level seems low, it can be attributed to the concentration of the XBT drop sites near the IES sites. Thus, the AXBTs, with more evenly distributed drop sites, give a better estimate of the true STD differences at the 35% error level. The good agreement between the expected RMS differences of 42-67 m and the observed RMS and STD differences of 34-74 m assures us that we have accounted for all the error.

4.5 Summary of Results

Comparisons of estimated IES OA Z_{12} values with the Z_{12} measured independently by XBTs and AXBTs were made in order to determine how well the OA technique maps the thermocline depth field. RMS and STD differences between the Z_{12} values determined from IES OA maps and from XBTs and AXBTs were calculated at five estimated error levels ranging from 10-35% for standard maps (case A) and high temporal resolution maps (case B).

To check for biases introduced by navigation offsets between the ship and aircraft, we looked for large discrepancies between the RMS and

STD values. For the XBT comparisons with the IES OA maps, no significant differences were found, confirming that there were no navigation offsets between the ships that dropped the XBTs and those that deployed IESs. Large differences were found, however, for four of the AXBT comparisons, indicating that navigation offsets occurred between the ship and aircraft. In order to minimize these biases, we have used the STD values for the AXBT comparisons.

For the standard maps (case A), the comparison of the IES OA Z_{12} values with those of the XBTs resulted in RMS differences ranging from 40 m at the 10% map error level to 50 m at the 35% error level (Figure 4.7). The AXBT STD differences ranged from 39 m at the 10% error level to 68 m at the 35% error level (Figure 4.10).

The comparison of the Z_{12} values from the high temporal resolution maps (case B) with those of the XBTs yielded RMS differences of 39 m at the 10% map error level to 50 m at the 35% error level (Figure 4.3). The AXBT comparisons with these maps produced STD differences ranging from 34 m at the 10% error level to 74 m at the 35% error level (Figure 4.16).

For both cases A and B, the AXBT STD values spanned a greater range than the XBT RMS values. The difference can be attributed to differences in the drop-site locations of the XBTs and AXBTs; the AXBTs were more evenly distributed throughout the regions delimited by the five error levels.

It is interesting to note that the RMS and STD values at the 15% error level for case A (standard maps) are nearly the same as those at the 20% error level for case B (high temporal resolution maps). This is true for both the XBTs and AXBTs. For case A, the RMS and STD values at the 15% error level were 47 m for the XBTs and 53 m for the AXBTs. The

XET and AXET RMS and STD differences were identical (47 m) at the 20% error level for case B. Inspection of the estimated error fields shown in Figure 4.1 reveals that the area outlined by the 15% error level for case A is very similar to that described by the 20% error level for case B. Thus, the subsets of probes used for these tests were nearly the same. In either case, the RMS and STD differences of less than 50 m indicate that there is good agreement between the estimated (from the OA maps) and observed (from the XBTs and AXETs) Z_{12} values.

For the IES OA standard (case A) maps, we chose the region delimited by the 15% error level as the largest area of accurate mapping. Correspondingly, we chose the region defined by the 20% error level for the high temporal resolution (case B) maps. There are several reasons why we believe that the map quality within these areas is good. First, the observed RMS differences between the IES OA maps and the XBTs and AXBTs were only 47 m. For both cases, large increases in RMS error were obtained for each 5% error increase beyond these limits, while the mapping areas were only slightly increased. Secondly, having identified three contributing sources of error, we can account for the observed RMS differences. Additionally, the observed RMS differences are less than the contour interval used for the Z_{12} maps. This corresponds to a small (-5 km) error in the lateral displacement of the Z_{12} depth. Finally, the error of 47 m represents less than 8% of the total thermocline depth variation of 700 to 800 m found in the Gulf Stream.

SECTION 5. CONCLUSIONS

Watts and Tracey (1985) modified the objective analysis method presented in Carter (1983) and Carter and Robinson (1987) in order to extend its application to the thermal frontal region of the Gulf Stream. In this report, we present the results from a series of tests which assessed the sensitivity of the technique to variations in the control parameter selections. Having chosen the parameters that produce the best output maps of the thermocline depth field, we then determined the accuracy of these maps by comparing them against concurrent measurements of the temperature field made by XBTs and AXETs.

We tested the robustness of the methodology to the selection of the mean field, standard deviation field, correlation function, and decimation time. Despite variations in these parameters, the interpolated areas (between the instrument sites) of all the output maps are very similar. All output maps, evaluated at the measurement sites. differed from the actual observations by less than 15 m RMS, regardless of the control parameter chosen. The extrapolated regions (away from the instrument sites) were strongly affected by the choice of mean field, with two of the three fields introducing unrealistic thermal features to the output maps. Variations in the choice of correlation function produced little effect on the output maps themselves, but the sizes of the estimated error fields associated with them varied considerably between the three functions tested. Only minor differences in the output Z_{12} maps were produced by the decimation time and the standard deviation field. However, large subsampling intervals result in increased smoothing, which in turn may result in the loss of the high-frequency fluctuations that are of scientific interest.

We found that the best output maps were obtained by using the temporal mean (Z_T) and standard deviation (σ_T) fields. Subsampling the input data at either one-day ($\delta t = 1$ d) or two-day ($\delta t = 2$ d) intervals appeared to resolve many of the important fluctuations while keeping smoothing to a minimum. The analytic correlation function based on IES measurements in the Gulf Stream, ρ_{WT} , predicted the smallest errors, and these agreed well with the observed differences from independent data.

One of the purposes of applying the OA technique on the IES 2,, measurements is to map accurately (i.e., with minimal estimated errors) the Gulf Stream thermocline depth field over a large area. In order to objectively choose the limits of extrapolation beyond the instrument sites, comparisons of the output maps were made with independent measurements of Z₁₂ obtained from XBTs and AXBTs. Two cases were tested: Case A evaluated OA maps produced using the standard map parameters (in particular $\delta t = 2$ d and T = ±4 d) and case B evaluated maps produced with higher temporal resolution ($\delta t = 1 d$ and $T = \pm 1 d$). RMS and STD differences for both cases were computed at five levels of estimated error ranging from 10-35%. These differences ranged from 34 m at the 10% level to about 74 m at the 35% level. The mapping regions delimited by the 15% error level for case A and the 20% error level for case B were nearly indentical. The observed differences between the IES OA maps and the XBTs and AXBTs were 47 m at the 15% (case A) and 20% (case B) error levels. We have chosen the 15% error level for the standard maps and the 20% error level for the high temporal resolution maps as the limits of the Z_{12} field extrapolation. These were selected because the RMS differences are less than one contour interval on the output $Z_{i:t}$ maps and represent less than 8% of the total thermocline depth change (700-800 m) across the Gulf Stream.

ACKNOWLEDGEMENTS

This research program was funded by the National Science Foundation under grants OCE82-01222 and OCE85-17746 and by the Office of Naval Research under contract N00014-81-C-0062. John Bane of the University of North Carolina provided the AXBT data used for the comparisons. Skip Carter supplied the basic objective mapping and contouring programs. We thank Julie Rahn for editorial assistance.

REFERENCES

Boyd, J.D. 1986. Improved depth and temperature conversion equations for Sippican AXBTs. NORDA Report 156. NSTL, Mississippi.

÷

- Bretherton, F.P., R.E. Davis, and C.B. Fandry. 1976. A technique for objective analysis and design of oceanographic experiments applied to MODE-73. <u>Deep-Sea Res</u>. 23: 559-582.
- Carter, E.F. 1983. The statistics and dynamics of ocean eddies. Ph.D. Thesis. Harvard University.
- Carter, E.F. and A. R. Robinson 1987. Analysis models for the estimation of oceanic fields. J. <u>Atmos. Oceanic Technol. 4</u>: 49-74.
- Freeland, H.J. and W.J. Gould. 1976. Objective analysis of meso-scale ocean circulation features. <u>Deep-Sea Res. 23</u>: 915-923.
- Friedlander, A.F., K.L. Tracey, and D.R. Watts. 1986. The Gulf Stream Dynamics Experiment: Inverted echo sounder data report for the July 1982 to April 1983 deployment period. University of Rhode Island. GSO Technical Report 86-5. 101 pp.
- Gandin, L.S. 1965. Objective analysis of meteorological fields. Israel Program for Scientific Translations. Jerusalem. 242 pp.
- Halliwell, G.R., Jr. and C.N.K. Mooers. 1983. Meanders of the Gulf Stream Downstream from Cape Hatteras 1975-1978. J. Phys. Oceanogr. 13: 1275-1292.
- Tracey, K.L., M. Cronin, and D.R. Watts. 1985. The Gulf Stream Dynamics Experiment: Inverted echo sounder data report for the June 1984 to May 1985 deployment period. University of Rhode Island. GSO Technical Report 85-3. 176 pp.
- Tracey, K.L. and D.R. Watts. 1986a. On Gulf Stream meander characteristics near Cape Hatteras. J. <u>Geophys. Res. 91</u>: 7587-7602.
- Tracey, K.L. and D.R. Watts. 1986b. The Gulf Stream Dynamics Experiment: Inverted echo sounder data report for the April 1983 to June 1984 deployment period. University of Rhode Island. GSO Technical Report 86-4. 228 pp.
- Watts, D.R. and W.E. Johns. 1982. Gulf Stream meanders: observations on propagation and growth. <u>J. Geophys</u>. <u>Res</u>. <u>87</u>: 9467-9476.

Watts, D.R. and H.T. Rossby. 1977. Measuring dynamic heights with inverted echo sounders: Results from MODE. J. Phys. Oceanogr. 7: 345-358.

Watts, D.R. and K.L. Tracey. 1985. Objective analysis of the Gulf Stream thermal front from inverted echo sounders. <u>Gulf Stream</u> <u>Workshop Proceedings</u>. University of Rhode Island. II. 525-548.

96

:

۲

Ł

APPENDIX

The following discussion, with minor changes, was originally presented in Watts and Tracey (1985).

An essential input to the objective analysis is the space-time correlation function $\rho(x',y',t')$, where primes indicate lag distances in space and time. To estimate $\rho(x',y',t')$, we combined data from previous IES deployment-pairs in the Gulf Stream to estimate the average correlation function $\rho(x',y',t')$, for all (x',y') spatial separations and time lags t' from -16 to +16 d. Fifty-three individual instruments, from 1979 to 1984 in six deployment periods, were used and all the pair separations are plotted in Figure A.1. To check for anisotropy of ρ , we first identified cross-stream and along-stream IES pairs and separately calculated their correlation functions. These were averages in 10 km bins and are showm in Figure A.2 versus distance. At zero time lag, the observations show ρ to be remarkably isotroic, since the functional shapes for instruments spaced in either direction are indistinguishable. Consequently we can approximate $\rho = \rho(r)$. Figure A.3 shows the observed correlation function in plan view for time lags out to 10 days. These have been smoothed by a 50 km Gaussian weighted low-pass filter. At non-zero time lag, the peak of the observed correlation function moves downstream at 12 km/d, decays slowly (e.g., exceeding 0.7 at t' = 6 d), and maintains its symmetric shape.

We can approximate ρ by the functional form:

 $\rho(\mathbf{x}',\mathbf{y}',\mathbf{t}') = \exp(-\mathbf{t}'/T_{\bullet}) \exp(-\mathbf{r}/A) \cos(\pi r/2B)$ where $\mathbf{r}^2 = (\mathbf{x}'-\mathbf{ct}')^2 + (\mathbf{y}')^2$, $T_{\bullet} = 9.3$ d, A = 391 km, B = 171 km, and c = 12 km/d. Figure A.3 also shows the idealized function for the same

time lags as . \Rightarrow observed function. We chose this function such that the temporal decay rate of the central peak is similar to the observed values. The spatial decay rate is exactly the same as that observed for zero time lag; thus the idealized function at zero time lag (upper left corner) is another view of $\rho(r)$, which was already shown in Figure A.2. The decay rates of both functions remain similar out to 4 d time lag, but the observed correlations decay more slowly than the idealized function for the longer time lags.



Figure A.1 Plot of all IES pair separations (x',y') with a different symbol used to represent each deployment period. The center box corresponds to the region for which the smoothed $\rho(x',y',t')$ is contoured in Figure A.3.


Figure A.2 Correlation functions for cross-stream, along-stream, and diagonal IES pairs versus distance. The solid curve through the values is the idealized $\rho(x',y',t')$ at a time lag of 0 days.



the symmetry relation $\rho(-x',-y',-t') = \rho(x',y',t')$. Contour interval is Darker shading indicates $\rho \ge 0.7$; 2-day steps. For negative time lags, note that ρ is implicitly given by $\rho(x',y',t')$, contoured in plan view for time lags from 0 to 10 days in 0.1 and negative contours are dashed. Iighter shading indicates $\rho \ge 0.4$.



Unclassified SECURITY CLASSIFICATION OF THIS PAGE

103

a REDAT SCLARY CLASSFCATON 0 REFARCTVE VARANOS UnclassField 1 SYTABUTON, VARANOS 2 SECATOR VARANOS AUTAGRTY 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS AUTAGRTY 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS AUTAGRTY 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS AUTAGRTY 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS AUTON SECON VAREAD 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS AUTON SECON VAREAD 1 SYTABUTON, VARANOS TO REPORT 2 SECATOR VARANOS 1 SYTABUTON, VARANOS 2 SECATOR VARANOS 1 SYTABUTON, VARANOS 2 SECATOR VARANOS 1 SYTABUTON 2 SANT CANNOS 1 SYTABUTON 2 SANT CANNO	REPORT DOCUMENTATION PAGE						
21 SECURY CASSECATON SUF-DRIV 3) STRAUTON AVALABLY TO SERVET 21 SECURY CASSECATON SUF-DRIV 3) STRAUTON AVALABLY TO SERVET 21 SECURITY CASSECATON SUF-DRIV Distribution for public release; distribution for public release;	Ta. REPORT SECURITY CLASSIFICATION Unclassified		16. RESTRICTIVE MARKINGS				
a. SECURSPECTATION SOUNDERLOWER a SECURSPECTATION SECOND december of necessary and denny by block number) alignment of the duil Stream thermal front Inverted Echo Sounders advers of second Stream and Stream and Stream thermal front Inverted Echo Sounders access of the space of the s	2a. SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION/AVAILABILITY OF REPORT Distribution for public release;				
1 3#2600MMG DRGANZATON #200FT VUMBERIS	LD. DECLASSIFICATION DOWNGRADING SCHEDU	distribution is unlimited.					
Su VANG DF SERGEMING DEGLANDATION So DFFCE SYMBOL A. VANE DF MONIFORING DEGLANDATION Graduate School of Oceanography A. VANE DF MONIFORING DEGLANDATION A. VANE DF MONIFORING DEGLANDATION Sc ADDRESS CRY, Size, and IPCode 75. ADDRESS CRY, Size, and IPCode South Ferry Road South Ferry Road . . . I'M SATINGARD SPONSORING IBD. OFFICE SYMBOL S PROCHEMENT INSTRUMENT DENTIFICATION NUMBER I'M SATING Science Foundation PHY STEAM Ocean graphy Program OCES2-01222 and OCEES-17746 I'M SCH Vauel Bascarch Code 12:D 10 I'M Code 422 PO, SUO North Quincy, Arlington, VA 10 SOURCE OF FUNDING NUMBERS I'M Code 422 PO, SUO North Quincy, Arlington, VA PROCHAMENT OC NOA I'M Code 422 PO, SUO North Quincy, Arlington, VA PROCHAMENT OC NOA ACCESSION NO. 2: Code 422 PO, SUO North Quincy, Arlington, VA PROCHAMENT OC NOA ACCESSION NO. 2: Code 422 PO, SUO North Quincy, Arlington, VA PROCHAMENT OCUMENT OCUMENT OCUMENT NOA ACCESSION NO. 2: 20500 North Quincy, Arlington, VA State of PRONT NOA ACCESSION NO. 2: 20500 North Quincy, Arlington, VA State of PRONT NOA ACCESSION NO. 2:	PERFORMING ORGANIZATION REPORT NUMBE Graduate School of Oceanograph Technical Report 87-2	5 MONITORING ORGANIZATION REPORT NUMBER(S)					
Sc ADDRESS CR, Size. and ZP Code) To ADDRESS CR, Size. and ZP Code) South Ferry Road	5a. NAME OF PERFORMING ORGANIZATION University of Rhode Island Graduate School of Oceanography	6b. OFFICE SYMBOL (If applicable)	Ta. VAME OF MONITORING ORGANIZATION				
South Ferry Road Narragansett, RI 02582 is AMAG 27 JUDNICS PONSONG is ADDRES (Constance JUDNICS PONSONG is ADDRES (Constance JUDNICS PONSONG is ADDRES (Constance JUDNICS PONSONG 2) GEFICE SYMBOL 2) GEGIC STANDA 2) GEGIC STANDA 2) GOLD STANDA 2) GOLD STANDA 2) GER STANDA 2) GER STANDA 2) GER STANDA 2) GER STANDA 3) STANDA <td>Sc. ADDRESS (City, State, and ZIP Code)</td> <th><u> </u></th> <td colspan="4">7b. ADDRESS (City, State, and ZIP Code)</td>	Sc. ADDRESS (City, State, and ZIP Code)	<u> </u>	7b. ADDRESS (City, State, and ZIP Code)				
As. WANG DF FUNDING SPONSORING Bs. SPRICE SYMBOL 9 PROCUREMENT NSTAURENT DENTIFICATION NUMBER 11 National Science Foundation PH/SPRICE argany Program OCES2-01222 and OCES2-17746 2) Office of Xaval Research Code 422 PO NOOId14-81-C-0062 2: ADDRESS CEV, Stee and ZPCOBH 10 SOURE DF SUNDING VUMBERS MOOID14-81-C-0062 2: ADDRESS CEV, Stee and ZPCOBH 10 SOURE DF SUNDING VUMBERS MOOID14-81-C-0062 2: Ocde 422 PO, SOO North Quincy, Arlington, VA PROST PROVING VUMBERS MOOR 2: PROSONAL AUTHORSIS NO. MCCESSION NO. X.L. Tracey, A.I. Friedlander, and D.R. Watts 14 Date OF REPORT (Year Monm.Dev) 15 PAGE COUNT Summary 10. TIME COVERED 14 Date OF REPORT (Year Monm.Dev) 15 PAGE COUNT Summary 13. NOVE OF REPORT (Year Monm.Dev) 15 PAGE COUNT December 1987 12 COSATI CODES 11. SUBJECT TERMS (Continue on revers if metersary and identify by block number) 104 14: DATE OF REPORT (Year Monm.Dev) 15 PAGE COUNT December 1987 104 13: NVE OF REPORT 13. SUBJECT TERMS (Continue on revers if metersary and identify by block number) 114 14: DATE OF REPORT (Year Monm.Dev) 15 PAGE COUNT December 1987 <td< td=""><td>South Ferry Road Narragansett, RI 02882</td><td colspan="4"></td></td<>	South Ferry Road Narragansett, RI 02882						
32 ΔΟΟRESTICH, State and ZP COMP 10 SOURCE SF = UNDING YUMMERS 1) 1800 G St. NW, Washington D.C. 20550 10 SOURCE SF = UNDING YUMMERS PROGRAM 2) Code 422 PO, SOO North Quincy, Arlington, VA 22217 Task MORE JANK 11 THE UNDUCK Security Classification 22217 NO. NO. ACCESSION NO. 2217 2217 2217 10 ACCESSION NO. ACCESSION NO. 2218 MORE OF REPORT 130. THE COVERED 2217 10 ACCESSION NO. 2218 SUMPLEMENTARY NOTATION 10 DACESSIGN ACOUNT 104 ACCESSION NO. 12 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 104 17 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 1	3a. NAME OF FUNDING, SPONSORING (1) Sational Science Foundation (2) Office of Naval Recearch	85. OFFICE SYMBOL (If applicable) Physical Oceand Code 122 PO	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER graphy Program OCE82-01222 and OCE85-17746 NO0011 81 C 0062				
1) 1800 G St. NW, Washington D.C. 20550 PROJECT NO. TASK NO. WORK JWT ACCESSION NO. 2) Code 422 P0, 800 North Quincy, Arlington, VA Ligton, VA Light No. NO. WORK JWT ACCESSION NO. 11 THE (Include Secury Cashication) Discretion Cashication) Discretion Cashication NO. WORK JWT ACCESSION NO. 22 PERSONAL AUTHOR(S) N.L. Tracey, A.I. Friedlander, and D.R. Watts Iso Time Covered Iso Time Covered Iso Time Covered 13. TYPE OF REPORT Iso Time Covered Iso Time Covered Iso Time Covered Iso Time Covered 13. TYPE OF REPORT Iso Time Covered Iso Time Covered Iso Time Covered Iso Time Covered 13. TYPE OF REPORT Iso Time Covered Iso Time Covered Iso Time Covered Iso Time Covered 13. TYPE OF REPORT Iso Time Covered Iso Time Covered Iso Time Covered Iso Covered Iso Covered Iso Covered 14 Supplementary Iso Time Covered Iso Time Covered Iso Covered I	BC. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS				
11 TILE (Include Security Classification) Objective Analysis of the Gulf Stream Thermal Front: Methods and Accuracy (Unclassified) 22 PERSONAL AUTHOR(S) K.L. Tracey, A.I. Friedlander, and D.R. Watts 13a. TYPE OF REPORT 13b. TIME COVERED 14 DATE OF REPORT (Year. Month. Day) 15 PAGE COUNT Summary 13b. TIME COVERED 14 DATE OF REPORT (Year. Month. Day) 15 PAGE COUNT Summary 16 SUPPLEMENTARY NOTATION 17 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 17 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 17 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 19 ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time-average mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the O	 (1) 1800 G St. NW, Washington D.C. 20550 (2) Code 422 PO, 800 North Quincy, Arlington, VA 		PROGRAM ELEMENT NO.	PROJECT NO	TASK NO.	WORK JNIT ACCESSION NO.	
2. 2FRSONAL AUTHOR(S) K.L. Tracey, A.I. Friedlander, and D.R. Watts 13a. TYPE (G REPORT) 13b. TIME COVERED 13b. TIME COVERED 14 DATE OF REPORT (Year. Month. Day) 15 PAGE COUNT 2000 2010 13b. TIME COVERED 14 DATE OF REPORT (Year. Month. Day) 15 PAGE COUNT 2000 2010 13b. TIME COVERED 14 DATE OF REPORT (Year. Month. Day) 15 PAGE COUNT 2011 2010 2000 2010 104 104 2015 2010 2000 2010 104 104 2016 2010 2000 2010 104 104 2017 2010 2000 2010 101 104 2017 2010 2000 2010 101 101 2018 2010 2000 2010 118. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) 2016 2010 GROUP Gulf Stream thermal front Inverted Echo Sounders 2017 2010 2018 2000 019 Stream thermal front Inverted Echo Sounders 2019 2010 104 2019 2000 Gulf Stream. Here, we test the robustness of the adapted 0A 2010 2010 1010 2010 2010 Adate the adapted 0A Stream thermal field, with the most realistic results produced using a time- <td colspan="7">11 TITLE (Include Security Classification) Objective Analysis of the Gulf Stream Thermal Front: Methods and Accuracy (Unclassified)</td>	11 TITLE (Include Security Classification) Objective Analysis of the Gulf Stream Thermal Front: Methods and Accuracy (Unclassified)						
13a. TYPE OF REPORT 13b. TIME COVERED 14. DATE OF REPORT (Year. Month. Day) 15. PAGE COUNT Summary 104 104 16. SUPPLEMENTARY NOTATION 10. 17 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) FIELD GROUP SUB-GROUP 19 ABSTRACT (Continue on reverse if necessary and identify by block number) Guif Stream thermal front Inverted Echo Sounders 19 ABSTRACT (Continue on reverse if necessary and identify by block number) Guif Stream thermal front Inverted Echo Sounders 19 ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal cone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most averaged mean. The choice of the space-time correlation function has a large influence on the ssize of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, ρ_{WT} , which is based on four years of in	2. PERSONAL AUTHOR(S) K.L. Tracey, A.I. Friedlander, and D.R. Watts						
15 SUPPLEMENTARY NOTATION 17 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Gulf Stream thermal front Inverted Echo Sounders objective analysis 19 ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time-averaged mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, P _{WT} , which is based on four years of inverted echo sounder data collected in the same region of the Gulf Stream. Variations in the selection of the standard deviation field and decimation time have little effect on the output OA maps. We determined the accuracy of the output OA maps by comparing them with independent measurements of the thermal field. Two cases are evaluated: standard maps and high temporal resolution maps, with decimation times of 2 days and 1 day, respectively. Standard deviations 20 DISTRIBUTION/AVAILABILITY OF ABSTRACT 21 ABSTRACT SECURITY CLASSIFICATION unclassified 22a. VAME OF RESPONSIBLE NOIVIOUAL 21 ABSTRACT SECURITY CLASSIFICATION 22b. TELEPHONE (Include Area Code) 22c. OFF/CE SYMBOL	13a. TYPE OF REPORT13b. TIME COVERED14. DATE OF REPORT (Year, Month, Day)15. PAGE COUNTSummaryFROM 7/1982 T05/1985December 1987104						
17COSATI CODES18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)FIELDGROUPSUB-GROUPGulf Stream thermal frontInverted Echo Sounders0objective analysisOutput Stream thermal frontInverted Echo Sounders19ABSTRACT (Continue on reverse if necessary and identify by block number)The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the19ABSTRACT (Continue on reverse if necessary and identify by block number)The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the10thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA16technique to the selection of four control parameters: mean field, standard deviation field,17correlation function, and decimation time. Output OA maps of the thermocline depth are most17affected by the choice of the space-time correlation function has a large influence on18still the same region of the Gulf Stream. Variations in the selection of19the standard deviation field and decimation time have little effect on the output OA maps.19We determined the accuracy of the output OA maps by comparing them with independent19measurements of the thermal field. Two cases are evaluated: standard maps and high temporal19Tool JSTRIBUTION/AVAILABILITY OF ABSTRACT10DISTRIBUTION/AVAILABILITY OF ABSTRACT11ABSTRACT SECURITY CLASSIFICATION12UD STRIBUTION/AVAILABILITY OF ABSTRACT12DOINT AVAILABILITY OF ABSTRACT12DOINT AVA	16 SUPPLEMENTARY NOTATION						
FIELDGROUPSUB-GROUPGulf Stream thermal front objective analysisInverted Echo Sounders objective analysis19ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time- averaged mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, ρ_{WT} , which is based on four years of inverted echo sounder data collected in the same region of the Gulf Stream. Variations in the selection of the standard deviation field and decimation time have little effect on the output OA maps. We determined the accuracy of the output OA maps by comparing them with independent measurements of the thermal field. Two cases are evaluated: standard maps and high temporal resolution maps, with decimation times of 2 days and 1 day, respectively. Standard deviations20DISTRIBUTION/AVALABULTY OF ABSTRACT TAUNCLASSIFIED/UNLIMITED211.ABSTRACT SECURITY CLASSIFICATION unclassified22a. VAME OF RESPONSIBLE NDIVIDUAL22b. TELEPHONE (Include Area Code)22c. OFFICE SYMBOL	17 COSATI CODES	18. SUBJECT TERMS (C	ontinue on reverse	if necessary ai	nd identify by	block number)	
19 ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time-averaged mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, ρ _{WT} , which is based on four years of inverted echo sounder data collected in the same region of the Gulf Stream. Variations in the selection of the standard deviation field and decimation time have little effect on the output OA maps. We determined the accuracy of the output OA maps by comparing them with independent measurements of the thermal field. Two cases are evaluated: standard maps and high temporal resolution maps, with decimation times of 2 days and 1 day, respectively. Standard deviations 20 DISTRIBUTION/AVAILABILITY OF ABSTRACT DOTE USERS 21. ABSTRACT SECURITY CLASSIFICATION unclassified 222. VAME OF RESPONSIBLE NDIVIDUAL 224. VAME OF RESPONSIBLE NDIVIDUAL	FIELD GROUP SUB-GROUP	Gulf Stream th objective anal	ermal front Inverted Echo Sounders ysis				
	19 ABSTRACT (Continue on reverse if necessary and identify by block number) The objective analysis (OA) technique was adapted by Watts and Tracey in order to map the thermal frontal zone of the Gulf Stream. Here, we test the robustness of the adapted OA technique to the selection of four control parameters: mean field, standard deviation field, correlation function, and decimation time. Output OA maps of the thermocline depth are most affected by the choice of mean field, with the most realistic results produced using a time-averaged mean. The choice of the space-time correlation function has a large influence on the size of the estimated error fields, which are associated with the OA maps. The smallest errors occur using the analytic function, ρ_{WT} , which is based on four years of inverted echo sounder data collected in the same region of the Gulf Stream. Variations in the selection of the standard deviation field and decimation time have little effect on the output OA maps. We determined the accuracy of the output OA maps by comparing them with independent measurements of the thermal field. Two cases are evaluated: standard maps and high temporal resolution maps, with decimation times of 2 days and 1 day, respectively. Standard deviations 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT 21. ABSTRACT SECURITY CLASSIFICATION 22. NAME OF RESPONSIBLE NOLVIDUAL 21. ABSTRACT SECURITY CLASSIFICATION 22. DEFICE SYMBOL						
	00 508M 1472 44 142						

SECURITY CLASSIFICATION OF THIS PAGE

£

-

All other editions are obsolete.

19.

(STD) between the standard maps at the 15% estimated error level and the XBTs (AXBTs) are determined to be 47-53 m. The comparisons of the high temporal resolution maps at the 20% error level with the XBTs (AXBTs) give STD differences of 47 m.