

#### A RAND NOTE

AD-A200 264

Aircraft Airframe Cost Estimating Relationships: Bombers and Transports

R. W. Hess, H. P. Romanoff

December 1987



DISTRIBUTION STATEMENT A Approved for public releases Distribution Unlimited

### 88 10 24 005

### RAND

The research reported here was sponsored by the United States Air Force under Contract F49620-86-C-0008. Further information may be obtained from the Long Range Planning and Doctrine Division, Directorate of Plans, Hq USAF.

ŀ

•

The RAND Publication Series: The Report is the principal publication documenting and transmitting RAND's major research findings and final research results. The RAND Note reports other outputs of sponsored research for general distribution. Publications of The RAND Corporation do not necessarily reflect the opinions or policies of the sponsors of RAND research.

Published by The RAND Corporation 1700 Main Street, P.O. Box 2138, Santa Monica, CA 90406-2138

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING SOPH
REPORT NUMBER 2. GOVT A	CCESSION NO. 3. RECIPIENT'S CATALOG NUMBER
	S. TYPE OF REPORT & REPORT OF
Aircraft Airframe Cost Estimating Pelation	Interim
Bombers and Transports	
	- PERFORMING ORG. REPORT NUMBER
AUTHOR()	8. CONTRACT OR GRANT NUMBER(3)
R. W. Hess, H. P. Romanoff	F49620-86-C-0008
PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
1700 Main Street	
Santa Monica, CA 90406	
CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE December 1987
Office, DCS/Plans and Operations	13. NUMBER OF PAGES
Hq, USAF, Washington, DC 20330	
- HUNIUNING AUGNUT NAME & ADUNESSII dillerent irom Confr	(of this report)
	Unclassified
	154. DECLASSIFICATION/DOWNGRADING SCHEDULE
DISTRIBUTION STATEMENT (of the Report) Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the ebefrect entered in Block 20,	Unlimited
DISTRIBUTION STATEMENT (of the Report) Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the abetract entered in Block 20, No Restrictions	Unlimited
DISTRIBUTION STATEMENT (of the Report) Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the aboutect entered in Block 20, No Restrictions SUPPLEMENTARY NOTES	Unlimited
Approved for Public Release; Distribution OISTRIBUTION STATEMENT (of the abetract entered in Block 20, No Restrictions SUPPLEMENTARY NOTES	Unlimited
Approved for Public Release; Distribution OISTRIBUTION STATEMENT (of the observect entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by	Unlimited  It different from Report)  block number)
Approved for Public Release; Distribution OISTRIBUTION STATEMENT (of the observed entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft.	Unlimited If different from Report) block number)
Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the obstract entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft	Unlimited  If different from Report)  block number) t
Approved for Public Release; Distribution Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the observect entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations	Unlimited <pre>if different from Report) block number) t</pre>
Approved for Public Release; Distribution Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the observed in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations,	Unlimited  If different from Report)  block number)  t
Approved for Public Release; Distribution OISTRIBUTION STATEMENT (of the observed entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations, ABSTRACT (Continue on reverse side if necessary and identify by & See reverse side	Unlimited If different from Report) block number) t
Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the abstract entered in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations, ABSTRACT (Continue on reverse side If necessary and identify by 6 See reverse side	Unlimited  If different from Report)  block number)  t  block number)
Approved for Public Release; Distribution  DISTRIBUTION STATEMENT (of the observed in Block 20.  No Restrictions  SUPPLEMENTARY NOTES  KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft. Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations,  ABSTRACT (Continue on reverse side If necessary and identify by 6 See reverse side	Unlimited If different from Report) block number; t
Approved for Public Release; Distribution OISTRIBUTION STATEMENT (of the observed in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement, Military Aircraft Equations, ABSTRACT (Continue on reverse side if necessary and identify by d See reverse side	Unlimited  If different from Report)  block number)  t  block number)
Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the observed in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft, Cost Estimates, Transport Aircraft Procurement. Military Aircraft Equations , ABSTRACT (Continue on reverse side If necessary and identify by 6 See reverse side	Unlimited If different from Report) block number) t black number)
Approved for Public Release; Distribution DISTRIBUTION STATEMENT (of the observed in Block 20, No Restrictions SUPPLEMENTARY NOTES KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft. Cost Estimates, Transport Aircraft Procurement. Military Aircraft Equations , ABSTRACT (Continue on reverse side If necessary and identify by & See reverse side	Unlimited  If different from Report)  block number)  t  block number)
Approved for Public Release; Distribution  DISTRIBUTION STATEMENT (of the obstract entered in Block 20, No Restrictions  SUPPLEMENTARY NOTES  KEY WORDS (Continue on reverse side if necessary and identify by Airframes, Bomber Aircraft. Cost Estimates, Transport Aircraft Procurement. Military Aircraft Equations,  ABSTRACT (Continue on reverse side if necessary and identify by 6 See reverse side	Unlimited  If different from Report)  block number)  t  linck number)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

This Note is part of a series of Notes that derive a set of equations suitable for estimating the acquisition costs of various types of aircraft airframes in the absence of detailed design and manufacturing information. A single set of equations was selected as being the most representative and applicable to the widest range of estimating situations. For bombers and transports, no single acceptable estimating relationship could be identified. Estimates for these aircraft should be developed by analogy or by using the equation set developed for all mission types.

-4'

FLT: 9

#### UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

#### A RAND NOTE

N-2283/3-AF

Aircraft Airframe Cost Estimating Relationships: Bombers and Transports

R. W. Hess, H. P. Romanoff

December 1987

Prepared for The United States Air Force





### RAND

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

#### PREFACE

- iii -

This Note describes an attempt to develop a set of equations suitable for estimating the acquisition costs of bomber/transport airframes in the absence of detailed design and manufacturing information. In broad form, this research represents an extension of the results published in J. P. Large et al., *Parametric Equations for Estimating Aircraft Airframe Costs*, The RAND Corporation, R-1693-1-PA&E, February 1976, and used in the RAND aircraft cost model, DAPCA: H. E. Boren, Jr., *A Computer Model for Estimating Development and Procurement Costs of Aircraft (DAPCA-III)*, The RAND Corporation, R-1854-PR, March 1976.

The present effort was undertaken in the context of a larger overall study whose objectives included: (a) an analysis of the utility of dividing the full estimating sample into subsamples representing major differences in aircraft type (attack, fighter, and bomber/transport); and (b) an examination of the explanatory power of variables describing program structure and airframe construction techniques. Additionally, for the fighter subsample only, the study investigated the possible benefits of incorporating an objective technology measure into the equations. A detailed description of the overall study including the research approach, evaluation criteria, and database may be found in R. W. Hess and H. P. Romanoff, Aircraft Airframe Cost Estimating Relationships: Study Approach and Conclusions, The RAND Corporation, R-3255-AF, December 1987.

To address the issue of sample homogeneity, each of the subsamples, as well as the full sample, had to be investigated in detail with the ultimate goal of developing a representative set of cost estimating relationships (CERs) for each. The purpose of this Note is, therefore, to document the analysis of the bomber/transport subsample. Study results concerning the full estimating sample as well as the other subsamples are available in a series of companion Notes: Aircraft Airframe Cost Estimating Relationships: All Mission Types, N-2283/1-AF, December 1987.

Aircraft Airframe Cost Estimating Relationships: Fighters, N-2283/2-AF, December 1987.

Aircraft Airframe Cost Estimating Relationships: Attack Aircraft, N-2283/4-AF, December 1987.

This research was undertaken as part of the Project AIR FORCE study entitled "Cost Analysis Methods for Air Force Systems," which has since been superseded by "Air Force Resource and Financial Management Issues for the 1980s" in the Resource Management Program.

While this report was in preparation, Lieutenant Colonel H. P. Romanoff, USAF, was on duty in the System Sciences Department of The RAND Corporation. At present, he is with the Directorate of Advanced Programs in the Office of the Assistant Secretary of the Air Force for Acquisition.

- iv -

#### SUMMARY

This Note documents an attempt to derive a set of equations suitable for estimating the acquisition costs of bomber/transport aircraft. The estimating sample consists of eight bomber/transport aircraft with first flight dates ranging from 1954 to 1968. The aircraft technical data were for the most part obtained from either original engineering documents such as manufacturer's performance substantiation reports or from official Air Force and Navy documents. The cost data were obtained from the airframe manufacturers either directly from their records or indirectly through standard Department of Defense reports such as the Contractor Cost Data Reporting System.

The key result of this effort is that we were unable to identify a single acceptable estimating relationship for any of the individual cost elements or for the total program cost element. This discouraging result is not too surprising, however, since the bomber/transport sample is very small and not especially homogeneous. Estimates for proposed bomber/transport aircraft should be developed on the basis of analogy (using the data provided in this Note) or by using the equation set developed for all mission types (N-2283/1-AF).

•

#### - vii -

#### CONTENTS

PREFAC	Ε	iii
SUMMAR	¥¥	v
FIGURE	s	ix
TABLES	•••••••••••••••••••••••••••••••••••••••	xi
MNEMON	ICS	xiii
EVALUA	TION CRITERIA NOTATION	xv
Sectio	n	
Ι.	INTRODUCTION	1
II.	DATABASE AND ANALYTICAL APPROACH Estimating Sample Dependent Variables Potential Explanatory Variables Approach Evaluation Criteria	3 3 4 5 8 11
III.	INITIAL OBSERVATIONS Influential Observations Performance variables Construction/Program Variables	17 17 19 19
IV.	ENGINEERING	20
Υ.	TOOLING	23
VI.	MANUFACTURING LABOR	26
VII.	MANUFACTURING MATERIAL	29
VIII.	DEVELOPMENT SUPPORT	32
IX.	FLIGHT TEST	36
Χ.	QUALITY CONTROL	39
XI.	TOTAL PROGRAM COST	41
XII.	CONCLUSIONS Cost-Quantity Slopes Fully Burdened Labor Rates	44 44 45
Append	ix: CORRELATION MATRIXES	47
REFERE	NCES	51

#### - ix -

#### FIGURES

1.	Number of First Flight Events as a Function of the Year of First Flight	16
2.	Effect of B/RB-66 and C-5	19
3.	Engineering Hours per Pound as a Function of Airframe Unit Weight	21
4.	Tooling Hours per Pound as a Function of Airframe Unit Weight	24
5.	Manufacturing Labor Hours per Pound as a Function of Airframe Unit Weight	27
6.	Manufacturing Material Cost per Pound as a Function of Airframe Unit Weight	30
7.	Development Support Cost per Pound as a Function of Airframe Unit Weight	33
8.	Flight Test Cost per Test Aircraft as a Function of the Quantity of Flight Test Aircraft	37
9.	Quality Control Hours per Pound as a Function of Airframe Unit Weight	40
10.	Total Program Cost per Pound as a Function of Airframe Unit Weight	42

#### - xi -

#### TABLES

1.	Percentage Breakdown of Bomber/Transport Airframe Program Costs	4
2.	Bomber/Transport Aircraft Characteristics	6
3.	A Priori Notions Regarding Effect of Explanatory Variable Increase on Cost Element	9
4.	Comparison of Full Bomber/Transport Sample and Sample Excluding B-58	18
5.	Engineering Hour Estimating Relationships	22
6.	Tooling Hour Estimating Relationships	25
7.	Manufacturing Labor Hour Estimating Relationships	28
8.	Manufacturing Material Cost Estimating Relationships	31
9.	Development Support Cost Estimating Relationships	34
10.	Development Support Cost as a Percentage of Unit 1 Engineering Cost	35
11.	Flight Test Cost Estimating Relationships	38
12.	Total Program Cost Estimating Relationships	43
13.	Cumulative Total Cost Quantity Slopes	45
A.1.	Correlation Matrix: Cost Variables with Potential Explanatory Variables	49
A.2.	Correlation Matrix for Identification of Pairwise Collinearity	50

Ľ

0

Ø

#### - xiii -

#### MNEMONICS

AUW	Airframe unit weight (lb)
AVAUW	Ratio of avionics weight to airframe unit weight
BLBOX	Number of black boxes
CA	Cumulative average
DS	Development support cost (thousands of 1977 dollars)
ENGR <sub>100</sub>	Cumulative engineering hours for 100 aircraft (thousands)
EW	Empty weight (lb)
EXPDV	Contractor experience designator $(1 = yes; 2 = no)$
FT	Flight test cost (thousands of 1977 dollars)
LABR 100	Cumulative manufacturing labor hours for 100 aircraft (thousands)
MATL 100	Cumulative manufacturing material cost for 100 aircraft (thousands of 1977 dollars)
PROG <sub>100</sub>	Cumulative total program cost for 100 aircraft (thousands of 1977 dollars)
Q	Quantity
QC <sub>100</sub>	Cumulative quality control hours for 100 aircraft (thousands)
SP	Maximum speed (kn)
TESTAC	Number of flight test aircraft
TOOL	Cumulative tooling hours for 100 aircraft (thousands)
USELD	Useful load fraction
WGWET	Ratio of wing area to wetted area
WTAREA	Wetted area (sg ft)

1

#### EVALUATION CRITERIA NOTATION

Notation	Explanation
EQ SIG: F-TEST	Equation as a whole is not significant at 5 percent level (based on F-statistic)
EXP MAG: variable mnemonic	Question exists regarding magnitude of variable exponent (reasonableness)
EXP SIGN: variable mnemonic	Sign of variable exponent does not agree with a priori notions
F	F-statistic
IO: aircraft identification	Based on "Cook's Distance," aircraft is indicated to be influential observation
LDIFF: variable mnemonic	Limited differentiation in dummy variable; coefficient determined by single observation or portion of dummy variable range not included in a subsample
MCOL: r(variable) > .7, .8, or .9	Indicates degree of intercorrelation of specified variable with other equation variables (only provided when threshold of .7 is exceeded)
Ν	Number of observations
R <sup>2</sup>	Coefficient of determination
RP: CUR: OVER/UNDER	Residual pattern indicates that the most recently developed aircraft in the sample are over- or underestimated •
RP: DIST	Residual pattern indicates that the error is not normally distributed with zero mean and constant variance
SEE	Standard error of estimate
VAR SIG: variable mnemonic	Variable is not significant at the 5 percent level (t-statistic) <sup>1</sup>

[•

0

•

•

٠

- xv -

<sup>&</sup>lt;sup>1</sup>Variable significance is provided in parentheses beneath each variable.

#### I. INTRODUCTION

Parametric models for estimating aircraft airframe acquisition costs have been used extensively in advanced planning studies and contractor proposal validation. These models are designed to be used when little is known about an aircraft design or when a readily applied validity and consistency check of detailed cost estimates<sup>1</sup> is necessary. They require inputs that: (a) will provide results that are relatively accurate; (b) are logically related to cost; and (c) can easily be projected prior to actual design and development. The intent is to generate estimates that include the cost of program delays, engineering changes, data requirements, and phenomena of all kinds that occur in *e* normal aircraft program.

Since 1966, RAND has developed three parametric airframe cost models.<sup>2</sup> These models have been characterized by: (a) easily obtainable size and performance inputs (weight and speed); (b) the estimation of costs at the total airframe level; and (c) the utilization of heterogeneous aircraft samples. They have normally been updated when a sufficient number of additional aircraft data points has become available to suggest possible changes in the equations. Such is the case with the present effort: the A-10, F-15, F-16, F-18, F-101, and S-3 have been added to the full estimating sample.<sup>3</sup>

In addition to the expansion of the database, we also examined: (a) the utility of dividing the estimating sample into subsamples representing major differences in aircraft type (attack, fighter, bomber/transport); (b) the explanatory power of variables describing

<sup>1</sup>Examples of this latter application include the Independent Cost Analysis (ICA), prepared as part of the Defense Systems Acquisition Review Council (DSARC) process, and government analyses of contractor cost proposals during source selections.

 $^{3}$ Additionally, the F-86, F-89, and F3D, which were dropped from the DAPCA-III estimating sample, were reintroduced.

<sup>&</sup>lt;sup>2</sup>See Refs. 1, 2, and 3.

program structure and airframe construction techniques; and (c) the possible benefits of incorporating an objective technology measure into the fighter sample equations. In order to address the issue of sample homogeneity, each of the subsamples, as well as the full sample, had to be investigated in detail with the ultimate goal of developing representative sets<sup>4</sup> of cost estimating relationships (CERs) for each. The purpose of this Note is, therefore, to document the analysis of the bomber/transport subsample.

Section II provides brief descriptions of the database and statistical analysis methods. Section III gives some general indication, based on initial observations, of what can be expected in subsequent sections. Sections IV through XI provide, by cost element, data plots and each of the estimating relationships that meets our initial screening criterion with respect to variable significance. Section XII summarizes the main findings of the study. The appendix contains correlation matrixes.

<sup>&</sup>lt;sup>4</sup>A set encompasses the following cost elements: engineering, tooling, manufacturing labor, manufacturing material, development support, flight test, and quality control.

#### II. DATABASE AND ANALYTICAL APPROACH

A detailed description of the research approach, evaluation criteria, and database for this study may be found in R-3255-AF. However, in order that this Note may have a degree of self-sufficiency, a synopsis of the database and analytical approach is presented prior to the reporting of results.

#### ESTIMATING SAMPLE

The full bomber/transport estimating sample consists of the following eight "new design" aircraft:<sup>1</sup>

Model	First Flight Date <sup>2</sup>
B-52	1954
B-58	1957
B/RB-66	1954
C-5	1968
C-130	1955
C-133	1956
KC-135	1957
C-141	1963

<sup>1</sup>The classification of an aircraft as new or derivative is not an entirely objective procedure. For example, although the B/RB-66 evolved from the A-3, the B/RB-66 is classified as a new design in the database. "During the course of B/RB-66 development, more than 400 alterations were made, including a two-degree change in wing incidence, a reduction in the sweep angle of the inboard wing trailing edge to decrease thickness/chord ratio and minimize pitchup, and a completely new fuselage layout, and these changes, added to the specialized equipment demanded for the various B/RB-66 versions, resulted in a full-scale development project" (Ref. 4, p. 149).

<sup>2</sup>The first flight dates presented in this Note are intended to reflect the first flight date of the version of the aircraft that was most representative of the aircraft which was to become operational. Put another way, these dates are intended to reflect the first flight date of the developmental aircraft and not earlier experimental or prototype aircraft.

#### DEPENDENT VARIABLES

Costs have been dealt with at both the total program level<sup>3</sup> and at the major cost element level (engineering, tooling, manufacturing labor, manufacturing material, development support, flight test, and quality control).<sup>4</sup> The relative importance of the various cost elements is shown in Table 1 for four alternative production quantities. Other things being equal, the accuracy of the estimating relationship for manufacturing labor is of greatest concern because of the relatively large share of program cost represented by that cost element.

#### Table 1

#### PERCENTAGE BREAKDOWN OF BOMBER/TRANSPORT AIRFRAME PROGRAM COSTS (8 aircraft average costs)

		Quar	ntity	
Cost Element	25	50	100	200
Engineering	21	19	16	13
Tooling	23	20	17	14
Manufacturing labor	29	33	37	41
Manufacturing material	11	15	19	23
Development support	6	5	3	2
Flight test	7	5	4	3
Quality control	3	3	4	4
•	100	100	100	100

<sup>&</sup>lt;sup>3</sup>Total program costs are "normalized" values and not the actual reported dollar amounts. They are normalized in the sense that the dollar amounts for engineering, tooling, manufacturing labor, and quality control have been determined by applying fully burdened, industry-average labor rates to the hours reported for each category. <sup>4</sup>Cost element definitions are provided in Appendix A of R-3255-AF.

Engineering, tooling, manufacturing labor, and quality control are estimated in terms of manhours rather than dollars for two reasons: (a) it avoids the need to make adjustments for annual price changes, and (b) it permits comparison of real differences in labor requirements.<sup>5</sup> Manufacturing material, development support, and flight test do not lend themselves to this approach and were therefore estimated in terms of dollars (in this case, constant 1977 dollars).

#### POTENTIAL EXPLANATORY VARIABLES

To be included among the characteristics that were considered for inclusion in the CERs, a variable had to fulfill the following requirements:

- It had to be logically related to cost: that is, a rationale had to be constructed that would explain why cost should be influenced by the variable;
- 2. It had to be "readily available" in the early stages of aircraft conceptualization; and
- 3. It had to have an available historical record.

During the formulation stage of this study, twenty aircraft characteristics were identified as potential explanatory variables for the bomber/transport sample CERs. Values for these characteristics, which are grouped into four general categories--size, performance, construction, and program, are provided in Table 2. Based on this table, the following observations are made:

1. For any of the three size measures, the C-5 is approximately twice as large as the next largest aircraft in the sample.

<sup>&</sup>lt;sup>5</sup>The major limitation of the manhour approach is that it does not account for differences in overhead rates. Consequently, differences in such things as capital/labor ratios cannot be addressed.

Table 2

þ

# BOMBER/TRANSPORT AIRCRAFT CHARACTERISTICS

				Aircr	aft						
Characteristic	8-52	B-58	B/RB-66	C-5	C-130	C-133	KC-135	C-141	Mean	Standa rd Deviation	
Size Airframe unit weight (AUW) Empty weight (EW) Wetted area	112,672 177,816 16,650	32,686 55,560 5,450	30,496 42,549 4,372	279.145 320,085 30,800	43,446 58,107 7,590	96,312 114,690 13,150	70,253 97,030 10,770	104, 322 136, 900 14, 100	96, 167 125, 342 12, 860	80,723 91,004 8,426	,
Technical/performance Maximum speed Speed class (a) Climb rate Useful load fraction	551 5,120 .605	1,147 3 17,830 .659	548 5,000 .487	495 1 5,160 .555	326 326 3,900 .532	304 1 3,400 .617	527 5,900 .677	191 1 1,270 573.	549  589	260  1064	
Construction Design ultimate load factor Carrier capability designator (b) Engine location designator (c) Wing type (d) Wara to vetted area Ratio of EW-AUW/AUW Ratio of EW-AUW/AUW Ratio of avionics weight to AUW Number of black boxes	3.00 2 2 240 .540 .070 .070	3.00 2 2 3 3 3 3 3 3 3 3 3 3 70 N.A.	4.80 122 .178 .092 N.A.	3.75 22 2012 .15 .017 .017 .27	3.75 3.75 2 2 2 2 2 2 3 4 .34 .085	3.75 3.75 2 2 2 2 2 2 15 .03 16	3.75 2.75 .225 .38 N.A.	3.75 2 228 .228 .023 .023	3.69  -224 .043 222	0.56   031 031 	
Program Number of test aircraft Maximum tooling capability New engine designator (b) Contractor experience designator (e) Program type designator (f)	5-7 5 <u>0</u> 3 5-7 50 5-7 500 5-7 50 5-7 50 500 500 500 500 500 500 500 500 500	000 N∽ 8	400	000	<b>∞∞</b> ν νν	000	8 7 0	NO	26	۵°۵۰ ۱۱۱۱	
N.A. = Not available. (a)Speed class: $1 = 1ess than Mac (b)No = 1; Yes = 2. (c)Engine location: 1 = embedded(d)Wing type: 1 = straight; 2 = s(e)Yes = 1; No = 2.(f)Program type: concurrent = 1;$	<pre>ch .95; 2 in fusels wept; 3 prototype</pre>	= Mach age; 2 = = delta; e = 2.	.95 to Ma in nacel 4 = vari	ch 1.94; les under able swee	3 = Mach ving. p.	1.95 to	4ach 2.5.				

- 6 -

- 2. With regards to speed, all aircraft in the sample are subsonic with the exception of the B-58 which is a Mach 2 aircraft. Similarly, the B-58 rate of climb is over twice that of the next fastest climbing aircraft in the sample.
- 3. The sample does not include any aircraft which are both relatively large and relatively fast (such as the B-1A was to have been--airframe unit weight of approximately 150,000 pounds and speed of Mach 2--and the B-1B is to be--dash speed of about Mach 1.2).
- 4. All of the sample aircraft have engines located in nacelles under the wing and all are land-based. Thus, there is no variation in these two variables and they will not be considered further.
- 5. The B-58 flight test program utilized more than twice as many aircraft as the next largest program.

There are, of course, differences between the aircraft which are not accounted for in Table 2. Some of the differences relate to the way an aircraft is constructed (materials, manufacturing technology), others to the way the program is managed. In any case, it is difficult to find an aircraft without at least one unique aspect. Therefore, the following list is intended only to be indicative of the types of differences which are difficult to account for in a generalized parametric model.

- 1. The C-130 and C-133 are prop aircraft while all other sample aircraft utilize turbojet or turbofan engines.
- 2. The KC-135 was designed and produced more or less concurrently with the commercial 707 model.
- 3. The B/RB-66 was produced concurrently with the A-3, the aircraft from which it evolved.
- The B-58's utilization of honeycombed skin panels represented a major state-of-the-art advance.

5. The C-5 program utilized the acquisition concepts of total package procurement and concurrent development and production.

A priori notions regarding the effect an increase in the value of an explanatory variable might have on each of the cost elements are indicated in Table 3.

#### APPROACH

Potential explanatory variables have been divided into four general categories-size, performance, construction, and program (see Table 3). As discussed in R-3255-AF,<sup>6</sup> the "ideal" airframe cost estimating relationship would incorporate one explanatory variable from each category. Thus, there would be four independent variables per estimating relationship. For the full estimating sample, which has 34 observations, the possible incorporation of four independent variables presents no difficulties since there would still be 29 degrees of freedom left with which to estimate the error term. Unfortunately, the bomber/transport subsample has only eight observations and the incorporation of four explanatory variables would leave only three degrees of freedom with which to estimate the error term. Consequently, the number of explanatory variables considered per equation for the bomber/transport sample was tentatively limited to two.<sup>7</sup>

With respect to the specific combinations of variable categories examined, it is our understanding that all airframe manufacturers use some measure of size (usually weight) as their basic scaling dimension in developing cost estimates (although other factors frequently do enter in). Consequently, it did not seem unreasonable for a similar

<sup>6</sup>R. W. Hess and H. P. Romanoff, *Aircraft Airframe Cost Estimating Relationships: Study Approach and Conclusions*, The RAND Corporation, R-3255-AF, December 1987, Sec. IV.

<sup>7</sup>We do not mean to suggest that this limit is an "absolute" maximum for it is not (theoretically, one could use six explanatory variables for a bomber/transport equation and still have one degree of freedom left). It simply reflects our *judgment* regarding an appropriate balance between sample size and the potential number of explanatory variables.

- 8 -

Table 3

## EXPLANATORY VARIABLE INCREASE ON COST ELEMENT A PRIORI NOTIONS REGARDING EFFECT OF

Explanatory Variable	Engr.	Tooling	Mfg. Labor	Mfg. Material	Dev. Support	Fl ight Test	Quality Control	Total Program
Size Airframe unit weight (AUW) Empty weight (EW) Wetted area	+++	+++	+++	+++	+++	+++	+++	+++
Technical/performance Maximum speed Speed class (a) Climb rate Useful load fraction	+ + + +	+ + + +	+ + + +	+ + + +	+ + +	+ + +	+ + +	+ + + +
Construction Design ultimate load factor Wing type (b) Ratio of Wing area to wetted area Ratio of (EW-AUW)/AUW Ratio of avionics weight to AUW Number of black boxes	++ +++	+ 1	++1+++	+ +++	++ +++	+ +++	+ + +	++1+++
Program Number of test aircraft Maximum tooling capability New engine designator (c) Contractor experience designator (d) Program type designator (e)	(L) + +	; (f) ; (f)	ı +	+	5 (L) +	(f) 3 + + +	+	(f) ~++~
NOTE: A plus indicates a positive e be negligible is indicated by a blank, (a)Speed class: 1 = less than Mach (b)Wing type: 1 = straight; 2 = swe (c)No = 1; Yes = 2.	ffect; while while while to the second secon	a minus a an uncert = Mach .9 delta; 4	negati ain eff 5 to Ma = vari	ve effect. ect is ind ch 1.94; 3 able sweep	An effe icated by = Mach 1	ct which a quest .95 to M	vas thou ion mark. ach 2.5.	ght to

•

(d)Yes = 1; No = 2. (e)Program type: concurrent = 1; prototype = 2. (f)Not known whether total cost (prototype effort plus full-scale development) for prototype program is greater or less than for concurrent program.

assumption to be made on our part--a size variable must appear in all equations (except for flight test in which case the number of test aircraft is the mandatory variable). Therefore, with this additional restriction, the specific variable combinations that were examined for the bomber/transport sample are as follows:

#### Size Size/Performance Size/Construction Size/Program

The first step in developing a representative set of CERs was to identify all potentially useful estimating relationships for each cost element resulting from the variable combinations listed above. For this first step, "potentially useful" included only those estimating relationships in which all equation variables were significant at the 5 percent level. Since the number of variable combinations was relatively small, all possible regressions were run and screened for variable significance. Then, each equation satisfying this initial screening criterion was scrutinized in accordance with a set of evaluation criteria dealing with statistical quality and reasonableness of results (these are described in a subsequent subsection).

The final step was the selection of the most suitable estimating relationship for each cost element (i.e., the selection of a representative set). Generally speaking, other things being equal, we tried to select estimating relationships that satisfied the following conditions:

- Each variable is significant at the 5 percent level
- Variables taken collectively are significant at the 5 percent level
- Results are credible

Unusual residual patterns are absent

If these conditions were satisfied by more than one equation, then the objective was minimization of the standard error of estimate. Traditionally, cost analysts have *tried* to achieve a standard error of estimate of  $\pm 20$  percent or better. For logarithmic models, this is approximately equivalent to 0.18 ( $\pm 20$  percent,  $\pm 16$  percent). On the other hand, if the conditions were not satisfied by any of the equations, then none was recommended.

Multiple regression analysis was the technique used to examine the relationship between cost and the explanatory variables. Because of time restrictions, only one equation form was investigated--logarithmiclinear. The linear model was rejected because its main analytic property--constant returns to scale--does not correspond to real world expectations. Of the two remaining equation forms considered (logarithmic and exponential), the logarithmic model seemed most appropriate for the cost-estimation process since it minimizes relative errors rather than actual errors as in the exponential model.

Cost element categories which are a function of quantity were examined at a quantity of 100. Developing the estimating relationships at a given quantity rather than utilizing quantity as an independent variable in the regression analysis avoids the problem of unequal representation of air'craft (caused by unequal numbers of lots).

#### EVALUATION CRITERIA

The estimating relationships obtained in this analysis were evaluated on the basis of their statistical quality, intuitive reasonableness, and predictive properties.

#### Statistical Quality

Variable Significance. Variable significance was utilized as an initial screening device to reduce the number of estimating relationships requiring closer scrutiny. Normally, only those equations for which all variables were significant at the 5 percent level (onesided t-test) were reported in this Note. Occasionally, however, this criterion was relaxed in order that a useful comparison could be

- 11 -

provided. When an equation is reported for which not all equation variables are significant at the 5 percent level, it is denoted as follows:

#### VAR SIG: variable mnemonic

**Coefficient of Determination.** The coefficient of determination  $(R^2)$  was used to indicate the percentage of variation explained by the regression equation.

**Standard Error of Estimate.** The standard error of estimate (SEE) was used to indicate the degree of variation in the data about the regression equation. It is given in logarithmic form but may be converted into a percentage of the corresponding hour or dollar value by performing the following calculations:

(a) 
$$e^{+SEE} - 1$$
  
(b)  $e^{-SEE} - 1$ 

For example, a standard error of 0.18 yields standard error percentages of +20 and -16.

**F-Statistic**. The F-statistic was used to determine collectively whether the explanatory variables being evaluated affect cost. Those equations for which the probability of the null hypothesis pertaining was greater than 0.05 have been identified as follows:

Ľ,

I

Equations so identified were not considered for inclusion in the representative equation set.

**Multicollinearity**. Estimating relationships containing variable combinations with correlations greater than .70 are identified according to the degree of intercorrelation:

MCOL: r(variable mnemonic) > .7, .8, or .9

where the variable identified in parentheses is the equation variable showing the greatest collinearity. Generally speaking, estimating relationships with intercorrelations greater than .8 were avoided when selecting the representative equation set.

**Residual Plots.** Plots of equation residuals were given cursory examinations for unusual patterns. In particular, plots of residuals versus predictions (log/log) were checked to make sure that the error term was normally distributed with zero mean and constant variance. Additionally, plots of residuals versus time (log/linear) were examined to see whether or not the most recent airframe programs were over- or underestimated. The existence of such patterns resulted in one of the following designations:

RP: DIST (errors not normally distributed)
RP: CUR: OVER or UNDER (most recent aircraft over- or underestimated)

Generally speaking, we *tried* to avoid the use of estimating relationships with patterns in the representative equation set.

Influential Observations. "Cook's Distance" was utilized to identify influential observations in the least squares estimates. For this analysis, an influential observation was defined as one which if deleted from the regression would move the least squares estimate past the edge of the 10 percent confidence region for the equation coefficients. Such observations are identified as follows:

IO: aircraft identification

When an observation was consistently identified as influential, it was reassessed in terms of its relevance to the sample in question. If a reasonable and uniform justification for its exclusion could be developed, then the observation was deleted from the sample and the regressions rerun (in actuality, this occurred only once--when the B-58 was deleted from the bomber/transport sample). Otherwise, the influential observation was simply flagged to alert the potential user to the fact that its deletion from the regression sample would result in a significant change in the equation coefficients.

#### Reasonableness

I

The development of airframe cost-estimating relationships requires variable coefficients that provide both credible results and conform whenever possible to the normal estimating procedures employed by the airframe industry. Such credibility and conformity are reflected in both the signs of the variable coefficients as well as their magnitudes.

**Exponent Sign**. Estimating relationships for which the sign of the variable coefficient was not consistent with a priori notions (see Table 3) are identified in the following manner:

#### EXP SIGN: variable mnemonic

Estimating relationships containing such inconsistencies were not considered for inclusion in the representative equation set.

**Exponent Magnitude.** Close attention was also paid to the magnitude of variable coefficients. This applied to exponents which were felt to be too small as well as those which were felt to be too large. Estimating relationships containing such variable coefficients are identified as follows:

#### EXP G: variable mnemonic

While determinations of this kind are largely subjective, there was one application that was fairly objective. Traditionally, size variables have always provided returns to scale in the production-oriented cost elements (tooling, labor, material, and total program cost). That is, increases in airframe size are accompanied by less than proportionate increases in cost. If the opposite phenomenon is observed, then it is generally believed to be the result of not adequately controlling for differences in construction, materials, complexity, and/or other miscellaneous production factors. Consequently, equations possessing a size-variable coefficient greater than one were always flagged.

When selecting a representative equation set, we generally tried to avoid estimating relationships containing variables with exponents that we felt were either too large or too small (that is, exponents that placed either too much or too little emphasis on the parameter in question). More restrictively, for the production-oriented cost elements, no estimating relationship possessing a size-variable exponent greater than one was considered for a representative equation-set.

#### **Predictive Properties**

Confidence in the ability of an equation to accurately estimate the acquisition cost of a future aircraft is in large part dependent on how well the acquisition costs of the most recently produced aircraft are estimated. Normally, statistical quality and predictive capability would be viewed as one and the same. Unfortunately, when dealing with airframe costs this is not always the case; our knowledge of what drives airframe costs is limited and the sample is fairly small in size and not evenly distributed with respect to first flight date (see Fig. 1). Consequently, the estimating relationships were also evaluated on the basis of how well costs for a subset of the most recent aircraft in the database are estimated.

An indication of an equation's predictive capability would usually be obtained by excluding a few of the most recent aircraft from the regression and then seeing how well (in terms of the relative deviation) the resultant equation estimates the excluded aircraft. However, in



Fig. 1-Number of first flight events as a function of the year of first flight

this case, the small sample size precluded this option. Consequently, the measure of predictive capability used in this analysis was the average of the absolute relative deviations for the E-52, C-5, and C-141. These relative deviations were determined on the basis of the predictive form of the equation and not the logarithmic form used in the regression.<sup>8</sup>

<sup>8</sup>If cost is estimated in a log-linear form, such as

$$\ln \text{ COST} = \beta_0 + \beta_1 \ln \text{ WEIGHT} + \beta_2 \ln \text{ SPEED} + \ln \epsilon$$

the expected cost is given by

$$COST = \begin{pmatrix} \beta_0 & \beta_1 & \beta_2 \\ e & WEIGHT & SPEED \end{pmatrix} e^{\frac{3}{2}/2}$$

where  $\hat{\sigma}^2$  is the actual variance of  $\epsilon$  in the log-linear equation. Since the actual variance is not known, the standard error of the estimate may be used as an approximation.

#### **III. INITIAL OBSERVATIONS**

This section provides an initial overview of the individual cost element analyses which follow.

#### INFLUENTIAL OBSERVATIONS

#### The B-58

Preliminary data analysis consistently identified the B-58 as an influential observation. This is not altogether surprising since it is a relatively small, supersonic aircraft while the remaining bombers and transports are relatively large, subsonic aircraft. Furthermore, an examination of the data plots, especially the engineering, material, development support, and total program cost plots, shows the B-58 to be considerably more expensive on a per pound basis than the other bomber/transport aircraft. Consequently, the B-58 has been excluded from our analysis of the bomber/transport sample.

A comparison of a few of the key variables for the full bomber/transport sample and the sample excluding the B-58 is provided in Table 4. As indicated, by excluding the B-58 from the sample, most of the variation in speed, climb rate, and number of test aircraft is lost.

#### The B/RB-66 and C-5

The B/RB-66 and C-5, because they are at the extremes of the bomber/transport sample with respect to size, are also consistently identified as influential observations in nearly every equation documented in this Note. This point is easily visualized from the representative data plot provided in Fig. 2. However, we did not feel that size alone was a sufficient reason for excluding the aircraft. Furthermore, note that any attempts to develop simple scaling relationships without the B/RB-66 and C-5 are likely to prove futile since four of the five remaining aircraft (KC-135, B-52, C-133, and C-141) tend to line up vertically with respect to weight (dashed box in Fig. 2). Table 4

# COMPARISON OF FULL BOMBER/TRANSPORT SAMPLE AND SAMPLE EXCLUDING B-58

	2	lean	Sta Dev	nda rd 'i at i on	Rang	je
Variable	Full Sample	Excluding B-58	Full Sample	Excluding B-58	Full Sample	Excluding 8-58
Airframe unit weight (1b) Empty weight (1b)	96, 167 125, 342	105,235	80, 723 91,004	82,672 93,458	30,496-279,145 42.549-320.085	30, 496-279, 145 42, 549-320, 085
Wetted area (sq ft)	12,860	13,919	8,426	8,506	4,372-30,800	4,372-30,800
speed (KII) Slimb 2010 (St/min)	644	163	260	104	304- 1,147	304- 551
CLIMO Fate (Ft/min)	6, <u>6</u> 98	101, 4	4,650	1,2/1	3,400-17,830	3,400- 7,270
USETUI 1080 FLACTION	. 589	615.	.064	.062	.487677	.487677
Ratio of wing area to wetted area	.224	.215	.031	.022	.178283	.178240
AVAUW (a)	.043	.043	.031	.031	.017092	.017092
EWAUW	. 38	. 34	. 18	14	. 15 70	. 15 58
Number of test aircraft	12	10	80	£	5- 30	5- 14
Contraction of the second seco						

(a)No difference in statistics for AVAUW because B-58 value is missing.



Fig. 2-Effect of B/RB-66 and C-5

#### PERFORMANCE VARIABLES

Only five equations were determined in which both the size and performance variables were significant at the 5 percent level (two for the engineering cost element, one for tooling, and two for manufacturing material). However, in four of the five cases, the size of the performance variable exponent was counterintuitive, and in the fifth case, the equation as a whole was not significant at the 5 percent level. As stated previously, by excluding the B-58 from the sample, most of the variation in the performance variables was lost.

#### CONSTRUCTION/PROGRAM VARIABLES

The construction/program variables proved to be of little help in improving the quality of the bomber/transport estimating relationships. There were seven instances where such variables were found to be significant at the 5 percent level but, in each case, the overall equations did not produce results that we viewed as credible.

- 19 -

#### IV. ENGINEERING

Engineering hours per pound are plotted as a function of airframe unit weight in Fig. 3. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 5. General observations regarding these equations are as follows:

- The exponents of the size variables in Equations E1, E2, and E3 are all greater than one. An examination of Fig. 2 suggests that this is due in large part to a single aircraft--the C-5 (that is, deletion of the C-5 would result in an equation with a size exponent of less than one).
- 2) Only one performance variable was found to be significant at the 5 percent level in combination with a size variable--the useful load fraction (USELD). However, in each instance, the sign of its exponent is counterintuitive.
- 3) The magnitude of the contractor experience designator (EXPDV) in Equations E7 and E8 seems unreasonably large. For example, a contractor without experience would incur engineering costs 75 to 80 percent greater than a contractor with experience.
- 4) None of the estimating relationships listed in Table 5 is recommended. Although the three size-only equations have fair statistical qualities, their slope is determined largely by a single aircraft--the C-5.

- 20 -



Fig. 3-Engineering hours per pound as a function of airframe unit weight

ŗ.

C

K

Table 5ENGINEERING HOUR ESTIMATING RELATIONSHIPS(Bomber/transport sample excluding B-58)	
--	--

È.

P

$0:$ Equation $R$ SEE $\Gamma$ $N$ $O$			S	tati	stics		Relat	tive De	viations	(%)	
$\frac{31.E}{100} = \cdot 002 \ \frac{1}{0001} (3) $	<u></u>	Equation	~ ~	SEE	u	z	B-52	c-5	C-141	Abs Avg	Comments
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		<u>SIZE</u> ENGR = .105 AUW 100 = (.001)(a)	88.	. 29	37	~	7 1	+16	0	-	10:C-5,C-130,C-133,KC-135
3 $\operatorname{EKR}_{100} = \cdot \cdot 16^{5} \operatorname{WTARE}_{1.001}^{1.18}$ $\cdot 87$ $\cdot 30$ $35$ $7$ $-15$ $+24$ $+2$ $14$ $10 \cdot 100 \cdot 135, \mathrm{C} - 5, \mathrm{C} - 130, \mathrm{C} - 133, \mathrm{C} - 130, \mathrm{C} - 130,$	N	ENGR = .0446 EW 100 (.001)	.86	.31	32	٢	-28	+23	ī	17	10: C-5, C-130, KC-135
SIZE/PERFORMANCE         4.       ENGR $= .0103$ AUW $1.12$ USELD $1.94$ $.22$ $34$ $7$ $+4$ $-2$ $0$ $2$ VAR SIG:USELD         5       ENGR $= .0103$ AUW $(.001)$ $(.052)$ $.94$ $.22$ $34$ $7$ $+4$ $-2$ $0$ $2$ VAR SIG:USELD         5       ENGR $= .00242$ EW $(.001)$		1.18 ENGR = .165 WTAREA 100 (.001)	.87	.30	35	٢	-15	+24	2+	14	10:RB-66,C-5,C-130,C-133, KC-135
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		SIZE/PERFORMANCE									
5 $\operatorname{ENGR}_{100} = .00242 \operatorname{EW}_{(-001)}^{1.21} \operatorname{USELD}_{(-001)}^{2.22}$ .94 .23 32 7 -20 +5 0 8 EXP SIGN:USELD 6 $\operatorname{ENGR}_{100} = .00538 \operatorname{WTAREA}_{(-001)}^{1.38} \operatorname{USELD}_{(-004)}^{2.644}$ .98 .13 111 7 -4 +1 +3 3 EXP SIGN:USELD 7 $\operatorname{ENGR}_{(-000)}^{-1.038} \operatorname{WTAREA}_{(-001)}^{-1.38} \operatorname{USELD}_{(-004)}^{-2.644}$ .98 .13 111 7 -4 +1 +3 3 EXP SIGN:USELD 8 $\operatorname{ENGR}_{(-001)}^{-1.38} \operatorname{USELD}_{(-004)}^{-2.644}$ .98 .13 111 7 -4 +1 +3 3 EXP SIGN:USELD 9 $\operatorname{UO0} = .0250 \operatorname{AUW}_{-100}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.33}$ .94 .23 33 7 +2 +12 +1 7 $\operatorname{VAR}_{-126}^{-6.6, C-130}$ .5135, 1 $\operatorname{ENGR}_{(-001)}^{-1.053}$ .94 .23 33 7 +2 +12 +1 7 $\operatorname{VAR}_{-126}^{-130, C-130}$ .5136 $\operatorname{VAR}_{-136}^{-1.26} \operatorname{UOV}_{-130}^{-1.21}$ .51 $\operatorname{UO1}_{-1.053}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-130}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-1001}^{-1.21} \operatorname{EXPDV}_{-120}^{-5.6-130} \operatorname{UO1}_{-1.21}^{-1.21} \operatorname{EXPDV}_{-130}^{-1.21} \operatorname{EXPDV}_{-1.21}^{-1.21} \operatorname{EXPDV}_{-1.21}^{-1.$	<b>.</b>	1.12	.94	. 22	34	~	7+	- 2	0	2	VAR SIG:USELD EXP SIGN:USELD EXP MAG:USELD 10:RB-66,C-130
6 ENGR = .00538 WTAREA <sup>1.38</sup> <sup>-2.64</sup> .98 .13 111 7 -4 +1 +3 3 EXP SIGN:USELD (.000) (.004) (.004) (.001) (.001) (.001) (.001) (.003) 7 ENGR MAG: USELD $SIZE/CONS^{T}UCTION_PROGRAM$ 7 ENGR = .0250 AUW <sup>1.13</sup> EXPDV (.001) (.053) 8 ENGR = .00758 EW <sup>1.21</sup> EXPDV (.001) (.053) 8 ENGR = .00758 EW <sup>1.21</sup> EXPDV (.001) (.053) 9 ENGR = .00758 EW <sup>1.21</sup> EXPDV (.001) (.053) 1.12 EXPDV (.001) (.053) 1.24 28 7 -23 +19 +7 16 VAR SIG: EXPDV (.001) (.053) (.001) (.053) (.051) $(.053)(.051)$ $(.053)(.001)$ $(.052)(.001)$ $(.053)(.001)$ $(.053)(.001)$ $(.052)(.001)$ $(.053)(.001)$ $(.052)(.001)$ $(.052)$ $(.001)$ $(.052)$ $(.001)$ $(.052)$ $(.001)$ $(.052)$ $(.001)$ $(.052)$	5	ENGR = .00242 EW USELD 100 (.001) (.040)	46.	.23	32	1	-20	+5	0	Ø	EXP SIGN:USELD EXP MAG:USELD 10:RB-66,C-130
$\frac{\text{SIZE/CONSTRUCTION, PROGRAM}{\text{TOOM} \text{ EVEN}}$ $\frac{1.13}{100} = .0250 \text{ AUW} \text{ EXPDV} (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.001) (.053) \\ (.053) \\ (.001) (.001) (.053) \\ (.001) (.001) (.053) \\ (.001) (.001) (.001) \\ (.001) (.001) (.001) (.001) \\ (.001) (.001) (.001) \\ (.001) (.001) (.001) \\ (.001) (.001) (.001) (.001) \\ (.001) (.001) (.001) (.001) \\ (.001) (.001) (.001)$	6	ENGR = .00538 WTAREA USELD 100 (.000) (.004)	. 98	. 13	11	٢	* -	Ŧ	۴ ۲	e	EXP SIGN:USELD EXP MAG:USELD 10:RB-66,C-130,C-133,
7 $ENGR_{100} = .0250 AUW_{1001} EXPDV_{1001} (.053)$ .94 .23 33 7 +2 +12 +7 7 VAR SIG: EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{101F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{1001F1; EXPDV_{101F1; EXPDV_{1001F1; E		SIZE/CONSTRUCTION, PROGRAM									KC-135
8 ENGR = .00758 EW EXPDV 100 = .00758 EW EXPDV 100 (.001) (.053) .24 28 7 -23 +19 +7 16 VAR SIG: EXPDV EXP MAG: EXPDV LD1FF: EXPDV 10: RB-66, C-5, C-130	1	ENGR = .0250 AUW EXPDV 100 (.001) (.053)	46.	. 23	33	٢	42	+12	L+	٢	VAR SIG:EXPDV EXP MAG:EXPDV LDIFF:EXPDV 10:RB-66,C-5,C-130
	æ	ENGR = .00758 EW EXPDV 100 = .00158 (.001) (.053)	.93	<b>42</b> .	28	4	-23	+19	L+	16	VAR SIG:EXPDV EXP MAG:EXPDV LDIFF:EXPDV 10:RB-66,C-5,C-130

- 22 -

#### V. TOOLING

Tooling hours per pound are plotted as a function of airframe unit weight in Fig. 4. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 6. General observations regarding these equations are as follows:

- Of the five equations listed for tooling hours, none, when taken as a whole (F-test), is significant at the 5 percent level.
- 2) The economies of scale produced by the size variable exponents in Equations T1 through T5 seem somewhat excessive. For example, in Equation T1, a doubling of the airframe unit weight results in only a 32 percent increase in tooling hours. This result is driven largely by the smallest and largest aircraft in the database--the B/RB-66 and the C-5. Furthermore, if these two aircraft were excluded from the sample then no discernible trend would exist (see Fig. 4).
- None of the size/construction program variable combinations examined satisfied our initial screening criterion with respect to variable significance.
- None of the estimating relationships listed in Table 6 is recommended.

- 23 -



k

Fig. 4-Tooling hours per pound as a function of airframe unit weight

		ŝ	tatisl	ics		Relat	ive De	viations	(%)	
<u>.</u>	Equation	~~~	SEE	· ·	z	B-52	C-5	C-141	Abs Avg	Comments
=	<u>SIZE</u> TOOL = 163 AUW 100 (.061)	14.	. 38	ŝ	7	+24	41+	-65	34	VAR SIG:AUW EQ SIG:F-TEST EXP MAG:AUW
12	T001 ≈ 76.3 EW 100 ≈ 0.045)	.47	.36	4	7	117	+15	-65	32	10:RB-66,C-5,G-130,G-141 EQ SIG:F-TEST EXP MAG:EW C2101 C-101
13	100L = 248 WIAREA 100 (.076)	.36	04.	ŝ	٢	+21	+19	-64	35	VAR SIG:WTAREA VAR SIG:WTAREA EQ SIG:F-TEST EXP MAG:WTAREA
14	<u>SIZE/PERFORMANCE</u> .364 1.03 TOOL ± .462 AUM SP 100 ± .0471	. 73	. 29	ŝ	2	+10	+13	-73	32	EQ SIG:F-TEST EXP MAG:AUW
51	TOOL	.72	.30	5	~	9+	+16	-72	31	VAR SIG: WTAREA EQ SIG: F-TEST
	<u>SIZE/CONSTRUCTION, PROGRAM</u> None									EXP MAG: WIAKEA 10: RB-66, C-5, C-141

Table 6 TOOLING HOUR ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58) - 25 -

#### VI. MANUFACTURING LABOR

Manufacturing labor hours per pound are plotted as a function of airframe unit weight in Fig. 5. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 7. General observations regarding these equations are as follows:

- None of the size/performance combinations examined satisfied our initial screening criterion with respect to variable significance.
- 2) The magnitude of the wing area to wetted area (WGWET) exponents in Equations L4 through L6 seems unreasonably large--a 50 percent increase in the ratio of wing area to wetted area results in 50 to 60 percent fewer manufacturing labor hours.
- 3) The fit of the three size-only equations (L1, L2, and L3) is determined largely by the B/RB-66. If the B/RB-66 were excluded from the sample, no discernible trend would exist (see Fig. 5).
- None of the estimating relationships listed in Table 7 is recommended.

**i**e



ŧ

Fig. 5-Manufacturing labor hours per pound as a function of airframe unit weight

Table 7

.

l

•

•

## MANUFACTURING LABOR HOUR ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58)

			Stati	stics		Relat	ive De	viations	(%)	
Eq. No.	Equation	в 2	SEE	L.	z	B-52	C-5	C-141	Abs Avg	Comments
	<u>SIZE</u>									
Ē.	LABR = 16.1 AUW 100 (.003)	.80	.27	20	7	6+	+16	<b>h</b> #-	23	10:RB-66, C-5, C-141
L2	LARR = 8.81 EW 100 (.004)	.78	.28	18	٢	tı -	+21	<b>h</b> tı -	23	10:RB-66,C-5,C-141
L3	LABR = 31.5 WTAREA 100 = (.008)	.72	. 32	13	7	+	+24	-43	23	10:RB-66,C-5,C-130
	SIZE/PERFORMANCE									
	None									
	SIZE/CONSTRUCTION, PROGRAM									
L4	LABR = .669 AUW WGWET -1.67 100 (.002) (.064)	.89	.22	17	2	+25	₹ +	-29	19	VAR SIG:WGWET EXP MAG:WGWET 10:B-52,RB-66,C-5
۲2	.813 -2.13 LABR = .107 EW WGWET 100 (.001) (.020)	.93	21.	28	2	117	+3	-25	15	EXP MAG:WGWET 10:B-52,RB-66,C-5
PT	.894 -2.40 LABR = .205 WTAREA WGWET 100 (.002) (.026)	.90	.21	18	7	+25	Ŧ	-22	16	EXP MAG: WGWET 10: 8-52, RB-66

- 28 -

#### VII. MANUFACTURING MATERIAL

Manufacturing material cost per pound is plotted as a function of airframe unit weight in Fig. 6. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 8. General observations regarding these equations are as follows:

- The magnitude of the size variable exponent is greater than one for all equations listed in Table 8.
- 2) With the exception of the EW/USELD and WTAREA/USELD combinations documented in Equations M4 and M5, none of the size/performance combinations examined satisfied our initial screening criterion relative to variable significance. Furthermore, for the two combinations which did meet our initial criterion, the sign of the performance variable (USELD) exponent is counterintuitive.
- 3) None of the size/construction, program variable combinations examined satisfied our initial screening criterion with respect to variable significance.
- None of the estimating relationships listed in Table 8 is recommended.



Fig. 6-Manufacturing material cost per pound as a function of airframe unit weight

•

ŀ

MANUFACTURING MATERIAL COST ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58)

Table 8

EXP MAG: AUW 10: B-52, C-5, C-130, C-133 EXP MAG: EW 10:C-5,C-130,C-133 EXP MAG:WTAREA 10:RB-66, C-5, C-133 Comments Abs 15 16 11 Relative Deviations (%) C-141 -10 -12 ĥ C-5 +10 +18 +20 **B-5**2 +25 +16 77 ~ ~ z ~ Statistics ι. 33 77 34 SEE .39 . 38 . 34 ~ ~ .87 .90 .87 1.48 = .0417 EW (.001)1.26 = .194 AUW (.001) 100 = .306 WTAREA Equation MATL SIZE

Еq. No.

Ξ

Ω

щ

EXP SIGN:USELD EXP MAG:EW EXP MAG:USELD 10:RB-66,C-130,C-133, KC-135 EXP SIGN:USELD EXP MAG:WTAREA EXP MAG:USELD 10:C-133,KC-135 12 2ŝ +23 ~ 36 .28 .95 ) -2.75 USELD (.039) MATL = .00870 WTAREA 1.69 100 = .00870 WTAREA 1 MATL -Ж

~

-10

ř

+10

~

41

.26

.95

0 = .00197 EW USELD 0 (.000) (.049)

Ť

SIZE/PERFORMANCE

SIZE/CONSTRUCTION, PROGRAM

None

- 31 -

#### VIII. DEVELOPMENT SUPPORT

Development support cost per pound is plotted as a function of airframe unit weight in Fig. 7. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 9. General observations regarding these equations are as follows:

- None of the size variables in the size-only equations (D1, D2, and D3) is significant at the 5 percent level.
- None of the size/performance combinations examined satisfied our initial screening criterion relative to variable significance.
- 3) The sign of the construction variable (BLBOX) in Equation D4 is counterintuitive.
- None of the estimating relationships listed in Table 9 is recommended.
- 5) An examination of development support cost as a percentage of nonrecurring engineering cost was also made and is summarized in Table 10.<sup>1</sup> Unfortunately, the percentages span an order of magnitude--from a low of 13 percent to a kigh of over 130 percent.<sup>2</sup> Consequently, this percentage method of estimating development support cost is not recommended.

#### - 32 -

<sup>&</sup>lt;sup>1</sup>Nonrecurring engineering cost is a logical denominator since the mockups and test articles that make up development support are required for the airframe design effort.

<sup>&</sup>lt;sup>2</sup>Note that the three aircraft with the lowest development support percentages are all Lockheed aircraft.



Fig. 7-Development support cost per pound as a function of airframe unit weight

Table 9

6

ŀ

•

ŀ

DEVELOPMENT SUPPORT COST ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58)

		s l	tatis	tics		Relat	ive De	ev i a t i ons	(%)	
Eq. No.	Equation	~ ~	SEE	1 -	Z	B-52	C-5	C-141	Abs Avg	Comments
	SIZE									
10	. 741 DS = 18.0 AUW (.057)	.42	.68	4	7	9 +	-41	-98	418	VAR SIG: AUW EQ SIG: F-TEST LO.BP-66 C-130
02	.804 DS = 6.98 EW (.052)	44.	.67	t	7	-10	- 34	-98	47	10. NB-00, 0-130 VAR SIG: EW EQ SIG: F-TEST 10: RB-66, 0-130
D3	.790 DS = 49.9 WTAREA (.080)	.35	.72	3	7	-5	-26	-98	42	VAR SIG:WTAREA EQ SIG:F-TEST 10:RB-66.G-130
	SIZE/PERFORMANCE None									
75	SIZE/CONSTRUCTION, PROGRAM DS = .00301 EW BLB0X (.014) (.053)	.86	. 43	0	Q	+16	<i>1</i> 19-	+16	32	VAR SIG:BLBOX EXP SIG:BLBOX EXP SIGN:BLBOX EXP MAG:EU EXP MAG:BLBOX MCOL: r > .7 MCOL: r > .7

- 34 -

#### Table 10

#### DEVELOPMENT SUPPORT COST AS A PERCENTAGE OF UNIT 1 ENGINEERING COST

Aircraft	Unit 1 Engineering Hours	Unit 1 Engineering Cost (\$M)(a)	Development Support Cost (\$M)	Dev Support as a Percentage of Unit 1 Engr Cost
B-52	5,800,000	159.5	105.5	66
B-58	3,150,000	86.6	165.1	191
B/RB-66	1,600,000	44.0	53.0	120
C-5	23,200,000	651.8	138.5	21
C-130	3,350,000	92.1	12.3	13
C-133	3,000,000	82.5	101.6	123
KC-135	2,500,000	68.8	90.6	132
C-141	6,800,000	187.0	47.5	25

(a)At \$27.50 per hour.

#### IX. FLIGHT TEST

Flight test cost per aircraft is plotted as a function of the quantity of flight test aircraft in Fig. 8. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 11. As indicated, we were not able to identify any estimating relationships which satisfied our initial screening criterion relative to variable significance.

- 36 -

- 37 -



Natural logarithm of quantity of flight test aircraft

Fig. 8-Flight test cost per test aircraft as a function of the quantity of flight test aircraft

0

Table 11

•

Ð

# FLIGHT TEST COST ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58)

		S	tatis	tics		Relat	ive De	eviations	(%)	
Eq. No.	Equation	R 2	SEE	u	z	<b>B-</b> 52	C-5	C-141	Abs Avg	Comments
	<u>IESTAC</u> .725									
E	FT = 14/00 TESTAC (.273)	.08	. 93	0	~	+68	-22	-17	36	VAR SIG: TESTAC EQ SIG: F-TEST 10: B-52, RB-66, C-141
	SIZE/TESTAC									
	None									
	PERFORMANCE/TESTAC									
	None									
	TESTAC/CONSTRUCTION, PROGRAM									

None

#### X. QUALITY CONTROL

Quality control hours per pound are plotted as a function of airframe unit weight in Fig. 9. The data, which do not fit any obvious patterns, are available for only five aircraft (four excluding the B-58). Consequently, regression analysis does not seem appropriate. However, since quality control is closely related to direct manufacturing labor, it can be estimated as a percentage of same. The ratio of cumulative quality control hours to cumulative manufacturing labor hours is as follows:

Aircraft	Ratio (at Q=100)
B-52	.095
B-58	. 163
C-5	.097
C-141	.054
KC-135	. 103
Average, all aircraft	. 102
Average, excluding B-58	. 087

Excluding the B-58, the ratio of cumulative quality.control hours to cumulative manufacturing labor hours spans a range of 5.4 percent to 10.3 percent with an average of 8.7 percent.

#### - 39 -



Fig. 9-Quality control hours per pound as a function of airframe unit weight

#### XI. TOTAL PROGRAM COST

Total program cost per pound is plotted as a function of airframe unit weight in Fig. 10. Estimating relationships in which all equation variables are significant at the 5 percent level are provided in Table 12. General observations regarding these equations are as follows:

• Only one size/performance variable combination (EW/USELD) satisfied our initial screening criterion relative to variable significance. However, the sign of the performance variable exponent is counterintuitive.

e

- Only one size/construction, program variable combination satisfied our initial screening criterion relative to variable significance. However, the magnitude of the construction variable (AVAUW) exponent seems too large--each doubling of the avionics weight to airframe unit weight ratio results in a 32 percent increase in total program cost. Such a result may be reasonable for fighters but does not seem so for large, subsonic aircraft.
- The fit of the three size-only equations (P1, P2, and P3) is determined largely by the B/RB-66. If the B/RB-66 were excluded from the sample, no discernible trend would exist (see Fig. 10).
- None of the estimating relationships listed in Table 12 is recommended.

- 41 -



le

•

l

ŀ

Fig. 10-Total program cost per pound as a function of airframe unit weight

Table 12 M COST FETIMATING RELATION

TOTAL PROGRAM COST ESTIMATING RELATIONSHIPS (Bomber/transport sample excluding B-58)

		St	atis	tics		Relati	ve Dev	iations	(%)	
Eq. No.	Equation	× ~	SEE	ш	z	B-52	c-5	C=141	Abs Avg	Comments
	SIZE									:
Ы	761 PROC = 385 AUW 100 (.002)	. 83	.27	74	٢	+18	+16	- 38	24	10:RB-66,C-5,C-141
P2	.817 PROG = 163 EW 100 (.002)	.85	. 25	28	٢	-12	+21	- 38	21	10:RB-66,C-5,C-141
P3	.857 PROG = 699 WTAREA 100 (.004)	.77	.31	17	7	+12	+23	-36	24	10:RB-66, C-5
Ρţ	<u>SIZE/PERFORMANCE</u> .927 -1.70 PROG = 17.4 EW USELD 100 (.001) (.054)	. 93	.20	25	~	6+	9+	- 38	18	VAR SIG:USELD EXP SIG:USELD EXP MAG:USELD IO:RB-66,C-5,KC-135
	SIZE/CONSTRUCTION, PROGRAM									
P5	.991 .406 PROG = 112 AUW AVAUW 100 (.004) (.051)	44.	.20	24	9	-16	+17	-22	18	VAR SIG:AVAUW 10:B-52,RB-66,C-5 EXP MAG:AVAUW

#### XII. CONCLUSIONS

We were not able to identify any acceptable estimating relationships for any of the individual cost elements or for total program cost. We suggest that users develop estimates for proposed bomber/transport aircraft either on the basis of analogy (using the data provided in this volume) or by using the equation set developed for all mission types.

We believe that our inability to develop a set of statistically derived cost-estimating relationships for bomber/transport aircraft is the result of a sample that is both small and not as homogeneous as it appears at first glance. For example:

- The B-58 is a Mach 2 aircraft while all other aircraft in the sample are subsonic;
- The C-130 and C-133 are propeller-driven aircraft;
- The B/RB-66 and KC-135 were evolutionary developments;
- The B-52 was into its fourth series (the "D" version) by the time 100 aircraft had been produced;
- The C-141 had a very large percent of subcontract effort (approximately 50 percent), which may have distorted the distribution of equivalent in-plant cost (Ref. 2, p. 50);
- The C-5 program utilized the acquisition concepts of total package procurement and concurrent development and production.

Given this amount of diversity in so small a sample, it would have been surprising if we had been able to develop a credible set of CERs.

#### COST-QUANTITY SLOPES

10

Minimum, maximum, and average cost-quantity slopes for the bomber/transport subsample (excluding the B-58) are provided in Table 13

#### - 44 -

#### - 45 -

#### Table 13

#### CUMULATIVE TOTAL COST QUANTITY SLOPES

	Engineering	Tooling	Mfg Labor	Mfg Material	Quality Control	Total Program
Number of observations	7	7	7	7	4	7
Range (%)	110-116	108-122	146 <b>-</b> 168	160-182	146-158	, 130-138
Average (%)	114	114	154	168	152	136
Exponent	. 189	. 189	.623	.748	.604	.444

NOTES: Results are based on first 200 units; sample excludes B-58; cumulative average slope = cumulative total slope divided by two.

#### FULLY BURDENED LABOR RATES

All cost elements estimated directly in dollars are in 1977 dollars. Suggested 1977 fully burdened hourly labor rates (and those used to estimate total program cost) are:

Engineering	27.50
Tooling	25.50
Manufacturing labor	23.50
Quality Control	24.00

For estimates in 1986 dollars, the following hourly labor rates and adjustment factors are suggested:

Engineering	59.10
Tooling	60.70
Manufacturing labor	50.10
Quality control	55.40
Manufacturing material (index)	1.94
Development support (index)	1.94
Flight test (index)	1.94
Total program (index)	2.13

	Hour	ly Rates (\$)	
Labor Category	Average	Range	Range About Average (%)
Engineering	59.10	47.70-70.00	-19, +18
Tooling	60.70	56.50-65.00	7, +7
Manufacturing labor	50.10	41.70-58.00	-17, +16
Quality control	55.40	49.10-62.60	-11, +13

The 1986 labor rates are based on data provided by seven contractors:

Note that with the exception of tooling, the range about the average rate is at least ±10 percent. Such differences could arise from differences in accounting practices, business bases, and capital investment. Irrespective of cause, however, labor rate variation is one more component of a larger uncertainty which already includes the error associated with statistically derived estimating relationships and questions about the proper cost-quantity slope. Furthermore, in addition to the inter-contractor differences, these rates are also subject to temporal change--accounting procedures, relative capital/labor ratio, etc. Thus, the 1986 fully burdened rate is qualitatively different from the 1977 rate. Unfortunately, trying to estimate the magnitude of such quality changes, even very crudely, is a study in itself and beyond the scope of this analysis.

The material, development support, and flight test escalation indexes are based on data provided in AFR 173-13.<sup>1</sup> For the years 1977-1984, the airframe index presented in Table 5-3 ("Historical Aircraft Component Inflation Indices") was used. For the years 1985 and 1986, the aircraft and missile procurement index presented in Table 5-2 ("USAF Weighted Inflation Indices Based on OSD Raw Inflation and Outlay Rates") was used. The total program cost adjustment factor was then determined on the basis of a weighted average (at Q = 100) of the individual cost elements.

<sup>1</sup>See Ref. 6.

- 46 -

#### Appendix

#### CORRELATION MATRIXES

This appendix contains correlation matrixes for the full bomber/transport estimating sample. Table A.1 provides Pearson correlation coefficients for all possible pairwise combinations of dependent and independent variables. Table A.2 provides coefficients for all possible pairwise combinations of independent variables.

-	48	-

#### Table A.1

#### CORRELATION MATRIX: COST VARIABLES WITH POTENTIAL EXPLANATORY VARIABLES

EXPLANATORY			COST VA	RIABLE	S		
VARIABLES	ln ENGR	ln TOOL	In LABR	ln MATL	In OS	ln FT	In PROG
<u>SIZE</u>							
In AUW	0.5 <b>8</b>	0.37	0.80	0.71	0.35	0.11	0.66
In EW	0.63	0. <b>46</b>	0.83	0.77	0. <b>4</b> 2	0.26	0.72
In WTAREA	0. <b>58</b>	0.35	0.77	0.72	0.31	0.14	0.64
PERFORMANCE							
In SP	<u>0</u> 39	0.64	0.11	0.33	0.55	0.72	0.41
Im SPCLS	0.42	0.36	- 0.02	0.23	0.41	0.61	0.28
In CLIMB	0.45	0.43	0.00	0.32	0.43	0.62	0.32
In USELD	0.28	0.24	0.06	0.25	0.56	0.55	0.23
CONSTRUCTION							
In ULTLD	-0.61	- 0.43	- 0.29	- 0.61	- 0.40	- 0.84	- 0.5/
In WGTYPE	0.39	0.70	0.25	0.40	0.60	0.65	0. <b>48</b>
In WGWET	0.45	0.20	- 0.09	0.37	0.16	0.66	0.22
In EWAUW	- 0.16	0.13	- 0.44	- 0.17	0.0 <b>3</b>	0.55	- 0.18
In AVAUW	- 0.65	0.05	- 0.41	- 0.49	- 0.17	0.20	- 0.37
Im BLBOX	0. <i>8</i> 6	0.63	0.58	0.87	0.40	0.59	0.75
PROGRAM					Ų.		
In TESTAC	0.22	0.52	0.12	0.12	0.44	0.62	0.30
In TOOLCP	- 0.49	- 0.32	- 0.76	- 0.45	- <i>0.55</i>	- 0.07	- 0.59
In ENGDV	0.18	0.27	0.32	0.14	0.06	0.21	0.28
In EXPDV	0.17	- 0.13	- 0.36	- 0.14	- 0.34	0.11	- 0.13
In PREDV	- 0.28	- 0.12	- 0.32	- 0.14	- 0. <b>38</b>	0.03	- 0.28

Table A.2

Ø

0

CORRELATION MATRIX FOR IDENTIFICATION OF PAIRWISE COLLINEARITY

		SIZE		TECHNI	CAL/P	RFOR	NANCE		20	NSTRU	CTION				<b>ર</b>	606 81		
	ACW	<u>6</u> w	with all	200	Secto o	Lime .	USELD	منتنه	werre	weiter	EWAUN	AVAUN	action .	TESTAC 7	aol CP	ENEDY	ELED	PREDV
3/2E														-				
A AUN	1.00															_		
de EV	<u>0</u>	1.00																
In WTAREA	<b>66</b> 0	0.39	1.00							-								
TECHNICAL / PERFORMANCE					_											_		
A. 50	-0.3/	- 0./9	- 0.32	8														
An SPCLS	- 0.45	- 0.37	- 0.4	0.82	1.00													
An CLINB	- 0.32	- 0.22	- 0.32	0.93	0.89	8.												
An USELD	0.11	0.10	0.17	0.34	0.43	10	8.											
CONSTRUCTION			<b></b> _	ſ		T		-										
Tr 11210	- 0.17	- 0.29	- 0.25	€¥:0-	- 0.54	- 0.49	- 0.69	1.00									-	
A. WGTYPE	- 0.07	0.0	- 0.10	0.93	0.56	0.82	0.27	-0.29	8.									
In WOWET	- 0./9	- 0.07	- 0.10	0.56	0.7/	0.71	0.66	- 0.00	0.37	8.								
La EWAUN	-0.67	-0.54	-0.62	0.67	0.56	0.60	0.26	-0.44	0.51	0.63	8.							
A AVAUN	- 0.67	- 0.58	- 0.67	0.47		0.04	- 0.46	0./6	0.29	- 0.4	0.85	8						
The BLBOX	0.32	0.42	0.30	0.62	0.37	0.50	- 0.16	-04	0.72	0.32	0.16	- 0.03	8.					
PROGRAM							<b>_</b>	ſ										
Je TESTAC	- 0.47	- 0.39	- 0:48	a 69	0.79	0.56	0.15	-0.30	4.0	0.30	0.55	0.63	0.25	1.00				
12 TOOLCO	- 0.62	-0.57	- 0.56	0.19	0.05	0.19	-0.03	- 0.02	0.14	0.33	0.71	0.61	. 0.2	- 0.04	1.00			
An ENEDI	- 0.11	- 0.11	- 0.13	0.00	0.22	- 0.14	- 0.37	- 0.10	- 0.20	-0.10	-0.0/	0.30	0.10	0.65	NO-	8	_	
La EXPDV	- 0.57	150-	- 0.51	0.29	0.65	€¥0	0.06	- 0.36	E0.0 -	0.63	0.43	8.0	- 0.02	0.49	0.37	0.13	1.00	
La PREDV	- 0.07	- 0.03	0.03	-0.22	- 0.20	- 0.28	0.20	- 0.27	-0.24	0.26	10.0	66.0	- 0.47	- 0.17	3	- 0.15	0.15	1.00
			1	1		1								1				

#### REFERENCES

- Levenson, G. S., and S. M. Barro, Cost-Estimating Relationships for Aircraft Airframes, The RAND Corporation, RM-4845-PR, February 1966 (out of print).
- Levenson, G. S., H. E. Boren, Jr., D. P. Tihansky, and F. Timson, *Cost-Estimating Relationships for Aircraft Airframes*, The RAND Corporation, R-761-PR, December 1971 (For Official Use Only) (Privileged Information).
- 3. Large, Joseph P., Harry G. Campbell, and David Gates, *Parametric Equations for Estimating Aircraft Airframe Costs*, The RAND Corporation, R-1693-1-PA&E, February 1976.
- 4. Green, William, *The World's Fighting Planes*, Doubleday and Company, Garden City, New York, 1964.
- 5. Boren. H. E., Jr., A Computer Model for Estimating Development and Procurement Costs of Aircraft (DAPCA-III), The RAND Corporation, R-1854-PR, March 1976.
- 6. U.S. Air Force Cost and Planning Factors, AFR 173-13, Department of Air Force, Headquarters USAF, Washington, D.C., February 1, 1985 (updates through Change 3, January 31, 1986).

#### - 51 -