The Center for Night Vision and Electro-Optics



FEMTOSECOND TIME-RESOLVED SPECTROSCOPY



ARO-URI Center for Opto-Electronic Systems Research The Institute of Optics, University of Rochester . UNCLASSIFIED

.

SECURITY CLASSIFICATION OF THIS PAGE									
				REPORT DOCUM	ENTATION	PAGE			
1a. REPORT SE	CURITY CLASS	IFICATIO	N		1b. RESTRICTIVE	MARKINGS			
	lassified				3 DISTRIBUTION / AVAILABILITY OF REPORT				
ZO. SECURIT					Approved for public releases				
2b. DECLASSIF	ICATION / DOW	NGRADI	ING SCHEDU	LE	distrib	ution unlimi	ted.	aoc,	
4. PERFORMIN	G ORGANIZAT	ION REP	ORT NUMBE	R(S)	5. MONITORING	ORGANIZATION RE	PORT N	NUMBER(S)	
					410	24626.78	- PH	I-VIR	
6. NAME OF	PERFORMING	ORGANI	ZATION	Sb. OFFICE SYMBOL	7a. NAME OF MONITORING ORGANIZATION				
**	the of Dog		-	(If applicable)	11. S. A	rmy Research	Off	ice	
Univers:	City OI ROC	neste			7b. ADDRESS (CH	v. State, and ZIP C	ode)		
The Inst	tute of 0)ptics			P. O. F	12211	,		
Rochest	er, NY 146	527			Researc	h Triangle H	ark,	NC 27	709-2211
Sa. NAME OF	FUNDING / SPO	NSORIN	<u> </u>	86. OFFICE SYMBOL	9. PROCUREMEN	T INSTRUMENT IDE	NTIFICA	TION NUT	MBER
ORGANIZA	TION	- 1 04		(if applicable)	A				
U. S. A	my keseal	ren UI	tilce			HLO3-00-K	-011		
	ы у, жала, ал о 			· .	PROGRAM	PROJECT	TASK		WORK UNIT
Researc	h Triangle	e Parl	k, NC 27	709-2211	ELEMENT NO.	NO.	NO.		ACCESSION NO.
11. TITLE (Incl	ude Security C	Jassificat	tion)						
- -	Optoe	electr	conic Wor	kshop X: Femtos	second Time-	Resolved Spe	ctosc	ору	
12. PERSONAL	AUTHOR(S)	Ia	an Walms]	Ley					
13a. TYPE OF	REPORT		136. TIME C	OVERED	14. DATE OF REPO	RT (Year, Month, L)ay) 1	5. PAGE (OUNT
	IECHNICA		FROM	10	November	5, 1900			
of the e	uthor(c)	Th and al	ne view,	opinions and/or	findings co	ntained in 1	his i	report	are those
policy.	or decisio	$\frac{and}{on}$, $\frac{bn}{bn}$	less so	designated by o	ther documer	if areas and	identif	w he hlad	ny posicion,
FIELD	GROUP		GROUP	10. SUBJECT TERMIS (C	onunue on revers		A A A A A A A A A A A A A A A A A A A	<i>y by block</i>	
				Workshop	p; femtoseco	ond; spectoso	ору		
10 49578407			if name	and identify by black a	(mbor)				
Y. ABSTRACT	19. ABSTRACT (Continue on reverse if necessary and identify by block number)								
This workshop on "Femtosecond Time-Resolved Spectoscopy" represents the topth of a series of intensive academic/ government interactions in the field									
of advanced electro-optics, as part of the Army sponsored University Research									
Initiative. By documenting the associated technology status and dialogue it is									
hoped that this baseline will serve all interested parties towards providing a									
solution to high priority army requirements. Responsible for program and program execution are Dr. Nicholas George University of Rochester (ARO-									
URI) and Dr. Rudy Buser, NVEOC.									
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT 21. ABSTRACT SECURITY CLASSIFICATION									
228. NAME OF RESPONSIBLE INDIVIDUAL 22b.				226. TELEPHONE	(Include Area Code) 22c.	OFFICE SY	MBOL	
		N	icholas	George	716-275	-2417			

DD FORM 1473, \$4 MAR

\$3 APR edition may be used until exhausted. All other editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED

2

The Center for Night Vision and Electro-Optics

OPTOELECTRONIC WORKSHOPS

Χ

FEMTOSECOND TIME-RESOLVED SPECTROSCOPY

	Accession For			
November 3, 1988	NTIS GRA&I DTIC TAB Unannounced Justification			
	By Distribution/			
	Availability Codes			
ADIALOO ADIALOO	Avail and/or			
\bigcirc	Dist Special			
sponsored jointly by	A-1			

ARO-URI Center for Opto-Electronic Systems Research The Institute of Optics, University of Rochester

OPTOELECTRONIC WORKSHOP

ON

FEMTOSECOND TIME-RESOLVED SPECTROSCOPY

Organizer: ARO-URI-University of Rochester and Center for Night Vision and Electro-Optics

1. INTRODUCTION

.

- 2. SUMMARY -- INCLUDING FOLLOW-UP
- 3. VIEWGRAPH PRESENTATIONS
 - A. Center for Opto-Electronic Systems Research Organizer -- Ian Walmsley

Femtosecond Time-Resolved Spectroscopy Ian Walmsley

Experimental Techniques for Femtosecond Spectroscpy lam Walmsley

Femtosecond Relaxation Processes in Semiconductors Ian Walmsley

Femtosecond Spectroscopy of Large Molecules Ian Walmsley

B. Center for Night Vision and Electro-Optics Organizer -- Edward Sharp

> Nonlinear Optics: Materials Research Edward Sharp

- 4. LIST OF REFERENCES
- 5. LIST OF ATTENDEES
- 6. **DISTRIBUTION**

1. INTRODUCTION

This workshop on "Femtosecond Time-Resolved Spectroscopy" represents the tenth of a series of intensive academic/ government interactions in the field of advanced electro-optics, as part of the Army sponsored University Research Initiative. By documenting the associated technology status and dialogue it is hoped that this baseline will serve all interested parties towards providing a solution to high priority Army requirements. Responsible for program and program execution are Dr. Nicholas George, University of Rochester (ARO-URI) and Dr. Rudy Buser, NVEOC.

2. SUMMARY; AND FOLLOW-UP ACTIONS

Dr. Ed Sharp opened the meeting with a few preliminary remarks on the NVEOC mission, and how his group's work on optical materials and phase conjugation fit into the scheme.

Dr. Sharp then presented a talk on the development of materials for nonlinear optics. The characterization of these materials was highlighted, especially with regard to the use of time-resolved spectroscopy to obtain important material parameters.

Dr. Ian Walmsley then discussed the research at the Institute of Optics in ultrafast time-resolved spectroscopy. This involves developing new laser sources and new spectroscopic techniques, as well as their application to other research projects.

A tour of the NVEOC laboratory facilities followed, with demonstrations of new effects in phase conjugation by Dr. Greg Salamo and measurement of materials parameters, by Dr. Ed Sharp. This was preceded by a discussion of both group's work and the facilities available to and the interests of the participants:

The overlap of interests between the University and the Laboratory was not large in terms of finding common ground for collaborative work. However it was thought to be a worthwhile interaction because it allowed both sides to expand their horizons of possible techniques and applications.

One possible area of mutual interest is the problem of charge transport in liquid crystal molecules. The large dipole moments that are possible in these materials depends on the ability of electrons to move rapidly along the polymer chain. Time-resolved spectroscopy might be used as a method of measuring the rate at which this occurs. Kywovds: Electrooptics,

Femto second time; Workshops, Relaxation Time (jhd) e

5

CENTER FOR OPTO-ELECTRONIC SYSTEMS RESEARCH FEMTOSECOND TIME-RESOLVED SPECTROSCOPY

Research in Femtosecond Time-Resolved Spectroscopy

I.A. Walmsley The Institute of Optics University of Rochester Rochester NY 14627

-Development of new sources and amplifiers for ultrashort light pulses.

-Application to fundamental processes and potential device technologies.

1. Femtosecond Light Sources

- Lasers which produce extremely short (~20fs) light pulses are required for:
 - time-resolved spectroscopy
 - high-speed communications systems

- DOT SOLFCOS

- shorter pulses
- tunable wavelengths

- research goals:

- understand pulse-forming mechanisms
- develop new sources (esp. solid-state)

- 2. Current Status:
 - Passively Modelocked Dye lasers: (shortest pulse duration; 201s [Sleat, Finch & Sibbett 1988])
 - Colliding Pulse Modelocked (CPM)



SATURABLE ABSORPTION

ARGON

Ley Features

- Saturable Gain
- Saturable Absorption
- Dispersive Nonlinearity
- Variable GVD
- Theory: [Martinez, Fork & Gordon (1985), Petrov, Rudolph & Vilhelmi (1987), Avramopoulos, French, Villiams, Nev & Taylor(1988)]

-Not tunable -Liquid system

-Some regimes of operation not explained by theories

3. Laser output characterisation:

- Pulse shape and duration studied via intensity autocorrelation:

$$S_{Ac}(\tau) = \int_{-\tau} dt I(t) I(t+\tau)$$



- Typical results:



- $\tau_{\rm D}$ related to pulse duration, assuming a pulse shape



- laser has some characteristics of soliton-supporting modia;
 - monlinearity
 - dispersion

- in addition, there are also;

- gain and loss mechanisms
- non-continuous nonlinearity and dispersion



6. Evidence for soliton-like pulses:

- Soliton part of spectrum shows periodic modulation

- Soliton period, t, related to material dispersion

$$\frac{1}{\tau} = \frac{2\phi''}{0.3\pi \tau_{\rm b} T}$$

 $- = 5\mu s \Rightarrow \phi^* = -180, -250 f s^2 \Rightarrow 3-5mm of quartz$

- Inferred intracavity dispersion agrees with that estimated from the quartz prism sequence.

- 7. Effective zero-dispersion point:
 - Both types of pulses can occur simultaneously at the zero-dispersion point ($\phi^*=0$) of an optical fiber. [Vai & Menyuk (1988)]
 - Introduce "effective zero-dispersion point" for CPM which delimits regime of stable, modelocked behaviour.



8. Relation between goliton and dispersive waves:

- Interferometric intensity subcorrelation

 $S_{IAC}(z) = S_{AC}(z) + 4 \operatorname{Re} \int dt I(t) E(t)E(t+z)$ INTERFERENCE FRINGES



- lack of coherence between the dispersive parts and the soliton-like parts. Why?

9. Chirned solitons:

- aC measured after extracavity prism sequence



- Spectral windowing



- Solitons are "chirped"

10. <u>Current projects:</u>

Problems;

- Current models fail to predict all types of solitonlike behaviour.
- Soliton-like regimes of operation have not been fully characterised.

Solutions;

- Determine the pulse electric field envelope using triple correlation and energy spectrum measurements.

$$- S_{TC}(z_{1}, z_{2}) = \int_{-T}^{T} dt I(t) I(t+z_{1}) I(t+z_{2}) \\ -T \\ - S(z) = \int_{-T}^{T} dt E(t) E(t+z) = F.T. \{ |\tilde{E}(\omega)|^{\frac{1}{2}} \} \\ -T \\ - T \\ -$$

- Develop theory which includes molecular coherences and which retains high-order dispersion.

11. 2mmry:

- Soliton-like mechanisms are important in pulse shaping in the CPM. There are many different regimes in which solitons occur.
- The generation of soliton-like pulses in the CPM laser is not well understood, either via theory or experiment.
- There are significant differences from "usual" solitons (i.e. solutions to the nonlinear Schrodinger equation), due to the additional mechanisms (gain and loss) in the laser and the distributed nature of the nonlinearity and dispersion.
- There is a possibility for constructing passivelymodelocked lasers at other wavelengths and using more robust materials by understanding and utilising these pulse shaping mechanisms.

High Repetition Rate Femtosecond Amplifier System

- New scheme for amplifying femtosecond pulses

- High-energy pulses (>10µJ)

-High-repetition rates (>30kHz)

-No cavity locking required

40fs, 150pJ, 100MHz



EXPERIMENTAL TECHNIQUES FOR FEMTOSECOND SPECTROSCOPY CENTER FOR OPTO-ELECTRONIC SYSTEMS RESEARCH

Pump-Probe spectroscopy

Excitation: Pump pulse establishes medium excitation. Probe pulse is affected by medium excitation at some later time.

Measure: absorption, polarisation rotation, frequency upconversion of probe pulse

<u>Result</u>: Maps out time-development of medium excitation

Transmission-correlation spectroscopy

-measures transmitted intensity of both pump and probe pulses

-same information is returned as in a pump-probe experiment

-some technical advantages

Transmission-correlation spectroscopy

-measures same quantitizes as pump-probe -some sechnical advantages in this case





Data processing; linear prediction least squares fitting

-autoregressive fitting of the time series

-solve <u>linear</u> least squares problem for the linear prediction coefficients

-SVD allows distinction between signal and noise components (Kumaresan and Tufts, 1983)

-reconstruct signal estimator from truncated linear prediction filter

 $\Delta T(\tau) = \sum a_i \exp(-t/\tau_i) \cos(\omega_i \tau + \phi_i)$

This method has several important features;

-no initial guess about the number of components is required

-eliminates need for nonlinear least squares fitting

-higher resolution than FFT for short time series

All damped sinusoidal components that are present in the signal are found, without prior knowledge of the signal form and limited only by the SNR of the data.

Typical results;	50% C.A.
SNR = 60dB, 3 components,	$\Delta(\tau_i)^2 = 10\%$

 $\Delta(a_i)^2 = 20\%$

CENTER FOR OPTO-ELECTRONIC SYSTEMS RESEARCH FEMTOSECOND RELAXATION PROCESSES IN SEMICONDUCTORS

Femtosecond Time-resolved Spectroscopy

Enhanced temporal resolution

Semiconductors:

Characterisation of high-speed electronic devices Ballistic transistors Velocity-overshoot devices



Molecules:

Fundamental physics of chemical reactions Laser-selective chemistry



Band Structure and Optically Coupled Region for Bulk GaAs

• <u>Three transitions</u> from the valence bands into the Γ -valley conduction band are possible.



F19.1

In both GaAs and $Al_{0.35}Ga_{0.65}As$, the subpicosecond decay is dominated by 2 exponential components.

Al0.35Ga0.65As

- T₁ = 40 fs : Intervalley scattering by phonon emission and carrier- carrier scattering.
 (85%)
- $T_2 = 140$ fs : LO phonon emission. (9%)
- + long-lived component (1.6ps)

GaAs

 $T_1 = 35 fs$: IV + CC (85%)

 $T_2 = 160 fs$: LO (8%)

+ "rising wing" due to bandfilling









A 3 component exponential decay was found in all cases.

$$n(t) = \Sigma a_i \exp(-t/\tau_i)$$

- $T_1 = 40 \text{ fs}$: intervalley and carrier-carrier
- $T_2 = 140 \text{ fs}$: LO phonon emission
- $T_3 = 1 \text{ ps}$: (unspecified) depends on carrier density at 80K

For
$$n = 5 \times 10^{17} \text{ cm}^{-3}$$

At	300K	$a_1/a_2 = 10$	
	180K	$a_1/a_2 = 3$	(IV disallowed)
	80K	$a_1/a_2 = 5$	(LO reduced)

Estimate of the efficiency with which each mechanism removes electrons from the initially excited states: from the measured TCP curves;

Delay	temp.	% of carriers removed		possible mechanisms
100fs	300K	84		IV + CC + LO
100fs	180K	75	٩	CC+LO

-Then, roughly, of the carriers which leave the initial states in the first 100 fs

65% scatter to the satellite valleys
30% scatter via carrier-carrier interactions
5% scatter by LO phonon emission
Conclusions:

-The various physical mechanisms which govern the initial relaxation of photoexcited electrons in AlGaAs have been experimentally identified.

-Intervalley and carrier-carrier scattering occur on a 40fs timescale, and LO phonon emission on a 150 fs timescale.

-Intervalley scattering dominates the relaxation when it is energetically allowed.

Summary

-Resolved fastest electron scattering processes in AlGaAs;

implications for the uttimate speed of electron devices

-Observed THz quantum beats in organic dye molecules;

important in the determination of excited-state potential energy surfaces

-Possibilities for observing other coherent transient phenomena in semiconductors;

{coherent electric currents?}

Large organic dye molecules as a paradigm for semiconductors

-Energy scales and relaxation times are similar.

-Substantially fever electronic states: easier to perform understandable experiments.

FEMTOSECOND SPECTROSCOPY OF LARGE MOLECULES CENTER FOR OPTO-ELECTRONIC SYSTEMS RESEARCH

Femtosecond Spectroscopy of Large Molecules

I.A.Walmsley The Institute of Optics University of Rochester

F.W.Wise and C.L.Tang Cornell University





- COHERENT SUPERPOSITION OF STATES DEVELOPING IN TIME.



- e.g. MOLECULAR SYSTEM: EXCITE A VIBRATIONAL MODE IN A GROUND- OR EXCITED-ELECTRONIC STATE. -impulsive excitation of molecular nuclear vibrational mode

$$Q + \Gamma Q + \omega_0^2 Q = N (\delta \alpha / \delta Q)$$
: E E

Q = vibrational amplitude Γ = Raman linewidth ω_0 = Raman frequency

-electric field must have spectrum as broad as ω_0

-pulses must be shorter than timescale of all dynamics

-time domain analog of Raman scattering



(Raman selection rules)

-schematic energy levels



tri-phenyl methane

-molecular structure

TABLE -

$$\mathbf{y}(t) = \sum \mathbf{a}_i \exp(-t/T_i) \cos(2\pi v_i t + \phi_i)$$

Molecule	а	T (fs)	v(THz)	φ(deg)
Malachite Green	0.58 0.36 0.06	75 4800 205	6.60	11
Ethyl Violet	0.60 0.33 0.07	120 1700 380	6.45	7
Methyl Violet	0.55 0.23 0.19 0.03	39 2650 150 280	6.40	7
Victoria Blue	0.57 0.31 0.11 0.01	30 10000 105 190	6.14	13
Methylene Blue	0.98 0.01 0.002	27 1470 380	7.7	2
DODCI	0.47 0.32 0.09 0.07 0.03 0.02	185 1050 370 300 180 500	0.87 6.35 2.61 8.17 5.00	5 3 9 93 8
Nile Blue	0.72 0.20 0.04 0.02 0.006 0.005 0.005 0.0007 0.0004 0.0003	43 400 180 490 560 405 4300 4700 3900 11500	4.86 3.06 5.00 8.39 2.16 6.96 9.12 10.6	140 87 12 144 21 73 93 27

Theory

-3rd order perturbation solution to Liouville equation for 3-level system.

-signal form is relatively independent of dephasing and population lifetimes of optical transitions.

probing polarisibility, not polarisation

-useful in regimes where other time-domain techniques, such as photon echoes, are not possible.

-phase of sinusoids depend on nature of exciting pulses and particular energy level scheme





 $v_{2a}^{-1} = 150 \text{ fs}.$

1<u>,</u> = 0

Tas = 190fs

T.- 4.8ps

•



F"*-"

Measurements of the dephasing rates of optical transitions

- Phase of the quantum beats depends on the dipole moment decay rate $(T_2)^{-1}$

- Shape of signal is not very sensitive to T_2 or the inhomogeneous decay time.

-Phase of the beats depends on the phase of the phonon, which depends on the exact pulse shape, the population inversion etc.

-Solution . measure the phase of the beats through a spectrometer!

THREE - LEVEL MODEL.





•





INCIDENT

TRANSMITTED.



-phase of sinusoid is determined by ground-or excited-state sublevel excitation and pump detuning - phase across spectrum depends only on g.s ar e.s. sublevels.



The American go alter Bray Lee





· • • • •







Fig.3 The phase of the modulations in the absorption signal as a function of spectrometer tuning (assuming the pump laser is on resonance). The FWHM of the curve is used to determine

aition

Conclusions

-Observation of molecular nuclear motion in "real time" in organic dye molecules.

Implications for the determination of excited-state potential energy surfaces and laser-selective chemistry.

-Possible new method of measuring Raman linewidths.

Independent of the dephasing and population lifetimes of the optical levels.

-Technique for distinguishing ground- and excited-state quantum beats.

Important in understanding the dynamics of systems without prior knowledge of the energy level structure.

-Possibilities for observing other coherent transient phenomena in semiconductors.

{coherent optically-driven electric currents?}

Future Directions

- Relaxation on short timescales

For times short compared with the correlation time of the damping forces the decay of an elementary excitation (e.g. electronic states, phonons) is non-exponential.

An homogeneous line becomes inhomogeneous.

Use nonlinear optics to measure reservoir correlation functions

- Optical coherent transients in semiconductors

Excite electronic or phonon population impulsively and watch the wavepacket motion.

Time-domain observations of the phonon amplitude : measurements of anharmonic effects.

Time-domain observation of electron wavepacket motion : optical excitation of a phase-coherent electric current.

CENTER FOR NIGHT VISION AND ELECTRO-OPTICS NONLINEAR OPTICS: MATERIALS RESEARCH

LASER RESEARCH TEAM: R&D of n

R & D of nonlinear optical materials, techniques, and concepts

- **O** Beam Control Devices
- o Optical Switches
- o Optical Isolators
- o Filters
- O Laser Components
- o New Sources
- o Q-Switches
- o Modulators

RECENT RESEARCH ACTIVITY

- (SBN & BSKNN) O Tungsten-Bronze Family of Ferroelectric Crystals
 - o Ferroelectric Properties (Sensors)
- o Electro-Optic Properties (Broad-Band Modulators)
- o Photorefractive Properties
- Optical Isolation of Coherent Beams Via Beam Fanning and Two-Beam Coupling
- Phase Conjugation for Image Processing (Amplification, Storage, and Enhancement)
 - Nonlinear Organic Media (Short Pulse Studies)





Nonlinear Phenomena (Self-Induced Effects)

Third-Harmonic Generation	THG	χ ⁽³⁾ (– 3ω,ω,ω,ω)	<mark> k</mark> = 3 K
Nonlinear Refraction	NR(n ₂)	χ ⁽³⁾ (−ω,ω,ω,−ω) Re	К _р = К
Self-Focusing	SF	χ ⁽³⁾ (– ω,ω,ω, – ω) Re	0≠4 ⁷
Self-Defocusing	SD	−χ ⁽³⁾ (−ω,ω,ω,−ω)	7
Two-Photon Absorption	TPA	χ ⁽³⁾ (-ω,ω,ω,-ω) Im	•
Degenerate Four-Wave Mixing	DFWM	χ ⁽³⁾ (– ω,ω,ω, – ω) _{Re}	Kp K' K' K' [Kp] = [K'] = [K']
Stimulated Raman Scattering	SRS	χ ^[3] (-ω₂٬ω₁,-ω₁,ω₂)	
Stimulated Brillouin Scattering	SBS	χ ⁽³⁾ (– ω ₂ ,ω ₁ , – ω ₁ ,ω ₂)	$\omega_1 \sim \omega_2$
Raman-Induced Kerr Effect Scattering	RIKES	χ ⁽³⁾ (– ω ₂ ,ω ₁ , –ω ₁ ,ω ₂)	
Coherant Anti-Stokes Raman Scattering	CARS	χ ⁽³⁾ (-ϣ _{AS} ,ω ₁ ,ω ₁ ,-ω ₂)	

TABLE 1

NONLINEAR OPTICAL EFFECTS & APPLICATIONS

- OF NONLINEAR OPTICAL EFFECTS IN APPROPRIATE SPECTRAL RANGES O EFFORT AT CNVEO TO DEVELOP A FUNDAMENTAL UNDERSTANDING
- **O EFFECTS STUDIED:**
- **O MULTIPHOTON ABSORPTION**
- **O SATURATION EFFECTS**
- O SELF-FOCUSING/DEFOCUSING
- **O STIMULATED SCATTERING**
- O LASER INDUCED PLASMA ABSORPTION
 - **O** PHOTOREFRACTION
- O APPLICATIONS:
- O FAST OPTICAL SWITCHES & GATES
- O SECOND & THIRD HARMONIC GENERATION
 - O FOUR WAVE MIXING (NEW SOURCES)
- STIMULATED SCATTERING (NEW COHERENT SOURCES , PHASE CONJUGATION) 0
 - O OPTICALLY BISTABLE DEVICES (LOGIC, FILTERING)
- O SATURABLE ABSORPTION (Q-SWITCHES, MODE-LOCKERS)
 - O OPTICAL ISOLATORS/POWER LIMITERS
- O WAVE-FRONT REVERSAL, PHASE CONJUGATION

NONLINEAR MATERIALS



KEV ISSUES

- TIME RESPONSE
- SENSITIVITY
- **BANDWIDTH**
- MATERIAL AVAILABILITY/QUALITY
- MATERIAL IMPROVEMENTS
- POSSIBILITY FOR NEW DEVICES



•



,



NONLINEAR TRANSMISSION

ł



1. J. S. C. A. C. A. C. A.

そうちょうちょう かいちょうちょうちょう ちょうろう ちょうちょうちょう ちょうちょうちょうちょうちょうちょう ちょうちょうちょう ちょうちょうちょう

an interest and a desite of the



- THE THRESHOLD POWER P_{TH} CAN BE INFLUENCED BY A NUMBER OF NONLINEAR EFFECTS
- ABSORPTION (LINEAR AND NONLINEAR)
- SATURATION EFFECTS
- SELF-FOCUSING/DEFOCUSING
- SCATTERING
- LASER INDUCED BREAKDOWN
- THE STRENGTH OF THE NONLINEARITY IS DETERMINED BY THE NONLINEAR INDEX COEFFICIENT N2



NONLINEAR REFRACTION & ABSORPTION

÷



Ē

Linear Molecules

S = C = S

-(CH₂)₃CH₃ T MEBBA H₃C-

-(CH₂)₃CH₃ MBBA H₃C,

- S. 18.9. 19

- - - -



· Andrews and the second second



دی. ۸ میبیدی بر این این این این ا

ورجافي والمساور المراج



			· ·
	<u>CS</u> 2	MBBA	MEBBA
STAIE	ISOTROPIC LIQUID	LIQUID CRYSTALS	LIQUID CRYSTALS
DOMINANT EFFECTS	Self-focusing Laser Induced Plasma	Self-focusing Scattering	SELF-FUCUSING Nonlinear Absorpticn
N2(AT 0.53UM)	1.23x10-11 ESU	1.26x10-12 ESU	3.9x10-11 ESU
THRESHOLD POWER	7.8 KW	80 KW	2.5 KW
PROBLEMS	WELL UNDERSTOOD Material	NEMATIC AT Room Temp	POSSIGLE DECOMPOSITION Complex Absorption Processes



NEMATIC LIQUID CRYSTALS



MBBA
$$CH_3 - 0 - C_3 - CH = N - C_3 - CH_2 - CH_2 - CH_2 - CH_2 - H_2 - H_2 - CH_2 - CH_2 - H_2 - H_2 - CH_2 - CH_2 - H_2 - H_2 - CH_2 - CH_2 - CH_2 - H_2 - H_2 - CH_2 - C$$

÷





Isomers of Octahedral Chelates







Square-Planar Chelates





REFERENCES

Mol. Cryst. Liq. Cryst., 1985, Vol. 127, pp. 321-330 0026-8941/85/1274-0321/\$15.00/0 € 1985 Gordon and Breach, Science Publishers, Inc. and OPA Ltd. Printed in the United States of America

Studies of the Nonlinear Switching Properties of Liquid Crystals with Picosecond Pulses

M. J. SOILEAU, SHEKHAR GUHA, WILLIAM E. WILLIAMS, E. W. VAN STRYLAND, and H. VANHERZEELE

Center for Applied Quantum Electronics, Department of Physics, North Texas State University, Denton, Texas 76203

and

J. L. W. POHLMANN, E. J. SHARP, and G. WOOD

Night Vision and Electro-Optics Laboratory, Fort Belvoir, Virginia 22060

(Received September 6, 1984)

A comparative study of self-focusing in seven liquid crystals using picosecond 0.53 and 1.06 μ m pulses is presented. MEBBA was found to have the highest nonlinearity at 0.53 μ m as determined in an optical power limiting experiment. This limiting appears to be due to nonlinear refraction enhanced by two-photon absorption.

We report here the results of a sytematic study of self-focusing in several liquid crystals in the isotropic phase using picosecond pulses at 0.53 μ m and 1.06 μ m. The samples studied and their chemical compositions are listed in figure 1.

Large nonlinearities have been previously measured in liquid crystals using nanosecond pulses¹ and such materials have been used in cw four-wave mixing experiments.² The large nonlinear refractive indices n_2 observed in the earlier work are believed to be due to light induced reorientation of the anisotropic liquid crystal molecules which is a relatively slow process. In order to estimate the value of n_2 in the liquid crystals, a power limiting configuration was used.³ For highly nonlinear self-focusing materials such as CS₂, it was established in Ref. 3 that the limiting power obtained in such a configura-

MEBBA: CH₃ - (-) - CH = N - (-) - 4 MEGBBA:** CH₃-O - (-) - CH = N - (-) - 4

OTHER LIQUID CRYSTALS STUDIED:



** Commonly called MBBA

FIGURE 1 Chemical structures and nomenclature for the fiquid crystals studied in this work.

tion is P_2 , the second critical power for self-focusing. P_2 is related to n_2 by the relation.

$$P_2 = \frac{3.77c\lambda^2}{32\pi^2 n_2}$$
(1)

where c is the speed of light in vacuum, λ is the wavelength and 3.77 comes from a numerical solution to the nonlinear wave equation.⁴

The experimental technique is described in detail in Ref. 3 and is summarized here in Fig. 2. A lens (L_1) focuses light from a frequencydoubled mode-locked picosecond Nd: YAG laser operated in the TEM₀₀ spatial mode. A second lens (L_2) reimages the transmitted light through an aperture onto the detector D_4 which measures the transmitted energy. As the incident power reaches P_2 , the beam undergoes severe phase distortion and the reading on D_4 stops increasing for further increase of input power. This switching is due to self-lensing and subsequent optical breakdown. Figure 3 shows an example of such laser induced switching for CS₂ and MEBBA at 0.53 μ m. The input field was linearly polarized. It is to be noted that the switching power for MEBBA is less than that of CS₂.

NONLINEAR OPTICAL SWITCH



FIGURE 2 Technique for measuring the onset of self-focusing. The solid lines schematically trace the input beam for low input power. The beam is focused into the nonlinear medium by lens L_1 and then imaged by L_2 through an aperture onto detector D_4 . The transmission for low input powers can be near unity. As the input power is increased to approximately P_2 , the critical power for self-focusing, 'the beam undergoes severe phase aberrations (i.e., nonlinear refraction) and the transmission through the aperture decreases. The high power situation is shown schematically by the dotted lines.



FIGURE 3 Nonlinear optical switching in CS₂ and MEBBA (4-methyl benzylidene 4'-n-butylaniline). The detector reading D_4 monitors the aperture transmission after the sample. D_4 remains unclamped with input power until P_2 is reached. The data shown are for 42 psec (FWHM), linearly polarized 0.53 µm pulses.

The ratio of the critical powers for the circularly polarized field to the linearly polarized field is approximately two for each of the samples studied, as shown in Figs. 4 and 5. Figure 4 shows the switching powers for the liquid crystals MEBBA, MEOBBA (commonly known as MBBA) and PPMEOB for linearly polarized input field and Fig. 5 shows the corresponding results for circularly polarized light. Figures 6 and 7 show the results for linear and circularly M. J. SOILEAU et al.



FIGURE 4 Comparison of nonlinear optical switching for the liquid crystals MEBBA, MEOBBA and PPMEOB. Linearly polarized light at 0.53 μm with 42 ps (FW1M) pulsewidth was used.



FIGURE 5 Comparison of nonlinear optical switching for the liquid crystals MEBBA, MEOBBA and PPMEOB. Circularly polarized light at 0.53 μ m with 42 ps (FWHM) pulsewidth was used.

NONLINEAR SWITCHING OF LIQUID CRYSTALS

.



FIGURE 6 Comparison of nonlinear optical switching for the liquid crystals PEP-BUB, BUPBUB, PEPPEB and BUPPEB. Linearly polarized light at 0.53 μ m with 42 ps (FWHM) pulsewidth was used.



FIGURE 7 Comparison of nonlinear optical switching for the liquid crystals PEP-BUB, BUPBUB, PEPPEB and BUPPEB. Circularly polarized light at 0.53 μ m with 42 ps (FWHM) pulsewidth was used.



FIGURE 8 Vidicon scans showing the far field spatial profile of a 0.53 μ m beam after transmission through an optically thin sample of MEBBA (thickness less than a Rayleigh range). The dashed curve is for low input irradiance and shows no beam distortion. The solid trace is for high irradiance and shows the effects of phase distortion in the sample.

polarized light, respectively, using the liquid crystals PEPBUB, BUP-BUB, PEPPEB and BUPPEB. P_2 is seen to have the same value for for each of these four samples and for the sample PPMEOB. The fact that this ratio of switching powers for circular and linear polarizations is two is a clear indication that self-focusing is the dominant mechanism as discussed in Ref. 3. In fact, this is exactly the ratio observed for CS₂ where the dominant nonlinearity is molecular reorientation. Therefore, the observed polarization dependence suggests that the dominant nonlinearity, even for the short pulses, is molecular reorientation for these materials. However, for these large molecules the decay time constant would be expected to be considerably longer than the 42 psec (FWHM) pulses used.

Figure 8 shows the distortion in the far field spatial pattern of the beam after transmission through an optically thin sample of MEBBA (thickness of the sample less than the Rayleigh range): The effect of the optically induced phase distortion is observed by comparing the profiles at high input irradiance (solid curve) to that at low input irradiance (dashed curve). That this phase distortion arises from self-focusing rather than self-defocusing is confirmed by the results



FIGURE 9 Comparison of nonlinear optical switching powers in MEBBA for different input irradiances. The focal length of the lens L_1 was 37.5 mm for the circles and 75 mm for the crosses so that the spot size in the sample changed by a factor of 2 (irradiance changes by 4 for a given power). Linearly polarized light at 0.53 μ m with 42 ps (FWHM) was used.

shown in Fig. 9 in which the power dependence of the switching is shown for different input irradiances. The two curves shown correspond to experiments using lenses of focal lengths differing by a factor of two yielding spot sizes differing by a factor of two. If the limiting were due to self-defocusing, a dependence on the input irradiance would be expected, which is seen to be absent in Fig. 9. Also the fact that the switching power remains constant when the irradiance changes by a factor of four shows the dominance of nonlinear refraction as opposed to, for example, nonlinear absorption. An additional indication of self-focusing was the observation that at and above the critical input power there was optical breakdown in the liquid crystal media.

In Fig. 10 a comparison of critical powers in MEBBA at 1.06 μ m and 0.53 μ m is shown. The ratio of the values of P_2 at the two wavelengths is approximately 20 whereas self-focusing theory only predicts a ratio of 4 between the two wavelengths (see equation 1).^{3,4} This large dispersion implies that the mechanism responsible for nonlinear refraction in MEBBA is not simply molecular reorientation.



FIGURE 10 Comparison of nonlinear optical switching power in MEBBA between $0.53 \mu m$ and $1.06 \mu m$ radiation. The pulsewidths used were 42 ps and 67 ps (FWHM) respectively. Linearly polarized light was used.

Figure 11 shows optical switching in PEPBUB, BUPBUB, PEPPEB and BUPPEB at 1.06 μ m. Comparing with Fig. 6 we find a ratio of 10 in the critical powers for this set of samples at the two wavelengths. The dispersion is still larger than the prediction of 4 from selffocusing theory, but smaller than that observed in MEBBA.

The larger nonlinearities at 0.53 µm may be due to an enhancement of the nonlinear refraction due to nonlinear absorption. Nonlinear absorption in MEBBA was observed at 0.53 µm and the results are plotted in Fig. 12 where the inverse transmission is displayed as a function of the incident irradiance. The nearly linear dependence on irradiance is consistent with a two-photon absorption process.⁵ The dotted line shows the theoretical predictions for a two-photon absorption coefficient of 0.6 ± 0.2 cm/GW. If we now go back to the limiting configuration and calculate, using linear optics, the expected irradiance at focus we find a maximum change of transmission due to two-photon absorption of 15%; not enough by itself to account for the limiting. No nonlinear absorption was observed at 1.06 µm up to irradiances where there was obvious material breakdown. It is worth mentioning that excimer formation by nonlinear absorption of picosecond laser pulses has been observed in liquid benzene⁶ and similar processes could play a role in liquid crystals as well.

NONLINEAR SWITCHING OF LIQUID CRYSTALS

٠



FIGURE 11 Comparison of nonlinear optical switching in PEPBUB, BUPBUB, PEPPEB and BUPPEB at 1.06 μ m using linearly polarized light with 67 ps (FWHM) pulsewidth.



FIGURE 12 The inverse of the transmission of a 0.5 cm pathlength cell filled with MEBBA is plotted as a function of the incident irradiance at 0.53 μ m. The solid line is a theoretical fit with a nonlinear absorption coefficient of 0.6 cm/GW.

M. J. SOILEAU et al.

To summarize, P_2 was measured for various liquid crystals and was found to vary greatly with minor changes in chemical composition. For example the difference between MEBBA and MEOBBA is the addition of a single oxygen atom. The liquid crystals were found to exhibit large and fast nonlinearities comparable to those of the Kerr liquids and are effective materials for optical power limiter applications. In addition, they have potential for applications in the areas of phase conjugation, optical-bistability and optical switching. Extensive studies of nonlinear hyperpolarizabilities of organic molecules have been performed with nanosecond pulses to determine the ways to maximize the nonlinear susceptibility by synthesizing molecules with different substituents.⁷ Similar work using liquid crystals and determination of the origins of the nonlinearities would be of practical interest. Further study, including other materials, a determination of the pulsewidth and temperature dependence of the nonlinearities, and a more refined theoretical modeling is currently in progress.

References

1. D. V. G. L. Narashimha Rao and S. Jayaraman, Appl. Phys. Lett. 23, 539 (1973).

2. I. C. Khoo, Phys. Rev. A 25, 1040 (1982).

 M. J. Soileau, É. W. Williams, and E. W. Van Stryland, IEEE Journ. Quant. Elec. QE-19 4, 731 (1893).

4. J. H. Marburger, *Progress in Quantum Electronics* J. H. Sanders and S. Stenholm, eds., (New York, Pergamon, 1977) pp. 35-110.

5. J. H. Bechtel and W. L. Smith, Phys. Rev. B13, 3515 (1976).

6. H. Masuhara, H. Miyasaka, N. Ikeda, and N. Mataga, Chem. Phys. Lett. 82, 59 (1981).

7. B. F. Levine and C. G. Bethea, Journ. Chem. Phys. 63, 2666 (1975).

Mol. Cryst. Liq. Cryst., 1987, Vol. 143, pp. 139-143 Photocopying permitted by license only © 1987 Oordon and Breach Science Publishers S.A. Printed in the United States of America

NONLINEAR OPTICAL PROPERTIES OF LIQUID CRYSTALS IN THE ISOTROPIC PHASE

M. J. SOILEAU, ERIC W. VAN STRYLAND, and SHEKHAR GUHA^{*}

Center for Applied Quantum Electronics, Department of Physics, North Texas State University, Denton, TX 76203 Present Address: Martin Marietta Laboratories, 1450 South Rolling Road, Baltimore, MD 21227

E. J. SHARP, G. L. WOOD, and J. L. W. POHLMANN Army Night Vision and Electro-Optics Center, Fort Belvoir, VA 22060-5677

Abstract Picosecond nonlinear absorption and nonlinear refraction were studied for several classes of isotropic phase liquid crystals, including Schiff base and ester compounds. Materials studied exhibit a large two-photon absorption coefficient (β) at 532 nm. Values of β were found to be ~0.6 cm/GW in several of the compounds studied. Nonlinear refraction was also observed and the nonlinear refractive index, n₃ was measured for each material at 1.06 μ m using an external self-focusing trrangement. n₃ ranged from 6 x 10⁻¹³ esu to 2 x 10⁻¹³ esu. The combination of nonlinear absorption and nonlinear refraction in these materials result in optical limiting for input energies as low as 0.15 microjoules for 30 psec pulses at 532 nm.

INTRODUCTION

In this paper we report the results of simple direct measurements of nonlinear absorption and nonlinear refraction in selected liquid crystals in their isotropic phase. These measurements are part of an extensive study of nonlinear optical properties of materials in our laboratories.

I. C. Khoo's invited talk at this meeting¹ contained many excellent examples of the so-called giant optical nonlinearities in liquid crystal materials. These giant nonlinearities are associated with the anisotropy in

M. J. SOILEAU, et al.

the linear susceptibility of these organic molecules and the large scale ordering and changes in structural phase induced by an impressed optical field. These nonlinearities involve large scale motion of the relatively massive liquid crystal molecules and as a result the nonlinear response is quite slow (with response times as large as seconds). Liquid crystals have the delocalized x-electronic structures that have been identified by many workers as potential sources of fast and large optical nonlinearities.² In this work we use single pulses of picosecond duration to study such nonlinearities at 532 and 1064 nm. Thermal effects, electrostriction and long time constant reorientational effects are minimized in these measurements and the nonlinearities reported are an upper bound for the fast electronic effects.

EXPERIMENTAL

The laser source for these measurements was a Nd:YAG operated at 1064 nm. This laser system produced output pulses of 30 to 200 psec duration and operated in a single spatial mode (TEM₀₀) as verified by pinhole scans and whole beam analysis with an optical multichannel analyzer. The energy and pulsewidth was monitored for each laser shot using the procedure described in ref. 3. The laser output was harmonically converted to give output at 532 nm. The maximum repetition rate used was 5 Hz, thus insuring that the duty cycle was very low and that thermal effects were minimized.

The measurements were conducted using two very simple techniques which are described in detail elsewhere. In one case the sample thickness is much larger than the depth of focus of the beam (i.e., Rayleigh range) that is tightly focused into the bulk of the material being tested.^{4,4} The nonlinear response is monitored by measuring the ratio of the input to the on-axis fluence in the far field of the beam after it exits the sample. This simple technique allows for the rapid comparison of the nonlinear response of many materials. In the case of simple

NONLINEAR OPTICAL PROPERTIES OF LIQUID CRYSTALS

nonlinearities, such as the electronic Kerr effect, the nonlinear refractive index (n_2) may be extracted from such measurements by monitoring the input power required for the onset of whole beam self-focusing. For more complex nonlinearities we simply determine the input power (P_c) required to limit the far field on-axis fluence. This parameter (P_c) is a rough measure of the combined effects of nonlinear refraction and nonlinear absorption and as such is a good indicator as to whether or not more quantitative measurements should be performed.

In the second technique the Rayleigh range of the beam incident on the sample is larger than the sample thickness and the beam is collimated as it traverses the sample. The two-photon absorption coefficient (β) is determined by measuring the total energy transmitted through the sample as a function of the input irradiance in the manner described in detail in refs. 6 and 7. The nonlinear refractive index (n₂) is determined by measuring the changes in beam shape and/or on-axis fluence in the near or far field of the test cell (see ref. 8 for details).

RESULTS

We have previously reported optical limiting in MBBA (p-methoxy benzylidene p-n-butylanilene).⁹ Table I is a summary of P_C , β and n_3 measurements in this material and other liquid crystals of similar structure. All the data shown are for pulsewidths of approximately 30 ps and the liquid crystals were in the isotropic phase. Data for CS₂ are shown for comparison. The data for P_C were taken using the optically thick arrangement described in refs. 4 and 5. P_C is indicative of the total nonlinear response of the materials as previously noted. For simple Kerr nonlinearities P_C is inversely proportional to n_3 . Note that P_C at 532 nm is about the same for all the samples tested including CS₃. The P_C (or limiting power) for CS₂ is associated with the onset of whole beam selffocusing whereas the observed limiting in the liquid crystal samples is associated with beam depletion due to two-photon absorption.

M, J. SOILEAU, et al.

The nonlinear refractive index (n_3) was directly measured for these materials using the thin sample arrangement described in ref. 8. Note that in all cases the n_3 values for the liquid crystals are approximately an order of magnitude smaller than that of CS_2 .

The relatively low values for the fast nonlinearity (assumed to be due to an optical Kerr effect) measured in these materials is somewhat disappointing considering reports of large, fast nonlinearities in organics reported by other workers. We are in the process of extending our measurements to other organics.

SUMMARY

The two-photon absorption coefficient (β) was measured for five isotropic phase liquid crystals at 532 nm. The values of β are large enough ($\approx 0.6 \text{ cm/GW}$) for use in various nonlinear optical device applications. The nonlinear refractive index, n_2 , was measured at 1064 nm for each sample and was found to be approximately an order of magnitude smaller than that of CS₂. Several other classes of organics were examined at 532 nm and all were found to have a smaller nonlinear response than CS₂.

REFERENCES

- 1. I. C. Khoo, "Beam Application by Two Wave Mixing with Moving Grating in Liquid Crystals," Proceedings of the International Conference, "Optics of Liquid Crystals," Naples, Italy, July 15-18, 1986.
- Michael Lee, et al., "Theoretical Determination of Nonlinear Molecular Polarization Using Effective P₁-Electron Hamiltonian," Proceedings of the International Conference, "Optics of Liquid Crystals," Naples, Italy, July 15-18, 1986.
- 3. Eric W. Van Stryland, M. J. Soileau, Arthur L. Smirl, and William E. Williams, Phys. Rev. B 23, 2144-2151 (1981).
- M. J. Soileau, William E. Williams, and Eric W. Van Stryland, IEEE J. Quantum Electron QE-19, 731-735 (1983).
- 5. William E. Williams, M. J. Soileau, and Eric W. Van Stryland, Opt. Commun. 50, 256-260 (1984).
- 6. Eric W. Van Stryland, H. Vanherzeele, M. A. Woodall, M. J. Soileau, Arthur L. Smirl, Shekhar Guha, and Thomas F. Boggess. Opt. Eng. 24, 613 (1985).

NONLINEAR OPTICAL PROPERTIES OF LIQUID CRYSTALS

- 7. Eric W. Van Stryland, M. A. Woodall, H. Vanherzeele, and M. J. Soileau, Opt. Lett. 10, 490-492 (1985).
- Shekhar Guha, Eric W. Van Stryland, and M. J. Soileau, Opt. Lett. 8. 10, 285-287 (1985).
- M. J. Soileau, Shekhar Guha, William E. Williams, Eric W. Van 9. Stryland, J. L. W. Pohlmann, E. J. Sharp, and G. Wood, Mol. Cryst. Liq. Cryst. 127, 321-330 (1984).

TABLE I

The molecular structure of the samples studied are of the form:

	r	'-«	у-с , Н	= 14 - 6		
Sample	Color	R ₁	R,	P _c (kW) at 532 nm	(cm/GW) at 532 nm	n ₂ x10 ¹³ (esu) at 1064 nm
MEBBA	Orange	СН,	C,H,	7±1	.55±.05	6±1
ETBBA	Light Yellow	C ₂ H ₅	C,H,	8±1	.5 ±.05	17±2
IPBBA	Light Yellow	C3H4	C4H8	8±1	.5 ±.05	13±2
BBIPA	Orange	C ₄ H ₉	C,H,	7±1	.5 ±.05	12±2
PEBBA	Orange	C ₅ H ₁₁	C₄H,	7±1	.55±.05	14±2
C3,	Clear			8±1	Small	130

$$R_{I} - \langle -C = N - \langle -R_{I} \rangle$$

ч.

:



-

.

.

.

5. LIST OF ATTENDEES

FEMTOSECOND TIME-RESOLVED SPECTROSCOPY

November 8, 1988

N	A	M	IE

Ron Antos

Bill Clark

Brian Monson

Greg Salamo

Edward Sharp

lan Walmsley

Gary L. Wood

AFFILIATION

University of Rochester

NVEOC

NVEOC/University of Arkansas

NVEOC/University of Arkansas

NVEOC

University of Rochester

NVEOC