

A PROGRAM OF BASIC RESEARCH FOR HIGH POWER SWITCHING
AND OTHER HIGH POWER DEVICES

FINAL REPORT

MARTIN A. GUNDERSEN

MAY 23, 1989

U.S. ARMY RESEARCH OFFICE

GRANT NUMBER: DAAG29-85-K-0240

UNIVERSITY OF SOUTHERN CALIFORNIA
DEPT. OF ELEC. ENGR.-ELECTROPHYSICS
LOS ANGELES, CA 90089-0484

DTIC
ELECTE
JUN 19 1989
E D

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED

AD-A209 201

89 6 16 088

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION <u>Unclassified</u>		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited.	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(S) <u>ARO 22998.25 PH</u>	
6a. NAME OF PERFORMING ORGANIZATION University of Southern California	6b. OFFICE SYMBOL <i>(if applicable)</i>	7a. NAME OF MONITORING ORGANIZATION U. S. Army Research Office	
6c. ADDRESS (City, State, and ZIP Code) University Park Los Angeles, CA 90089-0484		7b. ADDRESS (City, State, and ZIP Code) P. O. Box 12211 Research Triangle Park, NC 27709-2211	
8a. NAME OF FUNDING / SPONSORING ORGANIZATION U. S. Army Research Office	8b. OFFICE SYMBOL <i>(if applicable)</i>	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER <u>DAAG 29-85-K-0240</u>	
8c. ADDRESS (City, State, and ZIP Code) P. O. Box 12211 Research Triangle Park, NC 27709-2211		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO.	PROJECT NO.
11. TITLE (Include Security Classification) A Program of Basic Research for High Power Switching and Other High Power Devices (Unclassified)			
12. PERSONAL AUTHOR(S) Gundersen, Martin A.			
13a. TYPE OF REPORT Final Technical	13b. TIME COVERED FROM <u>9-1-85</u> TO <u>2-28-89</u>	14. DATE OF REPORT (Year, Month, Day) 1989 May 23	15. PAGE COUNT 10
16. SUPPLEMENTARY NOTATION The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) High power switching, high power devices, Back lighted thyatron (BLT), optoelectronic bistability	
FIELD	GROUP		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The study of the physics of thyatron type switches under this contract has led to a new low pressure glow discharge switch that has a number of features that are desirable for high power applications. The switch has achieved high stand-off voltage and peak current (70 kA), has very fast current rate of rise, and operates near the glow-to-arc transition in hydrogen and other gases. It appears to have intriguing scaling possibilities. In addition, we demonstrated a cold, hollow cathode that operates with much higher current densities than dispenser and oxide thermionic cathodes -- without forming an arc. Current densities that are about 2 orders of magnitude over heated cathode current densities -- 10,000 A/cm ² vs. 100 A/cm ² -- have been achieved over cathode areas of approximately 1 cm ² . 20,000 A peak current is readily achieved in a simple, unheated configuration. Finally, in a different area, an optoelectronic bistability in GaP has been observed. The bistable mechanism is based on trap filling, and has possible applications to optically integrated devices.			
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL		22b. TELEPHONE (Include Area Code)	22c. OFFICE SYMBOL

SUMMARY OF RESEARCH FINDINGS

A low pressure glow discharge switch that has a number of features that are desirable for high power applications has been designed and operated. The switch has achieved high stand-off voltage (30 kV), and peak current (70 kA), has very fast current rate of rise, and operates near the glow-to-arc transition in hydrogen or helium. It appears to have intriguing scaling possibilities. Closure is initiated by light incident on the back of the cathode. We call it a BLT (Back-Lighted Thyatron). Surface damage within the area of illumination is less than surrounding areas, in contrast to most laser triggered switches. We have continued to develop our new high power glow discharge switch for pulsed power applications (Appl. Phys. Lett. 49, 494 (1986)). The switch is a back-of-the-cathode light-activated thyatron type switch (BLT). This switch should be considered for applications where high power thyatrons are a limitation. The current research effort includes a detailed study of the operation of this switch directed towards optimizing switch performance. Two experimental switches have been built with removable electrodes that allow for the testing of different electrode materials and hole sizes. An experimental circuit and gas handling vacuum system has been set up and is being used to study switch operation. Peak current, maximum standoff voltage, current rate of rise, delay and jitter have been measured and show promising results.

Several interesting results have been recently obtained pertaining to hydrogen thyatrons and related plasma physics. A severe limitation of the thyatron as a high-power closing switch is the maximum repetition rate. Through a time-dependent theoretical plasma calculation and innovative experimental measurements, a much better understanding of the recovery phase of a hydrogen thyatron has been obtained. This work has shown that the atomic temperature plays a very important role in the rate of recovery. To make the required measurements, a new method appropriate for use in a hydrogen thyatron has been developed to measure the time-resolved electron density.

We have found a method for optically gating -- *opening and closing* -- a high voltage glow discharge. The switch has operated reliably at currents of the order of 20 mA, and the experiments yield information on a new method for optical control of the glow discharge.

The experimental results were obtained using a hollow electrode discharge structure, or back lighted thyatron (BLT), in parallel with a small capacitor. The discharge is initiated and extinguished by a short pulse of light from a UV flashbulb. The current is supplied by a high voltage supply through a current limiting resistor. The switch is filled with H₂ to about 0.5 torr and will hold off ~ 1.5kv. When the lamp is flashed once a glow discharge is initiated at 20mA with a forward drop of ~ 200v. When the lamp is flashed a second time the discharge is extinguished and the voltage returns to ~ 1.5kv.

These results demonstrated a reliable optically controlled gas opening switch. Research has established the feasibility of the BLT switch, and has also defined areas of switch studies, and applications of both the switch, and the principles upon which the switch is based. It is possible to achieve higher current, higher di/dt, and other results (described below), in this new family of switches, which operate in a glow discharge. It has thus been possible to establish that this glow, thyatron-type switch is a candidate to replace spark gaps, and hence extend applications.



For	
&I	<input checked="" type="checkbox"/>
ed	<input type="checkbox"/>
tion	<input type="checkbox"/>
ion/	
lity Codes	
avail and/or	
Special	

Dist
A-1

Recently this laboratory demonstrated a cold, hollow cathode that operates in thyatron type switches at *higher* currents than dispenser and oxide thermionic cathodes -- without forming an arc. Current densities that are about 2 orders of magnitude over heated cathode current densities -- $10,000 \text{ A/cm}^2$ vs. 100 A/cm^2 -- have been achieved over cathode areas of approximately 1 cm^2 . 20,000 A peak current is readily achieved in a simple, unheated configuration, and it may be possible to extend performance to peak currents over 100,000 A. In addition, this cathode has demonstrated thyatron operation with greatly improved dI/dt , 100 % reverse current capability, and lower forward drop. This is an anomalously high regime of operation for a cold cathode operating in a glow discharge plasma, and is of interest because in spite of the considerable phenomenological understanding of gas discharge phenomenon, these data were not predicted, and these results apparently will have important device applications. Although in the past higher but localised current densities have been achieved through the formation of filamentary arcs, devices (e.g. spark gaps) tend to be limited melting, sputtering and cratering of electrode material, and addition of electrode material to the arc plasma. This new cathode allows currents that formerly required arc-type devices, such as spark gaps.

An optoelectronic bistability in GaP has been observed. The bistable mechanism is based on trap filling, and has several possible applications. This simple bistable device can be realized using a commercial light emitting diode. The bistability is based on a negative resistance effect that can be observed in commercial GaP light emitting diodes (LEDs). An optical bistability is observed in both luminescence intensity and peak wavelength, and is produced by light incident on an electrically biased sample. The optical bistable operation with the GaP LED differs from that reported in semiconductors such as InSb, InAs, GaAs and CdHgTe, which are based on optical nonlinearity and typically use the same light for input and output. Also, the effect reported here is not a change in transmitted light intensity through a Fabry-Perot resonator due to an intensity-dependent refractive index change. The bistable states were shown to switch with an optical gating. The bistable mechanism was explained as a consequence of traps affecting the carrier characteristics (which also results in the negative resistance region of the diode I-V curve). It is also suggested that optically coupled devices may be possible in an integrated form.

The technological relevance of this work is in several important areas. These include the excimer laser industry, accelerators and beam switching applications in high energy physics, and several defense related activities. Applications to excimer lasers have generated considerable interest.

In addition to the switch work, additional applications include electron and ion beams, x-ray and microwave production, modulator development for various applications, a new superemissive cathode, applications for the cathode, and applications to plasma loaded devices such as accelerators and plasma lenses. These applications are being pursued independently, and are not considered in detail in this report. However, the potential impact supports the value, and encourages the further technological research and development of the present effort. As an example, the superemissive cathode produces $10,000 \text{ A/cm}^2$ over $\approx 1 \text{ cm}^2$. This should be compared to cathodes that are presently

considered highly emissive -- with $\approx 50 \text{ A/cm}^2$! Details that have recently been published in Physical Review Letters.

A parenthetical result is the new BLT application for high energy physics plasma lenses. The lens is based on a hollow cathode stable Z-pinch plasma that operates in a superdense glow mode, and has the following demonstrated characteristics: Current density 10 to 40 kA/cm², plasma density $3 \times 10^{15} \text{ cm}^{-3}$, the plasma extends very uniformly over an area of $\sim 1 \text{ cm}^2$, and the current pulse length is variable between $\approx 10 \text{ ns}$ and $10 \mu\text{s}$. Active focussing due to the magnetic field of the high current plasma and self focussing due to the strong radial wakefields generated in the beam-plasma interaction for a 20 Mev and 50 Gev have been analyzed.

PUBLICATIONS

"Measurement of excited-state densities during high-current operation of a hydrogen thyatron using laser-induced fluorescence," D.A. Erwin and M.A. Gundersen, *Appl. Phys. Lett.* **48**, 1773 (1986).

"Determination of electric field and electron temperature in the positive column of a high-power hydrogen thyatron from non-intrusive measurements," D.A. Erwin, J.A. Kunc and M.A. Gundersen, *Appl. Phys. Lett.* **48**, 1727 (1986).

Book Review, "High speed pulse technology," by Frank B.A. Frungel, *IEEE J. Quant. Electr.* **QE-21** 1974 (1985).

"Semi-empirical Formalism for Wavevector Dependent Deep Level Impurity Wavefunctions in Semiconductors," H-H. Dai, C.W. Myles, and M.A. Gundersen, Meeting of the American Physical Society, *Bull. Am. Phys. Soc.* **31**, 503 (1986).

"Fundamental processes in high current glow discharge switches," M.A. Gundersen, J.A. Kunc, D. Erwin, and C. Braun, Proceedings, Fifth IEEE Pulsed Power Conference, June 10-12, 1985.

"A low pressure, light initiated, glow discharge switch for high power applications," G.F. Kirkman and M.A. Gundersen, *Appl. Phys. Lett.* **49**, 494 (1986).

"Research issues in power conditioning," M.A. Gundersen, R. DeWitt, A.K. Hyder, C.R. Jones, J.A. Kunc, M.J. Kushner, E.P. Muntz, G. Schaefer, and P.F. Williams, Proceedings, 1986 Seventeenth Power Modulator Symposium, Hyatt Seattle, Seattle, Washington, June 23-25, 1986.

"A linear thyatron for developmental research," C.G. Braun, D.A. Erwin, G.F. Kirkman, and M.A. Gundersen, Proceedings, 1986 Seventeenth Power Modulator Symposium, Hyatt Seattle, Seattle, Washington, June 23-25, 1986.

"A semi-empirical formalism for the calculation of deep level wavefunctions in k space," H-H. Dai, M.A. Gundersen, and C.W. Myles, *Phys. Rev. B.* **33**, 8234 (1986).

"Fundamental processes affecting recovery in hydrogen thyatrons," C. G. Braun, D. A. Erwin and M.A. Gundersen, *Appl. Phys. Lett.* **50** (19), 1325 (1987).

"High power hollow electrode thyatron-type switches," K. Frank, E. Boggasch, J. Christiansen, A. Goertler, W. Hartmann, C. Kozlik, G. Kirkman, C. G. Braun, V. Dominic, H. Riege and M.A. Gundersen, Proceedings, Sixth IEEE Pulsed Power Conference, 213, June (1987).

"High power pseudospark and BLT switches," K. Frank, E. Boggasch, J. Christiansen, A. Goertler, W. Hartmann, C. Kozlik, G. Kirkman, C. G. Braun, V. Dominic, M.A. Gundersen, H. Riege and G. Mechttersheimer, *IEEE Trans. Plasma Science*, Vol. **16** (2), 317 (1988).

"Fiber optic triggered high-power low-pressure glow discharge switches," C.G. Braun, W. Hartmann, V. Dominic, G. Kirkman, M. Gundersen and G. McDuff, *IEEE Trans.*

Electron Devices, Vol. 35, (4), 559 (1988).

"A flashlamp triggered high power thyatron type switch with remarkable plasma characteristics," G. Kirkman, W. Hartmann, and M.A. Gundersen, *App. Phys. Lett.* 52, 613 (1988).

"Switch developments could enhance pulsed-laser performance," S. Spencer Merz and M.A. Gundersen, *Laser Focus*, 70 (1988).

"An optoelectronic bistability in gallium phosphide," M.S. Choi, J.H. Jur, and M.A. Gundersen, *App. Phys. Lett.* 52 (19), 1563 (1988).

"Phonon assisted indirect recombination of bound excitons in N-doped GaP, including near resonant processes," H. Dai, M.A. Gundersen, C. W. Myles and P. G. Snyder, *Phys. Rev. B* 37, 1205 (1988).

"Origin of anomalous emission in superdense glow discharge," W. Hartmann and M.A. Gundersen, *Phys. Rev. Lett.* 60, (23), 2371 (1988).

"Evidence for large area super-emission into a high current glow discharge," W. Hartmann, V. Dominic, G.F. Kirkman, and M.A. Gundersen, *App. Phys. Lett.* 53 (18), 1699 (1988).

"A super-emissive self heated cathode for high power applications," W. Hartmann, G. F. Kirkman, V. Dominic, and M.A. Gundersen, *IEEE Trans. Elect. Dev.* 36 (4), 825 (1989).

"Studies of Fundamental Processes in Plasma Devices," W. Hartmann, G. Kirkman, and M.A. Gundersen, Particle Beam Physics Topical Group/American Physical Society, Baltimore, Maryland, April 18-21, 1988, *Bull. Am. Phys. Soc.* 33, 1082 (1988).

"New High Power Thyratrons for High Energy Physics Applications," W. Hartmann, G. Kirkman, M.A. Gundersen, K. Frank, and J. Christiansen, Particle Beam Physics Topical Group/American Physical Society, Baltimore, Maryland, April 18-21, 1988, *Bull. Am. Phys. Soc.* 33, 1082 (1988).

"A plasma lens candidate with highly stable properties," G.F. Kirkman, H. Figueroa, and M.A. Gundersen, *Proceedings of the 1989 Workshop on Advanced Accelerator Concepts*, Lake Arrowhead, California, Jan. 9-13, 1989.

"High -power thyatron-type switch for laser applications," G. Kirkman, W. Hartmann, T.Y. Hsu, R.L. Liou, P. Ingwersen, M. Gundersen and S.S. Merz, *SPIE Proceedings* 1046, Los Angeles, California, Jan. 19-20, 1989.

"An analysis of the anomalous high current cathode emission in pseudo-spark and BLT switches," W. Hartmann, V. Dominic, G. Kirkman, and M.A. Gundersen, *J. Appl. Phys.*, to be published May 1989.

PRESENTATIONS

"Radiative Processes in a Hydrogen Glow Discharge," J.A. Kunc, C. Braun, D. Erwin, and M.A. Gundersen, NATO Advanced Study Institute Program, Radiative Processes in Discharge Plasmas, Pitlochry, Scotland, June 23 to July 5, 1985.

"Laser-Induced Fluorescence for the Study of Glow Discharges," D. Erwin, C. Braun, J.A. Kunc, and M.A. Gundersen, NATO Advanced Study Institute Program, Radiative Processes in Discharge Plasmas, Pitlochry, Scotland, June 23 to July 5, 1985.

"Laser-Induced Fluorescence Diagnostics in High-Current Glow Discharge Plasmas," D. Erwin and M.A. Gundersen, 38th Annual Gaseous Electronics Conference, Monterey, California, October 15-18, 1985.

"An Analytical Solution of a Three Level Atomic Model for Non-Equilibrium Argon Plasmas," C. Braun, J. Kunc, and M.A. Gundersen, IEEE LEOS Meeting at University of Southern California, November 14, 1985.

"Optical Energy Extraction from the Triplet States of Molecular Hydrogen," G.F. Kirkman and M.A. Gundersen, IEEE LEOS Meeting at University of Southern California, November 14, 1985.

"Deep Level Wavefunctions in Semiconductors," H-H. Dai and M.A. Gundersen, IEEE LEOS Meeting at University of Southern California, November 14, 1985.

"Model for Phonon-assisted Indirect Recombination at N-bound Exciton in GaP," H. H. Dai, C.W. Myles, P.G. Snyder, and M.A. Gundersen, Meeting of the American Physical Society, Bull. Am. Phys. Soc. 31, 504 (1986).

"Semi-empirical Formalism for Wavevector Dependent Deep Level Impurity Wavefunctions in Semiconductors," H-H. Dai, C.W. Myles, and M.A. Gundersen, Meeting of the American Physical Society, Bull. Am. Phys. Soc. 31, 503 (1986).

"Research Issues in Power Conditioning," R. DeWitt, M.A. Gundersen, A.K. Hyder, C.R. Jones, J.A. Kunc, M.J. Kushner, E.P. Muntz, G. Schaefer, and P.F. Williams, 1986 Seventeenth Power Modulator Symposium, Hyatt Seattle, Seattle, Washington, June 23-25, 1986.

"A Linear Thyatron for Developmental Research," C.G. Braun, D.A. Erwin, G.F. Kirkman, and M.A. Gundersen, 1986 Seventeenth Power Modulator Symposium, Hyatt Seattle, Seattle, Washington, June 23-25, 1986.

"Fundamental processes in high current glow discharge switches," M.A. Gundersen, J.A. Kunc, D. Erwin, and C. Braun, Proceedings Elektronenröhren und Vakuumelectronik, NTG-Fachberichte 95, 94 (1986).

"Light Activated Pseudospark High Power Switches Research," M.A. Gundersen, University of Erlangen, Erlangen West Germany, May 9, 1986.

"Laser Induced Fluorescence for Power Switches Research," M.A. Gundersen, Technische Universität München, May 12, 1986.

"A New High Power Switch," M.A. Gundersen, Sandia National Laboratory, May 19, 1987.

"Plasma Dynamics of a New High Power Switch and Application to Plasma Accelerators," M.A. Gundersen, presented to PS division, C.E.R.N., Geneva Switzerland, June 10, 1987.

"High Power Hollow Electrode Thyatron-type Switches," K. Frank, E. Boggasch, J. Christiansen, A. Goertler, W. Hartmann, C. Kozlik, G. Kirkman, C. G. Braun, V. Dominic, M.A. Gundersen, and H. Riege, Sixth IEEE Pulsed Power Conference, Washington D. C., July 2, 1987.

"High Power Electronics," M.A. Gundersen, Quantum Electronics Seminar, University of Southern California, Los Angeles, California, December 2, 1987.

"Optically Triggered High Power Glow Discharge Switches," W. Hartmann, G. Kirkman, V. Dominic, and M.A. Gundersen, 1988 High-Voltage Workshop, Monterey, California, March 8-10, 1988.

"The BLT - A High Current Cold Cathode Switch," G. Kirkman, W. Hartmann, V. Dominic, and M.A. Gundersen, 1988 Tri-Service Cathode Workshop, Ft. Monmouth, New Jersey, March 22-24, 1988.

"New High Power Thyratrons," G. Kirkman and M.A. Gundersen, Argonne High Energy Physics, Advanced Accelerator Test Facility Workshop, Argonne, Illinois, April 6-7, 1988.

"Fundamental Processes in Plasma Devices," G. Kirkman and M. A. Gundersen, Argonne High Energy Physics, Advanced Accelerator Test Facility Workshop, Argonne, Illinois, April 6-7, 1988.

"Studies of Fundamental Processes in Plasma Devices," W. Hartmann, G. Kirkman, and M.A. Gundersen, Particle Beam Physics Topical Group/American Physical Society, Baltimore, Maryland, April 18-21, 1988, Bull. Am. Phys. Soc. 33, 1082 (1988).

"New High Power Thyratrons for High Energy Physics Applications," W. Hartmann, G. Kirkman, M.A. Gundersen, K. Frank, and J. Christiansen, Particle Beam Physics Topical Group/American Physical Society, Baltimore, Maryland, April 18-21, 1988, Bull. Am. Phys. Soc. 33, 1082 (1988).

"Optoelectronic bistability in gallium phosphide," M.S. Choi, J.H. Jur, and M.A. Gundersen, 1988 Conference on Lasers and Electro-Optics 59, 244, Anaheim, California, April 27, 1988.

"A super-emissive cathode," M.A. Gundersen, UCLA, May 6, 1988.

"An experimental plasma lens device," M.A. Gundersen, SLAC Workshop on Plasma Lenses, Stanford, California, May 9, 1988.

"Preliminary results from the III-V pulsed power device research program at USC," M.A. Gundersen, Semiconductor Switch Workshop, Norfolk, Virginia, May 23-24, 1988.

"A review of high power hollow electrode thyatron-type switches," M.A. Gundersen, 1988 IEEE International Conference on Plasma Science, Seattle, Washington, June 6-8, 1988 (invited).

"Studies of Fundamental Processes in High Power Switches," W. Hartmann, G. Kirkman, V. Dominic, and M.A. Gundersen, European Particle Accelerator Conference, Rome, Italy, June 7-11, 1988.

"High power hollow cathode glow discharge switches," W. Hartmann, G. Kirkman, V. Dominic, and M.A. Gundersen, 18th Power Modulator Symposium, Hilton Head, South Carolina, June 20-22 1988.