

FILE COPY

6

MEMORANDUM REPORT BRL-MR-3773

BRL

AD-A210 233

A SIMPLE SCREW THREAD MODEL FOR USE
IN FINITE ELEMENT STRESS ANALYSIS

J.M. BENDER

JULY 1989

SDTICD
ELECTE
JUL 12 1989
Cb H

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

*Original contains color
plates: All DII reproductions
will be in black and
white.

89 7 11 258

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Form Approved
 OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED.	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE		4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-MR-3773	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-MR-3773		5. MONITORING ORGANIZATION REPORT NUMBER(S)	
6a. NAME OF PERFORMING ORGANIZATION USA Ballistic Research Lab	6b. OFFICE SYMBOL (if applicable) SLCBR-IB-M	7a. NAME OF MONITORING ORGANIZATION	
6c. ADDRESS (City, State, and ZIP Code) Aberdeen Proving Ground, MD 21005-5066		7b. ADDRESS (City, State, and ZIP Code)	
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO. 626218A	PROJECT NO. 1L662618 AH80 ✓
		TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) A Simple Screw Thread Model for Use in Finite Element Stress Analysis			
12. PERSONAL AUTHOR(S) J. M. Bender			
13a. TYPE OF REPORT TR	13b. TIME COVERED FROM Sep 88 TO Dec 88	14. DATE OF REPORT (Year, Month, Day)	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) A technique for modelling screw threads, such as those found on artillery projectiles, has been developed. The model employs a matrix of gap elements which are easier to use and require less computation time than the current method of modelling actual threads with material elements. A comparison of this new method to the current method illustrates that there is no tradeoff of accuracy. →			
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL James M. Bender		22b. TELEPHONE (Include Area Code) (301) 278-6116	22c. OFFICE SYMBOL SLCBR-IB-M

TABLE OF CONTENTS

I. INTRODUCTION..... 1
II. METHODOLOGY..... 2
III. RESULTS..... 5
IV. DISCUSSION..... 5
REFERENCES..... 9
DISTRIBUTION LIST..... 10



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

I. INTRODUCTION

Structural analysis of projectiles and other ballistic components often require the modelling of screw threads. Typically, many finite elements are required in the immediate vicinity of the joint to accurately define and model a thread. In addition, reconciling the effect of dimensional tolerances of threads is not a simple effort. For example, if an analyst were required to perform a complete analysis of a threaded region, including tolerance considerations, at least four iterations would be required. These would include the mating of large and small pitch diameter male threads (within the tolerance range) with both large and small female threads (also within tolerances).

A new technique for modelling threads was developed during a study of ogive failures of the M483 155-mm artillery projectile to simulate the coupling of the aluminum ogive to the steel body. The technique employs a simple matrix of gap elements to model thread behavior as opposed to the labor-intensive method of representing threads with a finite element mesh. Substantial time and computer memory savings can be realized by employing this technique with no penalty in accuracy.

These new "thread elements" greatly simplified the effort. Otherwise, it would have been necessary to use very small elements to accurately grid each of the threads in the joint region. For a dynamic analysis in which stress waves were a consideration, this would have required a very small time step which is proportional to element size in this case. The combination of small time steps and numerous elements would generate output data that may exceed the limits of the computer storage device. Also, the run times would be prohibitively long. For example, it requires one thread element (set of three gap elements) to model one thread pair and at least eight material elements to realistically mesh a single male or female thread. Also, slide lines would have to be included at the closing flanks which is built into the thread elements. The new technique is also useful in the study of thread fit and tolerances. The thread elements can be used to model these effects on the behavior of the overall structure by adjusting the "modulus" in the axial direction. This modulus might be determined from an experimental pull test on a thread specimen where a stress-strain curve can be developed for the thread "material". The modulus determined from such a test can then be input directly as a material property for the gap elements used to model threads. A set of three such gap elements are required to construct a standard thread element. The approach here has many benefits in analyzing coupled bodies. However, if the details of the stress and strain state in the vicinity of the threads must be studied, then there is no recourse other than the

construction of a detailed local model.

II. METHODOLOGY

The ANSYS finite element program is used for all analyses included in this report. However, any general finite element code with gap element capability could be used. The user must know a priori that small deformations are expected as there is no provision for releasing axial constraints should the threads completely decouple radially. The threaded joint used to develop this technique is found on the M483 155-mm artillery projectile between the steel body and aluminum ogive. An ongoing study of ogive failures provided the opportunity for the development of this technique. The original study of these failures was performed by Southwest Research Institute² whose finite element analysis includes gridding of the threaded region. Their analysis provides the "geometry" technique as a basis of comparison to the present "material model" technique for representing thread behavior.

A threaded joint has basically four possible responses to any given load. It can be sheared in tension or compression in response to a tensile or compressive axial load respectively. Also, the threads can either compress together or separate in response to a compressive or tensile radial load. The joint studied in this case has a buttress thread since the expected axial load can only act in one direction. A section of rotation of the threaded region is illustrated in Figure 1. There is virtually no chance that non-load bearing flanks will meet in this type of thread series.

A schematic representation of a buttress thread is shown in Figure 2 along with its finite element model. The flank gap element angle, θ , relative to the axis is defined to be the same as the actual flank angle and there is one radial gap element for each thread.

A gap element has only two properties: a stiffness modulus and coefficient of friction. The modulus of the closed gap elements, E_{eg} , is calculated by adding reciprocally the moduli of the two mating materials (the same as adding two spring constants in series, $E_{eg} = E_1 E_2 / (E_1 + E_2)$). Since each "spring" is only half the length typically used in this well-known equation, the modulus must be multiplied by 2. Thus, a gap element between aluminum and steel would have a

[2] Cox, P.A., et al, "A Root Cause Analysis of the M483A1 Ogive," Southwest Research Institute, April 1987.





Figure 1. Section of Rotation of the Threaded Joint.

Geometry Technique



Material Model Technique




Figure 2. Schematic Representation of a Buttress Thread and its Finite Element Model.

modulus of 15 Mpsi. Sliding is permitted after closure, and a coefficient of friction can be selected from a handbook or determined from other means.

Two finite element models of the threaded region are illustrated for comparison in Figure 3. The actual threads are modeled in the grid on the left and thread elements are depicted in the grid on the right. The dotted line on the left model represents the surface where internal pressure of 12,000 psi is applied.

III. RESULTS

One of the responses of the joint which can be measured is the separation of the closing faces. This gives an indication of the overall strength of the threads. The Southwest Research analysis predicts that the butt joint between the body and ogive will open .009 inch at peak load while the thread element model predicts a .010 inch separation indicating an agreement to within ten percent.

The gap separation indicated on the ANSYS color stress plot in Figure 4 compares favorably (within ten percent) with the plot above it of gap separation versus time from SRI. As far as stress levels in thread roots and crests are concerned the thread element model offers no information.

IV. DISCUSSION

The thread element model represents a method by which the analyst can more easily develop the finite element grid for jointed structures. A simple model is more easily understood both by the analyst and those to whom the results are conveyed. Also, the chances of modelling errors are reduced with less complex models.

In addition to model simplicity, less time is required for grid development and computer computations, often a concern with small networks. Also, fewer elements mean less computer storage space is needed. In some cases, the time and memory reductions can be significant. This is best illustrated when analyzing a structure for stress waves or vibration³.

[3] Bender, J.M. "Stress Waves Through Joints of Artillery Projectiles," Ballistic Research Laboratory-TR-2980, Jan 1989.




Figure 3. Comparison of Finite Element Models.

When performing a finite element dynamic analysis, the time step is a function of the element size³. The element size for a thread element is the distance between two threads. In contrast, the geometry method may require the use of many elements to span a thread. Consequently, the time step must be much smaller to accomodate the smaller elements for accurate modelling of dynamic effects such as vibration and stress waves. The disadvantage with smaller time steps is that many more iterations are required during the time span of the analysis. For example, if element size is reduced to one fourth of its original size, the time step is likewise reduced. This means it will take four times the number of time steps to span the duration of the analysis since each time step represents one computation of strains. Almost always, this means a similar increase in computer time and memory storage.

[4] Kohnke, P.C., ANSYS Theoretical Manual, Swanson Analysis Systems, Inc., 1983.

OGIVE DYNAMIC ANALYSIS
 NODE 452 VS NODE 883





Figure 4. Comparison of Models' Responses.

REFERENCES

- [1] Swanson Analysis Systems, Inc., ANSYS Finite Element Program, Revision 4.3.
- [2] Cox, P.A., et. al. "A Root Cause Analysis of the M483A1 Ogive Failure," Southwest Research Institute, April 1987.
- [3] Bender, J.M., "Stress Waves Through Joints of Artillery Projectiles," Ballistic Research Laboratory Technical Report TR-2980, January 1989.
- [4] Kohnke, P.C., ANSYS Theoretical Manual, Swanson Analysis Systems, Inc., 1983.
- [5] Timoshenko, S.P., and Goodier, J.N., Theory of Elasticity, Prentice-Hall, 1970.
- [6] Kolsky, H., Stress Waves in Solids, Oxford University Press, 1953.

DISTRIBUTION LIST

No. Of Copies	Organization	No. Of Copies	Organization
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	3	Commander USA AMCCOM, ARDEC ATTN: SMCAR-TDC, Gyorg SMCAR-TDA SMCAR-TDS Picatinny Arsenal, NJ 07801-5000
1	Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209	2	Commander USA AMCCOM, ARDEC ATTN: SMCAR-TSS Picatinny Arsenal, NJ 07801-5000
1	Commander USA Materiel Command ATTN: AMCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	6	Commander USA AMCCOM, ARDEC ATTN: SMCAR-LCU, E. Barrieres SMCAR-LCU-M M. Weinstock SMCAR-LCU, D. Robertson SMCAR-LCU-M, J. Sikra Picatinny Arsenal, Dover, NJ 07801-5000
1	Commander USA Materiel Command ATTN: DRCLDC 5001 Eisenhower Avenue Alexandria, VA 22333		
5	Commander USA AMCCOM, ARDEC ATTN: SMCAR-SC SMCAR-LC SMCAR-SE SMCAR-SA SMCAR-AC Dover, NJ 07801-5000	3	Commander USA AMCCOM, ARDEC ATTN: SMCAR-LCA, B. Knutelski SMCAR-LCS, K. Rubin Dover, NJ 07801-5000
5	Commander USA AMCCOM, ARDEC SMCAR-SCF, K. Pflieger SMCAR-SCS-E, J. Blumer SMCAR-SCF, G. DelCoco Picatinny Arsenal, NJ 07801-5000	7	Commander USA AMCCOM, ARDEC ATTN: SMCAR-SCF, C.J. McGee SMCAR-SCA, S. Goldstein SMCAR-SCA, F.P. Puzychki SMCAR-SCA, E. Jeeter SMCAR-SCF, M.J. Schmitz SMCAR-SCF, L. Berman SMCAR-SCZ, P. Petrella Picatinny Arsenal, NJ 07801-5000
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001		

DISTRIBUTION LIST

No. Of Copies	Organization	No. Of Copies	Organization
4	Commander USA AMCCOM, ARDEC ATTN: SMCAR-LCA, S. Yim SMCAR-LCA, L. Rosendorf SMCAR-LCA, S.H. Chu SMCAR-LCW, R. Wrenn Picatinny Arsenal, NJ 07801-5000	1	Commander ATTN: Army Fuze Mgmt Proj Of SMCAR-FU Picatinny Arsenal, Dover, NJ 07801-5000
1	Product Manager for 30mm Ammo ATTN: AMCPM-AAH-30mm Picatinny Arsenal, NJ 07801-5000	2	Commander USA AMCCOM, ARDEC ATTN: Development Project Office For Selected Ammunitions SMCAR-DP Picatinny Arsenal, Dover, NJ 07801-5000
7	Commander SMCAR-SCM, W. Gadomski SMCAR-SCM, J. Mulherin SMCAR-SCS, B. Brodman SMCAR-SCS, T. Hung SMCAR-SCS, E. Maletesta Picatinny Arsenal, NJ, 07801-5000	2	Commander USA AMCCOM, ARDEC ATTN: Product Assurance Directorate SMCAR-QAR-RIB, D. Inhof NJ 07801-5000
3	Director USA AMCCOM, ARDEC Benet Weapons Laboratory ATTN: SMCAR-LCB-T SMCAR-LCB-TL SMCAR-LCB Watervliet, NY 12189	1	Commander USA AMCCOM, ARDEC ATTN: SMCAR-NS Picatinny Arsenal, NJ 07801-5000
2	Director Benet Weapons Laboratory ATTN: SMCAR-LCB-RA T. Simkins SMCAR-LCB-D, J. Zweig Watervliet, NY 12189	1	Commander USA AMCCOM, ARDEC ATTN: L. Goldsmith Picatinny Arsenal, NJ 07801-5000
2	Commander USA AMCCOM, ARDEC ATTN: SMCAR-SC, B. Shulman SMCAR-SC, Picatinny Arsenal, NJ 07801-5000	1	Commander USA Rock Island Arsenal ATTN: DRSMC-TSE-SW, R. Radkiewicz Rock Island, IL 61299
		2	Commander ATTN: SMCAR-SE Picatinny Arsenal, Dover, NJ 07801-5000

No. of Copies	Organization	No. of Copies	Organization
1	Commander USA AMMCCOM, ARDEC ATTN: SMCAR-ESP-L, Tech Lib Rock Island, IL 61299	1	Commander US Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5241
1	Commander USA Aviation Research and Development ATTN: AMSAV-E 4300 Goodfellow Blvd St. Louis, MO 63120	1	Commander USA Missile Command ATTN: AMSMI-RBL Redstone Arsenal, AL 35898
1	Director USA Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	Commander USA Missile & Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898
2	Director USA Research and Technology Laboratories (AVRADCOM) Ames Research Center Moffett Field, CA 94035	1	Commander USA Natick Research and Development Command ATTN: DRXRE, H. Sieling Natick, MA 01762
		2	Commander USA Tank Automotive Cmd ATTN: AMSTA-TSL Warren, MI 48090
		2	Dir, USA TRADOC Systems Analysis Activity ATTN: ATAA-SL WSMR, NM 88002
1	Commander USA Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703-5301	2	Commander USA Research Office ATTN: R. Weigle E. Saibel P.O. Box 12211 Research Triangle Park NC 27709
1	Commander USA Harry Diamond Labs ATTN: DELHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783	2	Commander USA Research Office P.O. Box 12211 ATTN: Technical Director Engineering Division Research Triangle Park, NC 27709

DISTRIBUTION LIST

No. Of Copies	Organization	No. Of Copies	Organization
1	Commander USA Research Office ATTN: J. Chandra Research Triangle Park, NC 27709	2	Commander US Materials Technology Laboratory ATTN: SLCMT-ATL Watertown, MA 02172-0001
2	Project Manager USA AMCCOM, ARDEC Cannon Artillery Weapons System ATTN: AMCPM-CAWS AMCPM-CAWS-A, R. DeKline Picatinny Arsenal Dover. NJ 07801-5000	1	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360
2	Project Manager Nuclear Munitions ATTN: AMCPM-NUC Picatinny Arsenal Dover, NJ 07801-5000	1	Commander Naval Ordnance Systems Command ATTN: ORD-9132 Washington, DC 20360
2	Project Manager Tank Main Armament Systems ATTN: AMCPM-TMA Picatinny Arsenal Dover, NJ 07801-5000	1	Commander Naval Sea Systems Command Washington, DC 20362
2	Product Manager Division Air Defense Gun ATTN: AMCPM-ADG Picatinny Arsenal Dover, NJ 07801-5000	1	Commander Naval Ship Systems Command Washington, DC 20360
2	Product Manager M110E2 Weapon System, DARCOM ATTN: AMCPM-M110E2 Rock Island, IL 61299	1	Commander Naval Ship Engr. Center Hyattsville, MD 20782
		1	Superintendent Naval Postgraduate School ATTN: Dir of Lib Monterey, CA 93940
		1	Commander Naval Air Development Center Johnsville Warminster, PA 18974
		1	Commander Pacific Naval Missile Center Point Mugu, CA 95042
		1	Commander Naval Research Laboratory Washington, DC 20375

DISTRIBUTION LIST

No. Of Copies	Organization	No. Of Copies	Organization
2	Commander Naval Ship Research and Development Center Bethesda, MD 20084	1	AFOSR ATTN: W.J. Walker Bolling AFB, Washington, DC 20332
4	Commander Naval Research Laboratory ATTN: W.J. Ferguson C. Sanday H. Pusey F. Rosenthal Washington, DC 20375	3	AFATL (DLA) Gun and Rocket Division ATTN: W. Dittrich, DLD D. Davis, DLDL Eglin AFB, FL 32542
2	Commander Naval Surface Weapons Center ATTN: G-13, W.D. Ralph Dahlgren, VA 22448	1	Air Force Armament Lab ATTN: AFTL DLODL Eglin AFB, FL 32542
1	Commander Naval Surface Weapons Center ATTN: Code X211, Lib Silver Spring, MD 20910	1	Gun Test Branch AD 3246 Test W/TETFG Eglin AFB, FL 32542
1	Commander Naval Surface Weapons Center ATTN: Code G-33, T.N. Tschirn Dahlgren, VA 22448	2	AFWL/SUL Kirtland AFB, NM 87117
2	Commander Naval Weapons Center ATTN: Code 3835, R. Sewell Code 3431, Tech Lib China Lake, CA 93555	2	ASD Wright-Patterson AFB, OH 45433
1	Commander Naval Ordnance Station Indian Head ATTN: Tech Library Indian Head, MD 20640-5000	1	ASD (ASAMCG) Tech Lib W-P AFB, OH 45433
2	Commandant USA Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905	1	AFML (T. Nicholas) W-P AFB, OH 45433
2	AFRPL ATTN: W. Andrepont T. Park Edwards AFB, CA 93523	1	Director U.S. Bureau of Mines Twin Cities Research Center P.O. Box 1660 Minneapolis, MN 55111
		2	Battelle Columbus Labs ATTN: L.E. Hulbert J.E. Backofen, Jr. 505 King Avenue Columbus, OH 43201
		2	Battelle Pacific NW Lab ATTN: M. Garnich M. Smith P.O. Box 999 Richland, WA 99352

DISTRIBUTION LIST

No. of Copies	Organization	No. of Copies	Organization
1	HQDA (SARD-TR) Washington, DC 20310-0001	1	Lawrence Livermore National Laboratory ATTN: Dr. R. Christensen P.O. Box 808 Livermore, CA 94550
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145	2	Sandia National Laboratory ATTN: Dr. C.W. Robinson Dr. Benidetti Applied Mechanics Department Engineering Mechanics Dept. Engineering Design Division Livermore, CA 94550
1	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000	1	Director Lawrence Livermore National Laboratory ATTN: Dr. Feng, Mr. Magness Livermore, CA 94550
2	Commander Armament RD&E Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	1	Director Los Alamos National Lab ATTN: Dr. Rabern Los Alamos, NM 87544
1	Commander USA Aviation Systems Cmd ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798	2	National Aeronautics and Space Administration Langley Research Center Langley Station Hampton, VA 23365
1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099	1	Director National Aeronautics and Space Administration Manned Spacecraft Center ATTN: Library Houston, TX 77058
1	Air Force Armament Lab ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000	1	Director NASA - Ames Research Center ATTN: Tech Lib Moffett Field, CA 94035
1	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI	1	Headquarters National Aeronautics and Space Administration Washington, DC 20546

DISTRIBUTION LIST

Aberdeen Proving Ground

- 6 Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen
AMXSY-G, E. Christman
AMXSY-OSD, H. Burke
AMXSY-TN, D. Metz
- 3 Cdr, USATECOM
ATTN: AMSTE-CE
AMSTE-TO-F
- 13 Dir, CRDEC, EA
ATTN: SMCAR-CL
SMCAR-CLB-PA, M. Miller
SMCAR-CLB-PA, D. Olson
SMCAR-CLB-PA, J. Huerta
SMCAR-CLD
SMCAR-CLY
SMCAR-CLN
SMCAR-CLN-D, L. Shaff
SMCAR-CLN-D, F. Dagostin
SMCAR-CLN-D, C. Hughes
SMCAR-CLN-D, R. Simak
SMCAR-CLN-D, M. Hayner
- 2 Dir, USACSTA
ATTN: Mr. Tag

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

BRL Report Number _____ Division Symbol _____

Check here if desire to be removed from distribution list. _____

Check here for address change. _____

Current address: Organization _____
Address _____

-----FOLD AND TAPE CLOSED-----

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T (NEI)
Aberdeen Proving Ground, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY LABEL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY



Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T (NEI)
Aberdeen Proving Ground, MD 21005-9989