

Air Force Space Technology Center Space Systems Division Air Force Systems Command Edwards Air Force Base, California 93523-500 9 8 07 0 5 9

#### Foreword

This document represents the final report for Task 8 Propulsion System Reliability Development, of the Research Applications SETA program. The work was performed over the period 30 June 88 to 24 February 1989.

The Air Force Project Officer for this task was Mr. David Perkins, AFAL/VSAB. The SAIC Program Managers were Dr. Robert Long and Mr. William Haynes. The task leader at SAIC was Mr. Joseph R. Fragola. The other principal technical contributors at SAIC were Lewie Booth and Dr. Yu Shen. We appreciate the assistance of Larry Quinn of AFAL in administering this task and Ms. Zun-Yan Wang and Ms. Carol Heymsfield of SAIC in the preparation of this report.

This report has been reviewed and is approved for distribution in accordance with the distribution statement on the cover and on the DD Form 1473.

CLARENCE J. C. COLEMAN, Capt, USAF

Chief, Advanced Concepts Branch

DAVID R. PERKINS Project Manager

FRANKLIN B. MEAD, JR., PhD / Chief, Future Technologies Section

FOR THE DIRECTOR

ROBERT C. CORLEY, PhD Deputy Director, Astronautical Sciences Division

#### NOTICE

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the fact that the Government may have formulated, furnished, or in any way supplied the solid drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any way licensing the hol'er or any other person or corporation, or conveying any rights or permission to manufacture, use of sell any patented invention that may be related thereto.



SECURITY CLASSIFICATION OF THIS PAGE					
REPORT	DOCUMENTATIO	N PAGE			Form Approved OMB No: 0704-0188
TA REPORT SECURITY CLASSIFICATION		16 RESTRICTIVE	MARKINGS	and gave group of a set of the se	
2a SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTIO	N / AVAILABILITY	OF REPORT	a de la compansión de la c
20 DECLASSIFICATION / DOWNGRADING SCHEDU	JLE	Approved Unlimited	for Public	Release; E	istribution is
A PERFORMING ORGANIZATION REPORT NUMB		5 MONITORING	ORGANIZATION	REPORT NUMP	IFR(S)
		AL-TP-89-	013		
De Home OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOU (If applicable)	7a. NAME OF N	MONITORING OR	SANIZATION	inter a land the second se
international Corporation		Astronaut	ics Laborat	tory (AFSC)	
oc AODRESS (City, State, and ZIP Code) 242 Madison Avenue, Suite 1100 New York NY 10173		75 ADDRESS(C AL/LSVF Edwards A	ity, State. and Z FB CA 93321	IP Сэзе) 1-энд00	899,269999,269,969,969,969,969,969,969,96
3a MAME OF FUNDING / SPONSORING ORGANIZATION	8b OFFICE SYMBOL (If applicable)	9 PROCUREME	NT INSTRUMENT	IDENTIFICATION	NUMBER
		F04611-8	8-C-0014		And the second state of the se
a: ADDRESS (City, State, and ZIP Code)		10 SOURCE OF	FUNDING NUMB	BERS	
		ELEMENT NO	NO.	NO	ACCESSION NO
		62302F	3058	00	25
Volume I: Executive Summary an 12 PERSONAL AUTHOR(S) Fragola, Joseph R.; Booth, Lewi 13a. TYPE OF REPORT Final FROM <u>88</u>	d Report Body e; and Shen, Yu OVERED /04 TO <u>89/09</u>	14. DATE OF REF 89/06	ORT (Year, Mon	th, Day) 15. Pi	AGE COUNT 02
16.SUPPLEMENTARY NOTATION Volume 2 of this report contain	s Appendix B.				
17 COSATI CODES	18. SUBJECT TERMS	(Con. n reve	rse if necessary a	and identify by	block number)
FIELD GROUP SUB-GROUP	out, failure co	prrelation,	variability	control,	reusability,
21 08	risk management	;, reliabili	ty performa	nce indica	itors (PTO),
19. ABSTRACT (Continue on reverse if necessary) This report describes the effective development methodologies and	and identify by block r ort to identify	number) liquid and ations tech	solid propu	ilsion desi	.gn parameters.
propulsion relability for future is a section on current practice reliability enhancing methods	re launch vehic ce and data base	eles. Six k e assessment	ey recomment. This is	ndations ar followed b	e made. There by a section on and prioritiza:
tion of methodologies. Volume historical failure correlation	l contains Appe factors using t	endix A whic the SSME tes	h includes t and fligh	an investi nt history	gation of as an example,
a quick calculation of failure analysis of current US launch contains only Appendix B which performance of this study.	vehicles, and a is a compendium	hitory of U n of trip re	S launch ve ports accom	ehicles. V plished du	volume 2 ring the
UNCLASSIFIED/UNLIMITED SAME AS I	RPT DTIC USERS	UNCLASSIFI	ED		
22a NAME OF RESPONSIBLE INDIVIDUAL David R. Perkins		225 TELEPHONE (805) 275-	(Include Area Co 5640	ode) 22c OFFIC AL/LSV	te symbol VF
DD Form 1473, JUN 85	Previous editions are	obsolete.	SECURI	TY CLASSIFICATI	ON OF THIS PAGE

# TABLE OF CONTENTS

# SECTION

	Executive	Summary	1
	Objective.	······	2
	Key Recor	nmendations	2
	Backgrour	nd	5
1.0	(Task1)	Current Practice and Data Base Assessment	
	1.1	Current Practice	6
	1.1.1	Current Practice Background	6
	1.1.2	Major Activities Constituting Infrastructures	6
	1.1.3	Current Infrastructure Activities Affecting Reliability	8
	1.2	Data Base (Historical)	16
	1.2.1	Data Collection.	16
	1.2.2	Data Organization	16
	1.2.3	Representative Design Parameter Development	17
	1.3	Deficiencies of Current Aerospace Reliability Practice in	
		Application to Advanced Launch System Needs	17
	1.3.1	FMEAs/FMECAs.	35
	1.3.2	Quantitative Reliability Analysis	36
2.0	(Task 2)	Reliability Enhancing Methodologies:	00
	21	Lessons Learned	38
	211	Variability Control	38
	212	Reusability	38
	213	Performance Indicators	38
	214	Correlation Factors	38
	215	Correlation vs Engine Out	30
	2.2	Historical Data Analysis (Reliability Growth)	<u> </u>
	221	Y Shen's Methodology	41
	222	D. Llovd's Methodology	41
	223	Curve Fitting	44
	224	Bavesian	44
	2.2.4	Classical Binomial	50
	2.2.5	Baseline Beliability Enhancement Methodology Identification	50
	231	Proposed Infrastructure Controls to Enhance Reliability	52
	2.3.1	Rick Management	52
20	2.3.2 (Tack 3)	Augustification and Prioritization of Methodologies	60
3.0	(1055.0)	Tasting of Quantitative Methoda	~ ~ ~
	3.1 2.1.1	Comparison of the Methods of Section 2.2	63
	3.1.1		63
	3.1.2	Characteristic Curves and Reliability	68
	3.1.3	Evoluation of Qualitative Methods	68
	3.2	Top Down Analysis	68
	3.2.1	Product Design EMEAs	58
	3.2.2	Manufacturing Interference	70
	3.2.3	Driediting interfaces	70
	3.3	Prioritization of Methodologies	70
	Recommer	ndations	71
	References	5	74

# T NDIX A

A.1	An Investigation of Historical Failure Correlation and loss Using the Shuttle SSME Test and Flight History as an Example .	7 t
A 2	A Quick Calculation of the Effect of Failure Contention Factor vs Engine Out Capability	131
<u>A</u> .3	Reliability Analysis of Current US Launch Vehicles.	125
A.4	History of US Launch Vehicles	i na s
્ર⊎IX B (Se	e Volume II)	

.



Accesius For	
NTIS CRA&I DTIC TAB Unational cert Justificatio	
By Distribution /	
Availability	Cortes
Dist Specia	t / or il
A-1	

# EXECUTIVE SUMMARY

The Air Force currently has several ongoing propulsion technology development programs including the significant joint development with NASA of the Advanced Launch System (ALS). Previous investigation by Air Force Astronautics Laboratory and others has indicated that launch vehicle reliability is perhaps the key driving parameter for development program success.

Given the key role played by reliability, AFAL requested that SAIC undertake a study of propulsion system reliability development. The objective of this study was to identify, and where possible quantify and prioritize, propulsion techniques related to launch vehicle reliability.

The study was to include visits to an engine manufacturer, a launch vehicle systems contractor, and NASA sites to develop information to supplement literature searches and independent research to provide a base of information sufficient to allow SAIC to:

- Assess Current Practice and the Resulting Historical Reliability Data Base
- Investigate Potential Reliability Enhancing Methodologies and to
- Quantify and Prioritize the Methodologies

The Study results indicated that current launch vehicle reliability levels are in the order of 90 - 95%. This is substantially below future Air Force system requirements of 99 - 99.9%. Investigation into how these historical levels of reliability could be significantly improved resulted in the development of the following six key recommendations for the consideration of the Air Force and AFAL.

1. <u>Failure correlation factors</u> are key factors of interest to design decision makers. Specific studies, which address what factors have been achieved in the past and what design trades have been made to ensure the low factors quoted by contractors are achievable, appear to be lacking. The Air Force should consider requiring that such studies be undertaken.

2.<u>Variability Control</u>, especially of residual variability, may be the key barrier to high launch reliability achievement. The Air Force should consider requiring that some specific program for variability control be included in future propulsion technology development programs.

3. <u>Reusability</u> has been shown to have indirect, potentially negative, impacts on high reliability achievement. The trade-offs which exist between high reliability and reusability should be clearly identified and included in propulsion programmatic decision making.

4. <u>Bisk Management</u> has been shown to have potential benefits in maintaining the high reliability of orograms in other industries. The advisability of risk management being included as an integral part of propulsion system development should be considered.

5. <u>Reliability Performance Indicators</u> should be developed whose trend trajectories lead, or presage, the occurrence of reliability problems so that program management action can be taken prior to the development of reliability problems.

6. <u>Reliability Growth Forecasting</u> is important during the development of systems with high reliability requirements. This is especially true when program economics prohibit extensive development test flights. Reliability growth approaches should be investigated and applied as appropriate to propulsion system development programs.

1

## OBJECTIVE

The objective of this effort was to identify, and where possible quantity and prioritize, liquid and solid upulsion design parameters, development methodologies, and production/operations techniques related abunch vehicle reliability.

#### **KEY RECOMMENDATIONS**

The following areas have been identified as having significant reliability impact. These areas each varrant further in-depth study if the high reliability goals of the Air Force advanced launch vehicle cograms are to be achieved in an operational system.

#### Failure Correlation\*

The percentage of failures which are likely to impact more than one engine in a multi-engine design is the critical design import. This percentage, or "failure correlation factor," must be well below 20% for chability oriented design approaches such as engine out capability to be effective. The lower that the design the more effective is this hubits to get extremely low factors (as low at 1%). On relations are used on recent engine design characteristics achieved on recent engine designs (e.g., 17% for the subject of the main engine test program). Finally, there did not appear to be any significant consideration given to be written to the low factors would be achieved in practice.

<u>Secommendation 1</u> - Failure correlation factors are key reliability parameters to Air Force laution of the design decision makers. Specific studies such as parameter design studies which address what inters have been achieved in the past and what design trades have been made to ensure the low factors quoted to be evident in the reliability designs appear to be lacking. It is recommended that these investigations of made prior to the selection of any design alternative.

## Variability Control

The currently achieved launch vehicle reliability has been shown by this investigation to be below 0.95 owaver, the investigation uncovered examples of reliabilities in other somewhat similar systems, such tacheal missile systems, which routinely achieve 0.99 and some which approach 0.999. These systems also operational reliabilities currently meet or exceed the reliability requirements for the Air Force theorem have achieved these high reliability levels through the use of intensive variability entroprograms. While it would be inappropriate to make any direct correlation between tactical missiles of such vehicles, it is also clear from a review of the failure data of mature launch systems that the or transplicantly higher reliabilities may be the residual variability constrained by the or and back that the programs. A cursory review of other somewhat compliant in products, while it would be and recent. Air Force and gus turbines and recent Air Force variability reduction studies performed as part of the set for program, provide further support for this argument.

<u>Aecommendation 2</u> - Residual variability may be the key barrier to high launch vehicle reliability ovement. For this reason, it is recommended that investigations be made into the effectiveness of the variability control programs such as Taguchi methods or alternatives. These investigations should

the patiention offed here is broader than that used traditionally by propulsion system designers. Then American successor of the difference be directed at determining the applicability of the methods to the launch vehicle production process. It is further recommended that some specific program for variability control be included throughout all phases of the advanced launch system program.

## 3. Reusability

Reusability is, on the surface, a design goal of significant program benefit. However, the benefits of reusability are significantly compromised if the reliability of an engine is adversely affected by the requirement. Besides the direct costs involved in developing a reusable design, there also appears to be significant indirect costs which are required to maintain reliability in a reusable design. For example, reusability by its very nature tends to decrease the production run. When production runs are decreased, investments in automated production equipment become less economical and the production process therefore tends to become more prototypical. Prototypical production, especially of complex equipment, increases the problems associated with variability control and therefore substantial postproduction testing may be required to ensure high reliabilities. A good example of such an indirect impact on reusability was seen at the Rocketdyne SSME production facility in Canoga Park, California.

<u>Recommendation 3</u> - Reusability has been shown to have indirect and potentially negative impacts on the achievement of high reliabilities at reasonable cost. The indirect impacts of reusability on reliability and cost through such mechanisms as variability control problems should be thoroughly investigated and the results of this investigation included in the programmatic decision making related to reusability.

#### 4. Risk Management

Achievement of high operational reliabilities in such areas as nuclear power plant safety systems have been significantly supported by a continually active program that attempts to identify the risks to reliable operation and to address them according to their importance. Such a risk management program has been investigated and recommended by NASA SRM & QA for future projects, but it is not clear whether a risk management program is planned for the acquisition of advanced launch systems.

<u>Becommendation 4</u> - The Air Force should investigate the advisability of incorporating a risk management program as an integral part of any launch system program.

#### 5. Reliability Performance Indicators and Trending

For high reliability programs it is important to identify, early on, symptoms of the process which presage deterioration in performance. This has been done in the financial community, in the commercial aircraft community and in the nuclear power safety community by the development of a set of "leading" performance indicators and developing performance trends based upon the indicator trajectories through time. If such a set of indicators could be developed and trended for advanced propulsion system development programs, the indicator trajectories might provide early warning of problems arising during development and operation. This early warning could provide the time required to institute corrective action before actual program reliability performance is affected.

<u>Recommendation 5</u> - The Air Force should develop as part of advanced propulsion system development programs a set of potential indicators of programmatic reliability performance. This indicator set should be based originally on historical information, but later updated and validated as advanced propulsion system development programs specific information becomes available.

#### Reliability Growth Analysis

In all developmental systems a certain degree of reliability growth is to be expected. However, program canagers need to know the pace of the expected growth so that they can determine if the program is likely or meet the operational reliability goals within developmental time constraints. An understanding of the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth process is therefore essential to the determination of the proper role to be played by history in the crewth suitable corrective action is implemented to prevent its recurrence, it is recognized that it would have is probability of occurring again diminished when it is utilized for predicting future performance. But by low much? The determination of how much each failure should be counted is important in order to establish the proper "calibration" for the reliability growth characteristic to be used to determine how we? In ability development is proceeding. Several approaches have been developed to address the issue of with. Among those developed are the early works of Duane at GE, that of David Lloyd of TRW, and that here reliable by Dr. Yu Shen of SAIC as part of this study. In addition, Bayesian approaches may show promise for improved growth forecasting.

Becommendation 6 - Reliability growth forecasting is important during the development of syclean ringh reliability requirements such as ALS. Accurate growth forecasts allow program in entries and ne early on if reliability requirements are likely to be met. (This is addressed y reductant when a smeeconomics prohibit extensive development test flights as is the met. (S). Several metric of tentily exist to allow for forecasts to be generated; however, further development is required to history a reasonable growth forecast is developed for advanced propulsion system development programs of tentily exist recommended that the concept of reliability growth be further developed as the applies of the propulsion system development programs.

#### BACKGROUND

The AFAL currently has several ongoing propulsion technology development programs that are aimed at iaunch vehicle applications. A fundamental goal for any new launch vehicle is low cost. One element of cost that is receiving increasing levels of national attention is the cost of unreliability. This issue was highlighted by the recent series of catastrophic launch failures. These failures included two Titans, a Delta, an Atlas, and a Shuttle. All were lost in a period of 2 years. Historical data bases indicate that in general, isunch vehicle reliability against catastrophic failure is approximately 0.92. This value is dominated by propulsion system failures and is unacceptably low for any future launch vehicles.

The traditional methodologies for the development of propulsion systems have involved the use of matricinal manufacturing methodologies coupled with traditional design methodologies that assume some measure of safety factor in the design process. The traditional issue that was fundamental to flaunch vehicle applications was that the vehicle payload capability was highly sensitive to the mass properties. Hence, margins were decreased to the maximum extent possible during the design phase. There remains a distinct development transition to flight weight hardware in most aerospace developments. Reliability was only subsequently evaluated as a secondary concern. Point estimate techniques for estimating application reliability were employed rather than rigorous statistical testing. Manufacturing process control was instituted after development in order to qualify vehicles for manned flight or higher confidence of success following catastrophic failures. It is apparent that in order to achieve higher levels of reliability in drepulsion systems, and hence in the launch vehicles, alternative development approaches need to be explored.

There have been several suggested approaches to achieving higher reliability. Design for reliability philosophies include redundancy techniques and higher design margins. Process control advocates point to human error contributions to failure and article to article variations, proposing that more automated production and higher levels of quality control and non-destructive testing will achieve desired reliability. It is fundamentally assumed that design engineers should be more aware of ultimate reliability and producibility issues as they pursue designs. Inevitably, the greatest stumbling block to achieving higher reliability goals is limited funding available for development and gualification programs and the historical reliability approach perspective, which consigns probablistic techniques to only the top most levels of program analysis and evaluation. While history has shown it to be true that in the ultimate design reliability not only costs nothing but will produce significant cost benefits, this is not true in the near term design development phase. Here reliability tasks increase, at least initially, the cost and they do so in an environment where funding is scarce and where reliability needs must compete with other more visible programmatic needs (such as performance upgrades). In such an environment of new program development within strict resource constraints reliability resources can be eroded in favor of programmatic needs considered more immediate unless investments in reliability are "fenced in" early and not confused with management reserves.

# 1.0 (TASK 1) CURRENT PRACTICE AND DATA BASE ASSESSMENT

#### Current Practice

#### 1.1.1 Current Practice Background

Corporations involved in the design, manufacture, test and operation of propulsion systems generally have infrastructures that result from specific government agency requirements. Those controls which exist within any given infrastructure that have an impact on reliability also exist largely due to government equirements. At the highest level these controls consist primarily of Failure Modes and Effects Analysis (MEAs) and Problem (or Failure) Reporting and Corrective Action Systems (PRACAs/FRACAs). Although these controls have had a positive impact on reliability the impact, because it is often somewhat indirect, a not readily measurable. Thus, it is difficult to ascertain quantitatively that spending a given amount of resources on FMEAs or PRACAs will in fact pay off. In addition, there are, at least in the initial phases of program development, few financial incentives for "better" reliability. Furthermore, even if there were coolity incentives, it would be difficult for manufacturers to know where is spend their scarce is ources to obtain the best reliability returns. This is primarily due to inconsistent or non-existent cability data bases.

The problem is further compounded by the constraint of sample size on the measurement of achieved is don'ty in highly reliable systems. In other words, to demonstrate that a given reliability has been is to even at a reasonable confidence level, a large number of systems must be tested. It is obvious that in the problem is not practical from a cost/schedule standpoint. This is not to say that presently duried reliabilities are inadequate to satisfy the previously and currently existing requirements. In fact, the attained reliability of any propulsion system is generally based on relatively small sample sizes and the underlying assumption that each propulsion system firing is independent of all others. This simply theats that while we may not know precisely (from a reliability standpoint) where we are now, we do know whate we are well enough to understand that we are far from the high reliability goals desired of future the propulsion systems.

cwever, the relevant question is not where we are now, but how can an improvement in reliability be merved? Because of the relative nature of this question, it may turn out that accurately predicting ability improvements is easier than measuring attained reliability.

- 1 E 2 Major Activities Constituting Infrastructures
- First billunding limitations it was not possible to revisit manufacturars in order to behavit from the total a instanced from the initial visit. The revisits would have concentrated not just on design, song and test, but on transportation and storage its well.

consecond visits would be used to form a clearer picture of the detailed approaches taken by liquid and or anufacturers.

revever, based on the initial visits taken, six major activities have been identified in the life cycle or propulsion system: design, manufacturing, test, transportation, storage, and operation. The intrustructure that has evolved has centered on design, manufacturing and test. Activities related to the pollation, storage and operation tend to be restricted to problem correction rather than a planned alongy to anticipate problems. <u>Design</u> - The Design activity primarily involves the creation of a system that meets the specified requirements of a contract. Typically a design is generated and goes through a design review process usually consisting of preliminary, critical, and final design reviews. The review of reliability requirement achievement during these reviews is currently based (because of the lack of a detailed historical data base for propulsion systems), upon the manufacturer's engineering judgement or on qualitative review of design specific failure modes whose elimination or mitigation is again based upon manufacturer's recommendations which are judgementally based and therefore difficult to objectively assess as to their probability of being successfully achieved in the implemented design.

<u>Manufacturing</u> - Once the transition is made from design to inanufacturing, the activities focus on how to best minimize the manpower and materials required to produce the system while satisfying duality control constraints. Manufacturing procedules and flot, diagrams are the primary electrarisms for this activity. Quality Control plans mutually prescribed by clients, primas at dimajor subcentractors are also imposed.

Testing activities primarily involve qualification and reastibility fosting. They are primarily intended to test the functional adequacy or the potential of a given design implementation. In this way they can clearly indicate that a propulsion system performance specification such as thrust to weight ratio, a specific impulse has not been achieved, but they only indirectly indicate lack of reliability achievement. This is especially true of new designs. These tests do not usually involve enough test time (or numbers of systems) to produce a statistically significant indication of system reliability capability. When failures do occur, they may have been induced by consciously over extending the design limits. In fact, the tests may be conducted to determine design weaknessus through fest failure so that the failures can be examined and corrective action taken to improve the design. These tests therefore may not always provide useful information concerning the assessment of system reliability capability although they certainly do produce information useful to reliability improvement.

<u>Transportation</u> - Transportation activities can have obvious negative impacts on reliability due to the influence of shock, vibration, humidity, and thermal transients. These and other environmental factors can act independently or synergistically to decrease reliability. Controls are in place dictating packaging and handling requirements primarily through specifications. Unfortunately, not all problem (or failure) reporting and corrective action systems feedback problems that occur because of inadequate package and handling requirements. Such a closed loop system would provide a mechanism for rewriting of specifications.

<u>Storage</u> - Like transportation, storage activities can also have a negative impact on reliability. This is true not only from the standpoint of environmental conditions, but storage time as well. When rocket booster dependent programs experience a delay, then all limited life items become factors affecting reliability.

Operation - The second sing one for booster rockets is a matter of a few hundred seconds with the proviso that some of the second secon

# 1.1.3 Current Infrastructure Activities Affecting Reliability

Although there are some specific differences between prime contractors and major subcontractors, in general the controls affecting reliability which are the responsibility of the reliability discipline are detability Predictions, Failure Modes and Effect Analysis (FMEAs) and Failure Reporting and Corrective Action systems (FRACAs). The quality control discipline has a direct impact on reliability but is not cormally a part of the reliability discipline. "Lessons Learned" is often a semi-formal approach to eliability improvement and when used, it is as likely to be found in the design group as the reliability group.

Dely the FRACA system provides a closed loop means of correcting problems. In their present form, PACAs are not structured to quantify reliability or to become a proactive part of measured (quantified; scability enhancement.



Figure 1. Existing infrastructure controls intended to emhance reliability.

Space 1 diustrates the six infrastructure activities as they relate to reliability activities. The most subjectly used reliability activities are:

- FMEAs
- Reliability Predictions/Trade-offs
- PRACA/FRACA Systems
- Measurement of Achieved Reliability

MEAs are and how they are used is described in the following section under "Reliability Eligible for deering Analysis". Reliability Predictions/Trade-offs are also discussed in the same section under the adding of "Quantitative Reliability Engineering Design Tools" along with other tools that are available to the ability engineers. Figure 2 contains a comprehensive list of reliability Tools and Techniques for CAFRACA Systems are discussed in detail in Section 1.1.3.2. Measurement of Achieved Reliability due to its complexity is treated separately in Section 2.2, "Historical Data Analysis (Reliability Growth)" and in Appendix A.3. "Reliability Analysis of Current US Launch Vehicles".

The purpose of Figure 1 is to illustrate the limited use of presently available reliability engineering techniques and tools as well as the limited use of information from activities such as transportation and storage.

It is clear, based on the information gathered to date, that no single company has utilized all the tools and techniques available to reliability engineers on any given project nor has the information from transportation and storage been fully utilized. The fact that all the resources of reliability technology have not been utilized is <u>not</u> a result of negligence on the part of manufacturers. Often they may not be provided with specific requirements to address all these issues by their government customers and are not normally funded to conduct these types of analyses.

Although not directly related to launch vehicle reliability, a recent example of how the storage activity can affect reliability is given by the recently launched TDRSS spacecraft. After the Challenger accident the spacecraft spent an extra 2 1/2 years on the ground. Deterioration was suspected in the bolt cutter ordinance and for this reason a reliability study was conducted by the contractor. The study resulted in the determination that the bolt cutters required replacement. The successful launch of TDRSS is now a matter of record. Total credit for this success cannot be taken by the individuals involved in this reliability analysis, but a significant contribution was made to this success as a result of diligent ordinance and reliability engineers taking the initiative and going beyond typical practice. The only way to make such protection "routine" is to expand current reliability practice so as to create an infrastructure such as the one depicted on Figure 8 in Section 2.3.

<u>Reliability Engineering Analysis</u> - There are a number of tasks that are specifically related to reliability as shown in Figure 2. It is not the purpose of this report to fully describe each technique and design tool but to highlight those most commonly used in the rocket industry. The two most commonly used methods for reliability analysis are:

- Failure Modes and Effects Analysis (FMEA) or Failure Modes, Effects and Criticality Analysis (FMECA).
- · Quantitative Reliability Engineering Design Tools such as predictions or Trade-offs.

Failure Modes and Effects Analysis is a "bottom up" method intended to identify, classify and document failure modes and their effects as well as possible corrective actions or compensating or mitigating provisions.

The purpose of an FMEA is to:

1. Assist in selecting design alternatives with high reliability and high safety potential during early design phase.

2. Ensure that all conceivable failure modes and their effects on operational success of the system have been considered.

3. List potential failures and identify the magnitude of their effects.

4. Develop early criteria for test planning and the design of the test and checkout systems.

5. Provide a basis for quantitative reliability and availability analyses.



Figure 2. Reliability engineering tasks typically used in design

6. Provide historical documentation for future reference to and in analysis of field failures and consideration of design changes.

7. Provide input data for tradeoff studies.

8. Provide a basis for establishing corrective action priorities.

9. Assist in the objective evaluation of design requirements related to redundancy, failure detection systems, fail-safe characteristics and automatic and manual override.

When considering reliability analysis of a design, one usually thinks of all the analytical steps leading to an estimate of the reliability of a given item. A complete analysis requires comprehensive input data that include material properties, design details and component failure rates; however, it is not necessary to wait until all of these are known before much can be determined about the reliability of the design.

Failure Mode Effects and Criticality Analysis (FMECA), is essentially similar to a Failure Mode and Effects Analysis but in this case the criticality of the failure is analyzed in greater detail (and may in some instances be quantitatively evaluated) and assurances and controls are described for limiting the likelihood of such failure. The four fundamental facets of such an approach are (1) Failure Identification; (2) Potential Effects of the Failure; (3) Existing or Projected Compensation and/or Control; and (4) Summary of Findings.

The most hazardous pitfall is the potential of mistaking form for substance. If the project becomes simply a matter of filling out the FMEA forms instead of conducting a proper analysis, the exercise will be ineffective. For this reason, it might be better for the analyst not to restrict himself to any prepared formalism. Another point: if the system is at all complex, it is risky for a single analyst to imagine that he alone can conduct a correct and comprehensive survey of all system failures and their effects on the system. When applied to complicated systems, these techniques call for a well coordinated team approach.

Comparative Analysis and Absolute Analysis are the two general types of quantitative reliability engineering design tools.

<u>Comparative Analysis</u> - When alternative designs for achieving given (or desired) levels of reliability are under consideration, characteristics for ...ch design are expressed quantitatively as a means of comparing the relative reliability of each design alternative. For this particular type of analysis, failure and repair data need not be exact since the purpose is to compare alternatives rather than to obtain estimates of absolute values.

There are three types of comparative analysis commonly undertaken:

- Trade-offs
- Sensitivity Studies
- Optimization Studies

Trade-offs, among various design alternatives, are conducted so that the alternatives with the best Benefit to Cost Ratio may be selected. The Benefit/Cost Ration is determined by incorporating the effects of reliability factors, installation and operating costs, degraded modes of operation, etc. Trade-offs involve achieving the proper balance among reliability, performance, and cost.

Sensitivity analysis involves the variation of input parameters to mathematical models in order to assess the relative effect of component characteristics and data accuracy on a given system's reliability. The results are used to identify areas where improvement in design will have the greatest potential impact on reliability.

Optimization studies carry the concept of sensitivity analysis one step further by varying the input carameters until a set which appears best from a reliability perspective within the system constraints is obtained.

Absolute Analysis involves the use of numerical results of an analysis in an absolute sense (Design A bas a reliability of 0.90"). It results in a "stand alone" number, not a "relative comparison" type under

The two types of absolute analysis are:

- Apportionment
- Prediction

Appartionment is used when a specific level of reliability is prescribed. For instance, a client may crescribe a certain percent increase in the reliability of an existing propulsion system. The procedure greatly simplified) is:

1 Apportion the reliability of the system to each subsystem based on past performance.

2. Identify those subsystems which have the least desirable reliability performance. Include all factors which affect this performance such as random failures, common cause failures, distribution of downtimes, summar reliability, etc.

3 Determine what corrective measures may be taken to increase the reliability of each subsystem.

Prediction requires utilizing mathematical models, input data, and probability theory for predicting estability taking design actions based upon the predictions, measuring (or gaining new knowledge) and it on repredicting, and acting again or remeasuring continually throughout a program of development or 200

<u>Reporting and Corrective Action Systems</u> - "Failure Reporting and Corrective Action": (FRACA) as well Problem Reporting and Corrective Action" (PRACA) are the two types of reporting and corrective costsystems that presently exist in the rocket industry. The FRACA system is required by the Air Force on the PRACA system is required by NASA. Although these two systems may differ in minor detail, the intent costsystements and methods used by manufacturers to carry them out is very similar. The following costsystem is required manufacturer.

Company XYZ maintains a closed-loop failure reporting and corrective action system to ensure investigation of the cause of failures and to provide appropriate corrective action and failure recurrence control. The FRACAs place emphasis on analysis of failure data to provide early detection of defects. Subsequent investigation and corrective action attempts to find and correct failure causes early in the build mycle in order to minimize costs associated with higher level failures.

FRACAs incorporate the following features:

1. Use of a failure report form which provides a failure description, analysis and corrective action, as well as basic information including: hardware name; operational level, type and environment; hardware identification number; date of failure; name of responsible unit engineer and failure reporting engineer.

2. A project failure reporting procedure or RAM program plan section which defines:

- The level at which failure reporting begins.

- The types of anomalies for which failure reports will and will not be written.

- The flow of hardware and paperwork associated with failure analysis.

- The responsibilities of the R&M and QA organizations.

3. The completed failure reports incorporate the corrective action implemented both immediately (e.g., part removed and replaced) and long term (e.g., engineering order to implement design change).

4. Every failure report requires a close out.

5. The program/project maintains a current list of all failures and the status of those failures.

Basic terminology used in FRACAs is as tollows:

1. TRS - Test Record Sheet - Running log of spacecraft area test events; initiated by test inspector.

2. SQUAWK (Log)- Narrative which records spacecraft or space propulsion system area assembly and test problems; initiated by test inspector.

3. TDR - Test Discrepancy Report - Records test failures at various levels of assembly and test; initiated by test inspector.

4. TRF -<u>Test Failure Report</u> Records the problem descriptions, failurs analyses, and corrective actions; initiated by reliability engineer.

5. RAR - Beliability Analysis Beport - Computerized output of combined information from TDR and TFR.

6. FRB - <u>Failure Beview Board</u> - Joint meeting of Contractor/Customer personnel to review and closeout failure.

<u>Sequence of Activities</u> - A typical flow of failure reporting paperwork and the associated hardware is shown in Figure 3.

Although FRACA/PRACA systems are intended to be a "cradle to grave" system, manufacturers tend to emphasize manufacturing (using Q.C. as the control and corrective action system) and test (using the process of Figure 3 as a corrective action system). This is primarily because these are the two areas over which they have complete control. Feedback from the customer (except, of course, for catastrophic failures) is often inconsistent.



Figure 3. TDR/TFR/RAR paper flow.

For example, if a failure occurs and the equipment is pulled for repair, the paper work often does not state why the equipment tailed. In the case of the SSME, a recent review of non-conference reports (UCRs) indicated that only 20% were included in the NASA PRACA system according to one contractor. 80% were excluded by the reporting requirements. These requirements are intended to limit the reporting to serious problems and to prevent the system from becoming overwhelmed by problems of a minor nature. Such a system serves well to aid in serious problem tracking and close out, but can sometimes eliminate the detailed background information required for definitive problem analysis and root cause determination. In the case of the SSME, such investigations required use of the UCRs combined with the contractor's (Rocketdyne) in house problem tracking systems. Thus, the problem is two-fold: not all problems are reported and those that are reported are not always adequately described.

<u>Comments</u> - Failure reporting is most effective when viewed as an engineering activity rather than as a bookkeeping function. Opportunities exist for failure reporting personnel to enhance screening effectiveness, identify potential trends, and to minimize costly downstream anomalies. Increased computerization of FRACAs allows for rapid information dissemination and less time spent on routine paperwork tasks, as long as increased use of computers must not be made by sacrificing detailed problem descriptions.

The FRACAs begin with procurement and continue through receiving inspection manufacturing, test, launch-site activities and mission operation. Control of discrepancies found in receiving and in-process inspection, all non-test discrepancies and Material Review Board (MRB) activities are primarily the responsibility of Quality Assurance and are described in the Quality Assurance Program Plan. Reporting of parts and materials problems (including Alerts, etc.) is the responsibility of Parts, Materials and Processes (PM&P) personnel. Test discrepancy control is primarily the responsibility of the reliability organization. In the course of performing this function, a reliability engineer may encounter conflicting priorities within the project in assuring that proper failure analysis and corrective action occur in response to test discrepancies. Examples include:

1. Manufacturing personnel want units repaired and out of their hands.

2. System Integration personnel want units back into stores or back into their hands.

3. The unit engineer wants a test discrepancy to be due to a manufacturing defect or a parts problem, and he may now, due to the passage of time, be assigned to a new project.

4. The project manager doesn't want to spend any more money on the situation.

5. The project engineer believes whatever the unit engineer tells him.

6. The system engineer is worrying about link performance or something of the sort.

In the face of these conflicts, the reliability engineer's objectives must prevail. The Failure Review Board exists to help assure that each failure is properly closed out. Satisfactory closeout of a failure will occur when:

1. A failed unit is fixed and has passed the test which it failed.

2. The probability of the problem recurring in the unit is negligibly small.

3. The problem has been shown not to exist in any other unit.

A computer system is often used to record and track test discrepancies from the time of occurrence through Failure Review Board closeout and beyond. The computerized system provides:

1. A reporting vehicle for alerting Quality Assurance, Reliability, Engineering, Manufacturing, Test and Program Management of failures and need for action.

2. A permanent record of the cause, significance, effect, and corrective action for each failure.

3. A vehicle for requesting remedial action of the procurement, design, manufacturing, test and handling organizations.

4. A retrieval system for identifying failure trends, providing status summaries and locating historical failure information.

While PRACAs/FRACAs perform well in the failure tracking and problem close out system mode for which they were intended, they were not designed to be reliability data bases even though they may contain information considered for this latter purpose. It should therefore not be surprising that PRACAs often lack the information required for reliability analysis and prediction. The reasons for this vary but the primary reason is as follows. PRACAs are intended primarily to keep reliability management and program management informed that serious problems have been identified and are being attended to. Including minor problems or supplemental information which is not critical to management tracking (such as the part exposure time at failure) may overload management and therefore this information is screened out of the system by the reporting requirements. While this may be desired from a problem tracking standpoint, it eliminates the precursor information essential to a reliability data base. For example, the SSME PRACA system only includes 20% of the UCR information which would be required for a reliability data base and it includes almost no exposure at time of failure information.

1.2 Data Base (Historical)

# 1.2.1 Data Collection

The objective of this subtask was to collect the material necessary to understand the present state of design, the current manufacturing techniques and the operational parameters of solid and liquid propulsion rockets. Collection methods included visits to NASA and Air Force sites responsible for solid and liquid propulsion rockets. Collection methods also included visits to the sites of rocket manufacturers and users and access to in-house publications, technical and public libraries for text books, reports and articles on rockets.

Trip reports (see Volume II: Appendix B) documented the names of contacts made, insights gained dirough formal or informal question and answer sessions with these contacts, the type of information collected (nard copy reports, historical data sets and for which rockets and time frames) and the type of process viewed during facility tours (production, maintenance, design). Information gathering focused on the retrieval of sets of historical rocket launch and test performance data, textbook discussions of the physical attributes of solid and liquid rockets and subtypes, and studies conducted to evaluate design and performance tolerances of individual or collective rocket performance parameters. The output of this task was a set of rocket characteristic and performance data.

#### 1.2.2 Data Organization

The data gathered from the site visits and the information collection process described above was organized to facilitate its use. For hardcopy material and site trip reports, a filing system was constructed,

separating solid from liquid rocket data, then categorizing by rocket use (booster, strap-on, Orbit Adjust, Payload Assist Module), followed by sorts on fuel type and rocket type. The Data Summary Sheets that follow were constructed to allow at-a-glance review of the data available on the various rocket types in these rocket use and fuel type categories. Historical data on rocket test/launch were organized by entering it into a computerized data base system, DBase III+, when the data was available, to allow data to be more easily stored and sorted.

# 1.2.3 Representative Design Parameter Development

Using the information gathered and organized, a candidate design configuration was selected for solid and liquid rockets as a baseline case. This baseline was used to establish a structure of rocket mission and performance characteristics which also define a structure for data entry and storage. The rocket mission data vector, or the column headings for a data table, reflects data categories from historical performance sets, such as data of test/launch, success or failure, rocket designation (name, production lot), and type of mission (R&D, space Mission). Rocket performance vector entries were determined by the technical literature search and site visit discussions citing rocket attributes such a fuel, oxidizer, thrust and diameter. The baseline structure which these vectors constitute was expanded and defined further as more insight was gained into the characteristics which drive rocket reliability.

Following the Data Summary Sheets is a matrix containing the reliability of U.S. launch vehicle failures, tabulated in Table 1 and 1a-1f. The details of how this matrix was generated are contained in Appendix A 3.

# 1.3 Deficiencies of Current Aerospace Reliability Practice In Application to Current Advanced Launch System Needs

Current Aerospace Reliability practice has not been able to affect the high reliabilities specified for Air Force advanced launch systems. Current practice, as it seems from the investigations undertaken as part of this effort, is relevant toward the production of launch vehicle systems whose range of achieved reliability is upper bounded at 95%, and these levels have been achieved only after significant development programs over which significantly lower reliabilities were the norm (80% - 90%). Many of the deficiencies in current practice are a product of the developmental history of aerospace reliability technology and its resulting evolution rather than direct misapplications of reliability techniques. It has taken almost 30 years for a systematic reliability discipline to be developed since its early beginnings in the Titan and Apollo programs. At the time of its creation, the US and world industrial base was guite different. Failures of small electronic components because of their use in great numbers in complex aerospace designs had a tendency to defeat the best efforts of system designers and render embarrassingly useless, expensively developed systems. In the case of early launch vehicles, national prestige and credibility of ICBM deterence required that these problems be eliminated quickly. The electronic systems were the roots of aerospace reliability, especially in the era when quantitative information was completely unavailable (if not unheard of). This tended to influence reliability technology development toward the generation of techniques which could help quickly to improve the performance of systems without undertaking the long term development of more reliable individual devices. Papers which touted the development of reliable systems from less reliable devices, the initiation of qualitative investigatory techniques such as FMEAs, and the use of redundancy to shore up the areas of weakness graduated from the academic classroom of the 50's and early 60's to become the industrial practice of the late 60's and early 70's. Finally, they became institutionalized in the late 70's and 1980's.

While exposure of component functional failure effects through FMEAs and their elimination through redundancy works, and works well for electronic systems where weight and operational constraints are minimized and the effect of a single failure is to some degree localized, the usefulness of this approach has always been limited in propulsion systems. In fact, the use of this currently institutionalized qualitative

	04/19/89		DATA SUMMARY	SHEET		PAGE 1
•.	M ENCINE on MOTOR NAME	MOTOR 1 UA 1205	MOTOR 2 UA 1207	MOTOR 3 THIOKOL TX526-2	MOTOR 4 THIOKOL IX-780	MOTOR 5 THTOKOL STAR 48
	Erer Agency	USAF, Commercial	USAF	INASA	USAI	INASA
	Monufacturer	lutc	lutc	  Thiokol	  Thiokol	  Thiokal
	Cosignation		1	Castor 4	Castor 4A	PAM - D
	Istage or motor) Engine or Motor			13,222	}	1
t.	Reight ((b) Peopellant weight	232,000	l I	  20,556	1	1
	(10,40 mumban	0	  0	)   1	1	13
2	Cudizer/Fuel	  solid	  solid	solid	l	l
.7	Mitture ratio (O/F)		(			
	na anti-arr≹		1		1	3
	rat Openeter	90.4/10.2	  112.9/10.2	36.6/3.3	  36.±/3 <b>.3</b>	  17.2.4 P
	<pre>////////////////////////////////////</pre>	 2]123,144,000*	  159,700,000*	  83.640	197 556	1
	to (b.sec Thisto (vacium)	1		192 400	1	
÷		1	Ì	1	l l	+5, UUN 
	(rsia)	1		540	}	1570
	Spro impuls Craticuela		1	230		
	troth regents	1		1 1256		
	(Januum) (Sce) Istal burn time				ļ	
	1 6 Y	1	1	56		85.3
	tottle expansion			8.0		54.9
• •,	Norte exit area		ł	  6.1	]	
u,	titifi) Fraing capt apple				r 	4.75
	(ana)	1	1	11	1	0
	in marei fal	1				
	∴ga⊵nt number	1				
	t enter contraction()	, , ,	l I		1	Spin Stabilized
.11	Thrus Conffient Of	1		1.411		  2.1
•	Nozzie discharge	1		6.13E-3	1	  7.2F-3
2.	Engine cycle	1	s   		1	1
``*	Mass Discharge Rate	1		363.7	\$ [	
	Engin: cost		}	1	1	1
23	Engine Reliability	  0.9975 		0.9993		  0.9769
	- bicts Name	Titan 340 Titan 3	  Titan 4 C.G.P.  Titan 4 IUS	  Delta 3914/3924  3910/3920/PAM-D	  Delta 6925 	  Delta 3910/PAM D, 

# DATA SUMMARY SHEET

NU	I ENGINE OF MOTOR	MOTOR 6	MOTOR 7	MOTOR 8	MOTOR 9	MOTOR 10
	NAME	THLOKOL 48B	HERCULES GEM	SPACE SRB	THIOKOL TE364-4	UTC ALGO 3
				*******************		
1	Jher Agency	USAF	L.SVE J	NASA	NASA 	NASA, USAF
2	Manufacturer	(hioka)	McD/Douglas	1	[Thiokol	
3	Designation	PAM-D	Gr-Ep Hotor (GEM)	1	TE-M-364-4	Algut 3A
4	Engine of Motor			1385,000	1200	
•	weight (1b)	1	1	1203,000	1200	14,000
5	Pricellant weight	1	1	1,115,000	2,300	1 128,000
~	Staan number	3	1	1	3	1
•	Isodozer (Fuel	l Isolid I	  set:d 	!  Alumium_powder/  Ammonium_perchlerate	  solid 	leolud I
9	"Heture ratio (O/F)		1	4.4	1	4 1
;	1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 -	1	1		1	1
10	<pre>congth.himmeter (ft)(ft)</pre>	(7,2,4,0) t	36.673.3	149.0/12.0	6.8/3.2	30.873.74
::	incont en leve (16)	t	194 554	12 650 000	1	103.750
	* = _bse	I	1	12,000,000	1	1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
· :	Servet Sentuum) Sha	115,000	1	Ì	14,800	,  105,112
17	bort i tonsure	1	ł	ļ.	1.55.0	
.,	(psia)	ļ	1	¶ 	550 	450 
••	Open impuls	1	ļ	l.	4	229
	(sea level)	1		1	1	1
15	Spect impuls	1	1	1	283	259
	(vacuum) (sce)			1	1	ł
15	iotal burn time (sec)	]		120 	4 4 	56.11 
17	Nozzle expansion	 			33	6.48
٠ġ	Nozzle exit area	l İ	1		3.14	  5.67
12	(ftxft) Engine cant angle	1	l t			
20	(deg)					
20	Sasé material	 	 			
51	Sase segment number	1	 			
22	Thrust vector	- # 1			Spin Stabilized	Acrodynamic Fins
23	Thrust Coeffiecnt Cf	1			1.96	and Jet Vanes 1.645
24	Nozzle discharan i				6 9/5 3	7 186 3
	coefficent Cd a			1	0.746.3	7.188.3
25	Engine cycle			l		
25	Mass Discharge Rate			l	52.3	407.2
	(lb/sec)		1	I	, I	
27	Engine cost		1	ļ	l	
28	Engine Reliability   			0.9813	0.9769	
29	Vehicle Name   	Delta 6925/7925	0elta 7925   	Space shuttle   	De(ta 3914/3924   	Scout Launch Vehicle (SLV)

# 16-19752

# DATA SUNMARY SHEET

•

÷

i

<b>₩</b> 1.14	ENGLAS OF MOLCR NAME	MOTOR 11 THTOKOL TX354+3	MOTOR 1.1 THICKOL IE:M-762	MUTOR 13 THIOKOL TE M-640	MOTOR 14 THIOKOL TE-M-364-4	MOTOR 15 THTOKOL TE-M-616
•	Joer Agericy	INASA, USAF	INASA, USAF	jNASA,USAF	JUSAF	JUSAF
	Microfactorine	Thiekol 1	1  Thiokol 	l  Thiokol 	I  Thiokol I	l  Thiokol (
3	Criegoateau Estage an motor)	Chster 2A 	  Antaros 3A 	Altair 3A 	י  SG0 Blk.1 	)  015 
•	Ergina i Motor Weight (lb)	13,000 1	1,000 1	[100	1	1
٢	Propellant weight (15)	8,000	3,000 	600	•	
•	Stade number	2	13	4	lupstage 2 L	upstage 1 L
•	المرية العريق (1	isolid I	isolid I	r İsolud	)  solid 	i  solid 
3	Mixture ratio (9/E)		i	1	4 [ [	
÷	ي. مەربى	•	il.	1   (		
\$0	<pre>/ft):(ft)</pre>	100.772.59 1	11_2/2.49 1	12.473.50	5.2/4 <b>.6</b>	1  5.9/4.6 1
•••	<pre>thrustlena lev) ((b)</pre>	I 1 2		1 	• 	1
12	Threest Conceptm) City	185,977	1 18,700	i j5,710	15,500	  6,000
13	there pressure (rstat	- 200 1	   700	670 1	t 	
<b>!</b>	Cree imputs	I I I	1 7 6	6 		
•	Tress inclus Tress inclus	1280 1	295	  288 		
16	Total burn time	35.32	  43.96 	1  29.30		
17	iony Nerzziene+ponsium + j+	121.2	! [ •6 . 0	50.3		
18	Horrie crit atea Storic	17.95 1	(   4 . 48	1 1.5		f I I
•2	English wit anglish	0 1	'   0 	0		
.)	Care caterial	4 1 	1	1   2	1	1
21	Care request sumber -					1
22	through vector	1 14202 405 1	H202 RCS	  Spin_Stabilized 		
2*	trout righteent Cf	1.572	1.905	1.985		
24	Nozzle discharge	6.04E-3	6.46E-3	6.89E-3		
25	Ergine cyste					
<u> 85</u>	Macs Discharge Rate   (15/5-5)	228.5	63.4	  19.8 		
27	Fraine - Sot			1	1	
85	Engine Reliability			1		
Ŷ	vibiche Nome	Schut	Schut	Scout	Stage Vehicle System	Orbit Insertion Sys

04719782

# DATA SUMMARY SHEET

N' !! )	ENGINE OF MOTOR NAME	MOTOR 16 THLOKOL (MM3)	MOTOR 17 THICKOL FAM-DIT	MUTOR 18 UTC SRM 1	MOTOR 19 UTC SRM-2	MOTOR 20 Thiakal Caster 2
1	John Agency	INASA	[Varies	USAF	INASA	INASA, USAF
ĩ	Minufacturer	i  Thickol 	I  Thiokiil 	ו  טדכ ו	ו  עדכ ו	f  Thiokol I
3	Designation (stage or motor)	   PAM - A 	PAM D11 	i  Boeing  Orbital_Sciences	i  Boeing 	Castor 24
4	Engine or Motor	<b>j</b>		1		1
5	Reight (15) Procellant weight	1	]	1		1
	(16)	1	I	ł		/ 
6	Stage number	upstage 1	upstage_1 	3	3	2
7	Oxidizer/Fuel	i İsolid İ	l [solid 1	l [solid ]	solid I	l (solid I
ß	Mixture ratio (O/F)	,   }	•	,   		1
9	Cholant			ĺ		
10	Longth/Niameter (ft3/(ft)	  7.5/5.0 	  6.5/5.3 	  10.7/9.5 	5.7/9.5	
11	Thrust(sea lev) (lb) * = lb.sec			s [		
12	Thrust (vacuum) (lb)	35,200 	17,600	44,100	16,800	61,890
13	(haider prosure (psa)	 		 		 
14	Spec imputs (sea level)	1		1		
15	Spec. Empuls		i ļ			
•	(vacuum) (sce)		1	1		1
16	(sec)			 		
17	Nozzle expansion ratio					
13	Nozzle exit area   (ftxft)			ţ Į		
17	Engine cant angle   (dog)					
20	Case material					
21	Case segment number			1		
55	Thrust vector					•
23	Thrust Coeffiecnt Cf					
24	Nozzle discharge   coefficent Cd g					
25	Engine cycle					
25	Mass Discharge Rate (					
27	Engine cost					
. 9	Englim Reliability					 
29	Vohicle Name   	STS/PAM·A	STS/PAM-D11	  Titan 4 105  Transfer orbit stage	Titan 4 IUS	Scont SLV-1A

# DATA SUMMARY SHEET

.

NU M	ENGINE or MOTOR NAME	MOTUR 21 Thiokol Antares 3	HOTOR 22 Thiokol Altair 3	MOTOR 23 Hercules X259-B4	MOTOR 24 Thiskol Castor 4H	MOTOR 25 Thiokol Star-30
1	Her Agency	INASA, USAF	INASA, USAF	NASA, USAF		
	Manufacturer	Thiokol 	Thiokol 	Hercules	Thiokol	Thiokol
3	Designation	Antares 3	Altair 3	Antares 2B	Castor 4H	Star-30
4	ingine or Mutor	1	ſ			
	weight (1b)	1		: 	1	1
5	Propellant weight	1	1	1		
	(lb)	1	1	1		
6	Stage number	3	4	3	1,2	4
7	Oxidizer/Fuel	l [solid 	  sotid 	  solid 	l solid	l  solid
8	Mixture ratio (O/F)	1	1	1	1	1
?	Coolant				1	
10	Length/Diameter	•	s I			1 
11	Thrust(sea lev) (lb)	1 	T 1 2	1		
12	Thrust (vacuum)	21,000	5,700	28,000	138,000	7,500
13	Churber pressure			1	1	
	(psta)					
14	Sheel imputs				·	
	(sea level)	1				
15	Spec. impuls		1		l	1
	(vaciasa) (sco)					1
16	Total Hurn time					}
	(sec)					
17	Nezzle expansion					
18	ratio					
10	(ftxft)					
19	Engine cant angle (deg)			[		1
20	Case material					
21	Case segment number (					
22	Thrust vector				1	1
	control (T.V.C)				l	
23	Thrust Coeffiecnt Cf					1
24	Nozzle discharge					
25	Engine cycle					1
.,	engine eyere					
26	Mass Discharge Rate					
	(Tb/sec)					
21	rngine cost		: 			1
28	Engine Reliability					1
29	Vehicle Name	Scout SLV-1A	Scout SLV-1A	Scout SLV-1A	Concstoge II	Conestoge II

NUM	ENGINE OF MOTOR NAME	MOTOR 26 Thiokol [E-M-364-2	MOTOR 27 Thiokol TE-M-442-1	Motar 28 Thiokal TE-M-360 4		
1	User Agency	lusaf	USAF	lusaf		
2	Manufacturer	f IThiokol	l  Thiokal 1	ł  Thiokol I		
3	Designation (stage or motor)	)  Burner 2, 2A 	)  Burner 2A 	  \$65 	 	
4	Engine or Motor weight (lb)	1	1	{ 	[   	
5	Propel(ant weight (lb)	1		1 1	1	
6	Stage number	upstage (varies) 	upstage 2 	Jupstage 2	] 	
7	Oxidizer/Fuel	solid 	solid 	solid 		
8	Mixture ratio (C/F)	1	 	   1		
y 10	Coolant	       5 0/5 7	     	    10.07/ 5	 	
11	(ft)/(ft) Thrust(sea lev) (lb)		]			
12	<pre>* = lb.sec Thrust (vacuum)</pre>	    10.000	    8,000	17.325	י ז ן	
13	(lb) Chamber pressure	   (		   }	1	
14	(psia) Spec impuls	}	 	 	-   	l I
15	(sea l <b>evel)</b> Spec. impuls	 	 	1	 	1
16	(vacuum) (sce) Total burn time	1			 	
17	(sec) Nozzle expansion	l	   2	   	 	1
18	Nozzle exit area	1 [ 1	۲   		   	1
19	Engine cant angle (deg)	1	1		/   	1
20	Case material			1	} 1	 
21	Case segment number	1 1	 	1 	f I	i 1
22	Thrust vector control (T.V.C)	 	1	1		1
23	Thrust Coeffiecat Cf			]		1
24	Nozzle discharge coefficent Cd g		1	 	 	
25	Engine cycle	   			1 [ 1	   
20 27	mass viscna <b>rge kate</b> ((b/sec) Engine cost	   	1 1 1		1 1 1	
28	Engine Reliability	 	<b>)</b> 	 	) [	 
29	Vehicle Name	  Burner 2, 2A 	  Burner 2A 	  Stage Vehicle sys 	   	   
		•	,		•	•

#### DATA SUMMARY SHEET

#### DATA SUMMARY SHEET

NUM	ENGINE or MOTOR NAME	ENGINE 1 Aerojet LR-87-AJ-11	ENGINE 2 Acrojet LR-91-AJ-11	ENGINE 3 Aerojet Aj10-138	ENGINE 4 Aerojet LR-87-AJ-5	ENGINE 5 Aerojet LR-91-AJ-5
1	User Agency	USAF, Commercial	USAF, Commercial	USAF	USAF	USAF
2	Manufacturer	  Aerojet 	  Acrojet 	  Aerojet 	Aerojet	Aerojet
3	Designation	1	1	Transtage		
4	Engine or Motor	1	1	1		
r	weight (lb)			1		1
>	(lb)	294,000	164,000	[ [		
6	Stage number	1	2	3	1	
7	Oxidizer/Enel	   N2047N2H4 - UDMH 	  n204/n2114-udnh 	i   N2O4 / N2H4 - UDMH 	N204/N2H4-UDMH	  N204/N2H4-UDMH 
8	Mixture ratio (O/F)	}	ļ 1	]		
9	Coolant	, , ,				1
10	Length/0:ameter		1			
11	Thrust(sea lev) (lb) * = (b.sec	  264,500 / 273,000		·	215,000	, , ,
12	Thrust (vacuum) (lb)		101,000 / 104,000 	8,000 		100,000
13	Chamber pressure (psia)		}			
14	Spec impuls (see lovel)		1	1	1	
15	Spec. impuls	í	1	1		
	(vacuum) (sce)	1	1	1	, ]	
16	Total burn time	1	Į.	}		
17	(sec) Nozzle expansion ratio		 	1   		
18	Nozzle exit area	, ] 	4 4 5	• • •	1	 
19	Engine cant angle (den)	1		1 1 1		
20	Case material		1			
21	Case segment number	1		] [ ]		
2 <b>2</b>	Thrust vector	· ] 1		1	• • •	
23	Thrust Coeffiecnt Cf	1	1	1 1		
24	Nozzle discharge	1	 		1	1
25	coefficent Cd g	ł	} I	} 1	) 1	1
74	Mass Discharge Pate		T 	e 8 5	/   	
εU	(1b/sec)	]	1	1		i f
27	Engline cost		•	 		1
28	Engine Reliability	   {	  0.9800 	1 [ 2	   	f }
29	Vehicle Name	Titan 340, 3, 4CGP, 41US	Titan 340, 3, 4CGP,  41US	Titan 34D	JTitan 2 SLV	Titan 2 SLV

.

-

•

# DATA SUMMARY SHEET

NUM	ENGINE or MOTOR NAME	ENGINE 6 Rocket. YLR-89-NA7	ENGINE 7 Rocket. YLR-105-NA7	ENGINE 8 P&W RL10A-3-3A	ENGINE 9 Rocket. RS-27	ENGINE 10 TRW TR201
1	User Agency	INASA	NASA	NASA	NASA, USAF	NASA
Z	Manufacturer	  Rocketdyne 	  Rocketdyne 	  P&W 	  Rocketdyne 	   TRW 1
3	Designation (stage of motor)	ί  ΜΑ - 5 Ι		l  Centaur I	t  ELT Thor 	l Delta I
4	Engine or Motor	   		1	1	
5	Propellant weight	   1 1 1 , 506 	77,825	1   14 , 867 	   175 , 000 	   10,000 
6	Stage number	1/2	1	  2 	1   1 	2
7	Oxidizer/Eunl	  LOX/RP-1 	ו  נטא/גדי 1 	  LOX/LH2 	፤ [LOX/Rቦ 1 6	1  N2027N2H4-UDMH 1
3	Mixture ratio (O/F)	2.25 	2.22	1 15.0 1	2.23	1.6
9	Coolant	)   		1		
10	Length/Diameter (ft)/(ft)	1				
11	Thrust(sea lev) (lb) * = lb.sec	188,750 I	60,500 		205,000	1
12	Thrust (vacuum) (ib)		,   	,   16,500 	229,600	9,530 I
13	Chamber pressure (psia)	j650	733	474	650 	100 
14	Spec impuls (sea level)	259 	220		261	
15	Spec. impuls (vacuum) (sce)	292	312	446.4	294	303
16	Total burn time (sec)	153 	283	404	227	318
17	Nozzle expansion ratio	8 	25	61	8	46
18	Nozzle exit area (ftxft)	11.24	11.56	8.22 	12.0	17.4
19	Engine cant angle (deg)	0 	0	0 	10 	0
20	Case material	1		1		
21	Case segment number			 		
22	Thrust vector control (T.V.C)	Gimballed Engines and Verniers	Gimballed Engines and Verniers	Gimballed Engines	Gimballed Engine	Gimballed Engine
23	Thrust Coeffiecnt Cf	1.44 	1.24	1.79 	1.46 	1.75 
24	Nozzle discharge coefficent Cd g	5.54e-3	5.64e-3	4.01e-3 	5.59e-3 	5.78e-3 
25	Engine cycle					
26 27	Mass Discharge Rate (1b/sec) Engine cost	728.8   	275.0	37.0   	785.4   	31.45   
28	Engine Reliability	0.9907	0.9905	0.9854	0.9833	0.9774
27	Vehicle Name	l Atlas G Centaur   D 1A/Atlas H	Atlas G, Centaur D-1A/Atlas H	]  Atlas G,Centaur D-1A   /D-1T, Titan 4CGP	  Delta3914/3924/6920/  6925,3910/3920/PAM·D	  Delta=3914/3924  -3910/3920/PAM-D

# DATA SUMMARY SHEET

NU	M ENGINE or MOTOR	ENGINE 11	ENGINE 12	ENGINE 13	ENGINE 14	ENCINE 15
	NAME	Aerojet AJ10-118k	Rocket, RS-51	P&W RI 10A - 3 - 3R	Rocket IR-89 NAS	Pockat 10-105-NAS
÷ 1	**********************					
1	User Agency	NASA, USAF	Varies	LUSAF	USAF	lUSAF
2	Manufacturer	Aerojet 	Rocketdyne	P&W	l  Rocketdyne 	Rocketdyne
3	Designation (stage or motor)	Delta	AMS	Centaur	MA - 3	I  MA - 3
4	Engine or Motor	1	 			]
-	weight ((b)		2,790		1	1
5	Propellant weight (15)	13,200	1	1	1	1
6	Stage number	2	lupstage	upstage	1/2	1
7	Oxidizer/Fuel	N2027N2H4-UDMH	/  N204/MMH 	LOX/LHS	LOX/RP-1	LOX/RP-1
8	Mixture ratio (O/F)	1.9				
ç	Coolant	1	r   2			1
10	Length/Diameter (ft)/(ft)	5	• • •			
11	Thrust(sea lev) (1b)	1			   165 , 000	  60,000
12	- Tolsec Thrust (vacuum)	9,710	2,650	  15,000	1	 
13	(Tb) Chamber pressure	  114	ł		1	1
14	(psia) Sphelimpuls	l I	1	]	1	<b>1</b>
	(sea level)	1			1	1
15	Spec. impuls	320.2		ĺ	l	1
	(vacuum) (sce)			1	Ì	
16	fotal burn time	43532		1	1	
	(sec)			1	1	1
17	Nozzle expansion ratio	65.2		\$	, ] ]	
18	Nozzle exit area (ftxft)	19.9     1		1	,   	
19	Engine cant angle (deg)			•		
20	Case material			1   		
21	Case segment number					
22	Thrust vector	Gimballed Engine		   		
23	Thrust Coeffiernt Cf	1.93				
24	Nozzle discharge   coefficent Cd a	6.03e-3				
25	Engine cycle	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
26	Mass Discharge Rate   ([b/ser])	30.32				
27	Engine cost					
2 <b>8</b>	Engine Reliability   	0.9774				
29	Vohicle Name	 Delta3914/3924/7920/  7925,3910/3920/PAM·D	Stage	STS/Centaur 9	Atlas E	Arlas E

# DATA SUMMARY SHEET

PAGE 4

-

NUM	ENGINE or MOTOR	ENGINE 16	ENGINE 17			
	NAME	Bell 8096	AGC Trostge			
====						
1	User Agency	USAF, NASA	NASA			
2	Manufacturer	Bell	AGC			
3	Designation	YLR-818A-11	Delta	!		
1	Forcing of Motor					
4	Engine of Hotor					/   •
	weight (LD)					
5	Propellant weight (lb)					
6	Stage number	upstage (varies)	2			1
?	Oxidizer/Fuel	IRFNA/UDMH	N202/A·50			ł
5	Mixture ratio (O/F)				) 	 
9	Coolant					1
10	Length/Diameter (ft)/(ft)					1
11	Thrust(sea lev) (lb) * = lb sec					1 1
12	Thrust (vacuum)	16,000	10,000			•   
13	Chamber pressure					F 
	(psia)		1		1	1
14	Spec impuls	1			1	1
	(sea level)					
15	Spec. impuls	1	1			ł
	(vacuum) (sce)		1			1
16	Total burn time	[				1
	(sec)	1				1
17	Nozzle expansion	 				1
18	Notile exit area	1	1		1	
10		1	1			1
10	Engine cant angle	f 1	l		1	1
.,	(den)	1			1	i i
20	Cane material	s f	1		•   	1
21	Case segment number		1		   	1
22	Thrust vector	i	İ			1
	control (I.V.C)		Í		1	1
23	Thrust Coeffieent Cf	1	1		1	1
24	Nozzle discharge	i	i	1	Ì	1
	coefficent Cd q	1	, I		Ì	i
25	Engine cycle	1	1			i
		2 2 2			י   	
26	Mass Discharge Rate		1		1	1
	(lb/sec)	t.	1		1	1
27	Engine cost	1	1	1	1	1
28	Engine Reliability	1	 	1	l I	1
29	Vehicle Name	Agena D 	Delta 3920/PAM-D		1 1	

S
Щ
3
S
<b>_</b>
ш
규
2
표
2
ž
Ş
5
4
S.
3
ö
ž
õ
ŝ
AF
<u>a</u>
Ň
8
ž
F
2
9
1
Ш
œ
щ
В
A
<b>••••</b>

1 3			Ther / Del	2			11 ten							ļ						┢──	, <sup>1</sup>	in 'Fee	۲. Te	ľ	ł	-	cout "Fan	7	\$T\$
Ī	Collection	23			Į į	i	į.	8	Contere	i	i	ů	1	Ĭ		3	2 0	z,	5 1	2 2	4			1	3		So a construction of the second secon	Canitre	
				ţ			Ì	Ì	Ì	8./1	8	8 8	695	80.08	1919	67- <b>6</b> 2	M-67	9 9	297 197	\$ 	\$ 	ð 	F <b>3</b>	6	8	8	3	82-25	<b>#</b> 5
3		2000	0 0402	0 9192	12490		0 9405	0 73556	0.6013	912710	0.55.56	0.5603	0.840	27426 0	1000	8	1	ă 1	5 8	8	3	8	1	0	7427.0 2		8	0	0 8275
Í		06/80	0 110	0 17 10	0.5065	12190	99008.0	0.4978	0.6075	0.1827	0102.0	2000	0.8015	0 15430 0	0 9000	0	10 5159	50 E FEE	MS0 047	0,0	20213	10 1	3 074	0.010	0.000	0 1506	1206 0	1281.0	000
	<b>95%</b>	18180	0 86 15	1998.0	8024 0	22280	19980 0		0.0654	0 4977	0 7866	0 BISBS	0.6734	06240	1 100	1		ă 	80	8	78 0 874			0,806	0 0000	22.50	0.9683	0.6744	0 9605
	<b>1690</b> 0	0 9965	0.9956					1.1	Γ	T	T	-	┢	┢╌	┢	-	$\left  \right $	┢	┢	╀	┞	┞		╞	$\downarrow$	╞			
	inge 1/2						F	[		ſ	$\left[ \right]$	1	ľ	5	0 8273			8		-	-	<b> </b>	-	1	+				
M R	1 -04	9404.0			1000	1000		0.8476	Γ	T			ľ	5	0 R 3		-	8	0		CT2A0	ļ		-	-	8	0 8847		0 6275
••   ••	<b>100 2</b>	1946	0 8746		0.7825	0.9256	0.8763			ļ			<del> </del>	$\left  \right $	Ĩ	1		8	8	057	2700	-	-	0.0422		8	580		
-	1	0 86.77	1				0.9667					<b> </b>	-			-		+-		-	e ve	<b> </b>	-	0		1	0.8746		
-														-			┝			8	0 09278	<u> </u>	-	-			0.000		
-	Topulation	0 9566	0 BLOI		0.6725	9800	0.9622	0.7355			0 6667		Ļ	0 C1/0	1612 0	3	-	8	8	8			L			ķ	0.0MB		0 BETTS
<u> </u>	luidence	0.000	0.0000				2000						Ê	5		$\vdash$	┢	-	<u> </u>	┝	┡	$\vdash$	<b> </b>	_	-	2 Ceo	0.0017		
<u>u</u> 113	<b>Nghi</b> Control	0.0007	0.9861			0.9656	-			9446	3898		ľ	0	i i i i i i i i i i i i i i i i i i i	ş	$\vdash$	ő	8	-	-	-			-	e e	00017		
<u></u>	tructure	0.9966			0.9702		0.904			0 7666			Ê	5986	-			8	3	┢	╞		-						
<u></u>	actrical	0.9815	0.9650			0.96039							Ê	98.57	ä	- ž		8	â		╞	╞	_	-	-		N.MO		
න්	speration	0 1001	0.9950			0 8456				<b> </b>			┢	┝──		ğ	╞	8	5	057	-		-	-	-	_	9986 0		
-	Wher or (UK)	12860													ž	$\left  \cdot \right $	$\ $		-	$\vdash$	$\parallel$	Ц			Ļ	3	9		

v	ehicle Name		Thor / Delta	
Da	ta Collection	Thor	Deita	Combine
	Period	57-83	60-87	57-87
Suc Rati	cess o: Mean 5% 95%	0.8982 0.8750 0.9181	0.9402 0.9110 0.9615	0.9192 0.8789 0.9551
	Stage 0	0.9965	0.9950	
	Stage 1/2			
NO.	Stage 1	0.9346	0.9850	
AGE	Stage 2	0.9764	0.9746	
S1	Stage 3	0.9877	0.9843	
	Stage 4			
	Propulsion	0.9568	0.9701	
	Guidance	0.9830	0.9950	
EM	Flight Control	0.9907	0.9851	
YST	Structure	0.9969		
05	Electrical	0.9815	0.9950	
	Separation	0.9969	0.9950	
	Other or (UK)	0.9923		

# TABLE 1A: RELIABILITY OF THE THOR/DELTA FAMILY

v	ehicle Name			Titan		
Da	ta Collection Period	Titan I	Titan II	Titan III	Titan 34D	Combine
		59-65	62-76	64-87	82-87	59-87
Suc Rati	cess o: Mean 5% 95%	0.6427 0.5585 0.7202	0.8864 0.8323 0.9272	0.9406 0.9055 0.9651	0.7355 0.4978 0.8990	0.8013 0.6075 0.9546
	Stage 0			0.9946	0.8678	
	Stage 1/2					
NO	Stage 1	0.8214	0.9574		0.8476	
TAGE	Stage 2	0.7825	0.9258	0.9783		
ິທ	Stage 3			0.9667		
	Stage 4					
	Propulsion	0.6725	0.9290	0.9622	0.7355	
	Guidance		0.9929	0.9892		
W	Flight Control		0.9858	0.9946		
YST	Structure	0.9702		0.9946		
0	Electrical		0.9929			
	Separation		0.9858			
	Other or (UK)					

# TABLE 1B: RELIABILITY OF THE TITAN FAMILY
v	ehicle Name					Atl	18					
Da	ta Collection Period	Atlas A 57-58	Atlas B 58-59	Atlas C 58-59	Atlas D 59-67	Atlas E 60-88	Atlas F 61-81	Atlas SLV 67-83	Atlas G 84-87	Atlas H 83-67	Atlas/ Centaur 62-87	Combine 57-88
Suc Rati	cess o: Mean 5% 95%	0.4219 0.1827 0.6977	0.5558 0.3010 0.7896	0.5833 0.2642 0.8585	0.8401 0.8015 0.8734	0.7426 0.6454 0.8240	0.8883 0.8359 0.9276	0.9445 0.8736 0.9652	no failure 0.6313	no failure 0.6313	0.9069 0.8450 0.9489	0.7883 0.4761 0.9953
	Stage 0											
	Stage 1/2					0.8713	0.9573	0.9861			0.9814	
Ň	Stage 1					0.8523	0.9279	0.9719			0.9810	
AGE	Stage 2							0.9856			0.9420	
ST	Stage 3											
	Stage 4											
YSTEM	Propulsion	0.8844	0.6667			0.8713	0.9212	0.9824			0.9535	
	Guidance					0.9571	0.9869					
	Flight Control	0.7688	0.8889			0.9428	0.9869	0.9824			0.9907	
	Structure	0.7688				0.9857					0.9814	
0	Electrical					0.9857		0.9824			0.9907	
	Separation					_		0.9824			0.9907	
	Other or (UK)						0.9934					

# TABLE 1C: RELIABILITY OF THE ATLAS FAMILY

Vehicle Name Data Collection Period				Saturn	"Family"		
		Jupiter 58-58	Juno 58-61	Saturn I 62-65	Saturn IB 66-75	Saturn V 67-73	Combine 58-75
Suc Rati	cess o: Méan 5% 95%	0.3611 0.1026 0.6879	0.4300 0.2135 0.6743	no failure 0.7943	no failure 0.7743	0.9822 0.8180 0.9997	0.7547 0.2652 0.9935
	Stage 0						
	Stage 1/2						
NO.	Stage 1		0.8575				
AGE	Stage 2	0.5741	0.7009			0.9822	
SI	Stage 3		0.7629			0.9822	
	Stage 4	0.6290	0.9378				
YSTEM	Proputsion	0.7870					
	Guidance						
	Flight Control						
	Structure						
UN I	Electrical						
	Separation	0.5741					
	Other or (UK)						

# TABLE 1D: RELIABILITY OF THE SATURN FAMILY

Vehicle Name Data Collection Period			Scout "Family"	
		Vanguard	Scout	Combine
		57-59	60-88	57-88
Suc Rati	cess c: Mean 5% 95%	0.3388 0.1555 0.5723	0.9420 0.9023 0.9683	0.6404 0.1821 0.9744
	Stage 0			
	Stage 1/2			
NO.	Stage 1	0.8347	0.9917	
LAGE	Stage 2	0.5049	0.9875	
S	Stage 3	0.8039	0.9746	
	Stage 4		0.9870	
EM	Propulsion	0.7521	0.9793	
	Guidance	0.9174	0.9917	
	Flight Control	0.8347	0.9917	
YST	Structure			
<b>9</b> 7	Electrical		0.9876	
	Separation		0.9959	
	Other or (UK)	0.8347	0.9959	

# TABLE 1E: RELIABILITY OF THE SCOUT FAMILY

		STS
Da	enicle Name its Collection Period	Space Shuttle
	r en lou	81-88
Suc Rati	cess o: Mean 5% 95%	0.9275 0.8147 0.9806
	Stage 0	
	Stage 1/2	
NO.	Stage 1	0.9275
LAGE	Stage 2	
S	Stage 3	
	Stage 4	
	Propulsion	0.9275
	Guidance	
EM	Flight Control	
SYST	Structure	
<i>v,</i>	Electrical	
	Separation	
	Other or (UK)	

# TABLE 1F: RELIABILITY OF THE SPACE SHUTTLE

system of reliability techniques can lead designers and decision makers to make incorrect decisions even if correctly applied as is demonstrated below. Finally, it appears that the currently institutionalized reliability technology base, because of its qualitative nature, will be unable to address just the residual reliability related issues such as residual variability reduction, risk management and human reliability that limit launch systems to their current operational reliability levels.

Here are some examples why. The examples fall into two broad categories: either they are the result of performing FMEAs/FMECAs or quantitative reliability analysis.

#### 1.3.1 FMEAs/FMECAs

FMEAs/FMECAs are structured to detect single point failures. When single point failures are identified they are either controlled or compensated for by use of redundancy.

<u>Redundancy and Correlation Factors</u> - When applied to electronics, redundancy can be a very effective way to enhance reliability. However, as Section 2.3.1.2, "Product Design FMEAs" points out, even electronics can be susceptible to "common cause" or "correlation" failure. These are the types of failures that can negate the benefits of reduidancy due to a single event. Product Design FMEAs have proven beneficial in reducing vulnerability to correlated failures in electronics systems and may prove to be beneficial in the analysis of propulsion systems. None-the-less, propulsion systems, like any high energy system, are inherently more vulnerable to correlated failures. This is supported by the study of the shuttle main engine development history which is summarized in Section 2.1.4 and provided in detail in Appendix A.1 "An Investigation of Historical Failure Correlation Factors Using the Shuttle SSME Flight History as an Example."

<u>Controls and Variability</u> - When redundancy, for whatever reason, is not an option when conducting an FMEA, the failure mode is "controlled" either by designing the failure mechanism directly out of the system or by placing more stringent controls on manufacturing and/or testing. Designing a failure mechanism out is usually not a viable option because it requires a physically different way of obtaining the same function. Thus, manufacturing or testing is the most practical way of constraining the failure mode. The only problem with this approach is that if methods are not in place to measure the effects in terms of reduced variability, there is no way to measure the impact on reliability.

<u>Reusability</u> - Another potential problem with FMEAs is that they tend not to be "living" documents in the sense that if a system is reused or is reusable, the FMEA is not structured to handle the potential results. For instance, weld failures on the Space Shuttle Main Engine can result from thermal cycling and fatigue through reuse. The FMEA is not structured to conveniently handle this situation.

<u>"Bottom Up" Methodology</u> - As has been previously discussed, FMEAs/FMECAs are "bottom up" methodologies and as such are not designed to list all potential malfunctions of a system, only those which propagate from known failure modes of components within the system. Witnout a comprehensive way of anticipating system or subsystem malfunctions in a global sense, the analyst can never be comfortable that the FMEA/FMECA is exhaustive. A "Top Down" methodology as described in Section 2.3.1.2 would help overcome this "Bottom Up" obstacle.

# 1.3.2 Quantitative Reliability Analysis

In order for quantitative reliability analysis to be effective the three following constituents must be present:

- 1. Meaningful Reliability Data/Issues
- 2. Proper Reliability Analysis Tools
- 3. Risk Analysis and Management Capabilities

<u>Meaningful Reliability Data/Issues</u> - For the current generation of launch vehicles, the historical data set (see Appendices A.1 and A.3) appears to be both meaningful and capable of addressing the key reliability issues. To be meaningful, the reliability data must:

1. Be complete for both success and failure.

- 2. Have failure causes consistently identified.
- 3. Have chronologies of failure history established.
- 4. Have design change chronologies established.

In order to be effective, however, the following issues must be resolved:

1. How relevant is history in predicting future performance in a developmental system?

- 2. How is historical reliability growth to be accounted for?
- old failures less than new?
- How are design changes factored in?

3. What effect does hold down time just prior to launch have on prevention of failures which otherwise would occur after launch?

These issues can only be addressed by applying the appropriate quantitative reliability models using a properly developed and structured historical data set.

Quantitative Reliability Analysis Tools Specifically for Propulsion Systems - Until now the only quantitative methodology available for propulsion systems which addresses the developmental nature of such systems have been traditional reliability growth methods (such as the Duane approach and Weibull methods) and D. Lloyd's methodology (see Section 2.2.2). Even if these methodologies were adequate in addressing overall launch vehicle reliability, three other areas should be considered in order for a quantitative reliability analysis to be fully effective.

They are:

- Estimation of Stage Reliability
- Estimation of System Reliability
- Estimation of Engine or Motor Reliability

A method of estimating launch vehicle reliability is summarized in Section 2.2.1 and all four methods are described in detail in Appendix A.3, "Reliability Analysis for Current US Launch Vehicles".

Risk Assessment/Management - Section 1.3.1 has described the limited value of FMEAs/FMECAs in the quantification of reliability. Although they are useful in constructing logic models (see reliability techniques, Figure 2), strictly speaking they can only be used to quantify consequences. For instance, they can be used to quantify total number of welds whose failure could cause loss of an engine, cluster, stage, or vehicle (consequences), but this approach does not provide the analyst with the quantitative risk discriminating information required of a decision making tool. A decision making tool allows the analyst to rank individual weld failures, for example, with other sources of propulsion system failures in order to determine where to best expend resources. If a decision is made to expend the funds, the funds must be dedicated or "fenced off" and made distinct from management reserve funding. Even well developed criticality ranking techniques do not do the job sufficiently because they do not develop rankings at the system level but only at subsystem or lower levels, since their system level rankings are often developed only on a near relative basis. This approach can give the impression that a thrust vector control system single failure is just as important as other propulsion system elements such as a heat exchanger or turbopump, even though the latter may have several orders of magnitude higher failure probability. The solution to this problem is to use the quantitative reliability analysis tools of Section 1.3.2.2 in conjunction with Risk Analysis/Assessment techniques as described in Sections 2.3.1.3 and 2.3.2.

Figure 8 (Section 2.3) shows the relationship of risk management and assessment to infrastructure controls that have an impact on reliability.

# 2.0 (TASK 2) RELIABILITY ENHANCING METHODOLOGIES

## 2.1 Lessons Learned

This section is concerned with lessons learned either as a direct result of plant visits or from a related analysis.

# 2.1.1 Variability Control

Variability control was highlighted as a reliability enhancer at Hercules (West Virginia) and McDonnell Douglas (Huntington Beach, CA), as noted in Appendix B.

The Hercules trip indicated that solid rocket motors can achieve high reliabilities (>.999) and maintain these reliabilities over reasonable production runs (as many as 1000 units/year), if the proper reliability considerations are included in the design and development phases of the program and the proper process controls are in place, and if the proper test program remains in place. The process control system must be able not only to detect penetrations of the Upper Quality Limit (UQL) and Lower Quality Limit (LQL), but also trends toward unacceptable quality. These trends must be thoroughly investigated and tied to causes, the causes addressed, solutions derived and implemented, and control mechanisms directed at controlling key process parameters verified as being reestablished.

# 2.1.2 Reusability

Reusability is, on the surface, a design goal of significant program benefit. However, the benefits of reusability are significantly compromised if the reliability of an engine is adversely affected by the requirement for reuse. Besides the direct costs involved in developing a reusable design, there now appears to be a significant indirect cost required to maintain reliability in reusable design. For example, reusability by its very nature tends to decrease the production run. When production runs are decreased, investments in automated production equipment becomes less economical and the production process therefore tends to become more prototypical. Prototypical production, especially of complex equipment, increases the problem of variability control and therefore substantial post production testing may be required to ensure high reliabilities. A good example of such an indirect impact on reusability was seen at the Rocxetdyne SSME production facility in Canoga Park, California.

#### 2.1.3 Performance Indicators

For high reliability programs it is important to identify early on symptoms of the process which presage deterioration in performance. This has been done in the financial community by the development of a set of "leading" performance indicators and developing performance trends based upon the indicator trajectories through time. If such a set of indicators could be developed and trended for advanced propulsion system development programs, the indicator trajectories might provide early warning of problems arising during development and operation. This early warning could provide the time required to institute corrective action before actual program reliability performance is affected.

# 2.1.4 Correlation Factors (See Appendix A.1)

Given the current state of rocket engine technology, there exists a finite probability of catastrophic engine failure during a vehicle launch. A catastrophic engine failure is considered one in which the engine does not shut down in a controlled manner and includes uncontrolled fire, explosion, breach of the pressure boundary, shrapnel, complete loss of fuel or oxidizer supply, or a combination of these. Given that an engine has failed catastrophically in flight, an immediate concern is for other critical hardware in the vicinity of the failed engine. For vehicles configured with multiple engines in a cluster, the question becomes whether the catastrophic failure of one engine will result in the catastrophic loss of the entire engine cluster.

In the present study, the correlation between a catastrophic failure of a Space Shuttle Main Engine (SSME) and the propagation of that failure to include the entire SSME three engine cluster has been developed based upon the SSME Test History.

<u>Conclusions</u> - In the development of future launch vehicles, the potential benefit of engine out capabilities must be weighed against the risks that if an engine fails in an uncontrolled manner, it will result in the loss of the entire engine cluster. This study evaluated the SSME which is flown in a three engine cluster. No uncontrolled SSME failures have occurred in flight. Only a limited amount of ground testing has actually been done in a three engine cluster and although failures have occurred, none have propagated to involve the entire cluster.

However, the test data evaluated here indicates there is a reasonable probability, approximately 17%, that an uncontrolled SSME failure will propagate to the adjacent engines given that an uncontrolled failure occurs. The confidence interval is between 4% and 41% that a failure will propagate to the cluster (at 95% confidence).

A summary of the results of the data review is given in Table 2.

2.1.5 Correlation vs. Engine Out Capability(See Appendix A.2)

A preliminary correlation factor vs. engine out capability study was conducted using the following assumptions:

• Smaller engines are more reliable than larger ones.

• Increased plumbing due to a larger number of engines decreases reliability.

The results of the study indicate that a four engine configuration would be the most reliable if correlation factors <u>are not</u> taken into account.

When correlation factors are between 20 and 27% the four engine configuration is no better than a single engine configuration. Section 2.1.4 indicates that the 95% interval for correlation failure is 4 to 41%. Therefore, there is a substantial probability that correlated failure on an engine design which is comparable to the SSME could negate engine out capability.

TABLE 2: SSME COPPELATION OF FAILURE FACTOR

		NOCINI	E		SUPPO	STAND					19
	(NC	NTT HDWF	A ENN	APPLICBL	HAPOWHI QUEL	R LXWN		1		TEST P	ΙŦ
FING CONFIG		UN FAILE	E THO	FAILURE	DAMAGE DAMAG	E TIME	RL C		COMMENT	NI WIN	5
· · · · ·	······································				•	+		-			1
NUM THAT POOLS	5		12	5.5	GV. GV			I CIP I	#KUIPFIREEXCOAM	- C - F -	r.
2. 1 30002 1P.H. 5 MCF		, // 7	ý	1.9	1 7 1 1 1 1 1		÷: د :	.= 		48 2 1	. <del>`</del>
		5							Control State (Control - Control		5
							2 C				
		, . 		1	z						-,
	•		e'	: ::. :=:::					1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		, ,
	·		•		-			-			
						· · · ·		5 5	The second second second second second second second second second second second second second second second s	-	•
			•		11 	-	•		1 . Chair 1443 [14] 1	2	
								•		•	
			2								
			, :		•		· ·	• .•			
		•	2				<i>4</i> '				
			•			•		• 		-	
	1911 A. 1011		ž	1. S		-	÷	-	ショナスソント A またき	4 - 14 - 1	- '
		r.				-	•	יבי ד	このでは、「たちがたい」では、「たい」で、	••	
		•	23	:		, ,	-			•	c
				1 				••••••••••••••••••••••••••••••••••••••			, 2 <sup>1</sup> ,
			21		· · · · · · · · · · · · · · · · · · ·						
					N.)			-	THE NULL COM (20 MINUTE IN A MINUTE INTE INTE IN A MINUTE INTE INTE IN A MINUTE IN A MINUTE IN A MINUT		3
1		•		e e		•		2	AAN NUECTOR (NIEMER) - AD I		ò
	1								APAU RUPPIN CUT EXTIDA		10
									LATIN CULTARE CONTINUES		
										т. Т.	3
							•		UNDER LANSING OLD - C 2010 C 72 UNV		C)
1.0001.07		3	z	2			ж: - с.		HETP TA DUCT SAME A CED	00 V.	ຕ. ເ
	2 2 - 10 0 4 - 1 V	0	S.	С. С.	2		×		OTROMEDIAT XT YAL AGE ICC. F.		
			) U						C. SED DAT 01 CO CAVY . VIDAL		• ; •
				-+- 1 1;;					CURRENT ON DEVELON ONE	8	1,
22. 01 That		2	5	2		-+		⊇¦ ≥¦	HOW SEAL ELEVEN	00000	1
	<u>्</u>	2	S	Q		रू 	<u>`</u>	~	X-DV GEAL CPACKED AND ERODED	360.00	
5 2 2 3 3 6 1 2 2 3 1		5	145	115	15	199 A	NAU D		HAD DUCT RUP TURE - FXLDAM	1564	
		5	5					1)    [	VID ACICUMNED EDOCKAN	101 C	10
		, , ,									chi
			22						I THE WITH A WAY UNITOR		יינ
- 3302 57 Frank	A014585 15	2	2	2		2			HACK AT F-13 FLANGF eng rotred	203 86	റ
1 10 to 10 2002 to 3	A016713 1155	Ę	YES	S S S	45 65	1501	XC		VISCH MAN HUPTURE - EXT DAM	0147	
-87.70		VFS	9	Ş		2	2		DI ASCI INDZ/J E LEAK	222 56	c
		2	2			1		1	DETD THORNE DISCHADOR DUICTEAN GIOC		
								+		00.000	2
	5	3	2	2					222 INTERPROPELLANT PLATE CHACK	204.12	2
		+				-+-	_	+			
							+				
GINE NUMBER						_		-+			
ENGINE CONFIGURATION	-						-	- 4			
ACCEPTABLE CONDITION	REPORT									•	
SHIDN - UNCONTROLLED	DENGINE SHUTDO	Ň			   						1
HDWR FALR - UNCONTA	INF D HARDWARE	FALURE						i     			
TRO . ENGINE BETIBED F	J SHU SNINC I C	VENT									ł
								-			
								+			ł
LAPDWR DAMAGE - EVEL	NT RESULTED NO.	AMAGE TO	SUPPOUN	DING HARD	NARE						
NAMAGE - FAILURE WOUL	D RESULT N DAM	AGE TO TH	IE ENGINE	CLUSTER							
DWN TIME - DAYS FROM	THIS EVENT UNTIL		TEST ON	THIS STANC				-			1
INE ISSUED FOR CLITC	FF	-						†			1
A ICE COMPONENT NVC	N VED N EVENT							Ī			
						╉		t		$\frac{1}{1}$	
	EVEL		_								

.

. . \*

## 2.2 Historical Data Analysis

"Historical Data Analysis" is intended only to acquain the reader with the various analytical options presently available. In fact, as is discussed in Section 3.0 (Comparison of the Methods of Section 2.2), there is insufficient information, as well as limited time and resources available to the study, to make a thorough comparison of methodologies. Further studies are, however, recommended as stated in the Recommendations Section.

2.2.1 Y. Shen's Methodology (Reliability Analysis for Launch Vehicles)

The performance history of any launch vehicle can be considered as having two time periods, the early development period and the stable performance period. During the early development period, the unreliability of a launch vehicle is generally high and unstable. After a "failure analysis and fix" process in combination with technical and design improvements, the unreliability of a launch vehicle goes down and stabilizes.

This effect of early transient behavior followed by stable reliability behavior is indicated in Table 11a for the Thor/Delta family and Table 11b for the Titan family. In both cases, oscillating reliability histories are observed early on with later stable performance. It is also interesting to note that Titan I appears to have never reached stability and the Delta, being based on the significant Thor history, reached a stable, high level of reliability very quickly.

These historical reliability growth curves are developed according to the following method.

The maximum-likelihood estimator (failure ratio) for unreliability can be defined as:

$$\hat{U} = F/L$$

Where F is a cumulative failure number, L is a cumulative launch number and F is a function of L.

The easiest way then to estimate the average unreliability of a launch vehicle is:

$$U_{g} = F/L \tag{1}$$

where U<sub>a</sub> is the estimated average unreliability, and F and L are the cumulative failure and launch numbers.

As was mentioned before, the reliability growth effect must be considered to get a more realistic estimation of the unreliability. In the present model, the average unreliability is defined as

$$U = U_{e} - \Delta U \tag{2}$$

where  $\Delta U$  is the correction reliability caused by the reliability growth effect and can be explained as

$$\Delta U = \Delta F/L$$
  
or  
$$\Delta F = \Delta U \cdot L$$
(3)

where  $\Delta F$  is the correction cumulative failure number.

Averaging both sides of equation (3), we get

U1

•,

$$\overline{\Delta F} = \Delta U \cdot \frac{L}{2}$$
$$\Delta U = \frac{2}{L} \cdot \overline{\Delta F}$$
(4)

Substitute equation (1) and equation (4) into equation (2)

$$U = \frac{F}{L} - \frac{2}{L} \cdot \Delta F$$
 (5)

The estimation of the unreliability of the launch vehicle at the nth launch can then be approximated as

$$U_{n} = \frac{\overline{r}_{n}}{L_{n}} \cdot \frac{2}{L_{n}} \cdot \frac{\frac{1}{i-1}}{N} \cdot \frac{F_{n}}{L_{n}} \cdot \frac{F_{n}}{L_{n}} \cdot \frac{F_{n}}{N}$$
(6)

where L, is the ith launch number, and F, is the cumulative failure number at ith launch.

The reliability R, at the nin launch is

$$R_{n} = 1 - U_{n} = 1 - \left[ \frac{\sum_{i=1}^{N} (F_{i} - \frac{F_{n}}{L_{n}} \cdot L_{i})}{\sum_{i=1}^{L_{n}} \frac{F_{n}}{L_{n}} \cdot \frac{F_{n}}{N}} \right]$$
(7)

The concepts of contidence level based on the value of average reliability from equation (7) are now illustrated as the following.

Let N be the launch number, then  $X = \mathbb{N} \cdot R_n$  is the success number. In this case, the 5th percentile confidence is given by -

$$R_{0.05} = \frac{x}{x + (n - x + 1) F_{0.35}(2n - 2x + 2, 2x)}$$
(8)

and the 95th percentile confidence is given by-

$$R_{0.95} = \frac{(x+1) F_{0.95}(2x+2,2n-2x)}{(n-x) + (x+1) F_{0.95}(2x+2,2n-2x)}$$
(9)

where  $F_r(n_1,n_2)$  is the 100 r<sup>th</sup> percentile or F-distribution with  $n_1$  numerator and  $n_2$  denominator degrees of freedom.

Test Months of		Re- sults	Valu	e of fail	lure f =	= <b>1</b> - (1	-γ) <sup>1/n</sup>	Σf	R=	Remarks
(N)	testing	30113	f,	f <sub>2</sub>	f <sub>3</sub>	f <sub>4</sub>	f <sub>s</sub>	_	1 - ∑f/N	
										<b>2</b>
1	0	S						0.000	1.000	Successful test
2	3	S						0.000	1.000	Successful test
3	5	F	1					1.000	0.667	Failure mode, 1, case burnthrough
4	8	S	1					1.000	0.750	Successful test
5	11	S	0.900					0.900	0.820	f, corrected, internal installation added, success
6	12	S	0.684					0.684	0.886	Successful test
7	13	S	0.536					0.536	0.923	Successful test
8	14	F	0.438	1				1.438	0.820	Failure mode, f <sub>2</sub> TVA failure
9	16	S	0.369	1				1.369	0.848	TVA not tested
10	18	S	0.319	0.900				1.219	0.878	Successful test of TVA fix
11	20	F	0.280	1	1			2.280	0.793	Failure mode f <sub>2</sub> re- curs, f <sub>2</sub>
12	21	S	0.250	1	1			2.250	0.812	TVA not tested
13	23	S	0.226	0.900	0.900			2.026	0.844	Successful test of 2nd TVA fix
14	25	S	0.206	0.684	0.684			1.574	0.888	Successful test
15	28	S	0.189	0.536	0.536			1.261	0.916	Successful test
16	29	F	0.175	0.438	0.438	1		2.051	0.872	Spec. violation,f
17	30	F	0.162	0.369	0.369	1	1	2.900	0.829	2nd spec violation, f.
18	32	S	0.152	0.319	0.319	0	0	0.790	0.956	Spec. change elimi-
19	32	S	0.142	0.280	0.280	0	0	0.702	0.963	Successful test
20	33	S	0.134	0.250	0.250	0	0	0.634	0.968	Successful test
21	35	S	0.127	0.226	0.226	0	0	0.579	0.972	Successful test
22	37	S	0.120	0.206	0.206	0	0	0.532	0.976	Successful test
23	39	S	0.114	0.189	0.189	0	0	0.492	0.979	Successful test
24	40	S	0.109	0.175	0.175	0	0	0.459	0.981	Successful test
25	42	S	0.104	0.162	0.162	0	0	0.428	0.983	Successful test

#### TABLE 3: AN EXAMPLE OF A TEST SEQUENCE PERFORMED ON A SOLID ROCKET, ITS RESULTS AND RELIA-BILITY COMPUTATION USING D. LLOYD'S METHOD

\* Number of months after start of test program, not length of test.

Notes: Test no. 4: failure from test no. 3 (f,) is not yet diminished because corrective action is not implemented until test no. 5; f, continues to diminish in all subsequent tests since it does not recur.

Test no. 9: failure from test no. 8 (f,) is not diminished because the thrust vector actuator (TVA) subsystem is not

"hooked up" until fix is implemented and successfully tested in test no. 10. Test no. 11: failure from test no. 8 (f.) recurs; therefore, fix implemented in test no. 10 is not considered successful, and both TVA failures are reinstated as full failures.

Test no. 12: TVA is not tested while failure mode is undergoing engineering analysis, therefore, f, and f, are not diminished; Test no. 13: successful test of new TVA fix applies to both failures  $(f_i, f_j)$ ; therefore, values of both failures are diminished. TVA failure does not recur in the remainder of the example and, therefore, both failure values continue to diminish.

Test no. 16: small performance anomaly occurs; however, it is outside current specification limits and therefore, must be considered a failure (f.).

Test no. 17: same as test no. 16 (f<sub>1</sub>). Test no. 18: Corrective action for f<sub>1</sub> and f<sub>1</sub> is to change specifications/conditions (with customer approval). With this change, tests 16 and 17 become "non-failures" and f, and f, immediately become zero.

Test nos. 19-25: all are successful, demonstrating a lower probability of failure for f., f, and f, failure modes.

For a complete discussion of this methodology, see Appendix A.3.

2.2.2 D. Lloyd's Methodology (Taken from Reference 14)

D. Lloyd developed a method for estimating and forecasting reliability from attribute data, using the binomial model, when reliability requirements are very high and test data are limited. Integer data—specifically, numbers of failures—are converted, using this approach, into non-integer data. The rationale is that when engineering corrective action for a failure is implemented, the probability of recurrence of that failure is reduced; therefore, such failures should not be carried as full failures in subsequent reliability estimates. The reduced failure value for each failure mode is the upper limit on the probability of failure based on the number of successes after engineering corrective action has been implemented. Each failure value is less than one and diminishes as successes continue. These numbers replace the integral numbers (of failures) in the binomial estimate.

In Lloyd's research, this method of reliability estimation was applied to attribute data from the life history of a previously tested system, and a reliability growth equation was fitted. It was then "calibrated" to allow for reliability projections to be developed for a new similar system. In this way, the model allows for management to discern early on whether the system's ultimate reliability requirement will be met and, if so, when is it likely to be achieved. By comparing current estimates of reliability with the expected value computed from the model, a reliability growth forecast can be obtained by extrapolation.

An example application of Lloyd's method to a solid rocket program is shown in Table 3. As can be seen, the methodology predicts a significantly higher success ratio (.983 vs .80) than would be obtained without considering growth.

2.2.3 Curve Fitting (Polynomial)

Polynomial trends are of the form

 $Y = A + BX + CX^{2} + DX^{3} + \ldots + JX^{k}$ 

The straight line is a special case, having only the first two terms on the right of the equality sign. With three terms on the right, the polynomial is of quadratic form, and so forth. Typical forms are shown in Figure 3. Generally speaking, it is unwise to fit a high-degree polynomial to the data because doing so almost assures the mixing of trend and cycle. Also, a glance at the figure below will show that none of the polynomials, other than the straight line, can be extended or projected very far without going off the page. Keep in mind that only a portion of the curve is used to represent the trend.





Of course, a polynomial can be forced to fit the data quite closely by adding enough terms. A well known theorem in algebra states that a polynomial of degree k can be passed through k+i points n a plane. Accomplishing this, or anything near to it, does not contribute any information about trend. This becomes evident when it is recalled that 1 degree of freedom is lost for error for every parameter that is estimated from the data. Thus, if there are *n* observations and *n* degrees of freedom are lost in fitting a polynomial of degree *n*-1, 0 degrees of freedom left for error.

All polynomials can be fitted utilizing the method of least squares.

2.2.4 Bayesian (Reference 15)

Suppose a propulsion system is being built with a 0.95 reliability requirement at the 90% confidence level. The system goes through a number of tests: component, environmental, subsystem, system, extended time, etc. There are failures which are corrected (permanently, it is hoped). A final configuration is attained. It is also assumed that the project is at least 50% sure that a 0.95 reliable system has been achieved. If thirteen tests are run with no failures, has the 0.95 requirement been met? The classical binomial approach (see section 2.2.5) would indicate that the requirement has not been met.

This problem is typical of today's work in the aerospace industry: few systems, few tests, compressed schedules and high reliability requirements and costs. The limited number of samples for test permit no failures since even one failure would imply an intolerably high failure rate. Indeed, all "hi-rel" programs have "failure recurrence prevention" systems. All failures are "fixed" and "closed". These activities, in effect, imply that at time of "buy off," no failures should occur on qualification or demonstration tests. Hence, any solution to the reliability demonstration problem should, as a practical matter, address itself to zero failures and few trials.

Bayes Theorem, in the continuous case, states:

Prob 
$$(B \le p \le 1 | r) = \int_{-\pi}^{1} g_r(r | p) w(p) dp$$
  
 $\int_{0}^{\pi} g_r(r | p) w(p) dp$  (1)

Here, R = lower (Bayesian) confidence limit of the true reliability, p;

r = observed number of failures in n trials;

 $g_r(r|p)$  = the conditional probability density function of r given p; and

w(p) = the a priori frequency function of p.

In the binomial case,

$$g_n(r|p) = {n \choose r} p^{n-r} q^r$$
 (2)

Here  $\binom{n}{r}$  = The number of combinations of n things taken r at a time;

q = 1 - p

It is assumed that the engineer is capable of assigning a probability, P (degree of belief) to the event that the required reliability, or more, has been attained prior to test. It is also assumed that this prior belief declines linearly to zero at P = 0 and P = 100%.

)

Thus, w(p) takes the form of the triangle distribution as follows:

$$w(p) = \frac{2(1-P)p}{R} \quad \text{for } 0 \le p \le R \quad (3)$$
$$w(p) = \frac{2P(1-p)}{(1-R)^2} \quad \text{for } R \le p \le 1 \quad (4)$$

Here, P = prior probability of having the required reliability, R.

That w(p) does have the proper values can be seen by obtaining the required heights at R and multiplying these frequencies by the bases R and (1-R) of the triangles of (3) and (4). Then for the left hand interval, (0, R), we have at p = R.

$$w(R) = \frac{2(1-P)R}{R^2} = \frac{2(1-P)}{R}$$

Area over

$$(0,R) = \frac{R \cdot w(R)}{2} = 1 - P$$

Similarly at p = R for the right hand interval, (R, 1), we have

Area over 
$$(R, 1) = \frac{(1 - R)w(R)}{2} = \frac{(1 - R)2P(1 - R)}{2(1 - R)^2} = P$$

Note: The discontinuity at R is of probability measure zero.

Inserting (2), (3), and (4) in (1) yields, after cancellation and simplication,

$$Prob(R \le p \le 1) = \frac{1}{(1 - P)(1 - R) \int_{0}^{2} p^{(n - r + 1)r} q \, dp} (5)$$

$$1 + \frac{(P)(R) \int_{0}^{2} p^{(n - r - r + 1)} q \, dp}{(P)(R) \int_{0}^{2} p^{(n - r - r + 1)} q \, dp}$$

Figure 4 graphically displays equation (5). Note that in this case, thirteen tests with zero failures are adequate to demonstrate a reliability of 0.95 at 90% confidence (given a 0.5 on the Bayesian Prior scale).

While there can be no doubt that Bayesian methods, as can be seen from this example, can provide significant test reduction to demonstrate a reliability requirement, performing the analysis requires the development of a prior distribution which is, at least to some degree, subjectively based. Also, Bayesian approaches are highly sensitive to the prior distributions used. If no meaningful estimate of the prior probability of success can be made, none of the above conclusions apply. Particularly, one must be wary of consistent optimism or pessimism when records of success do not support the prior probabilities.

For example, if optimism about a new design is guarded and feasibility tests are few or non-existent, then the analysis is driven towards a rectangular prior (equally probable prior intervals), and the results are just as unfavorable (in terms of the large number of tests required) as they are for the binomial distribution. In other words, since one cannot be over 0.5 on the prior scale, 11 tests are required with zero failures to be .90 reliable at 90% confidence, the same as the binomial. This defeats the purpose of the Bayesian approach.



Figure 4. Number of trials with 0 failures to achieve 90% confidence that reliability R has been attained when a Bayesian prior is used.

The following are two examples of applying Bayes Theorem.



Figure 5. The prior and posterior distribution in example 1.

Figure 5 portrays the results of applying Bayes Theorem to estimate the unreliability of the material (LX-13 or Exter) which is an extrudable high explosive used in a variety of systems (Ref. 15). As can be seen, the posterior distribution is not much different from the prior distribution. In this case, the present observed data (failure numbers, test numbers) is relatively small compared with the previous data, and the prior distribution is given great weight in the final unreliability estimation.



Figure 6. The prior and posterior distribution in example 2

Figure 6, on the other hand, portrays the results of applying Bayes Theorem to estimate the annual pump unreliability for pressurized water reactor (PWRS) in commercial operation in the United States (Ref. 15). It is observed that the posterior distribution is much less diffuse than the prior distribution as a consequence of incorporating the observed data. In this case, the present observed data set is large and it is given much weight in the final estimation.

# 2.2.5 Classical Binomial Approach

The "traditional" approach to reliability demonstration in a go-no-go type environment is the well known Binomial distribution.

Stated mathematically the Binomial Distribution is as follows:

$$\sum_{X=S}^{N} {\binom{N}{N-X}} R^{X} (1-R)^{N-X} = 1-C, \text{ if } N \le S \le 0$$

where;

S = number of successful start tests

N = number of trials

R = reliability

C = Confidence level

where it is assumed that

- · Trials or tests are independent
- · Each trial results in success or failure
- · The reliability (probability of success) of each system is the same on each trial
- · The number of tests is fixed in advance of the demonstration test

Note that it would take 45 tests with no failures to demonstrate 0.95 reliability at 90% confidence (see Table 4).

TABLE 4: BINONIAL TABLES

Number of Tests Without Failure Vs Reliability and Confidence Level

Reltabilitev					Con	fidence L	evel, Per	cent				
(R)	50	60	70	75	80	85	ß	95	97.5	66	99.5	9.99
0.999999	693150	916290 01629	1203970	1386290	1609440	1897120	2302590	2995730	3688889	4605170	5298320	6907760
0 0000			145031	670001	100944	71/691	230259	299573	368889	460517	529832	690776
0 000	2022	2016	12040	13863	16094	18971	23026	29957	36889	46052	52983	69078
0,000	560	916	1204	1386	1609	1897	2303	2996	3689	4605	5298	6908
0. 990	145	458	602	694	805	676	1152	1493	1845	2303	2650	3454
0.997	231	305	401	462	537	632	768	000	1230	1535	7761	
0.996	173	229	301	346	401	473	575	141	021	0711	00/1	5007 5661
0.995	138	183	241	277	321	379	460	805	727	020	3201	0761
0.994	115	· 152	201	230	267	315	383	498	613	765		8711
0.993	66	130	174	198	229	270	328	427	526	657	755	985
0.992	86	114	150	173	200	236	287	£2£ .	760	276	760	090
0.991	11	101	134	153	178	210	255	332	408	510	586	766
0.99	69	92	120	138	160	188	229	298	367	459	527	688
0.98	34	45	60	69	80	94	114	149	183	228	263	342
0.97	23	30	40	45	53	62	76	66	121	151	174	227
0.96	17	23	30	34	39	46	R	74	91	113	130	170
120.01	14	18	24	27	31	37	(5 y)	58	72	06	103	135
0.94		15	20	22	26	31	£E	67	60	75	86	112
0.93	10	13	17	19	22	26	32	42	51	64	74	96
0.92	6	=	15	17	19	23	28	36	45	55	64	83
0.91	80	10	13	15	17	20	25	32	39	67	57	74
0.9	7	6	12	13	15	18	22	29	35	44	51	66
0.8	<b>~</b> ·	4	9	Q	7	6	11	14	17	21	24	31
0.7	8	m	4	4	ŝ	9	7	6	11	13	15	20
0.6	7	. 12	Ē	e	4	4	5	9	80	6	Ξ	14
0.5	-	~	7	7	e	r,	4	S	Q	2	8	10
-												

# 2.3 Baseline Reliability Enhancement Methodology Identification

# 2.3.1 Proposed Infrastructure Controls Affecting Reliability

Figure 7 illustrates how various activities related to the categories of design, manufacturing, test, transportation, storage and operation can have an effect on reliability. Each category has listed underneath it examples of reliability enhancing technique and tools. They represent a cross section of ideas accumulated during the site visits of Task 1. Some of the techniques are well known and proven, such as reliability predictions/trade offs. Others are not, such as operating characteristic curves vs. reliability.

The following is a discussion of proposed infrastructure controls intended to enhance reliability. The discussion is divided into quantitative and qualitative approaches followed by a discussion of risk assessment as a decision making tool.

Quantitative Approaches - Analysis of Historical Data (See Section 2.2), PRACA/FRACA Trending - In order for a Problem/Failure Reporting and Corrective Action system to be suitable for mathematical trending, basic changes must take place in the way information is recorded and tracked (see Section 1.1.3.2). These changes include as a minimum:

· Recording total operating times on failed as well as unfailed components

• Total number of cycles or trials (both successes and failures)

• Inclusion of reports of all component malfunctions, even those which were noncatastrophic and occured on non-critical components.

<u>Operating Characteristic Curves Correlated to Failure Modes/Rates</u> - The example that follows illustrates one method of connecting defect rates from Q.C. sampling plans to reliability calculations for hardware. Although this example is for solar array calculations, there is every reason to believe that a similar approach could be used for propulsion systems.

# Data

- If entire population had random defect rate of 0.65%, one would expect to reject 10% of lots due to the randomness of sampling process. Figure 12 (page 73) illustrates the use of MIL-STD-414 for the purpose of determining the 10% reject rate. The 0.65% defect rate corresponds to a 90% confidence for the lots expected to be accepted or, conversely, 10% are expected to be rejected. Assume that the MIL-STD 414 plan has thus far rejected 58/434 = 13.4% of lots.

- This result is indicative of non-homogeneous population wherein some lots are worse than 0.65% and therefore have a higher probability of being rejected; clustering of bad lots is also indicative of non-homogeneous population

- Thus, residual defect rate in the accepted lot subpopulation will be less than 0.65% per test; assume observed rate in lots accepted to date is 0.65%

• For purposes of an example, consider estimating solar array reliability, a failure probability of 0.25%, will be assumed for each interconnect over the course of the three year mission (conservative)

• Each quarter string consists of an average quantity of 39 cells

Power margin allows subsystem to accept 22 quarter string failures in each of two sets
 of 992 quarter strings



Figure 7. Infrastructure controls proposed to enhance reliability.

• Two of four interconnects on a cell are pulled as part of sampling test; failure probability per pull estimated as 0.25%; two tested interconnects are from either end of cell; data from immediately adjacent interconnects is not available.

- Correlation between pull strength values from same cell analyzed and found to be .38 for all lots tested, .54 for the ten "bad" lots tested, and .32 for "unknown" lots; value would be somewhat smaller yet if attention were restricted only to lots accepted by sampling process

- Correlation of .32 means that knowing the strength of one interconnect helps one predict the strength of a second interconnect on the same cell (.32 - .32) = .10 or 10% more accurately than one could predict it without knowing the first value; the square of the correlation is known in statistics as the coefficient of determination.

• Probability of both interconnects failing is:

- PR (first failing) + PR (second failing/first fails);
- PR (A/B) read as probability of A given that B is known to occur
- If totally independent, PR (Second Failing/First Fails) = 0.0025
- If totally dependent, PR(Second Failing/First Fails)=1.0

- Since the 10% factor developed above measures the strength of the dependency which exists, it may be used to interpolate between .0025 and 1.0 to estimate PR (Second Failing/First Fails) (1.0 - .0025) \*.10 + .0025 = .10225

Probability of two interconnect failures out of two on same cell is thus estimated at
 .0025 \* .10225 = .00026

• Since adjacent interconnects are probably somewhat more correlated than those at either end of cell, and since degree of correlation is not known, if we assume that interconnects fail at both ends of the cell, then the cell will fail totally. Using this assumption will, of course, produce somewhat of an overestimate of probabilities. This overestimate is, however, small compared to the effect being observed.

- This means we will estimate the mission failure probability for a cell to be .00026.

- This equates to a cell failure rate or: -LN(1-.00026)/26298 = 9.9E-9/HR

- A quarter string with 39 cells will thus have a failure rate due to interconnects conservatively estimated at 39 \* 9.9E-9 or 386E-9/HR

• The impact of this new cell failure mode on the array is to change the failure probability from 6.25 x  $10^{-6}$  to 6.21 x  $10^{-4}$ , an approximate two order of magnitude change.

<u>Qualitative Approaches</u> - Product Design FMEAs - Although Product Design FMEAs are not unheard of in the aerospace industry, very few companies perform them. In essence, product design FMEAs are structured to identify sources of common cause failures (sometimes called "coverage factors" or "correlation factors" by propulsion manufacturers). Although the following product design description is directed towards electrical/electronics components, a similar approach could be used for propulsion system components.

Product design Failures Modes and Effects Analyses (FMEAs) are performed to verify that hardware reliability and integrity is maintained when electrical/mechanical designs are implemented as hardware during the product design phase. This type of analysis is typically done between PDR and CDR after drawings become available, but before they are released.

This analysis is particulally appropriate for examining areas where redundant or backup paths are in proximity.

When redundancy is implemented by using separate units, there is generally no need to do a product design FMEA inside each unit. However, this may not be true for high energy systems such as propulsion. In either case, unit external interfaces, e.g., input/output cross-straps, should be examined. Example: product design criteria are listed below. Results are documented on Product Design FMEA Forms. Where negative findings occur, remedial action is recommended. Adverse conditions are to be justified at design audits.

The following Reliability Criteria for Product Design are applied in performing product design FMEAs for printed circuit boards, connectors, and wiring interfaces:

## Cabling, Hardnesses, and Wire Bundles

a) Assure that fault isolation exists.

b) The routing of all wire bundles shall be such that all possible locations where wire pinching or chaffing could occur are eliminated to prevent shorts to ground or shorts to different voltage or signal source.

c) Assure that the design prevents screw threads from coming into contact with wire/leads during assembly.

d) Provide for special sleeving where wire routing is adjacent to sharp edges.

e) Prevent excessive pinching of wires by cable clamps by properly dressing bundle and sizing clamps.

f) Spot bond or tie wire adjacent to standoffs and with reasonable distance between supports such that loads/joints are not degraded during exposure to vibration or shock.

g) No single wires or single solder joints shall be system single point failures.

## **Connectors**

a) Similar connectors on a unit shall be keyed, color-coded, or have other mismating protection.

b) Physically separate power and ground pins.

c) Different polarity signals shall not have adjacent pin assignments (Vis.; +28Vdc, -15Vdc).

d) Sensitive low level signals should have pin assignments physically separated from high level power, high level signals, or ungrounded returns. This should also apply to grounds.

e) Critical power or signal lines shall not have adjacent pin assignments.

f) Redundant power or signal lines shall not have adjacent pin assignments.

g) Review pin and slip ring assignments to assure that shorts between adjacent pins will not result in single point failures.

h) No single connector pin shall be a system single point failure.

## Printed Circuit Boards

a) Review that redundant paths are kept physically separated as much as possible.

b) Traces carrying heavy current loads shall be verified as having adequate load carrying capacity per MIL-STD-275.

c) There shall be no open daisy chains for power or ground paths.

d) Sufficiency in the spacing between traces depends on trace voltages and conformal coating provisions. These should be reviewed against Standard Engineering Design Systems to confirm that trace-to-trace shorts will not occur.

e) A grounding circuit trace leading to board edge common ground should be filleted at the lead-in line to prevent development of cracks in circuit conductors.

f) Check that redundant paths don't go through the same piece part, e.g., a dual transistor or quad IC.

g) If there are any single PC traces or plated-thru-holds where an open would result in a system single point failure, hardwire should be added.

h) Care shall be taken to assure that high heat generating parts are isolated from cirtical signal paths (via distance/shielding) to preclude burnout of PC traces, etc.

i) Ensure that solder joints are inspectable. Avoid soldering flush-mounted parts near heat sinks or other items which might make the presence of solder balls undetectable.

j) Ascertain that the block diagram or schematic-illustrated redundancy is reflected by the wiring diagram.

k) Assure that solder reflow practices for boards (or within parts) will not reflow or degrade prior connections.

I) Handling and installation loads for cards and assemblies must be reviewed to ensure that stresses imposed on joints are within their load-carrying capability.

m) PC traces and wiring should be physically separated such that a fault is isolated and will not cascade to redundant or adjacent elements.

n) Verify that PC boards which contain redundancy or cross-strapping elements are adequately protected against shorts to ground (internal and external to the board) which could represent a system single point failure.

o) Plated-thru-holes shall have an aspect ratio (board thickness to hole diameter) or no greater than 3 to 1.

			0	1	2	3	4	5n
		0						
		1						
F	G TYPE)	2						
OUTPU	(WRON	3						
SULTING		4						
D OR RE		5 : n						
ROVIDE		More of (ii+1)						
<b>UCTION F</b>		Less Than (n+2)						
E	IONG OF	As Well As (n+3)						
	(WF	Part of (n+4)						
		Reverse (n+5)						
		Other Than (n+6)						

Function Expected\* or Output Required

\*Obtained from a clear, concise, unambiguous set of Engineering functional descriptions

Figure 8. Top down matrix.

<u>Manufacturing Control FMECAs</u> (See Appendix B: MCDAC Trip report) - In the case of the manufacturing control FMECA, the FMECA should be conducted incrementally by reliability engineering during the design phase to identify single point failure modes. The FMECA should be used in the Critical Item Control process by identifying critical items and the causes of critical failure modes. Proper design controls would then be implemented for each critical item and can be verified by a Manufacturing Control Plan. FMECAs should be supplemented with failure history prior to FMECAs of related designs and, along with the failure history, should be made available to designers.

A manufacturing Control Plan should contain as a minimum the following task:

- Identify flight critical items (FCIs) using FMECAs
- Determine flight critical characteristics for each FCI
- · Identify specific manufacturing methods for each FCI
- Prepare Manufacturing Flow Chart and annotate
- Identify Process Control for each select manufacturing method
- · Identify test and/or inspection methods for each select manufacturing method

<u>Top Down Analysis</u> (L. Booth Method) - The most common criticism of FMEAs is the possibility that not all conditions causing system anomalies, malfunctions or failures are attributable to inherent component failures.

One way to audress this concern is by conducting a "Top Down" analysis. A Top Down analysis is conducted by accomplishing the following tasks:

- Obtain a clear, concise, unambiguous set of <u>engineering functional descriptions</u>
- Form a matrix as shown on Figure 8

• For each intersection (square) on the matrix, describe the system condition (i.e., 0 = nominal thrust, n+6 (other than) = wrong direction). Therefore, (0, n+6) means correct thrust, wrong direction. The square (0,0) indicates correct nominal thrust was required and correct nominal thrust was delivered.

• Each square of the inalitix is a potential "Top Event" (undesirable condition).

• Explore leach top event (using fault trees, event trees or similar techniques) until all conditions leading to the top event have been exhausted.

Risk Assessment (reference Figure 7) - Risk assessment can be characterized as follows:

• Risk assessment is the process for estimating the risk associated with a particular alternative course of action

• Risk assessment considers probability of failure and consequence of failure as they relate to technical performance, schedule, and cost

#### Where

Risk is the probability and consequence of not achieving some defined program goal and is a function of:

- Probability of failure
- Consequence of failure
- Increased Cost
- Extended schedules
- Reduced performance

Risk assessment involves these steps indicated in the rollowing diagram:



Where risk levels are defined as:

High The problem is obvious and there is a high probability of failure to meet reliability, performance, schedule or cost objectives. Monitoring and control must be rigorous, with frequent update of risk status. A fall-back or alternative system or plan is mandatory.

Medium - The problem is identifiable and would impact program reliability, performance, schedule, or costs. The probability of occurrence is high enough to require close control of all contributing factors, establishing of risk management milestones, and an acceptable fall-back position.

Low - The problem is identifiable and would impact program objectives, but the probability of occurrence is low as to cause no concern other than normal monitoring and control.

#### 2.3.2 Risk Management

Risk management is the process which encompasses the identification, assessment, tracking, control and mitigation of risks related to reliability and results in overt actions to accept known risks or to make adjustments which control their potential consequences.

Risk assessment assesses the chance and consequence of being unable to obtain higher reliability, when it is needed, within the allocated financial resources.

Establishing Factors - In order to assess and manage risk, factors must be established based on technical risks. Factors can be characterized by using the two following matrices (Figures 9 and 10).

Assessing Economic Risk - Given the information of sections 2.3.1.3 and 2.3.2.1 are available, the most efficient way to assess economic risk is to use an established model tailored to the rocket industry. The model accounts for both production and operational processes that would be impacted by unreliability. Additional economic modeling of the cost of unreliability to customer communities is essential to gain a meaningful estimate of economic risk. Economic models must evaluate the actual cost of finite activities required to reduce risk by finite amounts.

In the case of launch vehicles, most individuals recognize the direct costs of unreliability such as residual hardware that is scrapped due to more rigorous inspections or redesign effort. The incorporation of additional quality control that slows production rates and operational process timelines while increasing the total amount of personnel and facilities that are required to support the vehicle is a more subtle cost effect of unreliability. The largest cost is related to payload communities that suffer direct losses in the form of lost hardware and higher insurance rates, as well as launch schedule backlog effects that result in program slippage that has cost of money and cost of storage implications. Actual costs of unreliability are difficult to estimate accurately, but the costs may be bounded from documented historical events that give a real estimate of cost risk exposure.

Perhaps the greatest single "cost" of unreliability can be related to loss of strategic capability at critical time windows. For the military, this may be the absence of reconnaisance capability during evolving international crises or a less capable navigation or communications environment for operations. For the private sector, the strategic loss may be in the form of lost opportunity to penetrate specific markets at advantageous time windows. Unreliability also results in loss of national stature and a hinderance in the ability to successfully compete with the international community.

The economic risk of unreliability is but one element of the overall risk assessment. The overall risk is a combination of economic risk, schedule risk, and mission capability risk. In essence, the approach would be to assign relative figures of merit (ranging from 0 to 1) of each of the risk factors of Figures 9 and 10, then compare the summed risk factors against a cost of reducing the overall risk. The program manager can then look at the relative cost benefit of risk reduction investment options that assures ultimate program viability.

Maturi	ty Factor	Complexity	y Factor	Dependency Factor		
Hardware	Software	Hardware	Software	Dependency Factor		
Existing	Existing	Simple design	Simple design	Independent of existing system, facility, or associate contractor		
Minor redesign	Minor redesign	Minor increases in complexity	Minor increases in complexity	Schedule dependent on existing system, facility, or associate contractor		
Major change feasible	Major change feasibio	Moderate increase	Moderate Increase	Performance dependent on existing system performance, facility, or associate contractor		
Technology availabie, complex de- sign	New software, similar to exist- ing	Significant increase	Significant in- crease/major increase in a number of mod- ules	Schedule dependent on new system schedule, facility, or associate contractor		
State of art, some research complete	State of art, never done be- fore	Extremely complex	Extremely complex	Performance dependent on new system schedule, facility, or associate contractor		

Figure 9. Typical top-level factors contributing to probabilty of failure.

# Typical Top-Level Factors Contributing to Consequence of Failure

Technical Factor	Cost Factor	Schedule Factor
Minimal or no consequences, unimportant	Budget estimates not ex- ceeded, some transfer of money	Negligible impact on program, slight development schedule change compensated by available schedule slack
Small reduction in technical performance	Cost estimates exceed budget by 1 to 5 percent	Minor slip in schedule (less than 1 percent), some adjust- ment in milestones required
Some reduction in technical performance	Cost estimates increased by 5 to 20 percent	Small slip in schedule (1 to 10 percent)
Significant degradation in technical performance	Cost estimates increased by 20 to 50 percent	Development schedule slip (10 to 30 percent)
Technical goals cannot be achieved	Cost estimates increased in excess of 50 percent	Large schedule slip that affects segment milestones or has pos- sible affect on system milestones (greater than 30 percent)

Figure 10. Typical top-level factors contributing to consequence of failure.

# 3.0 (TASK 3) QUANTIFICATION AND PRIORITIZATION OF METHODOLOGIES

In many cases, there is insufficient information to completely quantify and prioritize the methodologies that have been identified. In other cases they are difficult to prioritize because of the qualitative nature of the methods. In any case, thorough testing of the various methodologies should be the subject of future studies (see recommendations).

## 3.1 Testing of Quantitative Methods

Three areas of study appear to be promising. They are:

- Comparison of the methods of Section 2.2
- PRACA/FRACA Trending
- · Connecting Operating Characteristic Curves to Reliability
- 3.1.1 Comparison of the Methods of Section 2.2

Section 2.2 includes a description of a selected number of quantitative methods intended to indicate reliability growth as well as demonstrating the achievement of a prescribed reliability goal.

Four of the methodologies - Binomial model, Beta-Binomial model (Bayesian Estimation), Lloyd's model and Shen's model for estimating reliabilities of launch vehicles from attribute data are introduced and compared in a preliminary manner.

<u>Binomial Model</u> - The simplest way to estimate the reliabilities of launch vehicles is to use the Binomial model. It is easy to perform the calculations, but a large size sample is required to demonstrate high reliability. The results obtained by applying this model do not account for the reliability growth effect expected during the developmental history of the launch vehicles.

<u>Beta-Binomial Model</u> (Bayesian Estimation) - The Beta-Binomial model is based on the Bayesian Estimation. In this model, several similar components are treated as a single class. The probability p of each component in the class is assumed to be constant but will have different values from component to component [i.e., g(p)]. If the Binomial distribution is used to obtain the probability of K failures in n tests for each component, the conjugate distribution g (p) for the class is the Beta distribution. This model weights the reliability growth effect and can be applied to forecast the reliabilities of launch vehicles. The detailed theoretical analysis can be found in Ref. 19, "Bayesian Reliability Analysis" by Harry F. Martz and Ray A. Waller, 1982. The disadvantage of this model is that it is very difficult to separate the total sample data into several similar components, unless we have the detailed engineering analysis and each failure model at the different periods of the launch vehicle developmental history.

Lloyd's Model (Ref. 14) - In Lloyd's model, the rationale is that when engineering corrective action for a failure is implemented, the probability of recurrence of that failure is reduced; therefore, such failures should not be carried as full failures in subsequent reliability estimates. The failure value for each failure model is assumed to be

$$f = 1 - (1 - \gamma)^{1/n}$$
(1)

where  $\gamma$  is the confidence level and n is the number of successful tests after corrective action.

Based on a detailed engineering analysis for each failure mode, the result of failure number for each failure mode can be obtained by solving eq. 1. The final result of the reliability estimation is  $R = 1 - \Sigma f/N$ , where  $\Sigma f$  is the cumulative failure number of all failure modes. N is the test number.

This model weights the growth effect and can be extended to forecast the reliability. For this model one needs to know not only at which launch number the failure occured, but also at which launch number the failure was corrected. The confidence level chosen in eq. 1 directly affects the final results and is difficult to justify. The confidence level for the final result  $R = 1 - \Sigma f/N$  is not clear.

<u>Shen's model</u> (Ref. Appendix A.3) - In Shen's model, the reliability Rn of a launch vehicle at the n<sup>th</sup> launch is obtained as

$$R_{n} = 1 - U_{n} = 1 - [F_{n'}L_{n} - 2/L_{n'} \sum_{i=1}^{N} (F_{i'} F_{n'}L_{n'}L_{i})/N] \quad (2)$$

where U<sub>n</sub> is the unreliability at n<sup>th</sup> launch

F, is the cumulative failure number at n<sup>th</sup> launch

L, is the n<sup>th</sup> launch number

F, is the cumulative failure number at i<sup>th</sup> launch

L, is the ith launch number.

The term  $F_{a}/L_{a}$  in eq.2 is the estimated average unreliability at the n<sup>th</sup> launch. The term

 $2/L_{n^{e}} \sum_{i=1}^{N} (F_{n} F_{n'} L_{n^{e}} L_{i}) / N$  in eq.2 is the corrective unreliability caused by growth effect.

This model is simple and easy to apply. It weights the growth effect and can be extended to predict the future reliabilities of the launch vehicles. The final results of the model are obtained directly from the collected data in which only the launch numbers at which the failures occured need to be known.

However, since this model does not assume any knowledge of what changes were made subsequent to failures, it does not directly incorporate the effects of engineering analysis and corrective action taken after each failure. For this reason, its reliability growth forecast lags that of Lloyd's method.

From the above analysis of these four methodologies, the Lloyd's model and Shen's model are considered to be the better models for estimating reliabilities of launch vehicles.

Fig.11 illustrates the results by applying Lloyd's and Shen's models to an example from Ref. 1. As we can see, the tendencies of the results for both models are similar, the values of estimating reliability from Lloyd's model are higher then those from Shen's model.

In the present study, based on the collected data, the Shen model is used to estimate the reliabilities for twenty-four U.S. launch vehicles. The growth trends obtained from the model are shown in Figures 11a, and 11b for the Delta and Titan families of launch vehicles.



Figure 11. Lloyd vs. Shen comparison.

R



Figure 11a. Reliability estimation of Thor and Delta.


Figure 11b. Reliability estimation of Titan I, II, III.

# 3.1.2 PRACA/FRACA Trending

An additional dimension could be added to PRACA/FRACA system to allow trending if a "cradle to grave" concept were established. Under the current circumstances PRACA/FRACA systems frequently report only through the testing phase (except for reusable systems) and do not always report on total time and cycles on both failed and unfailed components.

In addition, PRACA/FRACA systems should include not only failure phenomenon but precursors to failure problems as well. Such precursor problems should include unexpectedly low margins or larger than expected variability. The corrective actions should be accomplished interactively with system functional descriptions and the FMECA to insure that those efforts are up to date while the search for root cause is pursued.

In order for an evaluation of PRACAs/FRACAs trending capabilities to be affected, a pilot program needs to be established using the trending techniques of reference 2.

## 3.1.3 Operating Characteristic Curves and Reliability

An example was given in Section 2.3.1.1 correlating operating characteristic curves to failure modes and failure rates. Reference 17 illustrates some recent work in this area. In this work an effort was made to tie safety factors developed in the traditional engineering approach to resulting structural reliability using a probabilistic representation of these traditionally developed factors.

Figure 12 illustrates the relationship of defect rates (quality of submitted lots) to operating characteristics (OC) curves. In this way, changes in sampling plans and procedures could be linked to criticality ranking in FMECAs.

For example, suppose the amount of moisture in a bonding liner polymer used in solid rocket motor cases is linked to poor quality of bonding, thus to separation. A change in the sampling procedure could reduce the defect rate and reduce the potential for failure by a similar amount.

A study should be undertaken to test the validity of such a link.

# 3 2 Evaluation of Qualitative Methods

As was noted earlier, it is difficult to prioritize qualitative methodologies. However, the three methods that do show promise based upon the information obtained from this study effort are:

- Top Down Analysis
- Product Design FMEAs
- Manufacturing Interfaces

Tests of these techniques could help to more firmly establish these capabilities. Suggested tests are defined below:

## 3.2.1 Top Down Analysis

In order to rate the value of "Top Down Analysis" when conducted in accordance with the method

MIL-STD-414 11 June 1957

# SAMPLE SIZE CODE LETTER

( C.

F

### irves for sampling plans based on range method and known variability are essentially equivalent )





described in Section 3.2.1.2, the results of an FMEA should be compared to the results of a Top Down analysis.

## 3.2.2 Product Design FMEAs

Product Design FMEAs have proved to be valuable in identifying and eliminating sources of common cause failures in electrical/electronics applications (see Section 2.3.1.2). A study should be undertaken to see if a Product Design FMEA would be fruitful when applied to the non-electronic propulsion subsystems.

## 3.2.3 Manufacturing Interfaces

Flight critical item and manufacturing control plans have a great deal of potential for controlling critical items as described in Section 2.3.1.2 "Manufacturing Control FMECAs". The effectiveness of such an approach remains to be demonstrated, however. A study should be undertaken to demonstrate the effectiveness of manufacturing control FMECAs.

### 3.3 Prioritization of Methodologies

The prioritization of methodologies cannot be completed until the studies described in this section are completed.

### **KEY RECOMMENDATIONS**

The following areas have been identified as having significant reliability impact. These areas each warrant further in-depth study if the high reliability goals of the Air Force advanced launch vehicle programs are to be achieved in an operational system.

# 1. Failure Correlation\*

The percentage of failures which are likely to impact more than one engine in a multi-engine design is of critical design import. This percentage, or "failure correlation factor," must be well below 20% for reliability oriented design approaches such as engine out capability to be effective. The lower this percentage the more effective is this hueristically pleasing design option. Not surprisingly therefore, contractor new engine design characteristics quote extremely low factors (as low as 1%). Correlations as low as 1 out of 100 do not seem consistent with other design parameters specified (such as high chamber pressures) and are considerably lower than factors achieved on recent engine designs (e.g. 17% for the shuttle main engine test program). Finally, there did not appear to be any significant consideration given to how these low factors would be achieved in practice.

<u>Recommendation 1</u> - Failure correlation factors are key reliability parameters to Air Force launch vehicle design decision makers. Specific studies such as parameter design studies which address what factors have been achieved in the past and what design trades have been made to ensure the low factors quoted will be evident in the resulting designs appear to be lacking. It is recommended that these investigations be made prior to the selection of any design alternative.

# 2. Variability Control

The currently achieved launch vehicle reliability has been shown by this investigation to be below 0.95. However, the investigation uncovered examples of reliabilities in other somewhat similar systems, such as tactical missile systems, which routinely achieve 0.99 and some which approach 0.999. These systems whose operational reliabilities currently meet or exceed the reliability requirements for the Air Force advanced launch system have achieved these high reliability levels through the use of intensive variability control programs. While it would be inappropriate to make any direct correlation between tactical missiles and launch vehicles, it is also clear from a review of the failure data of mature launch systems that the barrier to significantly higher reliabilities may be the residual variability inherent in the current launch vehicle production process. A cursory review of other somewhat comparable products, such as commercial jet engines and gas turbines and recent Air Force variability reduction studies performed as part of the R&M 2000 program, provide further support for this argument.

<u>Recommendation 2</u> - Residual variability may be the key barrier to high launch vehicle reliability achievement. For this reason, it is recommended that investigations be made into the effectiveness of specific variability control programs such as Taguchi methods or alternatives. These investigations should be directed at determining the applicability of the methods to the launch vehicle production process. It is further recommended that some specific program for variability control be included throughout all phases of the advanced launch system program.

\* The definition cited here is broader than that used traditionally by propulsion system designers. See Appendix A.1 for discussion of the difference.

# 3. Reusability

Reusability is, on the surface, a design goal of significant program benefit. However, the benefits of reusability are significantly compromised if the reliability of an engine is adversely affected by the requirement. Besides the direct costs involved in developing a reusable design, there also appears to be significant indirect costs which are required to maintain reliability in a reusable design. For example, reusability by its very nature tends to decrease the production run. When production runs are decreased, investments in automated production equipment become less economical and the production process therefore tends to become more prototypical. Prototypical production, especially of complex equipment, increases the problems associated with variability control and therefore substantial postproduction testing may be required to ensure high reliabilities. A good example of such an indirect impact on reusability was seen at the Rocketdyne SSME production facility in Canoga Park, California.

<u>Recommendation 3</u> - Reusability has been shown to have indirect and potentially negative impacts on the achievement of high reliabilities at reasonable cost. The indirect impacts of reusability on reliability and cost through such mechanisms as variability control problems should be thoroughly investigated and the results of this investigation included in the programmatic decision making related to reusability.

# 4. Risk Management

Achievement of high operational reliabilities in such areas as nuclear power plant safety systems have been significantly supported by a continually active program that attempts to identify the risks to reliable operation and to address them according to their importance. Such a risk management program has been investigated and recommended by NASA SRM & QA for future projects, but it is not clear whether a risk management program is planned for the acquisition of advanced launch systems.

<u>Recommendation 4</u> - The Air Force should investigate the advisability of incorporating a risk management program as an integral part of any launch system program.

## 5. Reliability Performance Indicators and Trending

For high reliability programs it is important to identify, early on, symptoms of the process which presage deterioration in performance. This has been done in the financial community, in the commercial aircraft community and in the nuclear power safety community by the development of a set of "leading" performance indicators and developing performance trends based upon the indicator trajectories through time. If such a set of indicators could be developed and trended for the Advanced Propulsion Systems program, the indicator trajectories might provide early warning of problems arising during development and operation. This early warning could provide the time required to institute corrective action before actual program reliability performance is affected.

<u>Recommendation 5</u> - The Air Force should develop as part of advanced propulsion system development programs a set of potential indicators of programmatic reliability performance. This indicator set should be based originally on historical information, but later updated and validated as advanced propulsion system development programs specific information becomes available.

## 6. Reliability Growth Analysis

In all developmental systems a certain degree of reliability growth is to be expected. However, program managers need to know the pace of the expected growth so that they can determine if the program is likely to meet the operational reliability goals within developmental time constraints. An understanding of the growth process is therefore essential to the determination of the proper role to be played by history in the forecasting of future system reliability. If an historical failure has been analyzed and its cause determined and suitable corrective action is implemented to prevent its recurrence, it is recognized that it would have its probability of occurring again diminished when it is utilized for predicting future performance. But by how much? The determination of how much each failure should be counted is important in order to establish the proper "calibration" for the reliability growth characteristic to be used to determine how well reliability development is proceeding. Several approaches have been developed to address the issue of growth. Among those developed are the early works of Duane at GE, that of David Lloyd of TRW, and that developed by Dr. Yu Shen of SAIC as part of this study. In addition, Bayesian approaches may show promise for improved growth forecasting.

<u>Recommendation 6</u> - Reliability growth forecasting is important during the development of systems with high reliability requirements such as ALS. Accurate growth forecasts allow program managers to determine early on if reliability requirements are likely to be met. (This is especially important when program economics prohibit extensive development test flights as is the case with ALS). Several methods currently exist to allow for forecasts to be generated; however, further development is required to assure that a reasonable growth forecast is developed for advanced propulsion system development programs. It is therefore recommended that the concept of reliability growth be further developed as it applies to advanced propulsion system development programs.

<u>Eurther Recommended Studies</u> - The recommended studies as discussed in Section 3.0 are judged to be somewhat less in importance than the Key Recommendations above. Nonetheless, the following recommended studies could have a significant impact on reliability.

- 1. Detailed Comparison of the Methods of Secion 2.2
- 2. PRACA/FRACA Trending
- 3. O.C. Curves and Reliability
- 4. Top Down Analysis
- 5. Product Design FMEAs
- 6. Manufacturing Interfaces

# REFERENCES

- 1. "A Historical Look at United States Launch Vehicles 1967-Present" by R. Barrett, et. al. STDN 88-3 prepared by ANSER, Suite 800, 1215 Jefferson Davis Highway, Arlington, VA 22202.
- \*Performance Trend Analysis System Technical Requirements Guidelines" prepared by Pan American World Services, under Rockwell Test Integration Contract WBS 19.1.2 dated Sep 30, 1988, for NASA Johnson Space Transportation Systems.
- 3. "Low Cost Reliable Access to Space-A Solids Approach" Prepared by the Solid Rocket Technical Committee of the AIAA July 1988.
- 4. "Advanced Launch Systems Operations and Cost Analysis" Contract No. F0 4701-85-C-0055. Prepared by L. Systems Inc., 2250 East Imperial Highway Suite 600, El Segundo, CA 90245. Prepared for Air Force Systems Command Space Division.
- 5. "An Assessment of Liquid Propulsion in the United States" by Liquid Propulsion Technical Committee of the AIAA.
- 6. "Launch Vehicle Reliability Study Data Base" compiled by C. T. Clague of Aerospace Corporation as transmitted to G. Platt of Marshall Space Flight Center in a memo dated July 18, 1988.
- 7. \*Space Shuttle Failure Mode and Effect Analysis (FMEA) and Critical Items List (CIL) Ground Rules" Prepared by Marshall Space Flight Center Reliability and Quality Assurance Office, EG01 EG 5320.1.
- 8. "Problem Reporting and Corrective Action (PRACA) System Requirements for the Space Station Program" by Johnson Space Flight Center Product Assurance, November 26, 1986.
- 9. "Defences Against Common-Mode Failures in Redundancy Systems" by United Kingdom Atomic Energy Authority , Wigshaw Lane, Culcheth, Warrington WA 34 NE.
- 10. "Assessment of Methods for Implementing Availability Engineering in Electrical Power Plants" by Holmes and Narver, nc., EPRI Report NP-493 TPS76-662, May 1977.
- 11. "Fault Tree Handbook" U.S. Nuclear Regulartory Commission, NUREG-0492, January 1981.
- 12 "Hazard Analysis of Commercial Space Transportation" Vols I, II, III by DOT Transportation Systems Center. Office of Commercial Space Transportation Licensing Programs Division, May 1988.
- 13. "IEEE Guide for General Principles of Reliability Analysis of Nuclear Power Generating Station Protection Systems " IEEE Std 352-1987.
- 14 "Forecacting Heilability Growth" by D. K. Lloyd TRW Inc., Electronics and Defense Sector, One Space Park, Redundo Beach, CA 90278, from Proceedings--Institute of Environmental Sciences 1986 John Wiley & Sons, Ltd.
- 15 "Why Bayes is Better: by A. J. Bonis from the 1975 Proceedings of the Annual Reliability and Maintainability Symposium(Including notes taken from Dr. Bonis' lectures at the Eleventh A. nual Reliability Engineering and Management Institute, November 11-20, 1973, University of Arizona).
- "Techniques for Reliability Assessment and Growth in Large Solid Rocket Motor Development" by D. K. Lloyd et. al., AIAA Paper Number 67-435. Presented at AIAA 3rd Propulsion Joint Specialist Conference, Washington, D. C., July 17-21, 1967.

- 17. "Safety Factors QC Screen and Failure Rates" by Sid Lishman, NASA MSFC, June 22, 1988
- 18. "Statistical Analysis" by E.C. Bryant, McGraw Hill, 1960
- 19. "Bayesian Reliability Analysis" by H.F. Martz and R.A. Waller, Wiley, 1982

Appendix A.1

An Investigation of Historical Failure Correlation Using the Shuttle SSME Test and Flight History as an Example

### INTRODUCTION

Given the current state of *icklet* engine technology there exists a finite probability of a catastrophic engine failure during a vehicle launch. A catastrophic engine failure is considered one in which the engine does not shut down in a controlled manner and includes uncontrolled fire, explosion, breach of the pressure boundary, shrapnel, or a combination of these. Given that an engine has failed catastrophically in flight an immediate concern is for other critical hardware in the vicinity of the failed engine. For vehicles configured with multiple engines in a cluster the question become whether the catastrophic failure of one engine will result in the catastrophic loss of the entire engine cluster.

This study develops the correlation between a catastrophic failure of a Space Shuttle Main Engine (SSME) and the propagation of that failure to include the entire SSME three engine cluster.<sup>+</sup>

### SSME FAILURE DATABASE

The SSME database used for this study consists of ground test and flight data from May 19, 1975 through April 20, 1988. The database includes 1480 records detailing the SSME exposure history by test and date

Significant SSNE events which have resulted in damage or the loss of hardware are classified by NASA as major incidents. Catastrophic engine events are a subset of the events classified as major incidents. A catastrophic event is one in which its occurrence in flight results in significant uncontained engine damage and subsequently in the loss of crew and vehicle. The consideration of major incidents is the basis for developing the correlation of failure factor for the SSME.

Within the total oSME experience there have been 36 major incidents. Of these 32 of these incidents have been during single engine ground tests, which must be judged as applicable to this study and whether the event would have resulted in damage to an engine cluster. Three of the major incidents occurred during three engine cluster static firings and it should be noted that none of these events resulted in damage to the other engines in the cluster. The remaining major incident occurred to flight during the STS-11 mission and again did not result in damage to the cluster, however, this event occurred late in the engine burn with no consequence to the engine involved and the engine shut down at its programmed time.

The failure events included in the study consider all SSME history and has not been filtered. Since the major consideration is to determine the probability of cluster failure given an engine failure has occurred, all of the SSME experience is considered. Thus, engine configuration, test objectives, power level, subsequent hardware redesigns, etc., are considered irrelevant. The object of this study is not to determine whether the SSME will fail, but, given that one has failed, to determine the probability of an entire cluster failure.

<u>Failure</u> Criteria - Not all of the 36 major incidents are applicable to this study. Since the study involves failures which could potentially affect or data ge other engines of the cluster an appropriate screening criteria is required in order to determine which of the major incidents in the database are applicable. The criteria used to develop the correlation of failures must consider only those events which either directly damage the cluster due to shrapnel, for example, or which indirectly result in cluster failure by disrupting the fuel flow to all engines.

<sup>+</sup> During the course of this study i descrepancy in the definition of "correlation factor" was discovered between the propolision system developers and the ultimate later h vehicle users (here the US Air Force). The propulsion system developers limit correlated failures only to catastrophic engine failures which would propagate to a cluster as in discussed in this section. To the user <u>any</u> failure which causes loss of more than a single engine whether via catastrophic failure, unscheduled shut down, loss of facil supply, improper thrust vectoring, etc. so that the pavload to orbit capability is icoparadized is a correlated failure. In this way, catastrophic engine failures which propagate are only a subset, albeit an important one of all correlated failures.

The following criteria were used to determine which of the major incidents should be considered applicable for this study:

<u>Uncontrolled SSME Shutdown</u> - The event occurred in such a way that the SSME controller was not in control of the shutdown sequence. That is, the failure mode is one which can not be or is not redline protected; or even though redline protection exists and may have been activated, the action of the controller is insufficient or is not fast enough to maintain control of the event.

<u>Uncontained Hardware Failure</u> - The failure of an engine component results in uncontained damage or damage propagation to other major components such as in the case of an uncontrolled oxygen fire or in the event of an explosion in which debris and shrapnel cause subsequent hardware failures. Of primary concern to the surrounding engines of the cluster is breach of the engine pressure boundary and the release of hot gas, fire or shrapnel.

Retirement of an Engine from Further Testing - Due to the limitations in some of the failure descriptions additional data is required to make a judgement as to the applicability of an event. One readily available piece of information is the subsequent disposition of an engine following an event. Retirement of an engine from the test program is generally a good indication that the damage to the engine resulting from the incident was severe enough to preclude use of the hardware in the future. It is recognized, however, that this is not a definitive indicator of severe engine damage since engines are retired as a function of their firing exposure as well as according to damage resulting from testing.

The above criteria are thus used to determine if a major incident should be considered an applicable failure to consider in developing the correlation of failure factor. Once the event is judged applicable a final criteria is used to determine if there is the potential for damage to the engine cluster.

Damage to Surrounding Hardware - Only in the flight configuration and in the three engine cluster static firing is direct indication of damage to an adjacent engine available. Thus, for single engine test firings an indirect indication of propagation of the failure to adjacent engines is damage to surrounding hardware, particularly the test stand itself. The extent of damage to the test stand is generally available and provides a good indication of the severity of the failure.

Due to the limited data available at the time of this study, for incidents in which the available failure description is not sufficient to determine the extent of damage to the surrounding hardware one available piece of data is the test stand down time following an event. Note that a long down time following an event is not necessarily an indication of damage to the test stand, but may indicate a lack of available test hardware, schedule considera lons, ongoing failure investigation, or the installation of the next test engine. However, a short down time following an event is a definite indication of little or no damage to the test stand.

If essentially no damage to surrounding hardware resulted from the incident then propagation to the cluster is not considered likely. If damage was done to the surrounding hardware or the test stand the severity of the event is considered and a judgement is made as to whether 'he event would propagate to the cluster. Events in which the effect on adjacent engines is not clear are ranked as <u>not</u> propagating to the cluster.

Application of this criteria thus provides a framework withi.: which to judge the 36 major incidents as to whether they are applicable to this study. Given that a failure is considered applicable for final consideration, and based on the severity of the post event damage, it is ranked as to whether the event would propagate to a cluster failure.

### SSME FAILURE SUMMARY

There are a total of 36 major incidents in the SSME database which were evaluated for the purposes of this study. Of these, 18 are considered to be applicable to this study in that they meet the criteria described previously. They are indicated in the failure summaries by an asterik (\*) following the test number. Of these 3 major incidents are considered failures which would have propagated to adjacent hardware and would result in failure of the entire cluster. These are indicated by an additional asterik (\*\*).

Table 1 summarizes all 36 of the major incidents considered in this study. In addition to providing information about the event, such as test number, test date, engine number, configuration, the table details the results of implementing the criteria evaluation.

### SSME MAJOR INCIDENT DESCRIPTIONS

The SSME major incidents are discussed chronologically in the following paragraphs. The event is described and the rationale for its use in developing the correlation of failure factor is discussed.

<u>Test 901-110</u><sup>\*</sup> - During test 901-110 (UCR A005353) rubbing in the HPOTP of engine 0003 caused failure of the primary lox seal and an uncontained engine fire. The redline cut was set by a HPOTP overspeed. This failure resulted in an increase of the intermediate seal purge pressure, revised redlines, and a design change from a lift-off seal to a labyrinth seal design.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 901-133</u> - Test 901-133 (UCR A005072) experienced a burn-through of the FPB wall during testing of engine 0004. The test was cut by an observer. This failure resulted in uncontrolled engine shutdown and damage to the engine. The engine survived this event and was used for later testing. Since the engine was not severely damaged and there is no indication of test stand damage (operational again in 6 days) this failure is not considered applicable to the study.

<u>Test 901-136</u><sup>\*</sup> - A failure of engine 0004 HPOTP turbine end bearings occurred during test 901-136 (UCR A005350) which resulted in an uncontained engine fire. The test was cut by an observer. The failure resulted in design changes to heavy duty 209 series bearings, improved bearing mounts and modifications to the coolant circuit orifice.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 902-095</u> - During test 902-095 of engine 0002 (UCR  $\Delta$ 008624) a leading edge airfoil crack resulted in blade failure, however, the engine damage was contained. The redline for the test cut was from the HPOTP radial accelerometer. Design and process changes have been implemented to increase blade life.

This failure resulted in uncontrolled engine shutdown, however, damage to the engine was contained. The engine survived this event and was used for later testing. There is no indication of damage to the test stand (operational within 11 days) in the available decumentation. This failure is not considered applicable to this study.

<u>Test 901-147</u>\* - HPFTP turbine blade failure of engine 0103 during test 901-147 (UCR A005094) resulted in a rapid power loss, reduced fuel flow and LOX rich operation of the engine. The test was cut by the HPOTP radial accelerometer redline. As a result, HPFTP turbine blade and damper redesigns were initiated.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand (operational within 11 days) in the available decumentation this failure would not have propagated to an engine cluster failure.

Test 901-173\* - Main injector lox post failure, cut off by HPFTP turbine discharge temperature.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 901-183</u> - Main injector lox post failure occurred during test 901-183 (UCR A018710) of engine 0002. Cutoff was by the HPFTP turbine radial accelerometer. The failure resulted in the incorporation of lox post flow shields.

This failure resulted in uncontrolled engine shutdown, however, damage to the engine was contained. The engine survived this event and was used for later testing. There is no indication of damage to the test stand in the available documentation. This failure is not considered applicable to this study.

<u>Test 902-112</u> - During test 902-112 (UCR A019208) of engine 0101 on June 10, 1978 a blockage of the fuel supply resulted in a HPFTP turbine overspeed. The redline cut for the test was the HPFTP turbine speed.

This failure resulted in uncontrolled engine shutdown, however, damage to the engine was contained. The engine survived this event and was used for later testing. There is no indication of damage to the test stand in the available documentation. This failure is not considered applicable to this study.

<u>Test 902-120</u> \* - During test 902-120 (UCR A005745) of engine 0101 structural failure and rubbing of a capacitor position instrumentation sensor in the HPOTP resulting in engine fire and uncontained engine damage. The test was cut by the PBP axial accelerometer redline. The capacitance device is no longer used.

This failure was uncontrolled resulting in destruction of the engine and damage to the test stand. Although the capacitance device is no longer used it does demonstrate the result of a HPOTP failure, subsequent fire and shrapnel. This failure is considered applicable to the study and although some damage was noted to the test stand it would not have propagated to a cluster failure.

<u>Test 902-132</u> - During test 902-132 (UCR A005780) of engine  $0006 \approx f$  accurred as the result of the MOV being clocked wrong. The test was cut by the low chamber product. The failure resulted in a guideline for the first test of a new engine to be only 1.5 seconds.

This failure resulted in uncontrolled engine shutdown, however, damage to the engine was contained. The engine survived this event and was used for later testing. There is no indication of damage to the test stand in the available documentation. This failure is not considered applicable to this study.

<u>Test 901-222</u> - During test 901-222 (UCR A017972) of engine 0007 a failure occurred as a result of undetected internal HEX damage caused during arc welding which resulted in an engine fire. HEX coil leakage resulted in an uncontained engine fire and severe damage. The test was cut by the HEX discharge pressure redline. The leak was caused by vall thinning of the HEX coil which occurred during welding and reaming operations. The failure resulted in increased HEX proof test requirements.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine. However, the engine survived this event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

<u>Test 901-225</u><sup>\*</sup> - During test 901-225 (UCR A01816) of engine 2001 flow induced fretting of the MOV sleeve resulted in autoignition, fire and explosion. The test was cut by the HPFTP turbine discharge temperature redline. The incident resulted in several design modifications (ECP's 248, 258, 271) including a redesigned MOV inlet sleeve/scal area and the incorporation of a vibration redline.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 750-041</u>\* - During testing of engine 0201 on May 14, 1978, the steerhorn tube fractured due to high structural loading (UCR A006466). The test was cut by the HPFTP turbine discharge temperature redline. The failure resulted from structural fatigue associated with high strain accelerations attributed to exhaust gas flow shock phenomena during start and cutoff transients causing failure of the flight nozzle steerhorn fuel distribution manifold. The failure resulted in fuel starvation and loss of mixture ratio control. Engine damage as a result of the high temperature was extensive and included the HPFTP, HPOTP, nozzle, main injector and the high pressure fuel distribution manifold steerhorn damage. The failure resulted in redesign of the feedline assembly and nickel plating of steerhorn tees.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Static Firing 6-01</u> - During Static Firing 6-01 (UCR A009437) high cycle fatigue resulted in the failure of engine 2002 MFV housing, fuel leakage and fire. The test was cut by the HPFTP turbine discharge temperature redline. The MFV housing crack extended from the cap flange to the outlet flange. The failure resulted in housing design modifications (ECR 09738). Rework housing cam bearing cutout to reduce stress concentration.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine during a three engine cluster firing. The failure resulted in fuel leakage and fire during the ground test. In flight, the chance of fire is a function of the available oxygen which is altitude dependent. There is no indication of significant damage to the other engines or to the test stand. The engine survived this event and was used for later testing. Damage to the engine was not significant and this event is not considered applicable to the study.

<u>Static Firing 6-03</u>\* - Testing of engine 0006 (engine position 3) during a cluster firing on November 4, 1979, resulted in a nozzle steerhorn rupture (UCR A010997). The test was cut by the HPOTP intermediate seal purge pressure redline. The failure was traced to use of an incorrect weld filler wire during fabrication. The failure resulted in the implementation of stringent weld wire audits. Added nickel plating to tee weld joints and redesigned to incorporate steam loop.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine during a three engine cluster firing. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the adjacent engines or to the test stand in the available documentation this failure did not propagate to an engine cluster failure.

<u>Test 902-198</u>\* - Main injector lox post failure resulted during test 902-198 of engine 2004. Cutoff was by the HPOTP turbine discharge temperature redline. The failure resulted in a change from the existing injectors to Haynes 188 lox post tips in rows 10 through 13. New injectors have all Haynes 188 lox posts.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 901-284</u>\* - During test 901-284 (UCR A015786) of engine 0010 a malfunctioning MCC chamber pressure lee jet caused the controller to lower the HPOTP output and resulted in HPOTP fire and external damage. The test was cut by HPOTP accelerometer redlines. The failure resulted in installation of a positive retainer in Pc port flange to prevent lee jet from backing out.

This failure was uncontrolled resulting in destruction of the engine and damage to the test stand. Although redesigns have been implemented this failure does demonstrate the result of a HPOTP failure, subsequent fire and shrapnel. This failure is considered applicable to the study and although some damage to the test stand was noted, it would not have propagated to a cluster failure.

<u>Static Firing 10-01</u> - During Static Firing 10-01 (UCR A015391) of engine 0006 a burn-through of the FPB liner and housing occurred. The test was cut by an observer. The failure resulted in the addition of a molybdenum insulator and new divergent ring liner.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine during a three engine cluster firing. The failure resulted in external leakage of hot gas from the FPB burn through. There is no indication of significant damage to the other engines or to the test stand. The engine survived this event and was used for later testing. Damage to the engine was not significant and this event is not considered applicable to the study.

<u>Test 901-307</u><sup>\*</sup> - During test 901-307 of engine 0009 a failure occurred in which the FPB injector experienced a burn-through. This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 750-140</u> - Main injector lox post failure resulted during test 750-140 of engine 0110. This failure resulted in a controlled engine shutdown and contained engine damage. The engine survived this event and was used for later testing. Thus, this failure is not considered applicable to the study since it resulted in a controlled engine shutdown and minor damage.

<u>Test 901-331</u><sup>\*</sup> - During testing of engine 2108 on July 15, 1981, injector post and engine damage was caused by material failure of the lox posts (UCR A013786). The test was cut by the HPOTP turbine discharge temperature redline. The failure resulted in the application of new materials for the lox posts and the addition of flow shields.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 750-148</u> - Main injector lox post failure resulted during test 750-148 (UCR A016031) of engine 0110. Cutoff was by the HPOTP turbine discharge temperature redline. The failure resulted in the implementation of all Haynes 188 lox posts and extended flow shields.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine. However, the engine survived this event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

Test 902-249\* - The HPFTP inlet volute of engine 0204 failed during test 902-249 (UCR A018288) as a result of non-standard fuel preburner injector modifications which produced a hot FPB core. A group of plugged FPB LOX posts created a hot spot and delamination of the Ni/Rene first stage blade tip seal, resulting in blade failure, shrapnel and inlet volute rupture. The test was cut by the HPFTP radial accelerometer redline. The resulting fire destroyed both turbines, the powerhead, MCC and nozzle. This failure resulted in a design change to all Rene blade tip seals and preburner modification restrictions to preclude a "hot core."

This failure was uncontrolled resulting in destruction of the engine and damage to the test stand. Although fixes have been implemented this failure does demonstrate the result of turbine blade failure and subsequent fire and shrapich i has failure is considered applicable to the study and although some damage to the test stand was noted, it would not have propagated to a cluster failure.

<u>Test 901-340</u> - A HPFTP turbine discharge sheet metal failure of weld 56 during test 901-340 (UCR A018305) of engine 0107 caused turbine flow blockage and resulted in contained turbopump damage. The test was cut by exceeding the HPFTP turbine discharge temperature redline. The failure resulted in weld prep redesign to achieve 100% penetration and the inclusion of x-ray inspection where accessible.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine. However, the engine survived dus event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

<u>Test 750-160</u>\* - A blockage of the fuel supply as a result of ice formation occurred during test 750-160 (UCR A016045) of engine 0110 which burned both turbines, HGM, main injector, MCC and nozzle. The test was cut by the HPFTP turbine discharge temperature redline. The failure resulted in revised engine drying procedures to remove all water following EDM operations.

This failure resulted in uncentrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 901-364</u>\*\* - A new redesigned Kaiser cap nut allowed hot gas leakage into the coolant circuit during test 901-364 (UCR A006810) of engine 2013 which resulted in bearing failure, uncontained engine damage and complete destruction of the engine. The failure produced significant shrapnel and test stand damage with the engine ultimately separating from the test stand. A redline cut was set by the PBP radial accelerometer. The redesigned nut was tested no further and all engines continue to use the original design.

This failure was uncontrolled resulting in destruction of the engine and damage to the test stand. Although this hardware configuration is no longer in use it does demonstrate the result of a loss or disruption of coolant flow to the turbomachinery. This failure is considered applicable to the study and would have propagated to a cluster failure.

<u>Test 750-165</u> - During test 750-165 of engine 0107 the OPOV experienced seal erosion. The test continued for the programmed duration. This failure resulted in a controlled engine shutdown and contained engine damage. The engine survived this event and was used for later testing. Thus, this failure is not considered applicable to the study since it resulted in a controlled engine shutdown and minor damage.

Test 750-168 - During test 750-168 of engine 0107 ASI blowback caused post cut-off OPOV ball seal leakage. Inspection revealed the seal was cracked and croded. The test conditioned through the programmed duration. The solution was sequence and purge requirements were revised.

The follower resulted in a controlled engine shudown and contained engine damage. The engine was retired following this event. Thus, the failure is not considered applicable to the study since it resulted in a controlled engine shudown as 5 mean damage.

<u>Test 750-175</u>\*\* - The HPO duct of engine 2208 was modified with the installation of an ultrasonic flow meter. During test 750-175 (UCR A011506) a failure resulted in HPOTP overspeed to 44,000 rpm (nominal 27,300 rpm) causing disc rupture, pump fire, shrapped and extensive engine damage. The test was cut by the PBP accelerometer redline. The failure occurred at the brazed joint between the prototype ultrasonic flowmeter and the high pressure exidizer turbopump discharge duct and resulted in destruction of the HPO IP, the HGM and the controller. Further use of ultrasonic flow meter on HPO duct was eliminated.

This failure was uncontrolled resulting in destruction of the engine and damage to the test stand. Although this hardware configuration is no longer in use it does demonstrate the result of a loss of oxidizer flow and subsequent HPOTP turbine overspeed, lox fire and shrapnel. This failure is considered applicable to the study and would have propagated to a cluster failure.

<u>STS-11</u> - One major incident actually occurred in flight during STS-11 and was obviously not catastrophic. During the flight the ASI chamber of engine 2015 experienced erosion due to a drill chip lodged in an ASI orifice. Engine cut-off was by programmed duration. The failure resulted in the addition of an ASI fuel filter to the supply line.

The engine burn continued for the programmed duration. This failure resulted in a controlled engine shutdown and contained engine damage. Although there was damage to the engine itself, there was no damage to the adjacent engines. The engine survived this event and was used for later testing. Thus, this failure is not considered applicable to the study since it resulted in a controlled engine shutdown and minor damage.

<u>Test 901-436</u><sup>\*</sup> - A hydrogen leak during test 901-436 (UCR A013338) of engine 0108 overpressurized the HPFTP coolant cavity and resulted in a coolant liner failure and major engine damage, destroying both turbines, the powerhead, MCC and nozzle. A redline cut was issued due to high HPFTP turbine discharge temperature. Design changes were incorporated to decrease hot gas leakage into the coolant circuit, a coolant liner pressure redline was implemented and inspection requirements were increased on the coolant liner close-out weld.

This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 901-468</u> - During test 901-468 (UCR A014585) of engine 0207 a stress concentration at the welded boss caused the FPB manifold to crack resulting in fire and major engine damage. This failure resulted in uncontrolled engine shutdown and uncontained engine damage. The engine was retired following this event. Thus, this failure is considered applicable to the study. Since there is no indication of significant damage to the test stand in the available documentation this failure would not have propagated to an engine cluster failure.

<u>Test 750-259</u><sup>\*\*</sup> - A failure of the MCC outlet manifold weld occurred during test 750-259 (UCR A015713) of engine 2308 and resulted in complete engine destruction. The failure resulted in shrapnel and test stand damage with the engine ultimately separating from the test stand. The test was cut by the HPFTP accelerometer and turbine discharge temperature redlines. Failure investigation determined that the MCC outlet assembly had ruptured due to fatigue or undetected flaws. The failure resulted in improved inspection of the assembly, redesign of the outlet neck and splitter and implementation of life limitations on other MCC's.

This failure resulted in uncontrolled engine shutdown, destruction of the engine and significant damage to the test stand. This failure is considered applicable to the study and would have propagated to an engine cluster failure.

<u>Test 750-285</u> - A Class I leak was experienced during test 750-285 at the number 8 feedline. Engine 0210 (May 21, 1987) experienced a feedline crack at the saddle bracket stop weld. The test was cut by a facility ambient air thermocouple. The failure resulted in improved feedline/saddle bracket and weld interference inspections.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine. However, the engine survived this event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

Test 902-427 - During testing of engine 2106 on June 26, 1987 at the NSTL A-2 test stand the low

pressure fuel pump discharge duct experienced a corrosion induced leak and subsequent external hydrogen fire. The test was cut by an ambient powerhead temperature redline. To preclude the possibility of corrosion induced failures, flight engines will use low pressure fuel turbopump discharge ducts with low calendar life and/or hotfire time (DAR 2074). Subsequent flight engines will use corrosion protected low pressure fuel turbopump discharge ducts (ECP 977).

This failure resulted in uncontrolled engine shutdown, however the damage to the engine was contained. The engine survived this event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

<u>Test 902-428</u> - During test 902-428 of engine 2106 a crack in the OPB interpropellant plate resulted in the formation and build up of ice, blocking the fuel supply which altered the OPB exhaust flow distribution and burned through the liner causing faceplate erosion and HPOTP turbine end damage. The test was cut by a facility redline. The failure was caused by cracks in the interpropellant plate-to-element braze joints. The cracks allowed propellant mixing and caused ice contamination to form in fuel manifold. The failure was determined to be the result of poor braze joints made during fabrication. Flight engines are cleared by a review of the manufacturing braze joint records.

This failure resulted in uncontrolled engine shutdown and uncontained damage to the engine. However, the engine survived this event and was used for later testing. There is no indication of significant damage to the engine in the available documentation so that this failure is not considered applicable to this study.

### ANALYSIS

The results of applying the criteria to the SSME major incidents database results in a total of 18 applicable failures, of which 3 are considered to propagate to a cluster failure.

The mean is then computed by

$$X = 3/18 = 0.167$$

Due to the small sample size the F distribution is assumed in order to develop the confidence interval for this case. For a 95% confidence interval the results of applying the F distribution are

0.036 < X < 0.414

Thus, with a 95% confidence interval the probability that a failure will propagate to the adjacent engines in the cluster is between 4% and 41%, given that an uncontrolled engine failure occurs.

### CONCLUSIONS

In the development of future launch vehicles the potential benefit of engine out capabilities must be weighed against the risks that if an engine fails in an uncontrolled manner it will result in the loss of the entire engine cluster. This study evaluated the SSME which is flown in a three engine cluster. No uncontrolled SSME failures have occurred in flight. Only a limited amount of ground testing has actually been done in a three engine cluster and although failures have occurred none have propagated to involve the entire cluster.

However, the test data evaluated here indicates there is a reasonable probability, approximately 17%, that an uncontrolled SSME failure will propagate to the adjacent engines given that an uncontrolled failure occurs. The confidence interval is between 4% and 41% that a failure will propagate to the cluster with a 95% confidence level.

# TABLE A1: SSME CORRELATION OF FAILURE FACTOR

r

1

51616

				:	I			Consid	lered by this	Study
			1	Program	Power	Level Exposure	(%)			
Test/Flt	4		Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per lest	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(38C)	(28C)	(20S)	(580)	(S8C)	Failures	Incidents	Failures
901001	19-May-75	0001	0.00	0	0.00	0.00	0.00			
901002	22-May-75	0001	1.00	-	0.00	0.00	0.00			
901003	2-Jun-75	0001	1.50	e	0.00	0,00	0.00			
901004	6-Jun-75	0001	0,80	e	0.00	0.00	0.00			
901005	12-Jun-75	0001	0.80	4	0.00	0.00	0.00			
901006	14-Jun-75	0001	1.00	5	0.00	0.00	0.00			
901007	23-Jun-75	0001	1.00	9	0.00	0.00	0.00			
901008	30-Jun-75	0001	0.50	7	0.00	0.00	0.00			
901009	8-Jul-75	0001	1.40	8	0.00	0.00	0.00			
901010	17-Jul-75	0001	1.60	10	0.00	0.00	0.00			
901011	8-Aug-75	0001	1.00	11	00.00	0.00	0.00			
901012	29-Aug-75	0001	1.00	12	0.00	0.00	0.00			
901013	4-Sep-75	0001	1.40	13	0.00	0.00	0.00			
901014	10-Sep-75	0001	1.50	15	0.00	0.00	0.00			
901015	2-Oct-75	0001	1.69	16	0.00	0.00	0.00			
901016	10-Oct-75	0001	1.84	18	0.00	0.00	0.00			
901017	26-0ct-75	0001	1.70	20	0.00	0.00	0.00			
901018	29-0c1-75	0001	1.95	22	0.00	0.00	0.00			
901019	31-Oct-75	0001	2.15	24	0.00	0.00	0.00			
901020	3-Nov-75	0001	2.35	26	0.00	0.00	00 0			
901021	4 - Nov - 75	0001	2.55	29	0.00	00.00	00.00			
901022	7-Nov-75	0001	2.76	31	00.00	0.00	0.00			
901023	12.Nov.75	0001	2.99	34	0.00	0.00	0.00			
901024	14-Dec-75	0001	2.35	37	0.00	0.00	0.00			
901025	22-Dec-75	0001	0.90	38	0.00	00.00	0.00			
901026	23-Dec-75	0001	2.35	40	0.00	0.00	0.00			
901027	30-Dec-75	0001	1.90	42	0.00	0.00	0.00			
901028	3-Jan-76	0001	1.74	44	0.00	0.00	0.00			

SSME CHRONOLOGICAL EXPERIENCE

					00			Consid	dered by this	Study
TwenEll			of card	Evera	100 103	104 109	( \% )			
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Applicable Catastrophic
			(sec)	(sec)	(sec)	(sec)	(S8C)	Failures	Incidents	Failures
901029	7-Jan-76	1000	1.93	46	0.00	0 00	0,00			
901030	13-Jan-76	0001	2.35	48	0.00	00.00	0.00			
901031	15-Jan-76	0001	2.73	51	0.00	0.00	0.00			
901032	16-Jan-76	0001	2.76	53	0.00	0.00	0.00			
901033	19-Jan-76	0001	2.86	56	0.00	0.00	0.00			
901034	21-Jan-76	0001	2.35	59	0.00	0.00	0.00			
901035	24-Jan-76	0001	3.16	62	0.00	0.00	0.00			
901036	27-Jan-76	0001	3.11	65	0.00	0.00	0.00			
901037	29-Jan-76	0001	3.36	68	0.00	0.00	0.00			
901038	5-Feb.76	0001	2.36	71	00°U	0.00	0.00			
60103 J	27-Feb-76	0001	2.88	74	0.00	00.00	0.00			
901040	2-Mar-76	0001	3.39	77	0.00	0.00	0.00			
901041	5-Mar-76	0001	3.84	81	000	0.00	0.00			
901042	8 - Mar - 76	0001	10.18	91	ر ا	0.00	0.00			
901043	10-Mar-76	0001	23.20	114	0.1 J	0.00	0,00			
901044	12-Mar-76	0001	45.18	159	0.00	0.00	0.00			
901045	23-Mar-76	0001	4.20	164	0,00	0.00	0.00			
902001	31-Mar-76	0002	1.54	165	00.00	0.00	0.00			
901046	2-Apr-76	0001	6.27	171	0.00	0.00	00'U			
901047	5-Apr-76	0001	1.92	173	0.00	0.00	0.00			
901048	7-Apr-76	0001	2.35	176	0.00	0.00	0.00			
901049	8-Apr-76	0001	2.36	178	0.00	0.00	0.00			
902002	19-Apr-76	0002	2.35	180	00.00	0.03	0.00			
901050	20-Apr-76	0001	4.20	185	0.00	0.00	0.00			
902033	21-Apr-76	0002	2.35	187	0.00	00.00	0.00			
901051	22-Apr-76	0001	10.32	197	0.00	0.00	0.00			
902004	24-Apr-76	0002	1.68	199	0.00	0.00	0.00			
901052	26-Apr-76	0001	7.34	206	0.00	0.00	0.00			
902005	28-Apr-76	0002	2.35	209	00.00	0.00	0.00			
902006	30-Apr-76	0002	2.35	211	0.00	0.00	00.00			
902007	3-May-76	0002	2.35	213	0.00	0.00	0.00			
901053	5-May-76	0001	6.52	220	0.00	0.00	0.00			
962008	5-May-76	0002	2.35	222	0.00	00.00	0.00			
901054	8-May-76	0001	7.31	229	0.00	0.00	00.00			

P;.ge 2

					University		1 /0/	Consid	dered by this	Study
Test/Flt			Duratn	Exprnc	100-103	1 04 - 1 08	109+		Acolicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(20C)	(sec)	Failures	Incidents	Failures
90200	15-May-76	0002	4.20	234	0.00	0.00	00.0			
901055	18-May-76	0001	6.29	240	0.00	0.00	0.00			
902010	19-May-76	0002	2.35	242	0.00	0.00	00.0			
901056	21-May-76	0001	7.27	250	0.00	0.00	0.00			
902011	22-May-76	0002	4.20	254	0.00	0.00	0.00			
902012	25-May-76	0002	8.20	262	0.00	0.00	0.00			
901057	26-May-76	0001	11.86	274	0,00	0.00	00.00			
902013	1-Jun-76	0002	11.10	285	0.00	0.00	0.00			
901038	3-Jun-76	0001	12.08	297	0.00	0.00	0.00			
901059	5-Jun-76	0001	3.97	301	0.00	0.00	0.00			
902014	7-Jun-76	0002	3.16	304	0.00	0.00	0.00			
901060	8-Jun-76	0001	2.35	307	0.00	0.00	00.00			
901061	10-Jun-76	0001	2.35	309	0.00	0.00	0.00			
902015	12-Jun-76	0002	3.27	312	0.00	0.00	0.00			
902016	15-Jun-76	0002	16.70	329	0.00	0.00	0.00			
901062	16-Jun-76	0001	16.40	345	0.00	0,00	0.00			
901063	18-Jun-76	0001	64.04	409	0.00	00.00	0.00			
901064	23-Jun-76	1000	1.81	411	00.00	0.00	0.00			
901065	7-741-76	0001	16.91	428	0.00	0.00	0.00			
901066	9 - Jul - 76	0001	4.24	432	0.00	0.00	0.00			
902017	9-Jul-76	0002	16.44	449	0.00	0.00	0.00			
902018	14-Jul-76	0002	22.07	471	0.00	0.00	0.00			
902019	23-Jul-76	0002	1.68	472	0.00	0.00	0.00			
901067	26-Jul-76	0001	41.45	514	0.00	0.00	0.00			
902020	27.Jul-76	0002	33.00	547	0.00	0.00	0.00			
902021	11-Aug-76	0002	3.73	551	0.00	00.00	6.00			
902022	13-Aug-76	0002	10.00	561	0.00	0.00	0.00			
902023	17-Aug-76	0002	3.43	564	00.00	0,00	0.00			
902024	18-Aug-76	0002	3.63	568	0.00	0.00	00.00			
902025	20-Aug-76	0002	1.08	569	0.00	0.00	0.00			
902026	21-Aug-76	0002	3.77	573	00.00	0.00	0.00			
901068	23-Aug-76	0003	0.30	573	00.00	0.00	0.00			
902027	24-Aug-76	0002	2.96	576	0.00	0.00	0.00			
901069	25.Aug-76	0003	1.64	577	0.00	0.00	00.00			

•

Page 3

SSME Chirchological Experience with Power Levels

-

•

-1

2

Study	Applicable	Catastropnic Failures																																		
dered by this :	Applicable	Incidents																																		
Consi	Catacteochio	Failures																																		
(º/º) Ө	109+	1991 (SHC)	00.0	0.00	0.00	0.00	0 <sup>°</sup> 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	00.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00
evel Exposure	104-108	(285)	00.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	00.00	00.00	0.00	00.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0 00	00.00	0.00
Power I	100-103	(200)	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Program	Exprnc	(20C)	582	584	592	610	634	680	697	720	769	854	881	908	911	914	944	1,094	1,394	1,420	2,070	2,104	2,132	2,152	2,172	2,175	2,178	2,182	2,193	2,195	2,198	2,202	2,205	2,213	2,225	2,258
	Duratn nar tast	(S8C)	4.20	2.35	8.00	18.30	24.03	46.00	17.15	22.19	49.53	85.00	26.52	27.00	2.96	3.05	30.00	150.00	300.00	26.52	650.00	33.88	28.09	20.03	20.00	2.35	2.99	4.23	11.72	1.08	3.71	4.20	2.33	8.20	11.72	33.20
	Fron	20	0003	0002	0002	0003	0002	0002	0003	0002	0003	0002	0003	0002	0003	0003	0002	0003	0003	0002	0003	0002	0003	0003	0003	0003	0003	0003	0003	0002	0002	0002	0002	0002	0003	0002
	ЧrU	2	27-Aug-76	30-Aug-76	31-Aug-76	1-Sep-76	10.Sep.76	12-Sep-76	13-Sep-76	15-Sep-76	16.Sep.76	18.Sep.76	20-Sep-76	22-Sep-76	23-Sep-76	24-Sep-76	25.Sep.76	26-Sep-76	28-Sep.76	29-Sep-76	30-Sep-76	1 - Oci - 76	27-0c1-76	2-Nov-76	10-Nov-76	20-Nov-76	24.Nov.76	27-Nov-76	30-Nov-76	5-Dec-76	8-Dec-76	11-Dec-76	14-Dec-76	15-Dec-76	16-Dec.76	17-Dec-76
	Test/Fit Number		901070	902028	902029	901071	902030	902031	901072	902032	901073	902033	901074	902034	901075	901076	902035	901077	901078	902036	90105	902037	901080	901081	901082	901083	901084	901085	901086	9E02ro	902039	902040	902041	902042	901087	902043

, L			I	Program	Power	Level Exposure	(%) e	Consid	dered by this	Study
umber	Date	Engn	Duratn per test	Exprnc cumulatv	100-103 per test	104-108 per lest	109+ Der test	Catastrophic	Applicable Maior	Appl
			(S8C)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Fail
01088	18-Dec-76	000	6.20	2,264	0.00	0.00	0:00			
02044	20-Dec-76	0002	19.60	2,284	0.00	0.00	0.00			
01089	27-Dec-76	0003	8.00	2,292	0.00	0.00	0.00			
1090	28-Dec-76	0003	17.69	2,309	0.00	0.00	0.00			
1001	31-Dec-76	0003	64.00	2,373	0.00	0.00	0.00			
1092	3-Jan-77	0003	21.50	2,395	0.00	0.00	0.00			
1093	5-Jan-77	0003	18.08	2,413	0.00	0.00	00.00			
1094	6-Jan-77	0003	15.65	2,429	0.00	0.00	0.00			
1095	7-Jan-77	0003	26.44	2,455	5.00	0.00	0.00			
1096	11-Jan-77	0003	28.63	2,484	9.60	0.00	0.00			
2045	12-Jan-77	0002	1.06	2,485	0.00	0.00	0.00			
2046	13-Jan-77	0002	405.01	2,890	0.00	0.00	0.00			
2047	17-Jan-77	0002	1.62	2,891	0.00	0.00	0.00			
2048	18-Jan-77	0002	4.23	2,896	0.00	0.00	0.00			
1097	28-Jan-77	0003	4.25	2,900	00.00	0.00	0.00			
1098	29-Jan-77	0003	64.12	2,964	21.12	0.00	0.00			
1099	31-Jan-77	0003	39.80	3,004	15.30	0.00	0.00			
2049	6-Feb-77	0002	3.23	3,007	0.00	0.00	0.00			
1100	11-Feb-77	0003	14.18	3,021	0.00	0.00	0.00			
1101	13-Feb-77	0003	4.31	3,026	0.00	0.00	0.00			
1102	14-Feb-77	0003	29.85	3,055	0.00	0.00	0.00			
1103	18-Feb-77	0003	23.01	3,078	3.51	0.00	0.00			
2050	20-Feb-77	0002	6.00	3,084	0.00	0.00	0.00			
2051	22-Feb-77	0002	2.37	3,087	0.00	0.00	00.00			
2052	23-Feb-77	0002	2.37	3,089	0.00	0.00	00.00			
2053	25-Feb-77	0002	2.35	3,091	0.00	0.00	00.00			
1104	26-Feb-77	0003	10.61	3,102	0.00	0.00	0.00			
12054	28-Feb-77	0002	11.42	3,114	0.00	0.00	0.00			
1105	3-Mar-77	0003	35.33	3,149	15.83	0.00	00.00			
1106	6-Mar-77	0003	86.43	3,235	0.00	0.00	0.00			
1107	9-Mar-77	0003	8.50	3,244	0.00	0.00	0.00			
1108	10-Mar-77	0003	29.49	3,273	4.99	0.00	00.00			
1109	12-Mar-77	0003	80.49	3,354	60.99	0.00	0.00			
2055	14-Mar-77	0002	2.35	3,356	0.00	0.00	0.00			

Page 5

SSME Chronological Experience with Power Levels

• •

Applicable Catastrophic Failures

91

.

.

-

.

•

•

Considered by this Study

٠

-

				Program	Ромег	Level Exposure	(%)			•
Test/Flt			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Cate	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(38C)	(S8C)	(380)	(38C)	Failures	Incidents	Failures
902056	16-Mar-77	0002	24.50	3,381	5.00	0.00	00,0			
902057	18-Mar-77	0002	22.01	3,403	0.00	0.00	0.00			
902058	21-Mar-77	0002	540.00	3,943	0.00	0.00	0.00			
901110	24-Mar-77	0003	74.07	4,017	0.00	0.00	0.00	×		
902059	27-Apr-77	0002	4.13	4,021	0.00	0.00	0.00			
902060	29-Apr-77	0002	10.01	4,031	0.00	0.00	0,00			
902061	2-May-77	0002	80.01	4,111	0.00	0.00	0.00			
902062	5-May-77	0002	29.93	4,141	0.00	0.00	0.00			
902063	10-May-77	0002	100.00	4,241	0.00	0.00	0.00			
902064	12-May-77	0002	104.02	4,345	0.00	0.00	0.00			
902065	14-May-77	0002	80.00	4,425	10.00	0.00	0.00			
901111	15-May-77	0004	2.35	4,427	0.00	0.00	0.00			
901112	17-May-77	0004	2.35	4,429	0.00	0.00	0.00			
901113	20-May-77	0004	17.34	4,447	0.00	0.00	0.00			
901114	23-May-77	0004	7.70	4,455	0.00	0.00	0.00			
901115	18-Jun-77	0004	100.01	4,555	0,00	0.00	0.00			
901116	21-Jun-77	0004	73.23	4,628	0,00	0.00	0.00			
901117	28-Jun-77	0004	0.54	4,628	0.00	0.00	0.00			
901118	29-Jun-77	0004	5.00	4,633	0.00	0.0.0	0.00			
901119	1-Jul-77	0004	31.74	4,665	0.00	0.00	0.00			
901120	2-Jul-77	0004	238.70	4,904	0.00	0.00	0.00			
901121	5-Jul-77	0004	4.65	4,908	00.00	0.00	00.00			
901122	6-Jul-77	0004	6,06	4,914	00.00	0.00	0.00			
901123	7-Jul-77	0004	149.48	5,064	00.00	0.00	0.00			
902066	3-Jul-77	0002	10.01	5,074	0,00	0.00	0.00			
902067	15-Jul-77	0002	30.00	5,104	0.00	0.00	00.00			
902068	18-Jul-77	0002	5.06	5,109	0.00	0.00	0.00			
902069	19-Jul-77	0002	35.01	5,144	9.00	0.00	00.00			
902070	21-Jul-77	0002	29.31	5,173	5.70	0.00	0.00			
901124	25-Jul-77	0004	6.64	5,180	00.00	0.00	0.00			
901125	27-Jul-77	0004	425.01	5,605	0.00	0.00	0.00			
901126	28-Jul-77	0004	415.00	6,020	10.00	0.00	0.00			
901127	30-Jul-77	0004	328.30	6,348	00.00	0.00	0.00			
901128	1 - Aug - 77	0004	424.94	6,773	0.00	0.00	0.00			

;				Program	Ромы	Level Exposure	(%) e		•	•
Test/Fit			Duratn	Exprnc	100-103	104-108	109+		Applicable	Apolicable
Number	Date	Engi	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(380)	(20C)	(sec)	(380)	Failures	Incidents	Failures
901129	4-Aug-77	0004	257.10	7,030	0.00	0.00	0.00			
901130	5-Aug-77	0004	425.00	7,455	0.00	0.00	0.00			
901131	8-Aug-77	0004	425.00	7,880	0.00	00.00	0.00			
902071	9-Aug-77	0002	13.40	7,894	0.00	0.00	0.00			
902372	10-Aug-77	0002	4.41	7,898	0.00	0.00	0.00			
902073	15-Aug-77	0002	155.50	8,054	0.00	0.00	0.00			
902074	18-Aug-77	0002	7.05	8,061	0.00	0.00	0.00			
902075	20-Aug-77	0002	21.71	8,082	0.00	0.00	0.00			
902076	24-Aug-77	0002	230.39	8,313	5.00	0.00	0,00			
901132	25-Aug-77	0004	30.00	8,343	0.00	0.00	0.00			
902077	26-Aug-77	0002	321.00	8,664	301.01	0.00	0.00			
901133	27-Aug-77	0004	48.21	8,712	10.00	0.00	0.00	×		
902078	1-Sep-77	0002	335.99	9,048	10.00	0.00	00.00			
901134	2-Sep-77	0004	76.80	9,125	45.80	0.00	0.00			
901135	6-Sep-77	0004	335.00	9,460	0.00	0.00	00.00			
901136	8-Sep-77	0004	300.22	9,760	100.00	0.00	0.00	×		
902079	36-Sep-77	0002	3.05	9,763	0.00	0.00	00.00			
902080	28-Sep-77	0002	9.05	9,772	00.00	0.00	0.00			
902081	1-0c1-77	0002	15.01	9,787	0.00	0.00	00.00			
902082	9-0ct-77	0002	40.00	9,827	0.00	0.00	0.00			
902083	11-0ct-77	0002	34.94	9,862	0.00	0.00	0.00			
902084	13-Oct-77	0002	85.00	9,947	0.00	0.00	0.00			
902085	17-0ct-77	0002	2.35	9,949	0.00	0.00	00.00			
902086	20-0c1-77	0002	2.35	9,952	0,00	0.00	0.00			
902087	26-Oct-77	0002	2.35	9,954	0.00	0.00	0.00			
902088	27-0ct-77	0002	1.73	9,956	0,00	0.00	00.00			
902089	28-Oct-77	0002	55.01	10,011	0.00	0.00	0.00			
901137	31-Oct-77	0103	19.32	10,030	0.00	0.00	00.00			
902090	1-Nov-77	0002	48.63	10,079	0.00	0.00	0.00			
902091	3-Nov-77	0002	100.00	10,179	0.00	0.00	0.00			
901138	4-Nov-77	0103	100.00	10,279	0.00	0.00	00.00			
902092	6-Nov-77	0002	229.97	10,509	4.00	0.00	0.00			
901139	7-Nov-77	0103	54.83	10,564	00.00	0.00	0.00			
902093	9-Nov-77	0002	364.16	10,928	0.00	0.00	0.00			

Considered by this Study

SSME Chronological Experience with Power Levels

Page 7

\_

93

Considered by this Study

				Program	Power	I.evel Exposure	(%)			
Test/Fit			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulaty	per test	per test	per test	Catastrophic	Major	Catastrophic
			sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
901140	10-Nov-77	0103	100.00	11,028	0.00	0.00	0.00			
901141	11-Nov-77	0103	400.00	11,428	0.00	0.00	0.00			
901142	13-Nov-77	0103	400.00	11,828	0.00	00.00	0.00			
902094	14-Nov-77	0002	200.00	12,028	0.00	0.00	0.00			
902095	17-Nov-7	0002	51.09	12,079	0.00	0.00	0.00			
901143	21-Nov-7	0103	100.00	12,179	0.00	0.00	0.00			
901144	23-Nov-77	0103	400.00	12,579	0.00	00.00	0,00			
901145	26-Nov-77	0103	350.00	12,929	0.00	0.00	0.00			
902096	28-Nov-77	0002	91.04	13,020	0.00	00.00	0.00			
901146	29-Nov-77	0103	400.00	13,420	0.00	00.00	00.00			
901147	1-Dec-77	0103	31.36	13,451	0.00	0.00	0.00			
901148	12-Dec-77	0002	2.35	13,454	0.00	0.00	0.00			
901149	13-Dec-77	0002	10.01	13,464	0.00	0.00	00.00			
901150	15-Dec-77	0002	9.83	13,473	0.00	0.00	0.00			
901151	17-Dec-77	0002	9.00	13,482	0.00	00.00	00.00			
901152	19-Dec-77	0002	9.00	13,491	0.00	00.00	00 0			
901153	20-Dec-77	0002	9.00	13,500	0.00	00.00	00.00			
901154	22-Dec-77	0002	8.00	13,508	0.00	0.00	0.00			
901155	4-Jan-78	0002	12.00	13,520	0.00	0.00	00.00			
901156	5-Jan-78	0005	100.00	13,620	<b>C</b> 1, 5	0.00	00.00			
901157	9-Jan-78	0002	100.00	13,720	0.0	0.00	00.00			
902097	17-Jan-78	2001	49.01	13,769	5.00	00.00	00.00			
902098	25-Jan-78	2001	71.00	13,840	0.00	0.00	00.00			
902099	30-Jan-74	2002	60.00	13,900	00.00	0.00	00.00			
902100	2-Feb-75	2002	2.89	13,903	0.00	0.00	00.00			
901158	8-Feb-78	0002	100.00	14,003	0.00	0.00	00.00			
902101	9-Feb-78	2002	26.64	14,030	00.00	0.00	00.00			
901159	10-Feb-78	0002	96.33	14,126	00.00	00.00	00.00			
901160	12-Feb-78	0002	4.04	14,130	0.00	00.00	0.00			
901161	14-Feb-7E	0002	4.25	14,135	0.05	0.00	00.00			
901162	15-Feb-7E	0002	11.32	14,146	0.92	0.00	00.00			
902102	15-Feb-78	2002	41.49	14,187	00.00	0.00	00.00			
901163	17-Feb-76	0002	3.57	14,191	0.00	0.00	00.00			
901164	21-Feb-78	0002	6.08	14,197	00.00	0.00	0.00			

Major Catas Incidents Fail	Incidents Fail																																			
Catastrophic Failures	Failures																																			
per test		(sec)	00.0	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	00.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0,00
	per test	(ces)	0.00	0,00	0.00	0.00	0.00	0.00	0,00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	per test	(SBC)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.00	0.00	0.00	0.00	0,00	0.00	0.00	0.00	0.00	0.00	114.94	27.89	515.97	0.00	90.08	0.00	0.00	0.00	0.00	0.00	3.88	0.30	0.00	0.00
vietumi v		(sec)	14,257	14,317	14,377	14,379	14,382	14,385	14,393	14,604	14,915	14,926	15,286	15,487	15,493	15,502	15,510	15,513	15,514	15,515	15,516	15,564	15,683	15,715	16,235	16,240	16,363	16,381	16,402	16,422	16,424	16,444	16,452	16,503	16,505	16,510
nor toot		(sec)	60.00	60.04	60.04	2.35	2.03	3.83	7.95	210.97	310.74	10.71	360.03	201.17	5.90	8.83	8.55	2.99	1.19	1.04	0.98	47.97	119.07	32.03	520.00	4.27	122.90	18.84	20.52	20.42	1.41	20.00	7.82	51.00	2.35	4.53
	Engn		2002	2003	2003	0002	0002	0002	0002	0002	0002	0002	0002	0002	0101	0101	0101	0101	2001	2003	2002	0005	0005	0005	0005	0005	0005	2001	2003	2002	0005	0005	0005	0005	0101	0101
	Date		22-Fub-78	5-Mar-78	8-Mar.78	13-Mar-78	15-Mar-78	17-Mar-78	20-Mar-78	21-Mar-78	25-Mar-78	27-Mar-78	29-Mar-78	31-Mar-78	13-Apr-78	16-Apr-78	19-Apr-78	21-Apr-78	21-Apr-78	21-Apr-78	21-Apr-78	4-May-78	6-May-78	8-May-78	10-May-78	13-May-78	16-Mey-78	19-Mey-78	19-May-78	19-May-78	28-May-78	30-May-78	2-Jı n-78	5-Jun-78	6-Jun-78	8-Jun-78
	Number		902103	902104	902105	901165	901166	901167	901168	901169	901170	901171	901172	901173	902106	902107	902108	902109	SF01-02A	SF01-02B	SF01-02C	901174	901175	901176	901177	901178	901179	SF02-01A	SF02-01B	SF02-01C	901180	901181	901182	901183	902110	902111

Page 9

.

SSME Chronological Experience with Power Levels

Applicable Catastrophic Failures

95

				Prooram	Power	l aval Evnosura	1701	Consi	dered by this	Study
Test/Flt			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(S8C)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
902112	10-Jun-78	0101	5.74	16,515	0.00	0.00	00.00			
SF03-01A	15-Jun-78	2001	41.82	16,557	0.00	0.00	0.00			
SF03-01B	15-Jun-78	2003	42.24	16,599	0.00	0.00	0.00			
SF03-01C	15-Jun-78	2002	42.63	16,642	0.00	0.00	0.00			
902113	22 Jun-78	0101	25.00	16,667	4.20	0.00	0.00			
902114	24-Jun-78	0101	281.03	16,948	0.83	0.00	0.00			
902115	27-Jun-78	0101	299.98	17,248	0.00	0.00	0.00			
902116	29-Jun-78	0101	10.85	17,259	0.00	0.00	0.00			
SF04-01A	7-Jul-78	2001	103.88	17,363	0.00	0.00	0.00			
SF04-01B	7-Jul-78	2003	93.70	17,456	0.00	0.00	0.00			
SF04-01C	7-Jul-78	2002	103.63	17,560	0.00	0.00	0.00			
902117	8.Jul-78	0101	6.08	17,566	0.00	0.00	0.00			
902118	10-Jul-78	0101	6.84	17,573	0.00	0.00	0.00			
901184	14-Jul-78	0005	30,00	17,603	6.00	0.00	0.00			
902119	14-Jul-78	0101	166.69	17.770	50.69	0.00	0.00			
902120	18-Jul-78	0101	41.81	17,811	21.01	0.00	0.00			
901185	12-Aug-78	0005	50.00	17,861	9.20	0.00	0.00			
90;186	13-Aug-78	0005	240.39	18,102	199.59	0.00	00.00			
901187	18-Aug-78	0005	150.00	18,252	103.00	0.00	0.00			
901188	20-Aug-78	0005	300.00	18,552	274.20	0.00	0.00			
902121	22-Aug-78	2002	7.16	18,559	0.00	0.00	0.00			
901189	23-Aug-78	0005	64.64	18,624	60.42	0.00	0.00			
902122	24-Aug-78	2002	300.00	18,924	257.00	0.00	0.00			
901190	26-Aug-78	0005	137.83	19,061	133.77	0.00	0.00			
902123	27-Aug-78	2002	100.00	19,161	57.00	0.00	0.00			
901191	28-Aug-78	0005	300.00	19,461	295.92	0.00	0.00			
902124	29-Aug-78	2002	266.82	19,728	223.82	0.00	0.00			
901192	30-Aug-78	0005	300.00	20,028	295.99	0.00	0.00			
902125	31-Aug-78	2002	72.02	20,100	29.02	0.00	0.00			
902126	1-Sep-78	2002	300.00	20,400	247.00	0.00	0.00			
901193	2-Sep-78	0005	300.00	20,700	295.88	0.00	0.00			
902127	5-Sep-78	2002	111.56	20,812	68.56	0.00	0.00			
901194	6-Sep-78	0005	310.11	21,122	306.05	0.00	0.00			
902128	6-Sep-78	2002	300.00	21,422	247.00	0.00	0.00			

Оањ	Fran	Duratn ner test	Program Exprnc	Power 100-103 Der test	Level Exposure 104-108 ner test	) (%) 109+ Der test	Consi Catastrophic	dered by this Applicable	Study Applicable
	Liga	per (sec)	cumutatv (sec)	per (sec) (sec)	per test (\$ec)	per test (sec)	catastropnic Failures	Major Incidents	Catastrophic Failures
	78 0005	520.00	21,942	515.92	0.00	·0.00			
12	78 2002	300.00	22,242	247.00	0.00	0.00			
17	8 0005	520.00	22,762	515.92	00.00	0.00			
۱ <u>۲</u>	8 0005	520.00	23,282	515.97	00.00	0.00			
ä	8 0005	520.00	23,802	515.91	0.00	0.00			
à	18 2002	301.50	24,103	258.50	0.00	0.00			
ď	8 0005	520.00	24,623	355.94	00.00	0.00			
à	18 0005	289.10	24,913	285.00	0.00	0.00			
ġ	8 2002	300.04	25,213	132.50	0.00	0.00			
à	78 0005	3.05	25,216	0.00	0.00	0.00			
ġ	8 0005	138.51	25,354	134.41	0.00	0.00			
de	78 0005	300.00	25,654	295.84	0.00	0.00			
1-1-1	78 0005	300.00	25,954	0.00	0.00	0.00			
0ct-7	78 0006	2.36	25,957	00.00	0.00	0.00			
0c1-7	78 0005	300.00	26,257	219.00	0.00	0.00			
Det-7	78 0005	300.00	26,557	0.00	0,00	0.00			
C-10	18 0005	2.35	26,559	0,00	0.00	00.00			
) - 1 - C	78 0005	4.88	26,564	0.00	0.00	0.00			
) c t - ]	78 0005	100.00	26,664	00.00	0;00	0.00			
C-1-C	78 0005	300.00	26,964	9.50	0.00	0.00			
Ct-1	78 2002	50.00	27,014	0.00	0.00	0.00			
Det-1	78 0005	520.00	27,534	0.00	0.00	0.00			
0ct-1	78 0005	300.00	27,834	199.00	00.00	0.00			
001-1	78 0005	1.30	27,835	0.00	0.00	00.00			
Det-1	78 0005	290.38	28,125	189.38	0.00	00.00			
001-	78 2002	100.00	28,225	0.00	0.00	0.00			
Det-1	78 0005	823.00	29,048	0.00	0.00	0.00			
0 10	78 0005	3.57	29,052	0.00	00.00	0.00			
- 70	78 2002	2.79	29,055	0.00	0.00	0.00			
- 70	78 0005	520.00	29,575	0.00	0.00	0.00			
-70	78 2002	285.00	29,860	226.50	0.00	0.00			
lov-	78 0201	2.35	29,862	0.00	0.00	0.00			
2	78 0005	520.00	30,382	0.00	0.00	0.00			
->0	78 2002	50.00	30,432	00.00	0.00	0.00			

.

SSME Chronological Experience with Power Levels

Page 11

٠

•

					ć	L		Consid	dered by this	Study
				rrogram	1'OWBL	t evel Exposure	(%)			
I 9SI/FII	ſ	1	Durain	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
901219	9-Nov-78	0005	520.00	30,952	0.00	0.00	0.00			
902138	9-Nov-78	2002	100.00	31,052	0.00	0.00	0.00			
750002	10-Nov-78	0201	4.00	31,056	0.00	00.00	0.00			
901220	11-Nov-78	0005	197.80	31,254	0.00	0.00	0.00			
902139	13-Nov-78	2002	200.00	31,454	0.00	00.00	0.00			
901221	15-Nov-78	0005	665.00	32,119	0.00	0.00	0.00			
902140	15-Nov-78	2002	200.00	32,319	19.00	0.00	0.00			
902141	17-Nov-78	2002	300.00	32,619	185.96	0.00	0,00			
750003	22-Nov-78	0201	15.00	32,634	0.00	0.00	0.00			
750004	29-Nov-78	0201	50.00	32,684	9.00	0.00	0.00			
902142	2-Dec-78	2002	2.71	32,687	0.00	0.00	0.00			
902143	3-Dec-78	2002	2.81	32,689	0.00	0.00	0.00			
902144	4-Dec-78	2002	36.29	32,726	29.02	0.00	0.00			
750005	5-Dec-78	0201	1.50	32,727	0.00	00.00	0.00			
901222	5-Dec-78	0007	4.35	32,732	0.00	0.00	0.00	×		
750006	7-Dec-78	0201	40.90	32,773	0.00	0.00	0.00			
902145	8-Dec-78	2002	68.61	32,841	35.65	0.00	0.00			
750007	9-Dec-78	0201	300.00	33,141	0.00	0.00	0.00			
902146	11-Dec-78	2002	520.00	33,661	427.00	0.00	0.00			
750008	13-Dec-78	0201	300.00	33,961	0.00	0.00	0.00			
902147	15-Dec-78	2002	260.16	34,221	256.16	00.00	0.00			
750009	16-Dec-78	0201	35.00	34,256	10.00	0.00	00.00			
901223	19-Dec-78	2001	1.61	34,258	0.00	0.00	0.00			
750010	20-Dec-78	0201	264.30	34,522	244.00	0.00	0.00			
901224	23-Dec-78	2001	60.01	34,582	56.03	0.00	0.00			
901225	27.Dec.78	2001	255.63	34,838	222.57	0.00	0.00	×		
750011	30-Jan-79	0201	1.40	34,839	0.00	0.00	0.00			
750012	2-Feb-79	0201	1.50	34,841	0.00	0.00	0.00			
750013	4-Feb-79	0201	25.00	34,866	9.50	0.00	0.00			
901226	5-Feb-79	2003	1.40	34,867	0.00	0.00	0.00			
750014	8-Feb-79	0201	1.50	34,869	0.00	0.00	0.00			
750015	10-Feb-79	0201	25.00	34,894	9.52	0.00	0.00			
750016	12.Feb.79	0201	300.00	35,194	0.00	0.00	0.00			
750017	24-Feb-79	0201	41.00	35,235	25.62	0.00	0.00			

Page 12

:

Page 13

Applicable Catastrophic Failures

study	Applicable	Catastrophic	Failures																																		
dered by this S	Applicable	Major	Incidents																																		
Consi		Catastrophic	Failures																																		×
1.00	109+	per test (	(sec)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	00.00	0.00	00.00	00.00	0.00	0.00	0.00	0.00	00.00	00.00	0.00	0.00	00.00	00.00	00.00	00.00	0.00	0.00	0.00	0.00	0.00	٥٥.0	00.00	00.00	0.00
Exposite	104-108	per test	(S8C)	0.00	00.0	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.0	0.00	0.00	0.00
Dower L	100-103	per test	(sec)	295.84	62.70	295.84	0.00	295.86	195.80	195.80	96.17	0.00	0.00	0.00	29.10	6.15	252.42	55.09	427.13	0.07	23.77	85.19	427.14	85.15	424.60	614.61	0.00	96.23	50.73	51.76	50.21	0.58	427.18	424.61	430.85	519.18	14.64
Prooram	Exprnc	cumulatv	(sec)	43,219	43,299	43,599	43,600	43,900	44,250	44,633	44,733	44,735	44,736	44,738	44,800	44,810	45,095	45,186	45,706	45,710	45,738	45,838	46,358	46,458	46,978	47,643	47,644	47,744	47,799	47,855	47,909	47,913	48,433	48,953	49,473	50,296	50.315
	Duratn	per test	(sec)	300.00	80.07	300.00	1.50	300.02	350.00	382.77	100.05	1.51	1.52	1.50	61.87	10.05	285.30	90.50	520.06	4.32	27.67	100.07	520.04	100.07	520.00	665.00	1.50	100.07	54.60	55.69	54.07	4.45	520.04	520.06	520,06	823.06	18.49
		Engn		0201	2005	0201	2007	0201	0201	0201	2007	2002	2003	0006	2007	2004	2007	2004	2007	0201	2004	2005	2005	2004	2004	2004	2006	2006	2002	2003	0000	2004	2006	2004	2004	2004	2002
		Date		21-Apr-79	24-Apr-79	25-Apr-79	26-Apr-79	27-Apr-79	30-Apr-79	2-May-79	2-May-79	4-May-79	4-May-79	4-May-79	5-May-79	7-May-79	10-May-79	10-May-79	12-May-79	14-May-79	22-May-79	23-May-79	26-May-79	31-May-79	2-Jun-79	8-Jun-79	9-Jun-79	12-Jun-79	12-Jun-79	12-Jun-79	12-Jun-79	13-Jun-79	16-Jun-79	21-Jun-79	25-Jun-79	27-Jun-79	2-Jul-79
	Test/Flt	Number		750036	902155	750037	901236	750038	750039	750040	901237	SF05-01A	SF05-01B	SF05-01C	901238	902156	901239	902157	901240	750041	902158	901241	901242	902159	902160	902161	901243	901244	SF05A-1A	SF05A-1B	SF05A-1C	902162	901245	902163	902164	902165	SF06-01A

			00.00	0.00	424.62	52,597	520.06	2004	1-0c1-79	902177
			0.00	0.00	89.21	52,077	93.23	0105	1-0c1-79	750050
			0.00	0.00	1.53	51,983	5.16	0105	29-Sep-79	750049
			0.00	0.00	30.93	51,978	49.97	0105	25-Sep-79	750048
			0.00	00.00	424.68	51,928	520.06	2004	22-Sep-79	902176
			0.00	0.00	6.00	51,408	10.43	0105	22-Sep-79	750047
			0.00	0.00	222.17	51,398	257.48	2004	20-Sep-79	902175
			0.00	0.00	0.00	51,140	1.50	0105	19-Sep-79	750046
			0.00	0.00	100.66	51,139	135.96	2004	17-Sep-79	902174
			0.00	0.00	64.71	51,003	100.00	0007	17-Sep-79	901256
			0.00	0.00	29.18	50,903	34.55	0007	15-Sep-79	901255
			0.00	0.00	0.00	50,868	1.82	2004	8-Sep-79	902173
			0.00	0.00	2.84	50,866	6.63	2004	6-Sep-79	902172
			0.00	00.00	96.23	50,860	100.05	0007	27-Aug-79	901254
			0.00	0.00	0.00	50,760	1.53	0007	22-Aug-79	901253
			0.00	0.00	6.16	50,758	10.00	0007	21-Aug-79	901252
			0.00	0.00	6.23	50,748	10.05	0007	18-Aug-79	901251
			0.00	0.00	45.96	50,738	56.04	2004	13-Aug-79	902171
			0.00	0.00	0.00	50,682	1.51	2004	11-Aug-79	902170
			0.00	0,00	2.65	50,681	6.48	0007	11-Aug-79	901250
			0.00	0.00	46.24	50,674	50.05	0002	4-Aug-79	901249
			0.00	0.00	0.00	50,624	1.57	0002	3-Aug-79	901248
			0.00	0.00	56.68	50,623	100.07	2004	31-Jul-79	902169
			0.00	0.00	34.68	50,522	50.04	2004	26-Jul-79	902168
			0.00	0.00	6.25	50,472	10.07	2004	24-Jul-79	902167
			0.00	0.00	0.00	50,462	1.54	2004	20-Jul-79	902166
			0.00	0.00	96.23	50,461	100.05	2007	16-Jul-79	901247
			0.00	0.00	0.00	50,361	3.73	2007	12-Jul-79	901246
			0.00	0.00	0.00	50,357	1.56	0002	12-Jul-79	750045
			0.00	0.00	0.00	50,355	1.30	0007	10-Jul-79	750044
			0.00	0.00	0.00	50,354	0.00	0001	9-Jul-79	750043
			0.00	0.00	0.00	50,354	00.00	0007	6-Jul-79	750042
			0,00	0.00	16.12	50,354	19.96	0006	2-Jul-79	SF06-01C
			0.00	0.00	15.49	50,334	19.36	2003	2-Jul-79	SF06-01B
Fai	Incidents	Failures	(sec)	(၁ፀ၄)	(S8C)	(sec)	(38C)			
Catas	Major	Catastrophic	per test	per test	per test	cumulatv	per test	Engn	Date	Number
Appl	Applicable		109+	104-108	100-103	Exprnc	Duratn			Test/Flt
(none		)	(%)	Level Exposure	Ромег	Program				
Study	dered by this	Consi								

Applicable Applicable Major Catastrophic Incidents Failures

SSME Chronological Experience with Power Levels

.

Considered by this Study

				Program	Ромөг	l evel Exposure	(%)			·
Test/Flt			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(38C)	(sec)	(sec)	Failures	Incidents	Failures
750051	6-0c1-79	0105	300.01	52,897	295.97	0.00	00:00			
901257	6-0ct-79	0008	1.50	52,898	0.00	0.00	0.00			
901258	10-0c1-79	0008	1.57	52,900	0.00	0.00	0.00			
902178	10-Oct-79	2004	10.00	52,910	6.12	0.00	00.00			
901259	11-0cl-79	0008	100.00	53,010	96.16	0.00	0.00			
902179	12-Oc1-79	2004	823.00	53,833	519.13	0,00	0.00			
750052	16-Oct-79	0105	96.13	53,929	92.24	0.00	0.00			
901260	18-Oct-79	0008	£20.00	54,449	424.68	0.00	0.00			
902180	20-051-79	2004	10.00	54,459	6.09	0.00	0.00			
750053	23-Oc1-79	0105	300.00	54,759	287.10	0.00	0.00			
750054	26-Oc1-79	0105	60.00	54,819	19.11	0.00	00.00			
901261	26-Oc1-79	0008	520.00	55,339	424.66	0.00	0.00			
902181	26-0c1-79	2004	665.02	56,004	314.64	0.00	0.00			
750055	1-Nov-79	0105	94.56	56,098	16.11	0.00	0.00			
750056	3-Nov-79	0105	1.50	56,100	0.00	0.00	0.00			
SF 06-03A	4-Nov-79	2002	9.72	56,110	5.88	0.00	0.00			
SF06-03B	4-Nov-79	2003	10.35	56,120	6.45	0.00	0.00			
3F06-03C	4-Nov-79	0006	8.69	56,129	4.81	0.00	0.00			
901262	24-Nov-79	0008	100.05	56,229	86.18	0.0,0	0.00			
750057	15-Dec-79	0007	1.50	56,230	0,00	0.00	0.00			
SF06-04A	17-Dec-79	0008	553.70	56,784	336.16	0.00	0.00			
SF06-04B	17-Dec-79	2003	508.75	57,293	336.04	0.00	0.00			
SF06-04C	17-Dec-79	0006	553.97	57,847	336.15	0.00	0.00			
750058	19-Dec-79	0007	350.00	58,197	116.12	0.00	0.00			
750059	27-Dec-79	0007	313.25	58,510	116.13	0.00	0.00			
750060	29-Dec-79	0007	300.00	58,810	296.14	0.00	0.00			
902182	9-Jan-80	2004	520.04	59,330	424.50	0.00	0.00			
750061	11-Jan-80	0007	300.00	59,630	:46.12	0.00	0.00			
750062	14-Jan-80	0007	300.00	59,930	236.12	0.00	0.00			
902183	14-Jan-80	2004	520.00	60,450	424.48	00.00	00.00			
902184	18-Jan-80	2004	520.00	60,970	424.42	00.00	0.00			
901263	22-Jan-80	6000	1.50	60,971	0.00	0.00	0.00			
901264	24-Jan-80	6000	1.50	60,973	0,00	0.00	00.00			
750063	25-Jan-80	0007	300.00	61,273	146.08	0.00	0.00			
   
   
   
   |  |  
   |   |   
  |   |  |   
  |  |   |   |   |  |  |   
   
   |   |  |  |   
   |  |  |   |  |  | 4   |   
   |
|--------------|---|--|--|--|---|--|--|---|--
--
--
--
---|--
--
--|---|--|---
--|--
--|---|---|---|--|--
--
---|---|--
--|---|--|--|---|--|--
---|---|
| Catastrophic | Failures  |  |  |  |   |  |  |   |  |   
   
   
   
   |  |  
   |   |   
  |   |  |   
  |  |   |   |   |  |  |   
   
   |   |  |  |   
   |  |  |   |  |  |   |   
   |
| Major        | Incidents   |  |  |  |   |  |  |   |  |   
   
   
   
   |  |  
   |   |   
  |   |  |   
  |  |   |   |   |  |  |   
   
   |   |  |  |   
   |  |  |   |  |  |   |   
   |
| Catastrophic | Failures  |  |  |  |   |  |  |   |  |   
   
   
   
   |  |  
   |   |   
  |   |  |   
  |  |   |   |   |  |  |   
   
   |   |  |  |   
   |  |  |   |  |  | •   |   
   |
| per test (   | (sec)   | 0.00   | 00.00  | 0.00   | 00.00   | 0.00   | 00.00  | 00.00   | 0.00   | 00.00   
   
   
   
   | 0.00   | 00.00  
   | 0.00  | 00.00   
  | 0.00  | 0.00   | 0.00  
  | 00.00  | 00.00   | 0.00  | 0.00  | 00.00  | 00.00  | 00.00   
   
   | 10.00   | 0.00   | 0.00   | 00.00   
   | 00.00  | 00.00  | 0.00  | 00.00  | 0.24   | 0.00  | 0.00  
   |
| per test     | (S3C)   | 0.00   | 0.00   | 0.00   | 0.00  | 0.00   | 0.00   | 0.00  | 0.00   | 0.00  
   
   
   
   | 0.00   | 0.00   
   | 0.00  | 0.00  
  | 0.00  | 0.00   | 0.00  
  | 0.00   | 0.00  | 0.00  | 0.00  | 0.00   | 00.00  | 25.00   
   
   | 10.00   | 0.00   | 0.00   | 0.00  
   | 0.00   | 0.00   | 0.00  | 0.00   | 0.50   | 0.00  | 0.00  
   |
| per test     | (S8C)   | 0.00   | 145.96   | 0.00   | 0.92  | 1.50   | 0.66   | 35.78   | 430.52   | 6.02  
   
   
   
   | 424.70   | 0.00   
   | 248.38  | 0.00  
  | 254.34  | 329.32   | 329.26  
  | 329.29   | 424.36  | 248.29  | 95.88   | 518.88   | 254.26   | 63.87   
   
   | 89.96   | 248.29   | 614.34   | 254.26  
   | 357.11   | 344.11   | 357.11  | 424.34   | 236.14   | 34.78   | 430.60  
   |
| cumulatv     | (sec)   | 61,274   | 61,574   | 61,576   | 61,581  | 61,586   | 61,591   | 61,630  | 62,150   | 62,160  
   
   
   
   | 62,680   | 62,682   
   | 62,982  | 62,985  
  | 63,285  | 63,839   | 64,362  
  | 64,917   | 65,437  | 65,737  | 65,837  | 66,660   | 66,960   | 67,070  
   
   | 67,195  | 67,495   | 68,161   | 68,461  
   | 69,000   | 69,539   | 70,079  | 70,599   | 70,840   | 71,140  | 71,660  
   |
| per test     | (sec)   |  | 300.00   |  |   | 0  | 4.61   | 39.62   | 520.00   | 10.00   
   
   
   
   | 520.00   | 1.50   
   | 300.00  | 2.85  
  | 300.00  | 554.30   | 523.43  
  | 554.82   | 520.00  | 300.00  | 100.00  | 823.08   | 300.00   | 110.04  
   
   | 125.06  | 300.04   | 665.03   | 300.00  
   | 539.38   | 539.48   | 539.61  | 519.90   | 241.04   | 300.00  | 520.00  
   |
| Engn         |   | 6000   | - U 0 0  | 6070   | 0008  | 2007   | 0006   | 6000  | 2004   | 2004  
   
   
   
   | 6000   | 0007   
   | 0007  | 6000  
  | 0007  | 0008   | 2003  
  | 0006   | 6000  | 0007  | 2004  | 6000   | 0007   | 2004  
   
   | 2004  | 0007   | 6000   | 0007  
   | 0008   | 2003   | 0000  | 6000   | 2004   | 0007  | 6000  
   |
| Date         |   | 25-Jan-80  | <b>31-Jan-80</b>   | 31.Jan-80  | 1-Feb-80  | 1-Feb-80   | 1-Feb-80   | 2-Feb-80  | 5.Feb-80   | 7.Feb.80  
   
   
   
   | 8-Feb-80   | 11-Feb-80  
   | 12-Feb-80   | 15-Feb-80   
  | 22-Feb-80   | 28-Feb-80  | 28-Feb-80   
  | 28-Feb-80  | 29-Feb-80   | 1-Mar-80  | 4-Mar-80  | 5-Mar-80   | 7-Mar-80   | 7-Mar-80  
   
   | 13-Mar-80   | 15-Mar-80  | 15-Mar-80  | 18-Mar-80   
   | 20-Mar-80  | 20-Mar-80  | 20-Mar-80   | 22-Mar-80  | 24-Mar-80  | 26-Mar-80   | 28-Mar-80   
   |
| Number       |   | 901265   | 750064   | 901266   | SF07-01A  | SF07-01B   | SF07-01C   | 901267  | 902185   | 902186  
   
   
   
   | 901268   | 750065   
   | 750066  | 901269  
  | 750067  | SF07-02A   | SF07-02B  
  | SF07-02C   | 901270  | 750068  | 902187  | 901271   | 750069   | 902188  
   
   | 902189  | 750070   | 901272   | 750071  
   | SF08-01A   | SF08-01B   | SF08-01C  | 901273   | 902190   | 750072  | 901274  
   |
|              | Number Date Engin per test per test per test per test catastrophic Major Catastrophic | Number Date Engn per test cumulativ per test per test catastrophic Major Catastrophic Major Catastrophic (sec) (sec) (sec) (sec) Failures Incidents Failures | Number Date Engn per test cumulativ per test per test per test Catastrophic Major Catastrophic<br>(sec) (sec) (sec) (sec) (sec) Failures Incidents Failures<br>901265 25-Jan-80 000950 61,274 0.00 0.00 0.00 | Number         Date         Engn         Per test         Cumulativ         Per test         Per | Number         Date         Engn         Per test         cumulatv         per test         per test         per test         catastrophic         Anjor         catastrophic           Number         Date         Engn         per test         cumulatv         per test         per test         per test         catastrophic         Major         catastrophic           901265         25-Jan-80         0009         1.50         61,574         0.00         0.00         0.00         0.00           750064         31-Jan-80         000 <sup>-</sup> 300.00         61,574         145.96         0.00         0.00         0.00         0.00           901266         31-Jan-80         00'09         1.576         0.00         0.00         0.00         0.00 | Number         Date         Engn         per test         cumulativ         per test         per test         catastrophic         Anjour         catastrophic           901265         25-Jan-80         0009         1.50         61,274         0.00         0.00         0.00         0.00         75005           901266         31-Jan-80         0009         1.57         145.96         0.00         0.00         0.00         0.00           750064         31-Jan-80         0007         300.00         61,574         145.96         0.00         0.00         0.00           901266         31-Jan-80         0009         1.576         0.00         0.00         0.00         0.00         0.00           901206         31-Jan-80         0008         1.576         0.00         0.00         0.00         0.00         0.00 | Number         Date         Engn         per test         cumulativ         per test         per test         catastrophic         Anjor         catastrophic           901265         25-Jan-80         0009         1.50         61,274         0.000         0.000         0.00         0.00         0.000           901266         31-Jan-80         0009         1.50         61,574         145.96         0.00         0.00         0.00         0.00           750064         31-Jan-80         0007         300.00         61,574         145.96         0.00         0.00         0.00         0.00           7500701A         1-Feb-80         0008         7.56         0.00         0.00         0.00         0.00         0.00           8F07-01B         1-Feb-80         2002         2.56         0.00         0.00         0.00         0.00 | Number         Date         Engn         per test         cumulativ         per test         catastrophic         Anjor         catastrophic           901265         25-Jan-80         0009         1.50         61,274         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           901265         25-Jan-80         0009         1.50         61,274         145.96         0.00         0.00         0.00         0.00         Catastrophic         Anjor         Catastrophic           750064         31-Jan-80         0007         300.00         61,574         145.96         0.00         0.00         0.00         0.00         0.00         Catastrophic         Failures         Incidents         Failures         Incidents         Failures           750064         31-Jan-80         0007         300.00         61,574         145.96         0.00         0 | Number         Date         Engn         per test         cumulativ         per test         cumulativ         per test         catastrophic         Major         Catastrophic           901265         25-Jan-80         0009         1.50         (5ec)         (5ec)         (5ec)         (sec)         failures         incidents         Failures           901265         25-Jan-80         0009         1.50         61,574         145.96         0.00         0.00         0.00         75006         731-Jan-80         0007         300.00         61,574         145.96         0.00         0.00         0.00         0.00         75006         731-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         0.00         75000         75000         75000 | Number         Date         Engn         per test         cumulativ         per test         per test         per test         catastrophic         Major         catastrophic           901265         25-Jan-80         0009         7.50         61,974         0.00         0.00         0.00         0.00         74prives         74prives           901266         31-Jan-80         0007         300.00         61,974         145.96         0.00         0.00         0.00         75006           750064         31-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         0.00         75006           750064         31-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         0.00           750064         31-Jan-80         00009         61,576         0.00 <t< th=""><th>Number         Date         Engn         per test         cumulativ         per test         cumulativ         per test         catastrophic         Major         catastrophic           901265         25-Jan-80         0009         7.50         61,274         0.00         0.00         0.00         Major         catastrophic           901265         25-Jan-80         0009         7.50         61,274         145.96         0.00         0.00         0.00         Pailures         Incidents         Failures           750064         31-Jan-80         0007         3/0.00         61,576         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           750064         31-Jan-80         0007         3/0.00         61,576         0.00         0.00         0.00         Catastrophic         Failures         Incidents         Failures           901266         31-Jan-80         0/09         0.00         0.00         0.00         0.00         Cool         Cool</th><th>Number         Data         Engn         per test         current         representation         representation<!--</th--><th>Number         Data         Engn         per test         cumulative         per test         per test         per test         catastrophic         Anjor         Catastrophic           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901266         31-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           750064         31-Jan-80         0007         300.00         0.00         0.00         0.00         0.00         Coi         Coi         Catastrophic         Major         Catastrophic           901266         31-Jan-80         0008         1.50         61,586         1.50         0.00         0.00         0.00         Coi         Coi</th><th>Number         Data         Engin         Fign         Der test         cumulative         Der test         cumulative         Der test         Catastrophic         Manue         Approximative         Approxinative         Approximative         Approxima</th><th>Number         Data         Engn         per test         test         per test&lt;</th><th>Number         Data         Engn         per test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         Catastrophic         Approximate         Der test         Catastrophic         Approximate         Der test         Catastrophic         Der test         Der test</th><th>Number         Data         Engn         per field         Der field<!--</th--><th>Number         Dale         Fngn         per test         cumulative         per test         per test</th><th>Number         Data         Engn         Figs         Cumulary         Part less         P</th><th>Number         Data         Ergn         Formulative         Test         Peri test         Catastrophic         Peritest         Perites</th><th>Number         Data         Fign         peritist         perit</th><th>Number         Date         Engn         Fign         Engn         Fign         Engn         Fign         Part less         Part les         Part les         Part les</th></th></th></t<> <th>Number         Dale         Engn         Peri lesi         Cumulary         Peri lesi         Peri lesi         Cumulary         Peri lesi         Peri lesi         Cumulary         Peri lesi         Cumulary</th> <th>Number         Data         Engn         First         Current of test         Current of test<th>Number         Data         Ergn         per less         cumulary         per less         per l</th><th>Number         Data         Engn         per fest         cumulative         per fest         per fest</th><th>Number         Date         Engn         per fest         cumulative         Test         T</th><th>Number         Data         Ergn         Part less         runt         Part less         Part less</th><th>Number         Date         Eng         per last currulary         per last cur</th><th>Number         Date         Eng         less         currative         per feast         per feast         currative         per feast         per feast         per feast         per feast</th><th>Number         Data         Ergn         partiest         cumulative         cumulative         cumulative         cumulative         cumulative         partiest         cumulative         cumulative</th><th>Number         Data         Ergn         partiest         cumulative         partiest         cumulative         partiest         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulat</th><th>Number         Date         Ergn         Features         Commany         Periods         Peri</th><th>Number         Data         Ergn         Fer isst         Curuniary         Per isst         Curuniary</th><th>Mumber         Data         Engn         Partiest         Curvative         Partiest         Calastrophic         Pariures         Calastrophic         <t< th=""></t<></th></th> | Number         Date         Engn         per test         cumulativ         per test         cumulativ         per test         catastrophic         Major         catastrophic           901265         25-Jan-80         0009         7.50         61,274         0.00         0.00         0.00         Major         catastrophic           901265         25-Jan-80         0009         7.50         61,274         145.96         0.00         0.00         0.00         Pailures         Incidents         Failures           750064         31-Jan-80         0007         3/0.00         61,576         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           750064         31-Jan-80         0007         3/0.00         61,576         0.00         0.00         0.00         Catastrophic         Failures         Incidents         Failures           901266         31-Jan-80         0/09         0.00         0.00         0.00         0.00         Cool         Cool | Number         Data         Engn         per test         current         representation         representation </th <th>Number         Data         Engn         per test         cumulative         per test         per test         per test         catastrophic         Anjor         Catastrophic           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901266         31-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           750064         31-Jan-80         0007         300.00         0.00         0.00         0.00         0.00         Coi         Coi         Catastrophic         Major         Catastrophic           901266         31-Jan-80         0008         1.50         61,586         1.50         0.00         0.00         0.00         Coi         Coi</th> <th>Number         Data         Engin         Fign         Der test         cumulative         Der test         cumulative         Der test         Catastrophic         Manue         Approximative         Approxinative         Approximative         Approxima</th> <th>Number         Data         Engn         per test         test         per test&lt;</th> <th>Number         Data         Engn         per test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         Catastrophic         Approximate         Der test         Catastrophic         Approximate         Der test         Catastrophic         Der test         Der test</th> <th>Number         Data         Engn         per field         Der field<!--</th--><th>Number         Dale         Fngn         per test         cumulative         per test         per test</th><th>Number         Data         Engn         Figs         Cumulary         Part less         P</th><th>Number         Data         Ergn         Formulative         Test         Peri test         Catastrophic         Peritest         Perites</th><th>Number         Data         Fign         peritist         perit</th><th>Number         Date         Engn         Fign         Engn         Fign         Engn         Fign         Part less         Part les         Part les         Part les</th></th> | Number         Data         Engn         per test         cumulative         per test         per test         per test         catastrophic         Anjor         Catastrophic           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901265         25-Jan-80         0009         1.50         (sec)         (sec)         (sec)         (sec)         failures         Incidents         Failures           901266         31-Jan-80         0007         300.00         61,576         0.00         0.00         0.00         Catastrophic         Major         Catastrophic           750064         31-Jan-80         0007         300.00         0.00         0.00         0.00         0.00         Coi         Coi         Catastrophic         Major         Catastrophic           901266         31-Jan-80         0008         1.50         61,586         1.50         0.00         0.00         0.00         Coi         Coi | Number         Data         Engin         Fign         Der test         cumulative         Der test         cumulative         Der test         Catastrophic         Manue         Approximative         Approxinative         Approximative         Approxima | Number         Data         Engn         per test         test         per test< | Number         Data         Engn         per test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         cumulary         Der test         Catastrophic         Approximate         Der test         Catastrophic         Approximate         Der test         Catastrophic         Der test         Der test | Number         Data         Engn         per field         Der field </th <th>Number         Dale         Fngn         per test         cumulative         per test         per test</th> <th>Number         Data         Engn         Figs         Cumulary         Part less         P</th> <th>Number         Data         Ergn         Formulative         Test         Peri test         Catastrophic         Peritest         Perites</th> <th>Number         Data         Fign         peritist         perit</th> <th>Number         Date         Engn         Fign         Engn         Fign         Engn         Fign         Part less         Part les         Part les         Part les</th> | Number         Dale         Fngn         per test         cumulative         per test         per test | Number         Data         Engn         Figs         Cumulary         Part less         P | Number         Data         Ergn         Formulative         Test         Peri test         Catastrophic         Peritest         Perites | Number         Data         Fign         peritist         perit | Number         Date         Engn         Fign         Engn         Fign         Engn         Fign         Part less         Part les         Part les         Part les | Number         Dale         Engn         Peri lesi         Cumulary         Peri lesi         Peri lesi         Cumulary         Peri lesi         Peri lesi         Cumulary         Peri lesi         Cumulary | Number         Data         Engn         First         Current of test         Current of test <th>Number         Data         Ergn         per less         cumulary         per less         per l</th> <th>Number         Data         Engn         per fest         cumulative         per fest         per fest</th> <th>Number         Date         Engn         per fest         cumulative         Test         T</th> <th>Number         Data         Ergn         Part less         runt         Part less         Part less</th> <th>Number         Date         Eng         per last currulary         per last cur</th> <th>Number         Date         Eng         less         currative         per feast         per feast         currative         per feast         per feast         per feast         per feast</th> <th>Number         Data         Ergn         partiest         cumulative         cumulative         cumulative         cumulative         cumulative         partiest         cumulative         cumulative</th> <th>Number         Data         Ergn         partiest         cumulative         partiest         cumulative         partiest         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulat</th> <th>Number         Date         Ergn         Features         Commany         Periods         Peri</th> <th>Number         Data         Ergn         Fer isst         Curuniary         Per isst         Curuniary</th> <th>Mumber         Data         Engn         Partiest         Curvative         Partiest         Calastrophic         Pariures         Calastrophic         <t< th=""></t<></th> | Number         Data         Ergn         per less         cumulary         per less         per l | Number         Data         Engn         per fest         cumulative         per fest         per fest | Number         Date         Engn         per fest         cumulative         Test         T | Number         Data         Ergn         Part less         runt         Part less         Part less | Number         Date         Eng         per last currulary         per last cur | Number         Date         Eng         less         currative         per feast         per feast         currative         per feast         per feast         per feast         per feast | Number         Data         Ergn         partiest         cumulative         cumulative         cumulative         cumulative         cumulative         partiest         cumulative         cumulative | Number         Data         Ergn         partiest         cumulative         partiest         cumulative         partiest         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulative         cumulative         partiest         cumulative         cumulat | Number         Date         Ergn         Features         Commany         Periods         Peri | Number         Data         Ergn         Fer isst         Curuniary         Per isst         Curuniary | Mumber         Data         Engn         Partiest         Curvative         Partiest         Calastrophic         Pariures         Calastrophic <t< th=""></t<> |

Considered by this Study

SSME Chronological Experience with Power Levels

103

Page 17

ċ

÷.,

				Prooram	Doutor	t avot Evnocut	1 /0/	Consid	ered by this	Study
Test/Flt			Durato	Exproc	10.0.1.0.3	104-108	1001		Analicable	
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
750073	29-Mar-80	0007	300.00	71,960	28.72	0.00	0.00			
902191	31-Mar-80	2004	610.00	72,570	232.10	5.50	360.10			
750074	5-Apr-80	0007	300.00	72,870	254.28	0.00	0.00			
901275	8-Apr-80	6000	520.00	73,390	424.32	00.00	0.00			
750075	11-Apr-80	0007	10.00	73,400	5.74	00.00	0.00			
901276	12-Apr-80	6000	520.00	73,920	424.36	0.00	0.00			
750076	14-Apr-80	0007	10.00	73,930	5.74	00.00	0.00			
902192	14-Apr-80	2004	610.00	74,540	232.13	5.50	360.10			
SF09-01A	16-Apr-80	0008	5.84	74,546	1.64	0.00	0.00			
SF09-01B	16-Apr-80	2003	4.72	74,550	0.49	0.00	0.00			
SF09-01C	16-Apr-80	0000	6.62	74,557	2.46	0.00	0.00			
901277	18-Apr-80	6000	10.00	74,567	5.88	0.00	0.00			
902193	19-Apr-80	2004	610.00	75,177	232.18	5.50	360.10			
750077	21-Apr-80	0007	300.00	75,477	254.30	0.00	0.00			
901278	21-Apr-80	6000	10.00	75,487	5.87	00.00	0.00			
901279	24-Apr-80	0000	300.00	75,787	245.76	0.00	0.00			
901280	28-Apr-80	6000	520.00	76,307	424.32	00.00	00.00			
750078	30-Apr-80	0007	300.00	76,607	248.02	0.00	0.00			
750079	7-May-80	0007	300.00	76,907	248.33	0.00	0.00			
750080	15-May-80	0007	300.00	77,207	254.88	00.00	0.00			
750081	21-May-80	0007	300.00	77,507	285.83	00.00	0.00			
SF09-02A	30-May-80	0008	578.24	78,085	351.34	0.00	0.00			
SF09-02B	30-May-80	2003	548.81	78,634	351.14	0.00	0.00			
SF09-02C	30-May-80	0006	533.89	79,168	351.38	00.00	0.00			
902194	2-Jun-80	2005	520.00	79,688	427.14	00.00	0.00			
750082	5.Jun-80	0001	300.00	79,988	152.84	00.00	0.00			
901281	5-Jun-80	2006	520.00	80,508	424.30	0.00	00.00			
750083	9-Jun-80	0007	300.00	80,808	143.30	0.00	00.00			
750084	11-Jun-80	0007	300.00	81,108	145.88	0,00	0.00			
901282	16-Jun-80	2007	520.00	81,628	424.34	00.00	00.00			
750085	19-Jun-80	0007	300,00	81,928	227.50	00.00	0.00			
902195	20-Jun-80	2004	251.03	82,179	246.95	0.00	0.00			
750086	23-Jun-80	0007	300.00	82,479	254.12	0.00	00.00			
902196	24-Jun-80	2004	520.00	82,999	430.62	0.00	0.00			

				Brossem	Domot	Lough Evenesity	10/1	Consi	dered by this	Study
Test/Fli			Duratn	Exprnc	100-103	1.94 - 1.08	(%) 109+		Applicable	Annlicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Faitures	Incidents	Failures
902197	2-Jul-80	2004	520.00	83,519	430.60	0.00	00'0			
750087	3.Jul.80	0007	300.00	83,819	246.75	0.00	0.00			
SF10-01A	12-Jul-80	0008	105.29	83,924	69.49	0.00	0.00			
SF10-01B	12-Jul-80	2003	105.92	84,030	70.00	0.00	0.00			
SF10-01C	12-Jul-80	0006	106.52	84,137	70.76	0.00	0.00	×	×	×
750088	15-Jul-80	0007	300.00	84,437	241.80	0.00	0.00			
902198	23-Jul-80	2004	8.53	84,445	4.53	0.00	0.00		×	
750089	28-Jul-80	0007	130.00	84,575	95.82	0.00	0.00			
901283	28-Jul-80	0010	1.50	84,577	0.00	0.00	0.00			
901284	30-Jul-80	0010	9.89	84,587	0.00	0.00	0.00		×	
750090	16-Aug-80	0007	160.00	84,747	145.76	0.00	0.00			
750091	20-Aug-80	0007	100.00	84,847	85.78	0.00	0.00			
901285	27-Aug-80	0000	1.56	84,848	0.00	0.00	0.00			
901286	29-Aug-80	0000	10.00	84,858	5.80	0.00	0.00			
901287	2-Sep-80	6000	100.00	84,958	95.76	0.00	0.00			
750092	3.Sep.80	0007	174.84	85,133	160.80	0.00	0.00			
902199	8-Sep-80	2008	1.50	85,135	0.00	0.00	0.00			
750093	9-Sep-80	0007	300.00	85,435	285.80	0.00	0.00			
901288	11-Sep-80	6000	392.60	85,827	356.90	0.00	0.00			
902200	13-Sep-80	2008	100.00	85,927	95.72	0.00	0.00			
902201	16-Sep-80	2008	250.00	86,177	218.50	9.70	0.00			
901289	18-Sep-80	6000	520.00	86,697	430.30	0,00	0.00			
750094	20-Sep-80	0002	285.27	86,982	281.21	0,00	0.00			
902202	23-Sep-80	2008	50.00	87,032	45.72	0.00	0.00			
750095	27-Sep-80	0002	99.52	87,132	85.80	0.00	0.00			
750096	30-Sep-80	0007	99.52	87,232	85.80	0.00	0,00			
750097	2-Oct-80	0002	100.12	87,332	85.80	0.00	0.00			
750098	4-Oc1-80	0007	100.12	87,432	85.78	0.00	0.00			
750099	7-Oc1-80	0007	137.06	87,569	85.84	0.00	0.00			
901290	7-Oct-80	6000	520.00	88,089	430.40	00.00	0.00			
750100	9-Oct-80	0007	100.01	88,189	85.79	0.00	0.00			
901291	10-Oct-80	6000	520.00	88,709	13.40	423.20	0.00			
750101	11-Oct-80	0007	100.01	88,809	14.81	0.00	00.00			
902203	11-Oct-80	0000	1.50	88,810	00.00	0.00	0.00			

SSME Chronological Experience with Power Levels

. . .

÷

3

÷

. स्

.

105

Levels	
th Power	
rience wit	
ical Expe	
Chronolog	
SSME C	

. . .

Considered by this Study

				Program	Power	Level Exposure	(%)		•	•
Test/Flt			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(S8C)	Failures	Incidents	Failures
902204	13-Oct-80	0006	260.00	89,070	231.80	0.00	0.00			
901292	15-Oct-80	6000	520.00	89,590	430.40	0.00	0,00			
750102	20-Oct-80	0007	300.00	89,890	248.30	0.00	0.00			
901293	22-Oct-80	6000	823.00	90,713	518.89	0.00	00.00			
901294	24-Oct-80	0000	665.00	91,378	610.40	0.00	0.00			
902205	28-Oc1-80	2008	1.50	91,380	0.00	0.00	0.00			
902206	29-Oct-80	2008	100.00	91,480	95.76	0.00	00.00			
750103	3-Nov-80	0007	33.48	91,513	5.75	0.00	00.00			
SF11-01A	3-Nov-80	0008	20.70	91,534	16.61	0.00	0.00			
SF11-01B	3-Nov-80	2003	19.50	91,554	15.22	0.00	0.00			
SF11-01C	3-Nov-80	0006	21.44	91,575	17.36	0.00	0.00			
902207	4-Nov-80	2008	520.00	92,095	430.34	0.00	0.00			
750104	6-Nov-80	0007	10.00	92,105	5.71	0.00	0.00			
901295	6-Nov-80	0000	520.00	92,625	430.38	0.00	0.00			
750105	8-Nov-80	0007	10.00	92,635	5.82	0.00	0.00			
902208	10-Nov-80	2008	520.00	93,155	430.22	0.00	0.00			
750106	11-Nov-80	0007	15.00	93,170	5.96	0.00	0.00			
901296	11-Nov-80	6000	519.93	93,690	430.40	0.00	0.00			
750107	13-Nov-80	0007	3.64	93,694	0.00	0.b0	0.00			
901297	13-Nov-80	0000	10.00	93,704	5.76	0.00	0.00			
750108	15-Nov-80	0007	15.00	93,719	5.98	0.00	0.00			
902209	15-Nov-80	2008	823.00	94,542	518.72	0.00	0.00			
750109	18-Nov-80	0007	15.00	94,557	5.72	0.00	0.00			
901298	19-Nov-80	6000	10.00	94,567	5.72	0.00	0.00			
902210	21-Nov-80	2008	665.00	95,232	610.46	0.00	0.00			
901299	24-Nov-80	6000	10.00	95,242	5.74	0.00	0.00			
750110	25-Nov-80	0007	450.00	95,692	10.76	0.00	00.00			
750111	1-Dec-80	0007	300.00	95,992	222.84	0.00	0.00			
901300	2-Dec-80	6000	10.00	96,002	5.82	0.00	0.00			
SF11-02A	4-Dec-80	0008	590.03	96,592	352.32	0.00	0.00			
SF11-02B	4-Dec-80	2003	441.76	97,033	352.08	0,00	0.00			
SF11-02C	4-Dec-80	0006	590.33	97,624	352.34	00.00	0.00			
902211	5-Dec-80	2008	250.00	97,874	245.80	0.00	0.00			
750112	6-Dec-80	0007	300.00	98,174	295.76	00.00	0.00			

				Program	Ромег	Level Exposure	(%)		•	
Test/FII			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(280)	(280)	Failures	Incidents	Failures
902212	10-Dec-80	2008	520.00	98,694	13.82	422.80	0.00			
901301	15-Dec-80	6000	823.00	99,517	518.78	0.00	0,00			
750113	16-Dec-80	0007	300.00	99,817	295.80	0.00	0.00			
750114	18-Dec-80	0007	300.00	100,117	295.80	0.00	0.00			
902213	18-Dec-80	2008	520.00	100,637	430.42	0.00	0.00			
750115	20-Dec-80	0007	300.00	100,937	295.79	0.00	0.00			
902214	23-Dec-80	2008	520.00	101,457	430.40	00.00	0.00			
902215	30-Dec-80	2008	520.00	101,977	430.20	0.00	0.00			
750116	2-Jan-81	0007	300.00	102,277	295.76	0.00	0.00			
902216	5-Jan-81	2008	520.00	102,797	430.20	0.00	0.00			
750117	9-Jan-81	0007	300.00	103,097	290.71	0.00	0.00			
901302	12-Jan-81	6000	1.50	103,098	0.00	0.00	0.00			
SF12-01A	17-Jan-81	0008	628.36	103,727	624.11	0.00	0.00			
SF12-01B	17-Jan-81	2003	628.46	104,355	623.90	0.00	0.00			
SF12-01C	17-Jan-81	0000	238.94	104,594	234.76	0.00	0.00			
901303	19-Jan-81	6000	53.10	104,647	5.74	0.00	0.00			
901304	21-Jan-81	0000	81.70	104,729	5.74	0.00	0.00			
750118	22-Jan-81	0007	300.00	105,029	295.72	0.00	0.00			
901305	23-Jan-81	6000	79.57	105,108	5.75	0.00	0.00			
901306	26-Jan-81	0000	80.29	105,189	5.79	0.00	0.00			
750119	28-Jan-81	0007	5.25	105,194	0.85	0.00	0.00			
901307	28-Jan-81	6000	75.02	105,269	5.77	0.00	0.00		×	
902217	31-Jan-81	2009	1.57	105,270	0.00	0.00	0.00			
750120	2-Feb-81	0007	235,00	105,505	230.68	0.00	0.00			
902218	3-Feb-81	2009	100.00	105,605	95.94	0.00	0.00			
750121	9-Feb-81	0007	20.00	105,625	5.68	00.00	0.00			
902219	9-Feb-81	2009	520.00	106,145	418.38	00.00	0.00			
FRF001-A	20-Feb-81	2007	21.86	106,167	15.26	0.00	0.00			
FRF001-B	20-Feb-81	2006	23.83	106,191	17.13	0.00	00.00			
FRF001-C	20-Feb-81	2005	23.97	106,215	17.24	0.00	0.00			
750122	23-Feb-81	0110	1.50	106,217	00.00	0.00	0.00			
750123	25-Feb-81	0110	300.00	106,517	223.72	0.00	0.00			
901308	25-Feb-81	0000	3.90	106,520	00.00	0,00	0.00			
901309	28-Feb-81	0000	67.26	106,588	5.72	0.00	00.00			

Considered by this Study

 $\mathbf{i}$ 

• • •

•

ų

SSME Chronological Experience with Power Levels

107

Page 21

:

· • •

÷

٨þr	Applicable	atastrophic	Failures																																		
lared by this Sti	Applicable	Major C	Incidents																																		
Consic		Catastrophic	Failures																																		
1701	109+	per test (	(sec)	0.00	0.00	0.00	0.00	0.00	30.00	00.00	219.20	0.00	360.40	0.00	0.00	360.40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	00.00	0.00	00.00	190.20	00.00	0,00	00.00	0.00	0.00	0.00	189.90	239.20
aval Exposite	104-108	per test	(sec)	0.00	0.00	0.00	0.00	361.00	110.10	361.00	1.00	0.00	1.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0,00	0.00	57.84	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	5.70	1.00
Power I	100-103	per test	(Sec)	58.18	5.83	5.80	87.74	236.39	155.54	236.36	75.48	5.80	236.22	5.88	43.47	236.26	5.72	5.68	5.88	5.56	5.68	432.45	432.60	432.76	55.65	00.00	5.84	0.00	42.16	0.00	5.86	0.00	95.48	85.82	95.39	71.06	5.94
Program	Exprnc	cumulatv	(sec)	106,688	106,755	106,819	106,919	107,529	107,829	108,439	108,739	108,799	109,409	109,473	109,521	110,131	110,146	110,156	110,223	110,238	110,253	110,772	111,292	111,611	111,929	111,931	111,946	111,950	112,250	112,253	112,268	112,270	112,370	112,470	112,570	112,870	113,140
	Duratn	per test	(S8C)	99.96	67.36	64.30	100.00	610.00	300.00	610.00	300.00	60.11	610.00	63.66	47.63	610.00	15.00	10.00	66.84	15.00	15.00	519.42	519.56	519.68	118.14	1.50	15.00	3.71	300.00	3.80	15.00	1.50	100.00	100.00	100.00	300.00	270.00
		Engn		0110	0006	0006	0008	0008	0110	0008	0110	0006	0008	0006	0006	0008	0110	0110	0006	0110	0110	2007	2006	2005	0110	0204	0006	0204	0110	0204	0000	0000	0204	0000	0204	0110	0204
		Date		2-Mar-81	3-Mar-81	5-Mar-81	6-Mar-81	10-Mar-81	11-Mar-81	12-Mar-81	14-Mar-81	14-Mar-81	17-Mar-81	18-Mar-81	20-Mar-81	23-Mar-81	24-Mar-81	26-Mar-81	26-Mar-81	28-Mar-81	31-Mar-81	12-Apr-81	12-Apr-81	12-Apr-81	13-Apr-81	13-Apr-81	14-Apr-81	15-Apr-81	17-Apr-81	17-Apr-81	20-Apr-81	21-Apr-81	21-Apr-81	23-Apr-81	24-Apr-81	27-Apr-81	27-Apr-81
	Test/Flt	Number		750124	901310	901311	902220	902221	750125	902222	750126	901312	902223	901313	901314	902224	750127	750128	901315	750129	750130	STS001-A	STS001-B	STS001-C	750131	902225	901316	902226	750132	902227	901317	901318	902228	901319	902229	750133	902230

# Pago 22

	Applicable	Major	Incidents																																		
		Catastrophic	Failures																																		
(%) 8	109+	per test	(sec)	199:20	261.10	402.80	260.90	382.60	0.00	261.10	0.00	0.00	222.80	261.00	127.00	20.00	127.00	261.10	20.00	449.20	449.20	15.00	0.00	385.90	449.20	449.20	5.20	261.10	00'0	377.40	4.20	261.10	261.10	215.60	8.00	15.00	0.00
Level Exposur	104-108	per test	(sec)	1.00	1.50	9.70	1.50	9.70	0.00	1.50	0.00	0.00	29.70	1.50	42.00	85.00	42.00	1.50	60.50	1.00	1.00	1.00	0.00	2.00	1.00	1.00	1.00	1.50	0.00	10.25	0.50	1.50	1.50	2.00	16.50	75.50	0.00
Power	100-103	per test	(sec)	45.96	5.92	12.09	6.20	12.28	0.00	5.80	295.62	0.00	32.02	6.06	45.82	160.82	45.97	6.00	165.94	65.45	65.34	10.76	295.56	6.03	65.42	65.46	6.20	5.50	5.72	13.50	5.96	5.52	5.49	6.89	53.98	75.11	15.76
Program	Exprnc	cumulatv	(S8C)	113,409	113,709	114,229	114,529	115,029	115,030	115,330	115,630	115,632	116,132	116,432	116,932	117,222	117,722	118,022	118,282	118,802	119,322	119,372	119,672	120,147	120,667	121,187	121,212	121,512	121,522	122,022	122,037	122,337	122,637	122,937	123,037	123,207	123,657
	Duratn	per test	(sec)	268.80	300.00	520.00	300.00	500.00	1.48	300.00	300.00	1.33	500.00	300.00	500.00	290.00	500.00	300,00	260.00	520.00	520.00	50.00	300.00	475.00	520.00	520.00	25.00	300.00	10.00	500.00	15.00	300.00	300.00	300.00	100.00	170.00	450.00
		Engn		0204	0110	0204	0110	0204	2108	0110	2108	0110	0204	0110	0204	2108	0204	0110	2108	2108	2108	0204	2108	0204	2108	2108	0204	0110	0204	2108	0204	0110	0110	0204	0204	2108	0204
		Date		5-May-81	7-May-81	7-May-81	9-May-81	9-May-81	11-May-81	12-May-81	13-May-81	14-May-81	14-May-81	19-May-81	19-May-81	23-May-81	23-May-81	26-May-81	26-May-81	28-May-81	30-May-81	5-Jun-81	6-Jun-81	9-Jun-81	11-Jun-81	16-Jun-81	19-Jun-81	20-Jun-81	22-Jun-81	23-Jun-81	24-Jun-81	27-Jun-81	30-Jun-81	2-Jui-81	8-Jul-81	10-Jul-81	14-Jui-81
	Test/Fli	Number		902231	750134	902232	750135	902233	901320	750136	901321	750137	902234	750138	902235	901322	902236	750139	901323	901324	901325	3u2237	901326	902238	901327	901328	902239	750140	902240	901329	902241	750141	750142	902242	902243	901330	902244

**Considered by this Study** 

SSME Chronological Experience with Power Levels

Applicable Catastrophic Failures

Page 23

.

				Program	Power	Level Exposure	(%)	Consic	dered by this	Study
ate		Engn	Duratn per test	Exprnc cumulatv	100-103 per test	104-108 per test	109+ Der test	Catastrophic	Applicable Maior	Applicable Catastrophic
		•	(sec)	(sec)	(sec)	(280)	(286)	Failures	Incidents	Failures
15-Ju	1-81	2108	233.14	123,890	208.52	1.00	8.20		×	
6-Au	9-81	0110	39.00	123,929	8.91	8.60	7.20			
8-Au	g-81	0008	1.50	123,930	0.00	0.00	0.00			
10-Au	18-91	0110	48.00	123,978	14.46	8.60	7.20			
11-AU	18-91	0008	81.83	124,060	5.59	0.00	0.00			
12-AL	18-81	0204	25.00	124,085	6.20	1.00	4.20			
14-AL	19-81	0110	48.01	124,133	14.41	8.60	7.20			
14-A1	18-81	0008	84.18	124,217	5.66	0.00	0.00			
17-AI	19-81	0008	57.73	124,275	53.42	0.00	0.00			
18-AI	18-6r	0110	10.00	124,285	5.62	0.00	0.00			
19-A	ug-81	0008	54.45	124,339	50.15	0.00	0.00			
22-A	18- <u>8</u> 1	0204	25.00	124,364	6.22	1.00	4.20			
24-A	ug-81	0110	39.00	124,403	8.20	8.60	7.20			
31-A	ug-81	0204	200.00	124,603	6.12	1.00	179.20			
2-S	ep-81	0110	16.00	124,619	0.90	3.50	7.20			
14-S	ep-81	0204	500.00	125,119	6.46	1.00	479.20			
21-S	ep-81	0204	450.57	125,570	6.13	0.50	439.77	×		
<u>^-</u> (	Oct-81	0107	1.50	125,571	0.00	0.00	0.00			
9.0	Jct-81	0107	15.20	125,587	10.99	0.00	0.00			
13-0	<b>Dct-81</b>	0107	300.00	125,887	276.35	1.00	9.20			
15-0	<b>Jct-81</b>	0107	405.50	126,292	5.98	0.50	394.70			
30-0	<b>Jct-81</b>	0107	100.00	126,392	46.30	1.00	39.20			
2-N	l 8 - 70	0107	200.00	126,592	6.23	1.00	179.20			
2-X	lov-81	0110F	1.50	126,594	0.00	0.00	0.00			
8-N	ov-81	0107	500.00	127,094	6.23	1.00	479.20			
12-N	ov-81	2007	520.13	127,614	435.78	0.00	00.00			
12-N	ov-81	2006	520.24	128,134	436.03	0.00	0.00			
12-N	ov-81	2005	520.36	128,654	436.07	0.00	0,00			
14-1	lov-81	0107	500.00	129,154	6.04	1.00	479.20			
N-7-N	0v-81	0110F	60.00	129,214	35.38	1.00	9.20			
18-N	ov-81	0107	270.00	129,484	5.96	1.00	249.20			
N-61	ov-81	0107	500.00	129,984	5.95	1.00	479.20			
20-N	lov-81	0107	95.40	130,080	90.70	0.00	0.00			
2.D	ec-81	0107	750.00	130,830	200.13	1.00	509.20			

	i	Duratn	Program Exprnc	Power 100-103	Level Exposure 104-108	ө (%) 109+	
	Engn	per test	cumulatv	per test	per test	per test	Catastrophic
		(sec)	(S8C)	(S8C)	(suc)	(380)	Failures
ec-81	0110F	3.61	130,833	0.00	0.00	0,00	
0c-81	0107	463.58	131,297	5.45	0.50	452.78	
ec-81	2010	1.50	131,298	0.00	0.00	0.00	
ec-81	0110F	80.50	131,379	21.40	1.00	10.20	
ec-81	2010	100.00	131,479	95.88	0.00	0.00	
ec-81	0110F	60.00	131,539	15.38	1.00	9.20	
ec-81	2010	500.00	132,039	12.44	9.70	380.10	
18-Je	0107	300.00	132,339	264.52	00.00	0.00	
<b>BC-81</b>	2010	500.00	132,839	12.43	9.70	380.10	
)ec-81	2010	250.00	133,089	5.20	0.50	240.10	
<b>Jec-81</b>	0107	500.00	133,589	96.22	1.00	389.20	
<b>Dec-81</b>	0110F	65.00	133,654	21.05	10.60	9.20	
<b>Jec-81</b>	0107	500.00	134,154	11.98	9.70	380.20	
lan-82	2 0110F	65.00	134,219	21.00	10.60	9.20	
lan-82	2010	750.00	134,969	199.62	1.00	510.10	
Jan-82	2010	500.00	135,469	12.14	9.70	380.10	
Jan-82	2010	595.00	136,064	5.04	0.50	585.10	
Jan-82	2 0110F	65.00	136,129	20.96	10.60	9.20	
Jan-82	2 0110F	200.00	136,329	44.00	10.80	9.20	
Jan-82	0107	424.09	136,753	5.18	0.50	414.19	
Jan-82	2 0110F	200.00	136,953	120.56	1.00	9.20	
Jan-82	2010	10.00	136,963	5.62	00.00	0.00	
Jan-82	2 0107	270.00	137,233	46.04	0.50	219.20	
Jan-82	2010	60.00	137,293	5.08	0.50	50.10	
Jan-82	2 0107	500.00	137,793	46.02	0.50	449.20	
Jan-82	2 0107	37.16	137,830	25.94	0.50	6.36	
Jan-82	2010	250.00	138,080	5.16	0.50	240.10	
Jan-82	2010	500.00	138,580	12.26	9.70	380.20	
Feb-82	2 0107	500.00	139,080	26.04	0.50	469.20	
Feb-82	2010	500.00	139,580	12.66	382.14	0.00	
Feb-82	2 0110F	65.00	139,645	20.96	10.60	9.20	
Feb-82	2010	500.00	140,145	12.14	9.70	384.08	
Feb-82	2 0107	500.00	140,645	25.98	0.50	469.20	
:eb-82	2010	10.00	140,655	5.74	0.00	0,00	

Considered by this Study

SSME Chronological Experience with Power Levels

Applicable Applicable Major Catastrophic Incidents Failures

111

Page 25

.

.

÷

Considered by this Study

				Program	Power	Level Exposure	(%) (		•	
Test/Fit			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
750160	12-Feb-82	0110F	3.16	140,658	0.00	0.00	0.00	×	×	×
902265	19-Feb-82	2010	100.00	140,758	95.86	00.00	0.00			
902266	22-Feb-82	2010	500.00	141,258	12.38	9.70	380.10			
901359	7-Mar-82	2013	1.50	141,260	0.00	00.00	0.00			
902267	8-Mar-82	2010	500.00	141,760	12.40	9.70	380.10			
901360	10-Mar-82	2013	100.00	141,860	95.76	0.00	0.00			
750;61	15-Mar-82	0107	100.00	141,960	83.88	1.00	9.20			
902268	15-Mar-82	2010	500.00	142,460	12.14	9.70	380.20			
750162	22-Mar-82	0107	133.80	142,594	129.12	0.00	0.00			
901361	22-Mar-82	2013	500.00	143,094	12.58	9.70	380.20			
STS003-A	22-Mar-82	2007	519.67	143,613	435.66	0.00	00.00			
STS003-B	22-Mar-82	2006	519.80	144,133	435.69	0.00	0.00			
STS003-C	22-Mar-82	2005	519.91	144,653	435.74	0.00	0.00			
902269	23-Mar-82	2010	500.00	145,153	11.96	9.70	384.08			
750163	25-Mar-82	0107	2.00	145,155	0,00	0.00	0.00			
901362	26-Mar-82	2013	500.00	145,655	12.58	9.70	380.20			
902270	29-Mar-82	2010	250.00	145,905	4.99	0.50	240.10			
901363	30-Mar-82	2013	250.00	146,155	5.12	0.50	240.10			
750164	1-Apr-82	0107	118.94	146,274	5.74	0.50	108.14			
901364	7-Apr-82	2013	392.16	146,666	6.01	1.50	352.36			
750165	21-Apr-82	0107	280.00	146,946	5.31	1.50	240.20			
750166	29-Apr-82	0107	300.00	147,246	5.68	1.50	260.20			
902271	30-Apr-82	2010	300.00	147,546	295.88	0.00	0.00			
750167	2-May-82	0107	269.92	147,816	5.60	1.50	230.12			
902272	5-May-82	2010	500.00	148,316	12.42	9.70	380.30			
902273	8-May-62	2010	500.00	148,816	12.42	9.70	380.30			
902274	11-May-82	2010	60.00	148,876	5.18	0.50	50.10			
902275	13-May-82	2010	750.01	149,626	199.68	1.00	510.10			
750168	15-May-82	0107	300.00	149,926	5.68	1.50	260.20			
901365	15-May-82	2014	1.50	149,928	00.00	0.00	00.00			
901366	19-May-82	2014	100.00	150,028	95.83	0.00	0.00			
901367	25-May-82	2014	500.00	150,528	12.44	9.70	380.20			
902276	29-May-82	2010	595.00	151,123	5.54	1.00	575.10			
901368	<b>3-Jun-82</b>	2014	60.00	151,183	5.49	1.00	40.10			

Tott			Ċ	Program	Power	Level Exposure	ө (%)	
	c	i	DULAIN	Exprnc	100-103	104-108	103+	
Number	Date	гиди	per test	cumulatv	per test	per test	per test	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures
901369	5-Jun-82	2014	500.00	151,683	12.34	9.70	380.20	
902277	6-Jun-82	2010	250.00	151,933	5.54	1.00	225.10	
901370	7-Jun-82	2014	750.00	152,683	199.70	1.00	510.10	
901371	15-Jun-82	2014	250.00	152,933	5.52	1.00	230.10	
901372	17-Jun-82	2014	250.00	153,183	5.50	1.00	230.10	
902278	18-Jun-82	2010	1.50	153,184	0.00	0.00	0.00	
901373	20-Jun-82	2014	50.00	153,234	35.89	0.00	00.00	
902279	20-Jun-82	2010	50.00	153,284	5.50	1.00	30.10	
STS004-A	27-Jun-82	2007	519.03	153,803	443.06	0.00	0.00	
STS004-B	27-Jun-82	2006	519.13	154,322	443.18	0.00	0.00	
STS004-C	27-Jun-82	2005	519.31	154,842	443.04	0.00	0.00	
902280	28-Jun-82	2010	1,50	154,843	0.00	00.00	00.00	
902281	29-Jun-82	2010	1.50	154,845	0.00	0.00	0.00	
901374	30-Jun-82	2014	500.00	155,345	12.46	9.70	380.20	
902282	1-Jul-82	2010	1.50	155,346	0.00	0.00	00.00	
901375	3-Jul-82	2014	50.00	155,396	35.83	0.00	0.00	
902283	3-Jul-82	2010	50.00	155,446	5.50	1.00	30.10	
902284	9-Jul-82	2010	500.00	155,946	12.25	9.70	380.20	
901376	10-Jul-82	2014	5.12	155,951	00.00	0.00	0.00	
902285	13-Jul-82	2010	10.00	155,961	5.75	0.00	0.00	
901377	14-Jul-82	2014	300.00	156,261	295.89	0.00	0.00	
902286	19-JL -82	2010	250.00	156,511	14.62	1.00	230.10	
902287	21-Jul-82	2010	500.00	157,011	5.12	490.60	0.00	
901378	23-Jul-82	2014	1.50	157,013	00.00	0.00	0.00	
901379	25-Jul-82	2014	50.00	157,063	5.48	1.00	30.10	
750169	27-Jul-82	2208	1.49	157,064	0.00	00.00	0.00	
901380	27-Jul-82	2014	500.00	157,564	12.42	9.70	380.20	
902288	27-Jul-82	2010	250.00	157,814	5.38	1.00	230.10	
750170	29-Jul-82	2208	50.00	157,864	35.78	00.00	0.00	
901381	30-Jul-82	2014	500.00	158,364	12.40	9.70	380.20	
902289	1-Aug-82	2010	250.00	158,614	5.10	1.00	230.10	
901382	2-Aug-82	2014	500.00	159,114	12.15	9.70	384.08	
750171	4-Aug-82	2208	299.89	159,414	15.52	1.00	270.10	
902290	4-Aug-82	2010	750.00	160,164	199.44	1.00	510.10	

Considered by this Study

•

:

.

SSME Chronological Experience with Power Levels

Applicable Catastrophic Failures

Applicable Major ( Incidents

113

Page 27

-

-

Considered by this Study

۰.

				Program	Power	Level Exposure	(%)			6000
Test/Fit			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
750172	7-Aug-82	2208	300.00	160,464	15.47	1.00	270,10			
902291	7-Aug-82	2010	250.00	160,714	61.64	10.50	9.70			
902292	9.Aug-82	2010	146.02	160,860	4.96	0.50	136.12			
901383	15-Aug-82	2014	300.00	161,160	295.85	00.00	0.00			
750173	18-Aug-82	2208	41.76	161,202	5.16	0.50	31.86			
901384	24-Aug-82	2014	595.00	161,797	5.26	0.50	585.10			
750174	25-Aug-82	2208	300.00	162,097	5.54	1.00	270.10			
750175	27-Aug-82	2208	116.08	162,213	5.26	0.50	106.18			
901385	27-Aug-82	2014	250.00	162,463	5.22	0.50	240.10			
902293	2-Sep-82	2012	1.50	162,464	0.00	0.00	0.00			
902294	10-Sep-82	2012	120.00	162,584	96.49	9.70	0.00			
901386	13-Sep-82	2011	1.54	162,586	0.00	0.00	0.00			
901387	19-Sep-82	2011	1.50	162,587	0.00	0.00	0,00			
901388	21-Sep-82	2011	5.40	162,593	0.92	0.00	0.00			
902295	23-Sep-82	2015	1.50	162,594	0.00	0.00	0.00			
901389	25-Sep-82	2011	120.00	162,714	96.42	9.70	00.00			
902296	25-Sep-82	2015	120.00	162,834	96.32	9.70	0.00			
902297	30-Sep-82	2015	23.50	162,858	5.30	0.50	13.50			
901390	4-Oc1-82	2011	175.06	163,033	146.48	10.60	9.60			
902298	6-Oc1-82	2015	185.00	163,218	146.24	10.60	9.60			
901391	7-0ct-82	2011	500.00	163,718	12.90	380.20	0.00			
902299	8-Oct-82	2015	500.00	164,218	12.51	9.70	380.10			
901392	18-Oc1-82	2012	1.50	164,219	0.00	0.00	0.00			
901393	21-Oc1-82	2012	51.00	164,270	46.76	0.00	0.00			
902300	23-Oct-82	2016	1.50	164,272	00.00	0.00	0.00			
902301	25-Oc1-82	2016	4.60	164,277	0.20	00.00	0.00			
901394	26-Oc1-82	2012	210.00	164,487	126.26	60.60	9.60			
750176	29-Oc1-82	2308	1.52	164,488	0.00	0.00	0.00			
901395	30-Oct-82	2012	500.00	164,988	12.22	9.70	380.20			
750177	2-Nov-82	2308	210.00	165,198	126.28	60.60	9.60			
750178	7-Nov-82	2308	300.00	165,498	46.26	170.60	69.60			
STS005-A	11-Nov-82	2007	517.04	166,015	439.02	0.00	0.00			
STS005-B	11-Nov-82	2006	517.21	166,532	439.06	0.00	0.00			
STS005-C	11-Nov-82	2005	517.29	167,050	439.06	00.00	0.00			

Engn per test cumul (sec) (s
2016 215.40 167,2
2308 300.00 167,5
2308 300.5.167,8
2308 160.00 168,0
2308 299.77 168,3
2014 1.50 168,3
2016 210.00 168,5
2014 100.00 168,6
2016 500.00 169,1
2308 299.95 169,4
2014 500.00 169,9
2308 300.00 170,2
2014 500.00 170,7
2011 21.80 170,7
2015 23.76 170,7
2012 23.88 170,6
2014 500.00 171,3
2014 500.00 171,
2308 10.00 171,
2014 250.00 172,
2308 15.00 172,
2017 1.50 172
2017 86.44 172
2308 15.00 172
2308 300.00 172,
2014 50.00 172,
2011 21.80 172,
2015 23.80 172,
2012 23.92 172,
2308 3.65 172,
2014 250.00 172
2308 250.00 173
2014 500.00 173
2308 250.00 173

Page 29

.

•

4

				0.0000	Jennor		( )9)	Consic	lared by this	Study
Test/Fli			Durato	Expror	100-103	Level Exposure 1.04 - 1.08	1001		Annicable	Anticatio
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(38C)	(sec)	(sec)	Failures	Incidents	Failures
902307	15.Feb.83	2017	500.00	174,358	13.13	380.20	0.00			
901406	17-Feb-83	2014	60.00	174,418	6.13	40.10	0.00			
750192	2-Mar-83	2308	39.89	174,458	5.51	29.99	0.00			
901407	13-Mar-83	2014	500.00	174,958	12.99	380.20	0.00			
750193	23-Mar-83	2308	70.00	175,028	6.10	50.10	0.00			
S1S006-A	4-Apr-83	2017	505.76	175,533	14.99	400.40	0.00			
STS006-B	4-Apr-83	2015	505.87	176,039	14.95	400.28	0.00			
STS006-C	4-Apr-83	2012	505.99	176,545	15.25	400.02	0.00			
901408	6-Apr-83	2014	520.64	177,066	6.28	510.10	0.00			
902308	8-Apr-83	2011	1.50	177,067	0.00	0.00	0.00			
750194	14-Apr-83	2308	16.84	177,084	5.66	6.94	0.00			
902309	14-Apr-83	2011	4.95	177,089	0.39	0.00	0.00			
502310	18-Apr-83	2011	190.00	177,279	96.53	79.70	0.00			
901409	20-Apr-83	2014	750.00	178,029	200.65	510.10	0.00			
750195	22-Apr-83	2308	300.00	178,329	12.85	240.20	0.00			
901410	23-Apr-83	2014	595.00	178,924	5.66	585.10	0.00			
902311	29-Apr-83	2011	500.00	179,424	13.08	380.20	0.00			
750196	2-May-83	2308	150.00	179,574	65.19	59.70	0.00			
750197	16-May-83	2308	320.00	179,894	13.05	240.20	0.00			
901411	18-May-83	2018	1.50	179,896	0.00	0.00	0.00			
901412	21-May-83	2018	5.22	179,901	0.82	0.00	0.00			
750198	23-May-83	2308	320.00	180,221	19.18	240.20	0.00			
901413	25-May-83	2018	190.00	180,411	96.46	79.70	0.00			
750199	28-May-83	2308	190.00	180,601	35.90	140.10	00.00			
902312	<b>3-Jun-8</b> 3	2019	1.56	180,602	0.00	00.00	0.00			
750200	4-Jun-83	2308	190.00	140,792	25.83	150.10	0.00			
901414	6-Jun-83	2018	500.00	181,292	13.06	380.20	0.00			
750201	9-Jun-83	2308	100.00	181,392	6.07	80.10	0.00			
902313	9-Jun-83	2019	190.00	181,582	96.47	79.70	0.00			
S1S007-A	18-Jun-83	2017	506.50	182,089	13.98	402.10	0.00			
S1S007-B	18-Jun-83	2015	506.60	182,596	13.89	402.10	0.00			
S1S007-C	18-Jun-83	2012	506.71	183,102	14.09	401.95	00.00			
902314	20-Jun-83	2019	500.00	183,602	13.05	380.70	0,00			
750202	21-Jun-83	2308	2.20	183,604	0.00	0.00	0.00			

<b>(</b> )
7
۳.
~
ų
-
~
ā
- 5
2
9
a_
_
4
.=
_≥
-
Ð
ŏ
ž
2
. <u>w</u>
<u> </u>
Ψ
a
~
ш
_
77
.≌
0
ŏ
Ť
0
ç
0
5
5
O
-
ш
₹
2
c۵.
ĩń.
<b>v</b> )

.

				Drocram	Donnol		1/87	Consid	dered by this	Study
Test/Fit			Duratn	Exprnc	100-103	104-108	1 ( /o/) = 109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(20C)	(38C)	(sec)	(cec)	(sec)	Failures	Incidents	Failures
750203	25-Jun-83	2308	100.00	183,704	6.06	80.10	0,00			
750204	30-Jun-83	2308	320,02	184,024	12.99	240.20	0.00			
750205	6-Jul-83	2308	320.00	184,344	12.98	240.20	0.00			
901415	7-Jul-83	2010	1.50	184,346	0.00	00.00	0.00			
750206	11-Jul-83	2308	320.00	184,666	28.66	224.80	0.00			
90i416	11-Jul-83	2010	190.00	184,856	96.46	79.70	0.00			
901417	15-Jul-83	2010	510.00	185,366	18.80	390.00	0.00			
901418	20-Jul-83	2010	510.00	185,876	18.80	390.00	0.00			
750207	21-Jul-83	2308	100.10	185,976	20.90	74.70	0.00			
750208	2-Aug-83	2308	320.00	186,236	12.79	240.20	0.00			
750209	8-Aug-83	2308	320.00	186,616	13.36	240.00	0.00			
901419	13-Aug-83	2010	510.00	187,126	18.36	390.20	0.00			
750210	19-Aug-83	2308	15.00	187,141	5.52	0.00	0.00			
902315	22-Aug-83	2109	1.50	187,143	0.00	0.00	0.00			
750211	24-Aug-83	2308	300.00	187,443	58.94	145.70	59.20			
750212	30-Aug-83	2308	300.00	187,743	15.67	44.00	214.70			
901420	30-Aug-83	2010	750.00	188,493	200.34	510.10	0.00			
STS008-A	30-Aug-83	2017	527.98	189,021	433,12	0.00	00.00			
STS008-B	30-Aug-83	2015	528.11	189,549	432.98	0.00	0.00			
STS008-C	30-Aug-83	2012	528.19	190,077	432.78	00.00	0.00			
902316	31-Aug-83	2109	4.24	190,081	0.09	0.00	0.00			
750213	10-Sep-83	2308	320.00	190,401	12.62	240.20	0.00			
750214	22-Sep-83	2308	300.00	190,701	79.16	115.60	59.20			
901421	25-Sep-83	2010	148.49	190,850	5.54	138.59	0.00			
750215	27-Sep-83	2308	300.00	191,150	15.78	43.90	214.80			
901422	28-Sep-83	2010	50.00	191,200	45.64	0.00	0.00			
901423	1-Oc1-83	2010	50.00	191,250	35.56	0.00	0.00			
750216	5-Oct-83	2308	70.00	191,320	15.80	40.10	0.00			
902317	9-Oct-83	2109	1.50	191,321	0.00	0.00	0.00			
750217	11-Oct-83	2308	300.00	191,621	285.45	0.00	0.00			
901424	13-Oct-83	2010	50.00	191,671	36.16	9.70	0.00			
902318	14-Oct-83	2109	190.00	191,861	96.47	79.70	0.00			
901425	17-Oct-83	2010	510.00	192,371	18.52	390.20	0.00			
750218	18-Oct-83	2308	300.00	192.671	15.60	270.10	00.00			

. 1.

а,

tludy	Applicable	Catastrophic	Failures																																		
dered by this S	Applicable	Major	Incidents																																		
Consi		Catastrophic	Failures																																		
(%)	109+	per test	(sec)	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.00	29.60	123.60	0.00	0.00	0.00	0.00	59.20	0.00	214.80	379.60	680.10
l aval Exnosure	104-108	per test	(sec)	392.20	270.10	0.00	0.00	390.20	0.00	0.00	240.20	79.70	240.20	390.20	383.90	585.10	408.20	406.25	406.45	0.00	79.70	0.00	390.20	0.00	384.10	171.90	55.10	135.10	00.00	79.70	0.00	0.00	115.70	384.10	44.20	301.50	1.00
Power	100-103	per test	(sec)	18.35	15.67	2.33	5.64	18.42	00.00	0.00	12.85	96.37	12.80	18.44	18.15	5.70	11.17	11.32	11.52	0.00	96.48	0.00	18.52	20.24	18.22	78.45	39.56	15.44	0.00	96.55	0.90	2.30	79.33	18.40	16.08	5.67	5.66
Prooram	Exprnc	cumulatv	(sec)	193,181	193,481	193,488	193,503	194,013	194,014	194,016	194,336	194,526	194,846	195,356	195,866	196,461	196,976	197,492	198,008	198,009	198,199	198,201	198,711	198,761	199,271	199,571	199,721	200,021	200,022	200,212	200,218	200,224	200,524	201,034	201,334	202,034	202,734
	Duratn	per test	(sec)	510.00	300.00	6.61	15.00	510.00	1.50	1.50	320.00	190.00	320.00	510.00	510.00	595.00	515.52	515.65	515.78	1.50	190.00	1.80	510.00	50.00	510.00	300.00	150.00	300.00	1.50	190.00	5.18	6.42	300.00	510.00	300.00	700.00	700.00
		Engn		2109	2308	2010	2308	2010	2020	2020	2308	2020	2308	2010	2020	2010	2011	2018	2019	2021	2021	2308	2017	2308	2021	2308	2308	2308	0108	0108	2306	2010	2308	2010	2308	0108	0108
		Date		18-Oc1-83	24-0at-83	24-Oc1-83	1-Nov-83	2-Nov-83	4-Nov-83	9-Nov-83	10-Nov-83	11-Nov-83	15-Nov-83	18-Nov-83	19-Nov-83	23-Nov-83	28-Nov-83	28-Nov-83	28-Nov-83	1-Dec-83	5-Dec-83	6-Dec 83	7-Dec 83	10-Dec-83	10-Dec-83	15-Dec-83	22-Dec-83	28-Dec-83	29-Dec-83	4-Jan-84	9-Jan-84	10-Jan-84	13-Jan-84	15-Jan-84	19-Jan-84	21-Jan-84	24-Jan-84
	Test/Flt	Number		902319	750219	901426	750220	301427	902320	902321	750221	902322	750222	901428	902323	901429	STS009-A	STS009-B	S1S009-C	902324	902325	750223	901430	750224	902326	750225	750226	750227	901431	901432	750228	902327	750229	902328	750230	901433	901434

			00.00	0.00	0.00	211,006	1.50	2023	8-Jun-84	902338
			0.00	0.00	15.44	211,005	19.72	2017	2-Jun-84	FRF004-C
			0.00	0.00	15.24	210,985	19.60	2018	2-Jun-84	FRF004-B
			0.00	0,00	13.30	210,965	17.60	2021	2-Jun-84	FRF004-A
			00.0	384,00	18.52	210.948	510.00	2022	22-May-84	902337
			14,60	15,60	96.65	210,438	160.00	0207	19-May-84	901444
			0.00	38.04	4.40	210,278	47.44	2308	19-May-84	750235
			6.00	14.20	76.56	210,230	110.00	0207	14-May-84	901443
			00.00	149.70	86.50	210,120	250.00	2022	10-May-84	902336
			0.00	9.70	76.59	209,870	100.00	0207	8-May-84	901442
			0.00	0.00	0.00	209,770	1.50	0207	2-May-84	901441
			30.10	15.50	16.60	209,769	100.00	2308	19-Apr-84	750234
			0.00	149.70	86.41	209,669	250.00	2022	12-Apr-84	902335
			0.00	190.10	35.66	209,419	250.00	2019	11-Apr-84	901440
			0.00	0.00	0.00	209,169	1.50	2022	7-Apr-84	902334
			0.00	409.31	14.36	209,167	517.40	2012	6-Apr-84	STS013-C
			0.00	410.05	13.60	208,650	517.25	2020	6-Apr-84	STS013-B
			0.00	410.34	13.44	208,133	517.14	2109	6-Apr-84	STS013-A
			0.00	190.10	35.71	207,616	250.00	2019	6-Apr-84	901439
			0.00	0.00	20.52	207,366	50.00	2308	6-Apr-84	750233
			0.00	390.20	18.47	207,316	510.00	2019	27-Mar-84	901438
			0.00	20.20	6.93	206,806	60.00	2019	22-Mar-84	901437
			0.00	8.70	6.14	206,746	60.00	2010	21-Mar-84	902333
			0.00	20.30	6.89	206,686	60.00	2010	13-Mar-84	902332
		×	601.16	0.50	5.32	206,626	611.06	0108	14-Feb-84	901436
			0.00	390.20	18.48	206,014	510.00	2010	13-Feb-84	902331
			15.10	8.70	11.82	205,504	60.00	0108	8.Feb.84	901435
			194.60	64.10	15.40	205,444	300.00	2308	6-Feb-84	750232
			0.00	00.00	0.00	205,144	1.74	2010	4-Feb-84	902330
			0.00	0.00	437.27	205,143	528.01	2012	3-Feb-84	STS011-C
	×		0.00	0.00	437.77	204,615	527.89	2015	3.Feb.84	STS011-B
			0.00	0.00	438.04	204,087	527.79	2109	3-Feb-84	STS011-A
			59.20	120.20	89.20	203,559	315.00	2308	30-Jan-84	750231
			00:0	384.00	18.54	203,244	510.00	2010	25-Jan-84	902329
Fail	Incidents	Failures	(280)	(sec)	(sec)	(38C)	(S8C)			
Catas	Major	Catastrophic	per test	per test	per test	cumulatv	per test	гиди	Date	Number
Appl	Applicable		109+	104-108	100-103	Exprnc	Duratn	ı	C	I est/Fit
•	•		e (%)	Level Exposur	Power	Program				
Study	dered by this	Consi								

4

Applicable Catastrophic Failures

119

Page 33

•

.,

Considered by this Study

.

				Program	Ромег	Level Exposure	(%)		•	•
Test/Fit			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(28C)	(280)	(sec)	(280)	(58C)	Failures	Incidents	Failures
901445	9-Jun-84	0207	100.00	211,106	17.24	15.50	30.10			
902339	13-Jun-84	2023	250.00	211,356	48.79	149.70	0.00			
750236	15-Jun-84	2308	100.00	211,456	14.60	15.50	30.10			
901446	15-Jun-84	0207	91.30	211,547	40.22	26.00	0.00			
750237	20-Jun-84	2308	300.00	211,847	78.80	115.70	59.20			
902340	21-Jun-84	2023	250.00	212,097	86.50	149.70	0.00			
750238	26-Jun-84	2308	300.00	212,397	16.20	53.10	205.60			
STSA14-A	26-Jun-84	2109	00.00	212,397	0.00	0.00	0.00			
STSA14-B	26-Jun-84	2018	2.00	212,399	0.00	0.00	0.00			
STSA14-C	26-Jun-84	2017	0.22	212,400	0.00	0.00	0,00			
901447	27-Jun-84	0207	100.00	212,500	17.26	15.50	30.10			
750239	30-Jun-84	2308	300.00	212,800	16.64	15.50	208.10			
902341	30-Jun-84	2023	510.00	213,310	18.47	390.20	0.00			
750240	9-Jul-84	2308	310.64	213,620	5.04	15.50	235.10			
901448	10-Jul-84	0207	500.00	214,120	18.08	16.50	380.10			
901449	14-Jul-84	0207	500.00	214,620	17.96	16.50	380.10			
750241	18-Jul-84	2308	100.00	214,720	16.97	15.50	30.10			
902342	19-Jul-84	2014	1.50	214,722	0.00	0.00	0.00			
902343	21-Jul-84	2014	250.00	214,972	48.82	149.70	0.00			
901450	26-Jul-84	0207	124.34	215,096	5.22	4.84	110.10			
750242	27-Jul-84	2308	100.00	215,196	16.95	15.50	30.10			
750243	7-Aug-84	2308	312.65	215,509	5.94	1.00	249.60			
902344	7-Aug-84	2014	250.00	215,759	48.87	149.70	00.00			
901451	9-Aug-84	0207	10.96	215,770	5.20	0.50	1.06			
902345	12-Aug-84	2014	250.00	216,020	86.46	149.70	00.00			
750244	15-Aug-84	2308	318.88	216,339	5.59	1.00	249.90			
902346	20-Aug-84	2014	250.00	216,589	86.49	149.70	00.00			
901452	21-Aug-84	0207	100.00	216,689	17.32	15.50	30.10			
750245	23-Aug-84	2308	25.61	216,714	4.97	0.50	15.61			
STS014-A	30-Aug-84	2109	521.53	217,236	13.74	401.50	0.00			
STS014-B	30-Aug-84	2018	521.67	217,757	13.34	401.70	0.00			
STS014-C	30-Aug-84	2021	521.78	218,279	13.75	401.60	00.00			
901453	31-Aug-84	0207	300.00	218,579	79.43	115.70	59.20			
901454	12-Sep-84	0207	100.00	218,679	17.26	15.50	30.10			

90.00 226 90.00 226 250.04 226 70.01 227 32.95 227 500.08 227 517.15 228 517.15 228	0207 0207 0207 0207 0207 0207 0207 0207	* ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
	2500.80 22 500.80 22 90.00 22 90.00 22 90.00 22 90.00 22 90.00 22 517.02 22	2014     2018     2018     2018       2014     250.80     22       2014     250.00     22       0207     90.00     22       0207     90.00     22       0207     250.04     22       0207     250.04     22       0207     283.75     22       0207     283.75     22       0207     283.75     22       0207     32.95     22       0207     500.04     22       0207     283.75     22       2308     70.01     22       2109     517.15     22       2109     517.15     22
<ul> <li>a-NUV-54 2109</li> <li>B-NOV-84 2018</li> <li>B-NOV-84 2012</li> <li>12-NOV-84 2014</li> <li>1-Dec-84 2014</li> <li>1-Dec-84 2014</li> <li>1-Dec-84 2017</li> <li>5-Jan-85 0207</li> <li>14-Jan-85 0207</li> <li>24-Jan-85 2018</li> <li>24-Jan-85 2018</li> </ul>	8-Nov-84 8-Nov-84 8-Nov-84 12-Nov-84 1-Dec-84 5-Jan-85 14-Jan-85 17-Jan-85 18-Jan-85 24-Jan-85 24-Jan-85 24-Jan-85 24-Jan-85 24-Jan-85 24-Jan-85	

Page 35

•

SSME Chronological Experience with Power Levels

# Applicable Applicable Major Catastrophic Incidents Fai'ures

.

.....

- 1

					C	1		Consic	lered by this	Study
T 1			(	Program	Power	Level Exposure	(%)			
IBSI/FIL		4	Durain	Exprnc	100-103	104-108	109+		Applicable	Applicabl
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
901467	30-Jan-85	0207	586.82	229,931	26.32	2.12	554.00			
750251	1-Feb-85	2308	340.00	230,271	20.40	23.88	82.08			
901468	4-Feb-85	0207	203.86	230,474	25.32	1.20	172.92			
902355	6-Feb-85	2015	1.55	230,476	0.00	0.00	0.00			
750252	9-Feb-85	2308	340.01	230,816	21.08	24.08	81.80			
902356	11-Feb-85	2015	250.00	231,066	96.48	149.28	0.00			
750253	19-Feb-85	2308	177.32	231,243	5.36	1.56	166.00			
902357	19-Feb-85	2015	510.04	231,753	85.24	383.32	0.00			
750254	22-Feb-85	2308	300.00	232,053	6.44	279.40	0.00			
901469	23-Feb-85	2105	1.50	232,055	0.00	0.00	0.00			
750255	25-Feb-85	2308	300.00	232,355	6.20	141.00	139.20			
901470	25-Feb-85	2105	250.06	232,605	75.44	20.76	149.64			
901471	27-Feb-85	2105	503.00	233,108	107.24	11.32	380.20			
150256	1 - Mar - 85	2308	300.00	233,408	5.28	2.52	268.60			
901472	4 - Mar - 85	2105	520.00	233,928	99.84	415.88	0.00			
902358	5-Mar-85	2014	250.04	234,178	96.24	149.60	0.00			
750257	6-Mar-85	2308	300.00	234,478	5.12	22.00	249.08			
901473	6-Mar-85	2105	503.02	234,981	107.44	11.08	380.28			
902359	13-Mar-85	2014	250.04	235,231	96.44	149.40	0.00			
902360	16-Mar-85	2014	250.00	235,481	96.12	149.64	0.00			
901474	22-Mar-85	2105	503.06	235,984	107.20	11.72	379.76			
750258	23-Mar-85	2308	70.00	236,054	20.00	16.48	29.20			
902361	26-Mar-85	2014	250.08	236,304	58.60	149.48	0.00			
750259	27-Mar-85	2308	101.56	236,406	5.36	1.70	90.12	×		
STS023-A	12-Apr-85	2109	538.23	236,944	421.74	0.00	0.00			
STS023-B	12-Apr-85	2018	538.33	237,482	422.02	0.00	0.00			
STS023-C	12-Apr-85	2012	538.47	238,021	422.02	0.00	0.00			
901475	17-Apr-85	2105	520.03	238,541	100.04	415.56	0.00			
902362	22-Apr-85	2024	1.50	238,542	0.00	0.00	0.00			
902363	24-Apr-85	2024	250.05	238,792	58.60	149.72	0.00			
STS024-A	29-Apr-85	2023	521.63	239,314	27.04	338.06	0.00			
STS024-B	29-Apr-85	2020	521.46	239,835	27.28	387.78	0.00			
STS024-C	29-Apr-85	2021	521.57	240,357	27.32	387.98	0.00			
902364	3-May-85	2024	250.00	240,607	58.64	149.64	0.00			

ļ				Program	Ромег	Level Exposur	e (%)	
1 951/F 11	,		Durain	Exprnc	100-103	104-108	109+	
Number	Dale	Engn	per test	cumulatv	per test	per test	per test	Catastrophic
			(286)	(sec)	(sec)	(SEC)	(sec)	Failures
902365	13-May-85	2024	380.41	240,987	7.28	331,60	0,00	
901476	21-May-85	2105	70.00	241,057	20.08	16.12	29.44	
901477	24-May-85	2105	250.00	241,307	75.44	20.60	149.64	
901478	1-Jun-85	2105	503.00	241,810	107.20	11.64	379.84	
901479	5-Jun-85	2105	503.00	242,313	107.20	11.48	379.96	
901480	7-Jun-85	2105	503.00	242.816	107.20	11.56	379.88	
901481	10-Jun-85	2105	520.06	243,336	99.84	415.84	0.00	
902366	17-Jun-85	2024	250.06	243,587	58.04	149.64	0.00	
STS025-A	17-Jun-85	2109	522.12	244,109	13.28	397.54	0.00	
STS025-B	17-Jun-85	2018	522.24	244,631	13.72	397.22	0.00	
STS025-C	17-Jun-85	2012	522.36	245,153	13.96	397.14	0.00	
902367	29-Jun-85	2024	250.00	245,403	57.92	149.44	0.00	
902368	2-Jul-85	2024	60.04	245,463	17.96	00.00	0.00	
901482	9-Jul-85	2105	520.00	245,983	99.88	415.80	0.00	
STSA26-A	12-Jul-85	2023	3.52	245,987	0,00	0.00	0.00	
STSA26-B	12-Jul-85	2020	1.74	245,989	0,00	0.00	0.00	
STSA26-C	12-Jul-85	2021	3.76	245,992	0.00	0.00	0.00	
901483	13-Jul-85	2105	520.00	246,512	100.04	415.64	0.00	
902369	17-Jul-85	2024	250.00	246,762	58.32	149.72	0.00	
901484	19-Jul-85	2105	603.06	247,365	12.28	1.40	585.00	
901485	24-Jul-85	2105	28.53	247,394	12.32	1.36	10.52	
STS026-A	29-Jul-85	2023	349.75	247,744	7.88	298.13	0.00	
STS026-B	29-Jul-85	2020	587.73	248,331	8.08	530.63	0.00	
STS026-C	29-Jul-85	2021	587.85	248,919	9.12	529.67	0.00	
901486	<b>30-Jul-85</b>	2105	520.00	249,439	99.68	416.00	0.00	
902370	31-Jul-85	2116	1.55	249,441	0.00	0.00	0.00	
902371	3-Aug-85	2116	249.84	249,691	38.52	20.88	149.32	
901487	4-Aug-85	2105	503.03	250,194	35.04	133.92	329.76	
901488	7-Aug-85	2105	502.96	250,697	103.24	10.20	385.24	
902372	9-Aug-85	2116	503.02	251,200	19.88	11.60	379.76	
901489	12-Aug-85	2105	302.04	251,502	20.96	276.76	00.00	
902373	13-Aug-85	2116	520.04	252,022	15.12	415.32	0.00	
902374	17-Aug-85	2116	225.54	252,247	8.32	186.44	0.00	
STS027-A	27-Aug-85	2109	513.92	252,761	12.64	412.82	0.00	

**Considered by this Study** 

SSME Chronological Experience with Power Levels

7

Applicable Catastrophic Failures

Applicable Major Incidents

123

Page 37

•

.

•

. .

ŝ

• 1

				Prooram	Power	l aval Evnoetra	1701	Consic	fered by this	Study
Test/Fli			Duratn	Exprnc	100-103	104-108	109+		Annlicable	Anninahlo
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(S8C)	(SBC)	Failures	Incidents	Failures
STS027-B	27-Aug-85	2018	514.04	253,275	13.84	411.82	0.00			
STS027-C	27-Aug-85	2012	514.16	253,789	13.48	412.14	0.00			
901490	31-Aug-85	2105	503.06	254,292	107.40	11.72	379.68			
902375	6-Sep-85	2116	466.03	254,758	38.96	120.36	19.48			
750260	7-Sep-85	2025	1.52	254.760	0.00	0.00	0.00			
901491	7-Sep-85	2105	503.05	255,263	107.40	11.32	380.04			
750261	12-Sep-85	2025	249.95	255,513	58.16	149.68	0.00			
902376	12-Sep-85	2116	466.08	255,979	38.56	120.68	19.36			
FRF005-A	12-Sep-85	2011	19.20	255,998	14.92	0.00	0.00			
FRF005-B	12-Sep-85	2019	20.50	256,019	16.20	0.00	0.00			
FRF005-C	12-Sep-85	2017	21.96	256,041	17.76	0.00	0.00			
902377	17-Sep-85	2116	503.06	256,544	19.92	11.48	379.84			
901492	19-Sep-85	2105	503.06	257,047	107.28	11.60	379.88			
902378	20-Sep-85	2116	761.08	257,808	205.60	1.64	511.44			
901493	24-Sep-85	2105	350.06	258,158	291.40	45.36	8.96			
902379	25-Sep-85	2116	503.04	258,661	19.56	10.32	385.24			
STS028-A	3-Oc1-85	2011	518.28	259,179	11.80	416.74	0.00			
STS028-B	3-Oct-85	2019	518.40	259,698	11.44	417.18	0.00			
STS028-C	3-Oct-85	2017	518.52	260,216	11.64	417.02	0.00			
902380	7-Oct-85	2116	503.06	260,719	19.76	11.56	379.76			
750262	11-Oct-85	2025	250.00	260,969	56.72	1.68	149.44			
902381	14-Oct-85	2116	603.04	261,572	12.36	1.36	584.96			
901494	18-Oc1-85	2026	1.50	261,574	0.00	0.00	0.00			
902382	19-Oc1-85	2116	503.00	262,077	19.48	10.36	385.16			
901495	22-Oct-85	2026	250.04	262,327	38.88	207.04	0.00			
902383	26-Oct-85	2116	275.03	262,602	48.44	184.04	0.00			
STS030-A	30-Oc1-85	2023	521.32	263,123	24.76	389.94	0.00			
STS030-B	30-Oct-85	2020	521.46	263,645	25.32	389.74	0.00			
STS030-C	30-Oct-85	2021	521.58	264,166	25.24	389.98	0.00			
902384	5-Nov-85	2116	250.03	264,416	58.32	149.16	0.00			
902385	20-Nov-85	2116	250.00	264,666	38.52	20.60	149.68			
STS031-A	26-Nov-85	2011	517.65	265,184	13.20	413.86	0.00			
STS031-B	26-Nov-85	2019	517.77	265,702	13.20	413.82	0.00			
STS031-C	26-Nov-85	2017	517.88	266,220	13.36	413.78	00.00			

T			Ċ	Program	Power	Level Exposure	ө (%)	
Number	Cata	E.con	DULAIN	cumulativ	100-103	104 - 108	1091 100	Catactrophic
	222		1001 Jud	(ser)	1001 1001	100 Joh	lear (asi	Callastrupting
			(nac)	(nee)	(nec)	(000)	(nee)	
902386	11-Dec-85	2026	18.21	266,238	12.32	1.60	0.00	
902387	20-Dec-85	2026	503.06	266,741	20.24	31.72	349.88	
902388	23-Dec-85	2026	200.00	266,941	85.52	9.48	100.84	
STS032-A	12-Jan-86	2015	508.00	267,449	12.24	410.14	0.00	
STS032-B	12-Jan-86	2018	508.12	267,957	12.04	410.50	0.00	
STS032-C	12-Jan-86	2109	508.26	268,465	12.24	410.14	0.00	
902389	17-Jan-86	2022	250.00	268,715	38.64	20.48	149.84	
STS033-A	28-Jan-86	2023	79.40	268,795	8.00	31.92	0.00	
STS033-B	28-Jan-86	2020	79.56	268,874	8.16	31.92	0.00	
STS033-C	28-Jan-86	2021	79.62	268,954	8.24	32.00	00.00	
750263	11-Jun-86	2025	1.50	268,955	00.00	0.00	0.00	
750264	24-Jun-86	2025	40.00	268,995	12.12	23.72	00.00	
902390	26-Jun-86	2106	1.50	268,997	0.00	0.00	0.00	
902391	16-Jul-86	2106	250.00	269,247	95.84	149.96	00.00	
902392	25-Jul-86	2106	520.00	269,767	14.76	404.92	0.00	
902393	23-Aug-86	2106	520.00	270,287	14.80	415.88	0.00	
901496	13-Sep-86	2105	1.50	270,288	0.00	0.00	0.00	
901497	4-Oct-86	2105	520.00	270,808	16.08	499.76	00.00	
750265	8-Oct-86	2025	10.04	270,818	5.80	0.00	0.00	
901498	14-Oc1-86	2105	520.00	271,338	16.00	499.72	0.00	
750266	16-Oct-86	2025	6.00	271,344	1.76	0.00	0.00	
901499	18-Oct-86	2105	520.00	271,864	15.96	499.76	0.00	
901500	25-Oct-86	2105	520.00	272,384	15.88	499.88	00.00	
901501	6-Nov-86	2105	519.12	272,903	15.04	499.88	0.00	
902394	11-Nov-86	2106	1.50	272,905	0.00	0.00	00.00	
902395	15-Nov-86	2106	1.50	272,906	0.00	0.00	0.00	
750267	24-Nov-86	2012	80.00	272,986	17.28	58.52	0.00	
902396	24-Nov-86	2106	1.50	272,988	0.00	0.00	0.00	
901502	26-Nov-86	2105	520.00	273,508	16.04	499.68	0.00	
901503	3-Dec-86	2105	520.03	274,028	99.72	416.00	0.00	
750268	6-Dec-86	2012	213.00	274,241	42.04	13.72	0.00	
901504	6-Dec-86	2105	520.00	274,761	99.96	415.72	0.00	
902397	7-Dec-86	2106	520.00	275,281	14.76	415.92	0.00	
901505	9-Dec-86	2105	520.00	275,801	99,92	415.72	0.00	

Considered by this Study

SSME Chronological Experience with Power Levels

-

.

æ

Applicable Catastrophic Failures

Applicable / Major C Incidents

125

Page 39

•

Levels
Power
with
Experience
Chronological I
SSME

.: 1

. ,

Study
by this
<b>C</b> unsidered

				Program	Power	Level Exposure	(%)			
Test/Flt			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
Number	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(sec)	(sec)	Failures	Incidents	Failures
902398	11-Dec-86	2106	520.00	276,321	16.24	499.56	0.00			
750269	12-Dec-86	2012	5.00	276,326	0.68	0.00	0.00			
901506	12-Dec-86	2105	520.00	276,846	99.68	416.00	0.00			
902399	15-Dec-86	2106	600.00	277,446	16.04	579.72	00.0			
901507	16-Dec-86	2105	590.06	278,036	100.00	485.80	00.0			
750270	18-Dec-86	2012	321.00	278,357	38.68	38.84	35.96			
902400	18-Dec-86	2106	520.00	278,877	11.08	504.72	0.00			
750271	23.Dec-86	2012	250.00	279,127	28.76	15.72	3.00			
901508	30-Dec-86	2105	520.00	279,647	15.88	499.80	0.00			
902401	2-Jan-87	2106	520.00	280,167	16.12	499.68	0.00			
901509	5-Jan-87	2105	520.00	280,687	15.88	499.76	0.00			
902402	10-Jan-87	2106	520.00	281,207	16.08	499.68	0.00			
750272	12-Jan-87	2012	300.00	281,507	38.64	133.60	0.00			
901510	12-Jan-87	2105	520.00	282,027	16.00	499.64	0.00			
902403	13-Jan-87	2106	520.00	282,547	16.12	499.64	0.00			
901511	15-Jan-87	2105	520.00	283,067	15.88	499.76	0.00			
902404	16-Jan-87	2106	520.00	283,587	7.64	499.64	0.00			
750273	17-Jan-87	2012	300.00	283,887	81.08	139.64	0.00			
750274	23-Jan-87	2012	300.00	284,187	16.48	279.28	0.00			
901512	27-Jan-87	2105	5.06	284,192	0.80	0.00	0.00			
901513	30-Jan-87	2105	520.00	284,712	99.84	415.88	0.00			
750275	31-Jan-87	2012	300.00	285,012	16.12	279.64	0.00			
902405	<b>31-Jan-87</b>	2106	200.00	285,212	7.64	179.68	0.00			
902406	3-Feb-87	2106	200.00	285,412	7.44	179.72	0.00			
902407	6-Feb-87	2106	200.00	285,612	7.60	179.68	0.00			
901514	11-Feb-87	2105	520.00	286,132	99.68	416.04	0,00			
901515	14-Feb-87	2105	503.00	286,635	107.28	11.16	380.28			
902408	14-Feb-87	2106	200,00	286,835	7.64	179.60	0.00			
901516	17-Feb-87	2105	761.00	287,596	243.56	2.24	510.92			
902409	19-Feb-87	2106	200.00	287,796	7.52	179.64	0.00			
901517	24-Feb-87	2105	603.00	288,399	12.51	1.25	584.96			
750276	2 - Mar - 87	0210	1.50	288,401	0.00	00.00	0.00			
901518	2-Mar-87	2105	520.00	288,921	99.97	415.71	0.00			
902410	2-Mar-87	2106	520.00	289,441	15.20	415.64	0.00			

			585.00	1.28	12.28	303,737	603.00	2105	8-Jun-87	901529
			0,00	263.56	7.24	303,134	275.00	2106	6-Jun-87	902424
			380.04	11.28	107.28	302,859	503.00	2105	4-Jun-87	901528
			0.00	294.00	195.44	302,356	520.00	2106	3-Jun-87	902423
			0.00	601.12	94.44	301,836	700.00	2105	30-May-87	901527
			280.24	11.16	20.04	301,136	503.06	2106	29-May-87	902422
			0.00	668.60	7.24	300,633	680.00	2106	26-May-87	902421
			211.96	1.16	6.64	299,953	223.56	0210	21-May-87	750285
			0.00	378.08	137.52	299,730	520.00	2105	20-May-87	901526
			0.00	477.74	11.76	299,210	520.00	2106	18-May-87	902420
			0.00	211.08	34.52	298,690	250.00	2105	14-May-87	901525
			0.00	545.96	299.68	298,440	850.00	2105	9-May-87	901524
			0.00	51.68	8.20	297,590	90.38	2106	1 - May - 87	902419
			0.00	297.52	218.12	297,499	520.00	2105	30-Apr-87	901523
			0.00	283.84	11.92	296,979	300,00	0210	29-Apr-87	750284
			0.00	491.96	177.96	296,679	750.00	2106	28-Apr-87	902418
			0.00	415.92	99.72	295,929	520.00	2105	24-Apr-87	901522
			0.00	283.72	12.00	295,409	300.00	0210	22-Apr-87	750283
			547.48	1.60	206.00	295,109	797.00	2106	21-Apr-87	902417
			0.00	415.64	15.04	294,312	520.00	2106	9. Apr-87	902416
			0.00	183.76	12.00	293,792	200.00	0210	6-Apr-87	750282
			9.64	210.00	96.04	293,592	320.00	2011	4 - Apr - 87	901521
			0.00	183.96	11.84	293,272	200.00	0210	2-Apr-87	750281
			0.00	415.28	15.36	293,072	520.00	2106	31 - Mar - 87	902415
			0.00	183.80	11.96	292,552	200.00	0210	26-Mar-87	750280
			549.24	1.08	12.48	292,352	567.00	2106	23-Mar-87	902414
			49.36	129.92	16.28	291,785	200.00	2011	19-Mar-87	901520
			0.00	183.80	12.00	291,585	200.00	0210	19-Mar-87	750279
			380.16	11.28	20.04	291,385	503.00	2106	17-Mar-87	902413
			0.00	183.84	12.00	290,882	200.00	0210	16-Mar-87	750278
			0.00	0.00	0.00	290,682	1.50	2011	14-Mar-87	901519
			0.00	415.44	15.24	290,681	520.00	2106	13-Mar-87	902412
			0.00	183.92	11.92	290,161	200.00	0210	12-Mar-87	750277
			00.00	415.60	15.08	289,961	520.00	2106	11-Mar-87	902411
Faj	Incidents	Failures	(285)	(Sec)	(sec)	(280)	(sec)			
Catas	Major	Catastrophic	per test	per test	per test	cumulatv	per test	Engn	Date	Number
Appl	Applicable		109+	104-108	100-103	Exprnc	Duratn			Test/FH
•	•		e (%)	Level Exposur	Power	Program				
Study	dered by this	Consi								

Page 41

SSME Chronological Experience with Power Levels

۰.

1

4

Applicable Catastrophic Failures

127

~

,

`.

•

•

Considered by this Study

I				Program	Power	Level Exposure	(%)			(non
sı/FII			Duratn	Exprnc	100-103	104-108	109+		Applicable	Applicable
mber	Date	Engn	per test	cumulatv	per test	per test	per test	Catastrophic	Major	Catastrophic
			(sec)	(sec)	(sec)	(Sec)	(38C)	Failures	Incidents	Failures
1530	11-Jun-87	2105	503.00	304,240	107.28	11.32	380.04			
2425	11-Jun-87	2106	520.00	304,760	14.76	415.92	0.00			
1531	13-Jun-87	2105	520.05	305,280	100.12	415.48	0.00			
0286	16-Jun-87	0210	300.00	305,580	11.84	283.72	0.00			
1532	17-Jun-87	2105	520.00	306,100	41.56	474.06	0.00			
0287	19-Jun-87	0210	300.00	306,400	12.88	265.24	0.00			
2426	23-Jun-87	2106	1000.00	307,400	307.08	668.68	0.00			
0288	25-Jun-87	0210	4.40	307,405	0.00	0.00	0.00			
1533	25-Jun-87	2105	520.00	307,925	99.92	415.64	0.00			
2427	26-Jun-87	2106	138.36	308,063	59.72	74.36	0.00	×	×	×
2428	1-Jul-87	2106	204.12	308,267	82.88	114.06	0.00	×	×	: ×
0289	6-Jul-87	0210	300.00	308,567	11.92	283.68	0.00		1	:
1534	6-Jul-87	2105	520.00	309,087	224.72	290.92	0.00			
0290	9-Jul-87	0210	300.00	309,387	11.96	283.64	0.00			
0291	16-Jul-87	0210	300.00	309,687	12.04	283.56	0.00			
1535	18-Jul-87	2105	761.00	310,448	213.08	32.04	511.44			
0292	23-Jul-87	0210	100.00	310,548	11.88	83.68	0.00			
0293	28-Jul-87	0210	100.00	310,648	11.88	83.76	0.00			
0294	31-Jul-87	0210	100.00	310,748	11.80	83.84	0.00			
0295	4-Aug-87	0210	99.96	310,848	11.80	83.80	ר י			
1536	6-Aug-87	2105	520.00	311,368	99.92	415.66	0.00			
0296	7-Aug-87	0210	99.96	311,468	12.00	83.60	0.00			
2429	11-Aug-87	2027	1.50	311,469	0.00	0.00	0.00			
0297	12-Aug-87	0210	100.00	311,569	11.84	83.76	0.00			
1537	12-Aug-87	2105	656.66	312,226	454.92	197.36	0.00			
0298	1-Sep-87	0210	149.96	312,376	12.08	133.64	0.00			
0299	4-Sep-87	0210	210	312,586	12.04	193.68	0.00			
1538	4-Sep-87	0211	1.5	312,588	0.00	0.00	0.00			
1539	12-Sep-87	0211	300	312,888	16.00	279.68	0.00			
1540	15-Sep-87	0211	300.00	313,188	16.04	279.56	0.00			
2430	16-Sep-87	2027	250.00	313,438	29.92	144.76	19.52			
0300	17-Sep-87	0210	6.00	313,444	1.72	00.00	0.00			
1541	17.Sep.87	0211	300.00	313,744	15.96	279.68	0,00			
1542	19-Sep-87	0211	300.00	314,044	15.92	279.68	0.00			

Program Power Level Expos Duratn Exprnc 100-103 104-108 Ale Engn per test cumulatv per test per test (sec) (sec) (sec) (sec)	Program Power Level Expos Duratn Exprnc 100-103 104-108 Engn per test cumulatv per test per test (sec) (sec) (sec) (sec)	Program Power Level Expos Duratn Exprnc 100-103 104-108 per test cumulatv per test per test (sec) (sec) (sec) (sec)	Im Power Level Expos nc 100-103 104-108 itv per test per test c) (sec) (sec)	Power Level Expos 100-103 104-108 per test per test (sec) (sec)	evel Expos 104 - 108 per test (sec)	₹In	a (%) 109+ per test (sec)	Catastrophic Failures	Applicable Major Incidents
1-Sep-87 0211 300 00 314,344 15.96 27	0211 300.00 314,344 15.96 27	300.00 314,344 15.96 27	44 15.96 27	15.96 27	27	9.68	0.00		
3-Sep-8/ 0211 300.00 314,644 15.92 2 6-Sep-87 0211 210.00 314,854 18.12 14	0211 300.00 314,644 15.92 2 0211 210.00 314,854 18.12 14	300.00 314,644 15.92 2 210.00 314,854 18.12 14	14 15.92 2 54 18.12 16	15.92 2 18.12 18	∾ ∓	79.68 87.60	0,00		
0-Sep-87 0211 250.00 315,104 30.60 1	0211 250.00 315,104 30.60 1	250.00 315,104 30.60 1	34 30.60 1	30.60 1		65.84	49.20		
3-0cl-87 0211 135.00 315,239 16.00 1 5.0cl-87 0211 250 00 315,239 16.00 1	0211 135.00 315,239 16.00 1 0211 250.00 315,480 16.00 2	135.00 315,239 16.00 1 250.00 315,480 16.00 2	39 16.00 1 20 16.00 2	16.00 1	- (	14.60	00.00		
0-0c1-87 2027 520.00 316,009 21.24	2027 520.00 316,009 21.24	520.00 316,009 21.24	21.24	21.24	• • • •	348.92	51.44		
28-Oct-87 2022 1.50 316,010 0.00	2022 1.50 316,010 0.00	1.50 316,010 0.00	0.00	0.00		00.00	0.00		
6-Nov-87 2022 250.00 316,260 29.92	2022 250.00 316,260 29.92	250.00 316,260 29.92	30 29.92	29.92		144.88	19.52		
8-Nov-87 2105 280.00 316,540 11.92	2105 280.00 316,540 11.92	280.00 316,540 11.92	10 11.92	11.92		263.72	0.00		
0-Nov-87 2019 1.50 316,542 0.00	2019 1.50 316,542 0.00	1.50 316,542 0.00	42 0.00	0.00		0.00	0.00		
2-Nov-87 2105 280.00 316,822 16,56	2105 280.00 316,822 16.56	280.00 316,822 16.56	22 16.56	16.56		1.84	257.24		
7-Nov-87 2105 280.00 317,102 12.00	2105 280.00 317,102 12.00	280.00 317,102 12.00	02 12.00	12.00		263.64	0.00		
1-Nov-87 2105 280.00 317,382 12.00	2105 280.00 317,382 12.00	280.00 317,382 12.00	32 12.00	12.00		263.64	0.00		
1-Nov-87 2022 520.00 317,902 20.92	2022 520.00 317,902 20.92	520.00 317,902 20.92	32 20.92	20.92		348.88	51.56		
2-Nov-87 2019 250.00 318,152 67.12	2019 250.00 318,152 67.12	250.00 318,152 67.12	52 67.12	67.12		144.88	19.72		
B-Nov-B/ 2019 520.00 318,672 54.40	2019 520.00 318,672 54.40	520.00 318,672 54.40	72 54.40	54.40		352.68	51.52		
4-Uec-8/ 2105 280.00 318,952 12.04	2105 280.00 318,952 12.04	280.00 318,952 12.04	12.04	12.04		263.60	0.00		
8-Uec-8/ 2105 250.00 319,202 16,56 0.Dec 97 2028 1 50 210 202 0.00	2105 250.00 319,202 16.56	250.00 319,202 16.56	16.56 22 16.56	16.56		1.84	227.28		
5-Dec-87 2028 250.00 319 453 29 76	2028 250.00 319 453 29 76	250.00 319 453 29 76	53 29.76	00.0 29.76		0.00	0.00 50.20		
9 Dec-87 2105 280.00 319,733 46.52	2105 280.00 319,733 46.52	280.00 319,733 46.52	33 46.52	46.52		1.88	227.24		
3-Dec-87 2105 280.00 320,013 42.04	2105 280.00 320,013 42.04	280.00 320,013 42.04	13 42.04	42.04		233.56	0.00		
3-Dec-87 2028 520.00 320,533 20.72	2028 520.00 320,533 20.72	520.00 320,533 20.72	33 20.72	20.72		349.00	51.72		
9-Dec-87 2027 754.00 321,287 7.72	2027 754.00 321,287 7.72	754.00 321,287 7.72	37 7.72	7.72		468.52	0.00		
5-Jan-88 2105 0.50 321,288 0.00	2105 0.50 321,288 0.00	0.50 321,288 0.00	38 0.00	0.00		0.00	0.00		
2-Jan-88 0211 520.00 321,808 102.68	0211 520.00 321,808 102.68	520.00 321,808 102.68	08 102.68	102.68		360.40	52.60		
3-Jan-88 2105 10.12 321,818 5.72	2105 10.12 321,818 5.72	10.12 321,818 5.72	18 5.72	5.72		0.00	0.00		
4-Jan-88 2029 1.50 321,819 0.00	2029 1.50 321,819 0.00	1.50 321,819 0.00	00.0 61	0.00		0.00	0.00		
7-Jan-88 0211 520.00 322,339 100.04	0211 520.00 322,339 100.04	520.00 322,339 100.04	39 100.04	100.04		415.68	0.00		
9-Jan-88 2105 300.00 322,639 11.40	2105 300.00 322,639 11.40	300.00 322,639 11.40	39 11.40	11.40		264.96	19.20		
3-Feb-88 0211 519.96 323,159 99.68	0211 519.96 323,159 99.68	519.96 323,159 99.68	59 99.68	99.68		415.80	0.00		
9-Feb-88 2029 250.00 323,409 29.84	2029 250.00 323,409 29.84	250.00 323,409 29.84	09 29.84	29.84		109.64	51.84		
0-Feb-88 2105 9.96 323,419 5.24	2105 9.96 323,419 5.24	9.96 323,419 5.24	19 5.24	5.24		0.00	0.00		

.4

...

Considered by this Study

Applicable Catastrophic Failures .

129

Page 43

:

ì,

study	Applicable	Catastrophic	Failures																								
lered by this S	Applicable	Major	Incidents																								
Consid		Catastrophic	Failures																								
(70)	109+	per test (	(sec)	0,00	380.28	380.40	52.32	563.28	0.00	51.36	0.00	0.00	0.00	0.00	0.00	0.00	51.68	00.C	0.00	0,00	0.00	0,00	0,00	51.76	0.00	380.28	0.00
aval Evnosurs	104-108	per test	(28C)	415.72	11.16	11,20	348.20	3.12	468.76	147.12	415.60	415.48	0.00	8.40	0.00	0.00	109.92	26.66	0.00	40.88	580.28	415.76	0.00	348.76	415.28	11.04	199.40
Power 1	100-103	per test	(S8C)	99.52	107.08	106.84	21.00	32.04	99.64	21.80	99.76	99.84	0.00	7.00	0.00	5.68	29.88	488.52	0.00	95.84	34.68	99.56	20.24	20.96	100.04	107.00	15.96
Prooram	Exprnc	cumulatv	(sec)	323,939	324,442	324,945	325,465	326,068	326,641	326,891	327,411	327,931	327,932	327,952	327,954	327,964	328,264	328,784	328,785	328,926	329,549	330,069	330,094	330,614	331,134	331,637	331,857
	Duratn	per test	(sec)	519.88	502.96	503.00	519.96	602.96	572.96	250.00	519.96	519.96	1.50	20.00	1.55	10.00	300.00	519.94	1.50	140.96	622.96	520.00	25.00	520.00	519.96	502.96	220.00
		Engn		0211	0211	0211	2029	0211	0211	2029	0211	0211	0208	0211	2030	0208	2030	0211	2206	0208	0211	0211	2206	2030	0211	0211	2206
		Date		10-Feb-88	14-Feb-88	18-Feb-88	19-Feb-88	20-Feb-88	25-Feb-88	4-Mar-88	5-Mar-88	10-Mar-88	21-Mar-88	21-Mar-88	23-Mar-88	25-Mar-88	28 - Mar - 88	29-Mar-88	30-Mar-88	31-Mar-88	5-Apr-88	8-Apr-88	9-Apr-88	10-Apr-88	16-Apr-88	19-Apr-88	20-AF1-88
	Test/Fit	Number		901556	901557	901558	902440	901559	901560	902441	901561	901562	750313	901563	902442	750314	902443	901564	904001	750315	901565	901566	904002	902444	901567	901568	904003

.

## Appendix A.2

.

A Quick Calculation of the Effect of Failure Correlation Factor vs. Engine Out Capability A. P. CORRELATION VS ENGINE OUT CAPABILITY

A preliminary trade off study of single large liquid rocket engines vs "clustering" with reliability as the driver follows. Weight and cost as well as engine out capability is also considered but not calculated.

Let,

R1 = rocket engine reliability excluding plumbing to tanks.

R2 = reliability of plumbing.

Assume a single engine plumbing reliability of R2 = 0.999 and that increases in numbers of rockets produce directly proportional increases in plumbing complexity. Since reliability decreases with increasing complexity then if,

n := 1 ..16 the total number of rocket engines

R2 := exp(n ln(0.999))

Since smaller "state of the art" engines are more mature thus possibly more reliable then R1 increases as n (the no. of engines) increases. This is because the more engines there are, the smaller they are.

-

R1 :=	n					•
n	R1	R2		n		
.985	n	n	RT :	:= R2 R1		• •
.986	0.985	0.999	] n	n n		
.987	0.972196	0.998001				
.988	0.9615048	0.997003	.99			
.989	0.9528571	0.996006				
.99	0.9461968	0.99501	]			
.991	0.9414801	0.994015				• • •
.992	0.9386757	0.993021	RT			
.993	0.9377636	0.9920279	n [			
.994	0.9387355	0.9910359			. [] []]]	
.995	0.9415944	0.9900449				
.996	0.9463546	0.9890548				
.997	0.953042	0.9880658	.93			
.998	0.9616943	0.9870777		1 n	16	••••
.999	0.9723611	0.9860906	]	"No. of e	ngines"	5. <del>*</del>
.9991	0.9851045	0.9851045		RT = 0.9302877	minimum reliability	
	0.9856968	0.9841194	]	8	with 8 engines and	
					NO engine out cap~	
					ability.	

Consider now engine out capability:

if the number of engines varies from 4 to 16,

m = the total no. of engines

k = the maximum engine out capability

RS = total reliability with engine out capability.

C := 1.0 cost

W +- 1 0 whicht

m := 4 R1 := R2 := exp(m ln(0.999))m m .985 ,986 .987 Now let. . 788 k := 3 ..4 engines required for success .989 .99 .991  $\begin{bmatrix} m! \\ m' \\ m-k \end{pmatrix}! k' \\ m \\ \begin{bmatrix} m-k \\ m \end{bmatrix}$ .992 .993 m-k RE := .994 k .995 k .996 .997 RS := W C RE R2 RS = 0.9946881 k k m 4 .998 .999 .9991

Let REC = reliability with correlated failures

j := 1 ..7 = the number of correlated failures

REC :=  $\begin{vmatrix} j \\ 1 - \\ 1000 \end{vmatrix}$ , for four engines



Thus 4 engines are no better than 1 if the correlation factor is between 20 and 30% as shown below.

RT := REC RS j j 4

RI
ز
0.9907153
0.9867545
0.9828055
0.9788684
0.9749431
0.9710296
0.9671279

Not only are four engines no better than one under the above conditions, three or two engines are also no better. In fact the correlation factor drives the results and begins to do so at about 15%.

Time did not allow a thorough study of the effects of cost or weight. In fact the entire subject is complex enough to warrant a separate study.

One could easily envision that an increase in the number of engines, plumbing and detection apparatus would increase weight thus reduce payload and might quickly render a clustered system uneconomical.

The purpose of this brief set of calculations is not to draw conclusions but that correlation factors of about 15% are definitely a "red flag" that warrants further study. It appears that liquid engine manufacturers are overly optimistic about correlation factors.

## Appendix A.3

## Reliability Analysis of Current US Launch Vehicles

Yu Shen SAIC, Division 265, New York

December 21, 1988

## TABLE OF CONTENTS

### Section

### Page No.

	SUMMARY	137
	OBJECTIVE and BACKGROUND	137
1.0	EXISTING METHODOLOGIES	145
	1.1 The Binomial Method	145
	1.2 Polynomial Curve Fitting	145
	1.3 Bayesian Analysis	146
	1.4 D. Llovd's Method	146
2.0	A NEW STATISTICAL MODEL	147
	2.1 Estimation of Launch Vehicle Reliability	147
	2.2 Estimation of Stage Reliability	149
	2.3 Estimation of System Reliability	149
	2.4 Estimation of Engine (or Motor) Reliability	150
3.0	DATA COLLECTION	151
4.0	ALGORITHM	151
5.0	EXAMPLE	152
6.0	RESULTS	157
7.0	CONCLUSIONS	159
	BIBLIOGRAPHY	160

#### SUMMARY

This report contains reliability data for the following families of United States launch vehicles: Thor/ Delta, Titan, Atlas, the Saturn "Family", the Scout "Family", and the Space Shuttle.

The reliability data was obtained through the statistical models and procedures described in Section 2.0 as applied to the "Launch Vehicle Failure History Data Base" compiled by C.T. Clague of the Aerospace Corporation and other data sources given in the bibliography. The results of the analysis are summarized in the following table.

The statistical model and algorithm contained in this report is unique and is the only technique except for D. Lloyd's model that has been developed expressly for launch vehicles. It provides conservative reliability estimates during the "early launch" period of development. It also converges to the same value obtained by D. Lloyd when a sufficiently large number of launches and or tests have been attained. Unlike D. Lloyd's method, it does not require judgement as to whether or not a failure has been corrected nor does it require that component failure mode be known.

#### OBJECTIVE AND BACKGROUND

The objective of this report is to produce a statistical model and algorithm which can estimate launch vehicle reliability based solely on attribute data that presently exists. In addition, the methodology is to serve as a means of estimating stage and system reliability. A secondary objective is to use the model as a means of predicting the reliability of new systems.

Presently existing methodologies do not meet the objectives cited above.

By way of background, the first attempts to measure launch system reliability were made in order to either ascertain what level of reliability had been attained at a given point especially prior to customer "buy off" or acceptance.

In the 1960's the most widely accepted approach was to assume that each test or launch was independent of all others. Using this assumption, one could easily calculate the reliability at any given level of confidence using the Binomial distribution. It became obvious, however, that reliability and confidence levels above 90% would require an inordinately large number of tests. In the early 70's Bayesian analysis was introduced. However, due to the subjective nature of prior distributions which rely on expert judgement rather than direct results from experiments and tests, the Bayesian approach did not receive wide acceptance in the aerospace industry.

In recent years D. Lloyd of TRW began developing a methodology that does require judgement, but the judgement is based solely on evidence that the propensity for certain failure modes to occur has been reduced by redesign and retest.

Dr. D. Lloyd's method appears to be the most recent attempt made to estimate reliability or developmental environment which includes Reliability Growth until now.

The methodology developed for this study is discussed in Section 2.0 of this report and is an approach which has some attractive features not found in other methods. This methodology was applied to the historical data obtained during the course of the study to produce the tables of reliability data which follow. A summary of all the results is given in Table A.2 and results for individual launch vehicle failures are indicated in Tables A.2a through A.2f.

TABLE A.2: RELIABILITY COMPARISON OF U.S. LAUNCH VEHICLE FAMILIES

,

575		004 01675 121 0.8167 144 0.8608	-		0.8275				0.6275						
		0 0 0		-	-				_	-					
Cout 1			_	<b> </b>	8	0.007	0974	0.967	840	0.961	1980		E NO	8	0 986
<b>e</b> 7	5:-S	0110 0110 2310	<b> </b> _	_	0.63.0	0.50	804.0		E.	P2180	100ro				0.634
	R R	0.2560	_		<u> </u>										
	15					0	228								
5		E SEG													
find)		2													
Setur	4 <b>5</b>	0.4300 0.2135 0.6745			0.0573	0,7006	0.7%20	0 4224							
	10 S	0.026				0.5741		0.6280	0.760					0.5741	
	Combre ST-BB	0,7863 0,4781 0,9965										Ī			
				0.0814	0.9610	021610			90960	Γ	10000	1000	0 9907	10000	
	ž ž			Γ								Ī			
	0 1 1	1 S. G. G.	T										$\square$		
		11 M C 11	Γ	13800			$\square$		N.		ă		No.	ā	
	įŧ		F	1.000	1				2130	1			Ē	-	10,000
Attas	Į į			100	12580				SKIGO	E.		19860	1588		
	0 19 8	0.800 2.8015 0.8734	╞		Ť				-	Ē		Ē	ľ		
	° 8 I 8	0.2842 0.2842 0.85540	┢	$\left  \right $		-									
	Į š	80 0 10 K		$\vdash$	-	<u></u> 			1000		8				
	A	0.4218 0.1427 0.0417				-			1		Į	1			
		6108.0 6708.0	F								Ť	Ť			
	1 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3				5				9922.0			$\square$			
T ten	1 3	0.960 0.960 0.960	Į		ľ	01.51			g	300	ł	Ĩ			
		1	Ť		10574		Ē		0000	82667		Ē	8286	10026	
	ī \$	12.0	F		120	1982			22.00	Ť	Ē	a		Ť	
	Sy 42											ľ			
or / Defu			8		8	9).W	2		10.6	8	iii		9998	0000	
Ē	р \$ Е В	20 00 00 00 00 00 00 00 00 00 00 00 00 0			8046	9764	9 <b>1</b> 77		808	0000	0	1	813		1276
	Parlod		0.00	tage 1/2	<b>1</b> 0	<b>19</b> 06 2 0	6 3	100 I	roputaion c	uidence 0	Name Control o	tructure	lectrical o	perados o	ther or (UK) o
1	Ē	àā	۴-	.0	N B	DV.	LS	( <del>1</del> 1)		9	- <u>-</u>	318 1 00		69	0

138
- v	ebicie Name		Thor / Delta	
Da	ita Collection	Thor	Delta	Combine
	Ferrou	57-83	60-87	57-87
Suc Rati	cess o: Mean 5% 95%	0.8982 0.8750 0.9181	0.9402 0.9110 0.9615	0.9192 0.8789 0.9551
	Stage 0	0.9965	0.9950	
	Stage 1/2			
NO.	Stage 1	0.9346	0.9850	
AGE	Stage 2	0.9764	0.9746	
S	Stage 3	0.9877	0.9843	
	Stage 4			
	Propuision	0.9568	0.9701	
	Guidance	0.9830	0.9950	
M	Flight Control	0.9907	0.9851	
YST	Structure	0.9969		
Ś	Electrical	0.9815	0.9950	
	Separation	0.9969	0.9950	
	Other or (UK)	0.9923		

# TABLE A.2a: RELIABILITY OF THE THOR/DELTA FAMILY

v	ehicie Name			Titan		
Da	ta Collection	Titan I	Titan II	Titan III	Titan 34D	Combine
		59-65	62-76	64-87	82-87	59-87
Suc Rati	cess c: Mean 5% 95%	0.6427 0.5585 0.7202	0.8864 0.8323 0.9272	0.9406 0.9055 0.9651	0.7355 0.4978 0.8990	0.8013 0.6075 0.9546
	Stage 0			0.9946	0.8678	
	Stage 1/2					
NO.	Stage 1	0.8214	0.9574		0.8476	
IAGE	Stage 2	0.7825	0.9258	0.9783		
S	Stage 3			0.9667		
	Stage 4					
	Propulsion	0.6725	0.9290	0.9622	0.7355	
	Guidance		0.9929	0.9892		
W U	Flight Control		0.9858	0.9946		
YST	Structure	0.9702		0.9946		
0	Electrical		0.9929			
	Separation		0.9858			
	Other or (UK)					

# TABLE A.2b: RELIABILITY OF THE TITAN FAMILY

v	ehicle Name					Ati	<b>AS</b>					
Da	ta Collection Period	Atlas A 57-58	Atlas B 58-59	Atlas C 58-59	Atlas D 59-67	Atias E 60-88	Atlas F 61-81	Atlas SLV 67-83	Atlas G 84-87	Atlas H 83-87	Atlas/ Centaur 62-87	Combine 57-88
Suc Rati	cess o: Mean 5% 95%	0.4219 0.1827 0.6977	0.5558 0 3010 0.7896	0.5833 0.2642 0.8585	0.8401 0.8015 0.8734	0.7426 0.6454 0.8240	0.8883 0.8359 0.9276	0.9445 0.8736 0.9652	no failure 0.6313	no failure 0.6313	0.9069 0.8450 0.9489	0.7883 0.4761 0.9953
	Stage 0											
	Stage 1/2					0.8713	0.9573	0.9861			0.9814	
Ň	Stage 1					0.8523	0.9279	0.9719			0.9810	
AGE	Stage 2							0.9856			0.9420	
ST	Stage 3											
	Stage 4											
	Propuision	0.8844	0.6667		i	0.8713	0.9212	0.9824			0.9535	
	Guidance					0.9571	0.9869					
M	Flight Control	0.7688	0.8889			0.9428	0.9869	0.9824			0.9907	
YST	Structure	0.7688				0.9857					0.9814	
S	Electrical					0.9857		0.9824			0.9907	
	Separation							0.9824			0.9907	
	Other or (UK)						0.9934					

# TABLE A.2c: RELIABILITY OF THE ATLAS FAMILY

v	ehicle Name			Saturn	"Family"		
Da	ta Collection Period	Jupiter	Juno	Saturn I	Saturn IB	Saturn V	Combine
		58-58	58-61	62-65	66-75	67-73	<b>58</b> -75
Suc Rati	cess c: Mean 5% 95%	0.3611 0.1026 0.6879	0.4300 0.2135 0.6743	no failure 0.7943	no failure 0.7743	0.9822 0.8180 0.9997	0.7547 0.2652 0.9935
	Stage 0						
_	Stage 1/2						
NO.	Stage 1		0.8575				
<b>FAGE</b>	Stage 2	0.5741	0.7009			0.9822	
S	Stage 3		0.7629			0.9822	
	Stage 4	0.6290	0.9378				
	Propulsion	0.7870					
	Guidance						
EM	Flight Control						
3 Y S T	Structure						
v)	Electrical						
	Separation	0.5741					
	Other or (UK)						

# TABLE A.2d: RELIABILITY OF THE SATURN FAMILY

v	ehicie Name		Scout "Family"	
Data Collection Period		Vanguard	Scout	Combine
		57-59	60-88	57-88
Suci Rati	cess o: Mean 5% 95%	0.3388 0.1555 0.5723	0.9420 0.9023 0.9683	0.6404 0.1821 0.9744
	Stage 0			
	Stage 1/2			
NO.	Stage 1	0.8347	0.9917	
FAGE	Stage 2	0.5049	0.9875	
<i>o</i>	Stage 3	0.8039	0.9746	
	Stage 4		0.9870	
	Propulsion	0.7521	0.9793	
	Guidance	0.9174	0.9917	
EN	Flight Control	0.8347	0.9917	
YST	Structure			
07	Electrical		0.9876	
	Separation		0.9959	
	Other or (UK)	0.8347	0.9959	

## TABLE A.2e: RELIABILITY OF THE SCOUT FAMILY

V	chiele Name	STS
D٤	ata Collection	Space Shuttle
	Period	81-88
Suc Rati	cess o: Mean 5% 95%	0.9275 0.8147 0.9806
	Stage 0	
	Stage 1/2	
NO.	Stage 1	0.9275
AGE	Stage 2	
S	Stage 3	
	Stage 4	
	Propulsion	0.9275
	Guidance	
EM	Flight Control	
YST	Structure	
~~~	Electrical	
	Separation	
	Other or (UK)	

# TABLE A.2f: RELIABILITY OF THE SPACE SHUTTLE

#### 1.0 EXISTING METHODOLOGIES

For the purposes of this report, the following existing methodologies will be briefly discussed.

- Binomial
- Polynomial Curve Fitting
- Bayesian
- D. Lloyd's Method

#### 1.1 The Binomial Method

The "traditional," or classical, approach to reliability demonstration in a go/no-go type environment is the Binomial distribution shown below. In addition to the obvious constraints of the assumptions listed below, it is interesting to note, for example, that it would require 45 launches with <u>no</u> failures to demonstrate 0.95 reliability at 90% confidence. Since trials are assumed to be independent, the growth effect (a type of dependency) cannot be evaluated.

Stated mathematically the Binomial Distribution is as follows:

$$\sum_{X=S}^{N} {\binom{N}{N X}} R^{X} (1-R)^{N X} = 1 - C, \quad \text{if } N \le S \le 0$$

where;

- S = number of successful start tests
- N = number of trials
- R = reliability
- C = confidence level

where it is assumed that

- Trials or tests are independent
- · Each trial results in success or failure
- The reliability (probability of success) of each system is the same on each trial
- The number of tests is fixed in advance of the demonstration test

1.2 Polynomial Curve Fitting

Polynomial trends are of the form

 $Y = A + BX + CX^{2} + DX^{3} + ... JX^{k}$ 

The straight line is a special case having or if the first two terms on the right hald side of the equation. Generally speaking, it is unwise to fit a high-degree polynomial to the data because of the possibility of mixing trend and cycle. The polynomial can be forced to fit data quite closely by just adding enough terms. This, however, does not contribute any information about trend. In fact, 1 degree of freedom for error is lost for every parameter that is estimated from data. Thus, if there are n observations and n degrees of freedom are lost in fitting a polynomial of degree n-1 item, there are 0 degrees of freedom left for error!

#### 1.3 Bayesian Analysis

For the purposes of this report, Bayesian analysis can be divided into two categories:

1. Reduction of the number of tests or flights to demonstrate that a given level of reliability has been achieved.

#### 2. The Beta-Binomial Model

If it is desired to reduce the numbers of tests or flights required to demonstrate a given level of reliability, then Bayesian analysis can be useful. If the following equation, taken from reference 1, is solved for n at R=0.95, r=0, P=0.50 and C=90% confidence is desired, then it can be concluded that only 14 launches would be required.

$$C = \frac{1}{(1 - P)(1 - R)^{2} \int_{0}^{R} p^{n-r+1} q^{r} dp}$$

$$1 + \frac{(P)(R)^{2} \int_{0}^{1} p^{n-r} q^{r+1} dp}{(P)(R)^{2} \int_{0}^{1} p^{n-r} q^{r+1} dp}$$

where;

n = number of launches r = number of failures R = reliability C = contidence level P = Bayesian Prior

The Beta-Binomial Bayesian model is used for Bayesian estimation when information is available about components of similar design and application. In this model, several similar components are treated as a single class. The probability p of each component in the class is assumed to be constant, but will have different values from component to component. If the Binomial distribution is used to obtain the probability of K failures in n trials, then the conjugate distribution g(p) for the class is the Beta distribution. This model weights the reliability growth effect and can be applied to forecast the reliabilities of launch vehicles. The detailed theoretical analysis can be found in reference 2. The disadvantage of this model is that it is very difficult to separate the total sample data into several similar components unless there is detailed engineering analysis concerning each failure mode during the different periods of launch vehicle development history.

Bayesian approaches are highly sensitive to the prior distributions used. If no meaningful estimate of the prior probability of success can be made, none of the above conclusions apply. Particularly, one must be wary of consistent optimism or pessimism when records of success do not support the prior probabilities.

#### 1.4 D. Lloyd's Method

In Lloyd's model, the rationale is that when engineering corrective action for a failure is implemented, the probability of recurrence of that failure is reduced; therefore, such failures should not be carried as

full failures in subsequent reliability estimates. The failure value for each failure model is assumed to be

$$f = 1 - (1 - \gamma)^{1/n}$$

where  $\gamma$  is the confidence level and n is the number of successful tests after corrective action.

Based on a detailed engineering analysis for each failure mode, the result of each failure for each failure mode can be obtained by solving the above equation. The final result of the reliability estimation is  $R = 1 - \sum f/N$  where  $\sum f$  is the cumulative failure number of all failure modes and N = the test number.

This model weights the growth effect and can be extended to forecast the reliability, the failure mode and the launch number at which the failure mode occured as well as the launch number at which it was corrected. The confidence level  $\gamma$  is directly related to the final results and requires subjective judgement as to what value is to be used.

#### 2.0 A NEW STATISTICAL MODEL

The developmental history of any launch vehicle can be considered as two time periods - the early testing period and the performance period. Generally, during the early testing period the unreliability of a launch vehicle is high and unstable. After a "failure, analysis, and fix" process, in conjunction with technical and design improvements, the unreliability of a launch vehicle decreases and stabilizes in the performance period.

A statistical model which weights the reliabilities of these two periods has been developed. The detailed descriptions of the materials for reliability analysis of vehicles, stages, systems, and engines (or motors) are introduced in the following sections.

#### 2.1 Estimation of Launch Vechicle Reliability

The easiest way to estimate the average unreliability of a launch vehicle is:

$$U_{a} = F/L \tag{1}$$

where U<sub>a</sub> is the estimated average unreliability, and F and L are the cumulative failure and launch numbers.

As was mentioned before, the reliability growth effect must be considered to get a more realistic estimation of the unreliability. In the present model, the average unreliability is defined as

(3)

$$U = U_{a} - \Delta U \tag{2}$$

where  $\Delta U$  is the change in reliability caused by reliability growth and can be explained as

or

ΔΕ = ΔΟ • Γ

where  $\Delta F$  is the cumulative failure correction number.

 $\Delta U = \Delta F/L$ 

Averaging both sides of equation (3) results in

$$\overline{\Delta F} = \Delta U \cdot \frac{L}{2}$$
$$\Delta U = \frac{2}{L} \cdot \overline{\Delta F}$$
(4)

or

Substitute equation (1) and equation (4) into equation (2)

$$U = \frac{F}{L} - \frac{2}{L} \cdot \overline{\Delta F}$$
 (5)

The estimation of the unreliability of the launch vehicle at the nth launch can then be approximated as

$$U_{n} = \frac{F_{n}}{L_{n}} - \frac{2}{L_{n}} \cdot \frac{\sum_{i=1}^{N} \left(F_{i} - \frac{F_{n}}{L_{n}} \cdot L_{i}\right)}{N}$$
(6)

where  $L_i$  is the *i*<sup>th</sup> launch number, and  $F_i$  is the cumulative failure number at the *i*<sup>th</sup> launch.

The reliability R<sub>n</sub> at the n<sup>th</sup> launch is

$$R_{n} = 1 - U_{n} = 1 - \left[ \frac{F_{n}}{L_{n}} - \frac{2}{L_{n}} \cdot \frac{\sum_{i=1}^{N} \left(F_{i} - \frac{F_{n}}{L_{n}} \cdot L_{i}\right)}{N} \right]$$
(7)

The concepts of confidence levels based on the value of average reliability from equation (7) are now illustrated as the following.

Let N be the faunch number, then  $X = N \cdot R_n$  is the success number

5th confidence -

$$R_{0.05} = \frac{x}{x + (n - x + 1) F_{0.95}(2n - 2x + 2, 2x)}$$
(8)

95th confidence -

$$R_{095} = \frac{(x+1)F_{095}(2x+2,2n-2x)}{(n-x) + (x+1)F_{095}(2x+2,2n-2x)}$$
(9)

where  $F_r(n_1, n_2)$  is the 100 r<sup>th</sup> percentile of F-distribution with  $n_1$  numerator and  $n_2$  denominator degrees of freedom.

This completes the formulation of the launch vehicle reliability calculations. The example which applies this model is given in section 5.

#### 2.2 Estimation of Stage Reliability

The basic method of estimating the stage reliability of a launch vehicle in the present study is based on the following assumptions:

1. The failure of the launch vehicle must occur in one of its stages.

2. The starting operation time for each stage is followed by the order of stage number. In other words, the first stage should begin operating before the second stage.

The following formulation has been developed to perform the reliability estimation for the ith stage

$$R_{si} = 1 - \frac{F_{si} \cdot U_{v}}{F_{v} - (\sum_{j=1, j \le 1}^{i-1} F_{si}) \cdot U_{v}}$$
(10)

where  $R_{si}$  is the reliability of the i<sup>th</sup> stage,  $F_{si}$  is the cumulative failure number of the i<sup>th</sup> stage,  $F_v$  is the cumulative failure number of the launch vehicle,  $U_v$  is the unreliability of the launch vehicle from equation (6).

For example, the reliability for

First stage:  $R_{s1} = 1 - \frac{F_{s1} \cdot U_v}{F_v}$ Second stage:  $R_{s2} = 1 - \frac{F_{s2} \cdot U_v}{F_v \cdot F_{s1} \cdot U_v}$ Third stage:  $R_{s3} = 1 - \frac{F_{s3} \cdot U_v}{F_v \cdot (F_{s1} + F_{s2}) \cdot U_v}$ 

Since the value of  $U_v$  in equation (10) has been weighted, the estimation of reliability for each stage  $R_i$  is also a weighted average.

#### 2.3 Estimation of System Reliability

The basic assumption for the method of estimating system relaibility in the present study is that the failure of the launch vehicle must occur in one of its systems.

The average reliability of each system of the launch vehicle can be formulated as

$$R_{\text{sys}} = 1 - U_{\text{v}} \cdot F_{\text{sys}} / F_{\text{v}}$$

where  $R_{sysi}$  is the reliability of the i<sup>th</sup> system,  $F_{sysi}$  is the cumulative failure number of the i<sup>th</sup> system,  $U_v$  is the unreliability of the launch vehicle,  $F_v$  is the cumulative failure number of the launch vehicle.

(11)

#### 2.4 Estimation of Engine (or Motor) Reliability

The basic assumption of the method for estimating engine (or motor) reliability is if any of the engines (or motors) in a stage fails, then the entire stage has failed. Since the failure of a stage can be caused by either engine (or motor) failure or other failures, the cumulative failure number of engine (or motor) in this stage needs to be known. The model for estimating engine (or motor) reliability is described as

$$R_{ei} = (1 - U_{si} \cdot F_{ei} / F_{si})^{1/N_{ei}}$$

where

R<sub>ai</sub> is the reliability of the engine (or motor) in the i<sup>th</sup> stage.

 $U_{si}$  is the unreliability of the i<sup>th</sup> stage which can be obtained by 1-R<sub>si</sub> from equation (10).

F<sub>ai</sub> is the engine (or motor) cumulative failure number in the i<sup>th</sup> stage.

F, is the cumulative failure number of the ith stage.

 $N_{\rm ei}$  is the number of engines (or motors) in the  $i^{\rm th}$  stage.

#### 3.0 DATA COLLECTION

Based on the analysis of section 2, the following table for data collection of each launch vehicle was developed.

v	ehicle Name					
D	ata Collectio	n from	Yr t	o	Yr	
т	otal Launch	Number		. <u> </u>		
Т	otal Failure	Number				
Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Descrptn	Engine or Failure Y/N
	1					

#### Table A.3

In this table, <u>Date:</u> the date when the launch vehicle failed <u>Failure Launch:</u> the launch number at which the launch failed <u>Success Run:</u> the number of successful launches between two failures <u>Failure Stage:</u> failure stage number <u>Failure System:</u> one of the following systems failed: propulsion, separation, flight control, structure, electrical, guidance, etc... <u>Failure Description:</u> failure mode <u>Engine or Motor Failure Y/N:</u> Y = engine or motor failure; N = no engine or motor failure.

This table template was then applied to the history of all US Launch Vehicle Families according to given cut-off dates. The cut-off dates and the resulting historical tabulations are given in the supplement to this appendix.

#### 4.0 ALGORITHM

The general solution procedures of launch vehicle reliability analysis can be described by the following steps.

1. Use Table A.3 to collect the data for each launch vehicle.

2. From the date of "Failure Launch" listed in Table A.3, the launch vehicle reliability can be estimated by applying equation (7) in section 2.1. The corresponding 95th and 5th confidence levels can be obtained by solving equations (8) and (9) in section 2.1.

3. From the data of "Failure Stage" listed in Table A.3 and the launch reliability obtained in step 2, the reliability of each stage of the launch vehicle can be calculated by using equation (10) in section 2.2.

4. The date of "Failure System" together with the results of step 2 provide the information to obtain the reliability of each system in the launch vehicle by applying equation (11) in section 2.3.

5. From the data of "Engine (or Motor) Failure Y/N" listed in Table A.3 and the result of step 3, the reliabilities of each engine (or motor) can be obtained by solving equation (12).

#### 5.0 EXAMPLE

Consider the "Atlas/Centaur" as an example. The general information about the "Atlas/Centaur" is illustrated in the following figure which is taken from the report "Hazard Analysis of Commercial Space Transportation", Volume I, May 1988, published by the U.S. Department of Transportation.

Following the solution procedures described in section 4:

1. Table A.4 lists all the failure data on the "Atlas/Centaur", The data collection period is from 1962 to 1987. The launch number of the "Atlas/Centaur" during this period is 67, and the corresponding failure number is 11. In this example, the failure data was collected from the "Launch Vehicle Failure History Data Base," which was compiled by Cindy Thatcher Clague of the Aerospace Corporation (reference 4).

The March 26, 1987 failure, shown in Table A.4, which was caused by a lightning strike is considered as an externally caused failure. This failure is eliminated in the present reliability analysis otherwise all failures are included.

2. Based on the data in Table A.4, we used equation (7) in Section 2.1 to estimate the launch vehicle reliability. The estimation of the reliability for n=67 is

 $R_{n} = 0.9069$ 

The corresponding 95th and 5th confidence levels, obtained by solving equations (8) and (9), are

$$R_{0.05} = 0.8450$$
  
 $R_{0.95} = 0.9489$ 

3. From the "Stage Failure" data in Table A.4

The first stage is stage 1/2 and has the failure number  $F_{1/2} = 2$ . The second stage is stage 1 and has the failure number  $F_1 = 2$ . The third stage is stage 2 and has the failure number  $F_2 = 6$ .

The reliability of each stage can be obtained by solving equation (10). In this example, the unreliability of the vehicle is  $U_v = 1 \cdot R_v = 0.0931$ , and the cumulative failure number of the vehicle is  $F_v = 10$ . Substituting these values into equation (10), we get

 $R_{s1} = 0.9814$  for stage 1/2.  $R_{s2} = 0.9810$  for stage 1.  $R_{s3} = 0.9420$  for stage 2.

4. From the "System Failure" data in Table A.4

The failure number of the propulsion is 5. The failure number of the structure is 2. The failure number of the separation is 1. The failure number of the flight control is 1. The failure number of the electrical is 1.

## **General Dynamics**

Έ.



# <u>General Stage Data</u> Atlas Centaur Launch Vehicle

	Stage 1/2		Stage 1	Stage 2	
Stage Data			J		
Designation		Atlas	G	Centaur D-1A	
Stage Mass, klbm		320.67	15	38.777	
Usable Propellant, klbm		300.63	2	29.734	
Stage Length, ft		76.7		29.8	
Stage Diameter, ft		10		10	
Number of Engines	2		1	2	
Guidance Data					-
Manufacturer				Honeywell	
Type				Four Gimbal	
				Inertial	
Engine Data					
Manufacturer	Rocketdyne		Rocketdyne	Pratt and Whitney	<b>.</b>
Designation	YLR-89-NA-	.7	YLR-105-NA-7	RL-10A-3-3A	w
Number of Starts Possible	1		1	2	
Fuel	RP-1		RP-1	LN.	
Oxidizer	LOX		LOX	rox	
Mixture Ratio, O/F	2.25		2.22	5.0	
Average Thrust per Engine, lbf					
Sea Level	180,750		60,500		
Vacuum				16,500	
Average Chamber Pressure, psia	650		733	474	
Specific Impulse, sec					
Sea Level	259		220		•
Vacuum	292		312	446.4	
Total Burn Time, sec	153		283	404	
Nozzle Expansion Ratio	8		25	61	···- ··
Nozzle Exit Area, ft	11.24		11.56	8.22	
Engine Cant Angle, deg	0		0	0	
Thrust Vector Control	Gimballed E	Ingines	and Verniers	Gimballed Engine	• .

. .

-



## TABLE A.4: FAILURE HISTORY DATA OF ATLAS/CENTAUR

Vehicle Name: Data Collection from:62 to 87Total Launch Number:67.2 Total Failure Number: 11

1 1 1

المغدد المراجع

------

. . . .

Atlas/Centaur

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
05/08/62	1	0	2	Structure	Centaur upper stage structure failure	N
06/30/64	3	1	2	Propulsion	Centaur hydraulic failure, Loss of C <sub>2</sub> hydraulic power	N
03/02/65	5	1	1/2	Propulsion	Loss of Atlas thrust during liftoff, due to fuel starvation of booster engines stemming from closure of fuel prevelue	Y
04/07/66	7	1	2	Propulsion	Centaur restart sequence failure, engine ignition occurred but not sustained due to fuel deplation	N
08/10/68	16	8 .	2	Propulsion	Failure of boost pump H <sub>2</sub> O <sub>2</sub> supply system centaur didn't achieve its second main engine start	N
11/30/70	21	4	1	Separation	Nose fairing failed to jettison properly	N
05/08/71	23	1	2	Flight Control	Centaur pitch control lost	N
02/20/75	34	10	1	Electrical	Atlas booster section electrical disconnect failed during booster jettison	N
09/29/77	42	7	1/2	Propulsion	Atlas booster engine hot gas leak failed mission	Y
06/09/84	62	19	2	Propulsion	Failure occurred at A/C Separation a liquid oxygen tank crack	N
03/26/87	67	4		other	Lightning strike failed mission	N
					<u>.</u>	

154

ø

۳.

By solving equation (11), the reliability of each system can be obtained

5. There are two engines (YLR-89-NA-7) in stage 1/2, one engine (YLR-105-NA-7) in stage 1, and two engines (RL-10A-3-3A) in stage 2. From Table A.4, the failure number of engine YLR-89-NA-7 is 2. The failure number of engine YLR-105-NA-7 is 1, and the failure number of engine RL-10A-3-3A is 0. By solving equation (12) together with results of stage reliabilities, the reliabilities of each engine can be obtained.

The results of the reliability analysis for the "Atlas/Centaur" are summarized as

ATLAS/CENTAUR	RELIABILITY
Vehicle	
Mean	0.9069
5%	0.8450
95%	0.9489
Stages	
Stage 1/2	0.9814
Stage 1	0.9810
Stage 2	0.9420
System	
Propulsion	0.9535
Structure	0.9814
Separation	0.9907
Flight Control	0.9907
Electrical	0.9907
Enaines	
YLR-89-NA-7	0.9907
YLR-105-NA-7	0.9905
RL-10A-3-3A	No Failure

The reliability estimation of "Atlas/Centaur" based on equation (7) at each launch is described in the following figure, A.2.



Figure A.2. Reliability estimation of Atlas/Centaur.

#### 6.0 RESULTS

The statistical model (section 2) and the data collection method (section 3) following the solution procedures (section 4) have been applied to twenty-four U.S. launch vehicles. The results are listed in Table A.5.

In Table A.5, launch vehicles are separated into six groups based on their developmental histories. The results of the "Combine" in Table A.5 are the reliability estimates for each group. The following formulations, based on Bayesian reliability analysis, have been applied to perform the calculation for each group.

$$\mu = \frac{1}{N} \sum_{i=1}^{N} R_i$$

where N is the vehicle number in the group,  $R_i$  is the reliability of the i<sup>th</sup> vehicle,  $\mu$  is the mean reliability of the group.

$$\sigma^2 = \frac{1}{N-1} \sum_{i=1}^{N} (R_i - \mu)^2$$

where  $\sigma^2$  is the variance.

Let

$$b = \frac{\mu}{\sigma^2}(1 - \mu) + \mu - 1$$

 $a=\frac{\mu}{2}(1-\mu)-\mu$ 

Then the mean of the group is

$$\mu = a/(a+b)$$

The 5% confidence level is

$$R_{05} = \frac{a}{a + b \cdot F_{0.95}(2b, 2a)}$$

The 95% confidence level is

$$R_{095} = \frac{a \cdot F_{095}(2a, 2b)}{b + a \cdot F_{095}(2a, 2b)}$$

The reliability estimations for each engine of the launch vehicles are not listed in Table A.5. They are partially listed in the matrices which are for engine reliability analysis.

24

TABLE A.5: RELIABILITY COMPARISON OF U.S. LAUNCH VEHICLE FAMILIES

	-	har / Deli				Titen														สื	¥- E	, Andrew				Scout "F	-util	813
Venicie name Data Collection Period	2	8	-	ī	i	1	8	-	i	i	ů I	Ĵ	, ,	ž j	73	× 0	-3 . ±	J	7		8	<u></u>	8		5	006 000	5	66
	<b>8</b> +6	80-47	23- <b>62</b>	8	2 3	19-11	19-09	546	97 - 15	8 2	3	17-95	3	17 19	1.43	1	19-62	6.67	; \$\$	3 8	<b>9</b> 19	265	1. 2 L	*	5 2	50 ( <del>1</del> 0 G	8/9	8
Buccese	8	20140	38 KG ()	-	ł	0.940	922.0	1040	0.219	100	12	1	2	1	8	2	-	8	7863	30 11	8 8	2		20 22	47 03	000	310	2.280
Ratio: Mean St	92/30	0.910	0.6786	1	12190	0.9056	0.4978	0.8075	0.1627	0.3010	246	TROIS (	New York	3	-	6 SII3	6213 0	9450	0 1927	1026 0.2	8	3	10	180 0.26	6 20	80	2010	1 0.00
*58	19160	0.0615	0.6661	20220	2000	0.0651	09990	\$990	0.0077	0.7866	0.8565	HCLING	9		2598.0		a	-	0	10 C	2		98	0.00	70 52		-180 0	0990
Stage ()	O SPEED	0 9000					0.007.0								$\vdash$			$\vdash$	$\vdash$		H	Н	Η	$\square$	Η			
C Stage 1/2												°	513	5	1998		0	1914										
N Stage 1	0 8046	0 2000	Ē	1001	1 2674		10-02		-			l°-	5	8	8178		ō	961 0		8	R			_	<b>.</b> 10	1980 D		1736 0
~ ~ 386e ~	0 5794	0.9746		240	-	0978.0								•	99296		Ó	22.14	0	741 0.75	8		100	8	17 O	1960 944	-	
Stage 3	0 9877	0 9843				29960														Nυ	8		80	8	40	CD 0.074	_	_
8 <b>10</b> 00 4																			ó	290 060	g					0.967		
Propulaion	0.9564	0.5001		0,072	00000	200	0.73665	Ť	1	7 8087			8713 G	8212 0	1 See		•	838	ö	0.03	$\left  - \right $	$\left  \right $			<i>к</i> о	28 V		728.0
Guidence	0.9620	0.9860		Ť	8	39960				-			1.00	1											90	74 0.961	,	
Elight Control	0 9907	1988		Ť	19656	34050						Å	8	0	No.		0	<b>2007</b>							*	47 0961		
Structure	0.000			2016.90		0.00			The second second second second second second second second second second second second second second second se				LSS				•	1180										_
S Electrical	0 9815	0 9860			29629							•	15	0	100		0	1000								0.967	_	_
Beparadon	88680	0 9660		ř	-									đ	ā		đ	100	ō	741					_	8	_	_
Other or (UK)	0 9923													N.W											9.6	0000	_	_

158

~

**4**81;

#### 7.0 CONCLUSIONS

A new model has been developed which has the following advantages:

1. This model weights the reliability growth effect. Since the reliability of a launch vehicle can be estimated from each past launch, the extension of this model should be able to predict the future reliability of the launch vehicle.

2. The formulations of the model are simple and easy to apply. A computer program is being developed for future applications.

3. The results of the calculations are only dependent on the data collection.

4. The reliability estimations of vehicles, stages, systems, and engines are separated, which reduces the restrictions to the data collection.

#### BIBLIOGRAPHY

1. "Why Bayes is Better" by A. J. Bonis from the 1975 Proceedings of the Annual Reliability and Maintainability Symposium (Including notes taken from Dr. Bonis' lectures at the Eleventh Annual Reliability Engineering and Management Institute, November 11-20, 1973, University of Arizona.)

2. "Bayesian Reliability Analysis", H. F. Martz and R. A. Waller, John Wiley and Sons 1982.

3. "Techniques for Reliability Assessment and Growth in Large Solid Rocket Motor Development" by D. K. Lloyd et. al., AIAA Paper Number 67-435, Presented at AIAA 3rd Propulsion Joint Specialist Conference, Washington, D.C., July 17-21, 1967.

4. "Launch Vehicle Reliability Study Data Base" compiled by C. T. Clague of Aerospace Corporation as transmitted to G Platt of Marshall Space Flight Center in a memo dated July 18, 1988.

5. A Historical Look at United States Launch Vehicles 1967- Present, March 1988, Space Technology Division, Note STDN 88-3, ANSER

6. Hazard Analysis of Commercial Space Transportation, Volume I, May 1988, U.S. Department of Transportation.

7. Launch Vehicle Flight Failure Data Base, July 18, 1988. Cindy Thatcher Clague, The Aerospace Corporation.

8. Final Report of the Aerospace Independent Atlas E/F Review Team, Volume III Historical Data, January 29, 1982.

# Appendix A.4

History of US Launch Vehicles

# Cut-off dates for launch vehicle reliability data

Launch vehicle	Cut-off date	Failure No.	Launch No.
<u>Thor/Delta</u> Thor Delta	01/25/57 - 08/05/83 05/13/60 - 03/20/87	66 12	369 181
<b>Titan</b> Titan I Titan II Titan 1II Titan 34D	02/06/59 - 03/05/65 03/16/62 - 06/27/76 09/01/64 - 02/11/87 10/30/82 - 11/28/87	24 16 11 2	68 94 137 11
Atlas Atlas A Atlas B Atlas C Atlas D Atlas D Atlas E Atlas F Atlas SLV Atlas G Atlas H Atlas/Centaur	06/11/57 - 06/03/58 07/19/58 - 02/04/59 12/23/58 - 08/24/59 04/14/59 - 11/07/67 10/11/60 - 02/03/88 08/08/61 - 06/23/81 02/02/67 - 05/19/83 06/09/84 - 03/26/87 02/09/83 - 05/15/87 05/08/62 - 03/26/87	5 4 3 42 18 17 4 0 0 10	8 9 6 197 49 96 73 5 5 67
Saturn "Family" Jupiter Juno Saturn I Saturn IB Saturn V	07/26/58 - 10/23/58 12/06/58 - 05/24/61 10/27/62 - 07/30/65 02/26/66 - 07/15/75 11/09/67 - 05/14/73	3 5 0 0 1	6 10 10 9 13
Scout "Family" Vanguard Scout	12/06/57 - 09/18/59 07/01/60 - 03/25/88	8 14	11 110
Space Shuttle	04/12/81 - 09/29/88	1	26

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
01/25/57	1	0	1	Propulsion	Missile fell back on launcher, oxygen start tank fill and check valve malfunction	Y
04/19/57	2	0	1	Human	Erroneously destroyed by RSU	N
05/21/57	3	0	2	Structure	Fuel tank ruptured	N
08/30/57	4	0	1	Propulsion	Propellant valve pneumatic line failure	Y
10/03/57	6	1	1	Electrical	Microswitch failure in MFV delayed signal to gas generator valve opening	N
10/11/57	7	0	1	Propulsion	Possible turbopump failure	Y
12/07/57	9	1	1	Electrical	Electrical systems malfunction, no main engine cutoff	N
01/28/58	11	1	1	Guidance	Excessive trajectory dispersion after 95 sec. terminated by RSO	N
02/28/58	12	0	1	Propulsion	Premature shutdown, failure of gas generator LRRP or liquid ox line	Y
04/19/58	13	0	1	Propulsion	Fell back on launcher due to fuel system malfunction	Y
04/23/58	14	0	1	Propulsion	Turbopump failure	Y
07/13/58	18	3	1	Electrical	Main engine cutoff failed to get through circuit problem	N
07/26/58	20	1	1	Structure	Pneumatic line failure caused MLV closure missile broke up due to aerodynamic forces	N
08/17/58	22	1	1	Propulsion	First stage malfunction, Turbopump failure	Y
11/05/58	24	1	1	Guidance	Autopilot malfunction	N

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
11/08/58	25	0	3	Propulsion	3rd stage failed to ignite	Y
12/05/58	27	1	1	Propulsion	Liquid oxygen tank pressurization malfunction	N
12/30/58	30	2	1	Guidance	Guidance malfunction at liftoff	N
01/21/59	31	0	1	Propulsion	Exploded on pad. A malfunction during countdown	N
01/23/59	32	0	2	Electrical	Electrical malfunction prevented cutoff and 2nd stage Ignition	N
01/30/59	33	0	1	Propulsion	Liquid oxygen tank pressurization problem	N
06/03/59	47	14	3	Propulsion	Premature engine burnout due to fuel exhaustion, Insufficient velocity was gained for orbital attainment	Y
06/16/59	49	1	1	Guidance	Autopilot did not program possibly liftoff switch didnot extract	N
06/25/59	51	1	2	Electrical	A diode failure in the D-timer brake circuit caused the Agena engine to burn to fuel exhaustion	N
06/29/59	52	0	1	Electrical	Electrical malfunction R/V did not separate retro-rockets did not fine	N
07/21/59	53	0	1	Flight Control	Flight controller did not program; Launcher arm did not extract liftoff pin	N
08/14/59	60	6	1	Propulsion	Fuel depletion, fuel underload, leak or engine miscalibration	Y
09/17 <i>/</i> 59	65	4	2	Separation	2nd stage retro device failed, 3rd stage did not ignite	N
12/01/59	77	11	1	Propulsion	Main engine cutoff occurred 6 sec. early. Possibly main liquid oxygen valve closed prematurely	Y
12/14/59	79	1	1	Flight Control	Control failure, Missile stability lost	N

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
02/04/60	83	3	1	Electrical	Failure of the fuel injector pressure switches or a short around them	N
02/19/60	86	2	1	Guidance	Autopilot component failure	N
06/29/60	94	7	2	Guidance	2nd stage attitude instability	N
08/18/60	97	2	1	Propulsion	Failure of the first stage hydraulic system	Y
10/26/60	101	3	2	Separation	2nd stage failed to separate	N
11/30/60	103	1	1	Electrical	Main engine shutdown from a premature MECO signal	N
03/30/61	111	7	3	Propulsion	A hydraulic system failure resulted in lose of attitute control	Y
06/08/61	113	1	3	Propulsion	Fuel line leak, Engine failed to provide thrust	Y
07/21/61	118	4	1	Flight Control	Control system instability	N
08/03/61	119	0	2	Flight Control	A failure occurred in the hydraulic system which provides the power for engine gimballing	N
10/23/61	125	5	1	Propulsion	Hydraulic failure and a failure in the engine actuating system	Y
11/05/61	126	0	3	Guidance	Apogee was higher than predicted as a result of excess velocity	N
01/13/62	131	4	2	Electrical	Blew a fuse in the line to the gyro guidance packages	N
01/24/62	133	1	2	Propulsion	2nd stage misfired, An acutator lug on the 2nd stage thrust chamber was broken	Y
02/21/62	134	0	1	Propulsion	The fuel vent valve stuck open during first burn	Y

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
03/19/62	136	1	1	Guidance	Pitch HIG gyro malfunction	N
05/10/62	140	3	1	Electrical	Failure of the 1st and 2nd stages to separate which was caused by 1st stage electrical malfunction	N
06/20/62	147	6	1	Propulsion	High temps weakened the load-carrying capabilit of the Thor engine section	N
07/25/62	153	5	1	Propulsion	The main oxidizer valve only partially opened	N
10/15/62	162	8	1	Propulsion	The actuator potentionmeter voltage show a continuing loss of power	Y
02/28/63	174	11	0	Propulsion	Solid motor failure	Y
03/18/63	175	Ū	2	Electrical	Electrical short circuit in the safe-arm junction box	N
04/26/63	177	1	3	Guidance	Failure in horizon sensors	N
06/12/63	179	1	1	Propulsion	During 1st engine operation a power short condition developed, igniters were set off by radiated heat from the nozzle	Y
11/09/63	191	11	1	Propulsion	overheating of the boattail section	Y
11/10/63	192	0	1	Flight Control	Unstable and premature termination of powered flight	N
03/24/64	203	10	2	Electrical	Electrical short circuit, loss of guidance and control	N
04/21/64	204	0	UK	Flight Control	Failure of flight control	N
04/27/64	206	1	UK	UK	UK	UK
05/28/64	207	0	UK	UK	UK	UK

166

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
09/02/65	250	42	UK	Guidance	Guidance failure, destroyed by RSO	N
01/06/66	260	9	2	UK	Failed to orbit	UK
05/03/66	269	8	2	Propulsion	Fire in thrust section due to leakages	Y
05/18/68	301	31	1	Guidance	Gyro failure, Booster guidance malfunction	N
02/17/71	335	33	1	Propulsion	Exploded after 40 sec.	UK
02/18/76	354	18	UK	UK	UK	UK

Vehicle Name:	Delta		
Data Collection from:	60 to 87		
Total Launch Number:	181		
Total Failure Number:	12		

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
05/13/60	1	0	2	Flight Control	2nd stage attitude control malfunction, No 3rd stage ignition	N
03/19/64	24	22	3	Propulsion	Loss of 3rd stage halfway thru burn	Y
08/25/65	33	8	3	Propulsion	3rd stage ignition before separation, Did not achieve orbit	N
09/18/68	59	25	1	Guidance	1st stage control system (rate gyro)	N
07/25/69	71	11	3	Propulsion	3rd stage (AKM) thrust dropped during burn possibly nozzle blown off	Y
<b>08/2</b> 7/69	73	1	1	Propulsion	1st stage hydraulic system failure	Y
10/21/71	86	12	2	Flight Control	2nd stage control gas oxidizer vent valve failure, leak	N
07/16/73	96	9	2	Propulsion	2nd stage hydraulic system pump motor failure	Y
01/19/74	100	3	2	Flight Control	2nd stage electronics failure	N
04/20/77	130	29	2	Separation	Clamp band released early	N
09/13/77	134	3	0	Propulsion	SRM (Castor IV) burn-through	Y
05/03/86	178	43	1	Electrical	1st stage electrical short in relay box (main engine shutdown)	N

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
08/14/59	5	4	1	Structure	Vibration fired holddown bolts: 1B1E pulled causing shutdown	N
12/12/59	6	0	1	Propulsion	Failure on pad: destruct system	UK
02/05/60	8	1	1	Structure	Failure at T+43 sec.	N
03/08/60	10	1	UK	UK	UK	UK
04/08/60	12	1	UK	UK	UK	UK
07/01/60	18	5	1	Propulsion	Failure at stage I hydraulics	Y
07/28/60	19	0	1	Propulsion	Stage I premature shutdown	UK
08/10/60	20	0	UK	UK	UK	UK
09/29/60	23	2	UK	UK	UK	UK
12/03/60	26	2	1	UK	Vehicle destroyed	UK
12/20/60	27	0	2	Propulsion	No stage II ignition	υκ
01/20/61	28	0	2	Propulsion	No stage II ignition	UK
03/02/61	31	2	2	UK	Premature stage II shutdown	UK
03/31/61	33	1	1	UK	Premature stage I shutdown	UK
06/23/61	36	2	2	UK	Premature stage II shutdown	UK

Vehicle Name:	Titan I
Data Collection from:	59 to 65
Total Launch Number:	68
Total Failure Number:	24

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
12/15/61	49	12	2	Propulsion	No stage II ignition	UK
01/20/62	50	0	2	Propulsion	No stage II ignition	UK
02/23/62	52	1	2	Propulsion	No stage II ignition	UK
05/01/63	60	7	1	Propulsion	Failure at liftoff	UK
07/16/63	61	0	2	Propulsion	No stage II ignition	UK
08/30/63	63	1	1	Propulsion	Gas generator shutdown	Y
12/08/64	66	2	2	UK	Stage II prel. shutdown	UK
01/14/65	67	0	2	Propulsion	No stage II ignition	UK
03/05/65	68	0	1	Propulsion	Propellant depletion	Y

Vehicle Name:Titan IIData Collection from:62 to 76Total Launch Number:94Total Failure Number:16

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
06/07/62	2	1	2	Propulsion	Stage II gas generator oxidizer injection blocked	Y
07/25/62	4	1	2	Propulsion	Stage II fuel pump leak downstream of TCV failure due to combustion instability	Y
12/06/62	8	3	2	Propulsion	Stage II oxidizer bootstrap line failure	Y
01/10/63	10	1	2	Propulsion	Gas generator oxidizer injector blocked	Y
02/16/63	13	2	1	Separation	Umbilicals failed to disconnect properly	N
04/19/63	15	1	2	Propulsion	Bootstrap premature shutdown	Y
05/09/63	17	1	2	Propulsion	OX leak, Premature shutdown of stage II 10% loss of stage II oxidizer during S II flight	N
05/29/63	20	2	1	Propulsion	Subassembly 1 thrust chamber fuel valve leak occurred at engine ignition	Y
06/20/63	21	0	2	Propulsion	Gas generator oxidizer injector clogging	Y
04/30/65	45	23	1	Propulsion	Subassembly / shutdown abruptly and vehicle flight continued erratically, Turbopump failure	Y
06/14/65	48	2	1	Flight Control	Loss of vernier nozzle	N
09/21/65	54	5	2	Electrical	Premature shutdown of stage II, bad connector coupled with a surge in the AOS power	N
11/30/65	57	2	1	Propulsion	Fuel leak, possibly at cross-over manifold with resultant thrust vectoring	Y
12/22/65	60	2	2	Human (Guidance)	Control of record stage lost following staging Probably due to technician reading wrong scale	N
05/24/66	67	6	1	Separation	No r/v Separation	N

Vehicle Name:	Titan II
Data Collection from:	62 to 76
Total Launch Number:	94
Total Failure Number:	16

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
04/12/67	69	1	2	Flight Control	Stage II yaw rate gyro	N

Vehicle Name:Titan IIIData Collection from:64 to 87Total Launch Number:137Total Failure Number:11

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
09/01/64	1	0	3	Propulsion	Premature transtage cutoff, Pressure system failure	Y
10:15/65	6	4	3	Propulsion	Propellant freezing in stage III engine bi-prop valve engine failed to shutdown	Y
12/21/65	7	0	3	Flight Control	ACS engines failed to shutdown after vernier burn loss of attitude control	N
08/26/66	10	3	0	Structure	P/L fairing failure during SRM flight	Y
04/26/67	16	5	2	Propulsion	Stage II engine thrust dropped to 1/2 nominal gross contamination on Martin side of interface	Y
11/06/70	48	31	3	Guidance	IGS-IMU failure, The electronic suspension of the IMU shorted out	N
02/11/74	75	26	3	Propulsion	Centaur stage failed to start after separation, failure of LO <sub>2</sub> boost pump	N
05/20/75	85	9	3	Guidance	IMU failed, Internally shorted transistor	N
09/15/7€	99	13	2	Propulsion	Engine failed to shutdown on command burned to completion, hard contaminant in fuel valve	Y
09/05/77	106	6	2	Propulsion	Low velocity at stage II shutdown	Y
03/25/78	110	3	2	Propulsion	Turbine drive hydraulic pump failure after ignition	Y

Vehicle Name:Titan 34DData Collection from:82 to 87Total Launch Number:11Total Failure Number:2

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
08/28/85	8	7	1	Propulsion	Stage I engine shutdown prematurely-massive leak shortly after ignition	Y
04/18/86	9	0	0	Propulsion	Insulation/case debond vehicle disintegrated at T+8.764 the first explosive flash was noted	Y
1						
Vehicle Name:	Atlas A					
-----------------------	----------					
Data Collection from:	57 to 58					
Total Launch Number:	8					
Total Failure Number:	5					

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
06/1 i /57	1	0		Structure		
09/25/57	2	0		Structure		
02/07/58	5	2		Flight Control		
02/20/58	6	0		Flight Control		
04/05/58	7	0		Propulsion		

Vehicle Name:	Atlas B
Data Collection from:	58 to 59
Toial Launch Number:	9
Total Failure Number:	4

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
07/19/58	1	0		Flight Control		
09/18/58	5	3		Propulsion		
11/17/58	6	0		Propulsion		
01/15/58	8	1		Propulsion		

Vehicle Name:	Atlas C
Data Collection from:	58 to 59
Total Launch Number:	6
Total Failure Number:	3

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
01/27/59	2	1		Guidance		
02/20/59	3	0		Propulsion		
03/18/59	4	0		Propulsion		
			_			

Vehicle Name:	Atlas D
Data Collection from:	59 to 67
Total Launch Number:	197
Total Failure Number:	42

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
04/14/59	1	0		Propulsion		
05/18/59	2	0		Propulsion		
06/06/59	3	0		Propulsion		
09/09/59	6	2	1/2	Electrical	Electrical signal to initiate separation did not reach the pyrotechnic cartridges	N
09/16/59	8	1		Propulsion	Hydraulic failure	
01/26/60	19	10		Guidance		
03/10/60	23	3		Propulsion		
04/07/60	24	0		Propulsion		
05/06/60	26	1		Flight Control		
06/22/60	30	3		Electrical		
07/02/60	32	1		Electrical		
07/22/60	33	0		Flight Control		
07/29/60	34	0		Structure	Static or dynamic loads, higer than could be predected, rupture of LOX tank	N
09/12/60	37	2		Propulsion		
09/29/60	41	0		Electrical		

Vehicle Name:Atlas DData Collection from:59 to 67Total Launch Number:197Total Failure Number:42

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
10/12/60	43	1		Propulsion		
12/15/60	47	3	1	Structure	Rupture in the missile LOX tank	Ŷ
04/25/61	52	4	1/2	Flight Control	Unsatisfactory due to a failure in the flight control system	N
09/09/61	57	4	1/2	Electrical	Failure of the ground power umbilical to eject normally at liftoff	N
10/21/61	59	1	1/2	Guidance	roll control was lost	N
11/22/61	61	1	1/2	Flight Control	Booster pitch control lost	N
12/22/61	65	3	2	Flight Control	Sustainer engine failed to cutoff	N
01/26/62	68	2	1/2	Guidance	Failure of Mod III G Guidance system	N
02/21/62	71	2		Propulsion		
04/09/62	74	2	2	Electrical	Electrical failure, excess altitude and under- velocity condition	N
07/22/62	£7	12	2	Guidance	Failure of engine burning time	N
10/02/62	92	4		Electrical		
12/17/62	98	5	1	Propulsion	Thrust chamber oscillation	Y
01/25/63	100	1		Structure		
03/09/63	104	3		Flight Control		

Vehicle Name:	Atlas D
Data Collection from:	59 to 67
Total Launch Number:	197
Total Failure Number:	42

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
03/15/63	106	1		Propulsion	Hydraulic failure	
03/16/63	107	0		Flight Control		
06/12/63	111	3	1/2	Propulsion	Booster hydraulic accumulater failure, Exploded just after launch	Y
09/06/63	117	5		Propulsion	Hydraulic failure	
09/11/63	118	0		Propulsion		
10/07/63	119	0		Propulsion		
11/13/63	123	3		Propulsion	Hydraulic failure	
01/21/65	149	25		Propulsion	Injection failure, no separation	Y
03/02/65	153	3	1/2	Propulsion	Stage failed due to loss of thrust	Y
05/27/65	159	5	1/2	Propulsion	Booster exploded	Y
03/04/66	175	15	1/2	Flight Control	Failure of sustainer low pressure hydraulic system at booster jettison	N
05/03/66	179	3	UK	UK	UK	UK

Vehicle Name:Atlas EData Collection from:60 to 88Total Launch Number:49Total Failure Number:18

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
10/11/60	1	0	1/2	Guidance	Nitrogen control-gas was broken off, causing control-gas depletion	N
11/29/60	2	0	1	Propulsion	Loss of sustainer engine hydraulic pressure	Y
01/24/61	3	0	1	Flight Control	Lost vehicle stability	N
03/13/61	5	1	1	Flight Control	Premature shutdown of the sustainer engine due to fuel depletion	N
03/24/61	6	0	1/2	Flight Control	Control bottle helium was depleted during boost phase and the booster package was not iettisoned	N
06/07/61	9	2	1/2	Propulsion	Combustion instability in B1 thrust chamber	Y
06/22/61	10	0	1/2	Flight Control	Excessive pitchover rate during boost phase	N
09/08/61	13	2	1	Propulsion	Sustainer engine shutdown shortly after jettison of the booster section	Y
11/10/61	16	2	1	Propulsion	Sustainer engine shutdown during main stage transition	Y
02/28/62	20	3	UK	Structure	UK	UK
07/13/62	21	0	1	Propulsion	LOX leak during flight, failure of slow-closing propellant valve	Y
12/18/62	22	0	1/2	Propulsion	Booster engine shutdown due to loss of lube oil	Y
07/26/63	26	3	1	Electrical	Spurious voltage transients on range safey cutoff circuitry	N
09/25/63	29	2	1	Propulsion	Sustainer hydraulic system failed at staging	Y
02/12/64	30	0	1	Guidance	Guidance failure in premature engine cutoffs	N

Vehicle Name:	Atlas E
Data Collection from:	60 to 88
Total Launch Number:	49
Total Failure Number:	18

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
08/27/64	32	1	UK	Guidance	Radial impact error BB NM short, GD/A did not perform an analysis	N
12/08/80	36	3	1/2	Propulsion	Booster engine nol 2 shutdown prematurely, due to loss of oil	Y
12/18/81	37	0	1/2	Propulsion	Propulsion B1 GG burn through	Y
						· 

Vehicle Name:Atlas FData Collection from:61 to 81Total Launch Number:96Total Failure Number:17

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
12/12/61	3	2	1	Guidance	The ARMA guidance system computer mal- functioned. Engine cutoff 4 sec early	N
12/20/61	4	0	1	Propulsion	Loss of sustainer hydraulic pump iniet pressure	Y
04/09/62	5	0	1	Propulsion	The sustainer lox turbopump was destroyed by an internal overpressure	Y
08/10/62	7	1	1	Flight Control	Missile failed to roll to the planned target azimuth	N
11/14/62	12	4	1	Guidance	Guidance computer malfunctioned	N
03/23/63	17	4	UK	UK	Missle self-destructed at 91 sec.	JK
10/03/63	19	1	1/2	Propulsion	B1 Main fuel valve failed to open	Y
10/28/63	20	0	1	Propulsion	Sustainer hydraulic return system failed	Y
04/03/64	23	2	1/2	Propulsion	Thrust imbalance due to B1 main fuel valve sticking	Y
08/08/66	29	5	1/2	Propulsion	Abnormal operation of B2 engine caused high fuel and iow LOX usage, partial blockage of the B2 LOX high pressure system	Ŷ
10/11/66	30	0	1/2	Propulsion	Fuel starvation of B1 engine due to malfunction of B1 engine fuel prevalve	Y
10/27/67	39	8	1/2	Propulsion	Loss of vehicle stability caused by small leak in booster hydraulic high pressure system	Y
05/03/68	45	5	1	Flight Control	Divergent oscillations of booster pitch control	N
11/06/68	52	6	1	Propulsion	Vernier engine hydraulic pressure lost after SECO	Y
10/10/69	58	5	1	Propulsion	Sustainer and vernier engines shutdown prematurely	Y

Vehicle Name:	Atlas F		
Data Collection from:	61 to 81		
Total Launch Number:	96		
Total Failure Number:	17		

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failu <i>re</i> Description	Engine/Motor Failure Y/N
04/12/75	80	21	1	Propulsion	Damaged thrust section allowed overheating and premature shutdown of the sustainer and vernier engines	Y
05/29/80	95	14	1/2	Propulsion	B1 engine performance was 79% of nominal and injection time was late	Y
· ·						

Vehicle Name:	Atlas SLV
Data Collection from:	67 to 83
Total Launch Number:	73
Total Failure Number:	4

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
11/30/70	26	25	2	Separation	Nose fairing failure to jettison	N
12/04/71	30	3	1	Flight Control	Lost attitude control E pack	N
02/20/75	42	11	1	Electrical	Electrical disconnect failure during Atlas boost separation	N
09/29/77	52	9	1/2	Propulsion	Hot gas leak in the booster gas generator	Y

Vehicle Name:AtData Collection from:84Total Launch Number:6Total Failure Number:1

Atias G 84 to 87 6

Date	Failure Launch	Success Run	Failurc Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
03/26/87	6	5		Other	Lightning struck vehicle	N

Vehicle Name:Atlas HData Collection from:83 to 87Total Launch Number:5Total Failure Number:0

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
			'			
			· · · · · · · · · · · · · · · · · · ·			

Vehicle Name:Atlas/CentaurData Collection from:62 to 87Total Launch Number:67Total Failure Number:11

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
05/08/62	1	0	2	Structure	Centaur upper stage structure failure	N
06/30/64	3	1	2	Propulsion	Centaur hydraulic failure, Loss of $C_2$ hydraulic power	N
03/02/65	5	1	1/2	Propulsion	Loss of Atlas thrust during liftoff, due to fuel starvation of booster engines stemming from closure of fuel prevelue	Y
04/07/66	7	1	2	Propulsion	Centaur restart sequence failure, engine ignition occurred but not sustained due to fuel deplation	N
08/10/68	16	8	2	Propulsion	Failure of boost pump H <sub>2</sub> O <sub>2</sub> supply system centaur didn't achieve its second main engine start	N
11/30/70	21	4	1	Separation	Nose fairing failed to jettison properly	N
05/08/71	23	1	2	Flight Control	Centaur pitch control lost	N
02′20/75	34	10	1	Electrical	Atlas booster section electrical disconnect failed during booster jettison	N
09/29/77	42	7	1/2	Propulsion	Atlas booster engine hot gas leak failed mission	Y
06/09/84	62	19	2	Propulsion	Failure occurred at A/C Separation a liquid oxygen tank crack	N
03/26/87	67	4		other	Lightning strike failed mission	N
			· · · · · ·			· ·

Vehicle Name:JupiterData Collection from:58 to 58Total Launch Number:6Total Failure Number:3

Engine/Motor Failure Success Failure Failure Failure Date Failure Y/N Launch Run Stage System Description 03/05/58 4 Propulsion 4th stage failed to ignite Y 2 1 08/28/58 5 2 2 Separation Booster burned into remaining stage upper Ν stage fired in wrong direction 10/23/58 6 0 2 Separation 2nd stage failed to fire premature separation Ν

Vehicle Name:	Juno
Data Collection from:	58 to 61
Total Launch Number:	10
Total Failure Number:	5

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
07/16/59	3	2	UK	Guidance	Guidance failed, destroyed by RSO	N
08/14/59	4	0	1	Propulsion	Booster fuel depletion	Y
03/23/60	6	1	3	UK	Ignition malfunction	UK
02/24/61	8	1	2	UK	2nd stage malfunction	UK
05/24/61	10	1	2	UK	2nd stage failed to ignite	UK

Vehicle Name:Saturn IData Collection from:62 to 65Total Launch Number:10Total Failure Number:0

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
· · · · · · · · · · · · · · · · · · ·						

Vehicle Name.Saturn IBData Collection from:66 to 75Total Launch Number:9Total Failure Number:0

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N

Vehicle Name:Saturn VData Collection from:67 to 73Total Launch Number:13Total Failure Number:1

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
04/04/68	2	1	2 3	Propulsion	Second stage engine malfunction Third stage failure to restart	Y

Vehicle Name:VanguardData Collection from:57 to 59Total Launch Number:11Total Failure Number:8

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
12/06/57	1	0	1	Propulsion	First stage lost thrust, exploded after 2 second	Y
02/05/58	2	0	1	Flight Control	First stage control system malfunction after 57 sec	N
04/28/58	4	1	2	Propulsion	Bad 2nd stage shutdown preventing 3rd stage firing	Y
05/27/58	5	0	3	Flight Control	Improper 3rd stage trajectory loss of attitude control	N
06/26/58	6	0	2	UK	Early 2nd stage shutdown prevented 3rd stage firing	UK
09/26/58	7	0	2	UK	Below minimum 2nd stage performance prevented orbit	UK
04/14/59	9	1	2	Guidance	Loss of 2nd stage pitch control	N
06/22/59	10	0	2	Propulsion	Low tank pressures after 2nd stage ignition caused instability	Y
			,			

Vehicle Name:ScoutData Collection from:60 to 88Total Launch Number:110Total Failure Number:14

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
12/04/60	3	2	2	Electrical	Failed to ignite: Caused by wire break or disconnected power input	N
06/30/61	5	1	3	Propulsion	Improper venting causing ignition leads to be severed	Y
08/25/61	6	0	4	Separation	Diaphragm separation system failure	N
11/01/61	8	1	1	Guidance	Guidance failure destroyed by RSO after 30 sec	N
04/26/62	11	2	3	Guidance	Control was lost due to H <sub>2</sub> O <sub>2</sub> not being available	N
05/23/62	12	0	2	UK	2nd stage shock input all three axes 0.29 sec aiter ignition	UK
04/05/63	18	5	3	Flight Control	3rd stage reaction control system failure	N
04/26/63	19	0	3	Electrical	short circuit in the destruct system, attitude control was lost	N
07/20/63	23	3	1	Propulsion	stage I engine nozzle failure	Y
09/27/63	24	0	4	Flight control	Pitch motor failure, loss of vehicle control	N
06/25/64	28	3	2	Electrical	Linear shaped destruct charge was ignited by an unplanned electrical input	N
01/31/67	51	22	4	Propulsion	Motor graphite nozzle insert resulted in rupture of the motor case	Y
05/29/67	56	4	3	Propulsion	Failure of motor caused by unstable chumber pressure	Y
12, J5/75	94	37	3	Propulsion	3rd stage nozzle failure	Y

Vehicle Name:Space ShuttleData Collection from:81 to 88Total Launch Number:26Total Failure Number:1

Date	Failure Launch	Success Run	Failure Stage	Failure System	Failure Description	Engine/Motor Failure Y/N
01/28/86	25	24	0	Propulsion	Vehicle exploded 73 sec. after launch-SRM O-ring failure	Y