

TECHNICAL REPORT BRL-TR-3058

BRL

AD-A214 380

**EPIC-2 CALCULATED IMPACT LOADING HISTORY
FOR FINITE ELEMENT ANALYSIS
OF BALLISTIC SHOCK**

ENNIS F. QUIGLEY

DECEMBER 1989

S DTIC ELECTE D
NOV 17 1989
B

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

**BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

89 11 16 140

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commerial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OIMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-TR- 3058		
6a. NAME OF PERFORMING ORGANIZATION US Army Ballistic Research Laboratory			6b. OFFICE SYMBOL (if applicable) SLCBR-VL-V	5. MONITORING ORGANIZATION REPORT NUMBER(S)	
6c. ADDRESS (City, State, and ZIP Code) Aberdeen Proving Ground, MD 21005-5066			7a. NAME OF MONITORING ORGANIZATION		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (if applicable)	7b. ADDRESS (City, State, and ZIP Code)		
8c. ADDRESS (City, State, and ZIP Code)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) EPIC-2 CALCULATED IMPACT LOADING HISTORY FOR FINITE ELEMENT ANALYSIS OF BALLISTIC SHOCK					
12. PERSONAL AUTHOR(S) Quigley, Ennis F.					
13a. TYPE OF REPORT		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day)	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	→ EPIC-2; ADINA; Penetration mechanics; Ballistic impact; Shock; Loading Histories; Shock spectra; Computer simulation; Hydro-code; Finite element code; (K ²) ←		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Although the EPIC-2 code can predict the ballistic shock environments in projectile-impacted targets, these targets must be axisymmetric. By modifying the code one can calculate the target loading history which can be used as input for a finite element analysis of the ballistic shock in normal impacted, non-axisymmetric targets. The loading history of a 20 mm fragment simulator projectile with an impact velocity of 1508 m/s on a 914 mm x 70 mm thick circular rolled homogeneous armor plate has been calculated by the EPIC-2 code and has been used in an ADINA finite element analysis of the plate. Comparisons of the EPIC-2 and ADINA response calculations show that the EPIC-2 calculated loading history can be used as loading input for finite element ballistic shock analysis. <i>K² words</i></p>					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Ennis F. Quigley			22b. TELEPHONE (Include Area Code) (301) 278-6710	22c. OFFICE SYMBOL SLCBR-VL-V	

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE
UNCLASSIFIED

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	Page
LIST OF FIGURES	v
I. INTRODUCTION	1
II. EPIC-2 CODE AND CALCULATED LOADING HISTORY	1
III. ADINA CALCULATIONS AND EPIC-2 COMPARISONS	3
IV. SUMMARY AND CONCLUSIONS	10
REFERENCES	11
DISTRIBUTION LIST	13



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

Figure		Page
1.	EPIC-2 calculated impact loading history for $v_p = 1508$ m/s	3
2.	ADINA finite element model of 70 mm thick plate	4
3.	EPIC-2 and ADINA normal displacement histories at 106 mm for $v_p = 1508$ m/s	5
4.	EPIC-2 and ADINA normal displacement histories at 244 mm for $v_p = 1508$ m/s	6
5.	EPIC-2 and ADINA radial strain histories at 100 mm for $v_p = 1508$ m/s	6
6.	EPIC-2 and ADINA radial strain histories at 170 mm for $v_p = 1508$ m/s	7
7.	EPIC-2 and ADINA radial strain histories at 240 mm for $v_p = 1508$ m/s	7
8.	EPIC-2 and ADINA normal acceleration histories at 106 mm for $v_p = 1508$ m/s	8
9.	EPIC-2 and ADINA normal acceleration histories at 244 mm for $v_p = 1508$ m/s	8
10.	EPIC-2 and ADINA primary shock spectra at 106 mm for $v_p = 1508$ m/s	9
11.	EPIC-2 and ADINA primary shock spectra at 244 mm for $v_p = 1508$ m/s	9

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGEMENTS

I wish to acknowledge the Joint Live Fire Program for providing the funds for this investigation.

INTENTIONALLY LEFT BLANK.

I. INTRODUCTION

A series of nonperforating ballistic impact experiments¹ were conducted by the US Army Combat Systems Testing Agency (USACSTA) to characterize the ballistic shock environment in rolled homogeneous armor (rha) targets. One of these experiments involved the normal impact of a 20 mm fragment simulator projectile (fsp) on 914 mm x 914 mm x 70 mm rha plate at an impact velocity of 1508 m/s. Normal displacements were measured at radial distances of 105 mm and 241 mm from the center of the plates, and radial strains were measured at radial distances of 100 mm, 170 mm and 240 mm from the center of the plates. The EPIC-2 hydro-code² was used by the US Army Ballistic Research Laboratory to model these experiments and to calculate the plate's responses to impact of the fsp. Comparison³ of the measured and EPIC-2 calculated responses (normal displacement and radial strain) showed that the EPIC-2 could calculate the response of projectile-impacted targets within the limitations of the code.

EPIC-2 is an axisymmetric code; therefore, it is limited to axisymmetric targets and to normal impacting projectiles. If, however, the EPIC-2 code is modified to calculate the projectile loading history of the target, this loading history can be used as input for a finite element analysis of ballistic shock in normal impacted, non-axisymmetric targets. This report describes the EPIC-2 calculated loading history of a 20 mm fsp with an impact velocity of 1508 m/s on a 70 mm thick rha plate, the application of this loading history in an ADINA⁴ finite element analysis of the plate, and the results of the comparison of the EPIC-2 and ADINA calculations.

II. EPIC-2 CODE AND CALCULATED LOADING HISTORY

The major characteristics of the EPIC-2 code are listed in Table 1. The code performs elastic-plastic impact computations in two dimensions for axisymmetric and plane strain problems with either free or fixed boundaries. It is based on a Lagrangian finite element and lumped mass formulation in which the equations of motion are integrated directly. Nonlinear material strength and compressibility effects are included to account for elastic-plastic flow and wave propagation. The code has material descriptions for strain hardening, strain rate effects, thermal softening and failure. It uses a constant strain, triangular finite element which is well suited to represent the severe distortions occurring during high velocity impact.

The use of an axisymmetric code to model the USACSTA experiments was justified since the impact point in the experiments was the center of the plate. EPIC-2 calculations³ had shown that the plate's response would be axisymmetric and independent of the plate's geometry and edge boundary conditions for a period of time after impact.

One of the variables calculated by the EPIC-2 code for each computational time interval was the total linear momentum of the plate. The code was modified to calculate the loading history of the projectile on the plate by calculating the time rate-of-change in the plate's total linear momentum over each computational time interval. Although the computational time interval for the impact velocity was in the order of 0.05 μ s, the loading was printed out at 1.0 μ s intervals.

Table 1. EPIC-2 Code Characteristics

DISCRETIZATION:	FINITE ELEMENT METHOD <ul style="list-style-type: none">• 2D constant strain triangles• Lumped mass formulation
MESH DESCRIPTION:	LAGRANGIAN
MATERIAL MODEL:	CONSTITUTIVE MODEL <ul style="list-style-type: none">• Incremental elastic-plastic• Von Mises yield criterion• Compressibility effects• Strain rate effects• Strain hardening• Thermal softening EQUATION OF STATE <ul style="list-style-type: none">• Mie-Gruneisen
FAILURE CRITERIA:	VOLUMETRIC STRAIN EFFECTIVE PLASTIC STRAIN
POST-FAILURE MODELS:	PRESSURE CUTOFF SHEAR AND TENSION FAILURE TOTAL FAILURE

Figure 1 shows the computed loading history of the plate for the impact velocity of 1508 m/s. The loading has a duration time of 68 μ s and a maximum peak value of 6.3 MN. For the first 30 μ s the loading is very oscillatory with differences of up to 5 MN between maximum and minimum load values. There exists at 46 μ s a negative loading, implying that the projectile is pulling the plate rather pushing against it. A more reasonable explanation is in terms of the dilatation wave produced by the impacting projectile. The time at which the negative loading occurs is the arrival time of the wave at the impact point after the wave's second round trip through the 70 mm thickness of the plate. Since this is a tension wave when it arrives, the plate experiences a pulling rather than a pushing.




Figure 1. EPIC-2 calculated impact loading history for $v_p = 1508$ m/s.

III. ADINA CALCULATIONS AND EPIC-2 COMPARISONS

The ADINA finite element model of the plate is shown in Figure 2 and it is identical to the EPIC-2 model. The plate is modeled as a circular one, 914 mm in diameter and with free boundaries, and it consists of 1029 nodes and 1760 triangular elements. The horizontal and the vertical distances between the nodes are 7.62 mm and 8.67 mm, respectively. Only the first 160 mm of the plate's 457 mm radius is shown. One third of the loading shown in Figure 1 is applied to each of the top first three radial nodes as indicated in Figure 2. (The 20 mm fsp used in this experiment was completely destroyed. However, recovery of similar fsp's after lower impact velocity experiments showed the contact surface of the projectile mushroomed from a 20 mm diameter to a 33 mm diameter.)

The analysis is nonlinear, small deflection and small strain. The time integration scheme used is the Newmark method with a time step increment of $1 \mu\text{s}$, and the equilibrium iteration method used is the full Newton with line search. The material model of the plate is bilinear elastic-plastic in which Young's modulus $E = 145.1$ GPa, Poisson's ratio $\nu = 0.275$, yield stress $\sigma_Y = 916.2$ MPa, and strain hardening modulus $E_T = 510.1$ MPa; and the density of the plate is 7876 kg/m³. The same material properties are used in the EPIC-2 calculations.




Figure 2. ADINA finite element model of 70 mm thick plate.

Figure 3 through 9 are plots of both the ADINA and EPIC-2 calculated responses at the same locations on the back of the plate. Figure 3 shows excellent agreement of the normal displacements at 106 mm, and Figure 4 shows good agreement of the normal displacements at 244 mm. For time $t \geq 100 \mu\text{s}$, the ADINA displacements are less than the EPIC-2 displacements at 244 mm. Figure 5 shows good agreement of the radial strains at 100 mm except for $50 \mu\text{s} < t < 75 \mu\text{s}$. During this time interval the EPIC-2 maximum positive strain is approximately three times greater than the ADINA maximum positive strain. Figure 6 shows good agreement of the radial strains at 170 mm for all times. Also, it appears for $t > 250 \mu\text{s}$ that the ADINA curve is beginning to lag behind the EPIC-2 curve. Figure 7 shows good agreement of the radial strains at 240 mm. Figure 8 shows good agreement of the normal accelerations at 106 mm for $t \leq 75 \mu\text{s}$ and poor agreement for $t > 75 \mu\text{s}$. The ADINA positive and negative peak accelerations are much larger than the EPIC-2 peak values. Figure 9 shows good agreement of the normal accelerations at 244 mm for $t \leq 150 \mu\text{s}$ and poor for $t > 150 \mu\text{s}$. Figures 10 and 11 show the ADINA and EPIC-2 primary shock spectra obtained from the normal acceleration histories shown in Figures 8 and 9. A recursive filter technique⁶ is used to obtain these spectra. Figure 10 shows excellent agreement of the spectra for frequency $f \leq 50 \text{ kHz}$ and fair agreement for $f > 50 \text{ kHz}$. Figure 11 shows excellent agreement of the spectra for $f \leq 10 \text{ kHz}$, good agreement for $10 \text{ kHz} < f \leq 20 \text{ kHz}$, and poor agreement for $f > 20 \text{ kHz}$.




Figure 3. EPIC-2 and ADINA normal displacement histories at 106 mm for $v_p = 1508 \text{ m/s}$.




Figure 4. EPIC-2 and ADINA normal displacement histories at 244 mm for $v_p = 1508$ m/s.




Figure 5. EPIC-2 and ADINA radial strain histories at 100 mm for $v_p = 1508$ m/s.




Figure 6. EPIC-2 and ADINA radial strain histories at 170 mm for $v_p = 1508$ m/s.




Figure 7. EPIC-2 and ADINA radial strain histories at 240 mm for $v_p = 1508$ m/s.




Figure 8. EPIC-2 and ADINA normal acceleration histories at 106 mm for $v_p = 1508$ m/s.




Figure 9. EPIC-2 and ADINA normal acceleration histories at 244 mm for $v_p = 1508$ m/s.




Figure 10. EPIC-2 and ADINA primary shock spectra at 106 mm for $v_p = 1508$ m/s.




Figure 11. EPIC-2 and ADINA primary shock spectra at 244 mm for $v_p = 1508$ m/s.

IV. SUMMARY AND CONCLUSIONS

By modifying the EPIC-2 code to calculate the time rate-of-change of the target's linear momentum, the code can calculate a loading history of an impacting projectile on the target. The loading history of a 20 mm fragment simulator projectile for an impact velocity of 1508 m/s on a 914 mm x 70 mm thick circular rolled homogeneous armor plate has been calculated by the EPIC-2 code and has been used in an ADINA finite element analysis of the plate. Comparisons of the EPIC-2 and ADINA response calculations show that the EPIC-2 calculated loading history can be used as the loading input for finite element analysis of ballistic shock.

REFERENCES

1. Walton, W. Scott, Characterization of Ballistic Shock, USACSTA-6262, U.S. Army Combat Systems Test Activity, Aberdeen Proving, MD, November 1985.
2. Johnson, Gordon R., EPIC-2: A Computer Program for Elastic-Plastic Impact Computations in 2 Dimensions Plus Spin, Contractor Report ARBRL-00373, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1978.
3. Quigley, Ennis F., EPIC-2 Predicted Shock Environments in Rolled Homogeneous Armor for Nonperforating Ballistic Impact, BRL-TR-2886, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, January 1988.
4. "ADINA Users Manual, Volumes 1 and 2", Report ARD 87-1, ADINA R & D, Inc., Watertown, MA, December 1987.
5. Kelly, Ronald D. and Richman, George, *Principles and Techniques of Shock Data Analysis*, The Shock and Vibration Information Center, Washington, DC, 1969

INTENTIONALLY LEFT BLANK.

No of Copies	Organization	No of Copies	Organization
(Unclass., unlimited) 12	Administrator	1	Commander
(Unclass., limited) 2	Defense Technical Info Center		US Army Missile Command
(Classified) 2	ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145		ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	HQDA (SARD-TR) WASH DC 20310-0001	1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL (Technical Library) Warren, MI 48397-5000
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Director US Army TRADOC Analysis Command ATTN: ATAA-SL White Sands Missile Range, NM 88002-5502
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145	(Class. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000	(Unclass. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	(Class. only) 1	The Rand Corporation P.O. Box 2138 Santa Monica, CA 90401-2138
1	Director Benet Weapons Laboratory Armament RD&E Center US Army AMCCOM ATTN: SMCAR-LCB-TL Watervliet, NY 12189-4050	1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-5000		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen Cdr, USATECOM ATTN: AMSTE-TO-F Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI Dir, VLAMO ATTN: AMSLC-VL-D
1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798		
1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099		

DISTRIBUTION LIST

No. of Copies	Organization	No. of Copies	Organization
1	ODUSDRE (T&E) ATTN: J. O'Bryon Pentagon, Room 1B473 Washington, DC 20301	1	AAI Corporation ATTN: R. L. Kachinski P.O. Box 6767 Baltimore, MD 21204
1	Commander US Army Tank Automotive Command ATTN: AMSTA-RSS (K. Bishnoi) Warren, MI 48397-5000	1	ADINA R & D, Inc. 71 Elton Avenue Watertown, MA 02172
1	Commander US Army Combat Systems Test Activity ATTN: STECS-DA-I (S. Walton) Aberdeen Proving Ground, MD 21005	1	General Dynamics Land System Division ATTN: Dr. P. Kersten P.O. Box 2074 Warren, MI 48090-2074
3	Air Force Armanent Laboratory ATTN: AFATL/DLJW AFATL/DLORD AFATL/DLYV Eglin AFB, FL 32542-5000	1	Honeywell, Inc. ATTN: Dr. G. Johnson 7225 Northland Drive Brooklyn Park, MN 55428
2	Commander Naval Surface Weapons Center ATTN: Code R-13 Code U-11 Silver Spring, MD 20910	1	University of Denver Denver Research Institute ATTN: R. F. Recht 2390 S. University Blvd. Denver, CO 80210
2	Commander Naval Weapons Center ATTN: Code 3181 Code 3261 China Lake, CA 93555	1	Computational Mechanics Associates 8600 LaSalle Road, Suite 614 Baltimore, MD 21204
1	Orlanda Technology, Inc. ATTN: D. Matuska P.O. Box 855 Shalmir, FL 32579		
1	SouthWest Research Institute Dept. of Mechanical Sciences ATTN: Dr. C. Anderson 8500 Culebra Road San Antonio, TX 78228		

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

- 1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

- 2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

- 3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

- 4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

BRL Report Number _____ Division Symbol _____

Check here if desire to be removed from distribution list. _____

Check here for address change. _____

Current address: Organization _____
Address _____

-----FOLD AND TAPE CLOSED-----

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

OFFICIAL BUSINESS



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY LABEL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY



Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989