

1

USAARL Report No. 89-18



**Evaluation of Two Objective Measures  
of Effective Auditory Stimulus Level**

By

**Ted L. Langford  
Ben T. Mozo  
James H. Patterson, Jr.**

**Sensory Research Division**

**August 1989**

**DTIC  
ELECTE  
NOV 22 1989  
S B D**

Approved for public release; distribution unlimited.

**89 11 21 023**

**United States Army Aeromedical Research Laboratory  
Fort Rucker, Alabama 36362-5292**

**AD-A214 669**

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.


Human use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:




BRUCE C. LEIBRECHT, Ph.D.  
LTC, MS  
Director, Sensory Research Division



J. D. LAMOTHE, Ph.D.  
COL, MS  
Chairman, Scientific  
Review Committee

Released for publication:



DAVID H. KARNEY  
Colonel, MC  
Commanding

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			
4. PERFORMING ORGANIZATION REPORT NUMBER(S) USAARL Report No. 89-18		5. MONITORING ORGANIZATION REPORT NUMBER(S)	
6a. NAME OF PERFORMING ORGANIZATION Sensory Research Division U.S. Army Aeromedical Resch Lab	6b. OFFICE SYMBOL (if applicable) SGRD-UAS-AS	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research and Development Command	
6c. ADDRESS (City, State, and ZIP Code) P. O. Box 577 Fort Rucker, AL 36362-5292		7b. ADDRESS (City, State, and ZIP Code) Fort Detrick Frederick, MD 21701-5012	
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO.	PROJECT NO.
			TASK NO.
			WORK UNIT ACCESSION NO.
		BE162787A878	135
11. TITLE (Include Security Classification) Evaluation of two objective measures of effective auditory stimulus level			
12. PERSONAL AUTHOR(S) Ted I. Langford, Ben T. Mozo, and James H. Patterson, Jr.			
13a. TYPE OF REPORT	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 1989 August	15. PAGE COUNT 19
16. SUPPLEMENTARY NOTATION <i>Key-words + 4</i>			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	
06	04	Auditory brainstem response; auditory mid-latency response; hearing protectors; effective stimulus level (KT)	
24	07		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The brainstem auditory evoked response and the 40-Hz component of the auditory mid-latency response were measured in human subjects as a function of stimulus frequency and level to determine whether one of the two could be used to provide a reliable estimation of the amount of attenuation provided by hearing protective devices in situations in which the time available for measurement is restricted. Under the conditions of the present experiment, the variability of the data for both types of measure was too great to permit a reliable estimation of effective stimulus level. <i>contd pg 2</i>			
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Scientific Information Center		22b. TELEPHONE (Include Area Code) (205) 255-6907	22c. OFFICE SYMBOL SGRD-UAX-SI

Table of contents

Introduction..... 3

Materials and methods..... 5

Results..... 11

Discussion..... 14

Conclusions..... 16

References..... 17

Manufacturers' list..... 19

List of tables

1. ABR latencies and standards deviations..... 13

2. MLR magnitudes and standard deviations..... 15

List of figures

1. Waveform and spectrum for 250-Hz signal..... 6

2. Waveform and spectrum for 500-Hz signal..... 7

3. Waveform and spectrum for 1000-Hz signal..... 8

4. Waveform and spectrum for 2000-Hz signal..... 9

5. Waveform and spectrum for 4000-Hz signal..... 10

6. Mean latencies of wave V for all subjects..... 12

7. Mean magnitudes of MLR responses for all subjects and frequencies..... 14

<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
<b>Availability Codes</b>	
Dist	Avail and/or Special
A-1	

---

This page intentionally left blank.

---

## Introduction

Potentially harmful noise levels in many military environments require the use of hearing-protective devices by personnel operating in those environments. A rapid, reliable, and valid method for the field measurement of the amount of attenuation afforded by the various hearing protectors is needed to ensure that the devices are being properly used and are effective in reducing noise exposure. At present, a method for objectively measuring the attenuation of hearing protectors in a field environment is not available.

The purpose of the present study was to determine if evoked auditory potentials could provide objective measures which could be used as dependent variables in a more extensive study of the attenuation characteristics of hearing-protection devices. An additional purpose of the work was to provide baseline, laboratory data as a comparison for the field work of the attenuation study.

Noninvasive, electrophysiological recording techniques have been used to objectively measure the biologically effective levels of auditory stimuli in both laboratory and clinical settings. Such measures are objective in that they do not require a judgment on the part of the subject. Indeed, no overt response or active participation at all is required of the subject in order for a valid measurement to be made.

At present, the most commonly used of these measures is the auditory brainstem response (ABR). The ABR consists of a series of short-latency electrical potentials evoked by brief stimuli and recorded by surface electrodes placed at various locations on the head. The potentials are averaged over a number of stimulus presentations to isolate activity temporally locked to the stimulus from the random background activity. Wave V of the ABR can be reliably identified by trained observers over a wide range of measurement conditions and its latency in persons with normal hearing varies in a predictable manner with the level of the stimulus (Moore, 1983). Although human judgment and error have always been factors in measuring the latency of Wave V, several automated, statistical procedures are under development to objectively detect this wave (cf., Elberling and Don, 1987; Salvi et al., 1987).

A recently developed measure, the 40-Hz evoked response, is not yet in general use as a standard in auditory work. This response is derived from three waves of the mid-latency responses (MLR) which follow the ABR. These waves have natural latencies which are multiples of the period of 40-Hz. At a stimulus

repetition rate of 40 Hz they are enhanced, making them easily detectable in the averaged waveform (Galambos et al., 1981; Lenarz et al., 1986; Sammeth and Barry, 1985). This enhanced potential can be recorded from the same electrode placements as used for the ABR. Although there are a few reports regarding latency changes produced by changes in stimulus level, at present the dependent variable of choice is the amplitude of the 40-Hz MLR.

Both the ABR and the MLR have advantages and disadvantages as measures of the effectiveness of auditory stimulation. The ABR has been used extensively and the variation in the latency of its Wave V as a function of effective stimulus level is well known. On the other hand, the stimuli used in most cases are broad-band clicks, so that frequency-specific information is not produced. Another disadvantage is that different latency norms must be used for male and female subjects (Schwartz and Berry, 1985). The 40-Hz evoked MLR is reported to be a robust, frequency-specific response, which can be obtained with fewer stimulus presentations than the ABR, but it suffers from considerable variability depending on the attentional state of the subject. No data have been reported concerning possible gender differences for this measure.

Neither the ABR nor the MLR has been standardized well enough to be used in laboratory or clinical settings without considerable interpretation according to local ground rules. The stimuli which are described in most published reports have unknown frequency content and poorly specified levels. In addition, a variety of stimulus durations and repetition rates, both of which affect the ABR response (Moore, 1983), are used by different investigators. The filters used in recording are often chosen to eliminate various types of noise contamination with little regard to the resulting phase distortion of the evoked waveforms. Severe filtering can affect amplitudes, latencies and even the polarities of the waves of interest (Scherg, 1982; Janssen et al., 1986). The many electrode placements which are used also contribute to the difficulty of interpreting data from different sources.

For the above reasons, it is not possible to use evoked-response data already existing in the literature as a norm for the field study of attenuation. The present, preliminary, study was conducted to determine a feasible configuration of stimulus variables consistent with the rapid acquisition of objective data necessary for field attenuation measurements.

## Materials and Methods

Both the ABRs and the MLRs were recorded from the same subjects over a range of frequencies and levels. The stimuli used were 12-ms tone bursts produced by modulating sinusoids with an 83.3-Hz haversine. These waveforms met the requirement for a brief duration without exhibiting an excessive spread of energy to non-signal frequencies.

The stimuli for the ABR conditions were bursts of 250, 500, 1000, 2000, and 4000 Hz presented at a rate of 10 per second. With the exception of 4000 Hz, all were presented at sensation levels (SL) of 20, 35, and 50 dB. The levels for the 4000-Hz conditions were 20, 30, and 40 dB SL.

The same frequencies were used for the MLR conditions as were used for the ABR. At frequencies other than 4000 Hz, the levels were 20, 30, 35, 40, and 50 dB SL. At 4000 Hz, the levels were 20, 30, and 40 dB SL. The repetition rate was 40 per second.

The signals for both the ABRs and the MLRs were conducted to the ear from a TDH-49 headphone, sealed to a 2-ml coupler, by a length of polyethelene tubing. The tip of the tubing was passed through an opening in an E-A-R\* plug, which was used to seal the tube to the ear canal of the subject. Resonances in the tubing were damped by the insertion of tufts of steel wool into each end of the tubing. The headphone-coupler-tubing combination was calibrated with an additional 2-ml coupler and 0.5-inch microphone in place of the subject's ear. The waveforms and spectra for each frequency of tone burst measured in this manner are shown in Figures 1-5. The second harmonic distortion products were at least 35 dB below the signal levels at all frequencies, with the exception of 250 Hz, where the second harmonic was 33.7 dB lower than the signal.

Ten young adults, seven males and three females, selected from the subject pool of a local community college, were used in the experiment. Each subject was screened for acceptable hearing on the basis of a pure-tone audiogram obtained for each ear. Acceptable hearing was defined as thresholds between -10 dB and 20 dB at standard audiometric frequencies (ANSI S12.6, 1984). No other selection criteria were employed. The subjects were comfortably positioned in a reclining chair inside a double-walled Tracoustics audiometric testing booth for the recording sessions. Instructions were given them to relax during the

---

\* See manufacturer's list.







Figure 1. Waveform (upper panel) and spectrum (lower panel) for 250-Hz signal.





Figure 2. Waveform (upper panel) and spectrum (lower panel) for 500-Hz signal.





Figure 3. Waveform (upper panel) and spectrum (lower panel) for 1000-Hz signal.





Figure 4. Waveform (upper panel) and spectrum (lower panel) for 2000-Hz signal.





Figure 5. Waveform (upper panel) and spectrum (lower panel) for 4000-Hz signal.

recording sessions and most slept during the ABR recordings. For the MLR recordings, they were instructed to remain relaxed but alert. The experimenter made frequent checks to ensure that the subjects were awake, but no assessment of the degree of alertness was attempted.

Commercial, adhesive-backed disposable surface electrodes were used for the recordings. The same electrode array was used for both the ABR and the MLR recordings. The positive input to a differential isolation amplifier was obtained from the forehead, the negative input from the mastoid contralateral to the ear stimulated and the ground from the ipsilateral ear lobe.

The ABRs were filtered with a pass band of 5 to 2000 Hz and the MLRs with a pass band of 5 to 60 Hz. After filtering, the waveforms were digitized by a 12-bit A-to-D converter and averaged by an IBM XT-compatible computer.

Rapid data acquisition is a requirement for the field study and each ABR was based on 2000 stimulus repetitions. The results of a pilot experiment using a single subject had indicated that this number of repetitions would produce an adequate signal-to-noise ratio. The averaged waveforms were displayed on-line and stored on disk for more detailed analyses off-line.

The latency from the stimulus onset to the peak of Wave V was the dependent measure for the brainstem response. The amplitude of the 40-Hz component obtained from a fast Fourier transform of the averaged waveforms was the MLR dependent measure.

### Results

The ABR results are summarized in Figure 6. The figure shows the mean latencies for all subjects at all frequencies as a function of the SL of the stimulus. Any sex differences which may have been present in the latencies were obscured by other sources of variability. The latencies, therefore, were averaged without regard to sex. The latencies shown have been corrected in this and all subsequent figures for the acoustic delay introduced by the length of tubing which conducted the stimulus to the ear. It is evident that the overall latencies for the five frequencies are ordered according to the relative positions of their travelling wave maxima along the basilar membrane. The higher frequencies, with maxima near the basal end of the membrane, are represented by short latencies and the lower frequencies, with maxima nearer the apical end, are represented by longer latencies, indicating that the responses elicited by the various stimuli were frequency-specific.




Figure 6. Mean latencies of wave V for all subjects.

Filled circles: 250 Hz      Open squares: 500 Hz  
 Filled diamonds: 1000 Hz      Filled triangles: 2000 Hz  
 Filled squares: 4000 Hz

The mean ABR data for the individual frequencies are presented in Table 1. With the exception of the 500-Hz data, the mean latencies show little change as a function of the stimulus intensity. In addition, at most frequencies the variability around each data point is quite high, approaching and sometimes exceeding the magnitude of the change produced by the independent variable. Several methods were attempted to reduce the variability of the data, including digital filtering of the averaged waveforms and averaging the waveforms across subjects. None of these methods produced any practical improvement.

Table 1.

ABR latencies and standard deviations.  
Means for all subjects.

Sensation level (db)	Latency (ms)	Standard deviation (ms)
0.25 kHz		
20	14.22	0.58
35	13.93	0.76
50	13.37	0.34
0.50 kHz		
20	12.00	2.14
35	10.70	1.12
50	9.97	1.18
1.00 kHz		
20	7.96	0.74
35	8.71	1.16
50	8.38	0.83
2.00 kHz		
20	7.02	0.39
35	7.71	0.70
50	7.20	0.49
4.00 kHz		
20	7.35	0.37
30	7.47	0.10
40	10.90	0.43



The mean magnitudes of the 40-Hz component of the MLRs for all subjects are shown as a function of stimulus level in Figure 7. A general trend for the magnitude of the response to increase with increasing level can be discerned, with a 30 dB increase in stimulus level producing about a 10 dB increase in the magnitude of the 40-Hz component. The variability of the response, however, is extreme as shown in the data for individual frequencies presented in Table 2. Here, as in the ABR results, the magnitude of the effect due to variation of the independent variable is obscured by the uncontrolled variation in the dependent variable.




Figure 7. Mean magnitudes of MRL responses for all subjects and all frequencies.

Filled circles: 250 Hz      Open squares: 500 Hz  
 Filled diamonds: 1000 Hz      Filled triangles: 2000 Hz  
 Filled squares: 4000 Hz

#### Discussion

Although the pilot data taken from one subject indicated that the averaged ABR responses to 2000 stimulus repetitions would be an adequate number upon which to base an estimate of the latency of the Wave V component, this did not prove to be the case in the main experiment. The variability both within and across subjects was unacceptably high. The latency changes produced by the full range of stimulus intensity often were exceeded by the standard deviation at any given intensity (Table 1).

Table 2.

MLR magnitudes and standard deviations. Means for all subjects. Values in all columns are in decibels.

Sensation level	Magnitude	Standard deviation
0.25 kHz		
20	9.64	7.5
30	13.87	7.7
35	15.67	8.2
40	14.98	5.3
50	19.57	5.5
0.50 kHz		
20	11.96	6.5
30	9.13	10.7
35	15.18	6.3
40	16.19	8.4
50	20.72	5.6
1.00 kHz		
20	13.18	3.3
30	12.27	8.1
35	18.17	4.8
40	17.62	5.6
50	20.80	4.5
2.00 kHz		
20	9.00	5.6
30	12.53	4.3
35	15.62	6.7
40	18.15	3.4
50	18.94	5.4
4.00 kHz		
20	11.66	5.2
30	13.88	4.6
40	16.47	4.4

Most of the published reports regarding the magnitude of the 40-Hz component of the MLR as a function of stimulus level state that it is a good indicator of threshold. The variability of the measurements is rarely included in these reports, so that no meaningful comparisons can be made between them and the results of the present experiment in which the variability was considered unacceptably high. As in the case of the ABR results, the range of the dependent variable is small compared with the standard deviation at any given level (Table 2). Lenarz et al. (1986), however, do report the standard deviations for their measurements. For stimulus conditions similar to those of the present experiment, their variability appears to be comparable in magnitude. They attribute this large intrasubject and intersubject variability to contamination by myogenic potentials and to changes in the subject's state of vigilance. The variability of their data does decrease for near threshold levels, which they interpret to be the result of a decrease in myogenic potentials generated by cranial musculature. These potentials often contaminate middle latency responses, even when the subject appears to be in a relaxed state (Streletz et al., 1977). Since the present data were all collected at suprathreshold levels, the possibility of myogenic contamination cannot be ruled out.

### Conclusions

When evoked by the proper stimulus, Wave V of the ABR can produce frequency-specific information. It must be averaged over a large number of repetitions before it can be considered a reliable indicator of effective stimulus level, however, making it an unsuitable measure for field work in which time is limited. Some reduction in variability and in data collection time might be achieved through the use of one of the automated statistical procedures mentioned earlier. However, the length of time required for such a procedure is determined in part by the signal-to-noise ratio, which could not be known in advance.

The MLR also is unsuitable for use as a rapid measure of effective stimulus level due to its large variability. This variability might be reduced by the use of a data-collection protocol which provides for the maintenance of the subject's attention within narrow limits. It is not clear, however, whether the possible contribution of myogenic potentials to the variability could be reduced to an acceptable amount at suprathreshold stimulus levels.

For the conditions examined in the present experiment, neither measure provides a reliable estimate of the effective stimulus level.

## References

- American National Standards Institute. 1984. Method for the measurement of the real-ear attenuation of hearing protectors. New York: American National Standards Institute. ANSI S12.6 1984.
- Elberling, C., and Don, M. 1987. Threshold characteristics of the human auditory brain stem response. Journal of the acoustical society of america. 81: 115-121.
- Galambos, R., Makeig, S., and Talmachoff, P. J. 1981. A 40-Hz auditory potential recorded from human scalp. Proceedings of the national academy of sciences. 71: 2643-2647.
- Janssen, R., Benignus, V. A., Grimes, L. M., and Dyer, R. S. 1986. Unrecognized errors due to analog filtering of the brain-stem auditory evoked response. Electroencephalography and clinical neurophysiology. 65: 203-211.
- Lenarz, T., Gulzow, J., Grozinger, M., and Hoth, S. 1986. Clinical evaluation of 40-Hz middle-latency responses in adults: Frequency specific threshold estimation and suprathreshold amplitude characteristics. Oto-rhinolaryngology (Basel). 48: 24-32.
- Moore, E. J. 1983. Effects of stimulus parameters. In: E. J. Moore, ed. Bases of auditory brain-stem evoked responses. New York: Grune and Stratton. 221-251.
- Salvi, R. J., Ahroon, W., Saunders, S. S., and Arnold, S. A. 1987. Evoked potentials: Computer-automated threshold-tracking procedures using an objective detection criterion. Ear and hearing. 8: 151-156.
- Sammeth, C. A., and Barry, S. J. 1985. The 40-Hz event-related potential as a measure of auditory sensitivity in normals. Scandinavian audiology. 14: 51-55.
- Scherg, M. 1982. Distortion of the middle latency auditory response produced by analog filtering. Scandinavian audiology. 11: 57-60.
- Schwartz, D. M., and Berry, G. A. 1985. Normative aspects of the ABR. In: J. T. Jacobson, ed. The auditory brainstem response. San Diego: College-Hill Press. 65-97.

Streletz, L. J., Katz, L., Hohenberger, M., and Cracco, R. Q.  
1977. Scalp recorded auditory evoked potentials and  
sonomotor responses: An evaluation of components and  
recording techniques. Electroencephalography and clinical  
neurophysiology. 43: 192-206.

Manufacturers' list

E-A-R Division  
Cabot Corporation  
7911 Zionsville Road  
Indianapolis, IN 48268

Initial distribution

Commander  
U.S. Army Natick Research  
and Development Center  
ATTN: Documents Librarian  
Natick, MA 01760

Naval Submarine Medical  
Research Laboratory  
Medical Library, Naval Sub Base  
Box 900  
Groton, CT 05340

Commander/Director  
U.S. Army Combat Surveillance  
& Target Acquisition Lab  
ATTN: DELCS-D  
Fort Monmouth, NJ 07703-5304

Commander  
10th Medical Laboratory  
ATTN: Audiologist  
APO NEW YORK 09180

Commander  
Naval Air Development Center  
Biophysics Lab  
ATTN: G. Kydd  
Code 60B1  
Warminster, PA 18974

Naval Air Development Center  
Technical Information Division  
Technical Support Detachment  
Warminster, PA 18974

Commanding Officer  
Naval Medical Research  
and Development Command  
National Naval Medical Center  
Bethesda, MD 20014

Under Secretary of Defense  
for Research and Engineering  
ATTN: Military Assistant  
for Medical and Life Sciences  
Washington, DC 20301

Commander  
U.S. Army Research Institute  
of Environmental Medicine  
Natick, MA 01760

U.S. Army Avionics Research  
and Development Activity  
ATTN: SAVAA-P-TP  
Fort Monmouth, NJ 07703-5401

U.S. Army Research and Development  
Support Activity  
Fort Monmouth, NJ 07703

Chief, Benet Weapons Laboratory  
LCWSL, USA ARRADCOM  
ATTN: DRDAR-LCB-TL  
Watervliet Arsenal, NY 12189

Commander  
Man-Machine Integration System  
Code 602  
Naval Air Development Center  
Warminster, PA 18974

Commander  
Naval Air Development Center  
ATTN: Code 6021 (Mr. Brindle)  
Warminster, PA 18974

Commanding Officer  
Harry G. Armstrong Aerospace  
Medical Research Laboratory  
Wright-Patterson  
Air Force Base, OH 45433

Director  
Army Audiology and Speech Center  
Walter Reed Army Medical Center  
Washington, DC 20307-5001

Director  
Walter Reed Army Institute  
of Research  
Washington, DC 20307-5100

HQ DA (DASG-PSP-0)  
5109 Leesburg Pike  
Falls Church, VA 22041-3258

Naval Research  
Laboratory Library  
Code 1433  
Washington, DC 20375

Harry Diamond Laboratories  
ATTN: Technical Infor-  
mation Branch  
2800 Powder Mill Road  
Adelphi, MD 20783-1197

U.S. Army Materiel Systems  
Analysis Agency  
ATTN: Reports Processing  
Aberdeen proving Ground  
MD 21005-5017

U.S. Army Ordnance Center  
and School Library  
Building 3071  
Aberdeen Proving Ground,  
MD 21005-5201

U.S. Army Environmental Hygiene  
Agency  
Building E2100  
Aberdeen Proving Ground,  
MD 21010

Technical Library  
Chemical Research  
and Development Center  
Aberdeen Proving Ground,  
MD 21010-5423

Commander  
U.S. Army Institute  
of Dental Research  
Walter Reed Army Medical Center  
Washington, DC 20307-5300

Naval Air Systems Command  
Technical Air Library 950D  
Rm 278, Jefferson Plaza II  
Department of the Navy  
Washington, DC 20361

Naval Research Laboratory Library  
Shock and Vibration Infor-  
mation Center, Code 5804  
Washington, DC 20375

Director  
U.S. Army Human Engineer-  
ing Laboratory  
ATTN: Technical Library  
Aberdeen Proving Ground,  
MD 21005-5001

Commander  
U.S. Army Test  
and Evaluation Command  
ATTN: AMSTE-AD-H  
Aberdeen Proving Ground,  
MD 21005-5055

Director  
U.S. Army Ballistic  
Research Laboratory  
ATTN: DRXBR-OD-ST Tech Reports  
Aberdeen Proving Ground,  
MD 21005-5066

Commander  
U.S. Army Medical Research  
Institute of Chemical Defense  
ATTN: SGRD-UV-AO  
Aberdeen Proving Ground,  
MD 21010-5425

Commander  
U.S. Army Medical Research  
and Development Command  
ATTN: SGRD-RMS (Ms. Madigan)  
Fort Detrick, Frederick,  
MD 21701



Commander  
U.S. Army Medical Research  
Institute of Infectious Diseases  
Fort Detrick, Frederick,  
MD 21701

Director, Biological  
Sciences Division  
Office of Naval Research  
600 North Quincy Street  
Arlington, VA 22217

Commander  
U.S. Army Materiel Command  
ATTN: AMCDE-XS  
5001 Eisenhower Avenue  
Alexandria, VA 22333

Commandant  
U.S. Army Aviation  
Logistics School  
ATTN: ATSQ-TDN  
Fort Eustis, VA 23604

U.S. Army Training  
and Doctrine Command  
ATTN: ATCD-ZX  
Fort Monroe, VA 23651

Structures Laboratory Library  
USARTL-AVSCOM  
NASA Langley Research Center  
Mail Stop 266  
Hampton, VA 23665

Naval Aerospace Medical  
Institute Library  
Bldg 1953, Code 102  
Pensacola, FL 32508

Command Surgeon  
U.S. Central Command  
MacDill Air Force Base  
FL 33608

Air University Library  
(AUL/LSE)  
Maxwell AFB, AL 36112

Commander  
U.S. Army Biomedical Research  
and Development Laboratory  
ATTN: SGRD-UBZ-I  
Fort Detrick, Frederick,  
MD 21701

Defense Technical  
Information Center  
Cameron Station  
Alexandria, VA 22313

U.S. Army Foreign Science  
and Technology Center  
ATTN: MTZ  
220 7th Street, NE  
Charlottesville, VA 22901-5396

Director,  
Applied Technology Laboratory  
USARTL-AVSCOM  
ATTN: Library, Building 401  
Fort Eustis, VA 23604

U.S. Army Training  
and Doctrine Command  
ATTN: Surgeon  
Fort Monroe, VA 23651-5000

Aviation Medicine Clinic  
TMC #22, SAAF  
Fort Bragg, NC 28305

U.S. Air Force Armament  
Development and Test Center  
Eglin Air Force Base, FL 32542

U.S. Army Missile Command  
Redstone Scientific  
Information Center  
ATTN: Documents Section  
Redstone Arsenal, AL 35898-5241

U.S. Army Research and Technology  
Laboratories (AVSCOM)  
Propulsion Laboratory MS 302-2  
NASA Lewis Research Center  
Cleveland, OH 44135

AFAMRL/HEX  
Wright-Patterson AFB, OH 45433

University of Michigan  
NASA Center of Excellence  
in Man-Systems Research  
ATTN: R. G. Snyder, Director  
Ann Arbor, MI 48109

John A. Dellinger,  
Southwest Research Institute  
P. O. Box 28510  
San Antonio, TX 78284

Product Manager  
Aviation Life Support Equipment  
ATTN: AMCPM-ALSE  
4300 Goodfellow Blvd.  
St. Louis, MO 63120-1798

Commander  
U.S. Army Aviation  
Systems Command  
ATTN: AMSAV-ED  
4300 Goodfellow Blvd  
St. Louis, MO 63120

Commanding Officer  
Naval Biodynamics Laboratory  
P.O. Box 24907  
New Orleans, LA 70189

U.S. Army Field Artillery School  
ATTN: Library  
Snow Hall, Room 14  
Fort Sill, OK 73503

Commander  
U.S. Army Health Services Command  
ATTN: HSOP-SO  
Fort Sam Houston, TX 78234-6000

U.S. Air Force Institute  
of Technology (AFIT/LDEE)  
Building 640, Area B  
Wright-Patterson AFB, OH 45433

Henry L. Taylor  
Director, Institute of Aviation  
University of Illinois-  
Willard Airport  
Savoy, IL 61874

COL Craig L. Urbauer, Chief  
Office of Army Surgeon General  
National Guard Bureau  
Washington, DC 50310-2500

Commander  
U.S. Army Aviation  
Systems Command  
ATTN: SGRD-UAX-AL (MAJ Lacy)  
4300 Goodfellow Blvd., Bldg 105  
St. Louis, MO 63120

U.S. Army Aviation Systems Command  
Library and Information  
Center Branch  
ATTN: AMSAV-D1L  
4300 Goodfellow Blvd  
St. Louis, MO 63120

Federal Aviation Administration  
Civil Aeromedical Institute  
CAMI Library AAC 64D1  
P.O. Box 25082  
Oklahoma City, OK 73125

Commander  
U.S. Army Academy  
of Health Sciences  
ATTN: Library  
Fort Sam Houston, TX 78234

Commander  
U.S. Army Institute  
of Surgical Research  
ATTN: SGRD-USM (Jan Duke)  
Fort Sam Houston, TX 78234-6200

Director of Professional Services  
AFMSC/GSP  
Brooks Air Force Base, TX 78235

U.S. Army Dugway Proving Ground  
Technical Library  
Bldg 5330  
Dugway, UT 84022

U.S. Army Yuma Proving Ground  
Technical Library  
Yuma, AZ 85364

AFFTC Technical Library  
6520 TESTG/ENXL  
Edwards Air Force Base,  
CAL 93523-5000

Commander  
Code 3431  
Naval Weapons Center  
China Lake, CA 93555

Aeromechanics Laboratory  
U.S. Army Research  
and Technical Labs  
Ames Research Center,  
M/S 215-1  
Moffett Field, CA 94035

Sixth U.S. Army  
ATTN: SMA  
Presidio of San Francisco,  
CA 94129

Commander  
U.S. Army Aeromedical Center  
Fort Rucker, AL 36362

U.S. Air Force School  
of Aerospace Medicine  
Strughold Aeromedical Library  
Documents Section, USAFSAM/TSK-4  
Brooks Air Force Base, TX 78235

Dr. Diane Damos  
Department of Human Factors  
ISSM, USC  
Los Angeles, CA 90089-0021

U.S. Army White Sands  
Missile Range  
Technical Library Division  
White Sands Missile Range,  
NM 88002

U.S. Army Aviation Engineering  
Flight Activity  
ATTN: SAVTE-M (Tech Lib)  
Stop 217  
Edwards Air Force Base,  
CA 93523-5000

Ms. Sandra G. Hart  
Ames Research Center  
MS 239-5  
Moffett Field, CA 94035

Commander  
Letterman Army Institute  
of Research  
ATTN: Medical Research Library  
Presidio of San Francisco,  
CA 94129

Director  
Naval Biosciences Laboratory  
Naval Supply Center, Bldg 844  
Oakland, CA 94625

Commander  
U.S. Army Medical Materiel  
Development Activity  
Fort Detrick, Frederick,  
MD 21701-5009

Commander, U.S. Army  
Aviation Center  
Directorate  
of Combat Developments  
Bldg 507  
Fort Rucker, AL 36362

Chief  
Army Research Institute  
Field Unit  
Fort Rucker, AL 36362

Commander  
U.S. Army Safety Center  
Fort Rucker, AL 36362

U.S. Army Aircraft Development  
Test Activity  
ATTN: STEBG-MP-QA  
Cairns AAF  
Fort Rucker, AL 36362

Commander  
U.S. Army Medical Research  
and Development Command  
ATTN: SGRD-PLC (COL Sedge)  
Fort Detrick, Frederick  
MD 21701

Directorate  
of Training Development  
Bldg 502  
Fort Rucker, AL 36362

Chief  
Human Engineering Laboratory  
Field Unit  
Fort Rucker, AL 36362

Commander  
U.S. Army Aviation Center  
and Fort Rucker  
ATTN: ATZQ-T-ATL  
Fort Rucker, AL 36362

President  
U.S. Army Aviation Board  
Cairns AAF  
Fort Rucker, AL 36362

Dr. William E. McLean  
Human Engineering Laboratory  
ATTN: SLCHE-BR  
Aberdeen Proving Ground,  
MD 21005-5001