

REPORT NO. NADC-89084-60



AD-A218 139

**THE EFFECT OF WINDSCREEN BOWS AND  
HUD PITCH LADDER FORMAT ON PILOT  
PERFORMANCE DURING SIMULATED FLIGHT**

John E. Deaton, Ph.D., Michael J. Barnes, Nancy J. Lindsey, and  
Janettarose L. Greene  
Air Vehicle and Crew Systems Technology Department (Code 6021)  
NAVAL AIR DEVELOPMENT CENTER  
Warminster, PA 18974-5000

Jonathan Kern  
VEDA INC.  
Warminster, PA 18974-5000

DTIC  
ELECTE  
FEB 22 1990  
S D D

21 MAY 1989

FINAL REPORT  
Period Covering October 1987 to September 1988  
Task No. A5115116/0012/8241-000-749  
Work Unit No. 133150  
Program Element No. APN-1  
Project No. A5116B3-02

*Approved for Public Release; Distribution is Unlimited*

Prepared for  
NAVAL AIR SYSTEMS COMMAND (AIR-5116B)  
Department of the Navy  
Washington, DC 20361-0001

90 02 21 023

## NOTICES

**REPORT NUMBERING SYSTEM** — The numbering of technical project reports issued by the Naval Air Development Center is arranged for specific identification purposes. Each number consists of the Center acronym, the calendar year in which the number was assigned, the sequence number of the report within the specific calendar year, and the official 2-digit correspondence code of the Command Officer or the Functional Department responsible for the report. For example: Report No. NADC-88020-60 indicates the twentieth Center report for the year 1988 and prepared by the Air Vehicle and Crew Systems Technology Department. The numerical codes are as follows:

CODE	OFFICE OR DEPARTMENT
00	Commander, Naval Air Development Center
01	Technical Director, Naval Air Development Center
05	Computer Department
10	AntiSubmarine Warfare Systems Department
20	Tactical Air Systems Department
30	Warfare Systems Analysis Department
40	Communication Navigation Technology Department
50	Mission Avionics Technology Department
60	Air Vehicle & Crew Systems Technology Department
70	Systems & Software Technology Department
80	Engineering Support Group
90	Test & Evaluation Group

**PRODUCT ENDORSEMENT** — The discussion or instructions concerning commercial products herein do not constitute an endorsement by the Government nor do they convey or imply the license or right to use such products.

Reviewed By:   
Branch Head

Date: Oct 2 1987

Reviewed By:   
Division Head

Date: 10/16/89

Approved By:   
Director/Deputy Director

Date: 12/5/89

F. F. MORSEY  
U.S. NAVY

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS			
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for Public Release Distribution is Unlimited			
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) NADC-89084-60		5. MONITORING ORGANIZATION REPORT NUMBER(S)			
6a. NAME OF PERFORMING ORGANIZATION Air Vehicle and Crew Systems Technology Department		6b. OFFICE SYMBOL (If applicable) 6021	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) NAVAL AIR DEVELOPMENT CENTER Warminster, PA 18974-5000		7b. ADDRESS (City, State, and ZIP Code)			
8a. NAME OF FUNDING / SPONSORING ORGANIZATION NAVAL AIR SYSTEMS COMMAND		8b. OFFICE SYMBOL (If applicable) AIR-5116B	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code) Washington, DC 20361-5110		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO. APN-1	PROJECT NO. A5116B3-02	TASK NO. A5115116/ 0012/8241- 000-749	WORK UNIT ACCESSION NO. 133150
11. TITLE (Include Security Classification) The Effect of Windscreen Bows and HUD Pitch Ladder Format on Pilot Performance During Simulated Flight					
12. PERSONAL AUTHOR(S) John E. Deaton Ph.D., * Michael Barnes, * Nancy Lindsey, * Janettarose Greene, * & Jonathan Kern**					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM 10/87 TO 9/88	14. DATE OF REPORT (Year, Month, Day) 1989 May 21		15. PAGE COUNT 18
16. SUPPLEMENTARY NOTATION <i>Keyed to</i> *NAVAIRDEVCCEN **VEDA, Inc.					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Human Factors, Head-up Display; Pitch Ladder; Windscreen Bows; Situational Awareness; Display Formats; Spatial Disorientation		
FIELD	GROUP	SUB-GROUP			
01	03	03			
19. ABSTRACT (Continue on reverse if necessary and identify by block number) During the upgrade of the F-14 to the F-14D, pilots have expressed their concerns regarding the obscuration of the forward field-of-view due to the new Head-up Display (HUD) supports in conjunction with preexisting windscreen bows. An additional issue involves the proposed use of the HUD as the primary flight reference instrument. The HUD pitch ladder has been criticized for not providing enough information to enhance recovery from unusual attitudes. The purpose of the present study was, therefore, twofold: (1) to measure the levels of "target" detection with and without windscreen bows, and (2) to measure unusual attitude recovery performance using two different HUD pitch ladder formats - Standard versus Enhanced. During simulated flight, twelve subjects were required to make visual detections of enemy aircraft with and without the windscreen bow. Additionally, subjects were required to recover from various pitch/roll combinations. (Continued)					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED / UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL John E. Deaton			22b. TELEPHONE (Include Area Code) (215) 441-3119		22c. OFFICE SYMBOL Code 6021

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

S/N 0102-LF-014-6603

UNCLASSIFIED

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

BLOCK 19 (Cont.)

It was clear that removal of the windscreen bows improved target detection performance. Results of the obscuration study showed that in the first five seconds into the flight 80 percent of the targets were detected with bows off, while only 60 percent were detected with bows on. Evaluation of performance with the two HUD pitch ladder formats revealed that, at severe negative pitch attitudes, there was a marked performance benefit with the Enhanced HUD vice the Standard HUD. It was apparent that new display formats can result in significant improvements in recovering from unusual attitudes, thus addressing a vital safety of flight issue. Possible improvements in current HUD pitch ladder formats were suggested which would convey more cues to accurately and rapidly determine aircraft attitude, especially at negative pitch angles.

CONTENTS

	Page
FIGURES .....	iv
TABLES .....	iv
INTRODUCTION .....	1
BACKGROUND .....	1
METHODOLOGY .....	3
SUBJECTS .....	3
PROCEDURE .....	3
RESULTS AND DISCUSSION .....	5
HUD DISPLAY .....	5
WINDSCREEN BOWS .....	8
POSSIBLE HUD FORMAT ENHANCEMENTS .....	8
REFERENCES .....	13



Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Contract No.	
Availability Codes	
Dist	Availability for Special
A-1	

**NADC-89084-60**

**FIGURES**

<b>Figure</b>		<b>Page</b>
1	Standard and Enhanced HUD Formats.....	4
2	Unusual Attitude Recovery Performance for Each Unusual Attitude Configuration.....	7
3	Effect of Windscreen Bows on Percentage of Target Detection as a Function of Target Range.....	9
4	Effect of Windscreen on Percentage of Target Detection as a Function of Target Detection Time.....	10

**TABLE**

<b>Table</b>		<b>Page</b>
1	Unusual Attitude Recovery Criteria.....	6

# NADC-89084-60

## INTRODUCTION

### BACKGROUND

During the upgrade of the F-14 to the F-14D, pilots have expressed their concerns regarding the obscuration of the forward field-of-view due to the new Head-up Display (HUD) supports in conjunction with preexisting windscreen bows. The fact that the windscreen bows may hinder enemy aircraft detection, has led to the recommendation that a clear windscreen design, similar to the F/A-18, be considered as a replacement for the current windscreen. What effect the obscuration has on operational performance has not been systematically investigated.

An additional issue with the F-14 upgrade involves the proposed use of the HUD as the primary flight reference instrument. The attitude directional indicator (ADI) is currently the conventional flight reference system used for civil and most military aircraft. The ADI provides an artificial horizon allowing the pilot to assess pitch and roll of the aircraft without referencing the earth's horizon. Color coding is used to differentiate pitch attitude above and below the horizon. Thus, the design of the ADI follows the display principle of pictorial realism in that it represents a spatial analog of the real world<sup>1</sup>. Direct comparison between the display and the real world is not possible with symbolic displays such as the HUD. In fact, previous research has criticized the use of HUDs as primary flight reference instruments and as aids to recovering from unusual attitudes<sup>2</sup>. Reference 2 compared a HUD pitch ladder to an ADI for time to recover from unusual attitudes. Results showed that decision times for the ADI were significantly faster than the pitch ladder. Reference 3 compared an electronically-drawn ADI with the HUD and found results which paralleled those found by Reference 2. Reasons for the significantly faster recovery times for the ADI were attributed to the superiority of the color coding of the ADI for sky and ground over the dashed and solid pitch lines used for ground/sky coding on the HUD format.

In general, the HUD pitch ladder has been criticized for not providing enough information to enhance recovery from unusual attitudes<sup>4</sup>. Inadequate or ambiguous attitude displays in the cockpit pose serious problems and have been identified as contributing to numerous aircraft mishaps where loss of situational awareness or spatial disorientation were listed as confirmed or probable cause factors<sup>5</sup>. An alternative explanation for the HUD's inability to aid recovery asserts that it is not so much the *lack* of information displayed, but rather, the *format* in which it is presented. Reference 6 discussed various HUD pitch ladder formats in terms of the cognitive processes involved in assessing attitude. Pitch and roll indications on various HUD formats are complex multi-dimensional stimuli. Improving these formats, by incorporating redundant cues for example, may greatly reduce cognitive processing of information for assessment of attitude.

The purpose of the present study was twofold: (1) to measure the levels of "target" detection with and without windscreen bows; and (2) to measure unusual attitude recovery performance using two different HUD pitch ladder formats. For this purpose, a standard HUD format was compared with an enhanced HUD configuration developed at the Naval Air Development Center.

**NADC-89084-60**

**THIS PAGE INTENTIONALLY LEFT BLANK**



METHODOLOGY

SUBJECTS

Twelve volunteers were used as subjects for the present study. Ten subjects were pilots currently on active duty with F-14A, F-14A+, or F-14D experience; one was on active duty with A-6/A-7 experience; and one subject was a retired pilot with F/A-18 experience. F-14 flight hours ranged from a low of 190 to a high of 2,000. Total flight hours ranged from 975 to 3,500. Two pilots had previous experience in the dynamic flight simulator (DFS). All but the A-6/A-7 pilot had experience in flying with a HUD.

PROCEDURE

The study began with a practice simulator flight which exposed the subject to all of the methods and conditions used during the primary study. Subjects were then required to fly using either a standard HUD or the enhanced-HUD format (see Figure 1). As represented in Figure 1, the enhanced HUD included the use of "sawteeth" rather than dotted lines at negative pitch attitudes. Smaller sawteeth would appear at 30° negative pitch and increase in size at 60° negative pitch. Moreover, the enhanced HUD configuration included horizon pointing tails at the inner ends of the pitch lines. Subjects were required to fly with either the windscreen bows on or off. A balanced experimental design was thus achieved by employing a Latin square design resulting in four experimental profiles employing one of four combinations of bows (on/off) and HUD format (standard/enhanced). Each profile consisted of six segments referred to as "maneuvers" which dictated a specific commanded heading, altitude, airspeed, pitch, and roll. During each maneuver, five targets were pre-programmed to appear at randomized locations, orientations (aspects), and times. To quantify and control the position of the target, the forward field-of-view (FOV) was divided up into a series of imaginary grids. Exposure of the pilot to the target began by the random placement of the target at various grid locations in the pilot's forward FOV at an initial range (15,000 feet). The target remained fixed at this grid position (which is relative to the pilot's eyepoint) regardless of aircraft maneuvering. At a fixed-time interval (every 2 seconds), the target size would increase by a fixed amount (1,100 feet) simulating the closing range of a threat coming towards the aircraft. This continued until either the target crossed a minimum-range threshold (1,800 feet), or the pilot indicated target detection. Target detection was considered to be the first instant that the pilot detected a target to be in the FOV and was indicated verbally and with a trigger pull. To indicate trigger pull to the pilot and investigators, visual feedback was provided in the form of a large "X" appearing on the HUD. The target was automatically removed from the display if: (1) the target moved in closer than the minimum threshold; (2) target identification confirmation was recorded; or (3) the command indicating end of maneuver was received. Detection time and range was then recorded by the computer.

In between each maneuver segment, the pilot was requested to go "head down" for a total of five times for each HUD configuration. At this point, the simulation was commanded to achieve a random, pre-programmed unusual attitude from a choice of nine different pitch/roll attitude combinations which simultaneously commanded the visual display and instruments to "freeze" at their current conditions (to avoid peripheral indications as to the direction of the unusual attitude). Once the unusual attitude was achieved, the display and instruments were updated to reflect the current aircraft attitude. The subject was then instructed to return to head-up and recover the aircraft. Unusual attitude recovery time was automatically computed based on specific recovery criteria shown in Table 1. Following recovery, the pilot was instructed to return to the flight conditions of the just completed maneuver in preparation for the next maneuver. After all profiles were completed, subjects completed a Debriefing Questionnaire.




Figure 1. Standard and Enhanced HUD Formats.

## RESULTS AND DISCUSSION

## HUD DISPLAY

Data consisted of time to recover aircraft based on the criteria outlined in Table 1. These data were submitted to a  $9 \times 2$  (pitch/roll combination  $\times$  HUD configuration) analysis of variance with repeated measures on both factors. The overall analysis of variance (ANOVA) revealed a significant main effect for unusual attitude configuration ( $F(8, 64) = 10.80, p < 0.001$ ). In addition, the unusual attitude  $\times$  HUD configuration interaction effect was significant ( $F(8, 64) = 4.22, p < .001$ ). Tests of the simple effects of HUD format for each unusual attitude configuration revealed a significant HUD effect for unusual attitude #3 [ $-35^\circ$  pitch/ $0^\circ$  roll], ( $F(1, 8) = 14.72, p < .01$ ), unusual attitude #4 [ $-35^\circ/30^\circ$ ], ( $F(1, 8) = 17.44, p < .01$ ), unusual attitude #5 [ $0^\circ/30^\circ$ ], ( $F(1, 8) = 9.47, p < .05$ ), and unusual attitude #9 [ $-65^\circ/150^\circ$ ], ( $F(1, 8) = 6.93, p < 0.05$ ). Figure 2 shows unusual attitude recovery performance for each of the nine pitch/roll configurations. Considering only the cases in which a significant difference was reported between Standard and Enhanced HUDs, with the exception of unusual attitude #5, the significant differences reported above resulted in faster recovery time for the Enhanced HUD.

While a difference between formats appeared at unusual attitude #2 ( $+35^\circ/30^\circ$ ), this difference was not significant due to the variation in recovery techniques used by the pilots. For example, some pilots chose to simply "push" the nose down (negative Gz), while others took the aircraft through a  $360^\circ$  roll to maintain positive Gz. At the condition with  $-35^\circ$  pitch and  $150^\circ$  roll, the performance difference between the two HUD formats was negligible. Similar results were obtained for unusual attitudes that included only roll ( $120^\circ$  and  $180^\circ$ ). The Enhanced HUD was only marginally superior in these two cases.

The marked performance benefit of the Enhanced HUD was particularly apparent at severe negative pitch attitudes. This was to be expected since the design of the Enhanced HUD included features which were apparent only at negative pitch angles (the sawteeth). The major performance difference between HUD configurations occurred at the condition with  $-65^\circ$  nose down pitch and  $150^\circ$  right roll (nearly inverted). With the Enhanced HUD, recovery times were 24 percent shorter than with the Standard HUD. At the two conditions with  $-35^\circ$  nose down attitudes with little or moderate roll, the Enhanced HUD exhibited 20 percent and 26 percent shorter recovery times, respectively.

The overall difference in recovery performance for Enhanced versus Standard HUD format was less than 1 percent. This was misleading, however, due to the fact that much of the unusual attitude data was acquired for conditions at which one should not expect much improvement in recovery performance due to the Enhanced HUD. That is, in situations involving little roll or positive pitch, there is little reason to believe that the Enhanced HUD would be of benefit. These particular configurations were included in the study primarily to serve as baseline data in which to compare performance obtained in negative pitch situations. For those conditions where the Enhanced HUD might be expected to show some performance gains, e.g.,  $-35^\circ/0^\circ$ ,  $-35^\circ/30^\circ$ , and  $-65^\circ/150^\circ$ , the Enhanced HUD demonstrated significant improvements in recovery times on the order of 24 percent.

In terms of questionnaire data, pilots rated the performance of the Standard HUD and the Enhanced HUD in its ease of determining aircraft attitude during routine maneuvering. On a scale of 0 (Very Easy) to 10 (Very Difficult), subjects rated the Enhanced HUD and Standard HUD as 3.33 and 4.25, respectively. For assisting in recovering from unusual attitudes, the HUD's were rated on a scale of 0 (Little Help) to 10 (Very Helpful). The Standard HUD was rated at 5.25 (Moderate Help), while the Enhanced HUD was rated at 7.5. This 25 percent higher rating indicates that the pilots felt the Enhanced HUD to be superior in assisting them in recovering from unusual attitudes. When asked to

Table 1. Unusual Attitude Recovery Criteria.

<u>PARAMETER</u>		<u>CRITERIA</u>
ALTITUDE	>	0 FEET
AIRSPED	>	180 KNOTS
BANK ANGLE	<	30 DEGREES

THE PITCH AND VERTICAL VELOCITY CRITERIA WERE CONTINGENT ON THE INITIAL COMMANDED PITCH ATTITUDE:

	<u>INITIAL U.A. PITCH ATTITUDE</u>		
	NEGATIVE	0	POSITIVE
PITCH (DEG)	> -10	< 10	< 10
VERTICAL VELOCITY (FT/MIN)	> -100	> -100	< 1200




Figure 2. Unusual Attitude Recovery Performance for Each Unusual Attitude Configuration.

## NADC-89084-60

choose a HUD preference for routine and emergency/misoriented flight, the results showed that only one pilot selected the Standard HUD. Ten pilots chose the Enhanced HUD while one subject indicated no preference.

### WINDSCREEN BOWS

The dependent variables examined to analyze the effects of windscreen bow obscuration were the range at which the targets were detected, and the time-to-detect each target. Figure 3 shows the percentage of target detection versus target detection range. According to Figure 3, 59 percent of the targets were detected at the initial range with the windscreen bows removed. This is almost double the value of 32 percent detected at the initial range when the windscreen bows were installed. Though this ratio of nearly 2:1 is not maintained as range decreases, the effect of the windscreen bow on ability to detect targets persists to the point where the targets are automatically removed from the visual display and a "miss" is recorded.

Figure 4 shows the effect of windscreen on percentage of target detection as a function of target detection time. The overall ANOVA associated with average time to detect targets revealed a significant effect for windscreen bows ( $F(1, 7) = 16.90, p < 0.01$ ). More specifically, within the first five seconds, 80 percent of the targets were detected with the bows off, while only 60 percent were detected with the bows on. This represents approximately a 33 percent improvement in the ability to detect targets with removal of the windscreen bows.

Questionnaire data for the obscuration portion required pilots to rate the degree to which the windscreen bows obscured the forward FOV in their aircraft and in the DFS. Results indicated that the pilots felt that the DFS matched the level of obscuration in the actual aircraft (32 percent and 31.7 percent obscured ratings were reported for their aircraft and the DFS, respectively). The obscuration, due to the HUD supports, was rated as 10 percent.

Results clearly supported the recommendation for removal of the windscreen bows. In addition, it was apparent that new display formats can result in significant improvements in recovering from unusual attitudes.

### POSSIBLE HUD FORMAT ENHANCEMENTS

There have been numerous suggestions for changing HUD format configurations. The most promising recommendations have been made by an Air Force study.<sup>4</sup> The results of this study have shown that a 2:1 pitch-scale compression ratio is advantageous in recovering from an unusual attitude. Moreover, additional bank information and an upward pointing cue (Augie Arrow) on the velocity vector has been shown to be effective. The appearance of the Augie Arrow should be automatic whenever some attitude parameters are exceeded. For example, whenever pitch exceeds plus or minus 8° or 40° angle-of-bank, the Augie Arrow would be enabled. Using this algorithm removes the Augie Arrow from the display during most of the nearly level flight regimes. According to the Air Force study, automatic deletion of the velocity vector symbol at high angles-of-attack also enhances recovery.

Another format which is gaining in popularity is a pictorial display designed by Gilbert Klopstein of the French Service Technique Aeronautique for use during instrument approaches. In brief, this display was designed under the assumption that it is easier to interpret glideslope and azimuth deviations from a drawing of the runway environment than from Instrument Landing System needles. The Klopstein HUD has been implemented on some commercial aircraft HUD's and is used on the Navy A-6 Head-Down Display when the landing mode option is selected. In addition to the runway symbol, this format




Figure 3. Effect of Windscreen Bows on Percentage of Target Detection as a Function of Target Range.




Figure 4. Effect of Windscreen on Percentage of Target Detection as a Function of Target Detection Time.



## NADC-89084-60

also includes flight-path angle, angle-of-attack, heading, and track-angle information. It is important to note that none of this information is presented using digital readouts. The usefulness of the Klopstein HUD has not as yet been documented. However, the concept does have appeal in terms of displaying real-world cues (pictorial realism).

Other display methodologies have been suggested which enhance the rather poor three-dimensional spatial awareness characteristics of current HUDs.<sup>7</sup> One such approach is associated with the development of a textured standby attitude display. Attitude recognition is enhanced by a "full-ball display" (even though it may be very small — on the order of 30 mr). The "ground" of the display is textured rather than solid filled, preferably using a graduated horizontal and point perspective vertical field. The standby textured ball should be positioned down on the lower right of the HUD display. At this position it is unobtrusive but still available for immediate reference.

Numerous other design features have been suggested. The interested reader is encouraged to consult Reference 4 for examples of additional format recommendations. Clearly, modifications to HUD configurations can enhance recovery from unusual attitudes. The present study revealed that at severe negative pitch attitudes, there is a marked performance benefit with the Enhanced HUD used in this study compared to the Standard HUD. It is recommended that future investigations develop additional HUD pitch ladder format possibilities conveying more cues to accurately and rapidly determine aircraft attitude in order to enhance situational awareness.

**NADC-89084-60**

**THIS PAGE INTENTIONALLY LEFT BLANK**

## NADC-89084-60

### REFERENCES

1. Roscoe, S.N., Corl, L., & Jensen, R.S., Flight Display Dynamics Revisited, *Human Factors*, 23(3), 341-353, 1981.
2. Kinsley, S.A., Warner, N.W., & Gleisner, D.P., *A Comparison of Two-Pitch Ladder Formats and an ADI Ball for Recovery From Unusual Attitudes*. Naval Air Development Center (Report No. NADC-86012-60), 1985.
3. Guttman, J., *Evaluation of the F/A-18 Head-up Display for Recovery from Unusual Attitudes*. Naval Air Development Center (Report No. NADC-86157-60), 1986.
4. Newman, R., *Evaluation of Head-up Displays to Enhance Unusual Attitude Recovery*. Flight Dynamics Laboratory, Wright-Patterson Air Force Base, OH (Report No. AFWAL-TR-87-3055), 1987.
5. Kennedy, D., Better Attitude Displays for Enhanced Situational Awareness, *Approach*, 15, 25-32, 1987.
6. Taylor, R., *Some Effects of Display Format Variables on the Perception of Aircraft Spatial Orientation*. Presented at the NATO AGARD Medical Panel Symposium, Williamsburg, VA., 1984.
7. Hughes, R.E., *General Recommendations for Head-up Display Symbology for Fixed-wing Vehicles*. Naval Air Systems Command. Unpublished manuscript, 1989

**NADC**

**THIS PAGE INTENTIONALLY LEFT BLANK**

DISTRIBUTION LIST

REPORT NO. NADC-89084-60

	<i>No. of Copies</i>
Grumman Aerospace Corporation, L.I., N.Y. 11714..... (1 copy for Flight Test Division, Attn: R. Goodman) (1 copy for Attn: G. Ricard)	2
Defense Technical Information Center..... Attn: DTIC-FDAB Cameron Station BG5 Alexandria, VA 22304-6145	2
Center for Naval Analysis ..... 4401 Fort Avenue P.O. Box 16268 Alexandria, VA 22302-0268	1
1299th Physiological Flight Training ..... Malcolm Grow USAF Medical Center Andrews AFB, Washington, DC 20331-5300	1
NASA ..... Langley Research Center Hampton, VA 23665 (1 for Attn: L. Nguyen)	1
NASA ..... Hugh L. Dryden Flight Research Center P.O. Box 273 Edwards, CA 93523 (1 for Code E-EDC)	1
Naval Air Development Center ..... Warminster, PA 18974-5000 (2 for Code 8131) (1 for Code 2A1) (1 for Code 20A) (1 for Code 60B) (1 for Code 60B3) (1 for Code 6025) (1 for Code 602) (1 for Code 6022) (1 for Code 6021)	30

DISTRIBUTION LIST

REPORT NO. NADC-89084-60

*No. of Copies*

Naval Air Systems Command.....	15
Washington, DC 20361-0001	
(2 for AIR-5004)	
(2 for PMA-241)	
(1 for APC-205)	
(1 for AIR-511)	
(1 for AIR-5113B)	
(1 for AIR-5116B)	
(1 for AIR-530)	
(1 for AIR-53011)	
(1 for AIR-531)	
(1 for AIR-531B)	
(1 for AIR-5313)	
(1 for AIR-610)	
(1 for AIR-620)	
Chief of Naval Operations.....	3
Washington, DC 20350-2000	
(1 for OP-98)	
(1 for OP-506)	
(1 for OP-506N)	
Naval Safety Center.....	1
Naval Air Station	
Norfolk, VA 23511	
(1 for F-14 Analyst (Code 10))	
Naval Air Test Center.....	4
Patuxent River, MD 20670-5304	
(1 for Code SATD)	
(1 for Code SETD)	
(1 for Test Pilot School; Chief Flight Instructor)	
(1 for Code SY70)	
Naval Training Systems Center .....	2
(1 for Code 711)	
(1 for Code 222)	