

AD-A220 537

INTENSE ION BEAM FROM A MAGNETICALLY INSULATED DIODE WITH
AN ACTIVE ANODE SOURCE

A Thesis

Presented to the Faculty of the Graduate School
of Cornell University
in Partial Fulfillment of the Requirements for the Degree of
Doctor of Philosophy

by

Mario Ueda

August 1986

DTIC
ELECTE
APR 13 1990
S E D

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

90 04 12

Available from University Microfilms
Zeeb Road, Ann Arbor, MI 48106

INTENSE ION BEAM FROM A MAGNETICALLY INSULATED
DIODE WITH AN ACTIVE ANODE SOURCE

Mario Ueda, Ph.D.
Cornell University 1986

A magnetically insulated diode using an active anode plasma ion source was developed and thoroughly characterized. In this extraction-geometry ion diode, an anode plasma of annular shape and 30 cm diameter is formed independently of the injector voltage pulse. The anode plasma is produced by inductive voltage breakdown of a radially expanding gas cloud supplied by a fast puff valve. This diode was driven by the low voltage (<200 kV), long pulse ($>1 \mu\text{s}$) LONGSHOT II generator. It was capable of producing prompt ion current turn-on, long pulse ($1 \mu\text{s}$), high current density ($>100 \text{ A/cm}^2$) proton beam output at 70-150 keV when using hydrogen gas. Other characteristics of this diode include: extraction of a pure proton beam within the 20% measurement uncertainty; diode voltage pulse shape (flat, decreasing or increasing in time) and pulse length control by injection of the anode plasmas with differing density and/or timing; capable of flat or increasing impedances; an effective gap closure velocity of $< 2 \text{ mm}/\mu\text{s}$ during the main power pulse;

low neutral to plasma density ratio at the gap; up to 5 J/cm² energy density deposited over a beam extraction area of 300 cm²; more than 1×10^{17} particles per pulse with > 60 keV; global beam uniformity better than $\pm 35\%$ (10% on a 1 cm length scale); ion current efficiency of at least 40%; and typical divergence of $< 3^\circ$ half angle. With a nitrogen gas puff, beams with similar pulse shapes and current densities to the proton beams were obtained. No major diode components replacement was needed for over 700 shots. The aiming angle of the extracted beam varied in time and space by more than 25° (in the radial direction) when a high ion current density (> 60 A/cm²) was extracted and plasma was present in the diode when the high voltage pulse was applied. It was possible to eliminate the aiming angle variation for high current density beams by applying the high voltage pulse before plasma reached the gap or by using a conducting mesh anode. *Basics, 1/11*

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<i>per</i>
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<i>A-1</i>	