

AAMRL-SR-90-508

DTIC FILE COPY

## AD-A231 698

A MOTION ACTIVATED ARTICULATING SEAT (MAAS) - A DYNAMIC CONCEPT FOR COCKPIT SEAT DESIGN IN HIGH PERFORMANCE AIRCRAFT

T

VANCE D. SKOWRONSKI ROBERT L. ESKEN JAMES COOPER ALVA KARL\*

HARRY G. ARMSTRONG AEROSPACE MEDICAL RESEARCH LABORATORY

\*SYSTEMS RESEARCH LABORATORIES, INC.

NOVEMBER 1990

Final Report for the Period August 1987 through August 1988

Approved for public release; distribution is unlimited

HARRY G. ARMSTRONG AEROSPACE MEDICAL RESEARCH LABORATORY HUMAN SYSTEMS DIVISION AIR FORCE SYSTEMS COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-6573



91 2 07 046

## NOTICES

When US Government drawings, specifications or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Federal Government agencies registered with Defense Technical Information Center should direct requests for copies of this report to:

> Defense Technical Information Center Cameron Station Alexandria, Virginia 22314

TECHNICAL REVIEW AND APPROVAL

AAMRL-SR-90-508

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER

JAMES W. BRINKLEY, SES Director Biodynamics and Bioengineering Division Armstrong Aerospace Medical Research Laboratory



LeooA	sion For		
NTIS	GRA&I	P	
DTIC	TAB	ā	
Unann	ounced		
Justi	fication_		
By			
Distr	ibution/		
Avai	lability (	Codes	
	Avet1 and	/or	
Dist	Special		
1	Ì	}	
N-1		[	
n i			

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of ini- gathering and maintaining the data needed, an collection of information, including suggestions Davis Highway, Suite 1204, Arlington, VA 22202	ormation is estimated to average 1 hour per d completing and reviewing the collection of for reducing this burden. To Washington Hei -4302, and to the Office of Management and	response, including the time for in information. Send comments rega- adquarters Services, Directorate fo Budget, Paperwork Reduction Pro-	eviewing instructions, irding this burden esti r information Operati ject (0704-0188), Wash	searching existing data source mate or any other aspect of th ons and Reports, 1215 Jeffers lington, DC 20503	
1. AGENCY USE ONLY (Leave blar	k) 2. REPORT DATE	3. REPORT TYPE AN	D DATES COVE	RED	
4. TITLE AND SUBTITLE		Special Repor	<u>t – Aug 87</u> 5. funding n	<u> </u>	
A Motion Activated Articulating Seat (MAAS) - A Dynamic Concept For Cockpit Seat Design In High Performance Air- craft			723125D1		
6. AUTHOR(S)		· · · · · · · · · · · · · · · · · · ·			
Vance D. Skowronski, H and Alva Karl	Robert Esken, Lt Col J	ames Cooper,			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMIN	G ORGANIZATION	
Harry G. Armstrong Aerospace Medical Research Laboratory Wright Patterson AFB, OH 45433-6573			AAMRL-SR-90-508		
SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		;;;	10. SPONSORING / MONITORING AGENCY REPORT NUMBER		
		<b></b>			
		يند			
inpproved for rubite in	icase, distribution i	5 UNIIMILEU			
13. ABSTRACT (Maximum 200 word	s)				
The motion ac in lifting the sho MAAS system has th require a differen changing mission r	tivated articulati ulder/upper torso e ability to respo t shoulder/upper t equirements, such	ng seat (MAAS while flying and rapidly sh corso position	) is a pi an aircra ould the 'in respo 6". The	lot aid ft. The pilot onse to	
approach uses a hi specialized video geometrically desi functionable) with with a 30 degree s identifiable indic software program. successfully proce motion. The video laboratory researc	gh speed desk top processing capture aned air bags ( th operational valvi eat back angle, a ators, and an in h The system has be ssed head/helmet m capture technique h efforts.	as checking " computer, a v board, a set ng, a modifie flight helmet ouse develope en demonstrat ovements for is being app	ideo came of speci ntly d cockpit with d operati ed static generatir lied to c	era, a fically seat ng ally and g seat other	
approach uses a hi specialized video geometrically desi functionable) with with a 30 degree s identifiable indic software program. successfully proce motion. The video laboratory researc	gh speed desk top processing capture aned air bags ( th operational valvi eat back angle, a ators, and an in h The system has be ssed head/helmet m capture technique h efforts.	as checking " computer, a v board, a set ree independe ng, a modifie flight helmet ouse develope en demonstrat ovements for is being app	ideo came of speci ntly d cockpit with d operati ed static generatir lied to c	era, a fically seat ng ally and ng seat other	
approach uses a hi specialized video geometrically desident functionable) with with a 30 degree s identifiable indic software program. successfully proce motion. The video laboratory research <b>14. SUBJECT TERMS</b> (II) Aircraft Cockpit S (U) Video Capture, (U)	gh speed desk top processing capture aned air bags ( th operational valvi eat back angle, a ators, and an in h The system has be ssed head/helmet m capture technique h efforts. eat, (U) Bioengineeri Shoulder Lift	as checking " computer, a v board, a set ing, a modifie flight helmet touse develope en demonstrat ovements for is being app	ideo came of speci ntly d cockpit with d operati ed static generatir lied to c	era, a fically seat ng ally and og seat other UMBER OF PAGES	
approach uses a hi specialized video geometrically design functionable) with with a 30 degree s identifiable indic software program. successfully proce motion. The video laboratory research 14. SUBJECT TERMS (") Aircraft Cockpit S (U) Video Capture, (U) 17. SECURITY CLASSIFICATION OF REPORT Unclassified	gh speed desk top processing capture aned air bags ( th operational valvi eat back angle, a ators, and an in h The system has be ssed head/helmet m capture technique h efforts. eat, (U) Bioengineeri Shoulder Lift Shoulder Lift IS. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	as checking " computer, a v board, a set ree independe ing, a modifie flight helmet iouse develope en demonstrat ovements for is being app	ideo came of speci ntly d cockpit with d operatic generatic lied to c 15. N 16. P	era, a fically seat ng ally and og seat other UMBER OF PAGES RICE CODE	

,

Prescribed by ANSI Std 239-18

A Motion Activated Articulating Seat (MAAS) - A Dynamic Concept For Cockpit Seat Design In High Performance Aircraft

<u>BACKGROUND:</u> In air to air combat, it is assumed that the aircraft having the highest agility and G maneuvering capability have a decided tactical advantage over less capable systems. If two aircraft have the same operational flight characteristics there is another area that can influence the outcome; this is the position of the pilot in his seat. One of the most effective techniques for increasing man's tolerance to +Gz sustained acceleration is the use of reclined seats. Such seats, if properly designed, markedly decrease the effective length of the hydrostatic column of blood between the heart and the eyes, consequently reducing the pressure required to maintain retinal and cerebral perfusion.

To date, no design for such a seat has taken into account the fundamental objection voiced by fighter pilots to the effect that reclined seats do not permit them aftward vision into the plane normal to the lift vector of their aircraft. When seated in a radically reclined seat, rotating the head and torso (in order to look aft) results in an intrapupillary plane that is tilted away from vertical by an amount approximately equal to the back angle of the seat. Thus, in order to look into the required plane, the head must be rotated in the forward direction relative to the aircraft longitudinal axis while simultaneously rotated to the left or right. Unfortunately this is physically impossible.

A number of attempts have been made to improve mobility in a reclined seat. A Restraint and Mobility Test Fixture (RMTF) has been built with a swiveling back pan to make it easier to rotate the torso in a reclined position. Unfortunately, this concept does nothing to improve aftward vision.

<u>PURPOSE:</u> To evaluate the concept of a nonintrusive motion activated shoulder/upper torso articulating high performance cockpit seat.

<u>OBJECTIVE:</u> To develop a MAAS capable of rapidly shifting the pilot's shoulder position in response to changing mission requirements. In air combat, the ability of the pilot to check "6" may be enhanced with the assistance of a shoulder lift device. In either flying to a mission or in an air/ground engagement the operator may desire an upper torso aid.

<u>APPROACH:</u> Involved the use of a system, driven by a 386 computer, which consisted of a video camera, a specialized video processing capture board, a set of specifically geometrically designed air bags (3 independently functionable) with operational valving, a modified cockpit seat with a 30 degree back angle, a flight helmet with identifiable indicators, and an in house developed operating software program. <u>RESULTS</u> Dynamic testing of the total integrated system demonstrated the ability of this methodology to respond to the shoulder/upper torso lift demands of the user. The video capture technique using head position detection was successful and an Air Force invention and patent have been applied for. The video capture technique is also being used in another laboratory application. This technology may be used in future reclined/articulating seat research at AAMRL and at USAFSAM.

<u>CONCLUSIONS</u> The use of this technology requires no verbal or manual input from the pilot (two channels which are often oversaturated and cannot be used). Helmet motion is used to trigger the system. Thus, a system has been demonstrated which can afford the pilot increased operational capability during mission accomplishment with minimal increase in workload.