

AD-A235 589

2



US Army Corps
of Engineers
Hydrologic Engineering Center

Predicting Deposition Patterns in Small Basins

Technical Paper No. 133
March 1991

DTIC
ELECTE
MAY 13 1991
S E D

Approved for Public Release. Distribution is Unlimited.

91 5 10 048



Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

PREDICTING DEPOSITION PATTERNS IN SMALL BASINS¹

By D. Michael Gee, Research Hydraulic Engineer, Hydrologic Engineering Center, Davis, CA.

ABSTRACT

A technique for estimating sediment depositional patterns based upon flow patterns is described. Flow patterns are computed using a finite element model for two-dimensional, vertically averaged flow. Once the velocity and depth fields are computed, the bed shear stress distribution can be found. If the annual volume and approximate particle size of the inflowing load is known, anticipated depositional locations and quantities can then be estimated. Use of this technique to forecast the temporal development of the deposits by computing the velocity fields for several steady flow conditions is described. The resulting graphical displays of velocity fields and shear stress contours are very useful to the design engineer. This procedure avoids the complexity associated with use of a two-dimensional sediment transport and dispersion model. Application of the technique to the design of a basin 180 ft. (55 m.) wide by 610 ft. (186 m.) long is described.

INTRODUCTION


Conventional sediment basin design procedures rely on volumetric relationships to determine flow through times, estimated trap efficiency, and average annual deposition rates. Design guidance has been prepared by USACE (1989). These approaches do not necessarily reflect the interaction between changes in bed topography due to scour and/or deposition and the influence of these changes on velocity and shear stress distributions. Some designs have been approached using one-dimensional numerical modeling of flow and sediment such as HEC-6 (USACE-HEC, 1990). Some concerns with these approaches are that complex velocity patterns such as recirculation and short circuiting may not be properly described. These flow patterns may result in uneven distributions of sediment concentration and, therefore, an uneven distribution of sediment deposits (Montgomery, et al. 1983). The use of a fully two-dimensional model for both flow and sediment distribution such as TABS-2 (McAnally et al. 1984) is an attractive approach to improve the prediction of the distribution of sediment deposits. The use of such a model, however, may involve more effort and data acquisition than can be justified for small basin design. The technique described herein represents a midway approach that includes the velocity and shear stress fields in detail, from which the sediment deposition distribution and rates can be inferred. A brief description of this approach was presented by Deering and Larock (1989).

MODEL SELECTION

It is assumed that the salient flow features of small basins can be described in the two horizontal directions and that the variance of velocity in the vertical is the traditional logarithmic velocity distribution for turbulent flow in open channels (French 1985). A widely used model that is suitable for this condition is RMA-2 (King & Norton 1978). RMA-2 has been applied to a wide variety of problems including floodplain analysis (Gee et al. 1990), marsh flooding (MacArthur et al. 1990), sediment basin design (Deering & Larock 1989), has been adapted for bridge design (FHWA 1989), and serves as the hydrodynamic module of the TABS-2 system (McAnally et al. 1984). This model solves the depth integrated Reynolds equations for two-dimensional free-surface flow in the horizontal plane using the finite element method for both steady and unsteady flows. The finite element

¹Presented at the Fifth Federal Interagency Sedimentation Conference, Las Vegas, Nevada, March 1991.

formulation of RMA-2 allows boundary roughness and geometric resolution to vary spatially to accurately depict topography. It also provides a wide variety of boundary conditions. Wetting and drying of portions of the solution domain is allowed. The two-dimensional approach relieves the engineer from having to construct cross sections that are perpendicular to the flow for all flows, as is required in a one-dimensional analysis.



APPROACH

An example finite element mesh is shown in Fig. 1. Note that the elements are both quadrilateral and triangular. Computational nodes exist at the corners and mid-sides of each element. The bottom elevation is given at each corner node and linearly interpolated for the mid-side nodes. Bed roughness and turbulent exchange coefficients are assigned to groups of elements (not necessarily neighbors) by the user. Solution of the two-dimensional flow equations provides the x - and y -components of the velocity, and the depth, at each computational node. The local shear stress can be calculated from these variables if one assumes that the relation for average shear in a cross section can be applied locally as follows.

$$\tau = \gamma RS \quad (1)$$

Where τ is the bed shear stress, γ is the unit weight of water, R is the hydraulic radius (taken here as the local nodal depth) and S is the friction slope. Now, rewriting Manning's equation in terms of S , we have:

$$S = \frac{n^2 u^2}{2.22 R^{4/3}} \quad (2)$$

Where u is the resultant of the calculated x and y nodal velocity components, as shown in equation (3) and n is Manning's roughness coefficient.

$$u^2 = u_x^2 + u_y^2 \quad (3)$$

Combining, we can solve for the shear stress:

$$\tau = \gamma \frac{n^2 u^2}{2.22 R^{1/3}} \quad (4)$$

One must now relate the n -values, which are associated with elements, with the computed values for u and R (depth) which are located at nodes. For this study, the n -value associated with a node was computed as the arithmetic average of the n -values for all elements connected to that node. We have placed these computations in the vector plotting program (VECTOR) which is a post-processor for RMA-2. VECTOR also prepares files of water surface elevation and velocity magnitude for contouring.

AN EXAMPLE

Introduction

The Wildcat Creek sediment basin was designed to trap sediment that potentially could cause excess scour or deposition in a downstream flood control channel. Right-of-way considerations and environmental concerns dictated the bent alignment shown in Fig. 1 (flow is from right to left). Based on cross section average velocity and settling lengths computed from the particle fall velocity, it was estimated that the basin would trap 100% of the sediment larger than fine sand (0.125 mm). A hydrodynamic analysis was performed to ascertain whether the bent alignment would indeed trap the size range and volume of sediment needed and whether high velocities would impinge on the banks requiring some form of bank protection.

Sediment Basin Description

The Wildcat Creek sediment basin was designed to have a maximum width of 180 ft. (55 m.) and length of 610 ft. (186 m.). The bottom slope is 0.0005 and the side slopes 1V:3H. The maximum depth is about 12 ft. (3.7 m.).

Hydraulics

As Wildcat Creek is ephemeral, continuous simulation was not necessary. Therefore, several hydraulic scenarios were studied to verify that the basin would perform as designed. It was planned that deposits would most likely have to be removed from the basin on an annual basis. This led to simplification in the number of conditions to be analyzed because the problem was reduced to


evaluation of the interactions between average annual deposition and the occurrence of the design (1% exceedance) event. The results presented here are only for the design event; refer to Deering and Larock (1989) for information on other scenarios. Furthermore, as the basin volume is small relative to the hydrograph volume, the analysis could be performed assuming steady flow. The 1% chance exceedance event is 2300 cfs (65 cms). The drainage area is about 7.8 mi² (2000 hectares).

Scenario

The situation presented herein represents the condition of the basin after several years' average annual deposition (not removed). The flow evaluated is that of the design (1% chance exceedance) event. The distribution of the deposits shown in Fig. 2 was created based on simulation of the shear stress distribution in the empty basin and observation of other flood control projects having similar flow and sediment transport conditions. The bar deposits are formed from flows expanding into open areas. Initial deposits will form in the lower velocity areas causing the flow to redistribute, expanding again and reinitiating the bar formation process. This results in bar formation on the left and right banks, immediately downstream of the entrance, and a central bar further downstream. The assumed deposition pattern has a volume equivalent to that of the average annual deposits for the time period selected. The nodal elevations of the finite element mesh that was developed for the design (empty) basin were modified to reflect this hypothetical deposition pattern.

Modeling parameters

The Manning's n-values were set to 0.03 for most of the basin based on it being maintained as smooth earth. The values for one portion of the left bank were set to 0.06 based on maintaining the native heavy vegetation there. The sensitivity of the results to these values, assuming the project is




not well maintained should be checked and may be significant to the design event water surface

elevation. The turbulent exchange coefficients were uniformly set to 10 lb-sec/ft² (480 N-sec/m²) for all elements. This was based on prior experience with finite element meshes of this scale. The sensitivity of the results to variation of these values within reasonable ranges was checked and found to be insignificant.

Boundary conditions

This is a simple 2-D problem in that it is analogous to traditional 1-D backwater computations with regard to boundary conditions. A discharge was specified at the upstream (right) end of the model. In 2-D, however, the direction of the discharge must be given which was selected to be perpendicular to the inflow boundary line (see Fig. 3). The downstream boundary condition was specified as a water surface elevation appropriate for the discharge being analyzed based on design studies of the downstream reach. A rating curve could have been used for the downstream boundary if appropriate. Along all other boundaries, the flow direction is parallel to the boundary.




Modeling results

The flow field for the design event is depicted on Figure 3. The flow enters the basin as a plume of relatively high velocity. Recirculation zones are seen on each side of the inflow plume. This is obviously not a one-dimensional situation. The hypothetical bar formations do not appear to force the higher velocity jet against either of the banks as originally suspected. The associated shear stress field for this flow and bottom condition is shown in Figure 4.

The shear stress is low enough that sediments of the size of interest will be trapped in the basin. Note particularly the zones of near zero shear that correspond to the recirculation cells near the left and right banks. The clustering of contours near the banks is an artifact of the contouring process.

Figure 4. Shear Stress (lb/sq ft).



CONCLUSIONS

The technique presented herein represents a midway approach to the prediction of spatially complex sediment transport processes. Much can be inferred from viewing the velocity and shear stress distributions. Once the velocity field has been computed, the computation of the shear stress distribution is trivial. If, at this stage, one determines that simulation of the full two-dimensional transport and dispersion of sediment is necessary, the hydrodynamic analysis already performed can be used directly in the sediment transport simulation.

COMPUTATIONAL ASPECTS

The finite element mesh used for this study contains about 550 elements and 1370 nodes. This produces about 2300 simultaneous equations. To solve this system for steady flow using six iterations takes about 15 minutes on a 25 MHz 386 computer. The system can be run within the DOS 640K limitation.

ACKNOWLEDGEMENTS

This study was performed for the U. S. Army Corps of Engineers District, Sacramento with the assistance of the U. S. Army Corps of Engineers Waterways Experiment Station. The opinions expressed herein are those of the author and not necessarily those of the U. S. Army Corps of Engineers.

REFERENCES

- Deering, M. K. and Larock, B. E. (1989) "The Design of Sediment Basins Using Two-Dimensional Hydrodynamic Techniques," Proceedings of the 1989 ASCE National Conference on Hydraulic Engineering, New Orleans, LA.
- Federal Highway Administration (1989) "FESWMS-2DH Finite Element Surface-Water Modeling System: Two-Dimensional Flow in a Horizontal Plane," Pub. No. FHWA-RD-88-177.
- French, R. H. (1985) "Open-Channel Hydraulics," McGraw-Hill.
- Gee, D. M., et al. (1990) "Two-Dimensional Floodplain Modeling," Proceedings of the 1990 ASCE National Conference on Hydraulic Engineering and the International Symposium on the Hydraulics/Hydrology of Arid Lands, San Diego, CA.
- King, I. P. and Norton, W. R. (1978) "Recent Application of RMA's Finite Element Models for Two-Dimensional Hydrodynamics and Water Quality," Proceedings of the 2nd. Int. Conf. on Finite Elements in Water Resources, Pentech Press, London.
- MacArthur, R. C., et al. (1990) "Two-Dimensional Finite Element Simulation of the Flooding Characteristics in Kawainui Marsh, Hawaii," Proceedings of the 1990 ASCE National Conference on Hydraulic Engineering and the International Symposium on the Hydraulics/Hydrology of Arid Lands, San Diego, CA.
- McAnally, W. H., et al. (1984) "Application of Columbia Hybrid Modeling System," Jour. Hyd. Engr., ASCE Vol. 110, No. 5, Paper 18796.
- Montgomery, R. L., et al. (1983) "Dredged Material Sedimentation Basin Design," Jour. Env. Engineering, ASCE, Vol 109, No. 2.
- U. S. Army Corps of Engineers (1989) "Sedimentation Investigations of Rivers and Reservoirs," Engineer Manual 1110-2-4000.
- U. S. Army Corps of Engineers Hydrologic Engineering Center (1990) "HEC-6 Scour and Deposition in Rivers and Reservoirs," Users Manual.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

TECHNICAL PAPER SERIES
(\$2.00 per paper)

- | | | | |
|-------|---|-------|---|
| TP-1 | Use of Interrelated Records to Simulate Streamflow | TP-37 | Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes |
| TP-2 | Optimization Techniques for Hydrologic Engineering | TP-38 | Water Quality Evaluation of Aquatic Systems |
| TP-3 | Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs | TP-39 | A Method for Analyzing Effects of Dam Failures in Design Studies |
| TP-4 | Functional Evaluation of a Water Resources System | TP-40 | Storm Drainage and Urban Region Flood Control Planning |
| TP-5 | Streamflow Synthesis for Ungaged Rivers | TP-41 | HEC-5C, A Simulation Model for System Formulation and Evaluation |
| TP-6 | Simulation of Daily Streamflow | TP-42 | Optimal Sizing of Urban Flood Control Systems |
| TP-7 | Pilot Study for Storage Requirements for Low Flow Augmentation | TP-43 | Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems |
| TP-8 | Worth of Streamflow Data for Project Design - A Pilot Study | TP-44 | Sizing Flood Control Reservoir Systems by Systems Analysis |
| TP-9 | Economic Evaluation of Reservoir System Accomplishments | TP-45 | Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin |
| TP-10 | Hydrologic Simulation in Water-Yield Analysis | TP-46 | Spatial Data Analysis of Nonstructural Measures |
| TP-11 | Survey of Programs for Water Surface Profiles | TP-47 | Comprehensive Flood Plain Studies Using Spatial Data Management Techniques |
| TP-12 | Hypothetical Flood Computation for a Stream System | TP-48 | Direct Runoff Hydrograph Parameters Versus Urbanization |
| TP-13 | Maximum Utilization of Scarce Data in Hydrologic Design | TP-49 | Experience of HEC in Disseminating Information on Hydrological Models |
| TP-14 | Techniques for Evaluating Long-Term Reservoir Yields | TP-50 | Effects of Dam Removal: An Approach to Sedimentation |
| TP-15 | Hydrostatistics - Principles of Application | TP-51 | Design of Flood Control Improvements by Systems Analysis: A Case Study |
| TP-16 | A Hydrologic Water Resource System Modeling Techniques | TP-52 | Potential Use of Digital Computer Ground Water Models |
| TP-17 | Hydrologic Engineering Techniques for Regional Water Resources Planning | TP-53 | Development of Generalized Free Surface Flow Models Using Finite Element Techniques |
| TP-18 | Estimating Monthly Streamflows Within a Region | TP-54 | Adjustment of Peak Discharge Rates for Urbanization |
| TP-19 | Suspended Sediment Discharge in Streams | TP-55 | The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers |
| TP-20 | Computer Determination of Flow Through Bridges | TP-56 | Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models |
| TP-21 | An Approach to Reservoir Temperature Analysis | TP-57 | Flood Damage Assessments Using Spatial Data Management Techniques |
| TP-22 | A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media | TP-58 | A Model for Evaluating Runoff-Quality in Metropolitan Master Planning |
| TP-23 | Uses of Simulation in River Basin Planning | TP-59 | Testing of Several Runoff Models on an Urban Watershed |
| TP-24 | Hydroelectric Power Analysis in Reservoir Systems | TP-60 | Operational Simulation of a Reservoir System with Pumped Storage |
| TP-25 | Status of Water Resource Systems Analysis | TP-61 | Technical Factors in Small Hydropower Planning |
| TP-26 | System Relationships for Panama Canal Water Supply | TP-62 | Flood Hydrograph and Peak Flow Frequency Analysis |
| TP-27 | System Analysis of the Panama Canal Water Supply | TP-63 | HEC Contribution to Reservoir System Operation |
| TP-28 | Digital Simulation of an Existing Water Resources System | TP-64 | Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study |
| TP-29 | Computer Applications in Continuing Education | TP-65 | Feasibility Analysis in Small Hydropower Planning |
| TP-30 | Drought Severity and Water Supply Dependability | TP-66 | Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems |
| TP-31 | Development of System Operation Rules for an Existing System by Simulation | TP-67 | Hydrologic Land Use Classification Using LANDSAT |
| TP-32 | Alternative Approaches to Water Resource System Simulation | TP-68 | Interactive Nonstructural Flood-Control Planning |
| TP-33 | System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation | TP-69 | Critical Water Surface by Minimum Specific Energy Using the Parabolic Method |
| TP-34 | Optimizing Flood Control Allocation for a Multipurpose Reservoir | TP-70 | Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model |
| TP-35 | Computer Models for Rainfall-Runoff and River Hydraulic Analysis | | |
| TP-36 | Evaluation of Drought Effects at Lake Atitlan | | |

- TP-71 Determination of Land Use from Satellite Imagery for Input to Hydrologic Models
- TP-72 Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality
- TP-73 Flood Mitigation Planning Using HEC-SAM
- TP-74 Hydrographs by Single Linear Reservoir Model
- TP-75 HEC Activities in Reservoir Analysis
- TP-76 Institutional Support of Water Resource Models
- TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
- TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
- TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U. S. Hydropower Reservoirs
- TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
- TP-81 Data Management Systems for Water Resources Planning
- TP-82 The New HEC-1 Flood Hydrograph Package
- TP-83 River and Reservoir Systems Water Quality Modeling Capability
- TP-84 Generalized Real-Time Flood Control System Model
- TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
- TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
- TP-87 Documentation Needs for Water Resources Models
- TP-88 Reservoir System Regulation for Water Quality Control
- TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
- TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
- TP-91 HEC Software Development and Support
- TP-92 Hydrologic Engineering Center Planning Models
- TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Computer Program
- TP-94 Dredged-Material Disposal Management Model
- TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
- TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
- TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
- TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
- TP-99 Reservoir System Analysis for Water Quality
- TP-100 Probable Maximum Flood Estimation - Eastern United States
- TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
- TP-102 Role of Calibration in the Application of HEC-6
- TP-103 Engineering and Economic Considerations in Formulating
- TP-104 Modeling Water Resources Systems for Water Quality
- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model For Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computed Water Surface Profiles - Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the MicroComputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of the U.S. Army Corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Technical Paper No. 133		5. MONITORING ORGANIZATION REPORT NUMBER(S)	
5a. NAME OF PERFORMING ORGANIZATION Hydrologic Engineering Center	6b. OFFICE SYMBOL (If applicable) CEWRC-HEC	7a. NAME OF MONITORING ORGANIZATION U.S. Army Corps of Engineers Water Resources Support Center	
5c. ADDRESS (City, State, and ZIP Code) 609 Second Street Davis, California 95616		7b. ADDRESS (City, State, and ZIP Code) Casey Building #2594 Fort Belvoir, Virginia 22060	
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
5c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO.	PROJECT NO.
		TASK NO.	WORK UNIT ACCESSION NO.

1. TITLE (Include Security Classification)
Predicting Deposition Patterns in Small Basins

2. PERSONAL AUTHOR(S)
D. Michael Gee

3a. TYPE OF REPORT Technical Paper	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) March 1991	15. PAGE COUNT 7
---------------------------------------	--	---	---------------------

6. SUPPLEMENTARY NOTATION

7. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Two-dimensional Flow, Finite Elements, Sediment Transport Modeling
FIELD	GROUP	SUB-GROUP	

9. ABSTRACT (Continue on reverse if necessary and identify by block number)
A technique for estimating sediment depositional patterns based upon flow patterns is described. Flow patterns are computed using a finite element model for two-dimensional, vertically averaged flow. Once the velocity and depth fields are computed, the bed shear stress distribution can be found. If the annual volume and approximate particle size of the inflowing load is known, anticipated depositional locations and quantities can then be estimated. Use of this technique to forecast the temporal development of the deposits by computing the velocity fields for several steady flow conditions is described. The resulting graphical displays of velocity fields and shear stress contours are very useful to the design engineer. This procedure avoids the complexity associated with use of a two-dimensional sediment transport and dispersion model. Application of the technique to the design of a basin 180 ft. (55 m.) wide by 610 ft. (186 m.) long is described.

10. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION	
2a. NAME OF RESPONSIBLE INDIVIDUAL Darryl W. Davis, Director, HEC		22b. TELEPHONE (Include Area Code) (916) 756-1104	22c. OFFICE SYMBOL CEWRC-HEC