

REPORT DC

AD-A238 119

Form Approved
OMB No 0704-0188

2

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering the data needed, and reviewing and maintaining the data needed, and completing and reviewing the collection of information, including suggestions for reducing the burden. Send comments to Washington, DC 20503-4

Do not send this report to the DTIC unless you are specifically instructed to do so. Do not disseminate this report outside your organization unless you are specifically instructed to do so. For information on the DTIC Project (0704-0188) Washington, DC 20503

1. AGENCY USE ONLY (Leave blank) 2. REPORT DATE 07/09/91 3. REPORT TYPE AND DATES COVERED POP Test (06/91)

4. TITLE AND SUBTITLE
Performance Oriented Packaging Testing of Mk 588 Shipping and Storage Drum for Packing Group II Solid Hazardous Materials

5. FUNDING NUMBERS

6. AUTHOR(S)
Eric Wu

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
Naval Weapons Station Earle
Test and Evaluation Division (Code 403)
Colts Neck, NJ 07722-5000

8. PERFORMING ORGANIZATION REPORT NUMBER
DODPOPHM/USA/DOD/
NADTR91018

9. SPONSORING, MONITORING AGENCY NAME(S) AND ADDRESS(ES)
Naval Weapons Station Earle
Test and Evaluation Division (Code 8024)
Colts Neck, NJ 07722-5000

10. SPONSORING, MONITORING AGENCY REPORT NUMBER
Same as above

11. SUPPLEMENTARY NOTES
N/A

DTIC
SELECT
JUL 15 1991
S C D

12a. DISTRIBUTION AVAILABILITY STATEMENT

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)
Qualification tests were performed to determine whether the in-service Mk 588 Shipping and Storage Drum could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 14 kg (31 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods and the Department of Transportation's Title 49 CFR and the Final Rulings published in the Federal Register, Vol. 55 on 21 Dec 90. The drum has conformed to the POP performance requirements; i.e., the drum successfully retained its contents throughout the specified tests.

14. SUBJECT TERMS
POP Test of Mk 588 Shipping and Storage Container

15. NUMBER OF PAGES
5

16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT
UNCLASSIFIED

18. SECURITY CLASSIFICATION OF THIS PAGE
UL

19. SECURITY CLASSIFICATION OF ABSTRACT
UL

20. LIMITATION OF ABSTRACT
UL

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines to meet optical scanning requirements.**

Block 1. Agency Use Only (Leave Blank)

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of ..., To be published in When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denote public availability or limitation. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR)

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - DOD - Leave blank

DOE - DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports

NASA - NASA - Leave blank

NTIS - NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS only).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

DODPOPHM/USA/DOD/NADTR91018

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
DRUM, SHIPPING AND STORAGE, MK 588
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
Eric Wu
Mechanical Engineer

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

9 July 1991

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Weapons Station Earle
Code 8024
Colts Neck, New Jersey 07722-5000

Accession For	
DTIC GRA&I	<input checked="" type="checkbox"/>
DTIC Tab	<input type="checkbox"/>
Unclassified	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



91-04954



91 7 12 083

INTRODUCTION

The Mk 588 Shipping and Storage Drum tested, contained a simulated load of 7.2 kg (16 pounds) of sand representing the worst case of loading. Overall weight of the drum was 14 kg (31 pounds). This Performance Oriented Packaging (POP) test was performed to ascertain whether this standard container (Packing Group II) would meet the requirements as specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test was also conducted in accordance with the final rulings specified in the Department of Transportation's Performance Oriented Packaging Standards in the Federal Register Volume 55. Due to unavailability, the number of drums used was less than the number required by the UN recommendation. This has been approved by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

The objectives of these tests were to minimize the risk of personnel or environmental exposure to the hazards associated with the contents in the advent of a transportation or handling accident.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with paragraph 178.608 of the Performance Oriented Packaging Standards, Final Ruling, published in the Federal Register, Vol. 55, No. 246, December 21, 1990. One sample drum was placed on the repetitive shock platform. The drum was restrained during vibration in all but the vertical direction. The frequency of the platform was increased until the drum left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour at a frequency of 3.7 Hz.

2. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.6. One drum was used throughout the test. The drum was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (9.84 feet) (including the test sample). A weight of 158.7 kg (350 pounds) was stacked on the sample drum. The test was performed for 24 hours. After the allowed time, the weight was removed and the drum examined.

3. Drop Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.3. Two drops were performed from a height of 1.2 meters (4 feet) in the following orientations (one drum was used for both orientations):

- a. Horizontally.

b. Diagonally on the edge between the cover assembly and the top ring of the drum.

This test was performed at an ambient temperature of $+70 \pm 20$ °F.

PASS/FAIL (UN CRITERIA)

1. Base Level Vibration Test (HM-181 CRITERIA)

The criteria for passing the base level vibration test is outlined in paragraph 178.608 of the Title 49 CFR Final Ruling and states the following: "immediately following the period of vibration, each package shall be removed from the platform, turned on its side and observed for any evidence of leakage. Rupture or leakage from any of the packages constitutes failure of the test."

2. Stacking Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "... no test sample should leak. No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages."

3. Drop Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retained by an inner packaging or inner receptacle; e.g., a plastic bag, even if the closure is no longer sift-proof. A slight discharge from the closure(s) upon impact should not be considered to be a failure of the packaging provided that no further leakage occurs."

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

Immediately after the vibration test was completed, the drum was removed from the platform, turned on its side and observed for any evidence of leakage. There was no leakage to the drum as a result of this test.

2. Stacking Test

The drum was visibly checked after the 24-hour period was over. There was no leakage, distortion, or deterioration to the drum as a result of this test.

3. Drop Test

After each drop, the drum was inspected for any damage which would be a cause for rejection. Final inspection indicated damage was minimal with only minor denting noted. The drum remained intact and functional upon completion of the tests.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6

B. Title 49 CFR 107, et al., Performance Oriented Packaging Standard; Changes to Classification, Hazard Communication, Packaging and Handling Requirements Based on UN Standards and Agency Initiative; Final Rule, Federal Register, Vol. 55, No. 246 of December 21, 1990.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Headquarters, Military Traffic Management Command (2 copies)
ATTN: MT-SS, James Gibson
5611 Columbia Pike
Falls Church, VA 22041-5050

TEST DATA SHEET

DATA SHEET:	
Container: Mk 588 Shipping and Storage Drum	
Type: 1A2	Container P/N or NSN: NSN 8140-01-113-5430
Specification Number: DL 2541494	Material: Steel
Gross Weight: 14 kg (31 pounds)	Dimensions: 17.4" D x 10.3" L
Closure (Method/Type): Removable Cover w/Lock Ring	Tare Weight: 6.8 kg (15 pounds)
Additional Description:	
PRODUCT:	
Name: See table	NSN(s): See table
United Nations Number: See table	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container: 1	Flash Point: N/A
Net Weight: See table	
TEST PRODUCT: Simulated weights of sand and foam	
Name: Sand and foam	Physical State: Solid
Consistency: N/A	
Density/Specific Gravity: N/A	
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 7.2 kg (16 pounds)

TABLE 1
Mk 588 Shipping and Storage Drum

NALC	NSN	Type	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (lb)
WW78	1356-01-098-3955	Motor Ignition and Separation Assembly, and Airframe Separation Block Assembly	2541491	E137	0257	1	11

**MK 588 SHIPPING AND STORAGE DRUM
POP MARKING**

UN 1A2/Y14/S/*/USA/DOD/NAD**

**** YEAR LAST PACKED OR MANUFACTURED**