	NTATION	N PAGE	Form Approved OPM No. 0704-0188
n na shika ka k	1 hour per response, includ this burden estimate or any	ing the time for reviewing instructions, rother aspect of this collection of infor	, searching existing data sources gathering and maintaining the de mation, including suggestions for reducing this burden, to Washing
nagement and Budget, Washington, DC 20503.	To PERSON AND ATE	, Sulle 1204, Arlington, VA 22202-430	2, and to the Office of Information and Hegulatory Affairs, Office of
AGENCY USE ONLY (Leave Blank)	2. REPORT DATE	3. HEPOH	AT LOD 1002 to 01 LUD 1002
		Fillai.	
lidation Summary Report: IBM Can rsion, RISC System/6000. model 7 AUTHOR(S) right-Patterson AFB, Dayton, OH SA	ada Ltd., AIX Ada/6000 012-320 (Host & Target)	Internal Development), 920121W1.11234	
PERFORMING ORGANIZATION NAME(S) A la Validation Facility, Language Co lg. 676, Rm 135 right-Patterson AFB, Dayton, OH 4	ND ADDRESS(ES) ntrol Facility ASD/SCEL 5433	Marine and an	8. PERFORMING ORGANIZATION REPORT NUMBER AVF-VSR-524.0292
	E(S) AND ADDRESS(ES)	DHC	10. SPONSORING MONITORING AGENC
da Joint Program Office nited States Department of Defense entagon, Rm 3E114 /ashington, D.C. 20301-3081 . SUPPLEMENTARY NOTES		ELECTE MARI 0 1992 C	REPORT NUMBER
2a. DISTRIBUTION/AVAILABILITY STATEMEN proved for public release; distributi	ντ on unlimited.	ELECTE MARI 0 1992 C	12b. DISTRIBUTION CODE
da Joint Program Office Inited States Department of Defense entagon, Rm 3E114 /ashington, D.C. 20301-3081 . SUPPLEMENTARY NOTES 2a. DISTRIBUTION/AVAILABILITY STATEMEN pproved for public release; distributi 3. ABSTRACT (Maximum 200 words) BM Canada Ltd., AIX Ada/6000 Inte 012-320 (Host & Target), ACVC 1.1	AT on unlimited. Arran Development Version 1.	MAR 1 0 1992 C	REPORT NUMBER
da Joint Program Office Inited States Department of Defense entagon, Rm 3E114 /ashington, D.C. 20301-3081 . SUPPLEMENTARY NOTES 2a. DISTRIBUTION/AVAILABILITY STATEMEN pproved for public release; distributi 3. ABSTRACT (Maximum 200 words) BM Canada Ltd., AIX Ada/6000 Inte 012-320 (Host & Target), ACVC 1.1	AT on unlimited. ernal Development Version 1.	MARI 0 1992 C	12b. DISTRIBUTION CODE AFB, RISC System/6000. model
I. SUBJECT TERMS I. SU	VT on unlimited. In piler Val. Summary Re ce, Ada Val. Facility, AN	MAR 1 0 1992 C on, Wright-Patterson port, Ada Compiler Va ISI/MIL-STD-1815A, /	AFB, RISC System/6000. model AFB, RISC System/6000. model AFB, RISC System/6000. model 15. NUMBER OF PAGES al. AJPO.

Prescribed by ANSI Std. 239-128

AVF Control Number: AVF-VSR-524.0292 13 February 1992 91-11-12-IBM

Ada COMPILER VALIDATION SUMMARY REPORT: Certificate Number: 920121W1.11234 IBM Canada Ltd. AIX Ada/6000 Internal Development Version RISC System/6000, model 7012-320 => RISC System/6000, model 7012-320

> Prepared By: Ada Validation Facility ASD/SCEL Wright-Patterson AFB OH 45433-6503

11



ر انΩ ا⊤Ω∃**98**



Certificate Information

The following Ada implementation was tested and determined to pass ACVC 1.11. Testing was completed on 21 January 1992.

Compiler Name and Version: AIX Ada/6000 Internal Development Version Host Computer System: RISC System/6000, model 7012-320, AIX 3.2 Target Computer System: RISC System/6000, model 7012-320, AIX 3.2 Customer Agreement Number: 91-11-12-IBM

See section 3.1 for any additional information about the testing environment.

As a result of this validation effort, Validation Certificate 920121W1.11234 is awarded to IBM Canada Ltd. This certificate expires on 1 June 1993.

This report has been reviewed and is approved.

Ada Validation Facility

Steven P. Wilson Technical Director ASD/SCEL Wright-Patterson AFB OH 45433-6503

Ada Validation Organization Director Computer and Software Engineering Division Institute for Defense Analyses Alexandria VA 22311

Ada Joint Program Office

Dr. John Solomond, Director Department of Defense Washington DC 20301

92 3 05 011

declaration_of_conformance

Non Jan 20 13:23:04 1992

DECLARATION OF CONFORMANCE

Customer:

IBM Canada Ltd.

1 11

Ada Validation Facility:

Wright Patterson AVF ASD/SCEL WPAFB OII 45433 USA

ACVC Version;

Ada Implementation: Compiler Name and Wersion: Host Computer System: Target Computer System:

ATX Ads/COOD Internal Development Version RISC System/6000, model 7012-320, AIX 3.2 RIBC System/6000, model 7012-320, AIX 3.2

1

Customer's Declaration

I, the undersigned, representing IBM Canada Ltd., declare that IBM Canada Ltd. has no knowledge of deliberate deviations from the Ada Language Standard ANSI/MIL-STD-1815A in the implementation listed in this declaration.

To moogh

Peter Moogk IBM Canada Ltd. Laboratory 844 Don Mills Road North York, Ontario CANADA M3C 1V7

Co-Signer: 1an

Paul Kohlbrenner OC Systems, Inc. 9926 Main St. Suite 200 Fairfax, VA 22031 USA

Date: Jam 20 192

Dato: lan 20 1 282

· · -

TABLE OF CONTENTS

CHAPTER	1	INTRODUCTION
	1.1 1.2 1.3 1.4	USE OF THIS VALIDATION SUMMARY REPORT 1-1 REFERENCES
CHAPTER	2	IMPLEMENTATION DEPENDENCIES
	2.1 2.2 2.3	WITHDRAWN TESTS
CHAPTER	3	PROCESSING INFORMATION
	3.1 3.2 3.3	TESTING ENVIRONMENT3-1SUMMARY OF TEST RESULTS3-2TEST EXECUTION3-2
APPENDIX	A I	MACRO PARAMETERS

- APPENDIX B COMPILATION SYSTEM OPTIONS
- APPENDIX C APPENDIX F OF THE Ada STANDARD

CHAPTER 1

INTRODUCTION

The Ada implementation described above was tested according to the Ada Validation Procedures [Pro90] against the Ada Standard [Ada83] using the current Ada Compiler Validation Capability (ACVC). This Validation Summary Report (VSR) gives an account of the testing of this Ada implementation. For any technical terms used in this report, the reader is referred to [Pro90]. A detailed description of the ACVC may be found in the current ACVC User's Guide [UG89].

1.1 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the Ada Certification Body may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject implementation has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from the AVF which performed this validation or from:

> National Technical Information Service 5285 Port Royal Road Springfield VA 22161

Questions regarding this report or the validation test results should be directed to the AVF which performed this validation or to:

Ada Validation Organization Computer and Software Engineering Division Institute for Defense Analyses 1801 North Beauregard Street Alexandria VA 22311-1772

1.2 REFERENCES

- [Ada83] Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
- [Pro90] Ada Compiler Validation Procedures, Version 2.1, Ada Joint Program Office, August 1990.
- [UG89] Ada Compiler Validation Capability User's Guide, 21 June 1989.

1.3 ACVC TEST CLASSES

Compliance of Ada implementations is tested by means of the ACVC. The ACVC contains a collection of test programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable. Class B and class L tests are expected to produce errors at compile time and link time, respectively.

The executable tests are written in a self-checking manner and produce a PASSED, FAILED, or NOT APPLICABLE message indicating the result when they are executed. Three Ada library units, the packages REPORT and SPPRT13, and the procedure CHECK FILE are used for this purpose. The package REPORT also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The package SPPRT13 is used by many tests for Chapter 13 of the Ada Standard. The procedure CHECK FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK FILE is checked by a set of executable tests. If these units are not operating correctly, validation testing is discontinued.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that all violations of the Ada Standard are detected. Some of the class B tests contain legal Ada code which must not be flagged illegal by the compiler. This behavior is also verified.

Class L tests check that an Ada implementation correctly detects violation of the Ada Standard involving multiple, separately compiled units. Errors are expected at link time, and execution is attempted.

In some tests of the ACVC, certain macro strings have to be replaced by implementation-specific values — for example, the largest integer. A list of the values used for this implementation is provided in Appendix A. In addition to these anticipated test modifications, additional changes may be required to remove unforeseen conflicts between the tests and implementation-dependent characteristics. The modifications required for this implementation are described in section 2.3.

For each Ada implementation, a customized test suite is produced by the AVF. This customization consists of making the modifications described in the preceding paragraph, removing withdrawn tests (see section 2.1), and possibly removing some inapplicable tests (see section 2.2 and [UG89]).

In order to pass an ACVC an Ada implementation must process each test of the customized test suite according to the Ada Standard.

1.4 DEFINITION OF TERMS

Ada Compiler The software and any needed hardware that have to be added to a given host and target computer system to allow transformation of Ada programs into executable form and execution thereof.

Ada CompilerThe means for testing compliance of Ada implementations,Validationconsisting of the test suite, the support programs, the ACVCCapabilityuser's guide and the template for the validation summary(ACVC)report.

Ada An Ada compiler with its host computer system and its Implementation target computer system.

Ada Joint The part of the certification body which provides policy and guidance for the Ada certification system. Office (AJPO)

Ada The part of the certification body which carries out the Validation procedures required to establish the compliance of an Ada Facility (AVF) implementation.

Ada The part of the certification body that provides technical Validation guidance for operations of the Ada certification system. Organization (AVO)

Compliance of The ability of the implementation to pass an ACVC version. an Ada Implementation

Computer A functional unit, consisting of one or more computers and System associated software, that uses common storage for all or part of a program and also for all or part of the data necessary for the execution of the program; executes user-written or user-designated programs; performs user-designated data manipulation, including arithmetic operations and logic operations; and that can execute programs that modify themselves during execution. A computer system may be a stand-alone unit or may consist of several inter-connected units.

INTRODUCTION

- Conformity Fulfillment by a product, process, or service of all requirements specified.
- Customer An individual or corporate entity who enters into an agreement with an AVF which specifies the terms and conditions for AVF services (of any kind) to be performed.
- Declaration of A formal statement from a customer assuring that conformity Conformance is realized or attainable on the Ada implementation for which validation status is realized.
- Host Computer A computer system where Ada source programs are transformed System into executable form.
- Inapplicable A test that contains one or more test objectives found to be irrelevant for the given Ada implementation.
- ISO International Organization for Standardization.
- LRM The Ada standard, or Language Reference Manual, published as ANSI/MIL-STD-1815A-1983 and ISO 8652-1987. Citations from the LRM take the form "<section>.<subsection>:<paragraph>."
- Operating Software that controls the execution of programs and that System provides services such as resource allocation, scheduling, input/output control, and data management. Usually, operating systems are predominantly software, but partial or complete hardware implementations are possible.

TargetA computer system where the executable form of Ada programsComputerare executed.System

Validated Ada The compiler of a validated Ada implementation. Compiler

Validated Ada An Ada implementation that has been validated successfully Implementation either by AVF testing or by registration [Pro90].

Validation The process of checking the conformity of an Ada compiler to the Ada programming language and of issuing a certificate for this implementation.

Withdrawn A test found to be incorrect and not used in conformity test testing. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains erroneous or illegal use of the Ada programming language.

CHAPTER 2

IMPLEMENTATION DEPENDENCIES

2.1 WITHDRAWN TESTS

The following tests have been withdrawn by the AVO. The rationale for withdrawing each test is available from either the AVO or the AVF. The publication date for this list of withdrawn tests is 2 August 1991.

B28006C	C32203A	C34006D	C35508I	C35508J
C35508N	C35702A	C35702B	B41308B	C43004A
C45346A	C45612A	C45612B	C45612C	C45651A
B49008A	B49008B	A74006A	C74308A	B83022B
B83025B	B83025D	C83026A	B83026B	C83041A
C86001F	C94021A	C97116A	C98003B	BA2011A
СВ7001В	CB7004A	CC1223A	BC1226A	CC1226B
BD1B02B	BD1B06A	AD1B08A	BD2A02A	CD2A21E
CD2A32A	CD2A41A	CD2A41E	CD2A87A	CD2B15C
BD4008A	CD4022A	CD4022D	CD4024B	CD4024C
CD4031A	CD4051D	CD5111A	CD7004C	ED7005D
AD7006A	CD7006E	AD7201A	AD7201E	CD7204B
BD8002A	BD8004C	CD9005A	CD9005B	CDA201E
CE2117A	CE2117B	CE2119B	CE2205B	CE2405A
CE3116A	CE3118A	CE3411B	CE3412B	CE3607B
CE3607D	CE3812A	CE3814 .	CE3902B	
	B28006C C35508N C45346A B49008A B83025B C86001F CB7001B BD1B02B CD2A32A BD4008A CD4031A AD7006A BD8002A CE2117A CE3116A CE3607D	B28006C C32203A C35508N C35702A C45346A C45612A B49008A B49008B B83025B B83025D C86001F C94021A CB7001B CB7004A BD1B02B BD1B06A CD2A32A CD2A41A BD4008A CD4022A CD4031A CD4051D AD7006A CD7006E BD8002A BD8004C CE2117A CE2117B CE3116A CE3118A CE3607D CE3812A	B28006C C32203A C34006D C35508N C35702A C35702B C45346A C45612A C45612B B49008A B49008B A74006A B83025B B83025D C83026A C86001F C94021A C97116A CB7001B CB7004A CC1223A BD1B02B BD1B06A AD1B08A CD2A32A CD2A41A CD2A41E BD4008A CD4051D CD5111A AD7006A CD7006E AD7201A BD8002A BD8004C CD9005A CE2117A CE2117B CE2119B CE3116A CE3118A CE3411B CE3607D CE3812A CE3814i.	B28006C C32203A C34006D C35508I C35508N C35702A C35702B B41308B C45346A C45612A C45612B C45612C B49008A B49008B A74006A C74308A B63025B B83025D C83026A B83026B C86001F C94021A C97116A C98003B CB7001B CB7004A CC1223A BC1226A BD1B02B BD1B06A AD1B08A BD2A02A CD2A32A CD2A41A CD2A41E CD2A87A BD4008A CD4022A CD4022D CD4024B CD4031A CD4051D CD5111A CD7004C AD7006A CD7006E AD7201A AD7201E BD8002A BD8004C CD9005A CD9005B CE2117A CE2117B CE2119B CE2205B CE3116A CE3118A CE3411B CE3412B CE3607D CE3812A CE3814i CE3902B

2.2 INAPPLICABLE TESTS

A test is inapplicable if it contains test objectives which are irrelevant for a given Ada implementation. Reasons for a test's inapplicability may be supported by documents issued by the ISO and the AJPO known as Ada Commentaries and commonly referenced in the format AI-ddddd. For this implementation, the following tests were determined to be inapplicable for the reasons indicated; references to Ada Commentaries are included as appropriate. The following 201 tests have floating-point type declarations requiring more digits than SYSTEM.MAX DIGITS:

C24113LY	(14	tests)	C35705LY ()	14	tests)
C35706LY	(14	tests)	C35707LY ()	14	tests)
C35708LY	(14	tests)	C35802LZ ()	15	tests)
C45241LY	(14	tests)	C45321LY ()	14	tests)
C45421LY	(14	tests)	C45521LZ ()	15	tests)
C45524LZ	(15	tests)	C45621LZ ()	15	tests)
C45641LY	(14	tests)	C46012LZ (15	tests

The following 20 tests check for the predefined type LONG_INTEGER; for this implementation, there is no such type:

C35404C	C45231C	C45304C	C45411C	C45412C
C45502C	C45503C	C45504C	C45504F	C45611C
C45613C	C45614C	C45631C	C45632C	B52004D
C55B07A	B55B09C	B86001W	C86006C	CD7101F

C35713B, C45423B, B86001T, and C86006H check for the predefined type SHORT_FLOAT; for this implementation, there is no such type.

C35713D and B86001Z check for a predefined floating-point type with a name other than FLOAT, LONG_FLOAT, or SHORT_FLOAT; for this implementation, there is no such type.

C45531M..P and C45532M..P (8 tests) check fixed-point operations for types that require a SYSTEM.MAX_MANTISSA of 47 or greater; for this implementation, MAX_MANTISSA is less than 47.

C45624A..B (2 tests) check that the proper exception is raised if MACHINE OVERFLOWS is FALSE for floating point types and the results of various floating-point operations lie outside the range of the base type; for this implementation, MACHINE OVERFLOWS is TRUE.

B86001Y uses the name of a predefined fixed-point type other than type DURATION; for this implementation, there is no such type.

CA2009C and CA2009F check whether a generic unit can be instantiated before its body (and any of its subunits) is compiled; this implementation creates a dependence on generic units as allowed by AI-00408 and AI-00506 such that the compilation of the generic unit bodies makes the instantiating units obsolete. (See section 2.3.)

LA3004A..B, EA3004C..D, and CA3004E..F (6 tests) check pragma INLINE for procedures and functions; this implementation does not support pragma INLINE.

CD2A84A, CD2A84E, CD2A84I..J (2 tests), and CD2A84O use length clauses to specify non-default sizes for access types; this implementation does not support such sizes.

BD8001A, BD8003A, BD8004A..B (2 tests), and AD8011A use machine code insertions; this implementation provides no package MACHINE_CODE.

The tests listed in the following table check that USE ERROR is raised if the given file operations are not supported for the given combination of mode and access method; this implementation supports these operations.

Test	File Operati	ion Mode	File Access Method
CE2102D	CREATE	IN FILE	SEQUENTIAL IO
CE2102E	CREATE	OUT FILE	SEQUENTIAL IO
CE2102F	CREATE	INOUT FILE	DIRECT IO
CE21021	CREATE	IN FILE	DIRECTIO
CE2102J	CREATE	OUT FILE	DIRECTIO
CE2102N	OPEN	IN FILE	SEQUENTIAL IO
CE21020	RESET	IN FILE	SEQUENTIAL IO
CE2102P	OPEN	OUT FILE	SEQUENTIAL IO
CE21020	RESET	OUT FILE	SEQUENTIAL IO
CE2102R	OPEN	INOUT FILE	DIRECT IO
CE2102S	RESET	INOUT FILE	DIRECT IO
CE2102T	OPEN	IN FILE	DIRECT IO
CE2102U	RESET	INFILE	DIRECT IO
CE2102V	OPEN	OUT FILE	DIRECT IO
CF2102W	RESET	OUTTFILE	DIRECT IO
CE21020	CREATE	IN FILE	
CF31025	RESET	Any Mode	TEXTIO
CF3102G	DELETE		TEXT TO
CE31020	CREATE	OUT FILE	TEXTIO
CE3102.1	OPEN	IN FILE	TEXTIO
CE31020	OPEN	OTT FILE	TEXT
			17477 ¹ 10

The following 16 tests check operations on sequential, direct, and text files when multiple internal files are associated with the same external file and one or more are open for writing; USE_ERROR is raised when this association is attempted.

CE2107BE	CE2107GH	CE2107L	CD2110B	CE2110D
CE2111D	СЕ2111Н	CE3111B	CE3111DE	CE3114B
CE3115A				

CE2203A checks that WRITE raises USE_ERROR if the capacity of an external sequential file is exceeded; this implementation cannot restrict file capacity.

IMPLEMENTATION DEPENDENCIES

EE2401D uses an instantiation of DIRECT IO with an unconstrained array type whose index type is INTEGER; this implementation raises USE ERROR on the attempt to create a file of such a type, as the array type's size exceeds the implementation's maximum element size.

CE2403A checks that WRITE raises USE ERROR if the capacity of an external direct file is exceeded; this implementation cannot restrict file capacity.

CE3304A checks that SET LINE LENGTH and SET PAGE LENGTH raise USE ERROR if they specify an inappropriate value for the external file; there are no inappropriate values for this implementation.

CE3413B checks that PAGE raises LAYOUT ERROR when the value of the page number exceeds COUNT'LAST; for this implementation, the value of COUNT'LAST is greater than 150000, making the checking of this objective impractical.

2.3 TEST MODIFICATIONS

Modifications (see section 1.3) were required for 26 tests.

The following tests were split into two or more tests because this implementation did not report the violations of the Ada Standard in the way expected by the original tests.

B28003A	BA1001A	BA2001C	BA2001E	BA3006A	BA3006B
BA3007B	BA3008A	BA3008B	BA3013A		

C52008B was graded passed by Test Modification as directed by the AVO. This test uses a record type with discriminants with defaults; this test also has array components whose length depends on the values of some discriminants of type INTEGER. On elaboration of the type declaration, this implementation raises NUMERIC ERROR as it attempts to calculate the maximum possible size for objects of the type. The AVO ruled that this behavior was acceptable, and that the test should be modified to constrain the subtype of the discriminants. Line 16 was modified to create a constrained subtype of INTEGER, and discriminant specifications in lines 17 and 25 were modified to use that subtype; these lines are given below:

- 16 SUBTYPE SUBINT IS INTEGER RANGE -128 .. 127;
- 17 TYPE REC1(D1,D2 : SUBINT) IS
- 25 TYPE REC2(D1, D2, D3, D4 : SUBINT := 0) IS

CA2009C and CA2009F were graded inapplicable by Evaluation Modification as directed by the AVO. These tests contain instantiations of a generic unit prior to the compilation of that unit's body; as allowed by AI-00408 and AI-00506, the compilation of the generic unit bodies makes the compilation unit that contains the instantiations obsolete.

IMPLEMENTATION DEPENDENCIES

CD1009A, CD1009I, CD1C03A, CD2A21A..C (3 tests), CD2A22J, CD2A23A..B (2 tests), CD2A24A, CD2A31A, CD2A31B and CD2A31C were graded passed by Evaluation Modification as directed by the AVO. These tests use instantiations of the support procedure LENGTH CHECK, which uses Unchecked Conversion according to the interpretation given in AI-00590. The AVO ruled that this interpretation is not binding under ACVC 1.11; the tests are ruled to be passed if they produce Failed messages only from the instances of LENGTH_CHECK.--i.e, the allowed Report.Failed messages have the general form:

" * CHECK ON REPRESENTATION FOR <TYPE ID> FAILED."

CHAPTER 3

PROCESSING INFORMATION

3.1 TESTING ENVIRONMENT

The Ada implementation tested in this validation effort is described adequately by the information given in the initial pages of this report.

For technical information about this Ada implementation, contact:

Paul Kohlebrenner OC Systems, Inc. 9926 Main Street, Suite 200 Fairfax, VA 22031

For sales information about this Ada implementation, contact:

Peter Moogk IBM Canada Ltd. Laboratory 844 Don Mills Road North York, Ontario Canada M3C 1V7

Testing of this Ada implementation was conducted at the customer's site by a validation team from the AVF.

PROCESSING INFORMATION

3.2 SUMMARY OF TEST RESULTS

An Ada Implementation passes a given ACVC version if it processes each test of the customized test suite in accordance with the Ada Programming Language Standard, whether the test is applicable or inapplicable; otherwise, the Ada Implementation fails the ACVC [Pro90].

For all processed tests (inapplicable and applicable), a result was obtained that conforms to the Ada Programming Language Standard.

The list of items below gives the number of ACVC tests in various categories. All tests were processed, except those that were withdrawn because of test errors (item b; see section 2.1), those that require a floating-point precision that exceeds the implementation's maximum precision (item e; see section 2.2), and those that depend on the support of a file system -- if none is supported (item d). All tests passed, except those that are listed in sections 2.1 and 2.2 (counted in items b and f, below).

a)	Total Number of Applicable Tests	3777	
b)	Total Number of Withdrawn Tests	95	
c)	Processed Inapplicable Tests	97	
d)	Non-Processed I/O Tests	0	
e)	Non-Processed Floating-Point		
	Precision Tests	201	
f)	Total Number of Inapolicable Tests	298	(مبطبه)
•/	total number of indepitousie teses	2,0	(0.0.2)
g)	Total Number of Tests for ACVC 1.11	4170	(a+b+f)

3.3 TEST EXECUTION

A magnetic tape containing the customized test suite (see section 1.3) was taken on-site by the validation team for processing. The contents of the magnetic tape were {loaded directly onto the host computer.

After the test files were loaded onto the host computer, the full set of tests was processed by the Ada implementation.

The tests were compiled and linked on the host computer system, as appropriate. The results were captured on the computer system.

Testing was performed using command scripts provided by the customer and reviewed by the validation team. See Appendix B for a complete listing of the processing options for this implementation. It also indicates the default options. The options invoked explicitly for validation testing during this test were:

> -l Produces a compiler listing -b BIND_NAME Binds the object into an executable with BIND_NAME as the main unit. -m Binds the object into an executable with the first compilation unit in the file as the main unit. -v Produces compiler banner.

Test output, compiler and linker listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

APPENDIX A

MACRO PARAMETERS

This appendix contains the macro parameters used for customizing the ACVC. The meaning and purpose of these parameters are explained in [UG89]. The parameter values are presented in two tables. The first table lists the values that are defined in terms of the maximum input-line length, which is the value for \$MAX_IN_LEN-also listed here. These values are expressed here as Ada string aggregates, where "V" represents the maximum input-line length.

Macro Parameter	Macro Value
\$MAX_IN_LEN	200 — Value of V
\$BIG_ID1	$(1V-1 \Rightarrow 'A', V \Rightarrow '1')$
\$BIG_ID2	$(1V-1 \Rightarrow 'A', V \Rightarrow '2')$
\$BIG_ID3	(1V/2 => 'A') & '3' & (1V-1-V/2 => 'A')
\$BIG_ID4	(1V/2 => 'A') & '4' & (1V-1-V/2 => 'A')
\$BIG_INT_LIT	(1V-3 => '0') & "298"
\$BIG_REAL_LIT	(1V-5 => '0') & "690.0"
\$BIG_STRING1	'"' & (1V/2 => 'A') & '"'
\$BIG_STRING2	'"' & (1V-1-V/2 => 'A') & '1' & '"'
\$BLANKS	(1V-20 => ' ')
\$MAX_LEN_INT_BASED_L	ITERAL "2:" & (1V-5 => '0') & "11:"
\$MAX_LEN_REAL_BASED_1	LITERAL "16:" & (1V-7 => '0') & "F.E:"

Macro Parameter	Macro Value
\$MAX_STRING_LITERAL	'"' & (1V-2 => 'A') & '"'
\$ACC_SIZE	32
\$ALIGNMENT	4
\$COUNT_LAST	2_147_483_646
\$DEFAULT_MEM_SIZE	268_435_456
\$DEFAULT_STOR_UNIT	8
\$DEFAULT_SYS_NAME	AIX_6000
\$DELTA_DOC	2#1.0#E-31
\$ENTRY_ADDRESS	ENTRY0'ADDRESS
\$ENTRY_ADDRESS1	ENTRY1'ADDRESS
\$ENTRY_ADDRESS2	ENTRY2'ADDRESS
\$FIELD_LAST	1000
\$FILE_TERMINATOR	• •
\$FIXED_NAME	NO_SUCH_FIXED_TYPE
\$FLOAT_NAME	NO_SUCH_TYPE
\$FORM_STRING	PT 11
\$FORM_STRING2	"CANNOT_RESTRICT_FILE_CAPACITY"
\$GREATER_THAN_DURATIO	N 100_000.0
\$GREATER_THAN_DURATIO	N BASE LAST I31_073.0
\$GREATER_THAN_FLOAT_B	ASE LAST 1.0E308
\$GREATER_THAN_FLOAT_S	AFE LARGE
\$GREATER_THAN_SHORT_F	LOAT_SAFE_LARGE

The following table lists all of the other macro parameters and their respective values.

A–2

MACRO PARAMETERS

1.0E308 255 SHIGH PRIORITY SILLEGAL EXTERNAL FILE NAME1 Ā* SILLEGAL EXTERNAL FILE NAME2 ₹₿ SINAPPROPRIATE LINE LENGTH -1 SINAPPROPRIATE PAGE LENGTH -1 \$INCLUDE_PRAGMA1 PRAGMA INCLUDE ("A28006D1.TST") \$INCLUDE_PRAGMA2 PRAGMA INCLUDE ("B28006D1.TST") -2147483648 \$INTEGER_FIRST SINTEGER LAST 2147483647 \$INTEGER_LAST_PLUS_1 2147483648 SINTERFACE LANGUAGE FORTRAN \$LESS THAN DURATION -100_000.0 \$LESS_THAN_DURATION_BASE_FIRST -131 073.0 ASCII.LF **\$LINE TERMINATOR** \$LOW_PRIORITY 0 \$MACHINE_CODE_STATEMENT NULL; \$MACHINE CODE TYPE NO_SUCH_TYPE 31 \$MANTISSA DOC 15 \$MAX DIGITS 2147483647 **\$MAX INT** 2_147_483_648 SMAX INT PLUS 1 -2147483648 **\$MIN INT SNAME** SHORT_SHORT_INTEGER

MACRO PARAMETERS

\$NAME_LIST	0006_XIA
\$NAME_SPECIFICATION1	/dino/val/work/ctests/X2120A
\$NAME_SPECIFICATION2	/dino/val/work/ctests/X2120B
\$NAME_SPECIFICATION3	/dino/val/work/ctests/X3119A
\$NEG_BASED_INT	16#F000000E#
\$NEW_MEM_SIZE	65535
\$NEW_STOR_UNIT	16
\$NEW_SYS_NAME	AIX_6000
\$PAGE_TERMINATOR	ASCII.FF
\$RECORD_DEFINITION	NEW INTEGER;
\$RECORD_NAME	NO_SUCH_MACHINE_CODE_TYPE
\$TASK_SIZE	32
STASK_STORAGE_SIZE	32768
\$TICK	0.00006
\$VARIABLE_ADDRESS	VARIABLE'ADDRESS
\$VARIABLE_ADDRESS1	VARIABLE1'ADDRESS
SVARIABLE_ADDRESS2	VARIABLE2' ADDRESS
\$YOUR_PRAGMA	EXPORT

APPENDIX B

COMPILATION SYSTEM OPTIONS

The compiler options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report.

USAGE: ada [Option | FileName]

OPTION/SWITCH	EFFECT
~a	Produce assembler code.
-b UnitName	Bind and link unit.
d	Keep debug info in the Ada sublibrary.
~e	Suppress creation of executable file.
-G	Do partial optomization.
-h	Display info about the ada command.
-i FileName	Include archive or object file FileName when binding.
-I	Read a list of files to compile from standard input.
-1	Generate a compilation listing.
-L Library	Use this library list file.
~ m	Compile and bind the last unit as the main program.
-o FileName	Specify the name of the executable is to be FileName.

COMPILATION SYSTEM OPTIONS

OPTION/SWITCH	EFFECT
-0	Produce fully optomized code.
~ ₽	Turn on execution profiling option.
-Q	Consistently detect single precision floating point overflow.
-q Parameter=Value	Special parameters as follows:. task_stack=Bytes time_slice=Milliseconds.
S	Suppress run-time checks for Ada exceptions.
-u	Unlock the working sublibrary.
V	Verbose - display informative messages
-V Pages	Specify the number of 1K memory pages to be used.

COMPILATION SYSTEM OPTIONS

LINKER OPTIONS

The linker options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to linker documentation and not to this report.

There is no separate linker.

APPENDIX C

APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in Chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this Appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

package STANDARD is

type INTEGER is range -2147483648 .. 2147483647; type SHORT INTEGER is range -32768 .. 32767; type SHORT_SHORT_INTEGER is range -128 .. 127; type FLOAT is digits 6 range -3.40282E+38 .. 3.40282E+38; type LONG FLOAT is digits 15 range -1.79769313486232E+308 .. 1.79769313486232E+308; type DURATION is delta 2**(-14) range -86400.0 .. 86400.0;

end STANDARD;

Appendix 5 - Appendix F of the Ada Language Reference Manual

Appendix F. Implementation-Dependent Characteristics

The Ada language definition allows for certain target dependencies in a controlled manner. This appendix, called Appendix F as prescribed in the Ada Language Reference, describes implementation-dependent characteristics of the AIX Ada/6000 compiler running under the AIX operating system Version 3.

Implementation-Defined Pragmas

Implementation dependent pragmas are:

pragma COMMENT(String_Literal);

Imbeds String_Literal into object code.

pragma IMAGES(Enumeration_Type, immediate | deferred);

Generates a table of images for the enumeration type. deferred causes the table to be generated only if the enumeration type is used in a compilation unit.

pragma INTERFACE_INFORMATION
 (Interfaced_Subprogram_Name, Link_Name);

When used in conjunction with pragma INTERFACE, provides access to any routine whose name can be specified by an Ada string literal.

pragma LINKNAME (Interfaced Subprogram Name, Link Name);

When used in conjunction with pragma INTERFACE, provides access to any routine whose name can be specified by an Ada string literal. Pragma INTERFACE_INFORMATION is the preferred method for naming non-Ada routines.

pragma OS_TASK (Priority);

Appears within the declaration for a task or task type (in the same context as pragma PRIORITY), and causes the task or task type to be placed into a separate AIX process. The priority value is of type SYSTEM.PRIORITY, and is not currently acted upon. To maintain upward compatibility, always use a 0 for this parameter.

pragma NO_SUPPRESS(Condition_Name);

Prevents checks for a specified condition from being suppressed. It has the same scope as pragma SUPPRESS.

pragma PRESERVE_LAYOUT (Record_Type);

Prevents the compiler from re-ordering record components. It must occur in a declarative region, following the declaration of the record type to which it is applied.

pragma SUPPRESS_ALL;

Suppresses all error checks, including elaboration checks. It has the same scope as pragma SUPPRESS.

pragma EXPORT (object, String_Literal, Language);

Makes the named object visible to other programs. The object can be a procedure or a function or a data object. The string_literal is the name the linker will make global. The Language must be C, FORTRAN, or Assembler, all of which have the same effect.

Predefined Pragmas

Supported pragmas are INTERFACE, ELABORATE, SUPPRESS, PACK, PAGE, LIST, INLINE, and PRIORITY.

All pragmas have conventional meanings except LIST, which suppresses listings prior to pragma LIST(ON) regardless of the user request.

Pragma INTERFACE supports the interface languages C, FORTRAN, and ASSEMBLY.

Unrecognized and unsupported pragmas are ignored with the appropriate warning message.

Representation Clauses

Supported representation clauses include:

- w Length clauses
- w Enumeration representation clauses, except for Boolean types
- w Record representation clauses
- w Address clauses, including those for interrupt entries.

Records are aligned by default on 32-bit boundaries. You can use a representation clause to force them to be aligned on 64-bit boundaries.

Restrictions on Unchecked Conversion

The only restriction on unchecked conversion is that the two types (or subtypes) A and B must be the same static size, and that neither A nor B are private.

Package System

The package SYSTEM has the following characteristics:

PACKAGE system IS -- for integer use 32: TYPE Memory is private; TYPE Address is access Memory; TYPE name IS (AIX_6000);

OC Systems, Inc. - December 19, 1991

Pre-validation Overview RISC System/6000 Ada

System Name : CONSTANT name := AIX 6000; Storage Unit : CONSTANT := 8; Memory Size : CONSTANT := 1024*1024*256; -- 256 Mb. -- System-Dependent Named Numbers: Min Int : CONSTANT := -(2**31);Max Int : CONSTANT := (2 ** 31) -1; Max Digits : CONSTANT := 15; Max Mantissa : CONSTANT := 31; Fine Delta : CONSTANT := 1.0 / (2 ** MAX_MANTISSA); : CONSTANT := 0.00006; Tick -- Other System-Dependent Declarations SUBTYPE Priority IS integer RANGE 0..255; END System; Representation Attributes All defined representation attributes shall be supported. Implementation-Generated Names There are no implementation-generated names denoting implementation-dependent components. Component names generated by the compiler shall not interfere with programmer-defined names. Implementation-Dependent Characteristics of the I/O Packages Packages SEQUENTIAL IO, DIRECT IO, and TEXT IO are supported. Package LOW_LEVEL_IO is not supported. Unconstrained array types and unconstrained types with discriminants may be instantiated for I/O. File names follow the conventions and restrictions of the target operating system, except that non-printing characters, blank (' ') and asterisk ('*') are disallowed. In TEXT_IO, the type FIELD is defined as follows: subtype Field is integer range 0..1000; In TEXT_IO, the type COUNT is defined as follows: type Count is range 0..2_147_483_646; Form Parameters for File Operations Section 14.2 of the Language Reference describes the Ada functions for manipulating files. As stated in that section, the form string parameter allows you to set file protections when you create a file. The details of file protections and privileges under the AIX operating system are described under the chmod call in the AIX Calls and Subroutines Reference for IBM RISC System/6000 (SC23-2198).

OC Systems, Inc. - December 19, 1991

20

If you do not specify a form string, the default file protection is both read and write privileges for the owner, group, and all others. If you do specify a form string, it is interpreted in the following way:

w The form string consists of a series of substrings, separated by blanks.

w The substrings are not case sensitive.

w The order of the substrings does not matter.

w Some substrings control the file protection settings.

w Some substrings enable special AIX behavior for file opening, for example opening with no delay and opening a file for append.

w The list of recognized substrings is contained in the section entitled #Input/Output" in the User's Guide for IBM AIX Ada/6000 (SC09-1321).

Predefined Numeric Types

The current specification of package STANDARD includes:

type SHORT_SHORT_INTEGER
is range -128 .. 127;

type SHORT_INTEGER
is range -32768 .. 32767;

```
type INTEGER is
range -2147483648 .. 2147483647;
```

type FLOAT is digits 6 range -3.40282E+38 .. 3.40282E+38;

```
type LONG_FLOAT is
digits 15 range
-1.79769313486232E+308 .. 1.79769313486232E+308;
```

```
type DURATION is
delta 2**(-14) range -86400.0 .. 86400.0;
```

SHORT SHORT INTEGER

'First = -128

'Last = 127

'Size = 8

SHORT_INTEGER

```
'First = -32768
```

'Last = 32767

OC Systems, Inc. - December 19, 1991

```
'Size = 16
INTEGER
 'First = -2147483648
 'Last = 2147483647
 'Size = 32
FLOAT
 'Digits = 6
 'Emax = 84
 'Epsilon = 9.53674E-07
 'Large = 1.93428E+25
 'Machine_Emax = 128
 'Machine_Emin = -125
 'Machine_Mantissa = 24
 'Machine_Overflows = TRUE
 'Machine_Radix = 2
 'Machine_Rounds = TRUE
 'Mantissa = 21
 'Safe_Emax = 125
             = 4.25353E+37
 'Safe_Large
             = 1.17549E-38
 'Safe_Small
 'Size = 32
 'Small = 2.58494E-26
LONG_FLOAT
'Digits = 15
'Emax = 204
'Epsilon = 8.88178419700125E-16
'Large = 2.57110087081438E+61
'Machine_Emax = 1024
```

OC Systems, Inc. - December 19, 1991

Pre-validation Overview RISC System/6000 Ada

'Machine_Emin = -1021

'Machine_Mantissa = 53

'Machine_Overflows = TRUE

'Machine_Radix = 2

'Machine_Rounds = TRUE

'Mantissa = 51

'Size = 64

- .

'Safe_Emax = 1021

'Safe_Large = 2.24711641857789E+307

'Safe_Small = 2.22507385850720E-308

'Small = 1.94469227433161E-62

DURATION

'Delta = 2**(-14)

'First = -86400.0

'Last = 86400.0

'Machine_Overflows = FALSE

'Machine_Rounds = FALSE

Restrictions on Machine Code Insertions

Machine code insertions are not supported.

Parameters to a Main Subprogram

You can code an Ada/6000 main subprogram to accept parameters, or to return a value if it is a function. Any parameters to the main subprogram have undefined values when the program is run; use the subprograms in package COMMAND_LINE if you need to pass information to an Ada program when it is run. The operating system always ignores any function value it returns; use COMMAND_LINE.SET_RETURN_CODE if you need to return a value when the program is completed.