

AD-A247 727




TECHNICAL REPORT BRL-TR-3323

BRL

SENSITIVITY OF MUZZLE VELOCITY REPEATABILITY TO VARIATIONS IN INITIAL CONDITIONS

C. WATSON
J. D. KNAPTON
N. BOYER
I. C. STOBIE



MARCH 1992

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

92 3 23 070

92-07339



NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1992	3. REPORT TYPE AND DATES COVERED Final, Jan 87 - Jan 88	
4. TITLE AND SUBTITLE Sensitivity of Muzzle Velocity Repeatability to Variations in Initial Conditions			5. FUNDING NUMBERS 1L263637D155	
6. AUTHOR(S) C. Watson, J. D. Knapton, N. Boyer, and I. C. Stobie				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING / MONITORING AGENCY REPORT NUMBER BRL-TR-3323	
11. SUPPLEMENTARY NOTES The present working address of Cris Watson is Reichold Chemical Company, Inc., 6401 Chemical Road, Baltimore, MD, 21226.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Interior ballistic data from 20 tests with a 30-mm regenerative liquid propellant gun (RLPG) are examined. The tests are divided into four groups, with five tests in each group. The particular RLPG, referred to as Concept VI, is based on an annular-sheet-type of injector. The propellants used for the tests were liquid gun propellant (LGP) 1845 and LGP 1846. The mean muzzle velocity and the standard deviation for the first three groups was 855 ms (1.0%), 903 ms (1.9%), and 867 ms (2.1%). For groups 2 to 4, the igniter charge was increased from 3.0 g to 3.5 g. The significant increase in velocity for the second group of tests could not be explained by the small increase in the igniter charge. The increase in velocity, as well as the large standard deviations, is presently under study. Interestingly, the fourth test group, in which the initial conditions were more closely controlled, yielded a mean muzzle velocity of 873 ms with a standard deviation of 0.83%. Because of the large variations in the first three group of tests, especially when compared with other RLPG firing test data, a study of some of the parameters was undertaken which might influence the muzzle velocity.				
14. SUBJECT TERMS regenerative liquid propellant gun; muzzle velocity; repeatability; liquid propellant			15. NUMBER OF PAGES 26	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
LIST OF TABLES	v
1. INTRODUCTION	1
1.1 Propellant	1
1.2 Summary of Earlier Reproducibility Data	1
2. APPROACH	2
3. EXPERIMENTAL	4
3.1 Igniter	4
3.2 Closed Chambers	4
3.3 The 30-mm RLPG Concept	4
3.4 Temperature Measurement	5
4. RESULTS	7
4.1 Igniter Tests	7
4.2 The 30-mm Start-up Characteristics	10
4.3 Projectile Seating Methods	10
5. DISCUSSION AND CONCLUSIONS	12
6. REFERENCES	15
DISTRIBUTION LIST	17

Accession For	
A-1	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

INTENTIONALLY LEFT BLANK.

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Properties of the Liquid Propellants Used in the 30-mm Tests	1
2. Summary of Earlier Reproducibility Tests With the 30-mm, Concept VI, Using a 2/3 Charge	3
3. Thermochemistry of the Igniter Charge Used in the Closed Chamber and Gun Tests	5
4. Summary of Experimental Igniter Results for the 106-cm ³ Closed Chamber	8
5. Summary of Experimental Igniter Results for the 106-cm ³ , 30-mm Closed Chamber	8
6. Estimate of Propellant Burned in the Igniter Chamber and Unburned Propellant Which Vents Into the Gun Chamber	9
7. Estimate of Heat Loss From the Burning of the Propellant in the Igniter and the Larger Chamber	9
8. Summary of Piston and Ballistic Data	11
9. Summary of Start-up Characteristics	11
10. Comparison in Ballistic Performance Between Two Methods for Seating the Projectile	12

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

A 30-mm regenerative liquid propellant gun (RLPG) was used to investigate variations in both the initial conditions and the early time-dependent parameters which might influence the muzzle velocity. The gun is based on a design which has been referred to as Concept VI and has been described elsewhere (Mandzy, Cushman, and Magoon 1984a, 1984b; Reeve 1984; Pate and Magoon 1985; Magoon et al. 1985; Watson et al. 1985, 1986; Watson and Knapp 1987). Interest in examining the start-up conditions was based on some interior ballistic reproducibility data which was reported at the 22nd JANNAF Combustion Meeting (Magoon et al. 1985). In this earlier paper, it was shown that the muzzle velocity for the first group of tests performed with the 30-mm was poor, especially when compared with data obtained from similar regenerative fixtures. The reasons for the poor reproducibility were not identified. It was therefore considered important to further examine the parameters which might influence the poor reproducibility. The propellants tested included Otto-II, a naval torpedo fuel, and the hydroxylammonium nitrate-based liquid gun propellants (LGP) 1845 and 1846. A summary of the thermochemical properties of the propellants and the earlier reproducibility data are repeated here for convenience.

1.1 Propellant. A summary of the thermochemical properties are given in Table 1.

Table 1. Properties of the Liquid Propellants Used in the 30-mm Tests^a

LP	Fuel, Name	wt%	HAN, wt%	Water, wt%	Density, g/cm ³	Impetus, J/g	Flame Temperature, K	γ
1845	TEAN	20.0	63.2	16.8	1.45	934	2,592	1.218
1846	TEAN	19.2	60.8	20.0	1.43	898	2,469	1.223
Otto-II ^b					1.23	866	1,986	1.266

^a Loading Density = 0.2 g/cm³ (Freedman 1987).

^b Composition of Otto-II: 1, 2 dinitroxypropane 76%, di-N-butyl sebacate 22.5%, 2 nitrodiphenylamine 1.5%.

1.2 Summary of Earlier Reproducibility Data. The 30-mm was tested first at the General Electric (GE) test facility using Otto-II (Reeve 1984; Pate and Magoon 1985; Magoon et al. 1985). It was also tested at the U.S. Army Ballistic Research Laboratory (BRL), Aberdeen

Proving Ground, MD, using the LGPs 1845 and 1846 (Magoon et al. 1985; Watson et al. 1985, 1986; Watson and Knapton 1987). The results of the earlier reproducibility tests are summarized in Table 2. These tests include the first group of reproducibility test firings with the 30-mm Concept VI using Otto-II.

The tests with Otto-II LGP 1845 and LGP 1846 were all fired with a 2/3 charge and a relatively thin injection sheet. The thin injection sheet resulted in a relatively low ballistic performance, a result that could have been improved if the sheet thickness had been increased. The reproducibility of the tests with Otto-II gave a standard deviation of 1.6%. The initial position of the projectile was varied during these tests and therefore may have contributed to the poor reproducibility. The reproducibility of the tests with 1845 was about the same. For these tests, an attempt was made to initially seat the projectile in the same position. If the apparent outlier (Identification No. 364-046) is omitted, then the standard deviation becomes 0.80%. Furthermore, an inspection of the data suggests that the data may be divided into two groups with mean velocities of 1,005 ms and 1,019 ms. The respective standard deviation of the two groups is 0.05% and 0.24%. The reason for the apparent grouping of the data was not known when the data was presented at the 22nd JANNAF Combustion Meeting (Magoon et al. 1985). The lack of a satisfying explanation for the two groups of data was the basis for the present study.

2. APPROACH

Problems in interior ballistics are often related to abnormal ignition and/or combustion, which may depend on the initial conditions and which may show up in the early pressure rise in the chamber, or in the early projectile motion. We therefore decided it might be instructive to examine both the initial conditions and the early start-up conditions in some detail.

The initial conditions that were examined included the igniter charge, two methods for seating the projectile, and the overall assembly procedures. The evaluation of the igniter charge depended on performing some reproducibility tests in closed chambers with volumes similar to the chamber volume of the RLPG. The two methods for seating the projectile consisted of a simple hammer approach and a screw and clamp method for pressing the projectile into the engraving region. Additionally, two gun tubes were used. One gun tube showed some evidence of erosion; the other tube was new.

Table 2. Summary of Earlier Reproducibility Tests With the 30-mm, Concept VI, Using a 2/3 Charge

Identification No.	LP	Pressure ^a			LP, MPa	Velocity, m/s
		J120, MPa	C30, MPa	A90, MPa		
335:14	Otto-II	164	192	174	—	939
336:15	Otto-II	—	—	—	—	950
342:13	Otto-II	144	180	179	—	930
343:12	Otto-II	179	197	168	—	965
Mean	Otto-II	162	190	174	—	9.6 ^b
Std/Dev/Mean	(%)					1.6
364-032	1845	177	190	197	—	1,020
364-033	1845	167	181	181	—	1,005
364-034	1845	177	190	191	—	1,005
364-035	1845	182	186	194	—	1,020
364-041	1845	171	189	192	227	1,018
364-042	1845	182	181	195	202	1,021
364-043	1845	166	177	184	—	1,005
364-044	1845	—	—	—	—	1,004
364-046	1845	169	178	186	—	973.5
Mean	1845	174	184	190		1,008 ^c
Std/Dev/Mean	(%)	3.7	2.9	3.0		1.5
12	1846	190	195	205	—	1,023
13	1846	184	184	190	285	1,009
27	1846	213	205	231	—	1,011
Mean	1846	196	195	209	—	1,014 ^c

^aJ120 gage located 12 mm forward of the initial position of the piston face and gages C30 and A90 gages located, respectively, 21 mm and 36 mm to the rear of the initial position of the piston face. The error in the pressure readings, especially for the gages in the C and A plane, may be as high as 10%.

^bTested at GE. Initial position of projectile varied.

^cTested at BRL.

The early start-up conditions that were studied included the reproducibility of the igniter output and the early pressure and projectile start-up characteristics. The pressure and projectile start-up characteristics are based on the interior ballistic data which were recorded using the methods described in Magoon et al. (1985).

The early start-up parameters included shot start pressure (P1), a chamber pressure (P2) arbitrarily measured after the projectile had been displaced about 5.4 mm, time between P1 and P2, maximum pressure in the igniter chamber, an igniter rise time, igniter rise rate, the piston velocity during igniter venting, and the maximum piston velocity.

3. EXPERIMENTAL

3.1 Igniter. The igniter device consists of an M52A3B1 initiator and either 3.0 g or 3.5 g of IMR 4350. The principal ingredient in the M52A3B1 is lead styphnate. IMR 4350 is a single base extruded propellant normally used in small arms. Volume of the igniter cavity is 6.8 cm^3 , and the limiting vent orifice diameter into the larger closed chamber, or the gun fixture, is 3.86 mm.

The thermochemistry of the solid propellant igniter components, IMR 4350 and M52 primer, are summarized in Table 3. Two examples are included representing loading densities of 0.0280 and 0.4663 g/cm^3 . The first loading density example represents the pressure one would expect to obtain in the RLPG combustion chamber (volume equal to 95 cm^3) with the IMR 4350 booster charge. The second represents the pressure expected in the igniter chamber volume, 6.8 cm^3 .

3.2 Closed Chambers. The ignition and combustion of the igniter propellant were studied using two different closed chambers. Pressures were measured in both chambers. Importantly, the length to diameter ratio (L/D) of the first chamber was 1.5, and, therefore, heat losses (Klingenberg et al. 1987) were probably not important (<10%). The second chamber consisted of the 30-mm gun chamber. In this chamber, the L/D was about 0.3 and may have resulted in significant heat losses. As a result, the maximum pressures were considerably lower than the pressures recorded in the first chamber. The 6.8 cm^3 igniter chamber was used in both RLPG combustion chambers.

3.3 The 30-mm RLPG Concept. A description of the Concept VI RLPG is given in Mandzy, Cushman, and Magoon (1984a, 1984b); Reeve (1984); Pate and Magoon (1985); Magoon et al. (1985); Watson et al. (1985, 1986); and Watson and Knapton (1987). The following briefly describes the operation of the fixture. Propellant is injected into the

Table 3. Thermochemistry of the Igniter Charge Used in the Closed Chamber and Gun Tests (Freedman 1987)

Component	Loading Density, g/cm ³	Volume, cm ³	Flame Temperature, K	Impetus, J/g	Pressure, MPa
IMR 4350 3.0 g	0.0280	95.0	2,875	1,003	28.98
M52 and 3.0 g IMR	0.4663	6.8	2,884	974	777

combustion chamber in the form of an annular sheet. An illustration of the basic concept showing both the chamber and LP reservoir sections is given in Figure 1. In the upper half of the figure, the piston is in the forward position prior to firing. The lower half of the figure shows the piston in the rear position at the end of firing. The piston is a thin shell cylinder supported from deformation by a lubricating film and the chamber wall. At ignition, the pressure developed by the igniter in the combustion chamber forces the injection piston to the rear. Due to the differential area of the injection piston, the pressure in the reservoir is higher than the combustion chamber. As a result, LP is forced through the annulus formed by the outside of the control rod, or center bolt, and the inner diameter of the piston. The injected propellant then enters the combustion chamber. The instantaneous injection area is controlled by contours on the control rod. Initially, the area is sealed preventing leakage of LP into the chamber and allowing for the prepressurization of the LP reservoir. For the tests reported here, the initial prepressurization of the LP was 7.0 MPa. As the injection piston is displaced to the rear, the injection area rapidly increases, permitting an increase in the mass injection rate. Maximum injection area is reached at the end of the first or starting taper on the control rod. Motion of the injection piston is retarded towards the end of its stroke by the rear taper on the control rod.

3.4 Temperature Measurement. Temperatures were measured using a gage, referred to as an emission gage, which has been described by Klingenberg (1985). A brief description on the use of this device is given in this section. First, an optical pyrometer is calibrated using a calibrated tungsten lamp. The lamp used was a General Electric lamp with a tungsten ribbon filament with a nominal rating of 30 A at 6 V. The lamp was calibrated at the National




Figure 1. Schematic of the 30-mm, Concept VI, Regenerative Liquid Propellant Gun.

Institute of Standards and Technology from 1,173 K (12.37 A) to 2,573 K (42.55 A). A description on the use of this lamp is given by Kostkowski and Lee (1968). The lamp is calibrated in terms of a brightness temperature, defined as the temperature of a blackbody which has the same spectral radiance at a given wavelength as the unknown radiation source. The radiation from the lamp and the unknown source is detected with a photomultiplier (150 CVP/177) after passing through a narrow band filter (647.1 nm) and a diffuser. For calibration purposes, a chopper is used to conveniently detect the signal. Purpose of the diffuser is to generate a radiation source which approaches the random radiation emission associated with the actual test. The response of the photomultiplier, in volts, is recorded as a function of current through the tungsten filament. A table of brightness temperature vs. both current and the response of the photomultiplier can then be constructed, which provides a basis for fitting the tungsten brightness temperature and the photomultiplier response to a suitable function. Two functions were investigated—a logarithmic and a second degree power function. It was found that the power function gave a better fit to the data and was therefore used in converting the test data to a brightness temperature (by multiplying the test data with the generated calibration function using an on-line ballistic data acquisition system).

4. RESULTS

The results are divided into three sections: a summary of the closed chamber tests on the reproducibility of the igniter parameters; a summary of the parametric study on the 30-mm start-up characteristics; and the results of the assembly procedures for the 30-mm, which includes the two different methods for seating the projectile.

4.1 Igniter Tests. The 6.8-cm³ igniter chamber was tested in both closed chambers. The results are summarized in Tables 4 and 5. In these tables, the A, B, and C under the igniter column refer to the type of confinement of the IMR powder used in the 6.8-cm³ chamber. In the A configuration, a portion of the powder adjacent to the M52A3B1 is confined in a paper straw. In the B and C configurations, a slightly larger diameter plastic straw was used which allowed more propellant to be directly in line with the M52A3B1. The C configuration had 3.5 g of IMR, whereas A and B configurations used 3.0 g. Significantly, as shown in Table 4, the B configuration yielded improved reproducibility for the recorded maximum pressures.

Despite the increased charge used in the second chamber (Table 5), the recorded maximum pressures were significantly lower than the maximum pressures recorded in the first chamber, a result, as pointed out previously, of the low L/D of the chamber and the postulated high heat loss.

Based on the maximum pressure data summarized in Table 3, an estimate of the igniter charge burned in the small igniter chamber may be made and, by comparison with the pressure-time data, an estimate of the unburned mass flux into the larger chamber may be calculated. Assume that no gas is vented from the igniter chamber during the rise to maximum pressure and that there are no heat losses. Then the mass of propellant burned in the igniter chamber is approximately proportional to the ratio of the measured pressure and the theoretical pressure. For configuration B, and based on a loading density of 0.466 g/cm³, the comparison between the theoretical pressure from Table 3 and the observed pressure indicated that about 0.55 g of solid propellant actually burned in the igniter chamber while the remainder vented into the larger chamber (see Table 6). Examining the pressure-time data (Klingenberg 1985) or simply taking the 10 to 90% rise time given in Table 4 gives an approximate unburned mass flux, for configuration B, into the larger chamber of

Table 4. Summary of Experimental Igniter Results for the 106-cm³ Closed Chamber

Igniter	No. of Tests	Igniter Chamber, MPa	Mean Maximum Pressure			Rise Time, 10 to 90%	
			Standard Deviation, %	106-cm ³ Chamber, MPa	Standard Deviation, %	Mean, ms	Standard Deviation, %
M52	1	10.6	—	1.1	—	—	—
A. M52 and 3.0 g IMR	6	181	15.2	16.8	3.1	1.37	14.4
B. M52 and 3.0 g IMR	9	141.8	9.1	17.3	7.8	1.60	23.1
C. M52 and 3.5 g IMR	2	(not measured)	—	21.5	—	—	—

Note: The loading densities, neglecting the M52A3B1 and assuming all of the propellant is displaced into the larger chamber, were 0.0266 g/cm³ and 0.0310 g/cm³ for, respectively, the igniter configurations A or B and C.

Table 5. Summary of Experimental Igniter Results for the 106-cm³, 30-mm Closed Chamber

Igniter	No. of Tests	Maximum Pressure, MPa	Standard Deviation, %	Maximum Temperature, K	Standard Deviation, %
C. M52 and 3.5 g IMR	6	13.3	3.0	2527	5.8

Note: The loading density was 0.0325 g/cm³. The igniter chamber pressure was not measured in these tests.

$2.45 / (0.0016 \times 3.14 \times 3.86^2 / 4) = 131 \text{ g/mm}^2\text{s}$. Similarly, for the A configuration, the approximate unburned mass flux = $143 \text{ g/mm}^2\text{s}$.

Additionally, an estimate of the total heat loss may be determined by comparing the experimentally measured pressures with the theoretical pressures. The results are summarized in Table 7.

The recorded maximum chamber temperature (Table 5) of 2,527 K is 12% lower than the theoretical value (Table 3). A comparison of the maximum chamber pressure (Table 3) with the theoretical pressure would suggest a much lower value for the measured temperature.

Table 6. Estimate of Propellant Burned in the Igniter Chamber and Unburned Propellant Which Vents Into the Gun Chamber

Igniter Configuration	Loading Density of IMR, g/cm ³	Mass of IMR Charge, g	Pressure		Estimate of SP	
			Experimental, MPa	Theoretical, MPa	Burned in 6.8 cc Chamber, g	Vented in to 106 cc Chamber, g
B. M52 and 3.0 g IMR	0.441	3.0	142	777	0.55	2.45
A. M52 and 3.0 g IMR	0.441	3.0	181	777	0.70	2.30

Note: The experimental pressure is taken from Table 3, and the theoretical pressure is extrapolated linearly from Table 1.

Table 7. Estimate of Heat Loss From the Burning of the Propellant in the Igniter and the Larger Chamber

Igniter Configuration	Loading Density, g/cm ³	Mass of IMR Charge, g	Pressure		Estimate of Heat Loss During the Combustion in the Two Chambers, %
			Experimental, MPa	Theoretical, MPa	
Chamber No. 1					
B	0.0281	3.0	17.3	28.8	39.9
A	0.0281	3.0	16.8	28.8	41.7
C	0.0325	3.5	21.5	32.9	34.6
Chamber No. 2					
C	0.0325	3.5	13.3	32.9	59.6

The ratio of the measured pressure and the theoretical pressure (taken from Table 6) suggests a heat loss of over 30% for Chamber 1 and a much larger heat loss for Chamber 2. This large heat loss is not considered unreasonable since the igniter gases must pass through a long, narrow vent before entering the RLPG combustion chamber.

4.2 The 30-mm Start-up Characteristics. The results of an evaluation of the start-up parameters are summarized in Tables 8 and 9.

The tests listed as Test Series 1 and 2 are one-third charge firings. The propellant charge was 80 cm³ of LGP 1846. The projectile mass was 287 g nominal, and all projectiles were installed using the hammer technique.

The summary in Tables 8 and 9 of the various start-up parameters, aside from the maximum chamber pressure, showed no correlation with muzzle velocity. This lack of dependence raised questions on the overall experimental approach, including details of the assembly procedures.

4.3 Projectile Seating Methods. Two five-round comparison test series were performed. In the first test series, Series 3 (Table 10), the projectile was seated using one of two methods. A hammer was used for the first method, and a clamp and screw were used for the second method. The hammer method consisted simply of hammering the projectile into the engraving band. The clamp and screw method provided approach for forcing the projectile into the engraving band. In both cases, the projectile was displaced to the same position (i.e., flush with the end of the barrel).

The second test series, Series 4, used only the screw and clamp method. The conditions for the second test series also included paying closer attention to chamber assembly details than normally done in the earlier tests. These details included, for each test, the same orientation of the piston, transducer block, crash ring, and the same volume of grease used between the piston wall and the chamber. The results are summarized in Table 10 for Test Series 4. The tests were all fired from a new gun tube (starting with I.D. 68). The liquid propellant charge was a 1/3 charge (80 cm³) of 1845 using an igniter charge of 3.5 g of IMR 4350. The nominal projectile weight was 287 g.

The results from Test Series 3 did not indicate that either method for seating the projectile improved muzzle velocity reproducibility. The earlier test series showed that with the hammer technique, a reproducibility of 1.0 to 1.9% was achievable. In fact, the earlier study by Reeve (1984) suggested that the hammer technique would yield better reproducibility over the

Table 8. Summary of Piston and Ballistic Data

Identification No.	Max Chamber Pressure, MPa	Projectile Velocity, m/s	Piston Velocity	
			During Igniter Venting, m/s	Maximum, m/s
Test Series 1				
9	155	848	2.86	15.04
22	139	847	—	—
23	150	868	—	—
24	155	845	4.33	15.83
25	175	865	3.43	15.92
Mean	155	855		
Std Deviation	13.0 (18.4%)	11.0 (1.0%)		
Test Series 2				
56	188	917	2.42	15.48
57	160	880	2.71	15.20
58	196	918	2.88	14.30
59	156	891	hang fire	
61	175	909	2.10	13.40
Mean	175	903		
Std Deviation	17.3 (9.9%)	16.8 (1.9%)		

Note: The propellant was 1846. All tests in Series 1 and 2 were performed at the one-third propellant charge or 80 cm³.

Table 9. Summary of Start-up Characteristics

Identification No.	Igniter Charge	P1, MPa	P2, MPa	P _{Ign.} , MPa	Time Between P1 and P2, ms
Test Series 1					
9	3.0			10.0	
22	3.0			13.5	
23	3.0			17.5	
24	3.0			27.8	
25	3.0			23.5	
Test Series 2					
56	3.5			19.8	
57	3.5	12.8	28.3	22.2	1.7
58	3.5	5.5		22.0	
59	3.5	5.1	32.2		0.84 (hang fire)
61	3.5	9.0	26.8	15.1	2.7

Table 10. Comparison in Ballistic Performance Between Two Methods for Seating the Projectile

Identification No.	Projectile Seating Method	Chamber Pressure (Maximum), MPa	Muzzle Velocity, m/s
Test Series 3			
68	hammer	131	857
70	hammer	161	888
71	pressed	122	887
72	pressed	127	852
73	pressed	—	853
Mean		135	867
Std Deviation		17.6 (13.0%)	18.4 (2.1%)
Test Series 4			
74	pressed	115	870
75	pressed	113	865
76	pressed	115	870
78	pressed	125	881
79	pressed	126	881
Mean		119	873
Std Deviation		6.2 (5.2%)	7.23 (0.83%)

pressed screw approach. Based on the results of Test Series 3, it was decided to conduct a new series of tests using the pressed screw approach to determine if this was indeed true.

The results from Test Series 4 indicated that the pressed screw technique yielded better reproducibility than the earlier hammer technique. The results showed almost a factor of two improvement over previous test series at the one-third charge. Also, the improved level of reproducibility, demonstrated in Test Group 4, suggests the importance of reproducing the initial conditions for achieving repeatable muzzle velocity. Specifically, the data, although limited to five tests, strongly suggest the importance of duplicating the overall assembly procedures.

5. DISCUSSION AND CONCLUSIONS

Prior to the present study, the standard deviation for the tests with the BRL 30-mm RLPG, Concept VI, was typically about 1.5%. Using the pressed-screw-projectile seating technique and by paying close attention to reproducing the initial conditions, such as orientation of the assembly components and the lubrication procedures, the standard deviation was decreased to 0.8% for a five-round group.

It was found that none of the early start-up parameters that were studied could account for the observed variations in the muzzle velocity. The initial conditions having the most effect on the muzzle velocity reproducibility also were not identified. It would seem, however, that some of the parameters affecting the early projectile motion might play a key role in achieving reproducible muzzle velocity. These parameters include the projectile design, the amount of erosion in the gun tube, and the method for seating the projectile. Of lesser importance, but parameters which should not be overlooked, include the orientation of the piston in the chamber and the volume of lubrication which is used on the piston, parameters which might help to insure similar resistive profiles for the piston displacement.

It should be pointed out that all of the tests with the 30-mm reported here were performed with a reduced injection sheet thickness. For this reason, the muzzle velocities were lower than those which would have been obtained with an optimized injection profile. It is not known if a larger sheet thickness would have contributed to a more consistent muzzle velocity.

The effect of the maximum igniter output pressure was one parameter, which could be examined using an interior ballistic code. The model developed by Coffee (1985) was used. This is a lumped parameter model which specifies a maximum ignition pressure as an input to the model. Details of the igniter venting process are not simulated in the model. Four computer runs were made with the igniter output pressure varying from 12 to 25 MPa. The results of the igniter parametric sensitivity analysis show a decrease in the calculated maximum chamber pressure with an increase in igniter pressure, an unexpected result. A higher igniter pressure displaces the piston faster and moves the projectile earlier, resulting in a larger instantaneous volume, which may account for the predicted lower maximum chamber pressure.

INTENTIONALLY LEFT BLANK.

6. REFERENCES

- Coffee, T. P. "A Lumped Parameter Code for Regenerative Liquid Propellant Guns." BRL-TR-2703, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, December 1985.
- Freedman, E. Private communication. U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1987.
- Klingenberg, G. "Invasive Spectroscopic Technique for Measuring Temperature in Highly Pressurized Combustion Chambers." Optical Engineering, vol. 24, no. 4, pp. 692-696, July-August 1985.
- Klingenberg, G., J. D. Knapton, C. A. Watson, I. C. Stobie, and W. F. Morrison. "Liquid Gun Propellant Studies: Closed Bomb and Gun Experiments." The 10th International Symposium on Ballistics, San Diego, CA, October 1987.
- Kostkowski, H. J., and R. D. Lee. "Theory and Methods of Optical Pyrometry." Precision Measurements and Calibration, Temperature, edited by J. F. Swindells, National Bureau of Standards SP-300, vol. 2, pp. 375-13 to 376-14, 1968.
- Magoon, I. K., J. Mandzy, C. A. Watson, J. DeSpirito, and J. D. Knapton. "Test Data from a Regenerative-Sheet-Type of Liquid Propellant Gun." Chemical Propulsion Information Agency Publication 432, vol. 2, pp. 225-238, October 1985.
- Mandzy, J., P. G. Cushman, and I. K. Magoon. "Liquid Propellant Final Report." General Electric Ordnance Systems Division, Pittsfield, MA, August 1984a (Contract No. DAAK11-78-C-0054, also published as BRL-CR-546, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, October 1985).
- Mandzy, J., P. G. Cushman, and I. K. Magoon. "Technical Notes on Scaling Investigation of Concept VI." General Electric Ordnance Systems Division, Pittsfield, MA, August 1984b (Contract No. DAAK11-78-C-0054, also published as BRL-CR-580, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1987).
- Pate, R. A., and I. K. Magoon. "Preliminary Results from Ballistic Investigations in 30-mm Regenerative Gun Firings." Chemical Propulsion Information Agency Publication 432, vol. 2, pp. 213-224, October 1985.
- Reever, K. P. "Operating Manual and Final Test Report for 30-mm BRL Regenerative Liquid Propellant Test Fixture." General Electric Ordnance Systems Division, Pittsfield, MA, (Contract No. DAAK11-83-C-0007), 1984.
- Watson, C. A., and J. D. Knapton. "An Estimate of Sound Speed During the Interior Ballistic Firing of a Regenerative Liquid Propellant Gun." Chemical Propulsion Information Agency Publication No. 476, vol. 3, pp. 395-404, October 1987.

Watson, C. A., J. D. Knapton, N. Boyer, I. Stobie, and M. Decker. "The Ballistic Characteristics of Contaminated Liquid Propellants in a 30-mm Regenerative Liquid Propellant Gun." Chemical Propulsion Information Agency Publication No. 457, vol. 2, pp. 539-550, October 1986.

Watson, C. A., J. D. Knapton, J. DeSpirito, and N. Boyer. "A Study on High Frequency Oscillations Observed in a 30-mm Regenerative Liquid Propellant Gun." Chemical Propulsion Information Agency Publication 432, vol. 2, pp. 239-254, October 1985.

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander U.S. Army Materiel Command ATTN: AMCAM 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander U.S. Army Tank-Automotive Command ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-5000
1	Commander U.S. Army Laboratory Command ATTN: AMSLC-DL 2800 Powder Mill Road Adelphi, MD 20783-1145	1	Director U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI Ft. Sill, OK 73503-5000
		(Class. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	(Unclass. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050	1	Air Force Armament Laboratory ATTN: WL/MNOI Eglin AFB, FL 32542-5000
			<u>Aberdeen Proving Ground</u>
(Unclass. only) 1	Commander U.S. Army Armament, Munitions and Chemical Command ATTN: AMSMC-IMF-L Rock Island, IL 61299-5000	2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Director U.S. Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000	1	Cdr, USATECOM ATTN: AMSTE-TC
		3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
		1	Dir, VLAMO ATTN: AMSLC-VL-D
		10	Dir, BRL ATTN: SLCBR-DD-T

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Director Defense Advanced Research Projects Agency ATTN: J. Lupo J. Richardson 1400 Wilson Blvd. Arlington, VA 22209
1	HQ, U.S. Army Material Command ATTN: AMCICP-AD, B. Dunetz 5001 Eisenhower Ave. Alexandria, VA 22333-0001
7	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-BR, B. Brodman W. Seals A. Beardell SMCAR-AEE-B, D. Downs SMCAR-AEE-W, N. Slagg SMCAR-AEE, A. Bracuti J. Lannon Picatinny Arsenal, NJ 07806-5000
6	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-FSS-DA, Bldg. 94, J. Feneck R. Kopmann J. Irizarry M. Oetken SMCAR-FSS-D, L. Frauen SMCAR-FSA-S, H. Liberman Picatinny Arsenal, NJ 07806-5000
1	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCS-C, T. Hung Picatinny Arsenal, NJ 07806-5000

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
4	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-DS E. Conroy A. Graham SMCAR-CCB, L. Johnson SMCAR-CCB-S, F. Heiser Watervliet, NY 12189-4050
1	Commander Materials Technology Laboratory U.S. Army Laboratory Command ATTN: SLCMT-MCM-SB, M. Levy Watertown, MA 02172-0001
1	Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-IS-L-R, Myer Center Fort Monmouth, NJ 07703-5000
1	Commander U.S. Army Laboratory Command ATTN: SLCHD-TA-L 2800 Powder Mill Rd. Adelphi, MD 20783-1145
1	Commander U.S. Army Belvoir RD&E Center ATTN: STRBE-WC, Tech Library (Vault) B-315 Fort Belvoir, VA 22060-5606
1	Commander U.S. Army Research Office ATTN: Technical Library PO Box 12211 Research Triangle Park, NC 27709-2211
2	Commandant U.S. Army Field Artillery School ATTN: ATSF-CMW ATSF-TSM-CN, J. Spicer Fort Sill, OK 73503
1	Commandant U.S. Army Armor Center ATTN: ATSB-CD-MLD Fort Knox, KY 40121

<u>No. of</u>	<u>Organization</u>
1	Commander Naval Surface Warfare Center ATTN: D. A. Wilson, Code G31 Dahlgren, VA 22448-5000
1	Commander Naval Surface Warfare Center ATTN: J. East, Code G33 Dahlgren, VA 22448-5000
2	Commander Naval Surface Warfare Center ATTN: O. Dengel K. Thorsted Silver Spring, MD 20902-5000
1	Commander (Code 3247) Naval Weapons Center Guns Systems Branch China Lake, CA 93555-6001
1	OSD/SDIO/IST ATTN: Dr. Len Caveny Pentagon Washington, DC 20301-7100
1	Commandant USAFAS ATTN: ATSF-TSM-CN Fort Sill, OK 73503-5600
2	Director National Aeronautics and Space Administration ATTN: MS-603, Technical Library MS-86, Dr. Povinelli 21000 Brookpark Rd. Lewis Research Center Cleveland, OH 44135
1	Director National Aeronautics and Space Administration Manned Spacecraft Center Houston, TX 77058

<u>No. of</u>	<u>Organization</u>
1	Director Jet Propulsion Laboratory ATTN: Tech Library 4800 Oak Grove Drive Pasadena, CA 91109
10	Central Intelligence Agency Office of Central Reference Dissemination Branch Room GE-47 HQS Washington, DC 20502
1	Central Intelligence Agency ATTN: Joseph E. Backofen HQ, Room 5F22 Washington, DC 20505
1	Director Applied Physics Laboratory The Johns Hopkins University Johns Hopkins Rd. Laurel, MD 20707
2	Director CPIA The Johns Hopkins University ATTN: T. Christian Technical Library Johns Hopkins Rd. Laurel, MD 20707
1	University of Illinois at Chicago ATTN: Professor Sohail Murad Department of Chemical Engineering Box 4348 Chicago, IL 60680
1	University of Maryland at College Park ATTN: Professor Franz Kasler Department of Chemistry College Park, MD 20742
1	University of Missouri at Columbia ATTN: Professor R. Thompson Department of Chemistry Columbia, MO 65211

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	University of Michigan ATTN: Professor Gerard M. Faeth Department of Aerospace Engineering Ann Arbor, MI 48109-3796
1	University of Missouri at Columbia ATTN: Professor F. K. Ross Research Reactor Columbia, MO 65211
1	University of Missouri at Kansas City Department of Physics ATTN: Professor R. D. Murphy 1110 East 48th St. Kansas City, MO 64110-2499
1	Pennsylvania State University Department of Mechanical Engineering ATTN: Professor K. Kuo University Park, PA 16802
2	Princeton Combustion Rsch Laboratories, Inc. ATTN: N. A. Messina M. Summerfield 4275 U.S. Highway One North Monmouth Junction, NJ 08852
1	University of Arkansas Department of Chemical Engineering ATTN: J. Havens 227 Engineering Building Fayetteville, AR 72701
3	University of Delaware Department of Chemistry ATTN: Mr. James Cronin Professor Thomas Brill Mr. Peter Spohn Newark, DE 19711
1	University of Texas at Austin Bureau of Engineering Research ATTN: BRC EME133, Room 1.100 H. Fair 10100 Burnet Rd. Austin, TX 78758

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Calspan Corporation ATTN: Tech Library P.O. Box 400 Buffalo, NY 14225
6	General Electric Ord Sys Div ATTN: J. Mandzy, OP43-220 R. E. Mayer H. West W. Pasko R. Pate I. Magoon 100 Plastics Ave. Pittsfield, MA 01201-3698
1	General Electric Company Armament Systems Department ATTN: D. Maher Burlington, VT 05401
1	Alliant Techsystems, Inc. ATTN: R. E. Tompkins MN38-3300 10400 Yellow Circle Drive Minnetonka, MN 55343
1	IITRI ATTN: Library 10 W. 35th St. Chicago, IL 60616
1	Olin Chemicals Research ATTN: David Gavin P.O. Box 586 Cheshire, CT 06410-0586
2	Olin Corporation ATTN: Victor A. Corso Dr. Ronald L. Dotson 24 Science Park New Haven, CT 06511
1	Paul Gough Associates, Inc. ATTN: Paul Gough 1048 South St. Portsmouth, NH 03801-5423

No. of
Copies Organization

- 1 Safety Consulting Engineering
ATTN: Mr. C. James Dahn
5240 Pearl St.
Rosemont, IL 60018

- 1 Science Applications, Inc.
ATTN: R. Edelman
23146 Cumorah Crest
Woodland Hills, CA 91364

- 2 Science Applications International
Corporation
ATTN: Dr. F. T. Phillips
Dr. Fred Su
10210 Campus Point Drive
San Diego, CA 92121

- 1 Science Applications International
Corporation
ATTN: Norman Banks
4900 Waters Edge Drive
Suite 255
Raleigh, NC 27606

- 1 Sundstrand Aviation Operations
ATTN: Mr. Owen Briles
P.O. Box 7202
Rockford, IL 61125

- 1 Veritay Technology, Inc.
ATTN: E. B. Fisher
4845 Millersport Highway
P.O. Box 305
East Amherst, NY 14051-0305

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

BRL Report Number BRL-TR-3323 Division Symbol _____

Check here if desire to be removed from distribution list. _____

Check here for address change. _____

Current address: Organization _____
Address _____

DEPARTMENT OF THE ARMY
Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

