

2

NPS-MA-92-005

NAVAL POSTGRADUATE SCHOOL

Monterey, California

AD-A248 251



DTIC
S ELECTE D
APR 07 1992
D

ANALYTICAL STRENGTH FORMULAS
 FOR SHIP HULLS

Donald A. Danielson

February 1992

Approved for public release; distribution unlimited
 Prepared for: ATLSS Engineering Research Center
 Lehigh University
 Bethlehem, PA

92 4 6 151

92-08912



NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93943

Rear Admiral R. W. West, Jr.
Superintendent

Harrison Shull
Provost

This report was prepared in conjunction with research conducted for the ATLSS Engineering Research Center, Lehigh University and funded by the ATLSS Engineering Research Center. Reproduction of all or part of this report is authorized.

Prepared by:

D. A. Danielson

DONALD A. DANIELSON
Professor

Reviewed by:

Released by:

H. M. Fredricksen

HAROLD M. FREDRICKSEN
Chairman
Department of Mathematics

P. J. Marto

PAUL MARTO
Dean of Research

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No 0704-0188	
1a REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b RESTRICTIVE MARKINGS		
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b DECLASSIFICATION/DOWNGRADING SCHEDULE					
4 PERFORMING ORGANIZATION REPORT NUMBER(S) NPS-MA-92-005			5 MONITORING ORGANIZATION REPORT NUMBER(S)		
6a NAME OF PERFORMING ORGANIZATION Naval Postgraduate School		6b OFFICE SYMBOL (If applicable) MA	7a NAME OF MONITORING ORGANIZATION ATLSS Engineering Research Center		
6c ADDRESS (City, State, and ZIP Code) Monterey, CA 93943-5000			7b ADDRESS (City, State, and ZIP Code) Lehigh University Bethlehem, PA 18015-4729		
8a NAME OF FUNDING/SPONSORING ORGANIZATION ATLSS Engineering Research Ctr		8b OFFICE SYMBOL (If applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c ADDRESS (City, State, and ZIP Code) Lehigh University Bethlehem, PA 18015-4729			10 SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO	PROJECT NO	TASK NO
					WORK UNIT ACCESSION NO
11 TITLE (Include Security Classification) ANALYTICAL STRENGTH FORMULAS FOR SHIP HULLS					
12 PERSONAL AUTHOR(S) DANIELSON, Donald A.					
13a TYPE OF REPORT Technical		13b TIME COVERED FROM 9/91 TO 12/91		14 DATE OF REPORT (Year, Month, Day) 92 - 2 - 21	15 PAGE COUNT 20
16 SUPPLEMENTARY NOTATION					
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	ship, double hull, shell, plate, structure, solid mechanics, elasticity, strength, bending, pressure, cylinder, stress, bulkhead		
19 ABSTRACT (Continue on reverse if necessary and identify by block number) The subject of this report is a proposed new surface ship hull concept consisting of a double skin that wraps around the bottom, sides and main deck. The two skins are connected by plates normal to the surfaces, forming a cellular structure similar to a cardboard box. Modeling the ship hull as a circular cylindrical orthotropic shell surrounding an elastic core, we are able to obtain analytical formulas for estimating the principal stresses in such a structure, subjected to end bending moments and lateral pressure. These formulas indicate that the stiffness of the proposed bulkheads in the proposed design could be reduced by a factor of 10 without incurring significant secondary stresses in the double hull.					
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21 ABSTRACT SECURITY CLASSIFICATION		
22a NAME OF RESPONSIBLE INDIVIDUAL Donald A. Danielson			22b TELEPHONE (Include Area Code) (408) 646-2622	22c OFFICE SYMBOL MA/Dd	

DD Form 1473, JUN 86

Previous editions are obsolete

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

ANALYTICAL STRENGTH FORMULAS
FOR SHIP HULLS

BY

Donald A. Danielson

February 1992

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



1. INTRODUCTION: NEW SHIP STRUCTURE AND MODEL

The proposed new surface ship hull concept consists of a double skin that wraps around the bottom, sides, and main deck. The two skins are connected by plates normal to the surfaces forming a cellular structure similar to a cardboard box, as shown in Figure 1. The advantages of this type of construction have been described by Okamoto, et. al. [1], and Beach [2].

The object of this report is to develop formulas for estimating the principal stresses in such a structure. In order to be able to obtain simple analytical formulas, we model a ship hull as a circular cylindrical orthotropic shell surrounding an elastic core. Under a pure end bending moment M and a lateral pressure loading q which does not vary along the length, the cylinder bends into a curved tube of oval cross section, as shown in Figure 2.

2. SHELL EQUATIONS AND SOLUTION

The theory governing the deformation of thin shells is well developed and available in many forms. Here we use the semi-momentless shell theory of Axelrad [3]. ** When specialized to the linear St. Venant problem for circular cylindrical shells, Axelrad's equations (2.122) - (2.123) reduce to

$$\frac{\partial^4 \kappa_2}{\partial \eta^4} + \frac{\partial^2 \kappa_2}{\partial \eta^2} = -\frac{R^2}{D_2} \frac{\partial^2 q}{\partial \eta^2} \quad (1)$$

$$\frac{\partial^4 T_1}{\partial \eta^4} + \frac{\partial^2 T_1}{\partial \eta^2} = 0 \quad (2)$$

Here the coordinate η denotes the circumferential angle and R denotes the radius of the undeformed cylinder, as shown in Figure 2. The principal values of the change in curvature tensor are denoted by $\kappa_1(\eta)$ and $\kappa_2(\eta)$; their geometrical definitions are illustrated in Figure 3. The longitudinal membrane force $T_1(\eta)$ (force per unit length of the shell midsurface) is related to the longitudinal strain $e_1(\eta)$ by the constitutive law

$$T_1 = E h e_1 \quad (3)$$

Here h is the thickness of the shell, and E is Young's modulus. The longitudinal bending moment $M_1(\eta)$ and transverse bending moment $M_2(\eta)$ (moments per unit length of the shell midsurface) are related to the curvature changes $\kappa_1(\eta)$ and $\kappa_2(\eta)$ by the constitutive laws

$$M_1 = D_1(\kappa_1 + \nu \kappa_2), \quad M_2 = D_2(\kappa_2 + \nu \kappa_1) \quad (4)$$

** Our equations may also be obtained from other shell theories, such as that of Simmonds [4].

Here D_1 and D_2 are bending stiffnesses, and ν is Poisson's ratio. The longitudinal curvature change $\kappa_1(\eta)$ and transverse membrane force $T_2(\eta)$ are given in terms of the above variables by

$$\kappa_1 = -\frac{1}{EhR} \frac{\partial^2 T_1}{\partial \eta^2}, \quad T_2 = Rq + \frac{1}{R} \frac{\partial^2 M_2}{\partial \eta^2} \quad (5)$$

The net bending moment M acting on any cross section of the tube may be calculated from the formula

$$M = R^2 \int_0^{2\pi} T_1 \cos \eta \, d\eta \quad (6)$$

The strain measures are related to the displacement components by the equations

$$\kappa_1 = -\frac{1}{R^2} \frac{\partial^2 w}{\partial \xi^2} \quad (7)$$

$$\kappa_2 = -\frac{1}{R^2} \left(\frac{\partial^2 w}{\partial \eta^2} + w \right) \quad (8)$$

$$\tau = -\frac{1}{R^2} \left(\frac{\partial^2 w}{\partial \xi \partial \eta} - \frac{3}{4} \frac{\partial v}{\partial \xi} + \frac{1}{4} \frac{\partial u}{\partial \eta} \right) = 0 \quad (9)$$

$$e_1 = \frac{1}{R} \frac{\partial u}{\partial \xi} \quad (10)$$

$$e_2 = \frac{1}{R} \left(\frac{\partial v}{\partial \eta} + w \right) = 0 \quad (11)$$

$$\gamma = \frac{1}{R} \left(\frac{\partial u}{\partial \eta} + \frac{\partial v}{\partial \xi} \right) = 0 \quad (12)$$

Here $R\xi$ denotes the distance measured along the axis of the undeformed tube, as shown in Figure 2, and (u, v, w) denote displacement components in the $(\xi, \eta, \text{radial})$ directions.

We suppose that the pressure loading $q(\eta)$ acting normal to the surface of the shell can be expressed as

$$q(\eta) = -K[w(\eta) + w(\eta + \pi)] - \frac{\delta R}{2}(1 + \cos 2\eta) \quad (13)$$

at $\eta = 0$ is the longitudinal curvature of the cylinder axis due to the beam-like bending.

The terms in (15), (17), (19), (20) which are underlined are *secondary* quantities arising from ovalization of the cross section. Proper design requires that these quantities be made relatively small by having a large enough foundation modulus K .

3. APPLICATION TO DOUBLE HULL

As an example of the application of these formulas, let us consider the double hull sketched in Figure 1. An average hull section contains 3 plates each of thickness t and width b , as shown in Figure 5, so the average hull thickness is

$$h = 3t \quad (21)$$

The bending stiffnesses corresponding to this double hull geometry are

$$D_1 = \frac{7Eb^2t}{12(1-\nu^2)}, \quad D_2 = \frac{Eb^2t}{2(1-\nu^2)}. \quad (22)$$

Of interest for design purposes are the maximum stresses arising in the double hull. The magnitudes of the membrane stresses corresponding to the membrane forces (14) - (15) are less than

$$\sigma_{M1} = \frac{M}{3\pi tR^2} \quad (23)$$

$$\sigma_{M2} = \frac{\delta R^2}{4t} + \frac{\nu b^2 M}{12\pi(1-\nu^2)tR^4} + \frac{\delta R^2}{12t(1 + \frac{2KR^4}{9D_2})} \quad (24)$$

The magnitudes of the bending stresses corresponding to the bending forces obtained from (4) and (16) - (17) are less than

$$\sigma_{B1} = \frac{bM}{7\pi(1-\nu^2)tR^3} + \frac{\nu\delta R^3}{7bt(1 + \frac{2KR^4}{9D_2})} \quad (25)$$

$$\sigma_{B2} = \frac{\delta R^3}{6bt(1 + \frac{2KR^4}{9D_2})} + \frac{\nu bM}{6\pi(1-\nu^2)tR^3} \quad (26)$$

From the architectural drawings of the double hull cross section sketched in Figure 1, we have computed the average values displayed in the Table of the various geometrical and material parameters in our formulas. The value of M is the maximum value of the

design hogging bending moment. I is the moment of inertia of the hull cross section about its centroid. If we choose the cylindrical cross section to have the same moment of inertia as the hull, this determines the radius of the cylinder to be $R = 25.75$ ft. We suppose that the foundation stiffness K is the same as the bulkhead stiffness. From experiments on pyramidal truss cores typical of those which are proposed for the bulkhead structure, we have determined the average value of K shown in the Table.

Now let us put some of the numbers shown in the Table into the formulas (23) - (26):

$$\sigma_{M1} = 21.6 \quad (27)$$

$$\sigma_{M2} = 2.1 + \frac{.7}{1 + \frac{2KR^4}{9D_2}} \quad (28)$$

$$\sigma_{B1} = 1.15 + \frac{3.2}{1 + \frac{2KR^4}{9D_2}} \quad (29)$$

$$\sigma_{B2} = \frac{12.4}{1 + \frac{2KR^4}{9D_2}} + .4 \quad (30)$$

Here all stresses are in units of ksi. Note that if there were no elastic foundation ($K = 0$), the secondary stresses (those terms underlined in (28) - (30)) would be a sizeable fraction of the primary stresses. But $\frac{2KR^4}{9D_2} = 3733$, from the values in the table, so these secondary stresses are rendered negligible by the bulkhead stiffness.

4. CONCLUSION AND FUTURE WORK

Our analytical formulas indicate that the stiffness of the proposed bulkheads could be reduced by a factor of 10 without incurring significant secondary stresses in the double hull. A less bulky bulkhead design would have obvious cost and weight benefits.

This analysis models only the most fundamental aspects of the complex state of stress which could actually exist in the hull of a ship at sea. In future work the model should be refined to make its predictions correspond more closely to reality. Features which should be included are:

1. A more rectangular cross section corresponding to the actual hull shape. This could perhaps be included within the framework of the present analysis by conformal mapping techniques.
2. A more realistic applied loading, including torsion and internal pressures.
3. Discrete treatment of the bulkheads and other stiffeners. Also, allowance for nonuniform stiffness properties.
4. Geometric and material nonlinearities. This is essential for an ultimate strength analysis.

ACKNOWLEDGEMENTS

The author performed this work while a visiting researcher at Lehigh University in Bethlehem, PA, and was supported by the Fleet of the Future Program, directed by Prof. John W. Fisher. Prof. Le-Wu Lu of the Civil Engineering Department at Lehigh proposed the problem of determining how the secondary stresses depend upon the bulkhead stiffness. Mr. Alan Pang computed the values of the last four parameters shown in the Table.

REFERENCES

1. T. Okamoto, et. al., "Strength Evaluation of Novel Unidirectional - Girder - System Product Oil Carrier by Reliability Analysis," Transactions of the Society of Naval Architects and Marine Engineers, Vol 93, 1985.
2. J. Beach, "Advanced Surface Ship Hull Technology," Transactions of the American Society of Naval Engineers, 1990.
3. E. Axelrad, Theory of Flexible Shells, North Holland, 1987.
4. J. Simmonds, "A Set of Simple, Accurate Equations for Circular Cylindrical Elastic Shells," Int. J. Solids and Structures, vol 2, 1966, pp. 525-541.







Figure 1: Double hull designed by David Taylor Research Center.



Circular Cross Section
Undeformed



Deformed



Oval Cross Section
Springs Representing Foundation Stiffness, K

Section A-A

Figure 2: Idealized Model of Double Hull




Figure 3: Geometrical Definitions of Curvature Changes




Figure 4: Lateral Pressure Loading





Figure 5: Stresses Acting in Double Hull Wall

Table 1: Typical Parameter Values

M	665,000 kip-ft
δ	0.0624 kip/ft ³
E	29,500 ksi
ν	0.3
t	0.41 in
b	35 in
$I=\pi R^3 h$	5500 ft ⁴
K	15 kip/in ³

INITIAL DISTRIBUTION LIST

DIRECTOR (2)
DEFENSE TECH. INFORMATION
CENTER, CAMERON STATION
ALEXANDRIA, VA 22314

DIRECTOR OF RESEARCH ADMIN.
CODE 012
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93943

CENTER FOR NAVAL ANALYSES
4401 FORD AVENUE
ALEXANDRIA, VA 22311

ATLSS ENGINEERING RESEARCH
CENTER
LEHIGH UNIVERSITY
117 ATLSS DR., IMBT LABS
BETHLEHEM, PA 18015-4729

LIBRARY (2)
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93943

DEPT. OF MATHEMATICS
CODE MA
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93943

PROF. DONALD DANIELSON (25)
CODE MA/Dd
DEPARTMENT OF MATHEMATICS
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93943