

AD-A248 443



TATION PAGE

Form Approved
OMB No. 0704-0188

1 to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this form to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Avenue, Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE Final Technical Report	3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Dynamic Instability & Transient Vibrations in Gas-Propelled Guns		5. FUNDING NUMBERS	
6. AUTHOR(S) Iradj G. Tadjbakhsh			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Rensselaer Polytechnic Institute Troy, New York 1218		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Transient vibrations of long flexible and gas-propelled guns are studied. The effects of transverse shear and rotary inertia in the cylindrical shell are included. The vibrations at any point is null before the arrival of projectile and is followed by a sudden high frequency large amplitude radial response which then decays			
14. SUBJECT TERMS		15. NUMBER OF PAGES 3	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED
			20. LIMITATION OF ABSTRACT UL

DTIC
SELECTE
S APR 13 1992 D
D

DYNAMIC INSTABILITY & TRANSIENT
VIBRATIONS IN GAS-PROPELLED
GUNS

FINAL TECHNICAL REPORT

IRADJ TADJBAKESH

FEBRUARY 15, 1992

U.S. ARMY RESEARCH OFFICE
GRANT NO. DAAL0-3-89-K-0002

RENSSELAER POLYTECHNIC INSTITUTE

APPROVED FOR PUBLIC RELEASE

DISTRIBUTION UNLIMITED

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

92-09260



92 4 10 031

A. Problem Statement

In the first part of this study the gun tube is modeled as a flexible cylindrical shell with the effects of transverse shear and rotary inertia retained in the theoretical description. The projectile is modeled as a rigid body which rides on the gun tube and is driven by the expanding pressure front. Each body is governed separately by the laws of motion and the reaction forces that act between them. The interaction is considered to be that of two bodies that exert forces upon each other that are normal to the surface of contact. This type of interaction gives rise to forces acting on the projectile that depend upon the deformation of the cylinder. The reaction on the cylinder may be thought of as a traveling force whose magnitude, as well as position, depend upon the deformation. Thus the problem is nonlinear even in the context of linear shell theory.

B. Summary of the Most Important Results

Transient vibrations in the flexible gun tubes of gas-propelled hypervelocity gun was successfully analyzed employing Galerkin procedure and numerical integration of nonlinear initial value problems. In the hypervelocity range when the speed of the pressure front is faster than the critical velocity of the cylindrical shell, the nature of vibration changes significantly. Qualitatively, the bending response is directly proportional to the velocity and mass of the projectile. Quantitatively, the bending deflection is of the order of 10^{-4} which is negligible in most cases.

The response of the system is dominated by the rotationally symmetric mode. A resonant phenomenon occurs when the speed of the pressure front is near hypervelocity conditions. The peak value of the radial expansion and the resonant range depend on the acceleration of the projectile. Vibrations are wave-like, have a local character and decay exponentially after passage of the front.

C. List of All Publications

1. "The Transient Vibrations and Instability in Flexible Guns - I. Formulation," by Yuan-An Su and Iradj G. Tadjbakhsh, Int. J. Impact Engng., Vol. 11, No. 2, pp. 159-171, 1991.
2. "Transient Vibrations and Instability in Flexible Guns - II. Response Characteristics," by Yuan-An Su and Iradj Tadjbakhsh, Int. J. Impact Engineering, Vol. 11, No. 2, pp. 173-184, 1991.
3. "Optimal Coupled-Modal Control of Distributed Parameter System," by Iradj G. Tadjbakhsh and Yuan-An Su, ASME, Journal of Applied Mechanics, Vol. 56, No. 4, pp. 941-946, Dec. 1989.
4. "Optimal Control of Beams with Dynamic Loading and Buckling," by Yuan-An Su and Iradj Tadjbakhsh, ASME J. Appl. Mech., Vol. 58, No. 1, pp. 197-202, 1991.

D. List of Participants

Yuan-An Su, Ph.D. August 1991.

Yi-Ming Wang, Ph.D. (Expected August 1992)

F. Rofooei, Ph.D. (Expected August 1992)