

AD-A254 539



N PAGE

Form Approved
OMB No 0704-0188

Estimated to average 1 hour per response, including the time for reviewing instructions, the data needed, and completing and reviewing the collection of information. Send request of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1

Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 08/92		3. REPORT TYPE AND DATES COVERED POP Test (07/92)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Container, Shipping and Storage, for the Mk 132 Mod 0 Mine Refurbishing Kit for Packing Group II Solid Hazardous Materials				5. FUNDING NUMBERS	
6. AUTHOR(S) Dennis M. Kotun					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Weapons Station Earle Test and Evaluation Branch (Code 5023) Colts Neck, NJ 07722-5000				8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92021	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Deputy Commander, Naval Mine Warfare Engineering Activity Port Hueneme Division Naval Surface Warfare Center Yorktown, VA 23691-5076				10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A					
12a. DISTRIBUTION/AVAILABILITY STATEMENT			12b. DISTRIBUTION STATEMENT CODE A		
13. ABSTRACT (Maximum 200 words) This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Shipping and Storage Container for the Mk 132 Mod 0 Mine Refurbishing Kit meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was one inert Mk 132 Mod 0 Mine Refurbishing Kit weighing 82 kg (180 pounds)). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 9 kg (18 pounds) were added. Gross weight of the loaded container was 132 kg (291 pounds). The test results indicate that the container has conformed to the POP requirements.					
14. SUBJECT TERMS POP Test of Shipping and Storage Container for the Mk 132 Mod 0 Mine Refurbishing Kit				15. NUMBER OF PAGES 7	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UL		19. SECURITY CLASSIFICATION OF ABSTRACT UL	
				20. LIMITATION OF ABSTRACT UL	

DTIC
ELECTE
AUG 21 1992
S D

DODPOPHM/USA/DOD/NADTR92021

PERFORMANCE ORIENTED PACKAGING TESTING
OF
CONTAINER, SHIPPING AND STORAGE, FOR THE
MK 132 MOD 0 MINE REFURBISHING KIT
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

Author:
Dennis M. Kotun
Mechanical Engineering Technician

DTIC QUALITY INSPECTED 5

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

August 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Deputy Commander
Naval Mine Warfare Engineering Activity
Port Hueneme Division
Naval Surface Warfare Center
Yorktown, VA 23691-5076

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

92-23268



396835

7p

92 8 20 053

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Shipping and Storage Container for the Mk 132 Mod 0 Mine Refurbishing Kit (Packing Group II) meets the requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was one inert Mk 132/0 Mine Refurbishing Kit weighing 82 kg (180 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 9 kg (18 pounds) were added. Gross weight of the loaded container was 132 kg (291 pounds).

Due to unavailability only one container was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 264 kg (582 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

- a. Horizontally.
- b. Diagonally on the edge between the cover assembly and the top ring of the container.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 3.6 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the container was inspected. The inert refurbishing kit was completely retained by the container.

REFERENCE MATERIAL

- A. Code of Federal Regulations, Title 49 CFR, Parts 107-178.
- B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center
ATTN: DDRV-TMPA, D. Gay
Richmond, VA 23219

Commander
Naval Surface Warfare Center
ATTN: Crane Division (Code 4053)
Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:	
UN 1A2/Y132/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
Container: Shipping and Storage Container	
Type: 1A2	Container P/N or NSN: NSN 1351-01-208-2478
Drawing Number: 5479210	Outer Packaging Material: Steel
Dimensions: 46" H x 31.5" dia.	Gross Weight: 132 kg (291 pounds)
Closure (Method/Type): Removable Cover w/Locking Ring	Tare Weight: 43 kg (93 pounds)
Additional Description:	
PACKAGED COMMODITY:	
Name: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container: See table 1	Flash Point: N/A
Net Weight: See table 1	
PACKAGED COMMODITY USED FOR TEST:	
Name: Mk 132 Mod 0 Mine Refurbishing Kit	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	Net Weight: 90 kg (198 pounds)
Additional Description:	
The net weight includes the current maximum commodity weight plus an additional 9 kg (18 pounds).	

N/A = Not Applicable

TABLE 1
Commodities Approved for Shipping in the
Shipping and Storage Container for the
Mk 132 Mod 0 Mine Refurbishing Kit

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
1W33	1351-01-208-2478	Kit, Refurbishing, Mine, Mk 132 Mod 0 for Mine Mk 65	5479210	1.4B	0257	1	180	273