

AD-A254 797



KEEP THIS COPY FOR REPRODUCTION PURPOSES

IDENTIFICATION PAGE

Form Approved
OMB No. 0704-0188

Estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering the data, reviewing the collection of information, Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Avenue, Washington, DC 20540, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

Davis Highway, Suite 1000, Arlington, VA 22204-3042

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE Final May 92	3. REPORT TYPE AND DATES COVERED Final 1 Aug 89-31 Jan 92	
4. TITLE AND SUBTITLE Multidimensional Signals, Data and Processes		5. FUNDING NUMBERS DAAL03-89-K-0128	
6. AUTHOR(S) Eugene Wong and Jean Walrand			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of California Berkeley, CA 94720		8. PERFORMING ORGANIZATION REPORT NUMBER DTIC ELECTRONIC AUG 5 1992 A D	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARO 26144.1-MA	
11. SUPPLEMENTARY NOTES The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The first part of the work yielded new results on simulated annealing and neural networks while the second part focused on large deviations in high-speed communication networks.			
14. SUBJECT TERMS Neural Networks, Communication Networks, Simulated Annealing, High-Speed Networks		15. NUMBER OF PAGES 4	16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

92-20821



92 7 1 1 0

26144 -MA

MAY 26 RECD

UNIVERSITY OF CALIFORNIA, BERKELEY

BERKELEY • DAVIS • IRVINE • LOS ANGELES • RIVERSIDE • SAN DIEGO • SAN FRANCISCO



SANTA BARBARA • SANTA CRUZ

COLLEGE OF ENGINEERING
ELECTRONICS RESEARCH LABORATORY

BERKELEY, CALIFORNIA 94720

May 19, 1992

Dr. Jagdish Chandra
Director
Mathematical Sciences Division
Department of the Army
Army Research Office
P.O. Box 12211
Research Triangle Park, NC 27709-2211

Dear Dr. Chandra:

Enclosed please find the final technical report for ARO contract DAAL03-89-K-0128, "Multidimensional signals, data and processes", Professors Eugene Wong and Jean Walrand, Principal Investigators.

If you have any questions please call me at 510-642-7201 or Professor Walrand at 510-642-1529.

Sincerely,

A handwritten signature in cursive script that reads "Margie Berger".

Margie Berger
Grants Administrator

cc: Patsy S. Ashe
Linden Clausen

May 15, 1992

Multidimensional signals, data and processes

(Contract DAAL03-89-K-0128)



Department of Electrical
Engineering and Computer
Sciences

University of California

Berkeley, California 94720

Eugene Wong & Jean Walrand
(510 642 1529; wlr@ee.berkeley.edu)

Final report prepared for the
Mathematical and Computer Sciences Division of the
Army Research Office

1.0 Abstract

The work performed under this contract has two parts. The first part was performed by Professor Eugene Wong and Mr. George Kesidis. That part of the work yielded new results on simulated annealing and neural networks.

On May 1, 1990, Professor Wong was confirmed as Associate Director for Physical Science and Engineering with the White House Office of Science and Technology Policy. As a result of this appointment, Professor Walrand served as Acting Principal Investigator on this contract. The work performed by Professor Walrand and George Kesidis focused on large deviations in high-speed communication networks.

2.0 Succinct Description:

2.1 Neural Networks and Simulated Annealing

2.1.1 Motivation

A neural network computes the minimum of a function. When the function is suitably chosen, the neural network solves a practical optimization problem. Neural networks have been used to recognize speech, to identify features in pictures, to detect messages

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Availability or Special
A-1	

DTIC REPORT NUMBER 113

Succinct Description:

in noisy signals, to control routing in communication networks, to control robots and machinery, and in a variety of other engineering applications.

Simulated annealing refers to a class of global optimization algorithms. These algorithms are particularly useful when relatively little is known about the structure of the function to be minimized and when that function is likely to have many local minima that would trap the more classical optimization algorithms.

The extent of possible applications of neural networks and simulated annealing and their performance compared to other methods are of considerable interest because of their potential applications.

2.1.2 Technical Objectives

Our objectives are to contribute to the understanding of neural networks and simulated annealing. In this work, we propose a new class of neural networks called diffusion machines. We have designed implementations of these diffusion machines. We have also derived new results on the optimal cooling of simulated annealing algorithms.

The diffusion machine that we propose can be viewed as an improvement of Hopfield networks and of Boltzmann machines.

2.1.3 Approach

The diffusion machine is a stochastic version of a Hopfield network. The diffusion machine can be made to converge to the global minimum of a function when the Hopfield network would be trapped by a local minimum.

Alternatively, the diffusion machine can be viewed as a continuous-time version of a Boltzmann Machine. Consequently, the diffusion machine can be made to converge much faster than a Boltzmann machine.

Finally, we have shown that a diffusion machine is suitable for implementation, either with analog circuitry or with a digital signal processing microprocessor.

2.2 High-Speed Networks

2.2.1 Motivation

The future telephone network will probably be built using the Asynchronous Transfer Mode (ATM) technology. Before transporting information, an ATM network breaks it up into fixed size cells of 424 bits. The network transports cells that belong to the same information stream along the same path, called a virtual-circuit.

ATM networks are designed for losing only a very small fraction of cells. Both the network parameters, such as buffer size, and the rules of operations of the network, such as the call admission, the routing, and the priority mechanisms, must take this objective into account.

2.2.2 Technical Objectives

New design methodologies and adaptive control techniques must be developed that estimate efficiently and limit the small cell loss probabilities. Our research focuses on the development of such design methodologies and control techniques.

Our work has two main objectives. For *network design*, we need efficient simulation techniques. For instance, if the target cell loss probability is one per million, then a direct simulation must simulate a few million cells going through the network before it can estimate such a small loss probability. Consequently, such a direct simulation is exceedingly slow. Typically, estimating such a small loss probability by a direct simulation of even a very simple network requires many hours on a high-performance workstation. We have developed quick simulation techniques that achieve the same accuracy in a few minutes.

The second objective is the development of quick estimation techniques for the *real-time control* of ATM networks. Roughly speaking, to control the cell loss rate, the network must monitor that loss rate and make decisions on the basis of the measurements. If the network takes a long time before it has an accurate estimate of its cell loss rate, then it is not able to control that loss rate efficiently. We have developed quick estimators that speed up the collection of the relevant statistics by a few orders of magnitude.

2.2.3 Approach

Our methods are based on results from the theory of large deviations. This theory indicates the likely behavior of the traffic in an overflowing buffer. We use these results in two ways: to select a change of measure for quick simulation, and to speed up real-time estimations by extrapolations.

The quick simulation method can be described as follows. Say that you want to estimate the number of fish in a lake. Assume that you know that the density of fish in a particular region of the lake is 100 times larger than the average density. An efficient method is then to sample that particular region of the lake and to correct for the average density by dividing by the factor 100. The technique of importance sampling is based on that idea. The difficulty in using the technique is in guessing the dense region of the lake. In the simulation of ATM networks, the lake is the set of possible evolutions of the contents of the buffers in the ATM switches and the fish are the evolutions that lead to cell losses. The dense region of the lake, i.e., the evolutions that are likely to lead to cell losses, is discovered by the theory of large deviations. The correction factor (100 in the fishy analogy) is computed during the simulation by calculating a likelihood ratio. Technically, we use level 3 large deviation results for Markov chains. We have used this method for Markov fluid and Markov modulated Poisson models of ATM traffic. The measured speed up achieved by the quick simulation over the direct simulation is typically from 400 to 600.

The quick estimation method is also based on the theory of large deviations. The idea is simpler than quick simulation. Using the theory of large deviations we can show that the cell loss rate at a buffer of size B in a switch of an ATM network is asymptotically exponential in B . The idea is then to measure the cell loss rate for fictitiously small values of B and to extrapolate using the exponential form of the cell loss rate. In practice, the

**THIS
PAGE
IS
MISSING
IN
ORIGINAL
DOCUMENT**

4-4