

AD-A255 594



2

TECHNICAL REPORT BRL-TR-3391

BRL

AN INVERSE ANALYSIS OF ELECTROTHERMAL-CHEMICAL (ETC) GUN EXPERIMENTAL DATA

GLORIA P. WREN
WILLIAM F. OBERLE

S DTIC
ELECTE
SEP 15 1992
A **D**

SEPTEMBER 1992

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

92 9 14 069

050750

92-25173



70pgs

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE Sept. 1992	3. REPORT TYPE AND DATES COVERED Final, May 1990 - Jan 1991
----------------------------------	-------------------------------------	---

4. TITLE AND SUBTITLE An Inverse Analysis of Electrothermal-Chemical (ETC) Gun Experimental Data	5. FUNDING NUMBERS DA311380 PR: 1F2Z9W9XDGS3
6. AUTHOR(S) Gloria P. Wren and William F. Oberle	

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
--	--

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066	10. SPONSORING / MONITORING AGENCY REPORT NUMBER BRL-TR-3391
---	--

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.	12b. DISTRIBUTION CODE
--	------------------------

13. ABSTRACT (Maximum 200 words)

An inverse analysis is presented as one method of assessing ballistic control exhibited in electrothermal-chemical (ETC) experimental gun firings. The analysis attempts to determine the decomposition or gas generation rate necessary to satisfy an energy balance equation as gleaned from available experimental data. The apparent functional relationship between the electrical energy input and working fluid mass consumed is examined. As applied in this report, the inverse analysis of ETC gun firing data is essentially an energy balance between projectile kinetic energy, gas kinetic energy, and gas internal energy. Lagrange assumptions are made for the pressure gradient and gas velocity. Thermochemistry is assumed to be variable depending on the plasma energy to working fluid mass ratio. A sample database consisting of 20-mm and 30-mm gun firings is examined.

14. SUBJECT TERMS interior ballistics; plasma; guns; electrical energy	15. NUMBER OF PAGES 81
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL
--	---	--	---

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
ACKNOWLEDGMENTS	vii
1. INTRODUCTION	1
2. MODEL DESCRIPTION	2
3. NUMERICAL APPROACH	6
4. VALIDATION	7
5. THERMOCHEMISTRY	11
6. RESULTS OF INVERSE ANALYSIS	14
7. SURFACE AREA RATIO	18
8. CONCLUSIONS	19
9. REFERENCES	23
APPENDIX A: SAMPLE INPUT	25
APPENDIX B: INVERSE SIMULATION OF 20-MM AND 30-MM FIRINGS OF TiH_2/H_2O	29
APPENDIX C: SOURCE CODE LISTING	41
DISTRIBUTION LIST	63

Accession For	
NTIS CRA&I	
DTIC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability Code	
Dist	Availability Specimen
A-1	

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	Schematic of ETC Gun	1
2a.	Comparison of IBHVG2 Results With the Inverse Analysis	8
2b.	Comparison of IBHVG3 Results With the Inverse Analysis	9
3.	Electrical/Plasma Energy for 20-mm Shot 249	10
4.	Recorded Pressure Histories for 20-mm Shot 249	10
5.	Comparison Between Chamber Pressure Gage History and Filtered Chamber Pressure Gage History for 20-mm Shot 249	12
6.	Projectile Position Derived From a Polynomial Least-Squares Fit to Barrel Gage Arrival Times for 20-mm Shot 249	12
7.	Projectile Position Derived From a Polynomial Least-Squares Fit to Barrel Gage Arrival Times for 20-mm Shot 249 After 133 μ s, Together With a Quadratic Fit From 73 μ s to 133 μ s	13
8.	Impetus of TiH_2/H_2O With Electrical Energy Added	14
9	Electrical Energy Input (kJ) as a Function of Time (ms) for 20-mm Gun Firings	16
10.	Electrical Energy Input (kJ) as a Function of Time (ms) for 30-mm Gun Firings	16
11.	Normalized Electrical Energy Input vs. Normalized Working Fluid Consumed for 20-mm Gun Firings	17
12.	Normalized Electrical Energy Input vs. Normalized Working Fluid Consumed for 30-mm Gun Firings	17
13.	Surface Area Ratio for 20-mm Shots 240, 249, and 259 Compared to Inhibited, Monolithic Grain	20

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

The authors would like to express their appreciation to Dr. Bob Greig of GT-Devices, a subsidiary of General Dynamics Land Systems, who supplied the experimental data along with needed documentation. Dr. Paul Gough's criticisms of this work are appreciated. Dr. Eli Freedman of Eli Freedman Associates and Dr. Kevin White of the U.S. Army Ballistic Research Laboratory (BRL), Aberdeen Proving Ground, MD, supported this work with thermochemical data and advice. The authors acknowledge the invaluable assistance of Ms. Sharon Richardson of BRL who handled data and performed the code runs. Finally, the authors wish to thank Mr. Fred Robbins and Dr. Terry Coffee, BRL, for reviewing the final manuscript.

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

The electrothermal-chemical (ETC) gun, generically shown in Figure 1, is a propulsion concept which utilizes a low mass, high energy plasma to initiate and, hopefully, control the combustion/vaporization of the working fluid (propellant) during the ballistic cycle. Controlling combustion (exothermic working fluid) or vaporization (endothermic working fluid) of the working fluid in the ETC gun is necessary in order to tailor the pressure-time profile in the gun. Theoretically, tailoring the pressure-time profile to obtain a "flatter" and extended pressure curve should result in enhanced performance (increased muzzle energy) and provide a "softer" launch environment to enhance projectile integrity, especially for "smart" projectiles. In addition, precise control of the pressure history should also allow for the required projectile velocity repeatability required of indirect fire support (artillery) applications.




Figure 1. Schematic of ETC Gun.

One method of assessing the control exerted by the plasma on the combustion/ vaporization process is through the use of an inverse analysis which computes the decomposition or gas generation rate of the working fluid given experimental measurements of pressure, projectile motion, and plasma energy histories as an input to the model. If the plasma is controlling the process, then the inverse analysis should show decomposition rates to be a "strong" function of the plasma input (plasma energy-time input).

To illustrate the method, an inverse analysis of 20-mm and 30-mm ETC firings using an exothermic working fluid is presented. The objective is to ascertain to what extent these experimental ETC firings indicate control of the working fluid combustion by the plasma energy input to the gun. The results of the inverse analysis for these data sets are viewed as qualitative since the experimental measurements are not precise; for example, the projectile position is not accurately known from the experimental data.

2. MODEL DESCRIPTION

The derivation is traditional (Hunt 1951). At any given time, let Q be the total energy available, U the internal energy of the gas, and W the work performed by the gas. Then

$$Q = U + W + Losses . \quad (1)$$

A number of estimates exist for calculating losses due to heat loss, recoil, projectile resistance, projectile rotational energy, shocked air ahead of the projectile and energy in compression of the working fluid. In small caliber guns, heat loss can be significant. However, in the current implementation for a qualitative comparison between a number of small caliber shots, losses are assumed to be similar in each firing. Thus, the "losses" term is taken to be zero.

The total available energy at the time in which a fraction $z(t)$ of a total charge mass C has been burnt in a closed vessel is

$$Q = Cz(t) \int_{T_{ref}}^{T_o} c_v(T) dT \quad (2)$$

where c_v is the specific heat at constant volume of the gases at any temperature T , T_o is the flame temperature and T_{ref} is a reference temperature. Since only changes of energy will be considered, the actual value for T_{ref} is not significant.

Since work is performed in the gun, the gas temperature T is less than the flame temperature T_o , and the internal energy is given by

$$U = Cz(t) \int_{T_{ref}}^T c_v(T) dT . \quad (3)$$

The work performed by the gas is the kinetic energy of the projectile and kinetic energy of the gas. The kinetic energy of the projectile at any time is

$$KE(\text{projectile}) = \frac{1}{2} m v_p^2(x, t) \quad (4)$$

where $v_p(x, t)$ is the projectile velocity and m is the projectile mass.

The kinetic energy of the gas, $KE(\text{gas})$, is determined in a similar manner. However, since both the velocity and mass of gas can vary along the length of the gun,

$$KE(\text{gas}) = \frac{1}{2} \int_0^{x_p(t)} \rho(x, t) A(x) v_g^2(x, t) dx \quad (5)$$

where x_p is the projectile base position at time t , $\rho(x, t)$, $v_g(x, t)$ and $A(x)$ are respectively the fluid density, fluid velocity, and cross sectional area of the gun at position x .

To integrate Equation 5, the Lagrange assumption that the gas velocity $v_g(x, t)$ is linear from the breech at position 0.0 to the projectile base at x_p , with constant spatial density $\rho(t)$, that is,

$$v_g(x, t) = \frac{x}{x_p} v_p(t) \quad \text{and} \quad \frac{\partial \rho(x, t)}{\partial x} = 0 \quad (6)$$

is utilized. Then, assuming a constant area A for the gun, Equation 5, upon substitution of Equation 6, becomes

$$KE(\text{gas}) = \int_0^{x_p(t)} \frac{1}{2} \rho(t) A \left(\frac{x}{x_p(t)} v_p(t) \right)^2 dx \quad (7)$$

$$= \frac{1}{2} \rho(t) A \frac{v_p^2(t)}{x_p^2(t)} \int_0^{x_p(t)} x^2 dx \quad (8)$$

or,

$$= \frac{1}{6} \rho(t) A x_p(t) v_p^2(t) \quad (9)$$

$$KE(\text{gas}) = \frac{1}{6} C v_p^2(t) \quad (10)$$

assuming that the total charge is accelerated and uniformly distributed. Substituting Equations 2, 3, 4, and 10 into Equation 1,

$$Cz(t) \int_{T_{ref}}^{T_o} c_v(T) dT = Cz(t) \int_{T_{ref}}^T c_v(T) dT + \frac{1}{2} m v_p^2(t) + \frac{1}{6} C v_p^2(t) \quad (11)$$

or,

$$Cz(t) \int_T^{T_o} c_v(T) dT = \frac{1}{2} m v_p^2(t) + \frac{1}{6} C v_p^2(t) \quad (12)$$

Assuming an average value of c_v in the temperature range, $T(t)$ to T_o yields

$$Cz(t) \bar{c}_v (T_o - T(t)) = \frac{1}{2} m v_p^2(t) + \frac{1}{6} C v_p^2(t) \quad (13)$$

If $v_p(t)$ can be obtained experimentally, then Equation 13 has two unknowns, z and T . A Nobel-Able covolume equation of state,

$$\bar{P}(t) \left(V_c + x_p(t) A - \frac{m_a}{\rho_a} - \frac{C(1-z(t))}{\rho_c(t)} - bCz(t) \right) = \frac{RT(t)}{MW} Cz(t) \quad (14)$$

provides a second condition on the system. In Equation 14, $\bar{P}(t)$ represents the space-mean pressure based on the Lagrange ballistic assumptions, V_c the original free chamber volume, $x_p(t)$ the projectile travel, A the cross-sectional area of the tube, m_a the mass of air in the chamber, ρ_a the density of air, $\rho_c(t)$ the working fluid or charge density which has been calculated from a compressible equation of state, b the covolume correction, R the universal gas constant, and MW the molecular weight of reaction products. The effect of air in the chamber, m_a/ρ_a , is included since ETC firings can have large initial ullage.

The equation of state for the unvaporized fluid is in the form (Gough 1989)

$$\rho_c(t) = \begin{cases} \rho_o \left(1 + \frac{(P(t) - P_o)}{K_1} \right) & \text{if } K_2 = 0 \\ \rho_o \left(1 + \frac{K_2}{K_1} (P(t) - P_o) \right)^{1/K_2} & \text{if } K_2 \neq 0 \end{cases} \quad (15)$$

where $P(t)$ is the breech pressure and ρ_o is the fluid density at the initial breech pressure P_o (ambient in these calculations) assuming that the bulk modulus, K_p , is at most a linear function of pressure,

$$K_p = K_1 + K_2 (P(t) - P_o) \quad (16)$$

Using the standard definition of impetus, $I = \frac{RT_o}{MW}$, Equation 14 is solved for T .

$$T(t) = \frac{\frac{T_o P(t)}{MW} \left[V_c + x_p(t) A - \frac{m_a}{\rho_a} - \frac{C(1-z(t))}{\rho_c(t)} - bCz(t) \right]}{I Cz(t)} \quad (17)$$

The average value of c_v is expressed as

$$\overline{c_v} = \frac{I}{T_o(\gamma-1)} \quad (18)$$

where γ is the ratio of specific heats.

Substituting Equations 17 and 18 into Equation 13 and solving for $z(t)$ at any time yields

$$z(t) = \frac{\frac{1}{2} m v_p^2(t) \left(1 + \frac{1}{3} \frac{C}{m}\right) + \frac{\overline{P}(t)}{(\gamma-1)} \left(V_c + x_p(t)A - \frac{m_a}{\rho_a} - \frac{C}{\rho_c(t)}\right)}{\frac{1}{(\gamma-1)} \left(CI + \overline{P}(t) \left(bC - \frac{C}{\rho_c(t)}\right)\right)} \quad (19)$$

Experimental data are utilized to solve Equation 19 directly for z by providing chamber pressure from which the space-mean pressure $\overline{P}(t)$ is calculated assuming a Lagrange gradient. Experimental projectile position, $x_p(t)$, is utilized not only to calculate the projectile velocity $v_p(t)$, but also to determine the gun volume at any time. The initial charge mass, C , the bore area, A , and the projectile mass, m , are determined from the experiment. Propellant density, $\rho_c(t)$, is calculated from Equation 15. It is noted that in the calculation, each timestep is independent of any other timestep. The specification of the thermochemical values (impetus I , ratio of specific heats γ , and covolume b) is discussed in detail below.

3. NUMERICAL APPROACH

As mentioned earlier, each time step is independent of any other time step. Thus, Equation 19 can be solved algebraically for $z(t)$. However, since impetus, I , ratio of specific heat, γ , and covolume, b , are functions of $z(t)$ (see Section 5), it is necessary to iterate several times. Basically, to compute $z_{n+1}(t)$ at time t_{n+1} , values for I , γ , and b at time t_n are used in Equation 19 to determine $z'_{n+1}(t)$. New values of I , γ and b are then determined based upon $z'_{n+1}(t)$ and used in Equation 19 to determine the next approximation, $z''_{n+1}(t)$ to $z_{n+1}(t)$. This process continues until successive approximations are within the derived tolerance.

4. VALIDATION

In order to validate the inverse analysis, a 120-mm gun firing was simulated with a standard lumped parameter interior ballistic code, IBHVG2 (Anderson 1987) developed by the U.S. Army Ballistic Research Laboratory (BRL). The resulting IBHVG2 breech pressure history and projectile position were used as input to the inverse code. A comparison of the IBHVG2 calculation and the inverse analysis (ETINV) for mass consumed is shown in Figure 2. As can be seen, the inverse analysis accurately reproduces the time history of propellant mass burnt. However, as discussed elsewhere (Gough 1990), inaccuracies in the experimental data can lead to variability in the amount of mass burnt as determined by an inverse analysis. Thus, as discussed above, the inverse analysis is best viewed as a qualitative picture of the combustion process.

The ETC experimental database examined in this report consists of six 20-mm shots using titanium hydride and water, and three 30-mm shots using titanium hydride and water. All firings were performed at GT-Devices (Greig 1989), a subsidiary of General Dynamics Land Systems. A summary of the major physical parameters for the shots analyzed is shown in Table 1.

Table 1. Summary of 21-mm and 30-mm Initial Conditions

Tube Diameter	Chamber Volume	Working Fluid	Projectile Mass	Working Fluid Mass	Projectile Travel	Maximum EE Input
21 mm	72.4 cm ³	50 % TiH ₂ & 50% H ₂ O	20 g	64.0 to 64.64 g	199 cm	~500 kJ
30 mm	206.0 cm ³	50% TiH ₂ & 50% H ₂ O	100 g	168.84 g	300 cm	~400 kJ

A number of experimental measurements is available for each shot. The experimental data is used to determine plasma energy delivered to the combustion chamber, chamber pressure, and projectile position as functions of time.

As an example, the electrical or plasma energy computed from the product of the experimental voltage and current for a 20-mm shot, Shot 249, is shown in Figure 3. Pressure histories for Shot 249 are shown in Figure 4. Gages are located in the combustion chamber, and in the barrel at 13 cm, 14 cm, 18 cm, 88 cm, and 168 cm of projectile travel. The initial position of the projectile is at tube origin.

Mass Burned Computed by IBHVG2




Figure 2a. Comparison of IBHVG2 Results With the Inverse Analysis.

Mass Burned Computed by Inverse Code

120mm. no losses




Figure 2b. Comparison of IBHVG2 Results With the Inverse Analysis.




Figure 3. Electrical/Plasma Energy for 20-mm Shot 249.




Figure 4. Recorded Pressure Histories for 20-mm Shot 249.

For the majority of firings analyzed, the chamber pressure data is smoothed since the pressure history is "noisy." To illustrate, consider the chamber pressure for Shot 249, Figure 4, which is particularly "noisy" for the first 47 μs . To perform the smoothing, a low-pass filter is applied to the data, and the pressure history resulting from an inverse Fast Fourier Transform (FFT) is used in the analysis, a technique commonly utilized in the liquid propellant gun community. A comparison between the original data set and the data set resulting from the inverse FFT is shown in Figure 5. The filtering process is seen to maintain the characteristics of the data while removing the high frequency noise.

Projectile position is derived from arrival times at the barrel gage locations. Using the time of arrival at the barrel gage location, together with the actual gage locations, an interpolating fourth-degree polynomial of position as a function of time can be obtained. Experimental muzzle velocity, as measured by laser-velocity trap data, correlates very well with velocity predicted by the least-square fit (Greig 1989). In addition, any available radar data are utilized to confirm projectile position. However, in general, the radar data are not of sufficient fidelity to utilize in the inverse model. The polynomial method of determining projectile travel distorts the initial estimate of projectile motion prior to the first pressure probe since it is an extrapolation, as shown in Figure 6 for Shot 249. The projectile begins motion at 73 μs , and the projectile travel is negative from 73 μs to 133 μs . To eliminate negative projectile travel in the analysis, a quadratic fit is applied over the time from 73 μs to 133 μs using zero travel at 73 μs and the calculated travel at 133 μs . The resulting estimated projectile travel history is shown in Figure 7 for Shot 249. However, this procedure calls into question results obtained for approximately the first 15% of the analysis as a function of time.

The accuracy of the inverse analysis is dependent on accurate experimental data for plasma energy delivered to the combustion chamber, chamber pressure history, and projectile travel. Thus, since much of the needed information from the titanium hydride and water firings is inferred, as opposed to directly measured, the analysis of these firings is useful only as a comparison between experiments with similar initial conditions (i.e., gun geometry, plasma energy, etc.). An accurate estimation of gas generation rate will require precise experimental data.

5. THERMOCHEMISTRY

The specification of the thermochemical properties of the working fluid must consider the input of the plasma. Therefore, a series of BLAKE (Freedman, private communication) runs are performed with




Figure 5. Comparison Between Chamber Pressure Gage History and Filtered Chamber Pressure Gage History for 20-mm Shot 249.




Figure 6. Projectile Position Derived From a Polynomial Least-Squares Fit to Barrel Gage Arrival Times for 20-mm Shot 249.




Figure 7. Projectile Position Derived From a Polynomial Least-Squares Fit to Barrel Gage Arrival Times for 20-mm Shot 249 After 133 μ s, Together With a Quadratic Fit From 73 μ s to 133 μ s.

varying amounts of plasma energy input (Bunte and Oberle 1989). In the BLAKE calculations, the plasma energy is assumed to mix uniformly with some amount of working fluid, and the ratio of electrical energy input to working fluid mass is referred to as the electrical energy density. Based on the electrical energy density, BLAKE then defines an impetus, ratio of specific heats, temperature and molecular weight for the mixture. In the inverse analysis, the plasma energy is assumed to mix only with the dissociated working fluid as determined iteratively from Equation 19. Since the BLAKE entries are not defined above approximately 6,000 K where ionization would occur, the impetus values are extended with a linear regression line to define electrical energy densities outside the table range.

Impetus for a mixture of 50% TiH₂ and 50% H₂O as a function of electrical energy density is shown in Figure 8 for the BLAKE calculations and is denoted by the square boxes. The linear regression line is shown in Figure 8 as well, and is given by

$$\text{Impetus} = 134.238 * (\text{EE density}) + 424.69.$$




Figure 8. Impetus of TiH_2/H_2O With Electrical Energy Added.

The variable thermochemistry values are shown in Table 2. As can be seen from an examination of Table 2, the values of gamma and the covolume for electrical energy densities producing gas temperatures above 5,000 K are held constant at the last BLAKE calculation at 9 kJ/g. Although not accurate, better thermochemical data does not exist at the present time.

6. RESULTS OF INVERSE ANALYSIS

The inverse analysis assesses ballistic control exhibited in the experiment by inferring the relationship between electrical energy added to the system by the plasma and the amount of working fluid consumed. The delivery of electrical energy to the system is first discussed for the experimental shots. Results of the inverse analysis are then shown for 20-mm and 30-mm gun data with working fluid titanium hydride and water.

Electrical energy input in kilojoules vs. time in milliseconds is shown in Figure 9 for the six 20-mm firings (Shots 240, 249, 250, 257, 258, and 259). The shape of the curves is quite similar with a variation in pulse length and total energy. The 30-mm experiments are firings in which initial conditions and the

Table 2. Thermochemistry of 50% TiH₂ and 50% H₂O

EE Density (KJ/g)	Temperature (K)	Impetus (J/g)	Gamma (-)	Covolume (cm ³ /g)
0	1,627	511	1.1685	0.655
1	1,950	612	1.1685	0.655
2	2,162	679	1.2722	0.655
3	2,630	826	1.2553	0.668
4	3,078	969	1.2443	0.675
5	3,502	1,106	1.2370	0.681
6	3,899	1,239	1.2325	0.690
7	4,265	1,368	1.2302	0.702
8	4,604	1,495	1.2294	0.717
9	4,917	1,622	1.2299	0.735
10	—	1,767	1.2299	0.735
20	—	3,109	1.2299	0.735
30	—	4,451	1.2299	0.735
40	—	5,794	1.2299	0.735
50	—	7,136	1.2299	0.735
60	—	8,478	1.2299	0.735
70	—	9,821	1.2299	0.735
80	—	11,163	1.2299	0.735
90	—	12,506	1.2299	0.735
100	—	13,848	1.2299	0.735

delivery of electrical energy are nearly the same. Thus, these shots (Shots 39, 40, and 43A) form a repeatability series for this gun configuration. As shown in Figure 10, approximately 350 kJ of electrical energy is delivered as a simple ramped input over approximately 1.4 ms.

To assess the dependence of working fluid consumed on plasma energy input, the results are presented as groups of normalized electrical energy input vs. normalized working fluid consumed. The normalized curve (Figures 11 and 12) is obtained by dividing electrical energy by the maximum electrical energy




Figure 9. Electrical Energy Input (kJ) as a Function of Time (ms) for 20-mm Gun Firings.




Figure 10. Electrical Energy Input (kJ) as a Function of Time (ms) for 30-mm Gun Firings.




Figure 11. Normalized Electrical Energy Input vs. Normalized Working Fluid Consumed for 20-mm Gun Firings.




Figure 12. Normalized Electrical Energy Input vs. Normalized Working Fluid Consumed for 30-mm Gun Firings.

input and the mass consumed by the maximum mass of working fluid in the experiment. The computed mass of working fluid consumed is shown in Appendix B for each shot, with the sample input/output in Appendix A.

The results for the 20-mm shots with titanium hydride and water as the working fluid are shown in Figure 11. From Figure 9 the electrical energy input is a simple ramp. Although the mass of working fluid consumed (Figure 11) does indicate some linearity as a function of electrical energy, the results provide no evidence that the plasma energy input drives the ballistic response for the entire ballistic cycle.

The 30-mm shots using titanium hydride and water as the working fluid are shown in Figure 12. These shots form a set of repeatability experiments. As shown in Figure 10, the approximately 350 kJ of electrical energy is deposited uniformly over approximately 1.2 ms in each experiment. As can be seen in Figure 12, the working fluid response is similar in all three experiments. As in the 20-mm experiments, although the plasma energy is applied uniformly, the rate of working fluid mass consumed appears to increase during the ballistic cycle. Although the mass fraction of working fluid consumed appears to occur similarly in the experiments, it is not evident that the plasma controls the ballistic process.

In both experimental data sets, an increase in the rate of working fluid consumed over time is observed. In order to identify the role of plasma energy as the driving mechanism in the gas generation rate, shots in which the initial plasma input is substantially varied should be fired and compared.

An analysis of several firings with water as the working fluid was attempted. It is possible to devise an extended thermochemical description of the mixture of water and electrical energy similar to Table 2. However, as demonstrated by Gough (1990) and verified in the analysis of experimental data, the dependence of pressure on the fraction of working fluid consumed is weak for endothermic fluids for all electrical energy densities. As opposed to exothermic fluids, the possibility of multiple roots and bifurcation in the inverse analysis makes water firings unsuitable for inverse analysis. Thus, these firings are not further discussed in this report.

7. SURFACE AREA RATIO

A second method to investigate control of the ballistic process is to ascertain the surface area of the reacting working fluid. If the process is not controlled, it would be expected that the total reacting surface

area would display large fluctuations. To determine an apparent surface area, the experimental breech pressure and working fluid mass consumed (as computed from the inverse analysis) are used to compute a surface area ratio (current surface area to initial surface area) under the assumption of a pressure dependent combustion law for the working fluid reaction. Although the results are qualitative, the ratio provides some insight into the behavior of the surface which is in contact with the hot gases. Surface area ratios in solid propellants are well behaved.

A pressure dependent burn rate of JA2 propellant ($r = 0.12 P^{0.95}$, r in cm/s) and an initial surface area equal to the cross-sectional area of the chamber are assumed. Then for each percent mass consumed, the ratio of the current to the initial surface area can be computed. The selection of the initial surface area as the cross-sectional area of the chamber is arbitrary. However, changing the value of the initial surface area preserves the shape of the surface area ratio curve but changes its magnitude. Thus, the surface area ratio curves should not be viewed in terms of absolute magnitude but only in terms of characteristic shape. The results are similarly affected by the choice of burn rate law. Figure 13 shows the surface area ratio for three 20-mm firings, Shots 240, 249, and 259, with titanium hydride and water as the working fluid. For the first 50% of the mass consumed the ratios show minor fluctuations except for the early portions of the graph where the data is questionable due to the inaccuracies in the early portion of projectile travel. Unfortunately, the surface area ratios fluctuate sharply after approximately 50% of the working fluid mass has been consumed, especially Shot 249. In the experiments, the plasma continues to enter the chamber until almost all of the working fluid has been consumed as seen in Figure 11. Thus, the working fluid surface area appears to be well behaved only initially.

For comparison, the geometry of an inhibited, monolithic grain with dimensions suggested by the initial working fluid configuration is theoretically burned under the same pressure-dependent conditions. The surface area ratio as a function of percent mass consumed is shown in Figure 13 and is seen to be progressive and well-behaved.

8. CONCLUSIONS

An inverse analysis has been presented as one method of assessing ballistic control exhibited in ETC experimental gun firings. The analysis attempts to determine the decomposition or gas generation rate necessary to satisfy an energy balance equation as gleaned from available experimental data. The quantitative values of working fluid mass consumed are dependent on accurate experimental breech




Figure 13. Surface Area Ratio for 20-mm Shots 240, 249 and 259 Compared to Inhibited, Monolithic Grain.

pressure measurements and projectile position as well as the assumption of the form of the pressure gradient.

The analysis was applied to 20-mm and 30-mm experimental firings (rear plasma injection) using titanium hydride and water as the working fluids. The results of the analysis are viewed as qualitative for these data sets and suggest:

- (1) For the firings analyzed, there is little evidence to indicate that the electrical energy input plays a dominant role in the amount of working fluid consumed.
- (2) A large fluctuation in surface area occurs for the titanium hydride and water system when approximately 50% of the mass has been consumed regardless of the presence or absence of plasma energy in the configuration analyzed.

- (3) Accurate measurement of projectile position through in-bore radar is needed to accurately establish the volume behind the projectile.
- (4) The potential coupling between plasma energy input and working fluid mass consumed is obscured by the lack of comparable data sets in which the plasma energy input history is significantly varied.
- (5) Additional work is needed in defining the thermochemistry of working fluid/electrical energy combinations.

INTENTIONALLY LEFT BLANK.

9. REFERENCES

- Anderson, R. D., and K. D. Fickie. "IBHVG2—A User's Guide." BRL-TR-2829, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1987.
- Bunte, S. W., and W. F. Oberle. "A Thermochemical Analysis of Proposed Working Fluids for Electrothermal Guns." BRL-TR-3000, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1989.
- Freedman, E. Private communication. Information on thermochemical properties of propellants. Eli Freedman Associates, Baltimore, MD.
- Gough, P. "Numerical Simulation of Electrothermal Gun Interior Ballistics." 27th JANNAF Combustion Meeting, Frances E. Warren Air Force Base, Cheyenne, WY, 5-9 November 1990.
- Greig, J. R. "An Analysis of Fifty Shots on the 20-mm Electrothermal Gun for Reproducibility and Energy Dependence." Interim Report GTD 89-8, GT-Devices, Inc., Contract No. DAAA15-86-C-0015, 23 June 1989.
- Hunt, F. Internal Ballistics. New York: Philosophical Library, Inc., 1951.
- White, K. Private communication. U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD.

INTENTIONALLY LEFT BLANK.

APPENDIX: A
SAMPLE INPUT

INTENTIONALLY LEFT BLANK.

Enter the file containing input file names.

Inverse Electrothermal Gun Code

Pressure-time file:250tvp.IN
 Proj motion-time file:250tvpp.IN
 Proj travel-time file.

Electrical energy-time file:250tvce.IN
 Initial data file:250init.IN
 Chamber volume (cm³)- 72.40000
 Tube diameter (cm)- 2.1 Area (cm²)- 3.46361
 Projectile position (cm)- 0.00000
 Projectile mass (kg)- 0.02
 Working fluid mass (g)- 64.64000
 Initial working fluid density (g/cm³)- 1.59000
 Tolerance required in mass consumed- 0.00100
 Time start (sec)-0.00000000
 Time increment (sec)-0.00005000
 Time end (sec)-0.00120000
 Initial guess for mass consumed (g)- 0.10000
 Initial value of beta, fraction of wf moving (-)- 1.00000
 Mass of air initially in chamber (g)- 0.03750
 Bulk modulus of WF at 1 atmosphere (MPa)-5000.00000
 Derivative of bulk modulus wrt pressure (-)- 8.00000

Thermochemical data file:tihextra.prn

TIME (ms)	CHAM PR (MPa)	BASE PR (MPa)	PROJ TRAV (cm)	PROJ VEL (cm/s)	EL EN DEN (MJ/kg)	CUM WF (g)
0.00	0.10	0.04005	0.0000	0.00	0.000	0.00000
0.05	2.89	1.15726	0.3916	7831.56	19259.860	0.00079
0.10	98.12	39.29342	0.7832	7831.56	2101.635	0.02080
0.15	200.20	80.17240	1.1747	7831.56	1811.112	0.04470
0.20	338.07	135.38190	1.5663	27364.79	1433.635	0.08227
0.25	413.63	165.64180	3.9112	55843.03	1198.416	0.12971
0.30	493.50	197.62530	7.1506	73255.77	1039.150	0.19483
TIME-	0.00035	NO CONVERGENCE				
0.40	573.84	229.79470	16.1227	105250.30	17.629	16.52764
0.45	577.92	231.42860	21.7618	119858.60	11.768	28.05256
0.50	588.95	235.84870	28.1085	133558.50	8.616	43.34926
0.55	559.01	223.85940	35.1177	146363.10	7.105	56.13565
0.60	473.38	189.56690	42.7448	158286.10	7.172	56.85619
0.65	403.04	161.39790	50.9463	169340.30	7.109	57.92583
0.70	355.40	142.31970	59.6788	179538.80	6.588	62.86549
0.75	306.18	122.61100	68.9001	188895.20	6.544	63.38555
0.80	263.75	105.61900	78.5683	197422.40	6.623	62.64100
0.85	235.21	94.18995	88.6424	205134.10	6.418	64.93068

All fluid consumed.

Solution continues to balance energy.


0.90	213.39	85.45189	99.0817	212043.00	6.418	66.28542
0.95	190.69	76.36062	109.8466	218163.30	6.418	66.49628
1.00	171.73	68.76966	120.8980	223505.80	6.417	66.69440
1.05	156.52	62.67997	132.1973	228086.30	6.417	67.08662
1.10	143.31	57.38857	143.7066	231917.30	6.417	67.33691
1.15	130.72	52.34921	155.3890	235012.50	6.416	67.08495
1.20	119.08	47.68684	167.2078	237381.90	6.416	66.46645

INTENTIONALLY LEFT BLANK.


APPENDIX B:
INVERSE SIMULATION OF 20-MM AND 30-MM FIRINGS OF T/H₂/H₂O

INTENTIONALLY LEFT BLANK.


Shot 240




Shot 249




Shot 250




Shot 257




Shot 258




Shot 259




Shot 39



Shot 40



Shot 43A



INTENTIONALLY LEFT BLANK.

APPENDIX C:
SOURCE CODE LISTING

INTENTIONALLY LEFT BLANK.

PROGRAM ETINVBC

```
C
C ADD COMPRESSION OF WORKING FLUID - JULY 1990
C
C CONSIDER BETA--AMT OF FLUID WHICH MOVES
C APRIL 1990
C INVERSE PROGRAM TO CALCULATE INTERACTION RATE
C OF WORKING FLUID AND PLASMA FROM ET DATA
C ASSUMING LAGRANGE PRESSURE GRADIENT
C
C TYPE ETINVBC (WAIT FOR QUESTION ABOUT INPUT FILE!!)
C
  IMPLICIT REAL (A - H, O - Z)
  PARAMETER (NPT = 150, NPTT = 50)
  COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INTIN
  COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
  1 TRTIM (1:NPT), TRAV (1:NPT),
  2 VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
  COMMON /OUT/ WFTIM (NPT), WFCUM (NPT)
  COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
  COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
  1 PROJI, PROJW, TOL, TIMINC,
  2 TIMEND, WAIR, BM, DERBM
  COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
  1 ELECEN, TEMP, RIMPET, GAMMA,
  2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
  3 Z, RHO, ENCOMP
  COMMON /OPTIONS/ IBETA, ICOM
  COMMON /THERMO/ ELDEN1 (1:NPTT), TEMP1 (1:NPTT), RIMP1 (1:NPTT),
  1 GAMMA1 (1:NPTT), COVOL1 (1:NPTT)
C
  CHARACTER*20 ETIN, PRESIN, TRAVIN, ELECIN, THERIN, INTIN
C
  WRITE (*, 6000)
  6000 FORMAT(10X, ' Enter the file containing input file names. ')
  READ (*, 5000) ETIN
  OPEN (15, FILE = ETIN)
  REWIND (15)
C
C LINE 1: PRESSURE
C LINE 2: PROJECTILE TRAVEL
C LINE 3: ELECTRICAL ENERGY INPUT
C LINE 4: THERMOCHEMICAL VALUES BASED ON ELECTRICAL ENERGY INPUT
C LINE 5: INITIAL DATA
C Each file contains descriptor on line 1, number of points on line 2,
C time vs parameter on other lines or thermochems.
  READ (15, 5000) PRESIN
  READ (15, 5000) TRAVIN
  READ (15, 5000) ELECIN
```

```

READ (15, 5000) THERIN
READ (15, 5000) INTIN
CALL OUTPUT (1)
CALL PRESS (1)
CALL TRAVEL (1)
CALL ELECTR (1)
CALL INITIAL
CALL THERM (1, IREAC)
CALL OUTPUT (2)
C
C INITIALIZE AT TIME=0.
C SET UP ARRAY FOR WF TO FIND DERIVATIVE
  TIME = 0.0
  WF2 = 0.
  WFTIM (1) = 0.0
  WFCUM (1) = 0.0
  IEND = 0
  NWF = 1
  CALL PRESS (2)
  CALL TRAVEL (2)
  CALL THERM (2, IREAC)
  CALL OUTPUT (3)
C
C TAKE FIRST TIME STEP
  TIME = TIME + TIMINC
C
C INITIAL GUESS FOR MASS OF FLUID CONSUMED IN INITIAL
C ITERATE TO MATCH THERMOCHEMS WITH MASS CONSUMED
  1000 CONTINUE
    CALL PRESS (2)
    CALL TRAVEL (2)
    CALL ELECTR (2)
    M = 0
C
C IF IREAC=0, NO REACTION (EL EN DENSITY NOT LARGE ENOUGH)
C IF IREAC=1, REACTION
  1010 CONTINUE
    CALL THERM (2, IREAC)
    IF (IREAC .EQ. 0) THEN
      CALL SPMEAN
      CALL OUTPUT (3)
      TIME = TIME + TIMINC
      GO TO 1000
    END IF
C
  CALL STATE
C
C M IS COUNTER--CONVERGE BEFORE 100 STEPS OR SKIP
  IF (M .GT. 100) THEN

```

```

        WRITE (*, 6010) TIME
6010  FORMAT(1X, ' TIME=', F10.5, ' NO CONVERGENCE')
        TIME = TIME + TIMINC
        GO TO 1000
    END IF
    IF ((ABS (WF1 - WF2)) .LE. TOL) THEN
C FILL ARRAY FOR WF TO FIND DERIVATIVE
        NWF = NWF + 1
        WFTIM (NWF) = TIME
        WFCUM (NWF) = WF2
        CALL OUTPUT (3)
        TIME = TIME + TIMINC
C
C END CONDITIONS
        IF (TIME .GT. TIMEND) GO TO 1020
        IF (WF2 .LE. 0.) GO TO 1020
C END IF ALL FLUID CONSUMED
        IF ((WF2 .GE. WFMASI) .AND. (IEND .EQ. 0)) THEN
            WRITE (*, *) ' All fluid consumed.'
            WRITE (*, *) ' Solution continues to balance energy.'
            IEND = 1
        END IF
C
C READY TO TAKE ANOTHER STEP
        WF1 = WF2
        GO TO 1000
    ELSE
        WF1 = WF2
        M = M + 1
        GO TO 1010
    END IF
C
5000 FORMAT (A20)
C
C POST PROCESSING--TAKE DERIVATIVES
1020 CONTINUE
        CALL OUTPUT (4)
        CLOSE (26, STATUS = 'KEEP')
        CLOSE (27, STATUS = 'KEEP')
        CLOSE (28, STATUS = 'KEEP')
        CLOSE (29, STATUS = 'KEEP')
        STOP
        END
C *****
C SUBROUTINE PRESS (IOPT)
C
    IMPLICIT REAL (A - H, O - Z)
    PARAMETER (NPT = 150, NPTT = 50)
    COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INTIN

```

```

COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1 TRTIM (1:NPT), TRAV (1:NPT),
2 VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1 ELECEN, TEMP, RIMPET, GAMMA,
2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3 Z, RHO, ENCOMP
C
CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INITIN, IDENT
C
C
C IOPT=1 READ FILE
C TIME IN MS, PRESSURE IN MPA
C CHANGE TIME TO SEC
C CHANGE PRESSURE FROM MPA TO CONSISTENT UNITS WITH CGS SYSTEM
C BY MULTIPLYING BY 1.0E7 CONVERSION CONSTANT
C
IF (IOPT .EQ. 2) GO TO 1000
OPEN (21, FILE = PRESIN, STATUS = 'OLD', IOSTAT = IOS, ERR = 1010)
REWIND (21)
1010 CONTINUE
IF (IOS .NE. 0) WRITE (*, 6000) IOS
6000 FORMAT(' ERROR OPENING PRESSURE FILE:',I5)
READ (21, 5000) IDENT
WRITE (*, 6010) PRESIN
C WRITE(*,620) IDENT
READ (21, *) NPR
DO 1020 I = 1, NPR
READ (21, *) PRTIM (I), PRES (I)
C CHANGE TO SEC AND CGS SYSTEM
PRTIM (I) = PRTIM (I)*1.0E-3
PRES (I) = PRES (I)*1.0E7
1020 CONTINUE
GO TO 1030
C
C IOPT=2 INTERPOLATE
1000 CONTINUE
TIMTOL = ABS (TIME - .1E-10)
IF ((TIME .EQ. 0.0) .or. (TIMTOL .EQ. 0.)) THEN
PRESCH = PRES (1)
CALL SPMEAN
END IF
DO 1040 I = 2, NPR
IF (TIME .EQ. PRTIM (I)) PRESCH = PRES (I)
IF (TIME .GT. PRTIM (I - 1)) THEN
PRESCH = PRES (I - 1) + (PRES (I) - PRES (I - 1))*
1 ((TIME - PRTIM (I - 1))/(PRTIM (I) - PRTIM (I - 1)))
END IF

```



```

1040 CONTINUE
C
5000 FORMAT (A80)
6010 FORMAT(' Pressure-time file:',A20)
8000 FORMAT(' Pressure-time ident:',A20,/)
1030 CONTINUE
      RETURN
      END
C *****
      SUBROUTINE TRAVEL (IOPT)
C
C DETERMINE PROJECTILE TRAVEL
C CALL SUBROUTINE TO DETERMINE PROJECTILE VELOCITY
      IMPLICIT REAL (A - H, O - Z)
      PARAMETER (NPT = 150, NPTT = 50)
      COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INITIN
      COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1 TRTIM (1:NPT), TRAV (1:NPT),
2 VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
      COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
      COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1 ELECEN, TEMP, RIMPET, GAMMA,
2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3 Z, RHO, ENCOMP
      COMMON /OPTIONS/ IBETA, ICOM
C
      CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INITIN, IDENT
C
      IF ((IOPT .NE. 1) .AND. (IOPT .NE. 2))
1 WRITE (*, *) ' Error in Subroutine Travel.'
C
C IOPT=1 READ FILE
C IF 2ND LINE IS 1: TIME IN MS, TRAVEL IN CM
C IF 2ND LINE IS 2: TIME IN MS, TRAVEL IS IN CM, VELOCITY IN CM/S
C CHANGE TIME TO SEC
C TRAVEL MUST BE IN CM
C VELOCITY IN CM/S
C
      IF (IOPT .EQ. 2) GO TO 1000
      OPEN (21, FILE = TRAVIN, STATUS = 'OLD', IOSTAT = IOS, ERR = 1010)
      REWIND (21)
1010 CONTINUE
      IF (IOS .NE. 0) WRITE (*, 6000) IOS
6000 FORMAT(' ERROR OPENING TRAVEL FILE:',I5)
      READ (21, 5000) IDENT
      WRITE (*, 6010) TRAVIN
C      WRITE(*,620) IDENT
C ITRVEL=1 FOR TIME, TRAVEL PAIRS
C ITRVEL=2 FOR TIME, TRAVEL, VELOCITY PAIRS

```

```

READ (21, *) ITRVEL
IF (ITRVEL .EQ. 1) WRITE (*, 6020)
IF (ITRVEL .EQ. 2) WRITE (*, 6030)
IF ((ITRVEL .NE. 1) .AND. (ITRVEL .NE. 2)) THEN
  WRITE (*, 6040)
  STOP
END IF
READ (21, *) NTR
DO 1020 I = 1, NTR
C
C READ TIME-TRAVEL IF ITRVEL=1
C CHANGE TIME TO SEC
C **IBHVG2
C CHANGE TRAVEL TO CM (GIVEN IN .1 MM), VEL TO CM/SEC
C   IF (ITRVEL .EQ. 1) THEN
C     READ(21,*) TRTIM(I),TRAV(I)
C     TRTIM(I)=TRTIM(I)*1.0E-3
C     TRAV(I)=TRAV(I)*0.01
C   ENDIF
C
C READ TIME-TRAVEL-VELOCITY IF ITRVEL=2
C   IF (ITRVEL .EQ. 2) THEN
C     READ(21,*) TRTIM(I),TRAV(I),VEL(I)
C     TRTIM(I)=TRTIM(I)*1.0E-3
C     TRAV(I)=TRAV(I)*0.01
C     VEL(I)=VEL(I)*0.1
C   ENDIF
C***
C TIME IN MS, TRAVEL GIVEN IN CM
C   IF (ITRVEL .EQ. 1) THEN
C     READ (21, *) TRTIM (I), TRAV (I)
C     TRTIM (I) = TRTIM (I)*1.0E-3
C   END IF
C
1020 CONTINUE
GO TO 1030
C
C IOPT=2 INTERPOLATE
1000 CONTINUE
IF (TIME .EQ. 0.) THEN
  TRAVPR = TRAV (I)
  VELP = 0.0
END IF
C
C ITRVEL=1 HAVE JUST TIME-TRAVEL
IF (ITRVEL .EQ. 1) THEN
  DO 1040 I = 2, NTR
    IF (TIME .EQ. TRTIM (I)) THEN
      TRAVPR = TRAV (I)

```

```

        CALL VELPR (I)
        GO TO 1030
    END IF
    IF (TIME .GT. TRTIM (I - 1)) THEN
        TRAVPR = TRAV (I - 1) + (TRAV (I) - TRAV (I - 1))*
1         ((TIME - TRTIM (I - 1))/(TRTIM (I) - TRTIM (I - 1)))
        CALL VELPR (I)
    END IF
1040 CONTINUE
    END IF
C
C ITRVEL=2 HAVE TIME-TRAVEL-VELOCITY
    IF (ITRVEL .EQ. 2) THEN
        DO 1050 I = 2, NTR
            IF (TIME .EQ. TRTIM (I)) THEN
                TRAVPR = TRAV (I)
                VELP = VEL (I)
                GO TO 1030
            END IF
            IF (TIME .GT. TRTIM (I - 1)) THEN
                TRAVPR = TRAV (I - 1) + (TRAV (I) - TRAV (I - 1))*
1                 ((TIME - TRTIM (I - 1))/(TRTIM (I) - TRTIM (I - 1)))
                VELP = VEL (I - 1) + (VEL (I) - VEL (I - 1))*
1                 ((TIME - TRTIM (I - 1))/(TRTIM (I) - TRTIM (I - 1)))
            END IF
1050 CONTINUE
        END IF
C
5000 FORMAT (A80)
6010 FORMAT(' Proj motion-time file:',A20)
8000 FORMAT(' Proj motion-time ident:',A20,/)
6020 FORMAT(' Proj travel-time file.',/)
6030 FORMAT(' Proj velocity-time file.',/)
6040 FORMAT(' Error--unknown type file.',/)
1030 CONTINUE
    RETURN
    END
C *****
    SUBROUTINE ELECTR (IOPT)
C
    IMPLICIT REAL (A - H, O - Z)
    PARAMETER (NPT = 150, NPTT = 50)
    COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INTIN
    COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1   TRTIM (1:NPT), TRAV (1:NPT),
2   VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
    COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
    COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1   ELECEN, TEMP, RIMPET, GAMMA,

```

```

2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3 Z, RHO, ENCOMP
COMMON /OPTIONS/ IBETA, ICOM
C
CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INITIN, IDENT
C
IF ((IOPT .NE. 1) .AND. (IOPT .NE. 2))
1 WRITE (*, *) ' Error in Subroutine Electr.'
C
C IOPT=1 READ FILE
C ELECTRICAL ENERGY IS CUMULATIVE
C TIME IN MS, ELECTRICAL ENERGY IN kJ
C CHANGE TIME TO SEC
C
IF (IOPT .EQ. 2) GO TO 1000
OPEN (21, FILE = ELECIN, STATUS = 'OLD', IOSTAT = IOS, ERR = 1010)
REWIND (21)
1010 CONTINUE
IF (IOS .NE. 0) WRITE (*, 6000) IOS
6000 FORMAT(' ERROR OPENING ELECTRICAL ENERGY FILE:',I5)
READ (21, 5000) IDENT
WRITE (*, 6010) ELECIN
C WRITE(*,620) IDENT
READ (21, *) NEL
DO 1020 I = 1, NEL
READ (21, *) ELTIM (I), ELEC (I)
ELTIM (I) = ELTIM (I)*1.0E-3
1020 CONTINUE
GO TO 1030
C
C IOPT=2 INTERPOLATE
1000 CONTINUE
IF (TIME .EQ. 0.) ELECEN = ELEC (1)
DO 1040 I = 2, NEL
IF (TIME .EQ. ELTIM (I)) ELECEN = ELEC (I)
IF (TIME .GT. ELTIM (I - 1)) THEN
ELECEN = ELEC (I - 1) + (ELEC (I) - ELEC (I - 1))*
1 ((TIME - ELTIM (I - 1))/(ELTIM (I) - ELTIM (I - 1)))
END IF
1040 CONTINUE
C
5000 FORMAT (A80)
6010 FORMAT(' Electrical energy-time file:',A20)
8000 FORMAT(' Electrical energy-time ident:',A20,/)
1030 CONTINUE
RETURN
END
C *****
SUBROUTINE INITIAL

```

```

C
  IMPLICIT REAL (A - H, O - Z)
  PARAMETER (NPT = 150, NPTT = 50)
  COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INTIN
  COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
1  PROJ, PROJW, TOL, TIMINC,
2  TIMEND, WAIR, BM, DERBM
  COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1  ELECEN, TEMP, RIMPET, GAMMA,
2  COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3  Z, RHO, ENCOMP
  COMMON /OPTIONS/ IBETA, ICOM
C
  CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INTIN, IDENT
C
  OPEN (21, FILE = INTIN, STATUS = 'OLD', IOSTAT = IOS, ERR = 1000)
  REWIND (21)
1000 CONTINUE
  IF (IOS .NE. 0) WRITE (*, 6000) IOS
6000 FORMAT(' ERROR OPENING INITIAL DATA FILE:',I5)
C
C CHAMBER VOLUME IN CM^3
C INITIAL PROJECTILE POSITION IN CM WITH 0.0 AT ORIGIN OF TUBE
C TUBE DIAMETER IN CM--AREA IN CM^2
C PROJECTILE MASS IN KG
C INITIAL MASS OF WORKING FLUID IN GRAMS
C DENSITY OF WORKING FLUID IN G/CM^3
C TIME INCREMENT IN SEC
  READ (21, 5000) IDENT
  WRITE (*, 6010) INTIN
C
  WRITE(*,620) IDENT
  READ (21, *) CHVOL
  WRITE (*, 6020) CHVOL
C TUBE DIAMETER
  READ (21, *) DIAM
  AREA = 3.141592654*(DIAM/2.)*(DIAM/2.)
  WRITE (*, 6030) DIAM, AREA
C PROJECTILE INITIAL POSITION AND MASS (CHANGE KG TO G)
  READ (21, *) PROJ
  IF (PROJ .NE. 0.0) WRITE (*, *)
1  ' Change needed--proj not zeroed.'
  READ (21, *) PROJW
  WRITE (*, 6040) PROJ, PROJW
  PROJW = PROJW*1000.
C WORKING FLUID INITIAL MASS
  READ (21, *) WFMASI
  WRITE (*, 6050) WFMASI
  READ (21, *) RHOI
  WRITE (*, 6060) RHOI

```

```

RHO = RHOI
C TOLERANCE IN ITERATION
  READ (21, *) TOL
  WRITE (*, 6070) TOL
C TIME IN SEC
  READ (21, *) TIME
  READ (21, *) TIMINC
  READ (21, *) TIMEND
  WRITE (*, 6080) TIME, TIMINC, TIMEND
C INITIAL GUESS FOR MASS OF WORKING FLUID CONSUMED
  READ (21, *) WF1
  WRITE (*, 6090) WF1
C READ INITIAL VALUE OF BETA
C OPTIONS FOR BETA:
C   BETA IS INITIAL VALUE OF WORKING FLUID MOVING--
C   LAGRANGE ASSUMPTION IS BETA=1, I.E. ALL FLUID MOVES
C   IF BETA=0., FLUID IS AT REST
C   CHANGE FRACTION OF BETA MOVING IF IBETA=1
C   IF IBETA=0, LET BETA=CONSTANT (INITIAL VALUE)
C   IF IBETA=1, LET BETA=Z (FRACTION OF WF REACTED)
  READ (21, *) BETA, IBETA
  WRITE (*, 6100) BETA
  IF (IBETA .EQ. 1) THEN
    WRITE (*, 6110) IBETA
    Z = 0.
  END IF
C MASS OF AIR INITIALLY IN CHAMBER
  READ (21, *) WAIR
  WRITE (*, 6120) WAIR
C
C OPTION - COMPRESSION OF WORKING FLUID
C IF ICOM=0, DO NOT CONSIDER COMPRESSION
C IF ICOM=1, CONSIDER COMPRESSION
  READ (21, *) ICOM
  IF ((ICOM .NE. 0) .AND. (ICOM .NE. 1)) WRITE (*, *) 'Error--ICOM'
C BM=BULK MODULUS OF FLUID AT ONE ATMOSPHERE (MPa)
C DERBM=DERIVATIVE OF BULK MODULUS WITH RESPECT TO PRESSURE
  IF (ICOM .EQ. 1) THEN
    READ (21, *) BM, DERBM
    WRITE (*, 6130) BM, DERBM
C CHANGE TO CGS
  BM = BM*1.0E7
  END IF
C
5000 FORMAT (A80)
6010 FORMAT(' Initial data file:',A20)
8000 FORMAT(' Initial data ident:',A20)
6020 FORMAT(' Chamber volume (cm^3)=',F15.5)
6030 FORMAT(' Tube diameter (cm)=',F6.1,2x,' Area (cm^2)=',F12.5)

```

```

6040 FORMAT(' Projectile position (cm)=' ,F10.5,
1      2X,' Projectile mass (kg)=' ,F10.2)
6050 FORMAT(' Working fluid mass (g)='F10.5)
6060 FORMAT(' Initial working fluid density (g/cm^3)=' ,F10.5)
6070 FORMAT(' Tolerance required in mass consumed=' ,F10.5)
6080 FORMAT(' Time start (sec)=' ,F10.8,' Time increment (sec)=' ,
1      F10.8,' Time end (sec)=' ,F10.8)
6090 FORMAT(' Initial guess for mass consumed (g)=' ,F10.5)
6100 FORMAT(' Initial value of beta, fraction of wf moving (-)=' ,F10.5)
6110 FORMAT(' Option: ibeta=' ,I5,'
1' If ibeta=0 fraction moving is constant' ,/
2' If ibeta=1, fraction moving=fraction decomposed')
6120 FORMAT(' Mass of air initially in chamber (g)=' ,F10.5)
6130 FORMAT(' Bulk modulus of WF at one atmosphere (MPa)=' ,F10.5,'
1' Derivative of bulk modulus wrt pressure (-)=' ,F10.5,/)
C
CLOSE (21)
RETURN
END
C *****
SUBROUTINE THERM (IOPT, IREAC)
C
IMPLICIT REAL (A - H, O - Z)
PARAMETER (NPT = 150, NPTT = 50)
COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INTIN
COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
1 PROJ, PROJW, TOL, TIMINC,
2 TIMEND, WAIR, BM, DERBM
COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1 ELECEN, TEMP, RIMPET, GAMMA,
2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3 Z, RHO, ENCOMP
COMMON /OPTIONS/ IBETA, ICOM
COMMON /THERMO/ ELDEN1 (1:NPTT), TEMP1 (1:NPTT), RIMP1 (1:NPTT),
1 GAMMA1 (1:NPTT), COVOL1 (1:NPTT)
C
CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INTIN, IDENT
C
IF ((IOPT .NE. 1) .AND. (IOPT .NE. 2))
1 WRITE (*, *) ' Error in Subroutine Electr.'
C
C IOPT=1 READ FILE
IF (IOPT .EQ. 2) GO TO 1000
C BASED ON AMOUNT OF ELECTRICAL ENERGY INPUT
OPEN (21, FILE = THERIN, STATUS = 'OLD', IOSTAT = IOS, ERR = 1010)
REWIND (21)
1010 CONTINUE
IF (IOS .NE. 0) WRITE (*, 6000) IOS

```

```

6000 FORMAT(' ERROR OPENING THERMOCHEM DATA FILE:',I5)
C
C ELECTRICAL ENERGY DENSITY (Elec en/mass fluid in chamber) IN kJ/G
C TEMPERATURE IN K
C IMPETUS IN J/G
C GAMMA, RATIO OF SPECIFIC HEAT, UNITLESS
C COVOLUME IN CM^3/G
C CONVERT JOULES TO CGS: 1 JOULE=1.0E7 G-CM^2/S^2
  READ (21, 5000) IDENT
  WRITE (*, 6010) THERIN
C   WRITE(*,620) IDENT
  READ (21, *) NTH
  DO 1020 I = 1, NTH
    READ (21, *) ELDEN1 (I), TEMP1 (I), RIMP1 (I),
      1   GAMMA1 (I), COVOL1 (I)
C ELECTRICAL ENERGY DENSITY IN kJ/G
  RIMP1 (I) = RIMP1 (I)*1.0E+7
  1020 CONTINUE
  GO TO 1030
C
  1000 CONTINUE
C ELECTRICAL ENERGY DENSITY=CUMULATIVE ELEC ENERGY/CUMULATIVE WF REACTED
  IF (WF1 .LT. 0.0) THEN
    WRITE (*, 6020)
  END IF
C ASSUME FIRST LINE OF TABLE IS 0.
  IF ((WF1 .LE. 0.) .OR. (TIME .EQ. 0.)) THEN
    TEMP = TEMP1 (1)
    RIMPET = RIMP1 (1)
    GAMMA = GAMMA1 (1)
    COVOL = COVOL1 (1)
    GO TO 1030
  END IF
C
  IF (WF1 .GT. 0.) ELDEN = ELECEN/WF1
C
C IF WF CONSUMED, FIX THERMOCHEMS AT FINAL VALUE
  IF (WF1 .GT. WFMASI) ELDEN = ELECEN/WFMASI
C
C IF EL EN DENSITY NOT LARGE ENOUGH FOR REACTION,
C COMMUNICATE TO MAIN WITH IREAC=0 AND SKIP THIS STEP
  IF (ELDEN .LT. ELDEN1 (1)) THEN
    IREAC = 0
    GO TO 1030
  END IF
C
  DO 1040 I = 2, NTH
    IF (ELDEN .EQ. ELDEN1 (I)) THEN
      TEMP = TEMP1 (I)

```



```

RIMPET = RIMP1 (I)
GAMMA = GAMMA1 (I)
COVOL = COVOL1 (I)
END IF
IF (ELDEN .GT. ELDEN1 (I - 1)) THEN
  TEMP = TEMP1 (I - 1) + (TEMP1 (I) - TEMP1 (I - 1))*
1  ((ELDEN - ELDEN1 (I - 1))/(ELDEN1 (I) - ELDEN1 (I - 1)))
  RIMPET = RIMP1 (I - 1) + (RIMP1 (I) - RIMP1 (I - 1))*
1  ((ELDEN - ELDEN1 (I - 1))/(ELDEN1 (I) - ELDEN1 (I - 1)))
  GAMMA = GAMMA1 (I - 1) + (GAMMA1 (I) - GAMMA1 (I - 1))*
1  ((ELDEN - ELDEN1 (I - 1))/(ELDEN1 (I) - ELDEN1 (I - 1)))
  COVOL = COVOL1 (I - 1) + (COVOL1 (I) - COVOL1 (I - 1))*
1  ((ELDEN - ELDEN1 (I - 1))/(ELDEN1 (I) - ELDEN1 (I - 1)))
  END IF
  IREAC = 1
1040 CONTINUE
C
C IF FALL OUTSIDE ARRAY
  IF (ELDEN .GT. ELDEN1 (NTH)) THEN
    TEMP = TEMP1 (NTH)
    RIMPET = RIMP1 (NTH)
    GAMMA = GAMMA1 (NTH)
    COVOL = COVOL1 (NTH)
    WRITE (26, *) ' OUTSIDE THERM ARRAY'
  END IF
C
5000 FORMAT (A80)
6010 FORMAT(' Thermochemical data file:',A20)
8000 FORMAT(' Thermochemical data ident:',A20,f)
6020 FORMAT(' Error in Subroutine Electr--El En Density negative.')
```

C

```

1030 CONTINUE
  RETURN
  END
C *****
  SUBROUTINE STATE
C
  IMPLICIT REAL (A - H, O - Z)
  COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
1  PROJI, PROJW, TOL, TIMINC,
2  TIMEND, WAIR, BM, DERBM
  COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1  ELECEN, TEMP, RIMPET, GAMMA,
2  COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3  Z, RHO, ENCOMP
  COMMON /OPTIONS/ IBETA, ICOM
C
C DETERMINE SPACE-MEAN PRESSURE
  CALL SPMEAN
```

```

C
C IF ICOM=0, DO NOT CONSIDER COMPRESSION OF WF
C IF ICOM=1, CONSIDER COMPRESSION OF WF
C ENCOMP IS ENERGY PER UNIT MASS STORED BY COMPRESSED FLUID
C --NEED TO MULTIPLY BY AMT OF FLUID UNVAPORIZED
C IF (ICOM .EQ. 0) THEN
C   RHO = RHOI
C   ENCOMP = 0.0
C END IF
C IF (ICOM .EQ. 1) CALL COMPRES
C
C CUMULATIVE FLUID CONSUMED FROM ENERGY EQN, P 105, BK 9
C GAM1 = GAMMA - 1.
C DIV = RIMPET/GAM1 + SPMPR*(COVOL/GAM1 - 1./(RHO*GAM1))
C
C TOP = (CHVOL - WFMASI/RHO + TRAVPR*AREA)*(SPMPR/GAM1)
C 1 + VELP*VELP*((1./6.)*CM*PROJW + .5*PROJW)
C 2 + (1. - Z)*WFMASI*ENCOMP
C
C Z = (1./WFMASI)*(TOP/DIV)
C WF2 = Z*WFMASI
C
C RETURN
C END
C *****
C SUBROUTINE SPMEAN
C
C IMPLICIT REAL (A - H, O - Z)
C COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
C 1 PROJ, PROJW, TOL, TIMINC,
C 2 TIMEND, WAIR, BM, DERBM
C COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
C 1 ELECEN, TEMP, RIMPET, GAMMA,
C 2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
C 3 Z, RHO, ENCOMP
C COMMON /OPTIONS/ IBETA, ICOM
C
C SPACE MEAN PRESSURE EQUALS CHAMBER PRESSURE (IF EXPERIMENTAL)
C SPMPR=PRESCH
C
C SPACE-MEAN PRESSURE FROM LAGRANGE GRADIENT
C ASSUME PRESCH IS A PRESSURE MEASUREMENT AT THE BREECH
C INCREASE PROJECTILE MASS BY 5% TO ACCOUNT FOR FRICTION
C CHARGE TO MASS RATIO, CM, IS INITIAL MASS OF WORKING FLUID
C DIVIDED BY MASS OF PROJECTILE
C projw=1.05*PROJW
C For test case, no friction
C ALPHA = WF2/WFMASI
C

```

```

C CONSIDER BETA=FRACTION OF FLUID WHICH MOVES
C IF BETA=0., ALL THE FLUID IS AT REST
C IF BETA=1., ALL THE WF MOVES (LAGRANGE ASSUMP)
  IF (IBETA .EQ. 1) BETA = Z
  CM = (WFMASI*(ALPHA + BETA*(1. - ALPHA)) + WAIR)/PROJW
  IF (CM .LE. 0.0) WRITE (*, *) ' Error in Spmean--C/M <= 0.'
  SPMPR = ((1. + 1/3.*CM)/(1. + 1/2.*CM))*PRESCH
  BASEPR = (1/(1. + 1/3.*CM))*SPMPR
C
  RETURN
  END
C *****
  SUBROUTINE COMPRES
C
C DETERMINE DENSITY OF COMPRESSED WORKING FLUID
C DETERMINE ENERGY OF COMPRESSION
C
  IMPLICIT REAL (A - H, O - Z)
  PARAMETER (NPT = 150, NPTT = 50)
  COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
  1 PROJ, PROJW, TOL, TIMINC,
  2 TIMEND, WAIR, BM, DERBM
  COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
  1 ELECEN, TEMP, RIMPET, GAMMA,
  2 COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
  3 Z, RHO, ENCOMP
  COMMON /OPTIONS/ IBETA, ICOM
  COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
  1 TRTIM (1:NPT), TRAV (1:NPT),
  2 VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
C
C LET BULK MODULUS BE AT MOST A LINEAR FCN OF PRESSURE
  IF (BM .LE. 0.0) WRITE (*, *) 'ERROR--BM<=0.0'
  IF (DERBM .EQ. 0.0) THEN
    RHO = RHOI*(1. + (PRESCH - PRES (1))/BM)
  ELSE
    RHO = RHOI*(1. + (DERBM/BM)*(PRESCH - PRES (1))**(1./DERBM))
  END IF
C
C ENERGY PER UNIT MASS STORED BY COMPRESSED FLUID
  IF ((DERBM .EQ. 0.0) .OR. (DERBM .EQ. 1.0)) THEN
    ENCOMP = - 1.*(PRESCH - PRES (1))/RHO + (BM/RHOI)*
  1 LOG (1. + (PRESCH - PRES (1))/BM)
  ELSE
    ENCOMP = - 1.*(PRESCH - PRES (1))/RHO + (BM +
  1 DERBM*(PRESCH - PRES (1)))
  2 /((DERBM - 1.)*RHO) - BM/((DERBM - 1.)*RHOI)
  END IF
C

```

```

RETURN
END
C *****
  SUBROUTINE VELPR (I)
C
C DETERMINE PROJECTILE VELOCITY
C
  IMPLICIT REAL (A - H, O - Z)
  PARAMETER (NPT = 150, NPTT = 50)
  COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1  TRTIM (1:NPT), TRAV (1:NPT),
2  VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
  COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
  COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
1  PROJI, PROJW, TOL, TIMINC,
2  TIMEND, WAIR, BM, DERBM
  COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1  ELECEN, TEMP, RIMPET, GAMMA,
2  COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3  Z, RHO, ENCOMP
  COMMON /OPTIONS/ IBETA, ICOM
C
C CENTERED DIFFERENCE
  IF (I .EQ. NTR) THEN
    VELP = (TRAV (I) - TRAV (I - 2))/(2.*
1  (TRTIM (I) - TRTIM (I - 1)))
  ELSE
    VELP = (TRAV (I + 1) - TRAV (I - 1))/(2.*
1  (TRTIM (I) - TRTIM (I - 1)))
  END IF
C
  RETURN
  END
C *****
  SUBROUTINE DER (TIME, IOPT, AMT, AMTDER)
C
C FINDS DERIVATIVES: USED FOR dE/dt and dWF/dt
C ASSUMES CONSTANT STEP SIZE FOR TIME
C
  IMPLICIT REAL (A - H, O - Z)
  PARAMETER (NPT = 150, NPTT = 50)
  COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1  TRTIM (1:NPT), TRAV (1:NPT),
2  VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
  COMMON /OUT/ WFTIM (NPT), WFCUM (NPT)
  COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
C
C IF IOPT=1, FIND DER OF ENERGY
C IF IOPT=2, FIND DER OF WF

```

```

IF (IOPT .EQ. 1) GO TO 1000
IF (IOPT .EQ. 2) GO TO 1010
C
IF ((ABS (TIME - 1.E-10)) .EQ. 0.0) THEN
  AMT = 0.0
  AMTDER = 0.0
  GO TO 1020
END IF
C
C IOPT=1, DERIVATIVE OF ELEC EN
1000 CONTINUE
DO 1030 I = 2, NEL
  IF (TIME .EQ. ELTIM (I)) THEN
    AMT = ELEC (I)
    IMARK = I
    GO TO 1040
  END IF
  IF (TIME .GT. ELTIM (I - 1)) THEN
    AMT = ELEC (I - 1) + (ELEC (I) - ELEC (I - 1))*
1    ((TIME - ELTIM (I - 1))/(ELTIM (I) - ELTIM (I - 1)))
    IMARK = I
  END IF
1030 CONTINUE
C IF GREATER THAN LAST POINT, USE LAST POINT
C CENTERED DIFFERENCE
1040 CONTINUE
  IF (IMARK .EQ. NEL) THEN
    AMT = ELEC (NEL)
    AMTDER = (ELEC (IMARK) - ELEC (IMARK - 2))/(2.*(ELTIM (IMARK)
1    - ELTIM (IMARK - 1)))
  ELSE
    AMTDER = (ELEC (IMARK + 1) - ELEC (IMARK -
1    1))/(2.*(ELTIM (IMARK)
2    - ELTIM (IMARK - 1)))
  END IF
C
GO TO 1020
C
C IOPT=2 DERIVATIVE OF WF
1010 CONTINUE
C
DO 1050 I = 2, NWF
  IF (TIME .EQ. WFTIM (I)) THEN
    AMT = WFCUM (I)
    IMARK = I
    GO TO 1060
  END IF
  IF (TIME .GT. WFTIM (I - 1)) THEN
    AMT = WFCUM (I - 1) + (WFCUM (I) - WFCUM (I - 1))*

```

```

1      ((TIME - WFTIM (I - 1))/(WFTIM (I) - WFTIM (I - 1)))
      IMARK = I
      END IF
1050 CONTINUE
C IF GREATER THAN LAST POINT, USE LAST POINT
C CENTERED DIFFERENCE
1060 CONTINUE
      IF (IMARK .EQ. NWF) THEN
          AMT = WFCUM (NWF)
          AMTDER = (WFCUM (IMARK) - WFCUM (IMARK - 2))/(2.*(WFTIM (IMARK)
1      - WFTIM (IMARK - 1)))
          ELSE
          AMTDER = (WFCUM (IMARK + 1) - WFCUM (IMARK -
1      1))/(2.*(WFTIM (IMARK)
2      - WFTIM (IMARK - 1)))
          END IF
C
1020 CONTINUE
      RETURN
      END
C *****
      SUBROUTINE OUTPUT (IOPT)
C
      IMPLICIT REAL (A - H, O - Z)
      PARAMETER (NPT = 150, NPTT = 50)
      COMMON /START/ CHVOL, AREA, WFMASI, RHOI,
1  PROJI, PROJW, TOL, TIMINC,
2  TIMEND, WAIR, BM, DERBM
      COMMON /CURRENT/ TIME, PRESCH, TRAVPR,
1  ELECEN, TEMP, RIMPET, GAMMA,
2  COVOL, WF1, WF2, ELDEN, SPMPR, VELP, BETA, BASEPR, CM,
3  Z, RHO, ENCOMP
      COMMON /OPTIONS/ IBETA, ICOM
      COMMON /DATA/ PRTIM (1:NPT), PRES (1:NPT),
1  TRTIM (1:NPT), TRAV (1:NPT),
2  VEL (1:NPT), ELTIM (1:NPT), ELEC (1:NPT)
      COMMON /OUT/ WFTIM (NPT), WFCUM (NPT)
      COMMON /NUMBER/ NPR, NTR, NEL, NTH, ITRVEL, NWF
      COMMON /NAME/ PRESIN, TRAVIN, ELECIN, THERIN, INITIN
      CHARACTER*20 PRESIN, TRAVIN, ELECIN, THERIN, INITIN
C
C FILE 28 IS OUTPUT FOR DETAILS OF WORKING FLUID
C FILE 27 IS ENERGY BALANCE
C FILE 26 IS ERROR FILE AND MESSAGES
      IF (IOPT .EQ. 1) THEN
          WRITE (*, 6000)
          OPEN (26, FILE = 'MESSAGES.OUT')
          OPEN (27, FILE = 'ENERGY.OUT')
          OPEN (28, FILE = 'WORKFL.OUT')

```

```

      OPEN (29, FILE = 'COMPRESS.OUT')
      GO TO 1000
    END IF
    IF (IOPT .EQ. 2) GO TO 1010
    IF (IOPT .EQ. 3) GO TO 1020
    IF (IOPT .EQ. 4) GO TO 1030
  C
  1010 CONTINUE
      WRITE (*, 6010)
      WRITE (*, 6020)
      WRITE (27, 6030)
      WRITE (28, 6040)
      WRITE (29, 6050)
      GO TO 1000
  C
  1020 CONTINUE
  C CHANGE TO MPa AND TO JOULES
      TIMMS = TIME*1.0E+3
      PRESCH = PRESCH*1.0E-7
      BASEPR = BASEPR*1.0E-7
      SPMPR = SPMPR*1.0E-7
      WRITE (*, 6060) TIMMS, PRESCH, BASEPR, TRAVPR, VELP, ELDEN, WF2
      write (26, 6070) timms, presch, basepr
      rimpet = rimpet*1.0e-7
      enused = (rimpet/(gamma - 1.))*wf2
      enkp = .5*projw*velp*velp*1.0e-7
      alpha = wf2/wfmasi
      cm = (wfmasi*(alpha + beta*(1. - alpha)) + wair)/projw
      enkg = (1./6.)*cm*projw*velp*velp*1.0e-7
      vol = chvol - covol*wf2 - (wfmasi - wf2)/rho + travpr*area
      enigas = spmpr*vol/(gamma - 1.)
      encom = (1. - z)*wfmasi*encomp*1.0e-7
      if (enused .ne. 0.0)
  1  enerr = ((enused - enkp - enkg - enigas - encom)/enused)*100.
      write (27, 6080) timms, enused, enkp, enkg, enigas, encom, enerr
      write (29, 6090) timms, rho, encomp, encom
  C
      GO TO 1000
  C
  C IF IOPT=1, FIND DER OF ENERGY
  C IF IOPT=2, FIND DER OF WF
  1030 CONTINUE
      TIME = 0.0
      TIMEND = WFTIM (NWF)
      TIM2 = 0.0
      EL = 0.0
      WF = 0.0
      ELDEN = 0.0
      ELDER = 0.0

```

```

WFDER = 0.0
WRITE (28, 6100) TIM2, EL, WF, ELDEN, ELDER, WFDER
DO 1040 I = 1, NPT
  TIME = TIME + TIMINC
  IF (TIME .LE. TIMEND) THEN
    CALL DER (TIME, 1, EL, ELDER)
    CALL DER (TIME, 2, WF, WFDER)
    IF (WF .NE. 0.0) ELDEN = EL/WF
    TIM2 = TIME*1.E+3
C ELDEN IN MJ/s, WFDER IN kg/s
    ELDER = ELDER*.001
    WFDER = WFDER*.001
    WRITE (28, 6100) TIM2, EL, WF, ELDEN, ELDER, WFDER
  ELSE
    GO TO 1000
  END IF
1040 CONTINUE
C
6000 FORMAT(/, ' Inverse Electrothermal Gun Code' //)
6010 FORMAT(1X, ' TIME ', 2X, 'CHAM PR', 2X,
  1 ' BASE PR ', 3X, 'PROJ TRAV', 2X, ' PROJ VEL', 5X, 'EL EN DEN',
  2 2X, 'CUM WF')
6020 FORMAT(2X, ' (ms) ', 2x, 2x, '(MPa)', 3x, 2x, 1x, '(MPa)', 1x, 2x,
  1 2x, '(cm)', 3x, 2x, 3x, '(cm/s)', 2x, 2x, 2x, '(MJ/kg)', 1X,
  2 2X, 1X, '(g)' //)
6060 FORMAT(1X, F6.2, 2X, F7.2, 2X, F10.5, 2X, F9.4, 2X, F10.2, 2X, F9.3, 2X, F10.5)
6070 format(1x, f6.2, 2x, f15.7, 2x, f15.7)
6030 format(1x, 'ENERGY BALANCE' //,
  1 1x, 'time', 7x, 'enused', 10x, 'KE proj', 9x, 'KE gas', 8x,
  2 'Intgas', 5x, 'En comp', 5x, 'Error %',
  3 /, 1x, '(ms)', 7x, '(J) ', 11x, '(J) ', 9x, '(J) ', 10x, '(J)',
  4 10x, '(J)')
6080 format(1x, f10.3, 1x, f15.2, 1x, f10.2, 1x, f10.2, 1x, f12.2, 1X, F10.2, 1x,
  1 F6.1)
6040 FORMAT(1x, 'WORKING FLUID AND ELECTRICAL ENERGY SUMMARY' //,
  1 1x, 1x, 'TIME', 1x, 3x, 'EL EN', 2x, 5x, 'WF CUMULATIVE', 1X, 1x,
  2 'EL EN DENSITY', 1x, 'ELEC DER', 1X, 2x, 'WF DER',
  3 /, 1x, 1X, '(ms)', 1X, 3x, '(kJ)', 3X, 11X, '(G)', 6x, 4X, '(MJ/kg)', 5X,
  4 2x, '(MJ/s)', 2X, 3x, '(kg/s)')
6100 FORMAT(1x, f6.3, 1x, f10.2, 1x, f15.5, 1x, f15.5, 1x, f10.2, 1x, f10.2)
6050 FORMAT(1x, 'timms(ms), rho(g/cc), encomp(J/g), encom(J)')
6090 FORMAT(1x, f6.3, 1x, f8.5, 1x, f20.5, 1x, f10.5)
C
1000 CONTINUE
RETURN
END
C *****

```


<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Tank-Automotive Command ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-5000
1	Commander U.S. Army Materiel Command ATTN: AMCAM 5001 Eisenhower Ave. Alexandria, VA 22333-0001	1	Director U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
1	Commander U.S. Army Laboratory Command ATTN: AMSLC-DL 2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI Ft. Sill, OK 73503-5000
		(Class. only)1	Commandant U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	(Unclass. only)1	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000		
1	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050	1	WLMNOI Eglin AFB, FL 32542-5000
			<u>Aberdeen Proving Ground</u>
		2	Dir, USAMSA ATTN: AMXS-D AMXS-MP, H. Cohen
		1	Cdr, USATECOM ATTN: AMSTE-TC
(Unclass. only)1	Commander U.S. Army Rock Island Arsenal ATTN: SMCRI-TL/Technical Library Rock Island, IL 61299-5000	3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
1	Director U.S. Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000	1	Dir, VLAMO ATTN: AMSLC-VL-D
1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010	10	Dir, USABRL ATTN: SLCBR-DD-T

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commander U.S. Army Concepts Analysis Agency ATTN: D. Hardison 8120 Woodmount Ave. Bethesda, MD 20014
1	Director U.S. Army BMD Advanced Technology Center P. O. Box 1500 Huntsville, AL 35807
1	Chairman DOD Explosives Safety Board Room 856-C Hoffman Bldg. 1 2461 Eisenhower Ave. Alexandria, VA 22331-0600
3	Project Manager Autonomous Precision-Guided Munition (APGM) U.S. Army Armament Research, Development, and Engineering Center ATTN: AMCPM-CWW Picatinny Arsenal, NJ 07806-5000
1	Department of the Army Office of the Product Manager 155 mm Howitzer, M109A6, Paladin ATTN: SFAE-AR-HIP-IP, Mr. R. De Kleine Picatinny Arsenal, NJ 07806-5000
1	Commander Production Base Modernization Agency U.S. Army Armament Research, Development, and Engineering Center ATTN: AMSMC-PBM-E, L. Laibson Picatinny Arsenal, NJ 07806-5000
3	PEO-Armaments Project Manager Tank Main Armament Systems ATTN: AMCPM-TMA, K. Russell AMCPM-TMA-105 AMCPM-TMA-120 Picatinny Arsenal, NJ 07806-5000

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
5	Director Benet Laboratories U.S. Army Watervliet Arsenal ATTN: SARWV-RD, L. Johnson G. Carafano R. Thierry R. Hasoenbein P. Votis Watervliet, NY 12189
3	Commander U.S. Army AMCCOM ATTN: AMSMC-IRC, G. Cowan SMCAR-ESM(R), W. Fortune R. Zastrow Rock Island, IL 61299-7300
1	Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-IS-L-R, Myer Center Fort Monmouth, NJ 07703-5301
1	Commandant U.S. Army Aviation School ATTN: Aviation Agency Fort Rucker, AL 36360
1	President U.S. Army Armor and Engineering Board ATTN: ATZK-AD-S Fort Knox, KY 40121
1	Director HQ, TRAC RPD ATTN: ATCD-MA, MAJ Williams Fort Monroe, VA 23651-5143
1	Headquarters U.S. Army Materiel Command ATTN: AMCICP-AD, Michael F. Fisette 5001 Eisenhower Ave. Alexandria, VA 22333-0001

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
4	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCD, D. Spring SMCAR-CCS SMCAR-CCH-T, L. Rosendorf SMCAR-CCH-V, E. Fennell Picatinny Arsenal, NJ 07806-5000
8	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AE, J. Picard SMCAR-AEE-B, A. Beradell D. Downs S. Einstein A. Bracuti D. Chiu SMCAR-AEE, J. Lannon SMCAR-AES, S. Kaplowitz Picatinny Arsenal, NJ 07806-5000
11	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-FSA-T, M. Salsbury SMCAR-FSE, G. Ferdinand T. Gora B. Knutelsky K. C. Pan W. Davis C. Dunham A. Graf H. Naber-Lebby R. Lundberg J. Niles Picatinny Arsenal, NJ 07806-5000
2	Commander U.S. Army Research Office ATTN: Technical Library D. Mann P.O. Box 12211 Research Triangle Park, NC 27709-2211

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commander U.S. Army Belvoir R&D Center ATTN: STRBE-WC, Technical Library (Vault) Bldg. 315 Fort Belvoir, VA 22060-5606
1	Commander U.S. Army TRAC - Fort Lee Defense Logistics Studies Fort Lee, VA 23801-6140
1	President U.S. Army Artillery Board Fort Sill, OK 73503
1	Commandant U.S. Army Command and General Staff College Fort Leavenworth, KS 66027-5200
1	Commandant U.S. Army Special Warfare School ATTN: Rev and Tng Lit Div Fort Bragg, NC 28307
1	Commander Radford Army Ammunition Plant ATTN: SMCRA-QA/HL Library Radford, VA 24141
3	Commander U.S. Army Foreign Science and Technology Center ATTN: AMXST-MC-3 S. LeBeau C. Beiter 220 Seventh St., NE Charlottesville, VA 22901
1	Commandant U.S. Army Field Artillery Center and School ATTN: ATSF-CO-MW, B. Willis Fort Sill, OK 73503
1	Office of Naval Research ATTN: Code 473, R S. Miller 800 N. Quincy St. Arlington, VA 22217

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Commander Naval Sea Systems Command ATTN: SEA 62R SEA 64 Washington, DC 20362-5101
1	Commander Naval Air Systems Command ATTN: AIR-954-Technical Library Washington, DC 20360
1	Naval Research Laboratory Technical Library Washington, DC 20375
2	Commander Naval Surface Warfare Center ATTN: J. P. Consaga C. Gotzmer Silver Spring, MD 20902-5000
3	Commander Naval Surface Warfare Center ATTN: S. Jacobs/Code R-10 K. Kim/Code R-13 R. Bernecker/Code R-13 Silver Spring, MD 20902-5000
6	Commander Naval Surface Warfare Center ATTN: Code G33, T. Doran J. L. East W. Burrell J. Johndrow Code G23, D. McClure Code DX-21 Technical Library Dahlgren, VA 22448-5000
2	Commander Naval Underwater Systems Center Energy Conversion Dept. ATTN: Code 5B331, R. S. Lazar Technical Library Newport, RI 02840

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commander Naval Weapons Center ATTN: Code 388, C. F. Price Info Science Div China Lake, CA 93555-6001
1	OSD/SDIO/IST ATTN: Dr. Len Caveny Pentagon Washington, DC 20301-7100
1	OLAC PL/TSTL ATTN: D. Shiplett Edwards AFB, CA 93523
1	Commandant U.S. Army Field Artillery School ATTN: STSF-TSM-CN Fort Sill, OK 73503-5600
10	Central Intelligence Agency Office of the Central Reference Dissemination Branch Room GE-47 HQS Washington, DC 20502
1	Central Intelligence Agency ATTN: Joseph E. Backofen HQ Room 5F22 Washington, DC 20505
5	Director Sandia National Laboratories ATTN: T. Hitchcock R. Woodfin D. Benson S. Kempka R. Beasley Advanced Projects Div 14 Organization 9123 Albuquerque, NM 87185
2	Director Los Alamos National Laboratory ATTN: B. Kaswhia H. Davis Los Alamos, NM 87545

No. of
Copies Organization

- 1 Director
Lawrence Livermore National Laboratories
ATTN: M. S. L-355, A. Buckingham
P. O. Box 808
Livermore, CA 94550
- 2 Director
Sandia National Laboratories
Combustion Research Facility
Division 8357
ATTN: R. Armstrong
S. Vosen
Livermore, CA 94551-0469
- 1 University of Illinois
Dept. of Mech./Indust. Engr.
ATTN: Professor Herman Krier, 144 MEB
1206 N. Green St.
Urbana, IL 61801
- 1 Johns Hopkins University
Applied Physics Laboratory
Chemical Propulsion Information Agency
ATTN: T. Christian
Johns Hopkins Rd.
Laurel, MD 20707
- 1 Pennsylvania State University
Dept. of Mechanical Engr.
ATTN: Dr. K. Kuo
312 Mechanical Engineering Bldg.
University Park, PA 16802
- 1 North Carolina State University
ATTN: John G. Gilligan
Box 7909
1110 Burlington Engineering Labs
Raleigh, NC 27695-7909
- 1 SRI International
Propulsion Sciences Division
ATTN: Technical Library
333 Ravenswood Ave.
Menlo Park, CA 94025
- 1 SPARTA
ATTN: Dr. Michael Holland
9455 Towne Center Dr.
San Diego, CA 92121-1964

No. of
Copies Organization

- 5 FMC Corporation
ATTN: Mr. G. Johnson
Mr. M. Seale
Dr. A. Giovanetti
Mr. J. Dyvik
Dr. D. Cook
4800 East River Road
Minneapolis, MN 55421-1498
- 3 GT Devices
ATTN: Dr. S. Goldstein
Dr. R. J. Greig
Dr. N. Winsor
5705A General Washington Dr.
Alexandria, VA 22312
- 3 General Dynamics Land Systems
ATTN: Dr. B. VanDeusen
Mr. F. Lunsford
Dr. M. Weidner
P. O. Box 2074
Warren, MI 48090-2074
- 2 Alliant Techsystems, Inc.
ATTN: R. E. Tompkins
J. Kennedy
MN38-3300
10400 Yellow Circle Dr.
Minnetonka, MN 55343
- 2 Olin Ordnance
ATTN: V. McDonald, Library
Hugh McElroy
P. O. Box 222
St. Marks, FL 32355
- 1 Paul Gough Associates, Inc.
ATTN: P. S. Gough
1048 South St.
Portsmouth, NH 03801-5423
- 1 Physics International Company
ATTN: Library, H. Wayne Wampler
2700 Merced St.
San Leandro, CA 94577

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Rockwell International Rocketdyne Division ATTN: BA08, J. E. Flanagan J. Gray 6633 Canoga Ave. Canoga Park, CA 91304
2	Princeton Combustion Research Laboratory ATTN: M. Summerfield N. Messina 4275 U.S. Highway One Monmouth Junction, NJ 08852
2	Science Applications, Inc. ATTN: J. Batteh L. Thornhill 1519 Johnson Ferry Rd. Suite 300 Marietta, GA 30062-6438
1	Eli Freedman & Associates ATTN: E. Freedman 2411 Diana Rd. Baltimore, MD 21209
3	Deputy Commander Strategic Defense Command ATTN: SSFAE-SD-HVA S. Smith LTC Kee D. Kianos P. O. Box 1500 Huntsville, AL 35887-3801
1	Veritay Technology, Inc. 4845 Millersport Hwy. P. O. Box 305 East Amherst, NY 14051-0305
1	Battelle ATTN: TACTEC Library, J. N. Huggins 505 King Ave. Columbus, OH 43201-2693

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	California Institute of Technology Jet Propulsion Laboratory ATTN: L. D. Strand, MS 512/102 D. Elliot 4800 Oak Grove Dr. Pasadena, CA 91109
1	General Electrica Co. Defense Systems Division ATTN: Dr. J. Mandzy Mail Drop 43-220 100 Plastics Ave. Pittsfield, MA 01201
1	Naval Sea System Command Department of the Navy ATTN: CSEA/CDR Dampier 06KR12 Washington, DC 20362-5101
2	SAIC ATTN: Mr. N. Sinha Dr. S. Dash 501 Office Center Drive Suite 420 Fort Washington, PA 19034-3211
1	Dr. W. J. Sargeant James Clark Maxwell Professor Department of Electrical Engineering Bonner Hall—Room 312 Buffalo, NY 14260
	<u>Aberdeen Proving Ground</u>
4	Cdr, USACSTA ATTN: S. Walton G. Rice D. Lacey C. Herud
1	Dir, USAHEL ATTN: J. Weisz

No. of
Copies Organization

2 RARDE
GS2 Division
Building R31
ATTN: Dr. C. Woodley
Dr. G. Cook
Fort Halstead
Sevenoaks, Kent TN147Bt
ENGLAND

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number BRL-TR-3391 Date of Report September 1992

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

**CURRENT
ADDRESS**

Name

Organization

Address

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

**OLD
ADDRESS**

Name

Organization

Address

City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

DEPARTMENT OF THE ARMY
Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066



OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee.

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

**NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**

