

AD-A257 021

ION PAGE

Form Approved
OMB No. 0704-0188

2

Public
gather
collec
Davis



1 hour per response, including the time for reviewing instructions, searching existing data sources, collection of information. Send comments regarding this burden estimate or any other aspect of this Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. A

Sept. 17, 1992

3. REPORT TYPE AND DATES COVERED

Final -- 1 July 1989 to 30 June 1992

4. TITLE AND SUBTITLE

JSEP Fellowship for James G. Maloney

5. FUNDING NUMBERS

DAAL03-89-G-0078

6. AUTHOR(S)

James G. Maloney

DTIC
SELECTED
OCT 21 1992
S E D

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Georgia Institute of Technology
School of Electrical Engineering
Atlanta, GA 30332-0250

8. PERFORMING ORGANIZATION
REPORT NUMBER

T-87-109

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

U. S. Army Research Office
P. O. Box 12211
Research Triangle Park, NC 27709-2211

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

ARO 27006.2-EL-F

11. SUPPLEMENTARY NOTES

The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

The objective of this research was to study the mechanisms of transient radiation by various antenna structures, and to apply to understanding gained to the design of new, better transient antennas. The approach chosen for this research program was to extend the finite-difference time-domain (FDTD) numerical method to antenna analysis and to use the developed methodology to study/design transient antennas.

408631

92-27535



698

14. SUBJECT TERMS

15. NUMBER OF PAGES

5

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

FINAL REPORT

- 1. ARO PROPOSAL NUMBER: 27006-EL-F
- 2. PERIOD COVERED BY REPORT: 1 July 1989 - 30 June 1992
- 3. TITLE OF PROPOSAL: JSEP Fellowship
- 4. CONTRACT OR GRANT NUMBER: DAAL03-89-G-0078
- 5. NAME OF INSTITUTION: Georgia Institute of Technology
- 6. AUTHORS OF REPORT: James G. Maloney
- 7. LIST OF MANUSCRIPTS SUBMITTED OR PUBLISHED UNDER ARO SPONSORSHIP DURING THIS REPORTING PERIOD, INCLUDING JOURNAL REFERENCES:

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Date: _____	
Availability Codes	
Dist	Avail and/or Special
A-1	

Journal Papers

- J. G. Maloney, G. S. Smith, and W. R. Scott, Jr. "Accurate Computation of the Radiation from Simple Antennas Using the Finite-Difference Time-Domain Method," *IEEE Transactions on Antennas and Propagation*, vol. 38, No. 7, pp. 1059-1068, July 1990.
- J. G. Maloney and G. S. Smith, "The Use of Surface Impedance Concepts in the Finite-Difference Time-Domain Method," *IEEE Transactions on Antennas and Propagation*, vol. 40, no. 1, pp. 38-48, Jan. 1992.
- J. G. Maloney and G. S. Smith, "The Efficient Modeling of Thin Material Sheets in the Finite-Difference Time-Domain (FDTD) Method," *IEEE Transactions on Antennas and Propagation*, Vol. 40, no. 3, pp. 323-330, Mar. 1992.
- J. G. Maloney and G. S. Smith, "Optimization of Pulse Radiation from a Simple Antenna Using Resistive Loading," *Microwave and Optical Technology Letters*, vol. 5, no. 7, pp. 299-303, June 1992.
- J. G. Maloney and G. S. Smith, "A Study of Transient Radiation from the Wu-King Resistive Monopole - FDTD Analysis and Experimental Measurements," submitted for publication to *IEEE Transactions on Antennas and Propagation*.

- J. G. Maloney and G. S. Smith, "A Comparison of Methods for Modeling Electrically-Thin Dielectric and Conducting Sheets in the Finite-Difference Time-Domain (FDTD) Method," submitted for publication to *IEEE Transactions on Antennas and Propagation*.
- J. G. Maloney and G. S. Smith, "Optimization of a Conical Antenna for Pulse Radiation: An Efficient Design Using Resistive Loading," submitted for publication to *IEEE Transactions on Antennas and Propagation*.

Conference Papers

- J. G. Maloney, G. S. Smith, and W. R. Scott, Jr., "Accurate Computation of the Radiation from Simple Antennas Using the Finite-Difference Time-Domain Method," *Proc. 1989 IEEE AP-S Int. Symp.*, San Jose, CA, June 1989, vol. 1, pp. 42-45.
- J. G. Maloney and G. S. Smith, "Implementation of Surface Impedance Concepts in the Finite-Difference Time-Domain (FD-TD) Technique," *Proc. 1990 IEEE AP-S Int. Symp.*, Dallas, TX, May 1990, vol. 4, pp. 1628-1631.
- J. G. Maloney and G. S. Smith, "The Role of Resistance in Broadband, Pulse-Distortionless Antennas," *Proc. 1991 IEEE AP-S Int. Symp.*, London, Ontario, June 1991, vol. 2, pp. 707-710.
- J. G. Maloney and G. S. Smith, "Optimization of a Resistively Loaded Conical Antenna for Pulse Radiation," *Proc. 1992 IEEE AP-S Int. Symp.*, Chicago, IL, July 20-24, vol. 4, pp. 1968-1971.
- J. G. Maloney and G. S. Smith, "A Discussion of Efficient Methods for Including Thin Material Sheets in the FDTD Technique," *Proc. 1992 IEEE AP-S Int. Symp.*, Chicago, IL, July 20-24, vol. 3, pp. 1666-1669.

8. SCIENTIFIC PERSONNEL SUPPORTED BY THIS PROJECT AND DEGREES AWARDED DURING THIS PERIOD:

- James G. Maloney
School of Electrical Engineering
Georgia Institute of Technology
Atlanta, GA 30332

OUTLINE OF RESEARCH FINDINGS

The objective of this research was to study the mechanisms of transient radiation by various antenna structures, and to apply to understanding gained to the design of new, better transient antennas. The approach chosen for this research program was to extend the finite-difference time-domain (FDTD) numerical method to antenna analysis and to use the developed methodology to study/design transient antennas.

While it is difficult to quantify the performance of antennas used for pulse radiation, it is generally accepted that these antennas should have the following characteristics.

- The radiated pulse should be a faithful reproduction of the excitation; i.e., there should be little pulse distortion on radiation.
- The reflected signal at the input of the antenna should be small.
- The amplitude of the radiated signal in the desired direction should be as large as possible.

These characteristics were the standards by which transient antenna designs were judged.

Prior to this research program, the FDTD method had been widely and successfully used for scattering and interaction problems (mainly the calculation of target RCS); however, there had been little or no application to driven antenna problems. Therefore, the first task of this research program was to investigate the application of this method to driven antenna problems. The investigation began by applying the method to the calculation of the behavior of a few perfectly conducting antennas: the cylindrical and conical monopole antennas fed through an image plane by a coaxial transmission line. The FDTD results were validated by comparison with the experimental results of previous researchers. The level of agreement between the FDTD predicted behavior and the experimental results was excellent. Furthermore, various graphical displays, i.e, surface charge density "bounce" diagrams, gray scale plots of the near-field, "burst" diagrams of the time-domain far-field radiation, were used and proved very useful in describing the transient radiation from these antennas.

Transient antennas usually incorporate regions of resistive material into their structure. The resistive material can be categorized into two types: electrically thick and electrically thin. However, the direct modeling of these types of resistive material in the FDTD method is highly inefficient. Therefore, the next step in this research program was to develop efficient methods for modeling these types of resistive material.

The electrically thick case was considered first. Historically, electromagnetic problems involving electrically-thick resistive material are simplified by replacing the electrically-thick resistive material with a surface impedance boundary condition (SIBC). Therefore, the approach taken was to develop an efficient FDTD implementation of surface impedance concepts. The developed methodology was verified by comparison with exact theoretical results for several test problems. The problems included plane wave reflection off of a lossy dielectric half space, a pulsed wire over a lossy dielectric half space, and propagation down a parallel-plate waveguide with lossy walls. The FDTD predicted behavior for these three problems was in excellent agreement with the exact results.

As the "proof of concept" for this research program, the above described methodology was used in the "optimization" of the transient radiation of a canonical antenna: the open-ended parallel-plate waveguide. The walls of the antenna were made lossy/resistive over a section of the waveguide near the open-end. The FDTD computed results were used in a parametric study to determine the optimum resistive loading. The parametric study yielded a design that had a good radiated pulse shape, a small reflected signal, and an acceptable radiation efficiency; that is, the three criteria mentioned above were met. Again, various graphical displays were used to describe the transient radiation of this structure.

Of course, the open-ended parallel-plate radiator is a two-dimensional antenna; hence, it is unrealizable in practice. However, the methodology developed for optimizing the performance of this idealized antenna is applicable to more complex, practical three-dimensional antennas as will be shown below.

The next step in this research program was to consider the modeling of electrically-thin resistive material. Of course, the FDTD method could be used to directly model the electrically-thin material using very small FDTD spatial cells; however, this is very inefficient. The approach taken in the development of an efficient method was to consider a sub-cell model for the electrically-thin material. That is, a coarse spatial grid (large spatial cells) is used in the FDTD method with the few cells that contain the electrically-thin material being modified to include the effects of the material. Again, the developed methodology was verified by comparison with exact theoretical results for several test problems. The test configuration was a parallel-plate waveguide loaded with a thin resistive sheet. Results for both TEM and TM_1 excitation were in excellent agreement with the exact results. In addition to being able to model resistive sheets, the sub-cell model can be used to model thin-dielectric sheets. The results for dielectric

sheets were also in excellent agreement with the exact results.

The first antenna application of the sub-cell model for electrically-thin resistive material was the study of the transient radiation from resistively loaded, cylindrical monopole antennas. Specifically, the transient radiation from the tapered resistive cylindrical monopole proposed by Wu and King in 1965 was studied. Again, various graphical displays were used to describe the transient radiation from the antenna. A series of experimental models of resistively loaded monopoles were constructed and the experimental measurements were in excellent agreement with the FDTD predicted behavior.

The final step in this research program was to design a new, practical transient radiator. The structure considered was the resistively loaded conical monopole antenna. The resistive loading was again optimized by performing a parametric study. In comparison with the performance of a perfectly conducting conical monopole, the "optimized" resistive design had internal reflections reduced by 35 dB, had a superior pulse shape, and had the same radiated amplitude; that is, the three design criteria mentioned earlier were met. Again, a series of experimental models were constructed, and the experimental measurements were in excellent agreement with the FDTD predicted behavior, thus, confirming the "optimization".

In addition to the application to resistive antenna analysis, the efficient techniques developed for modeling electrically-thin and thick material can be used in many other applications. Other applications to which the electrically-thin material model can be applied include: thin resistive films or cloths used in waveguide components and absorbers; thin, substrate mounted, metallic or dielectric films used in integrated circuitry; or thin dielectric windows or radomes used to enclose antennas. Other applications to which the electrically-thick material model can be applied include: non-perfect (lossy) conductors found in various transmission lines; or the non-perfect (lossy) conductors found in various high-Q resonators.

The research described above has resulted in seven journal papers and five conference presentations to date.