DODPOPHM/USA/DOD/NADTR92030

AD-A257 817

PERFORMANCE ORIENTED PACKAGING TESTING OF PACKING BOX FOR CKU-5B/A AIRCRAFT EJECTION (ROCKET) CATAPULT FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

Author:
Richard Plummer
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5023

November 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Indian Head Division (Code 5120H)
Indian Head, Maryland 20640



REPORT DOCUMENTATION PAGE

Form Approved OMB No 0704-0188



Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED				
	11/92	POP Test (10/92)				
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Packing Box for the CKU-5B/A Aircraft Ejection (Rocket) Catapult for Packing Group II Solid Hazardous Materials		5. FUNDING NUMBERS DTIC ELECTE NOV 10.1992				
6. AUTHOR(S) Richard Plummer		JB				
7. PERFORMING ORGANIZATION NAME	(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER				
Naval Weapons Station Earle Test and Evaluation Branch (Coc Colts Neck, NJ 07722-5023	de 5023)	DODPOPHM/USA/DOD/NADTR92030				
9. SPONSORING/MONITORING AGENCY	NAME(S) AND ADDRESS(ES)	10. SPONSORING/MONITORING AGENCY REPORT NUMBER				
Commanding Officer, Naval Surf Indian Head Division (Code 5120 Indian Head, MD 20640		Same as above				
11. SUPPLEMENTARY NOTES						
N/A						
12a. DISTRIBUTION/AVAILABILITY STA	DESTRIBUTION STATES	12b. DISTRIBUTION CODE				
13. ABSTRACT (Maximum 200 words)	Approved for public re Distribution Unlimit	nd .				
This Performance Oriented Packagin	on (POP) test was conducted to	a ascertain whether the nacking how for the				

This Performance Oriented Packaging (POP) test was conducted to ascertain whether the packing box for the CKU-5B/A Aircraft Ejection (Rocket) Catapult meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was an inert CKU-5B/A Rocket Catapult weighing 9 kg (20 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 1 kg (2 pounds) was added. Gross weight of the loaded box was 21 kg (46 pounds). The test results indicate that the box has conformed to the POP requirements.

14. SUBJECT TERMS		15. NUMBER OF PAGES			
POP Test of Packing Box for CKU-5B/A Aircraft Ejection (Rocket) Catapult		16. PRICE CODE			
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICA- TION OF THIS PAGE	19. SECURITY CLASSIFICA- TION OF ABSTRACT	20. LIMITATION OF ABSTRACT		
UNCLASSIFIED	UL	UL	UL		

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the packing box for the CKU-5B/A Aircraft Ejection (Rocket) Catapult meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was an inert CKU-5B/A Rocket Catapult weighing 9 kg (20 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 1 kg (2 pounds) was added. Gross weight of the loaded box was 21 kg (46 pounds).

Due to unavailability only one box was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The box was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the box was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the box left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The box was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test box). A weight of 454 kg (1,000 pounds) was stacked on the test box. The test was performed for 24 hours. The weight was then removed and the box examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom.
- b. Flat top.

DODPOPHM/USA/DOD/NADTR92030

- c. Flat on long side.
- d. Flat on short side.
- e. One corner.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 3.4 Hz. Immediately after the vibration test was completed, the box was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The box was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the box was inspected. The rocket catapult was completely retained by the box.

REFERENCE MATERIAL

- A. Code of Federal Regulations, Title 49 CFR, Parts 107-178.
- B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies) ATTN: DTIC/FDA Bldg. 5, Cameron Station Alexandria, VA 22304-6145

Defense General Supply Center ATTN: DDRV-TMPA, D. Gay Richmond, VA 23219

Commander Naval Surface Warfare Center ATTN: Crane Division (Code 4053) Crane, IN 47522-5000

Access	ion For	1	
NTIS	GRASI	T	
DTIC T	TAT		
Unannounced			
Justification			
By			
Availability Codes			
Diat A/	Aveil an Specia		

TEST DATA SHEET

POP	MARKING:	
		 4040404

UN 4C1/Y21/S/**/USA/DOD/NAD

**YEAR LAST PACKED OR MANUFACTURED

Container P/N or NSN:

Container: Packing Box for the CKU-5B/A Aircraft Ejection (Rocket) Catapult

Type: 4C1 Con

Drawing Number: Outer Packaging Material:

NAVORDSTA 6610161 Wood

Dimensions: Gross Weight: 47" L x 8-1/2" W x 6" H 21 kg (46 pounds)

Closure (Method/Type): Tare Weight:

Nails and Strapping 11 kg (24 pounds)

Additional Description: PPP-B-621 Wood Box

PACKAGED COMMODITY:

Name: See table 1 NSN(s): See table 1

United Nations Number: See table 1

United Nations Packing Group: II

Physical State (Solid, Liquid, or Gas): Solid

Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A

Consistency/Viscosity: N/A Density/Specific Gravity: N/A

Amount Per Container: See table 1 | Flash Point: N/A

Net Weight: See table 1

PACKAGED COMMODITY USED FOR TEST:

Name: CKU-5B/A Rocket Catapult

Physical State: Solid (inert)

Consistency: N/A

Density/Specific Gravity: N/A

Test Pressure (Liquids Only): N/A Net Weight: 10 kg (22 pounds)

Additional Description:

The net weight includes the current maximum commodity weight plus an additional 1 kg (2 pounds).

N/A = Not Applicable

TABLE 1 Commodities Approved for Shipping in the Packing Box for the CKU-5B/A Aircraft Ejection (Rocket) Catapult

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
MT47	1377-01-359-3194	CKU-5B/A Rocket Catapult	6610161	1.3C	0186	1	20.5	44.5

N/A = Not Assigned