



EFFECTS OF GROUND REFLECTIONS ON FREQUENCY MODULATED SIGNALS

a alter Muteller

DTIC QUALITY INSPECTED 2

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

BEST AVAILABLE COPY

Rome Laboratory Air Force Systems Command Griffiss Air Force Base, NY 13441-5700







This report has been reviewed by the Rome Laboratory Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be releasable to the general public, including foreign nations.

RL-TR-92-172 has been reviewed and is approved for publication.

APPROVED:

Hund & Alterna

· · · .

EDWARD E. ALTSHULER, Chief Applied Electromagnetics Division Electromagnetics & Reliability Directorate

FOR THE COMMANDER:

han Khe

JOHN K. SCHINDLER, Director Electromagnetics & Reliability Directorate

If your address has changed or if you wish to be removed from the Rome Laboratory mailing list, or if the addressee is no longer employed by your organization, please notify RL(ERCE) Hanscom AFB MA 01731-5000. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document require that it be returned.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of info	ormation is estimated to average 1 hour per resp	ones, including the time for reviewir Send comments recenting this b	g instructions, searching existing data a	sources, gathering
information, including suggestions for reducing 1204, Arlington, VA 22202-4302, and to the Offi	this burden, to Washington Headquarters Service ice of Management and Budget, Paperwork Redu	es, Directorale for Information Oper otion Project (0704-0188), Washing	itions and Reports, 1215 Jefferson De ion, DC 20503.	vis Highway, Suite
1. AGENCY USE ONLY (Leave bian)	N 2. REPORT DATE	3. REPORT TYPE AN	D DATES COVERED	
	June 1992	in-House,	January 1992 May 1	992
4. TITLE AND SUBTITLE		· · · · · · · · · · · · · · · · · · ·	5. FUNDING NUMBERS	
Effects Of Ground Reflection	ns On Frequency Modulated S	Signals		
			PE - 61102F	
			PR - 2304	
6. AUTHOR(S)			TA - 14	
Saba Mudaliar *			WU - 02	
7. PERFORMING ORGANIZATION	NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZ REPORT NUMBER	ZATION
Rome Laboratory / ERC				
Hanscom AFB, MA 017	/31-5000		RL-1 H-92-172	
9. SPONSORING/MONITORING A	GENCY NAME(S) AND ADDRESS(E	3)	10. SPONSORING/MOVEN AGENCY REPORT NUMBE	oring R
11. SUPPLEMENTARY NOTES				
* National Research Co Research Associate	uncil			
12a. DISTRIBUTION/AVAILABILIT	Y STATEMENT		12b. DISTRIBUTION CODE	
Approved For Public Re	elease; Distribution Unlimited			
13. ABSTRACT (Maximum 200 wor	rds)			
It is well known that g	round reflections cause ambig	uities in radar detection	on and tracking. A more	serious
problem is the interference	that occurs when the phase d	ifference between the	direct signal and the gro	bund
reflected signal is small. Th	is has been well studied in the	context of the usual j	oulsed signals. There is	iittle
that can be done to entirely	eliminate this problem. In this	s report the effect on t	requency modulated sig	nals
of reflections from surfaces	with different statistics is inve	stigated. The ground	reflection studied in this	; amal
report is the concretit reflect	ation. Four different kinds of ro	ugn sunaces (normal,	exponential, reavieign a	
Although the normal distribu	ed. In each case an explicit ex ution is the most commonly us	ed model in applicati	ons the surfaces often h	ava
Although the normal distribution is the most commonly used model, in applications the sunaces often have				
found that the received signals for normal and exponential surfaces have quite different amplitude				
characteristics. It is found that the Gaussian model may be a reasonable approximation for such asymmetric				
surfaces only when the Rayleigh roughness parameter is small.				
14. SUBJECT TERMS			15. NUMBER OF	PAGES
Rough surfaces	Radar signals		60	
Surface height statistics Coherent surface reflection	U U		16. PRICE CODI	E
17. SECURITY CLASSIFI- CATION OF REPORT	18. SECURITYCLASSIFI- CATION OF THIS PAGE	19. SECURITY CLASSI CATION OF ABSTRACT	- 20. LIMITATION ABSTRACT	OF
Unclassified	Unclassified	Unclassified	SA	R

	Unclassified
E40 04	200 5500

NSN '

SAR

Contents

1. INTRODUCTION	1
2. DESCRIPTION OF THE PROBLEM	1
3. DIRECT SIGNAL	7
4. GROUND REFLECTED SIGNAL I	9
4.1 Normal distribution	9
4.2 Exponential distribution	11
4.3 Rayleigh distribution	14
4.4 Skew-normal distribution	18
5. GROUND REFLECTED SIGNAL II	23
5.1 Normal distribution	24
5.2 Exponential distribution	24
6. DISCUSSION	26
6.1 Ground Reflected Signal-I	27
6.2 Ground Reflected Signal-II	28
6.3 Numerical Results	29
7. CONCLUSION	43
REFERENCES	45
APPENDIX A. Characteristic functions	47
APPENDIX B. Coherent reflection coefficients	51
Nomenclature	53

. .

-- --

.

•

•

-

.

.

Illustrations

.

.

1.	Scattering geometry		2
2.	Comparison of Ground Reflected	Signal I	
	for normal and exponential	distributions	30
3.	Comparison of Ground Reflected	Signal II	
	for normal and exponential	distributions	37

Preface

The author is grateful to Dr. R.J.Papa for initiating interest in the topic of this report.

Acces	ion For	
NTIS DTIC Unanr Justifi	CRA&I TAB nounced cation	0 0 0 0
By Distrib	ution /	
A	vaitability	Codes
Dist R-1	Avait and Specie	d / or Bi

Effects Of Ground Reflection On Frequency Modulated Signals

1. INTRODUCTION

It is well-known that radar detection is often adversely affected by ground reflections [Evans. 1966; Smith and Mrstik, 1979]^{1,2}. Although several techniques have been devised to alleviate this problem there are still situations where the problem can be acute. Particularly in low-angle radar tracking, the problem is sometimes irremediable [Barton, 1974]³. The fact that the ground surface is almost always irregular introduces further complications and demands careful study [Papa et al. 1983]⁴. It must be noted here that all studies thus far on the effects of ground reflections have been restricted to conventional pulsed radars. However, chirp radars use frequency modulated signals and the effects of ground reflections on such signals may be quite different from those on ordinary pulsed signals. This report concentrates on the effect of ground reflections on frequency modulated signals.

2. DESCRIPTION OF THE PROBLEM

The geometry of the problem is shown in Figure 1. The ground is represented as a perfectly conducting random surface whose mean

Received for publication 12 June 1992







FIGURE.1 SCATTERING GEOMETRY

coincides with the xy-plane. Moreover the surface is assumed to be isotropic and smoothly varying in slopes so that the Kirchhoff method may be used for analysis.

The main quantity of interest to us in this report is the average power of the signal received by the chirp radar. There are four contributions to this quantity as shown in Figure 1. The target is assumed to have unit reflectivity. Both the target and the radar antenna are assumed to be isotropic. The ground reflection that we refer to in this report is the specular reflection or the coherent reflection.

Let $f_1(t)$. $f_2(t)$. $f_3(t)$ and $f_4(t)$ represent the received signals corresponding to the four cases shown schematically in Figure 1. The angle between the coherent ray and the z-axis is denoted as θ while the reflection coefficient associated with this ray is denoted as R. With these notations we have the relation

$$f_{2}(t) = R f_{1}(t+D)$$
 (1)

where D is the delay caused by the path difference between the direct signal (Figure 1a) and the ground reflected signal (Figure 1b). Also it is clear that

$$f_3(t) = f_2(t)$$
 (2)

For the same reason

$$f_{4}(t) = R^{2} f_{1}(t+2D)$$
 (3)

Thus the received signal f(t) is related to $f_1(t)$ as

$$f(t) = f_1(t) + 2R f_1(t+D) + R^2 f_1(t+2D)$$
(4)

Hereinafter we shall use capital letters to denote Fourier transforms of corresponding signals. For example

$$F_{1}(\omega) = \int_{\infty}^{\infty} dt f_{1}(t) \exp(i\omega t)$$
 (5)

is the Fourier transform of the signal $f_1(t)$. Fourier transformation of Eq.(4) leads to

$$\mathbf{F}(\omega) = \left[1 + 2\mathbf{R} \mathbf{e}^{-\mathbf{i}\omega \mathbf{D}} + \mathbf{R}^2 \mathbf{e}^{-\mathbf{i}2\omega \mathbf{D}} \right] \mathbf{F}_1(\omega) \tag{6}$$

The signal transmitted by the chirp radar $f_0(t)$ is a linear frequency-modulated pulse defined as:

where ω_c is the angular carrier frequency, T_o is half the pulse width, and m is the parameter determining the extent of frequency modulation.

On reception the signal passes through a matched filter whose transfer function $H(\omega)$ is given as

$$H(\omega) = \exp\left[-\frac{i}{2m} (\omega_c - \omega)^2\right]$$
(8)

This results in an effective pulse compression [Cook. 1960; Cohen. 1987]^{5.6}. Denoting the signal after this filtering as g(t) and its Fourier transform as $G(\omega)$,

$$G(\omega) = H(\omega) F(\omega)$$
 (9)

On substituting Eq.(6) into Eq.(9)

$$G(\omega) = G_0(\omega) + G_1(\omega) e^{-i\omega D} + G_2(\omega) e^{-i2\omega D}$$
(10)

where

$$G_0(\omega) = H(\omega) F_1(\omega)$$
 (11a)

$$G_1(\omega) = 2 H(\omega) R F_1(\omega)$$
(11b)

$$G_2(\omega) - R^2 H(\omega) F_1(\omega)$$
 (11c)

Inverse Fourier transformation of Eq.(10) leads to

$$g(t) = g_0(t) + g_1(t+D) + g_2(t+2D)$$
 (12)

Notice that $g_0(t)$ is the direct signal while $g_1(t+D)$ and $g_2(t+2D)$ are the ground reflected signals with delays D and 2D respectively. Quite often in practice these delays are very small and are much less than the pulse width of the signal. This inevitably results in an interference pattern that can be detrimental to radar detection and tracking. Clearly this problem is most acute when $g_1(t)$ or $g_2(t)$ is of the same magnitude as $g_0(t)$. For this reason, a significant part of this report will be devoted to the study of $g_1(t)$ and $g_2(t)$ for various kinds of rough surfaces.

In Section 3 we study the direct signal (Figure 1a). As mentioned above there are two ground reflected signals :- $g_1(t)$ and $g_2(t)$. One ground reflection is involved in $g_1(t)$ whereas $g_2(t)$ undergoes two such reflections (Figure 1d). These reflections are indeed coherent reflections and they invariably depend on the statistical

characteristics of the surface under consideration. In fact the coherent reflection coefficient R is given as $\chi(v_z)$ [Beckmann and Spizzichino. 1963]⁷ where χ is the characteristic function and $v_z = 2 \omega \sqrt{\mu_0} \sqrt{\epsilon_0} \cos \theta$. We consider several statistical distributions and in each case study the characteristics of ground reflected signals. The characteristic functions of the four statistical distributions considered in this report are given in Appendix A. The corresponding coherent reflection coefficients are given in Appendix B. Section 4 is devoted to the analysis of $g_1(t)$. For each statistical distribution, explicit expressions are derived for $g_1(t)$. In Section 5 similar expressions for $g_2(t)$ are obtained for normal and exponential distributions. The results thus obtained are studied in comparison to one another in Section 6. The conclusions are presented in Section 7.

3. DIRECT SIGNAL

Since we have assumed that the target has unit reflectivity. the direct signal $f_1(t)$ is identical to the transmitted signal $f_0(t)$ apart from the time delay, which depends on the range. For the analysis in this report, this time delay is irrelevant. We therefore let $f_1(t) = f_2(t)$. Thus

$$F_{1}(\omega) = \int_{0}^{1_{0}} dt \exp \left(-i(\omega_{c}t+0.5mt^{2})\right) e^{i\omega t}$$
(13)
- T₀

It follows from Eq.(11a) that

$$g_0(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega H(\omega) F_1(\omega) e^{-i\omega t}$$

$$-\frac{1}{2\pi}\int_{-\infty}^{\infty}d\omega \exp\left(-\frac{1}{2m}(\omega_{c}-\omega)^{2}\right)e^{-i\omega t}$$

$$\int_{-T_{o}}^{T_{o}} dr \exp \left(-i(\omega_{c}r + 0.5 mr^{2})\right) e^{i\omega r}$$

$$-\frac{1}{2\pi} \exp\left(-\frac{i}{2\pi} \omega_{c}^{2}\right) \int_{T_{o}}^{T_{o}} dr \exp\left(-i(\omega_{c}r + 0.5 mr^{2})\right) A_{1} \qquad (14)$$

where

$$A_{1} = \int_{-\infty}^{\infty} d\omega \exp \left(-\frac{i}{2m} (\omega^{2} - 2\omega\omega_{c}) - i\omega(t - \tau)\right)$$
$$= \left(2\pi m\right)^{.5} e^{-i\pi/4} \exp \left[\frac{i}{2m} (\omega_{c} - mt + m\tau)^{2}\right]$$
(15)

On substituting Eq.(15) into Eq.(14) and evaluating the integral we obtain

$$g_0(t) = \left(\frac{m}{2\pi}\right)^{.5} \exp\left[i\left(.5mt^2 - \omega_c t - \pi/4\right)\right] 2 T_0 \sin \left[mT_0 t\right]$$
 (16)

Thus the direct signal has the anticipated sharp peak at t = 0 and a 4 dB pulse width of $\frac{\pi}{m\Gamma_0}$. Noting that the pulse width of the transmitted signal is 2T_o we see that the ratio of pulse compression achieved is $2mT_o^2/\pi$.

4. GROUND REFLECTED SIGNAL I

Taking the inverse Fourier transform of Eq.(11b) we get

$$g_{1}(t) - \frac{1}{2\pi} \int_{\infty}^{\infty} d\omega \ 2R \ H(\omega) \ F_{1}(\omega) \ e^{-i\omega t}$$
(17)

We note that the reflection coefficient R for a normal distribution is nondispersive since its statistical characteristics are symmetrical. However, in applications, one notices that many surfaces do not possess this property. To study such situations we consider as examples three other distributions that have asymmetric characteristics. The reflection coefficients R associated with these statistical distributions are given in Appendix B. Below we analyze each case for the ground reflected signal I.

4.1 Normal Distribution

Substituting Eqs.(8), (13) and (B3) into Eq.(17) we get

$$g_{1}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \exp\left[-.5\alpha^{2}\omega^{2} - \frac{1}{2m} \left(\omega_{c}^{-}\omega\right)^{2}\right]$$

$$\cdot \int_{T_{0}}^{T_{0}} dr \exp \left(-i\omega_{c}r - .5imr^{2} + i\omega r - i\omega t\right)$$
(18a)
$$- \frac{1}{\pi} \exp \left[-\frac{1}{2m}\omega_{c}^{2}\right]$$
$$\cdot \int_{T_{0}}^{T_{0}} dr \exp \left(-i\omega_{c}r - .5imr^{2}\right) A_{2}$$
(18b)

where we have used Eq.(B3) which gives $R = \exp(-0.5\alpha^2\omega^2)$ for the reflection coefficient.

$$\alpha = 2 \left(\mu_{0} \varepsilon_{0}\right)^{0.5} \sigma \cos \theta.$$

$$A_{2} = \int_{-\infty}^{\infty} d\omega \exp \left[-\left(\frac{\alpha^{2}}{2} - \frac{1}{2m}\right)\omega^{2} - i\left(t - r - \omega_{c}/m\right)\right]$$

$$-\left(\pi/p_{0}\right)^{.5} \exp \left[-\frac{1}{4p_{0}}\left(\omega_{c}/m + r - t\right)^{2}\right]$$
(19)

and where

$$p_0 = .5\alpha^2 + \frac{i}{2m}$$
 (20)

Substituting Eq.(19) back into Eq.(18) and simplifying, we obtain

$$g_1(t) = (\pi p_0)^{-.5} \exp \left[-\frac{i}{2m} \omega_c^2 - \frac{1}{4p_0} (t - \omega_c/m)^2 \right] A_3$$
 (21)

where

$$A_{3} = \int_{T_{0}}^{T_{0}} dr \exp \left(- a_{1}r^{2} - b_{1}r \right)$$
(22)

$$a_1 = \frac{im}{2} + \frac{1}{4p_0}$$
 (23a)

and

$$b_1 - \omega_c \left(i + \frac{1}{2p_0^m} \right) - \frac{t}{2p_1}$$
 (23b)

The integral in Eq.(22) may readily be expressed in terms of error functions as follows

$$A_{3} = 0.5 \left(\pi/a_{1} \right)^{0.5} \exp \left[\frac{b_{1}^{2}}{4a_{1}} \right]$$

$$\cdot \left\{ erf \left[\sqrt{a_{1}^{2}} \left(T_{o}^{+} \frac{b_{1}}{2a_{1}} \right) \right] - erf \left[\sqrt{a_{1}} \left(- T_{o}^{+} \frac{b_{1}}{2a_{1}} \right) \right] \right\}$$
(24)

Thus the explicit solution for the ground reflected signal I for a normal distribution of the ground surface is contained in Eqs.(21), (23) and (24).

4.2 Exponential Distribution

From Eqs.(8), (13), (B5) and (17) we get

$$g_{1}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \frac{e^{-i\alpha\omega}}{1-i\alpha\omega} \ \exp\left[-\frac{i}{2m} \left(\omega_{c}^{-}\omega\right)^{2}\right]$$

$$\int_{-T_{o}}^{T_{o}} dr \exp \left(-i\omega_{c}r - .5imr^{2} - i\omega r - i\omega t\right)$$

$$-\frac{1}{\pi} \exp\left[-\frac{i}{2m}\omega_{c}^{2}\right]$$

$$\int_{-T_0}^{T_0} d\tau \exp\left(-i\omega_c \tau - .5im\tau^2\right) A_4$$
(25)

where

$$A_{4} = \int_{\infty}^{\infty} d\omega \frac{1}{1 - i\alpha\omega} \exp\left(-i\omega^{2} + ib\omega\right)$$
(26)

where

$$a = \frac{1}{2m}$$
(27a)

$$\mathbf{b} = \omega_c / \mathbf{n} + \mathbf{r} - \mathbf{t} - \boldsymbol{\alpha} \tag{27b}$$

Integration of Eq.(26) results in

$$A_{4} = - \exp \left[i\frac{b^{2}}{4a}\right] \frac{\pi}{\alpha} \exp\left(-2a\beta_{1}^{2}\right) \operatorname{erfc}\left(i/(2a)\beta_{1}\right)$$
(28)

where

$$\beta_{1} = 0.5 \left\{ \left[\frac{b}{2a} - \frac{1}{\alpha} \right] + i \left[\frac{b}{2a} + \frac{1}{\alpha} \right] \right\}$$
(29)

Substituting Eq.(28) in Eq.(25)

$$g_{1}(t) = -\frac{1}{\alpha} \exp\left[-\frac{i}{2m} \omega_{c}^{2}\right]$$

$$\cdot \int_{-T_{o}}^{T_{o}} dr \exp\left(-i\omega_{c}r - .5imr^{2}\right)$$

$$\exp\left[\frac{\mathbf{i} - \mathbf{b}^2}{4\mathbf{a}} - 2\mathbf{a}\beta_1^2\right] \operatorname{erfc}\left(\mathbf{i}/(2\mathbf{a}) \beta_1\right) \quad (30)$$

Use of Eq. (27b) leads to the simplified form:

$$g_1(t) = -\frac{1}{\alpha} \exp\left[-\frac{1}{2m}\omega_c^2 + i\frac{\Omega_1}{4a}\right] A_5$$
 (31)

where

$$\Omega_{1} = \omega_{c}/m - t - \alpha$$
(32)

$$A_{5} = \int_{T_{0}}^{T_{0}} dr \exp \left(-imr(t+\alpha)\right)$$

$$\exp \left[-2\alpha\beta_{1}^{2}\right] \operatorname{erfc} \left(i\sqrt{(2\alpha)}\beta_{1}\right)$$
(33)

It does not appear possible to express A_5 in terms of known functions. But we note the following. Since $\omega_c - mt - m\alpha \ge mr$ in our domain of interest, namely, $T_0 \le t$, if $\tau \le T_0$ it is clear that

 $\exp\left[-2a\beta_{1}^{2}\right]$ erfc $\left(\frac{i}{(2a)\beta_{1}}\right)$ is a slowly varying function of τ . We therefore approximate it by its mean value

$$\exp\left[-2a\beta_2^2\right] \operatorname{erfc}\left(i\sqrt{(2a)}\beta_2\right)$$

where

$$\beta_2 = 0.5 \left\{ \left[\frac{\Omega_1}{2a} - \frac{1}{\alpha} \right] + i \left[\frac{\Omega_1}{2a} + \frac{1}{\alpha} \right] \right\}$$
(34)

When this approximation is used. Eq.(33) becomes

$$A_5 = \exp\left[-2a\beta_2^2\right] \operatorname{erfc}\left(i\sqrt{(2a)}\beta_2\right)A_6 \tag{35}$$

$$A_{6} = \int_{T_{0}}^{T_{0}} dr \exp \left(-imr(t+\alpha)\right)$$

$$= 2T_{0} \operatorname{sinc}\left(mT_{0}(t+\alpha)\right)$$
(36)

Thus from Eqs. (31), (35), and (36)

$$g_{1}(t) = -\frac{1}{\alpha} \exp\left[-\frac{1}{2m}\omega_{c}^{2} + i\frac{\Omega_{1}^{2}}{4a}\right]$$

$$\cdot \exp\left[-2a\beta_{2}^{2}\right] \operatorname{erfc}\left(\frac{1}{(2a)\beta_{2}}\right)$$

$$\cdot 2 T_{a} \operatorname{sinc}\left(\pi T_{a}(t+\alpha)\right) \qquad (37)$$

4.3 Rayleigh Distribution

Using Eqs.(8), (13), and (B6) in Eq.(17) we get

$$g_{1}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \exp\left[-\frac{i}{2\pi} (\omega_{c} - \omega)^{2}\right]$$

$$\cdot \left\{1 + \frac{i}{2\pi} (\omega_{c} - \omega)^{2}\right\}$$

$$\cdot \int_{-\pi}^{T_{0}} dr \ \exp\left(-\frac{i}{2\pi} (-\frac{i}{2} (\omega_{c} - \frac{i}{2} (\omega_{c} - \omega_{c})^{2})\right)$$
(38)

$$-\frac{1}{\pi} \exp\left[-\frac{1}{2m}\omega_{c}^{2}\right]$$

$$-\int_{T_{0}}^{T_{0}} d\tau \exp\left(-i\omega_{c}\tau - .5im\tau^{2}\right)\left(I_{1}+I_{2}+I_{3}\right) \qquad (39)$$

$$I_{1} = \int_{\infty}^{\infty} d\omega \exp\left[i\omega(r-t) - \frac{i}{2m} \left(\omega^{2} - 2\omega\omega_{c}\right) - i\sqrt{\pi\alpha\omega}\right]$$
(40a)

$$I_{2} = \int_{-\infty}^{\infty} d\omega \exp\left[i\omega(\tau - t) - \frac{i}{2m} \left(\omega^{2} - 2\omega\omega_{c}\right)\right]$$

$$\cdot i\sqrt{\pi}\omega \exp\left(-i\sqrt{\pi}\omega - \overline{\alpha}^{2}\omega^{2}\right) \qquad (40b)$$

$$I_{3} = \int_{\infty}^{\infty} d\omega \exp \left[i\omega(r-t) - \frac{i}{2m} \left(\omega^{2} - 2\omega \omega_{c} \right) \right]$$

• $i\sqrt{\pi} \alpha \omega \exp \left(- i\sqrt{\pi} \alpha \omega - \overline{\alpha}^{2} \omega^{2} \right) \exp(-i\alpha \omega)$ (40c)

 I_1 and I_2 may be readily evaluated in terms of elementary functions as follows:

$$I_{1} = (2\pi m)^{.5} \exp \left[-i\pi/4 + i\frac{m}{2} \left(\omega_{c}/m + \tau - t - \sqrt{\pi \alpha} \right)^{2} \right]$$
(41)

$$I_{2} = -i\tilde{\alpha}\pi \frac{b_{2}}{2a_{2}^{1.5}} \exp\left[\frac{b_{2}^{2}}{4a_{2}}\right]$$
(42)

where

$$\mathbf{a}_2 = \overline{\alpha}^2 + \frac{\mathbf{i}}{2\mathbf{n}} \tag{43a}$$

$$b_2 = -i \left(\omega_c /m + r - t - \sqrt{\pi \alpha} \right)$$
(43b)

It turns out that I_3 can be expressed in terms of a confluent hypergeometric function.

$$I_{3} = -\frac{2\bar{\alpha}^{2}}{a_{2}^{1.5}} *_{1} \left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; \frac{-\bar{\alpha}^{2}}{a_{2}}, \frac{b_{2}^{2}}{a_{2}} \right]$$
(44)

$$\Psi_{1}(a,b;c,c';z,\zeta) = \sum_{k=0}^{\infty} \sum_{\ell=0}^{\infty} \frac{(a)_{k+\ell}(b)_{k}}{(c)_{k}(c')_{\ell}} \frac{z^{k}\zeta^{\ell}}{k!\ell!}$$
(45)

$$(a)_{k} = \frac{\Gamma(a+k)}{\Gamma(a)}$$
(46)

With these results we can write $g_1(t)$ as

$$g_1(t) = \frac{1}{\pi} \exp\left[-\frac{1}{2m} \omega_c^2\right] [J_1 + J_2 + J_3]$$
 (47)

where

$$J_{\ell} = \int_{0}^{T_{o}} dr \exp \left(-i\omega_{c}r - .5imr^{2}\right) I_{\ell}, \ \ell = 1, 2, 3$$
(48)

J₁ is readily evaluated as

$$J_{1} = (2\pi m)^{5} 2T_{0} \exp\left[-i\pi/4 + i\frac{m}{2}\Omega_{2}^{2}\right] \operatorname{sinc}\left[\left(t + \sqrt{\pi \alpha}\right)mT_{0}\right]$$
(49)

$$\Omega_2 = \omega_c^{-} \text{ mt} = m/\pi \overline{\alpha}$$
 (50)

After some rearrangements \boldsymbol{J}_2 may be written as

$$J_{2} = -\tilde{\alpha}\pi \left(\frac{1}{m}\right) \frac{1}{2a_{2}^{1.5}} \exp\left[\frac{\Omega_{2}^{2}}{4a_{2}m^{2}}\right] B$$
(51)

_

where

$$B = \int_{T_0}^{T_0} dr \ (mr + \Omega_2) \ \exp\left(-a_3 r^2 - b_3 r\right)$$
(52)

and where

$$a_3 = \frac{1}{4a_0} + \frac{im}{2}$$
 (53a)

$$\mathbf{b}_3 = \frac{\Omega_2}{2\mathbf{a}_0^{\mathbf{m}}} + \mathbf{i}\omega_{\mathbf{c}} \tag{53b}$$

$$\mathbf{a}_0 = \tilde{\alpha}^2 + \frac{\mathbf{i}}{2\mathbf{m}}$$
(53c)

On evaluating the integral in Eq. (52).

$$B = \exp\left[\frac{b_3^2}{4a_3}\right] (j_1 + j_2)$$
 (54)

where

$$j_{1} = \frac{n}{2a_{3}} \left\{ \exp\left[-a_{3}\left(-T_{0} + \frac{b_{3}}{2a_{3}}\right)^{-5}\right] - \exp\left[-a_{3}\left(T_{0} + \frac{b_{3}}{2a_{3}}\right)^{-5}\right] \right\}$$
(55a)
$$j_{2} = \left[\alpha_{2} - \frac{nb}{2a_{2}}\right] \frac{1}{2} \left(\frac{\pi}{a_{3}}\right)^{-5} \left[\exp\left[-a_{3}\left(T_{0} + \frac{b_{3}}{2a_{3}}\right)^{-5}\right] \right]$$
(55b)

It is apparent that the integral in J_3 is too complicated for analytic evaluation. But since $\omega_c/m - t - \sqrt{\pi \alpha} \ge \tau$ in $-T_0 \le \tau, t \le T_0$ we note that Ψ_1 is a slowly varying function of τ in the domain of the integrand. This enables us to approximate

$$\Psi_{1}\left[\frac{3}{2},\frac{1}{2};\frac{3}{2},\frac{3}{2};\frac{3}{2};\frac{\overline{\alpha}^{2}}{a_{2}},\frac{b_{2}^{2}}{4a_{2}}\right] \text{ by its mean value}$$
$$\Psi_{1}\left[\frac{3}{2},\frac{1}{2};\frac{3}{2},\frac{3}{2};\frac{\overline{\alpha}^{2}}{a_{2}},-\frac{\Omega_{2}^{2}}{a_{2}}\right].$$

Thus

$$J_{3} = -\frac{\sqrt{\pi \alpha^{2}}}{a_{2}^{1.5}} \Psi_{1} \left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; \frac{3}{2}; \frac{-\alpha^{2}}{a_{2}}, -\frac{\alpha^{2}}{4a_{2}} \right] A_{7}$$
(56)

where

$$A_{7} = \int_{T_{0}}^{T_{0}} dr \exp \left(-i\omega_{c}r - .5imr^{2}\right)$$

$$= \exp \left[i\frac{\omega_{c}^{2}}{2m}\right] \frac{1}{2} (\pi/m)^{-5} (1-i)$$

$$\left\{ erf \left[.5/m (1+i)\left(T_{0}+\omega_{c}/m\right)\right] \right]$$

$$= erf \left[.5/m (1+i)\left(-T_{0}+\omega_{c}/m\right)\right] \right\}$$
(57)

Equation (47), together with Eqs.(49), (51), (54), (55), (56), and (51) provide the explicit solution for the $g_1(t)$.

4.4 Skew-Normal Distribution

Substituting Eqs.(8), (13), and (B8) into Eq.(17) we have

$$g_{1}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \exp\left[-\frac{1}{2m} \left(\omega_{c}-\omega\right)^{2}\right]$$

$$\cdot \frac{1}{2\sigma} \exp\left[i\left(\frac{2}{\pi}\right)^{.5} (\alpha_{1}-\alpha_{2}) \omega\right]$$

$$\cdot \left\{\sigma_{1} \exp\left(-.5\alpha_{1}^{2} \omega^{2}\right) \operatorname{erfc}\left[-\frac{1}{\sqrt{2}} \alpha_{1}\omega\right]$$

$$+ \sigma_{2} \exp\left(-.5\alpha_{2}^{2} \omega^{2}\right) \operatorname{erfc}\left[-\frac{1}{\sqrt{2}} \alpha_{2}\omega\right]\right\}$$

$$\cdot \int_{-T_{0}}^{T_{0}} \operatorname{dr} \exp\left(-i\omega_{c}\tau - .5\operatorname{im}\tau^{2} + i\omega\tau - i\omegat\right) \qquad (58)$$

Let

$$g_1(t) = s_1(t) + s_2(t)$$
 (59)

$$s_{1}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \exp\left[-\frac{i}{2\pi} \left(\omega_{c} - \omega\right)^{2}\right]$$
$$\cdot \frac{1}{2\sigma} \exp\left[i\left(\frac{2}{\pi}\right)^{.5} \left(\alpha_{1} - \alpha_{2}\right)\omega\right]$$
$$\cdot \sigma_{1} \exp\left(-.5\alpha_{1}^{2}\omega^{2}\right) \operatorname{erfc}\left[-\frac{i}{\sqrt{2}}\alpha_{1}\omega\right]$$

•
$$\int d\tau \exp\left(-i\omega_{c}\tau - .5im\tau^{2} + i\omega\tau - i\omegat\right)$$
 (60a)
- T_{0}

$$s_{2}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \ 2 \ \exp\left[-\frac{1}{2m} \left(\omega_{c} - \omega\right)^{2}\right]$$

$$\cdot \frac{1}{2\sigma} \exp \left[i \left(\frac{2}{\pi} \right)^{.5} (\alpha_1^{-} \alpha_2^{-}, \omega \right] \right]$$

•
$$\sigma_2 \exp\left(-.5\alpha_2^2 \omega^2\right) \operatorname{erfc}\left[\frac{\mathrm{i}}{\sqrt{2}}\alpha_2\omega\right]$$

$$\int_{-T_0}^{T_0} dr \exp\left(-i\omega_c r - .5imr^2 - i\omega r - i\omega t\right)$$
 (60b)

Let us first consider $s_1(t)$. The RHS of Eq.(60a) may be rearranged as follows.

$$s_1(t) = \frac{\sigma_1}{2\pi\sigma} \int_{T_0}^{T_0} dr \exp\left(-i\omega_c r - .5imr^2\right) A_8$$
 (61)

where

$$A_{8} = \int_{-\infty}^{\infty} d\omega \exp \left[-\frac{i}{2m} \left(\omega_{c}^{-} \omega \right)^{2} + i\omega(r-t) \right]$$

$$\cdot \exp \left[-.5\alpha_{1}^{2} \omega^{2} + i \left(\frac{2}{\pi} \right)^{.5} (\alpha_{1}^{-} \alpha_{2}) \omega \right] \operatorname{erfc} \left[-\frac{i}{\sqrt{2}} \alpha_{1} \omega \right]$$

$$= \exp \left[-\frac{i}{2m} \omega_{c}^{2} \right] \int_{-\infty}^{\infty} d\omega \exp \left(-p_{1} \omega^{2} - q_{1} \omega \right) \operatorname{erfc} \left(\gamma_{1} \omega \right)$$

and where

$$p_1 = .5(\alpha_1^2 + i/m)$$
 (63a)

$$q_1 = -i \left[\frac{\omega_c}{m} + \left(\frac{2}{m} \right)^{.5} (\alpha_1 - \alpha_2) + r - t \right]$$
(63b)

and

$$\gamma_1 = -i\alpha_1//2$$
 (63c)

The integral in Eq.(62) may be represented in terms of the hypergeometric function mentioned earlier.

$$A_{8} = \exp \left[-\frac{1}{2m} \omega_{c}^{2} \right] \left\{ \left(-\frac{\pi}{p_{1}} \right)^{.5} \exp \left[-\frac{q_{1}^{2}}{4p_{1}} \right] + \frac{\gamma_{1}q_{1}}{p_{1}^{1.5}} \psi_{1} \left[-\frac{3}{2} , \frac{1}{2} ; \frac{3}{2} , \frac{3}{2} ; -\frac{\gamma_{1}^{2}}{p_{1}} , \frac{q_{1}^{2}}{4p_{1}} \right] \right\}$$

$$(64)$$

Substituting Eq.(64) into Eq.(61) and rearranging we get

$$s_1(t) = .5(\pi p_1)^{-.5} \frac{\sigma_1}{\sigma} \exp\left[-\frac{1}{2m} \omega_c^2 - \frac{\Omega^2}{4p_1}\right] A_3(\alpha_1, b_1)$$

$$+ \frac{\sigma_1}{2\pi\sigma} \exp\left[-\frac{i}{2m} \omega_c^2\right] A_g \tag{65}$$

where

$$\Omega = \frac{\omega_c}{m} + \left(\frac{2}{m}\right)^{.5} (\alpha_1 - \alpha_2) - t$$
(66)

$$a_1 = .25/p_1 + i.5m$$
 (67a)

$$b_1 = .5\Omega/p_1 + i\omega_c \tag{67b}$$

and

$$A_{9} = -\int_{T_{0}}^{T_{0}} d\tau \exp\left(-i\omega_{c}\tau - .5i\pi\tau^{2}\right)$$

$$\frac{\gamma_{1}q_{1}}{p_{1}^{1.5}} = \Psi_{1}\left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; -\frac{\gamma_{1}^{2}}{p_{1}}, \frac{q_{1}^{2}}{4p_{1}}\right]$$
(63)

Note that A_3 is the same integral as in Eq.(22) - Only the variables are now different. Here the result may immediately be obtained from Eq.(24). In the integral in Eq.(68) we may employ the same approximation as before. namely. identify the slowly varying part of the integrand by its mean value. To be more specific.

$$q \Psi_{1} \left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; -\frac{\gamma_{1}^{2}}{p_{1}}, \frac{q_{1}^{2}}{4p_{1}} \right]$$

$$= -i \Omega \Psi_{1} \left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; -\frac{\gamma_{1}^{2}}{p_{1}}, -\frac{\Omega^{2}}{4p_{1}} \right] \quad (69)$$

Thus

$$A_{9} = -i \Omega \frac{\gamma_{1}}{p_{1}^{1.5}} \Psi_{1} \left[\frac{3}{2}, \frac{1}{2}; \frac{3}{2}, \frac{3}{2}; -\frac{\gamma_{1}^{2}}{p_{1}}, -\frac{\Omega^{2}}{4p_{1}} \right] A_{7}$$
(70)

Equation (65) along with Eqs.(70) and (57) provides the solution for $s_1(t)$.

We note from Eq.(60) that the integrand in $s_2(t)$ is very similar in structure to that in $s_1(t)$. Thus the procedure for evaluating $s_2(t)$ is identical to that of $s_1(t)$. We therefore omit the steps and simply present the results.

$$s_{2}(t) = .25 \left(\alpha_{2} p_{2} \right)^{-.5} \frac{\sigma_{2}}{\sigma} \exp \left[-\frac{i}{2m} \omega_{c}^{2} - \frac{\Omega^{2}}{4p_{2}} + \frac{b_{2}}{4\alpha_{2}} \right] \\ \left[\operatorname{erf} \left\{ \int \alpha_{2} \left[T_{o} + \frac{b_{2}}{2\alpha_{2}} \right] \right\} - \operatorname{erf} \left\{ \int \alpha_{2} \left[-T_{o} + \frac{b_{2}}{2\alpha_{2}} \right] \right\} \right] \\ - .25 \Omega \left(\pi m \right)^{-.5} \frac{\sigma_{2}}{\sigma} \frac{\gamma_{2}}{p_{2}^{1.5}} (1+i) \Psi_{1} \left[\frac{3}{2} , \frac{1}{2} ; \frac{3}{2} , \frac{3}{2} ; -\frac{\gamma_{2}^{2}}{p_{2}} , \frac{\Omega^{2}}{4p_{2}} \right] \\ \left\{ \operatorname{erf} \left[.5 \sqrt{m} (1+i) \left[T_{o} + \omega_{c} / m \right] \right] \right\}$$
(71)

where

$$a_{2} = .25/p_{2} + i.5m$$
 (72a)

$$L_2 = .5\Omega/p_2 + i\omega_c \tag{72b}$$

$$p_2 = .5(\alpha_2^2 + i/m)$$
 (72c)

$$\gamma_2 = i\alpha_2//2 \tag{72d}$$

This completes our derivation for $g_1(t)$.

5. GROUND REFLECTED SIGNAL-II

On taking the inverse Fourier transform of Eq.(11c)

$$g_{2}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega R^{2} H(\omega) F_{1}(\omega) e^{-i\omega t}$$
(73)

In this section we evaluate Eq.(73) for two cases - normal distribution and exponential distribution.

5.1 Normal Distribution

Substituting Eqs.(8), (13) and (B3) into Eq.(73) we have

$$g_{2}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega e^{-i\omega t} \exp\left[-\frac{i}{2m} (\omega_{c}^{2} - \omega) - \alpha^{2} \omega^{2}\right]$$

$$= \int_{0}^{T_{o}} dr \exp\left\{-i\omega_{c}\tau - .5im\tau^{2} + i\omega\tau\right\}$$
(74)

On comparing Eq.(74) with Eq.(18a) we can immediately write down the result as

$$g_2(t) = .5 g_1(t, 2\alpha^2)$$
 (75)

5.2 Exponential Distribution

From Eqs.(8), (13), (B5) and (73) we have

$$g_{2}(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} d\omega \left\{ \frac{e^{-i\tilde{\alpha}\omega}}{1-i\tilde{\alpha}\omega} \right\}^{.5} \exp\left[-\frac{i}{2\pi} (\omega_{c}^{-} \omega)^{2}\right]$$

$$\int_{T_0}^{T_0} dr \exp\left\{-i\omega_c r - .5imr^2 + i\omega(r - t)^2\right\}$$

$$-\frac{1}{2\pi} \exp\left[-\frac{i}{2m} \omega_{c}^{2}\right]$$

$$\cdot \int_{T_0}^{T_0} dr \exp\left\{-i\omega_c \tau - .5imr^2\right\} B_1$$
(76)

where

$$B_{1} = \int_{\infty}^{\infty} d\omega \left\{ \frac{e^{-i\tilde{\alpha}\omega}}{1-i\tilde{\alpha}\omega} \right\}^{2} \exp\left[-\frac{i}{2m} (\omega_{c}^{-} 2\omega\omega_{c})^{2} + i\omega(r-t) \right]$$

$$= \frac{2\pi}{\tilde{a}^2} \exp\left\{ .251\pi + .251\tilde{b}^2/a \right\}$$

$$\left[\left(\frac{\mathbf{a}}{\pi}\right)^{.5} - \mathbf{i} \mathbf{a} \beta_2 \exp\left(-\mathbf{a} \beta_2^2\right) \operatorname{erfc}\left(\mathbf{i} \beta_2 \sqrt{\mathbf{a}}\right)\right]$$
(77)

where

$$\mathbf{\tilde{b}} = \mathbf{b} = \alpha \tag{78a}$$

$$\beta_2 = e^{i\pi/4} \left[\frac{\tilde{b}}{2a} + \frac{i}{\alpha} \right]$$
(78b)

Substituting Eq.(77) into Eq.(76) and simplifying we get

$$g_{2}(t) = \frac{1}{\tilde{\alpha}^{2}} \exp \left\{ 25i\pi - \frac{i}{2m} \omega_{c}^{2} + .5i\Omega_{3}^{m} \right\} \left[\left(\frac{a}{\pi} \right)^{.5} s_{1}^{+} s_{2}^{-} \right]$$
(79)

$$s_{1} = \int_{T_{0}}^{T_{0}} dr \exp \left\{-\operatorname{im} r(t+2\alpha)\right\}$$
(80a)

$$s_{2} = -ia \int_{T_{0}}^{T_{0}} d\tau \exp \left\{ -im\tau(t+2\alpha) \right\}$$
$$\cdot \beta_{2} \exp(-a\beta_{2}^{2}) \operatorname{erfc}(i\beta_{2}\sqrt{a})$$
(80b)

$$\Omega_3 - \Omega_1^{-\alpha}$$
 (80c)

Let us first consider the integral in Eq.(80b). Notice that $\operatorname{erfc}(i\beta_2 \sqrt{a})$ is a slowly varying function of τ and hence may be approximated by its mean value $\overline{\beta}_2 \exp(-a\overline{\beta}_2^2) \operatorname{erfc}(i\overline{\beta}_2/a)$. Here

$$\tilde{\beta}_2 = e^{i\pi/4} \left[\frac{\Omega_3}{2a} + \frac{i}{\tilde{a}} \right]$$
(81)

Thus

$$\mathfrak{I}_2 = -ia\overline{\beta}_2 \exp(-a\overline{\beta}_2^2) \operatorname{erfc}(i\overline{\beta}_2/a) \mathfrak{I}_1$$
 (82)

f, is readily evaluated as

$$S_{1} = 2 T_{o} \operatorname{sinc} \left(m(t+2\tilde{a})T_{o} \right)$$
(83)

Putting all these together

$$g_{2}(t) = \frac{1}{\tilde{\alpha}^{2}} \exp\left\{ 25i\pi - \frac{i}{2m} \omega_{c}^{2} + .5i\Omega_{3}^{m} \right\}$$

$$\left[\left(\frac{a}{\pi}\right)^{.5} - ia\tilde{\beta}_{2} \exp(-a\tilde{\beta}_{2}^{2}) \operatorname{erfc}(i\tilde{\beta}_{2}\sqrt{a}) \right] \mathfrak{I}_{1} \qquad (84)$$

6. DISCUSSION

In Sections 4 and 5 we have calculated the ground reflected signal of the chirp radar generated by four different statistical distributions. In this section we analyze these results and offer some physical interpretations. We first look at GRS-I.

6.1 Ground Reflected Signal - I

For normal distribution $g_1(t)$ is given by Eqs.(21) and (24). Although it is elementary to compute this expression to obtain a numerical value, the present form does not offer a physically transparent picture. In other words, the characteristics of the results are not immediately evident from the expressions in Eqs.(21) and (24).

One way to gain insight is to examine the local behavior. Recall that the signal has a peak at t = 0. Moreover our primary interest is in the study of the relative amplitude of the ground reflected signal with respect to the direct signal. We therefore look at the case when t = 0. We further simplify our task by restricting our attention to the region where $\alpha^2 \omega_c^2 < 1$. Thus to a first order in $\alpha^2 \omega_c^2$

$$g_1(0) = 2\left(\frac{2\pi}{\pi}\right)^{.5} T_0\left[1-.5\alpha^2\omega_c^2\right]$$
 (85)

Note that $\alpha \omega_c$ is the Rayleigh parameter. Hence $\alpha^2 \omega_c^2 < 1$ refers to the small roughness region. When $\alpha \omega_c = 0$, that is, when the surface is perfectly smooth, Eq.(85) reduces to

$$|g_1(0)| = 2T_0 (2m/\pi)^{.5}$$
 (86)

Also from Eq.(16) we see that

$$|g_0(0)| = T_0 (2m/\pi)^{-5}$$
(87)

This implies that

 $|g_1(0)| - 2 |g_0(0)|$ (88)

From Appendix B it is clear that when $\alpha\omega_{c} = 0$, R = 1, hence it follows that

$$g_1(t) = 2g_0(t)$$
 (89)

Thus it is seen that Eq.(85) is in agreement with Eq.(89). Also, Eq.(85) suggests that $|g_1(0)|$ should decrease with increasing $\alpha\omega_c$. This is in agreement with the physical fact that the coherent return should decrease with an increase in surface roughness.

We turn our attention now to the exponential case. As before we look at the special case when $\alpha^2 \omega_c^2 < 1$ and t = 0. It turns out that to a first order in $\alpha^2 \omega_c^2$. $|g_1(0)|_{exp}$ has the same expression as Eq. (85). This means that to a first order in $\alpha^2 \omega_c^2$. coherent returns from normally distributed and exponentially distributed surfaces are identical.

It is apparent that the results obtained for surfaces with Rayleigh and skew-normal statistics have fairly complicated structures. Even from a computational point of view the resulting expressions in the above cases are unmanageable. It turns out that for parameters appropriate for our problem the series representation of the hypergeometric function is not suitable for actual computations. Unless further study of these special functions are undertaken the value of these results may not be fully appreciated.

6.2 Ground Reflected Signal - II

Consider the results obtained for normally distributed surfaces. When t = 0 and $\alpha^2 \omega_c^2 < 1$ we have

$$|g_{2}(0)| - T_{o} \left(\frac{2m}{\pi} \right)^{-5} \left\{ 1 - 2 \alpha^{2} \omega_{c}^{2} \right\}^{-1}$$
(90)

Notice that when $\alpha \omega_c = 0$, Eq.(90) leads to

$$|g_{2}(0)| - |g_{0}(0)| \tag{91}$$

which agrees with the physical fact that $g_2(t) = g_0(t)$ when $\alpha \omega_c = 0$. Apart from having all similar characteristics as the corresponding $|g_1(0)|$ we note from Eq.(90) that $|g_2(0)|$ decreases much faster with $\alpha \omega_c$ than $|g_1(0)|$.

6.3 Numerical Results

Figure 2 is a plot of the computed results for GRS-I. More specifically it is a plot of $|g_1(t)/g_0(t)|$ versus t. The parameters chosen are to an extent arbitrary but at the same time pertinent to our problem. The solid lines and the dotted lines correspond respectively to normal and exponential statistics. The main signal centered around t=0 is the compressed pulse. The rest are sidelobes. When $\alpha = 0.01$ (Figure 2a) the normal and the exponential results coincide and $|g_1(t)/g_0(t)|_{max} = 2$. Since $\alpha = 0.01$ corresponds to $\alpha\omega_c = 0.015$ both these results are in agreement with our predictions. When α = 0.07 or $\alpha\omega_c$ = 0.104 (Figure 2b) we still see that the normal and exponential results coincide. But notice now that the amplitude of the coherent signal is reduced. For further increase in α we note that $|g_1(t)/g_0(t)|_{normal}$ decreases faster than $|g_1(t)/g_0(t)|_{exponential}$. The point to note is that in some situations these results can be quite different from one another.













In Figure 3 we have plotted GRS-II. Recalling the fact that for $\alpha\omega_c = 0$, $g_2(t) = 2g_1(t)$ we have appropriately chosen the scale so that the results for $g_2(t)$ may be easily compared with those of $g_1(t)$. It is evident that $g_2(t)$ has all the characteristics of $g_1(t)$. But notice that the rate of decrease of $|g_2(t)|$ with $\alpha\omega_c$ is much higher than that of $|g_1(t)|$ - a fact clearly in agreement with our predictions.

In applications, one often models the ground as a normally distributed surface. This is primarily because such a model facilitates easy analysis. But there is growing experimental evidence that contradicts this assumption. For example, terrain and a large class of sea surfaces do not have the symmetric roughness geometry of a normally distributed rough surface. To be more precise, the valleys are often more shallow and the hills more steep.

The exponential distribution is a good candidate for an asymmetric rough surface. The results obtained in this report bear out that the assumption of normal statistics can be meaningful only when $\alpha\omega_c$ is small. Otherwise this assumption can lead to significant errors.

The exponential distribution is a rather extreme case of asymmetric distribution. A model more suitable for application is the Rayleigh distribution. For terrain, perhaps the most appropriate distribution to use is the skew-normal. Further study of the results pertaining to these models is left for future work.













7. CONCLUSION

In this report, the effects of ground reflections on frequency modulated signals were studied. On recognizing the detrimental effect on target detection caused by interference due to ground reflections our primary objective is to compute the relative amplitude of the ground reflected signals with respect to the direct signal. Four different surfaces are considered for the analysis of the ground reflected signals. Among them the normal distribution has symmetric characteristics while the other three are asymmetric. Due to the nonlinear nature of the matched filter, the received signals for various types of ground have quite different characteristics. Notice that the coherent reflection coefficients of the four surfaces have distinct frequency dependences. Explicit analytic expressions for the ground reflected signal I are provided for each of the four types of surfaces. For the sake of illustration we have compared the ground reflected signals for exponentially distributed and normally distributed surfaces. It is observed that when the Rayleigh parameter is very small the two results are very close to each other. For larger Rayleigh parameters the results are quite different from each other. This means that the universally accepted Gaussian model may at times lead to significant errors. We conclude therefore that for the study of scattering from rough surfaces a careful choice of the statistical distribution appropriate for the problem is essential.

References

- 1. Evans, G. C.(1966), Influence of ground reflections on radar targettracking accuracy, Proc. IEE, 113:1281-1286.
- Smith, P. G. and Mrstik, A. V. (1979). Multipath tracking errors in elevation-scanning and monopulse radars. <u>IEEE Trans. Aerosp.</u> <u>Electron. Syst.</u>. **AES-15**:765-776.
- 3. Barton, B. K. (1974), Low-angle radar tracking. Proc. IEEE, 62:687-704
- 4. Papa, R. J., Lennon, J. F., and Taylor, R. L.(1983), Multipath effects on an azimuthal monopulse system, <u>IEEE Trans. Aerosp.</u> <u>Electron. Syst.</u>, **AES-19**:585-597.
- 5. Cook, C. E. (1960), Pulse compression, key to more efficient radar. Proc. IRE, 48:310-316.
- 6. Cohen, M. W. (1987), Pulse Compression in Radar Systems, in <u>Principles of Modern Radar</u> edited by J. L. Eaves and E. K. Reedy, Van Nostrand, 465-501.
- 7. Beckmann, P. and Spizzichino, A. (1963). <u>The Scattering of</u> <u>Electromagnetic Waves from Rough Surfaces</u>. Pergamon, Oxford.

Appendix A

Characteristic Functions

In this appendix we consider four statistical distributions and obtain their characteristic functions. The characteristic function $\chi(q)$ is defined as:

$$\chi(q) = \int_{-\infty}^{\infty} d\xi \ p(\xi) \ \exp(iq\xi) \tag{A1}$$

where $p(\xi)$ is the probability density function of the height of the randomly rough surface. The rough surface has zero mean and a root mean square height of α .

A1. NORMAL DISTRIBUTION

$$p(\xi) = \frac{(2\pi)^{-.5}}{\sigma} \exp\left[\frac{-\xi^2}{2\sigma^2}\right]$$
(A2)

$$\chi(q) = \exp\left(-.5q^2\sigma^2\right) \tag{A3}$$

A2. EXPOSISIFIAL DISTRIBUTION

$$p(\xi) = \begin{cases} \frac{1}{\sigma} \exp\left(-\frac{(\xi+\sigma)}{\sigma}\right) ; & \xi \ge -\sigma \\ 0 & ; & \xi < -\sigma \end{cases}$$
(A4)

$$\chi(q) = \frac{e^{-iq\sigma}}{1-iq\sigma}$$
(A5)

A3. RAYLEIGH DISTRIBUTION

$$p(\xi) = \begin{cases} \frac{2c^2}{\sigma^2} \left[\xi + \frac{\sqrt{\pi\sigma}}{2c} \right] \exp\left\{ - (c/\sigma)^2 \left[\xi + \frac{\sqrt{\pi\sigma}}{2c} \right]^2 \right\} \\ for \ \xi \ge -\frac{\sqrt{\pi\sigma}}{2c} \\ 0 & otherwise \end{cases}$$

(A6)

.

$$c^2 = 1 - \pi/4$$
 (A7)

$$\chi(q) = \exp\left[-i\frac{\sqrt{\pi\sigma q}}{2c}\right]$$

$$\left\{1 + i\frac{\sqrt{\pi\sigma q}}{2c}\operatorname{erfc}\left[-i\frac{\sqrt{\pi\sigma q}}{2c}\right]\exp\left(-(.5q\sigma/c)^{2}\right) \quad (A8)\right\}$$

A4. SKEN-MORMAL DISTRIBUTION

$$p(\xi) = \begin{cases} \frac{1}{\sqrt{(2\pi)}\sigma} & \exp\left[-.5\left((\xi-a)/\sigma_1\right)^2\right]; \ \xi \ge a \\ \\ \frac{1}{\sqrt{(2\pi)}\sigma} & \exp\left[-.5\left((\xi-a)/\sigma_2\right)^2\right]; \ \xi < a \end{cases}$$
(A9)

where

$$a = (2/\pi)^{-5} (\sigma_2^{-} \sigma_1)$$
 (A10a)

· [---

$$\sigma = .5(\sigma_1 + \sigma_2) \tag{A10b}$$

$$\chi(\mathbf{q}) = \frac{1}{2\sigma} \exp (\mathbf{i}\mathbf{q}\mathbf{a})$$

$$\left\{ \sigma_1 \exp \left(-.5q^2\sigma_1^2\right) \operatorname{erfc}\left[-\frac{\mathbf{i}}{\sqrt{2}}q\sigma_1\right] + \sigma_2 \exp \left(-.5q^2\sigma_2^2\right) \operatorname{erfc}\left[-\frac{\mathbf{i}}{\sqrt{2}}q\sigma_2\right] \right\}$$
(A11)

Appendix B

Coherent Reflection Coefficient

The coherent reflection coefficient R is given by Beckmann and Spizzichino [1963]⁷ as

$$\mathbf{R} = \boldsymbol{\chi}(\mathbf{v}_{\tau}) \tag{B1}$$

where

$$v_z = 2 (\mu_0 \varepsilon_0)^{0.5} \omega \cos \theta$$
 (B2)

Since the characteristic functions for various statistical distributions are given in Appendix A the corresponding reflection coefficients may readily be obtained as follows.

B1. NORMAL DISTRIBUTION

$$R = \exp\left(-0.5\,\alpha^2\omega^2\right) \tag{B3}$$

where

$$\alpha = 2 \left(\mu_0 \varepsilon_0\right)^{0.5} \sigma \cos \theta \tag{B4}$$

B2. EXPONENTIAL DISTRIBUTION

$$R = \frac{e^{-i\alpha\omega}}{1-i\alpha\omega}$$
(B5)

B3. RAYLEIGH DISTRIBUTION

$$R = \exp \left(- \frac{i}{\pi \alpha \omega} \right)$$

$$\cdot \left[\frac{1 + i}{\pi \alpha \omega} \operatorname{erfc}(i \alpha \omega) \exp \left(- \frac{\alpha^2 \omega^2}{\alpha^2 \omega} \right) \right] \qquad (B6)$$

where

$$\tilde{\alpha} = (\mu_0 \varepsilon_0)^{.5} \frac{\sigma}{c} \cos \theta \tag{B7}$$

٠

.

.

B4. SKEW-NORMAL DISTRIBUTION

$$R = \frac{1}{2\sigma} \exp\left[i(2/\pi)^{.5} \left(\alpha_{1}^{-} \alpha_{2}\right)\omega\right]$$

$$\cdot \left\{\sigma_{1} \exp\left(-.5 \alpha_{1}^{2} \omega^{2}\right) \operatorname{erfc}\left[-\frac{i}{\sqrt{2}} \alpha_{1}^{\omega}\right]$$

$$+ \sigma_{2} \exp\left(-.5 \alpha_{2}^{2} \omega^{2}\right) \operatorname{erfc}\left[-\frac{i}{\sqrt{2}} \alpha_{2}^{\omega}\right]\right\} \qquad (B8)$$

$$\alpha_1 = 2 \left(\mu_0 \varepsilon_0\right)^{.5} \sigma_1 \cos \theta \tag{B9a}$$

$$\alpha_2 = 2 \left(\mu_0 \varepsilon_0\right)^{.5} \sigma_2 \cos \theta \tag{B9b}$$

Nomenclature

χ characteristic	function
------------------	----------

- R reflection coefficient
- D delay in time for the ground reflected signal
- m frequency modulation parameter
- H transfer function of the matched filter
- **ω** angular frequency
- ω_c angular carrier frequency
- 2T_o pulse width of the transmitted signal
- Ψ_1 confluent hypergeometric function
- θ angle of incidence
- g₀(t) direct signal
- g₁(t) ground reflected signal-I

g₂(t) ground reflected signal-II

 σ rms height of the rough surface

$$\alpha = 2(\mu_0 \epsilon_0)^{0.5} \sigma \cos \theta$$

 $\tilde{\alpha}$ 0.5 α $(1 - 0.25 \pi)^{-0.5}$

 $\alpha_{i} = 2(\mu_{0}\varepsilon_{0})^{0.5}\sigma_{i}\cos\theta$: i = 1, 2

MISSION

OF

ROME LABORATORY

Home Laboratory plans and executes an interdisciplinary program in recearch, development, test, and technology transition in support of Air Verce Command, Control, Communications and Intelligence (C^{3}) activities for all Air Force platforms. It also executes selected acquisition programs in several areas of expertise. Technical and engineering support within trees of competence is provided to ESD Program Offices (POs) and other ESD elements to perform effective acquisition of C^{3} systems. In addition, Nome Laboratory's technology supports other AFSC Product Divisions, the Air Force user community, and other DOD and non-DOD agencies. Rome Laboratory maintains technical competence and research programs in areas including, but not limited to, communications, command and control, battle management, intelligence information processing, computational sciences and software producibility, wide area surveillance/sensors, signal processing, solid state sciences, photonics, electromagnetic technology, superconductivity, and electronic reliability/maintainability and testability.