



AD-A280 848



paper no.

55--SA-66

COPY

# The American Society of Mechanical Engineers

29 WEST 39TH STREET, NEW YORK 18, NEW YORK

HEAT TRANSFER TO LAMINAR FLOW IN A ROUND TUBE OR  
FLAT CONDUIT - - - THE GRAETZ PROBLEM EXTENDED

J. Sellars  
Assistant Professor  
Dept. Aeronautical Engrg.  
University of Michigan  
Ann Arbor, Mich.

M. Tribus, Member ASME  
Associate Professor  
Engineering Dept.  
University of California  
Los Angeles 24, Calif.

J. Klein  
Instructor in Mathematics  
Oberlin College  
Oberlin, Ohio

DTIC  
ELECTE  
JUN 09 1994  
S G D

LIBRARY

Contributed by the Heat Transfer Division for presentation at the ASME Diamond Jubilee Semi-Annual Meeting, Boston, Mass. - June 19-23, 1955. (Manuscript received at ASME Headquarters May 9, 1955.)

Written discussion on this paper will be accepted up to July 26, 1955.

(Copies will be available until April 1, 1956)

The Society shall not be responsible for statements or opinions advanced in papers or in discussion at meetings of the Society or of its Divisions or Sections, or printed in its publications.

**ADVANCE COPY:** Released for general publication upon presentation.

Decision on publication of this paper in an ASME journal had not been taken when this pamphlet was prepared. Discussion is printed only if the paper is published in an ASME journal.

Approved for public release

Printed in U.S.A.

Price: 50 cents per copy

(25 cents to ASME members)

1850-55

94 6 8 048

CN- 41526

94-17432  
1852  
[Barcode]

**Best  
Available  
Copy**

# HEAT TRANSFER TO LAMINAR FLOW IN A ROUND TUBE OR FLAT CONDUIT --- THE GRAETZ PROBLEM EXTENDED

By. hn Sellars, Myron Tribus, and John Klein

## NOMENCLATURE

The following nomenclature is used in the paper:

<p>A = Coefficient occurring in Equation (10).</p> <p>B = Coefficient occurring in Equation (10).</p> <p>b = Half width of flat duct, ft.</p> <p><math>C_n</math> = Coefficient in Equation (3).</p> <p><math>C_p</math> = Unit heat capacity at constant pressure, Btu/lb-°F.</p> <p>D = Coefficient occurring in Equation (18).</p> <p>E = Coefficient occurring in Equation (18).</p> <p>F = <math>F(s, r^+)</math>, Laplace transform of Graetz solution.</p> <p>g = <math>g(x^+, r^+)</math> Integrating kernel for heat-flux problems, see Equation (4k).</p> <p>G = <math>G(s, r^+)</math> Laplace transform of g.</p> <p>h = <math>h(x^+)</math> Integrating kernel for heat-flux problems, see Equation (3k).</p> <p>H = <math>H(s)</math> Laplace transform of h.</p> <p>i = <math>\sqrt{-1}</math>.</p> <p>J = Bessel function of first kind, zero order.</p> <p><math>J_{1/3}</math> = Bessel function of first kind, 1/3 order.</p> <p><math>J_{-1/3}</math> = Bessel function of first kind, -1/3 order.</p> <p>k = Thermal conductivity of fluid, Btu/sec-ft<sup>2</sup> (°F/ft).</p> <p><math>K_n</math> = Coefficient occurring in Equation (A-3).</p> <p>Pr = Prandtl modulus, dimensionless, <math>(\mu C_p/k)(3600 g_c)</math>.</p> <p>q = <math>q(x)</math> heat flux per unit wall area, Btu/hr-ft<sup>2</sup>.</p> <p>Q = Laplace transform of <math>(kq/r_0)</math>.</p>	<p>r = Radius, ft.</p> <p><math>r_0</math> = Tube radius, ft.</p> <p><math>r^+ = (r/r_0)</math>.</p> <p>R = <math>R(r^+)</math>.</p> <p><math>Re</math> = Reynolds modulus, dimensionless, <math>(2U_m r_0 \rho / \mu g_c)</math> or <math>(4U_m b \rho / \mu g_c)</math>.</p> <p>S = Transform variable.</p> <p>t = <math>t(x^+, r^+)</math> temperature, °F.</p> <p>T = <math>T(s, r^+)</math>, Laplace transform of t.</p> <p>u = Velocity of fluid, ft/sec.</p> <p><math>u_m</math> = Average fluid velocity in tube, ft/sec.</p> <p>x = Distance along tube, ft.</p> <p><math>x^+ = (x/r_0)(RePr)^{-1}</math> or <math>(x/b)(RePr)^{-1}</math>.</p> <p>y = Distance from duct wall, ft.</p> <p><math>y^+ = (y/b)</math>.</p> <p>z = Distance from tube wall, ft.</p> <p><math>z^+ = (z/r_0)</math>.</p> <p><math>\gamma</math> = Zero of <math>H(s)</math>.</p> <p><math>\lambda</math> = Eigenvalue.</p> <p><math>\mu</math> = Viscosity of fluid, lb-sec/ft<sup>2</sup>.</p> <p><math>\rho</math> = Fluid density, lb/ft<sup>3</sup>.</p> <p><math>\xi</math> = Dummy variable.</p> <p><math>\eta</math> = Dummy Variable.</p> <p><math>\Gamma</math> = Gamma function.</p>
--	--

Accession For	
NTIS CRA&I DTIC TAB Unannounced Justification .....	
By .....	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1 	

## INTRODUCTION

The problem considered here is posed by a system in which a fluid of constant properties flows in steady laminar motion in a round tube or flat duct. The velocity profile is fully established and parabolic. Up to a point ( $x = 0$ ) the fluid is isothermal. After this point a prescribed heat flux or temperature is given at the wall of the conduit and the problem is to find the temperature distribution, as well as the connection between heat flux and wall temperature. The application of this solution to practical problems of heat exchange has already been so well established that further comment is unnecessary.

The problem has been considered in detail by a number of workers and an excellent review is contained in the book "Heat Transfer" by M. Jakob.<sup>1</sup> The problem readily reduces to the finding of eigenvalues and prior to this paper only the first three eigenfunctions and the first four eigenvalues have been known. A recent paper<sup>2</sup> has brought out the importance of obtaining more eigenvalues, and by using the complete set of eigenvalues and the methods of reference 2 the classical "Graetz Problem"<sup>3</sup> is extended to more complicated boundary conditions.

The problem can be stated in mathematical terms as follows:

Given

$$\begin{aligned} t &= t(x, r) \\ u \rho c_p \frac{\partial t}{\partial x} &= \frac{k}{r} \frac{\partial}{\partial r} \left( r \frac{\partial t}{\partial r} \right) \\ u &= 2 u_m \left[ 1 - \left( \frac{r}{r_0} \right)^2 \right] \end{aligned} \quad (1)$$

and for

$$t = t_0 \quad x < 0$$

with either

$$\left. \begin{aligned} t(x, r_0) &= t_w(x) \\ \text{or} \quad k t_r(x, r_0) &= q(x) \end{aligned} \right\} x > 0$$

find  $t(x, r)$  and the relation between  $q(x)$  and  $t_w(x)$ .

The nondimensional form of the equations is

$$\frac{\partial t}{\partial x^*} = \frac{1}{1-r^{*2}} \frac{1}{r^*} \frac{\partial}{\partial r^*} \left( r^* \frac{\partial t}{\partial r^*} \right) \quad (2)$$

The boundary conditions are

$$t = t_0 \quad x^* < 0$$

and either

$$\left. \begin{aligned} t(x^*, 1) &= t_w(x^*) \\ \text{or} \quad t_{r^*}(x^*, 1) &= r_0 q(x^*) / k \end{aligned} \right\} x^* > 0$$

In view of the linearity of Equation (2), it is necessary to have only the fundamental solution, known as the Graetz solution, to construct all other needed solutions. Therefore, the initial step is the completion of the Graetz solution.

<sup>1</sup> "Heat Transfer," by Max Jakob, John Wiley & Sons, Inc., New York, N. Y., vol. 1, 1949.

THE GRAETZ SOLUTION

The problem considered by Graetz and most other workers is Equation (2) with boundary conditions.

$$t = 1 \quad z^+ < 0$$

$$t_v = 0 \quad z^+ > 0$$

Led  $\Theta$  be a solution of Equation (2), then

$$\Theta = \sum_{n=0}^{\infty} c_n R_n(z^+) e^{-\lambda_n^2 z^+} \quad (3)$$

where the  $\lambda_n$  are the eigenvalues required to make the solution to the following differential equation

$$z^+ R_n'' + R_n' + \lambda_n^2 z^+ (1 - z^{+2}) R_n = 0 \quad (4)$$

satisfying the boundary conditions  $R_n(1) = 0$ ,  $R_n(0) = 1$ . The coefficients  $C_n$  are determined from the relation

$$c_n = \frac{\int_0^1 z^+ (1 - z^{+2}) R_n dz^+}{\int_0^1 z^+ (1 - z^{+2}) R_n^2 dz^+} = \frac{-2}{\lambda_n \left( \frac{\partial R_n}{\partial \lambda} \right)_{\substack{z^+=1 \\ \lambda = \lambda_n}}}} \quad (5)$$

The eigenfunctions and eigenvalues have been given only for  $n = 1, 2, 3$ . The higher modes of Equation (4) are very difficult to calculate for large values of  $\lambda$ . Therefore, to obtain  $\lambda_n$  and  $C_n$  for  $n > 3$ , a solution is sought which will be valid as  $\lambda_n \rightarrow \infty$ . It will be found that the resulting formulae will provide good answers even when  $\lambda_n$  is small. First, look for a solution in the form

$$R = e^{g(z^+)}$$

and find that  $g(z^+)$  satisfies

$$g'' + g'^2 + \frac{1}{z^+} g' + \lambda^2 (1 - z^{+2}) = 0 \quad (6)$$

Now an asymptotic solution is sought in the form

$$g = \lambda g_0 + g_1 + \lambda^{-1} g_2 + \dots \quad (7)$$

Substitution in Equation (6) and equating powers of  $\lambda$  gives

$$g_0' = \pm i \sqrt{1 - z^{+2}} \quad (8)$$

$$g_1 = -\ln \sqrt{g_1^+ r^+} \quad (9)$$

Since  $\lambda$  is large, the remaining terms in Equation (7) are neglected. Substitution of Equations (8) and (9) in Equation (7) gives for  $R$

$$R = \frac{A e^{i\lambda \int_0^{r^+} \sqrt{1-\xi^2} d\xi} + B e^{-i\lambda \int_0^{r^+} \sqrt{1-\xi^2} d\xi}}{\sqrt{\lambda^+} (1-\lambda^{+2})^{1/4}} \quad (10)$$

Equation (10) is the so-called WKB approximation and is valid for  $0 < r^+ < 1$  for sufficiently large  $\lambda$ . Now the coefficients  $A$  and  $B$  must be determined so that Equation (10) will correspond to the regular solution of Equation (4), where  $r^+$  is small. For small  $r^+$  Equation (10) is

$$R = \frac{A e^{i\lambda r^+} + B e^{-i\lambda r^+}}{\sqrt{\lambda^+} (1-\lambda^{+2})^{1/4}} \quad (11)$$

Inspection of Equation (4) shows that when  $r^+$  is small enough so that  $\lambda^2 (1-r^{+2}) \rightarrow \lambda^2$ , the classical solution behaves as  $J_0(\lambda r^+)$ , since Equation (4) then becomes a Bessel equation. For large  $\lambda r^+$ , even if  $r^+$  is small, the asymptotic expression for  $J_0(\lambda r^+)$  is

$$J_0(\lambda r^+) = \sqrt{\frac{2}{\pi \lambda r^+}} \cos(\lambda r^+ - \frac{\pi}{4}) \quad (12)$$

and thus, it is seen that to make Equations (11) and (12) equal for  $r^+$  small, it is required that

$$A = \sqrt{\frac{2}{\lambda \pi}} e^{-i\frac{\pi}{4}} \quad B = \sqrt{\frac{2}{\lambda \pi}} e^{i\frac{\pi}{4}} \quad (13)$$

and for  $0 < r^+ < 1$

$$R(r^+) = \sqrt{\frac{2}{\pi \lambda r^+}} \frac{\cos(\lambda \int_0^{r^+} \sqrt{1-\xi^2} d\xi - \frac{\pi}{4})}{(1-\lambda^{+2})^{1/4}} \quad (14)$$

Equation (14) is not a good approximation to the solution as  $r^+ \rightarrow 1$ , since it has a singularity there. Because a boundary condition is to be imposed at  $r^+ = 1$ , the development of an alternate solution, valid near  $r^+ = 1$ , is considered. By patching it on to Equation (14) the solution over the range  $0 \leq r^+ \leq 1$  is obtained.

The following change of variable is made

$$z^+ = 1 - \lambda^+$$

and Equation (4) becomes

$$\frac{d^2 R}{dz^{*2}} - \frac{1}{1-z^*} \frac{dR}{dz^*} + \lambda^2 z^* (2-z^*) R = 0 \quad (15)$$

Now consider  $0 < z^* \ll 1$  and define a new variable

$$\eta = \lambda^{1/2} z^* \quad (16)$$

Substitution of Equation (16) into Equation (14) yields for large  $\lambda$

$$\frac{d^2 R}{d\eta^2} + 2\eta R = 0 \quad (17)$$

which has the solution

$$R = D \sqrt{z^*} J_{1/2} \left( \frac{\lambda^{1/2}}{3} z^{*3/2} \right) + E \sqrt{z^*} J_{-1/2} \left( \frac{\lambda^{1/2}}{3} z^{*3/2} \right) \quad (18)$$

The constants D and E are to be so chosen that for small  $z^*$  Equations (18) and (14) are equivalent.

Change the variable from  $r^+$  to  $z^+$  in Equation (14) and perform the integration

$$\int_0^{z^*} \sqrt{1-\xi^2} d\xi = \int_0^1 \sqrt{1-\xi^2} d\xi + \int_1^{z^*} \sqrt{1-\xi^2} d\xi = \pi/4 - \int_0^{z^*} \sqrt{2\xi-\xi^2} d\xi \quad (19)$$

For small  $z^+$  Equation (19) yields

$$\int_0^{z^*} \sqrt{1-\xi^2} d\xi = \pi/4 - \sqrt{2}/3 z^{*3/2} \quad (20)$$

so that Equation (14) for small  $z^+$  is

$$R(z^*) = \sqrt{\frac{2}{\pi\lambda}} \frac{\cos \left( \frac{\sqrt{2}}{3} \lambda z^{*3/2} - (\lambda-1)\pi/4 \right)}{2^{3/4} z^{*3/4}} \quad (21)$$

For large  $\lambda z^+$ , even if  $z^+$  is small, Equation (18) becomes

$$R(z^*) = \sqrt{\frac{2}{\pi\lambda}} \frac{D \cos \left( \frac{\lambda^{1/2}}{3} z^{*3/2} - \frac{5\pi}{12} \right) + E \cos \left( \frac{\lambda^{1/2}}{3} z^{*3/2} - \frac{\pi}{12} \right)}{2^{3/4} z^{*3/4}} \quad (22)$$

Expanding the cosines of differences of angle occurring in Equations (21) and (22) yields the simultaneous equation

$$D \cos \frac{5\pi}{12} + E \cos \frac{\pi}{12} = \sqrt{2} \cos (\lambda-1)\pi/4$$

$$D \sin \frac{\pi}{12} + E \sin \frac{\pi}{12} = \sqrt{\frac{2}{3}} \sin (\lambda-1)^{\frac{1}{4}} \quad (23)$$

from which D and E are evaluated. Therefore, Equation (18) is

$$R(z^+) = \frac{2}{3} \sqrt{\frac{2}{3}} \left[ \sin \left( \frac{\lambda \pi}{4} - \frac{\pi}{3} \right) J_{\frac{1}{3}} \left( \frac{\lambda \sqrt{8}}{3} z^{+\frac{3}{2}} \right) - \sin \left( \frac{\lambda \pi}{4} - \frac{2\pi}{3} \right) J_{-\frac{1}{3}} \left( \frac{\lambda \sqrt{8}}{3} z^{+\frac{3}{2}} \right) \right] \quad (24)$$

As  $z^+ \rightarrow 0$  the product  $\sqrt{z^+} J_{1/3} [\lambda \sqrt{8/3} z^{+3/2}] \rightarrow 0$ , but the product involving  $J_{-1/3}$  becomes constant. Therefore, the coefficient of  $J_{-1/3}$  must be zero if  $R = 0$  at  $z^+ = 0$ . The values of  $\lambda_n$  must therefore be given by

$$\lambda_n = 4n + \frac{2}{3} \quad n = 0, 1, 2, \dots \quad (25)$$

The equations for  $R_n$  are therefore

for small  $r^+$  (center of pipe)

$$R_n(r^+) = J_0(\lambda_n r^+) \quad (26)$$

for medium  $r^+$

$$R_n(r^+) = \frac{\sqrt{2}}{\pi \lambda_n r^+} \frac{\cos \frac{\lambda_n}{2} r^+ \sqrt{1-r^{+2}} + \lambda_n \sin r^+ - \frac{\pi}{4}}{(1-r^{+2})^{1/4}} \quad (27)$$

and for small  $z^+ = 1 - r^+$  (near the wall)

$$R_n(z^+) = \sqrt{\frac{2z^+}{3}} (-1)^n J_{\frac{1}{3}} \left( \frac{\lambda_n \sqrt{8}}{3} z^{+\frac{3}{2}} \right) \quad (28)$$

Equations (24) to (28) contain all the information essential to the problem solution. The coefficients  $C_n$  in Equation (3) are found from Equation (24) in accordance with Equation (5). Thus it is found that

$$\left( \frac{\partial R}{\partial \lambda} \right)_{\lambda=\lambda_n} = (-1)^{n+1} \frac{\pi \lambda_n^{-1/2}}{6^{3/2} \Gamma(3/2)} \quad n = 0, 1, 2, \dots \quad (29)$$

and therefore

$$C_n = (-1)^n \frac{2 \cdot 6^{3/2} \Gamma(3/2)}{\pi} \lambda_n^{-3/2} \quad n = 0, 1, 2, \dots \quad (30)$$

The derivative of R at the wall ( $z^+ = 0$ ) which is

$$R'_n(1) = - \left( \frac{\partial R_n}{\partial z^+} \right)_{z^+=0} = \frac{(-1)^{n+1} 2^{3/2} \lambda_n^{3/2}}{\Gamma(3/2) 3^{3/2}} \quad n = 0, 1, 2, \dots \quad (31)$$

will be required later.

Table I shows the first ten eigenvalues and the important constants for the case of flow in a round tube. Table II gives the same data for a flat duct with opposite walls at the same temperature. The development of the flat-duct system is similar to the round duct and the equations are given in the appendix, numbered to correspond with the text.

TABLE I FIRST TEN EIGENVALUES AND THE IMPORTANT CONSTANTS FOR THE CASE OF FLOW IN A ROUND TUBE

n	$\lambda_n$	$\lambda_n^2$	$C_n$	$-1/2 C_n R_n' (1)$
0	2 2/3	7.1129	+1.47989	0.7303
1	6 2/3	44.489	-0.80345	0.53810
2	10 2/3	113.785	+0.58732	0.460074
3	14 2/3	215.121	-0.474993	0.413743
4	18 2/3	348.457	+0.404448	0.381785
5	22 2/3	513.793	-0.355345	0.357853
6	26 2/3	711.129	+0.318858	0.338988
7	30 2/3	940.465	-0.290488	0.323555
8	34 2/3	1201.8	+0.267691	0.310596
9	38 2/3	1495.1	-0.248895	0.29950

$$C_n = (-1)^n \frac{2 \cdot 6^{2/3} \Gamma(1/2) \lambda_n^{-2/3}}{\pi} = (-1)^n 2.84606 \lambda_n^{-2/3}$$

$$-\frac{C_n}{2} R_n'(1) = \frac{6^{2/3} \Gamma(1/2) 2^{2/3} \lambda_n^{-1/3}}{\pi \Gamma(1/2) 3^{2/3}} = 1.01276 \lambda_n^{-1/3}$$

$$\lambda_n = 4n + \frac{2}{3} \quad n = 0, 1, 2, \dots$$

$$\theta = \sum C_n R_n(\eta^2) e^{-\lambda_n^2 x^2}$$

$$q(x^2) = -\frac{q_0}{d} \sum \frac{C_n}{2} R_n'(1) e^{-\lambda_n^2 x^2} (t_w - t_0)$$

The previously known eigenvalues given by Jakob are shown in Table III for comparison. Since the solution presented here is valid for large  $\lambda_n$ ,

TABLE II FIRST TEN EIGENVALUES AND THE IMPORTANT CONSTANTS FOR THE CASE OF FLOW IN A FLAT DUCT WITH OPPOSITE WALLS AT THE SAME TEMPERATURE

n	$\lambda_n$	$\lambda_n^2$	$K_n$	$-K_n Y_n'(1)$
0	1.667	2.779	+0.503	.683
1	5.667	32.11	-0.121	.454
2	9.667	93.45	+0.0648	.380
3	13.67	186.9	-0.0431	.338
4	17.67	312.2	+0.0319	.311
5	21.67	469.6	-0.0253	.291
6	25.67	658.9	+0.0207	.274
7	29.67	880.3	-0.0174	.262
8	33.67	1134	+0.0150	.251
9	37.67	1419	-0.0131	.242

$$K_n = (-1)^n \frac{3^{2/3} \Gamma(2/3) 2^{1/6}}{\pi^{3/2}} \lambda_n^{-2/6} = (-1)^n 0.913 \lambda_n^{-1/3}$$

$$-K_n Y_n'(1) = \frac{4 \cdot 2^{1/3} \Gamma(2/3) \lambda_n^{-1/3}}{\pi \Gamma(1/3) 3^{1/6}} = 0.910 \lambda_n^{-1/3}$$

$$\lambda_n = 4n + 5/3 \quad n = 0, 1, 2, \dots \quad \theta = \sum K_n Y_n(y^+) e^{-\lambda_n^2 \frac{2}{3} z^+}$$

$$g(z^+) = \sum -\frac{1}{b} K_n Y_n'(1) e^{-\frac{2}{3} \lambda_n^2 z^+} (t_w - t_0)$$

TABLE III COMPARISON WITH PREVIOUSLY KNOWN EIGENVALUES

n	Sellars, Tribus, Klein			Results Obtained			Analogue Computer		
	$\lambda_n$	$C_n$	$\frac{-C_n R_n'(1)}{2}$	$\lambda_n$	$C_n$	$\frac{-C_n R_n'(1)}{2}$	$\lambda_n$	$C_n$	$\frac{-C_n R_n'(1)}{2}$
0	2.667	+1.47989	0.7303	2.705	+1.477	0.749	2.71	1.46	0.735
1	6.667	-0.80345	0.5381	6.66	-0.810	0.539	6.69	-0.809	0.533
2	10.667	+0.58732	0.4601	10.3	+0.385	0.179	10.62	+0.592	0.444
3	14.667	-0.47499	0.4137	14.67*	-0.479*	-----	14.58	-0.51	0.398

\*Attributed to Lee, Nelson, Cherry and Boelter.

and in view of the agreement even at moderate values of  $\lambda_n$ , it has been concluded that all the eigenvalues and functions are now sufficiently accurately known.

The heat flux at the wall is computed from the equation

$$q(x^+) = k \left( \frac{\partial t}{\partial x^+} \right)_{x^+=1} = -\frac{k}{\alpha} \sum \frac{c_n}{2} \lambda_n'(1) e^{-\lambda_n x^+} (t_w - t_0) \quad (32)$$

Equation (32) is presented in the above form to bring it into agreement with Jakob.<sup>1</sup>

#### ARBITRARY WALL-TEMPERATURE VARIATIONS

If the wall-temperature variation is given by  $t_w(x)$ , then, as shown by Tribus and Klein,<sup>2</sup> the principle of superposition may be applied and the solution may be written in a Fourier-type Stieltjes integral

$$t - t_0 = \int_{\xi=0}^{x^+} [1 - \theta(x^+ - \xi, \lambda^+)] dt_w(\xi) \quad (33)$$

where  $\theta$  is the solution to Equation (2) defined by Equation (3). The temperature of the wall and fluid for  $x^+ < 0$  is  $t_0$ . The Stieltjes integral in Equation (33) is evaluated by substituting  $(dt_w/d\xi) d\xi$  for  $dt_w$  wherever  $t_w$  is continuous and substituting  $[1 - \theta(x^+ - \xi_1, \lambda^+)] [t(\xi_1^+) - t(\xi_1^-)]$  as the contribution of the integral wherever  $t_w(x^+)$  has a discontinuity. (See Tribus and Klein<sup>2</sup> for a more detailed discussion.) The heat flux is computed from

$$q(x^+) = k \left( \frac{\partial t}{\partial x^+} \right)_{x^+=1} = -\frac{k}{\alpha} \int_0^{x^+} \theta_\lambda(x^+ - \xi, 1) dt_w(\xi) \quad (34)$$

#### HEAT FLUX AT THE WALL GIVEN

The inverse problem; namely, "Given the heat flux at the wall, what is the temperature?", may be solved with the aid of the Laplace transform theory. Define the following transforms

$$T(s, \lambda^+) = \int_0^\infty e^{-s x^+} (t - t_0) dx^+ \quad (35)$$

$$T_w(s) = T(s, 1) \quad (36)$$

$$F(s, \lambda^+) = \int_0^{\infty} [1 - \theta(x^+, \lambda^+)] e^{-sx^+} dx^+ \quad (37)$$

$$H(s) = T_{\lambda^+}(s, 1) = - \int_0^{\infty} \theta_{\lambda^+}(x^+, 1) e^{-sx^+} dx^+ \quad (38)$$

$$Q(s) = \frac{\lambda_0}{k} \int_0^{\infty} e^{-sx^+} g(x^+) dx^+ \quad (39)$$

Applying the Faltung theorem to Equations (33) and (34) yields;

$$T(s, \lambda^+) = F(s, \lambda^+) s T_w(s) \quad (40)$$

$$Q(s) = H(s) s T_w(s) \quad (41)$$

If the heat flux is finite,  $t_w(x^+)$  will be continuous. Eliminating  $t_w(s)$  from the above equations,

$$T(s, \lambda^+) = \frac{F(s, \lambda^+)}{H(s)} Q(s) \quad (42)$$

Now define

$$G(s, \lambda^+) = \frac{F(s, \lambda^+)}{H(s)} \quad (43)$$

and let  $g(x^+, r^+)$  be the inverse transform of  $G(s, r^+)$ . Then, for arbitrary heat flux at the wall, the temperature is given by

$$t - t_0 = \frac{\lambda_0}{k} \int_0^{x^+} g(x^+ - \xi, \lambda^+) q(\xi) d\xi \quad (44)$$

Thus, the problem is reduced to finding  $g(x^+, r^+)$ , which is given by

$$g(x^+, \lambda^+) = \frac{1}{2\pi i} \int_{c-i\infty}^{c+i\infty} e^{sx^+} \frac{F(s, \lambda^+)}{H(s)} ds \quad (45)$$

Returning to Equations (37), (38), and (3) it is found that

$$F(s, \lambda^+) = \frac{1}{s} - \sum_{n=0}^{\infty} \frac{C_n R_n(\lambda^+)}{s + \lambda_n^2} \quad (46)$$

$$H(s) = - \sum_{n=0}^{\infty} \frac{C_n R_n'(1)}{s + \lambda_n^2} \quad (47)$$

Because  $F$  and  $H$  have poles at  $s = -\lambda_n^2$ , the quotient  $F/H$  has no poles except at  $s = 0$  and the zeroes of  $H(s)$  and the zeroes of  $H(s)$  must be found nu-

merically. Because  $H'(s)$  is monotonic, it is found that the zeroes of  $H(s)$  occur between the  $-\lambda_n^2$ . Letting  $\gamma_m^2$  be the values satisfying  $H(-\gamma_m^2) = 0$ , from the theory of residues

$$g(x, x') = \frac{1}{H(0)} - \sum_m \frac{e^{-\gamma_m^2 x'}}{\gamma_m^2 H'(-\gamma_m^2)} - \sum_m c_m R_m(x') \sum_m \frac{e^{-\gamma_m^2 x'}}{\lambda_m^2 - \gamma_m^2} \quad (48)$$

Table IV gives the values of  $\gamma_m^2$ ,  $H'(-\gamma_m^2)$  for the first three values of  $m$ . The term  $H(0)$  has been shown by others<sup>1</sup> to be given by

$$H(0) = + \frac{1}{4} \quad (49)$$

hence, the wall temperature may be easily calculated with the aid of

$$g(x', 1) = 4 - \sum_m \frac{e^{-\gamma_m^2 x'}}{\gamma_m^2 H'(-\gamma_m^2)} \quad (50)$$

TABLE IV THE VALUES OF  $\gamma_m^2$ ,  $H'(-\gamma_m^2)$  FOR THE FIRST THREE VALUES OF  $m$   
Roots of  $H(s) = 0$ , Values of  $H'(-\gamma_m^2)$

$$H(s) = - \sum_{n=0}^{\infty} \frac{c_n R_n'(1)}{s + \lambda_n^2}$$

$$c_n R_n'(1) = -2.02552 \lambda_n^{-1/3}$$

$$\lambda_n = 4n + \frac{2}{3} \quad n = 0, 1, 2, \dots$$

$$H'(s) = \sum_m \frac{c_m R_m'(1)}{(s + \lambda_m^2)^2}$$

$m$	$\gamma_m^2$	$-H'(-\gamma_m^2)$	$\frac{-1}{\gamma_m^2 H'(-\gamma_m^2)}$
1	25.639	$8.854 \times 10^{-3}$	4.405
2	84.624	$2.062 \times 10^{-3}$	5.7308
3	176.40	$9.435 \times 10^{-4}$	6.0084

TABLE V VALUES OF  $\gamma_m^2$ ,  $H'(-\gamma_m^2)$  FOR THE FIRST THREE VALUES OF  $m$  FOR A FLAT DUCT  
Roots of  $\bar{H}(s) = 0$ , Values of  $\bar{H}'(-\gamma_m^2)$

$$\bar{H}(s) = - \sum \frac{K_m Y_m'(1)}{s + \frac{2}{3} \lambda_m^2}$$

$$\bar{H}'(s) = \sum \frac{K_m Y_m'(1)}{(s + \frac{2}{3} \lambda_m^2)^2}$$

$$\lambda_m = 4m + \frac{1}{3} \quad m = 0, 1, 2, \dots$$

$m$	$\gamma_m^2$	$-\bar{H}'(-\gamma_m^2)$	$\frac{-1}{\gamma_m^2 \bar{H}'(-\gamma_m^2)}$
1	49.345	$7.45 \times 10^{-4}$	27.2
2	185.94	$1.67 \times 10^{-4}$	32.1
3	409.45	$6.89 \times 10^{-5}$	35.4

A SAMPLE CALCULATION FOR CONSTANT WALL HEAT FLUX

By way of illustration consider the computation of the asymptotic value of the Nusselt modulus for the case of constant heat flux at the wall. Combining Equations (44) and (48) with  $q(\xi) = q = \text{constant}$ , the following is obtained.

$$t(x^+, \lambda^+) - t_0 = \frac{q \lambda_0}{k} \int_0^{x^+} \left[ 4 - \sum_m \frac{e^{-\gamma_m^2 (x^+ - \xi^+)}}{\gamma_m^2 H'(-\gamma_m^2)} - \sum_m c_m R_m \sum_m \frac{e^{-\gamma_m^2 (x^+ - \xi^+)}}{\lambda_m^2 - \gamma_m^2} \right] d\xi^+ \quad (51)$$

Letting  $\beta x = x^+$ , where  $\beta = \pi k / 2WC_p$ , and integrating Equation (51) gives

$$t(x^+, \lambda^+) - t_0 = \frac{q \lambda_0}{k} \left\{ 4\beta x - \sum_m \frac{1 - e^{-\gamma_m^2 \beta x}}{\gamma_m^2 H'(-\gamma_m^2)} \right. \\ \left. - \sum_m c_m R_m \sum_m \frac{1 - e^{-\gamma_m^2 \beta x}}{\gamma_m^2 (\lambda_m^2 - \gamma_m^2)} \right\} \quad (52)$$

which may be rewritten as

$$t(x^+, \lambda^+) - t_0 = \frac{q \lambda_0}{k} \left[ 4\beta x - \sum_m \frac{1}{\gamma_m^2 H'(-\gamma_m^2)} \right. \\ \left. + \sum_m \frac{e^{-\gamma_m^2 \beta x}}{\gamma_m^2 H'(-\gamma_m^2)} - \sum_m c_m R_m \sum_m \frac{1 - e^{-\gamma_m^2 \beta x}}{\gamma_m^2 (\lambda_m^2 - \gamma_m^2)} \right] \quad (53)$$

Equation (53) shows that far down the pipe ( $x^+ \rightarrow \infty$ ) the derivative of  $t$  with respect to  $x$  is independent of  $x$  or  $r^+$ ; i.e.,

$$\frac{\partial t}{\partial x} = \frac{4q \lambda_0}{k} \quad \text{for } x^+ \rightarrow \infty \quad (54)$$

Substituting this quantity into Equation (2) leads to

$$\frac{4q \lambda_0}{k} = \frac{1}{\lambda^+ (1 - \lambda^{+2})} \frac{\partial}{\partial \lambda^+} \left( \lambda^+ \frac{\partial t}{\partial \lambda^+} \right) \quad (55)$$

which may be integrated directly to give

$$t(x^+, \lambda^+) - t(x^+, 0) = \frac{4 \lambda_0 q}{k} \left( \frac{\lambda^{+2}}{4} - \frac{\lambda^+}{16} \right) \quad (56)$$

Now the mixed mean temperature along the pipe is given by

$$t_{mm}(x^+) - t_0 = \frac{2\pi \lambda_0 q x}{WC_p} = \frac{4 \lambda_0 q}{k} \beta x \quad (57)$$

but the mixed mean temperature is also defined by

$$t_{mm}(x^+) = \frac{\int_0^1 u \rho c_p t(x^+, \eta^+) 2\pi \eta^+ d\eta^+}{W c_p} \quad (58)$$

Substituting Equation (56) into Equation (58) and integrating results in

$$t_{mm}(x^+) - t(x^+, 0) = \frac{7}{24} \frac{\lambda_0 q}{k} \quad (59)$$

Combining Equations (59) and (56)

$$t(x^+, \eta^+) = \frac{4\lambda_0 q}{k} \left( \frac{\eta^{+2}}{4} - \frac{\eta^{+4}}{16} \right) + t_{mm} - \frac{7}{24} \frac{\lambda_0 q}{k} \quad (60)$$

and substituting Equation (57) into Equation (60)

$$t(x^+, \eta^+) - t_0 = \frac{\lambda_0 q}{k} \left[ 4\beta x + \eta^{+2} - \frac{\eta^{+4}}{4} - \frac{7}{24} \right] \quad (61)$$

at  $r^+ = 1$ . This expression reduces to

$$t(x^+, 1) - t_0 = \frac{\lambda_0 q}{k} \left[ 4\beta x + \frac{11}{24} \right] \quad (62)$$

but from Equation (52), since  $R_n(1) = 0$ ,

$$t(x^+, 1) - t_0 = \frac{\lambda_0 q}{k} \left[ 4\beta x - \sum_m \frac{1}{\gamma_m^4 H'(1-\gamma_m^2)} \right] \quad (63)$$

Hence,

$$\sum \frac{1}{\gamma_m^4 H'(1-\gamma_m^2)} = -\frac{11}{24} \cong -0.458 \quad (64)$$

(Note that the first three terms sum to approximately -0.27.) Now, the Nusselt modulus is given by

$$Nu = \frac{2\lambda_0 q}{k(t_w - t_{mm})} \quad (65)$$

From Equation (60)

$$t(x^+, 1) - t_{mm} = \frac{11}{24} \frac{\lambda_0 q}{k} \quad (66)$$

which when substituted into Equation (65) gives

$$Nu = \frac{48}{11} \cong 4.36 \quad (67)$$

Substitution of (64), (58) and (53) into (65) yields the local value of the Nusselt Modulus for the case  $q(x^+) = \text{constant}$ .

$$Nu = \frac{1}{\frac{11}{48} + \frac{1}{2} \sum_m \frac{e^{-\lambda_m^2 x^+}}{\gamma_m H'(-\gamma_m^2)}} \quad (68)$$

CALCULATION FOR LINEARLY VARYING WALL TEMPERATURES

In similar fashion the use of the boundary condition  $T_w(x^+) - T_0 = Ax^+$  where  $A = \text{any constant}$ , gives:

$$q(x^+) = \frac{Ak}{4n_0} + \frac{2Ak}{n_0} \sum_m \frac{C_m}{2} \frac{R'_m(1)}{\lambda_m^2} e^{-\lambda_m^2 x^+} \quad (69)$$

$$T_{mm}(x^+) - T_0 = Ax^+ - \frac{88}{768} A - 8A \sum_m \frac{C_m}{2} \frac{R'_m(1)}{\lambda_m^4} e^{-\lambda_m^2 x^+} \quad (70)$$

$$Nu = \frac{\frac{1}{2} + 4 \sum_m \frac{C_m}{2} \frac{R'_m(1)}{\lambda_m^2} e^{-\lambda_m^2 x^+}}{\frac{88}{768} + 8 \sum_m \frac{C_m}{2} \frac{R'_m(1)}{\lambda_m^4} e^{-\lambda_m^2 x^+}} \quad (71)$$

APPROXIMATIONS FOR SMALL  $x^+$

Whenever  $x^+$  is small, a large number of the terms in the series, Equation (3) must be taken. The Leveque solution is a good approximation for such cases. As shown by Tribus and Klein,<sup>2</sup> the wall temperature and heat flux for such a case are related by

$$q(x) = \frac{k \rho_n^{1/3}}{3 \Gamma(4/3)} \left(\frac{\rho}{\rho_n}\right)^{1/3} \left(\frac{du}{dy}\right)_{y=0}^{1/3} \int_0^x (x-s)^{-2/3} dt_w(s) \quad (72)$$

and

$$t_w(x) - t_0 = \frac{2\rho_n^{-1/3}}{3 k \Gamma(4/3)} \left(\frac{\rho}{\rho_n}\right)^{-1/3} \left(\frac{du}{dy}\right)_{y=0}^{-1/3} \int_0^x \frac{q(s) ds}{(x-s)^{2/3}} \quad (73)$$

For flat ducts

$$\left(\frac{du}{dy}\right)_{y=0} = 3 u_{mm}/b \quad (74)$$

for round ducts

$$\left(\frac{du}{dy}\right)_{y=0} = 4 u_{mm}/r_0 \quad (75)$$

Substitution of Equation (75) into Equations (72) or (73) (and noting that the mixed mean temperature of the fluid is essentially equal to its inlet value at small values of  $x^+$ ) gives for the three cases under consideration:

For constant wall temperature:

$$Nu = \frac{2 \cdot 2^{1/3} x^{+ - 1/3}}{9^{1/3} \Gamma(4/3)} = 1.3565 x^{+ - 1/3} \quad x^{+} \leq 0.001 \quad (76)$$

For constant heat flux

$$Nu = \frac{2^{1/3} 9^{1/3} \Gamma(5/3)}{3} x^{+ - 1/3} = 1.6393 x^{+ - 1/3} \quad (77)$$

For linearly varying wall temperature

$$Nu = \frac{3 \cdot 2^{1/3} x^{+ - 1/3}}{9^{1/3} \Gamma(4/3)} = 2.0348 x^{+ - 1/3} \quad (78)$$

Figure 1 shows a graph of the functions  $R_0$ ,  $R_1$ , and  $R_2$  compared with solutions given by Jakob. Figure 2 shows the variations in Nusselt modulus for three cases





Fig.2. Laminar Flow of a Constant Property Fluid in a Round Tube

- (1) wall temperature constant,
- (2) heat flux constant, and
- (3) wall temperature increasing linearly along the pipe wall.

The Nusselt modulus is defined by the equation

$$Nu = \frac{q(x)}{t_w(x) - t_{mm}} \frac{2r_0}{k} \quad (79)$$

The mixed-mean temperature,  $t_{mm}$ , is determined by integrating the heat flux from the origin ( $X^+ = 0$ ) to the position where  $q(x)$  is known.

### CONCLUSIONS

The methods used in this paper have a wide applicability. For example, the liquid metals systems analyzed by Poppendiek<sup>4</sup> could be treated by the methods used here. The unsymmetrical boundary conditions treated by Yih and Cermak<sup>5</sup> can also be readily treated by these methods.

The authors are somewhat surprised at the fact that whereas the asymptotic formulae are all supposed to be valid only for very large  $\lambda$ , in actuality values of  $n$  as small as 4 seem to give excellent results. The reasons for the good results are not now clear.

### APPENDIX A

The equations for a flat duct system with walls at  $y = \pm b$  (A-1)

Defining  $Re = 4U_m \rho b / \mu$ ,  $x^+ = (x/b)(RePr)^{-1}$ ,  $y^+ = (y/b)$  the equation to be solved is

$$\frac{3}{8} \frac{\partial t}{\partial x^+} = \frac{1}{1-y^{+2}} \frac{\partial^2 t}{\partial y^{+2}} \quad (A-2)$$

which has a solution

$$\theta = \sum_{n=0}^{\infty} K_n Y_n(y^+) e^{-\frac{3}{8} \lambda_n^2 x^+} \quad (A-3)$$

satisfying  $\theta = 1$  at  $x^+ = 0$ ,  $\theta \rightarrow 0$ ,  $x^+ \rightarrow \infty$ , if  $y(y^+)$  satisfies

<sup>4</sup> 'Forced Convection Heat Transfer in Thermal Entrance Regions. Part 1,' by H. F. Poppendiek, Oak Ridge National Laboratory, Tenn., ORNL-913, Physics, series A, March, 1951.

<sup>5</sup> 'Laminar Heat Convection in Pipes and Ducts,' by C. S. Yih and J. E. Cermak, Civil Engineering Department, Colorado Agricultural and Mechanical College, Fort Collins, Colo., September, 1951. CNR Contract No. N90 nr 82401, NR063-071/k-19-49.

$$Y'' + \lambda^2(1 - y^2)Y = 0 \quad (\text{A-4})$$

with  $Y'(0) = Y(1) = 0$ ,  $Y(0) = 1$ .  $\lambda_n$  is the value of  $\lambda$  to permit  $Y_n(1) = 0$ . The coefficients  $K_n$  are given by

$$K_n = \frac{-2}{\lambda_n \left( \frac{\partial Y_n}{\partial \lambda} \right)_{y^2=1, \lambda=\lambda_n}} \quad (\text{A-5})$$

By the methods in the text the WKB approximation is found to be

$$Y(y^+) = \frac{\cos \left\{ \lambda \int_0^{y^+} (1-s^2)^{1/2} ds \right\}}{1-y^2} \quad (\text{A-14})$$

for  $0 \leq y^+ < 1$ .

Defining  $z = 1 - y^+$ , the solution of A(A-4) for  $z \ll 1$  is found to be

$$Y(z) = \frac{1}{2} (\lambda \pi z)^{1/2} \left\{ \sin \left( \frac{\pi \lambda}{4} - \frac{\pi}{12} \right) J_{1/3} \left( \frac{\lambda \sqrt{3}}{3} z^{3/2} \right) - \sin \left( \frac{\lambda \pi}{4} - \frac{5\pi}{12} \right) J_{2/3} \left( \frac{\lambda \sqrt{3}}{3} z^{3/2} \right) \right\}$$

The eigenvalues are

$$\lambda_n = 4n + 5/3 \quad (\text{A-25})$$

$$\left( \frac{\partial Y_n}{\partial \lambda} \right)_{\lambda=\lambda_n, y^2=1} = (-1)^{n+1} \frac{\pi^{1/2} \lambda_n^{1/6}}{3^{2/3} \Gamma(1/3) 2^{1/6}} \quad (\text{A-29})$$

$$K_n = (-1)^n \frac{3^{2/3} \Gamma(1/3) 2^{11/6}}{\pi^{3/2}} \lambda_n^{-7/6} \quad (\text{A-30})$$

$$\left( \frac{dY_n}{dy^+} \right)_{y^2=1} = (-1)^{n+1} \frac{\pi^{1/2} 2^{1/6} \lambda_n^{5/6}}{3^{5/6} \Gamma(1/3)} \quad (\text{A-31})$$

$$g(z^+) = -\frac{k}{b} (t_w - t_0) \sum_n K_n Y_n'(1) e^{-\frac{2}{3} \lambda_n^2 z^+} \quad (\text{A-32})$$

To obtain the fluid temperature for a given heat flux use

$$t - t_0 = \frac{k}{h} \int_0^{z^+} \bar{g}(z^+ - s, y^+) g(s) ds \quad (\text{A-44})$$

The integrating kernel,  $\bar{g}$ , is given by

$$g(z^+, y^+) = \frac{2}{3} - \sum_n \frac{e^{-\gamma_n^2 z^+}}{\gamma_n^2 \bar{H}'(-\gamma_n^2)} - \sum_n K_n Y_n(y^+) \sum_m \frac{e^{-\gamma_m^2 z^+}}{\frac{2}{3} \lambda_m^2 - \gamma_m^2} \quad (\text{A-48})$$

where the  $-\gamma_m^2$  are the zeroes of

$$\bar{H}(s) = - \sum_n \frac{K_n Y_n'(1)}{s + \frac{2}{3} \lambda_n^2} \quad (\text{A-47})$$