



US Army Corps
of Engineers
Waterways Experiment
Station

AD-A283 530




Miscellaneous Paper CERC-94-14
July 1994

①

Upgrade of Tropical Cyclone Surface Wind Field Model

by Vincent J. Cardone, Andrew T. Cox, J. Arthur Greenwood, Oceanweather, Inc.
Edward F. Thompson, WES




DTIC QUALITY INSPECTED 8

Approved For Public Release; Distribution Is Unlimited

DTIC QUALITY INSPECTED 8

10386
94-26566



94 8 19 078

Prepared for Headquarters, U.S. Army Corps of Engineers

Upgrade of Tropical Cyclone Surface Wind Field Model

by Vincent J. Cardone, Andrew T. Cox, J. Arthur Greenwood

Oceanweather, Inc.
5 River Road, Suite 1
Cos Cob, CT 06807

Edward F. Thompson
U.S. Army Corps of Engineers
Waterways Experiment Station
3909 Halls Ferry Road
Vicksburg, MS 39180-6199


Final report

Approved for public release; distribution is unlimited

**Prepared for U.S. Army Corps of Engineers
Washington, DC 20314-1000**



**US Army Corps
of Engineers
Waterways Experiment
Station**



FOR INFORMATION CENTER:
PUBLIC AFFAIRS OFFICE
U. S. ARMY ENGINEER
WATERWAYS EXPERIMENT STATION
880 HALLS FERRY ROAD
VICKSBURG, MISSISSIPPI 39180-0100
PHONE: (601)304-0202

Waterways Experiment Station Cataloging-in-Publication Data

Upgrade of tropical cyclone surface wind field model / by Vincent J. Cardone ... [et al] ; prepared for U.S. Army Corps of Engineers.

101 p. : ill. ; 28 cm. -- (Miscellaneous paper ; CERC-94-14)

Includes bibliographic references.

1. Storm winds -- Mathematical models. 2. Hurricanes -- Mathematical models -- Data processing. 3. Windstorms -- Mathematical models -- Computer programs. 4. Cyclones -- Mathematical models. I. Cardone, Vince J. II. United States. Army. Corps of Engineers. III. U.S. Army Engineer Waterways Experiment Station. IV. Coastal Engineering Research Center (U.S.) V. Series: Miscellaneous paper (U.S. Army Engineer Waterways Experiment Station) ; CERC-94-14.

TA7 W34m no.CERC-94-14

Contents

Preface	v
Conversion Factors, Non-SI to SI Units of Measurements	vi
1—Introduction	1
Background	1
Previous Studies	2
Scope	3
2—Existing Model Limitations	4
Physics	4
Initialization	5
Numerics	7
Summary of Limitations	9
3—Upgraded Model	10
Increased Resolution	10
Generalized Pressure Specification	12
Pressure profile form	12
Modified outflow	13
Specification of pressure parameters	15
Sample Runs	20
4—Summary	25
References	26
Appendix A: Comparison of Five-Nest and Seven-Nest Models for Hurricane Camille	A1
Appendix B: Documentation of CE Model Upgrades	B1
Appendix C: Sample Application of Upgraded CE Model to Simulation of 12 Snapshots of Hurricane Gilbert	C1
Appendix D: Sample Application of Upgraded CE Model to Simulation of 36-Hr Period of Hurricane Gilbert in the Gulf of Mexico	D1

List of Figures

Figure 1.	Temporal changes in the azimuthally averaged wind for NOAA reconnaissance flights into Hurricane Gilbert; changes are normalized to a 6-hr time interval (from Black and Willoughby (1992))	8
Figure 2.	Distribution of maximum wind speed differences between 5-nest and 7-nest model runs for Hurricane Camille	12
Figure 3.	Example of Oceanweather tropical storm analysis	17
Figure 4.	Some parameters in double exponential profile	21
Figure 5.	Comparison of azimuthally averaged reconnaissance winds and fitted gradient winds in 12 cases of Hurricane Gilbert defined by Black and Willoughby (1992)	24

List of Tables

Table 1.	Effect of Nest Activation Parameter, INSIDE	11
Table 2.	Maximum Inflow Observed in Frictionless Stationary Vortex Solution	14
Table 3.	Empirical Correction of Inflow Angle	15
Table 4.	Parameter Definitions for Fitting Single Exponential Profile	18
Table 5.	Generalized Single Exponential Profile Fits to Selected Hurricane Gilbert Cases	18
Table 6.	Parameter Definitions for Fitting Double Exponential Profile	20
Table 7.	Observed Pressure and Azimuthally Averaged Pseudo-Gradient Wind Maxima in Hurricane Gilbert and Estimated Generalized Profile Parameters	22
Table 8.	Comparison of Measured Flight-Level Wind Maxima and Fitted Gradient Wind Maxima for Double Exponential Pressure Profile	23

Preface

This report describes improvements developed for the planetary boundary layer surface wind field model traditionally used by the U.S. Army Corps of Engineers for hurricane modeling. Limitations of the model are also described. The upgraded model has increased flexibility for spatial resolution and pressure profile specification. The wind fields can be used in ocean response modeling, including wave and surge modeling activities.

This study was authorized by Headquarters, U.S. Army Corps of Engineers, under the Coastal Flooding and Storm Protection Area of the Coastal Research Program, Work Unit 32683, "Wind Estimation for Coastal Modeling." Technical Monitors were Messrs. John H. Lockhart, Jr.; John G. Housley; Barry W. Holliday; and John Saucier. Ms. Carolyn M. Holmes of the U.S. Army Engineer Waterways Experiment Station (WES), Coastal Engineering Research Center (CERC), was the Program Manager.

The study was conducted under Contract No. DACW39-93-C-0022 by Oceanweather, Inc. (OWI), Cos Cob, Connecticut. The report was prepared by Dr. Vincent J. Cardone and Messrs. Andrew T. Cox and J. Arthur Greenwood, all of OWI, and Dr. Edward F. Thompson of the Coastal Oceanography Branch (COB), Research Division (RD), CERC. Dr. Thompson was Principal Investigator of the research work unit funding this study. The work unit was under the direct supervision of Dr. Martin C. Miller, Chief, COB, and Mr. H. Lee Butler, Chief, RD, and under the general supervision of Mr. Charles C. Calhoun, Jr., Assistant Director, CERC, and Dr. James R. Houston, Director, CERC.

At the time of publication of this report, Director of WES was Dr. Robert W. Whalin. Commander was COL Bruce K. Howard, EN.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

Conversion Factors, Non-SI to SI Units of Measurement

Non-SI units of measurement used in this report can be converted to SI units as follows:

Multiply	By	To Obtain
degrees (angle)	0.01745329	radians
knots (international)	0.5144444	meters per second
miles (U.S. nautical)	1.852	kilometers

1 Introduction

Background

The unprecedented destruction of parts of the United States caused by hurricanes Andrew and Iniki last summer has aroused increased interest in the wind structure of tropical cyclones among the scientific and engineering communities. Unlike most past destructive storms, much of the loss in these recent storms was associated with direct wind damage. While simple parametric tropical cyclone wind models remain in use to model surface winds and to provide forcing for ocean response models, a few numerical vortex boundary layer models based upon solution of the primitive equations of motion have emerged, including most prominently the so-called U.S. Army Corps of Engineers (CE) wind model (Cardone et al. 1992). The model was developed originally at New York University in the early 1970's and later further developed at Oceanweather Inc. (OWI) under CE support in 1979. Recently the format of the CE model was modified to conform with the requirements of the CE Coastal Modeling System (Thompson 1993).

The CE numerical model was reviewed as part of a Workshop on Tropical Wind Modeling convened at the U.S. Army Engineer Waterways Experiment Station on 24-25 March, 1992. Invited participants in the review were:

- Dr. Wilson A. Schaffer, Techniques Development Laboratory, National Weather Service (NWS), National Oceanic and Atmospheric Administration (NOAA)
- Dr. Mark D. Powell, Hurricane Research Division (HRD), Atlantic Oceanographic and Meteorological Laboratory, Environmental Research Laboratories, NOAA
- Dr. Mukut B. Mathur, National Meteorological Center, NWS, NOAA
- Dr. Vincent J. Cardone, OWI

The workshop stressed the relationship between surface wind modeling and more general questions of the dynamical and thermodynamic nature of tropical cyclones. It also emphasized the need to carefully evaluate the reliability and representativeness of the scant surface marine wind data available in intense cyclones, before such data are used to further develop and validate numerical models.

The workshop addressed the potential for further development of existing numerical models, particularly the CE model. A number of specific research needs for improving wind models were identified and prioritized in terms of both importance to ocean response modeling and feasibility of success. These needs are summarized more fully in a "white paper" (Cardone and Thompson 1992).

Subsequent to the workshop, a study was initiated to address high priority upgrades to the CE model which could be accomplished with the limited funds available. The following tasks were chosen: (1) increase resolution and domain of the nested grid system; (2) generalize the surface pressure specification. The enhancements developed for the CE wind model are the subject of this report. The enhancements will be incorporated into the Coastal Modeling System in the near future.

Previous Studies

The CE wind model has been used mainly to provide wind fields in historical tropical cyclones to drive ocean response models operated in a hindcast mode (surface waves, mixed layer currents, storm surge). Those wind fields generally provide unbiased ocean predictions when used to drive CE and OWI ocean response models (e.g. Reece and Cardone 1982). They have also been used to drive ocean response models developed by other scientists independently, wherein CE model winds have also repeatedly been shown to provide unbiased hindcasts (e.g. Forristall 1980, WAMDI Group 1988, Cooper and Thompson 1989, Ly and O'Connor 1991, Grosskopf et al. 1991, Mairs et al. 1992). At OWI the model has been used in over three dozen studies to drive ocean response models to establish offshore design criteria in many parts of the world affected by tropical cyclones.

The CE model has been extensively used for both ocean wave and storm surge modeling for CE applications. Abel et al. (1989) applied the model to estimate wave statistics due to hurricanes in the Atlantic Ocean and Gulf of Mexico during 1956-75. Tracy and Hubertz (1990) estimated waves produced by 10 hurricanes impacting southern California during 1956-89. Mark and Scheffner (1993) describe a hurricane surge study for the coast of Delaware. A similar approach is presently being applied to the entire U.S. Atlantic Coast.

The generality of the CE model was also demonstrated when it was used to provide winds to test the third generation wave model (3GWAM) (WAMDI Group 1988). Winds supplied to the WAM model were exactly the same as winds for the subject storms (three intense Gulf of Mexico hurricanes) which had been used in previous studies to drive first and second generation models, and which had been used by other investigators. The WAM model was found to provide unbiased and skillful wave hindcasts in these storms, with WAM using its own calibration of source terms developed completely independently of CE winds. The same tuning on WAM has also been shown to provide

nearly perfect hindcasts in severe extratropical storms as well when driven by extremely accurate wind fields derived by direct kinematic analysis of wind measurements (Cardone et al. 1994).

Scope

In many of the studies cited above, ocean response models were used to evaluate the most extreme response (storm peak winds, waves, surge and currents) in a storm at a fixed site. In general, in storms in which the assumed storm pressure profile fits the actual radial distribution well, modeled storm peaks are unbiased in the mean and exhibit scatter index of 15 percent or less. The method is less successful in modeling the entire spatial and temporal distribution of the wind field in such storms. There are some storms in which even the storm peaks are difficult to simulate, where the storm structure departs from the simple structure implied by the presumed pressure distribution. This and other limitations of the CE model are described in more detail in Chapter 2.

In this study, two limitations of the CE tropical storm wind model are addressed and remedied. The first change is simply the addition of two additional nests to the grid system used to implement the numerical vortex model. This change provides lower truncation errors near the center of small intense storms, greater resolution near the vortex center, and an expanded solution domain. The second change is generalization of the radial surface pressure profile upon which the surface pressure initialization of the vortex model is based. The form adopted also allows the specification of profiles with two maxima in the radial pressure gradient. These changes are described in Chapter 3. A summary is given in Chapter 4.

2 Existing Model Limitations

The CE wind model developed by Cardone et al. (1992) has proved to be a powerful tool in ocean response modeling. However, the model, developed in 1979, includes a number of limitations. In light of enhanced computing power now available and the increasing field measurements and understanding of tropical storm behavior, it is timely to review the model limitations. Limitations of the CE model may be described in three basic categories: physics, initialization, and numerics.

Physics

The CE model evolved from the model of Chow (1971) who solved the momentum equations of an integrated boundary layer flow for a boundary layer of constant depth. The vertical friction force was taken parallel to the wind relative to the earth. Horizontal friction was also considered. The equations, however, were solved numerically on a nested cartesian grid system centered on the vortex and translating at constant velocity with the vortex. The steady solution in the moving coordinate system referred back to the earth yielded qualitatively realistic boundary layer wind patterns. The solution included supergradient flows inside the radius of maximum gradient wind and a decrease in the radius of maximum wind. It also included an asymmetric wind distribution with maxima in the right front quadrant for a typical superposition of a symmetric vortex and ambient gradient, and a boundary layer convergence pattern consistent with observed patterns of convection in typical storms.

Shapiro (1983) solved the same slab momentum equation as Chow (1971) but used a truncated spectral analysis in cylindrical coordinates, in order to allow a more convenient separation of the role of linear and non-linear asymmetric effects in the boundary layer flow. Chow's model and solution method provide the same patterns as that of Shapiro's model except that inside the radius of maximum wind truncation errors are larger than for the spectral solution. As a consequence, Chow's model may slightly overestimate the degree of supergradient flow inside the eye. These studies show that the essential physics governing the boundary layer flow are included in Chow's and Shapiro's models. The main physical processes missing are the feedback of

the convection (induced in part by the modelled convergence field) on the wind field, and strong non-steady effects (for example rapid deepening of the vortex in the moving frame) which may cause even the overlying vortex to be unbalanced.

The CE model is derived directly from Chow's formulation and uses Chow's numerical solution. Several improvements to Chow's solution were made to insure that it not only gives qualitatively realistic wind fields, but also provides a quantitatively correct surface stress vector distribution, from which the model diagnoses winds within the surface boundary layer as well. The main enhancements to Chow's model are in the inclusion of a similarity boundary layer formulation relating vertically integrated flow to the surface drag (magnitude and direction), adoption of more realistic boundary layer depths than considered by Chow or Shapiro, consideration of the effects of boundary layer stratification and variable surface roughness (expressed in terms of wind alone with no sea state effects considered), and incorporation of greater flexibility in the specification of the imposed pressure distribution of the vortex over the possibilities considered by Chow.

The CE model was developed with a secondary objective to provide winds over inland lake surfaces and land surfaces of arbitrary roughness. The theoretical development of this part of the model met with less success than the over-water treatment. A simplified equilibrium boundary layer approach was adopted which ignores the adjustment of the planetary boundary layer (PBL) wind field across discontinuities of roughness. Thus, while the model validation against winds measured over land indicated good agreement when the wind fetch was over a homogeneous roughness, little is known about the effect on ocean response modeling associated with failure in the CE model (probably) to resolve small scale PBL wind changes downwind of abrupt changes in roughness (e.g. the coast).

Initialization

The model is generally applied with boundary layer height in the range of 500 m - 650 m, slightly unstable stratification, a Charnock type surface roughness formulation (Charnock constant 0.035 with Karman constant 0.35), and a value of unity for the Ekman scale height parameter. This combination produces unbiased surface winds over the open sea when the model is applied to real storms and validated against measured surface wind time histories obtained by calibrated instruments (e.g. NOAA buoys, offshore rigs).

The pressure field is generally described as the superposition of the pressure gradient computed from the exponential pressure profile form for the symmetric part of the vortex:

$$p(r) = p_o + (p_{\infty} - p_o) e^{-\frac{r}{R_p}} \quad (1)$$

where

$p(r)$ = pressure

p_o = central pressure (at the eye)

p_{∞} = axisymmetric ambient pressure (far field pressure)

R_p = scaling radius

r = radius

and an uniform ambient gradient given by

$$f \bar{k} \times \bar{V}_g = - \frac{1}{\rho} \nabla p_{\infty} \quad (2)$$

where

f = Coriolis parameter

$\bar{k}$ = unit vector in the vertical direction

$\bar{V}_g$ = ambient uniform geostrophic flow

ρ = mean air density

∇p_{∞} = uniform ambient pressure gradient

This pressure initialization scheme (it is also a boundary condition since the model is solved to a steady state solution) often provides a very realistic simulation of the actual pressure field about a tropical cyclone. However, in some storms the actual pressure field departs from this simple picture in several possible ways. Often, particularly as a tropical cyclone enters the mid-latitudes, the ambient pressure field is inhomogeneous. The effect is especially evident if the tropical cyclone begins to interact with a frontal system or an extratropical cyclone or both. Within the tropics, some storms have been shown (Holland 1980) to follow the more general form:

$$p(r) = p_o + (p_m - p_o) e^{-\left(\frac{r}{r_m}\right)^B} \quad (3)$$

where

B = constant in the general range 0.5-2.5

Finally, in some storms the radial pressure profile in the inner core is more irregular than either of the above forms, with a shape which implies two maxima in the radial pressure gradient, accompanied by two distinct maxima in the wind speed. Willoughby (1990) and Black and Willoughby (1992) have described the tendency for "concentric rings" in the radial wind distribution to be a fairly typical characteristic of intense tropical cyclones. The rings appear to be related intimately to storm intensity evolution. For example, Figure 1 shows the evolution of concentric rings in Hurricane Gilbert (1988) over a six-day period. In this storm, the CE model might be expected to provide reasonably accurate wind fields in the initial stage of vortex development and intensification between September 11-13, but it would fail to model the complicated double maxima structures later. The impact on ocean response modeling of this failure to model concentric rings is unknown.

Numerics

The CE model is computationally demanding. For example, computational considerations drove the decision to presolve the boundary layer model for spatially homogeneous (constant) boundary layer height and stability and to use a table look-up procedure for the drag coefficient during the marching of the solution toward steady state. To relax the constraint of constant boundary layer height and stability would greatly increase computer time, unless a more efficient integration scheme could be found. The minimum grid spacing on the inner nest of the solution grid (as opposed to the target grid) is 5 km, which is a bit too large to resolve details of the wind field near the center in very tight storms. (For example, as Hurricane Andrew approached the south Florida coast, the radius of maximum wind was only about 11 km.) The grid spacing is also not sufficient to resolve boundary layer adjustments near roughness discontinuities, though that physical process is not presently incorporated in the numerical model. Further, the grid spacing is too coarse to resolve detailed gradients of wind over inland bays and estuaries. Limitations in temporal resolution are less serious, within the constraint of the steady-state model, since the "time step" of the windfields is simply the temporal resolution of the storm track. That temporal resolution can be refined within reason (say to intervals of 15 minutes or so) without significant computational cost.




Figure 1. Temporal changes in the azimuthally averaged wind for NOAA reconnaissance flights into Hurricane Gilbert; changes are normalized to a 6-hr time interval (from Black and Willoughby (1992))

Summary of Limitations

The main model limitations described in each category above may be listed as follows:

a. Physics.

- (1) Decoupling of boundary layer from full vortex dynamics, precluding mutual adjustment of pressure and wind fields; and feedback of convective scale effects on wind field.
- (2) Simplified PBL theory (e.g. constant Ekman scale height).
- (3) Extrapolation of Charnock roughness to extreme wind speeds, with no sea state dependence.
- (4) No boundary layer adjustment across roughness discontinuity.

b. Initialization.

- (1) Constant and homogeneous boundary layer height.
- (2) Constant and homogeneous stratification.
- (3) Relatively simple pressure specification:
 - (a) Exponential pressure profile provides only one radius of maximum wind (no concentric rings).
 - (b) Pressure profile may be inadequate even for unimodal maximum gradient pressure distributions.
 - (c) Homogeneous ambient linear pressure gradient.

c. Numerics.

- (1) Practical limit of spatial resolution to 5 km may be inadequate for very tight storms.
- (2) Large number of iterations (800) required for each steady state configuration, or snapshot (using the terminology of Cardone et al. 1992).

In this study, two of the above limitations are addressed and remedied, as described in the next section.

3 Upgraded Model

Increased Resolution

The CE program consists basically of two main programs (Cardone et al. 1992). The first, SNAP, solves the numerical vortex model on a nested grid a number of times to represent the storm wind field at discrete times within an event, thereby producing a number of *snapshot* wind fields on a nested grid. SNAP also writes the snapshots to a file for use by the second main program HIST, which among other functions, interpolates the nested grid solutions to hourly intervals and then interpolates the winds to an output or *target* grid (typically that of an ocean response model).

The nested grid consists of five square 21 by 21 grid point arrays. The grid spacing increases by a factor of two from nest to nest. In the program input, the user specifies a desired spacing of the inner nest (the variable DX in name-list NAME3 of SNAP). For the default value of 5 km, the grid spacing in the coarsest nest becomes 80 km and the entire grid covers an area of (1,600 km²). While the existing CE program allows users to set DX smaller than 5 km, this is not recommended since the grid coverage shrinks commensurately. The simplified boundary condition applied on the outer boundary of the outermost nest becomes increasingly tenuous as the gridded domain shrinks.

The upgraded program allows the use of up to seven nests. However, the user may specify the number of nests (from three to seven) in a given run. The new parameter INSIDE is used to specify the number of active nests. It designates which is the finest active nest, where nests are numbered from 1 to 7 going from finest to coarsest. For example, INSIDE = 1 activates all seven nests, and INSIDE = 2 activates only nests 2 through 7. The grid spacing of nest 1, the innermost nest, is specified as before with variable DX, regardless of whether or not the nest is active. The relationships between INSIDE, active nests, and spacing of the finest active nest are summarized in Table 1. The default value of DX is 2 km. If all seven nests are exercised, the execution time per snapshot is roughly four times as long as the existing CE model. For this case the number of iterations on the inner nest is set to the default value of 3200.

Table 1
Effect of Nest Activation Parameter, INSIDE

INSIDE	Active Nests	Spacing of Finest Active Nest
1	1 - 7	DX
2	2 - 7	2 DX
3	3 - 7	4 DX
4	4 - 7	8 DX
5	5 - 7	16 DX

The program with the new nesting was tested in two ways using the Hurricane Camille snapshots as test cases. First, vortex model winds were produced by the CE model (and its OWI equivalent) for the case of $DX = 8$ km. Then, the same SNAP inputs were used to generate winds with the new code for the case $DX = 2$ km, $INSIDE = 3$, which provides the equivalent number of nests and inner nest grid spacing as the CE model run. Winds produced by the two alternative programs were interpolated to a target grid covering the Gulf of Mexico (nominal spacing of 0.2 deg^1), compared and found to agree to within roundoff error of the VAX computer used for these tests.

The second test compared winds for Camille produced by the new code for the case $DX = 2$ km and $INSIDE = 1$; that is, all seven nests are live with inner nest grid spacing of 2 km, with winds produced by the CE program with $DX = 5$ km. These results are shown in Appendix A which gives, at 30-minute intervals, the maximum scalar wind speed, the location and the corresponding wind speeds and directions, and the same data for the maximum vector wind difference magnitude. The results (see also Figure 2) indicate that the largest differences (scalar differences of up to about 7 m/s), occur inside the eyewall, where truncation errors on the 5-km solution are expected to be large for an intense tight vortex such as Camille. Maximum scalar wind speed differences in the area of the eyewall are generally less than 1 m/sec. However, maximum vector difference magnitudes of up to 9 m/sec were observed occasionally in the vicinity of the eyewall reflecting a tendency for the wind direction on the 2-km solution to be turned systematically in the direction of less inflow, by up to 10 deg from the 5-km solution. The 2-km solutions are no doubt the more accurate solutions.

¹ A table of factors for converting non-SI units of measurement to SI units is presented on page vi.




Figure 2. Distribution of maximum wind speed differences between 5-nest and 7-nest model runs for Hurricane Camille

Generalized Pressure Specification

Pressure profile form

The upgrade to the pressure specification uses a generalized form of Holland's (1980) exponential pressure profile

$$p(r) = p_o + \sum_{i=1}^n dp_i e^{-\left(\frac{R_p}{r}\right)^{k_i}} \quad (4)$$

where

n = number of components

dp_i = pressure anomaly for the i 'th component ($dp_1 + dp_2 + \dots + dp_n = p_\infty - p_o$)

R_{pi} = scaling radius for the i 'th component

B_i = Holland's B coefficient for the i 'th component

The corresponding tangential and radial pressure gradients are:

$$\frac{\partial p}{\partial \theta} = 0 \quad (\text{tangential})$$

$$\frac{\partial p}{\partial r} = \sum_{i=1}^n B_i dp_i \left(\frac{R_{pi}}{r} \right)^{p_i} \left(\frac{1}{r} \right) e^{-\left(\frac{R_{pi}}{r} \right)^{p_i}} \quad (\text{radial}) \quad (5)$$

The CE model was modified to provide options for a single or double exponential component ($n = 1$ or $n = 2$). This form allows the specification of pressure profiles with two separate maxima in the radial pressure gradient, though the mere form does not guarantee two maxima. For example, the sum of two exponentials also allows the modeling of pressure profiles which have only one maximum but with shapes very different from those predicted by the single exponential even with the variable B included.

Incorporation of this model into the seven-nest version of the program led to extensive changes to program SNAP, in particular to Subroutines GRAD and PXYM and further changes to namelist NAME3, as documented in Appendix B. One immediate consequence of this model is that the quadrantal specification of profile parameters allowed in the single exponential form with $B = 1$ is lost. To retain this option in the CE model portfolio, two versions of the upgraded program were developed as follows:

SNAP_ADC.7NE and HIST_ADC.7NE - This version only upgrades the current CE program (which includes quadrantal variation of parameters for a single exponential with $B = 1$) to incorporate the additional nests.

SNAP_HOL.7NE - This version upgrades the current CE model to allow both 7 nests and the generalized pressure specification scheme, but without quadrantal variation. Note, however, that asymmetry in the pressure field is still modeled through superposition of the vortex pressure field and the background steering gradient. The background pressure gradient is required to be homogeneous (that is, the parameter ST12 is eliminated).

Modified outflow

In early tests of the upgraded CE program with hypothetical snapshot inputs estimated roughly to apply to several stages of Hurricane Gilbert (inputs for

Gilbert snapshots were derived more rigorously as described below), it was demonstrated that the program could produce the pattern of annular concentric wind maxima. However, it was noticed that the inflow characteristics of the model appeared to have changed somewhat from the unimodal model. In the standard CE model, Subroutine OUTFLOW serves to remove 8 degrees of inflow from the snapshot solution throughout the domain to compensate approximately for inflow believed to be spuriously introduced through the numerical solution. This spurious inflow is revealed by solving the model for a motionless vortex with all friction terms deactivated and comparing the modeled wind direction to the purely circular flow expected of a vortex in gradient balance.

The frictionless, motionless vortex test was repeated with the upgraded model for the series of nine snapshots indicated in Table 2. For the unimodal case (Case 1) and the bimodal cases with $B = 1$ for both exponentials (cases 2 and 6), the maximum inflow (which tends to occur just outside the wind maxima) averages 7.5 deg. As the value of B increases, however, there is a proportional increase in the inflow. In the bimodal profile with B varying between the two exponentials, the inflow varies with radius. Subroutine OUTFLOW was modified to compensate for dependence of spurious inflow on B (Table 3).

Table 2
Maximum Inflow Observed in Frictionless Stationary Vortex Solution¹

Case	p_0 mb	R_{m1} nm	R_{m2} nm	dp_1 mb	dp_2 mb	B_1	B_2	(Max inflow), deg	(Max inflow), deg
1	970	27	0	40	0	1.00	0.00	7.2	—
2	915	8	58	68	27	1.00	1.00	7.3	7.3
3	915	8	58	68	27	1.00	2.00	6.6	13.1
4	915	8	58	68	27	2.52	1.00	18.7	6.6
5	915	8	58	68	27	2.52	2.00	26.8	16.5
6	890	6	42	53	67	1.00	1.00	8.0	7.7
7	890	6	42	53	67	1.00	1.26	8.1	9.1
8	890	6	42	53	67	2.52	1.00	12.7	7.5
9	890	6	42	53	67	2.52	1.26	15.1	9.0

¹ All runs were done with the upgraded CE model with 7 nests and generalized pressure specification; $p_0 = 1010$ mb for all runs

Table 3 Empirical Correction of Inflow Angle	
Exponential	Reduction Applied To Inflow Angle deg
Unimodal $B = 1$	8
Unimodal $B \neq 1$	$8 B$
Bimodal	$8 \left(\frac{B_1 + B_2}{2} \right)$

Specification of pressure parameters

Single Exponential Profile: $B = 1$. In the standard CE model, the pressure profile may be specified in basically two ways. The most fundamental way is to fit the profile to sea level pressure measurements available at different radii at a given time, or transformed from time to space using single station data acquired at a station in the path of the storm. There are several examples of this approach as applied to historical U.S. Gulf of Mexico and East Coast hurricanes in Graham and Hudson (1960). The eye pressure may be prescribed, if it is known, for a more accurate fit, or the eye pressure may be extrapolated from a fit determined exclusively from data outside the center. A simplification to this procedure is often followed for oceanic storms, for which eye pressure may be known from aircraft dropsonde data, far field pressure is estimated from weather maps, and a few estimates of pressure at various radii about the storm are known from ship or island station synoptic reports. Then, the unknown parameter scale radius may be estimated from Equation 1 as follows for each such report and an average or weighted average of the estimates taken to represent the storm profile at map time:

$$R_p = -r \ln \left(\frac{p(r) - p_o}{p_m - p_o} \right) \quad (6)$$

If there are insufficient pressure data but eye pressure is known and an estimate of the radius of maximum wind, R_m , is known (e.g. from aircraft vortex message reports filed upon penetration of the eye and assuming that R_m at flight level is the same as R_m at the surface, or more crudely from radar or satellite eye diameter estimates), R_p may be estimated directly from R_m using the average relationship found between these two variables by the vortex model.

Single Exponential Profile: Variable B . Variants of these same two approaches may be followed to estimate the parameters of the generalized unimodal model, for which the additional parameter B must also be specified. Again, if there are sufficient pressure data, the profile may be fitted directly. For example, Figure 3 shows the screen display of a PC-based interactive system developed at OWI using a commercially available plotting/statistical analysis software package. The pressure data are composited (see window in upper right hand corner of screen) as a function of radius in a South China Sea typhoon from reduced (from flight level) aircraft pressures and pressures reported by ships within a 3-hr time window of analysis time. The aircraft also provided estimates of eye pressure (note the two conflicting estimates at the origin in the lower window of Figure 3). Far field pressure was estimated from weather maps. The best fit shown is for $p_o = 968$ mb, $B = 0.8$, and $R_p = (14 \text{ nm})^{0.8}$. The window at the upper left of the screen compares the azimuthally averaged solution for the model surface wind (downloaded from a run made on a VAX) and reduced aircraft and ship reports of wind.

The second approach is more indirect and emphasizes the use of aircraft wind data. In recent years such data have become quite accurate after the introduction of inertial navigation systems, onboard processing and the availability of coded messages (so-called supplementary or peripheral flight level winds) containing measured winds at flight level outside the eye. Figure 1 shows the complete analysis carried out by Black and Willoughby (1992) of flight data acquired over the main lifetime of Hurricane Gilbert in the Caribbean Sea and Gulf of Mexico. These curves show 12 separate radial profiles of the azimuthally averaged flight level (700 mb or 850 mb) tangential wind speed composited from flight legs near the indicated times. Most of the wind profiles exhibit two distinct wind maxima. On the assumption that the azimuthally averaged flow is approximately in gradient balance with the axisymmetric pressure field, the pressure profile associated with double concentric wind maxima should also exhibit two local maxima in the pressure gradient. Therefore they might be fitted by a double exponential profile. Even those profiles which do not exhibit two distinct peaks, such as those in panels *b*, *d*, and *e*, exhibit atypical shapes for tropical cyclones, with a single maximum and broad regions with little or no change of wind speed with radius. Nevertheless, we have selected five of these cases to illustrate the fitting of the single exponential profile using aircraft wind data and eye pressure. Parameters are defined in Table 4 and results from the fitting process are given in Table 5.

The fitting method is basically a systematic search of many possible solutions of the single exponential for that solution whose radial distribution of implied gradient wind provides a close match to the location and magnitude of the azimuthal average flight level wind. This searching program (implemented in a preprocessing program called 1EYEWALL.F90L) requires the input information listed in Table 5. Additional documentation is given in Appendix B. The searching program fixes the profile anomaly parameter ($p_m - p_o$), loops through possible values of the scale radius R_p (from R_m to $2R_m$) and B (from 0.5 to 2.52) and finds the pressure profile whose gradient wind simultaneously

Oceanweather Tropical System Analysis
Surface Winds and Pressures Estimated from
Recon, Vortex and Periperal Data Messages

Typhoon WAYNE86
86090212 +/- 3hrs




Figure 3. Example of Oceanweather tropical storm analysis

Table 4 Parameter Definitions for Fitting Single Exponential Profile	
Parameter	Definition
R_m	Observed radius of maximum wind
V_m	Azimuthally averaged tangential flight level wind at R_m
V_{m150}	Azimuthally averaged tangential flight level wind at 150 km from center
R_p	Scale radius of single exponential profile
dp	Storm pressure anomaly parameter of single exponential profile
B	Holland's B
R_{gm}	Radius of maximum gradient of fitted pressure profile
V_{gm}	Maximum gradient wind of fitted pressure profile
V_{g150}	Gradient wind of fitted profile 150 km from center

Table 5 Generalized Single Exponential Profile Fits to Selected Hurricane Gilbert Cases											
Case	Input					Output					
	P_o mb	P_{-} mb	R_m km	V_m m/s	V_{m150} m/s	r_p km	dp mb	B	V_{gm} m/s	R_{gm} km	V_{g150} m/s
3	905	1012	16	65	30	20	107	1.50	67.2	20	21
4	888	1012	13	69	30	16	124	1.41	70.3	16	20
7	951	1012	65	38	36	97	61	1.00	39.3	87	36
8	950	1012	69	41	38	92	62	1.12	42.2	85	38
9	949	1010	57	40	37	85	61	1.12	41.9	79	37

best matches the observed wind speeds at R_m and at 150 km in terms of absolute difference. For example, in Case 3 of Table 5 the selected profile gradient wind (not shown) is within 1 m/s of the V_m of 65 m/s at R_m . However the searching program places the absolute profile maximum of 67.2 m/s at a radius of 20 km, and fails to maintain the observed broad region of little change in wind speed between 50 and 150 km, resulting in a profile wind speed of only 21 m/s at 150 km, about 10 m/s lower than measured. Cases 7, 8 and 9 are somewhat more successful. The parameter B varies between 1.0 and 1.5 for these fits, or in the same general range reported by Holland for a single exponential.

Double Exponential Profile. While it is conceivable that there may be sufficiently voluminous and accurate pressure data in some tropical cyclones to

attempt to directly fit a double exponential profile to measurements of surface pressure as a function of radius, we have not attempted to construct such a data set and perform such a fit. We did try, without success, to develop useful fits to the profile from just the total storm anomaly, estimates of the two radii of maximum wind and a single pressure along the profile in the region between the two maxima. However, a generalization of the searching algorithm described above for a single exponential has met with some success.

The searching algorithm (called 2EYEWALL.HOL) as applied to a double exponential is documented in Appendix B. Parameters involved are defined in Table 6 and Figure 4. The searching program fixes the total storm anomaly, assumes the scale radius for the inner exponential is equal to the observed radius of maximum wind of the inner maximum, or ring, and loops through ranges of the outer scale radius, R_{p2} (from R_{m2} to $2R_{m2}$), inner and outer B (from 0.5 to 2.52) and the ratio of dp_1/dp_2 (from 1/8 to 8). The algorithm seeks the combination whose pressure profile provides a gradient wind profile that has maxima at R_{m1} and R_{m2} within ± 1 m/s of observed and which maximizes the following:

$$V_{s1} + V_{s2} - 2 V_{sm} \quad (7)$$

where

$$V_{sm} = \text{gradient wind at } (R_{m1} + R_{m2})/2$$

If it succeeds in finding such a profile it checks that the wind at 150 km is lower than the outer maximum, V_{m2} , and if it is, prints the solution. If these conditions are not met, another cycle is attempted. The matching criterion is relaxed to ± 2 m/s, this time requiring that the wind at $(R_{m1} + R_{m2})/2$ is less than the winds prescribed at R_{m1} and R_{m2} , and minimizing the wind at 150 km. The program also prints the profile parameters for the selected profile. If, after the second cycle the program still does not find a successful fit, it prints the closest fit found in each cycle.

Table 7 shows the results of the application of this searching algorithm to all 12 of the azimuthal average tangential flight level wind profiles in Hurricane Gilbert derived by Black and Willoughby (1992). The double exponential appears to require large values of B to resolve two distinct peaks in the radial profile of gradient wind, at least for most of these cases. Table 8 compares the location and magnitude of the double wind maxima derived from the fitted profile to those observed. Figure 5 compares the fitted and observed radial profiles of pseudo-gradient wind. The inner ring is usually fitted very closely. In 11 out of 12 of the cases a distinct outer wind maximum is resolved, and it is usually placed within ± 20 km of the observed maximum. In 9 out of those 11 cases, the maximum is within about ± 2 m/s of that observed. Case 8 is the poorest fit, but in practice Case 7 and Case 8 are so close in time

Table 6 Parameter Definitions for Fitting Double Exponential Profile	
Parameter	Definition
R_{m1}	Radius of maximum wind, inner ring
R_{m2}	Radius of maximum wind, outer ring
V_{m1}	Azimuthally averaged tangential flight level wind, inner ring
V_{m2}	Azimuthally averaged tangential flight level wind, outer ring
R_{p1}	Scale radius, inner exponential
R_{p2}	Scale radius, outer exponential
dp_1	Pressure anomaly, inner exponential
dp_2	Pressure anomaly, outer exponential
B_1	Holland's B , inner exponential
B_2	Holland's B , outer exponential
R_{g1}	Radius of maximum gradient wind of fitted profile, inner ring
R_{g2}	Radius of maximum gradient wind of fitted profile, outer ring
V_{g1}	Maximum gradient wind of fitted profile, inner ring
V_{g2}	Maximum gradient wind of fitted profile, outer ring

(in fact they are derived from the same flight) that Case 7 may be used to represent this phase of the storm history.

Sample Runs

The upgraded program, including seven nests and the generalized pressure specification, has been applied to provide sample wind fields on target grids using as test input the snapshots developed for Hurricane Gilbert. Two runs were made. The first generates a snapshot wind field for each of the 12 Gilbert cases (including realistic forward motion and steering flow parameters) and interpolates each snapshot to a polar grid using a test history table. Interpolations are also made from pairs of adjacent snapshots (equal time weight). Winds for the 23 wind fields so produced on the polar grid are then azimuthally averaged. These results are given in Appendix C.

A second test run was made which modeled Gilbert during its passage across the Gulf of Mexico between 1200 UT 15 September through 0000 UT 17 September, 1988. Snapshots for this run consisted of Cases 7, 9, 11, and 12. The target grid for this run was a grid of nominal 12 nm spacing covering the Gulf of Mexico. The wind fields were output at 12-hourly intervals. Additional details and surface wind field plots are given in Appendix D.




Figure 4. Some parameters in double exponential profile

Table 7

**Observed Pressure and Azimuthally Averaged Pseudo-Gradient Wind Maxima
In Hurricane Gilbert¹ and Estimated Generalized Profile Parameters**

Case	Date/ Time (UTC)	Input						Output					
		p_o mb	p_{-} mb	R_{m1} km	R_{m2} km	V_{m1} m/s	V_{m2} m/s	R_{p1} km	R_{p2} mb	dp_1 mb	dp_2 mb	B_1	B_2
1	11/1624	972	1011	47	90	40	35	47	127	23	16	2.52	2.52
2	11/2002	968	1011	58	108	47	36	58	162	32	11	2.52	2.52
3	13/1744	905	1012	16	111	65	32	16	125	94	13	1.68	2.39
4	13/2333	888	1012	13	100	69	38	13	100	110	14	1.59	2.52
5	14/0549	893	1012	13	70	62	44	13	70	101	18	1.41	2.52
6	14/1126	890	1012	13	69	62	48	13	69	102	20	1.41	2.52
7	15/1204	951	1012	22	65	25	38	22	87	45	16	0.56	2.52
8	15/1629	950	1012	32	69	28	41	32	103	35	27	0.94	2.51
9	16/0016	949	1010	22	57	27	40	22	81	41	20	0.75	2.52
10	16/0539	950	1011	55	120	41	37	55	170	52	9	1.12	2.24
11	16/1850	953	1010	50	100	42	43	50	119	47	10	1.33	2.52
12	16/2131	954	1009	40	100	39	40	40	112	45	10	1.19	2.52

¹ Cases correspond to Black and Willoughby's (1992) analysis of aircraft data in Hurricane Gilbert

Table 8
Comparison of Measured Flight-Level Wind Maxima and Fitted
Gradient Wind Maxima for Double Exponential Pressure Profile¹

Case	Inner Ring				Outer Ring				
	Measured		Fitted		Measured		Fitted		
	R_{m1} km	V_{m1} m/s	R_{g1} km	V_{g1} m/s	R_{m2} km	V_{m2} m/s	R_{g2} km	V_{g2} m/s	V_g at R_{m2} m/s
1	47	40	47	39.6	90	35	110	37.1	35.7
2	58	47	58	46.6	108	36	108 ²	35.7 ²	—
3	16	65	16	66.7	111	32	105	33.7	33.6
4	13	69	13	70.3	100	38	85	37.2	36.3
5	13	62	13	63.5	70	44	59	46.2	45.4
6	13	62	13	63.7	69	48	59	48.4	47.3
7	22	25	22	26.3	65	38	82	39.2	36.1
8	32	28	30	29.7	69	41	98	48.1	39.2
9	22	27	21	28.9	57	40	78	43.4	38.1
10	55	41	55	39.2	120	37	120	37.1	—
11	50	42	50	40.7	100	43	93	41.5	41.3
12	40	39	40	32.9	100	40	92	38.4	38.2

¹ Cases correspond to Black and Willoughby's (1992) analysis of Hurricane Gilbert

² Second ring maximum not resolved, profile gradually decays from inner maximum




Figure 5. Comparison of azimuthally averaged reconnaissance winds and fitted gradient winds in 12 cases of Hurricane Gilbert defined by Black and Willoughby (1992)

4 Summary

The CE tropical cyclone surface wind field model has been a very useful tool in ocean response modeling for more than a decade. The model continues to be used regularly. The CE recently held a workshop to reassess model assumptions, particularly in light of modern advances in computing technology and field measurement of hurricane structure. Model limitations were identified and evaluated in terms of their perceived importance to ocean response modeling and the level of effort required to develop improved solutions. The limitations are summarized in this report.

Two aspects of the CE model were targeted for improvement. This report describes the improvements developed for the upgraded model. First, the standard CE model represents a compromise between spatial resolution in the central region of very high gradients, coverage of the full ocean area affected by the tropical cyclone, and computer requirements. Computing resources are much more available now than at the time the model was developed in the late 1970's. The model was upgraded to include more computationally intensive options which give improved resolution and areal coverage. Up to seven nested grids are now available, compared to only five nests in the standard model. In a typical application, this upgrade can be used to achieve 2-km resolution around the eye (as compared to 5-km resolution often used in the standard model) and an expanded total coverage area.

The second upgrade to the standard CE model allows a more general specification of the axisymmetric pressure profile. This upgrade can be used to create wind fields with maxima at two different radii or with a broad maximum extending over a range of radii. It also provides more flexibility in fitting the shape of single peaked wind profiles.

The upgraded model is demonstrated with historical hurricanes. The five-nest and seven-nest models are applied to Hurricane Camille. The fully upgraded model, with seven nests and general pressure specification, is applied to Hurricane Gilbert. This hurricane was chosen because it is well-documented by Black and Willoughby (1992) and it evolved into some non-traditional storm structures. The upgraded model was more effective than the standard CE model in simulating the storm.

References

- Abel, C. E., Tracy, B. A., Vincent, C. L., and Jensen, R. E. (1989). "Hurricane hindcast methodology and wave statistics for Atlantic and Gulf hurricanes from 1956-1975," WIS Report 19, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- Black, M. L., and Willoughby, H. E. (1992). "The concentric eyewall cycle of Hurricane Gilbert," *Mon. Weather Rev.*, American Meteorological Society, 120, 947-957.
- Cardone, V. J., and Thompson, E. F. (1992). "Numerical modeling of tropical cyclone boundary layer winds: status, limitations and priorities," unpublished report prepared for U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- Cardone, V. J., Graber, H. C., Jensen, R. E., Hasselmann, S., and Caruso, M. J. (1994). "In search of the true surface wind field in SWADE IOP-1: ocean wave modelling perspective," to be submitted to *Atmosphere-Ocean System Journal*.
- Cardone, V. J., Greenwood, C. V., and Greenwood, J. A. (1992). "Unified program for the specification of hurricane boundary layer winds over surfaces of specified roughness," Contract Report CERC-92-1, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- Chow, S. H. (1971). "A study of the wind field in the planetary boundary layer of a moving tropical cyclone," M. S. thesis in Meteorology, School of Engineering and Science, New York University, New York, N.Y.
- Cooper, C., and Thompson, J. D. (1989). "Hurricane-generated currents on the outer continental shelf, 1, model formulation and verification," *J. Geophys. Res.* 94(C9), 12513-12540.
- Forristall, G. Z. (1980). "A two-layer model for hurricane driven currents on an irregular grid," *J. Phys. Oceanog.* 10(9), 1417-1438.

- Graham, H. E., and Hudson, G. N. (1960). "Surface winds near the center of hurricanes and other cyclones," National Hurricane Research Project Report No. 39, Wash., DC.
- Grosskopf, W. D., Griffon, D. L., Berek, E. P., and Sharma, J. N. (1991). "Gulf of Mexico wind, wave, and current database," *Proc., Offshore Tech. Conf. OTC 6539*, Houston, TX, 1, 357-364.
- Holland, G. J. (1980). "An analytic model of the wind and pressure profiles in hurricanes," *Mon. Weather Rev.* 108, 1212-1218.
- Ly, L. N., and O'Connor, W. P. (1991). "Gulf coast hurricane surge simulations using a numerical ocean circulation model," *Proc., MTS '91 Conf.*, Marine Technology Society, New Orleans, LA.
- Mairs, H. L., Koch, S. P., Gordon, R. B., and Cuellar, R., Jr. (1992). "The storm current response of Gulf of Mexico hurricanes," *Proc., Offshore Tech. Conf. OTC 6833*, Houston, TX, 235-242.
- Mark, D. J., and Scheffner, N. W. (1993). "Validation of a continental-scale storm surge model for the coast of Delaware," *Proc. Estuarine and Coastal Modeling Conference*, ASCE, Chicago, IL, 249-263.
- Reece, A. M., and Cardone, V. J. (1982). "Test of wave hindcast model results against measurements during four different meteorological systems," *Proc., Offshore Tech. Conf. OTC 4323*, Houston, TX, 269-293.
- Shapiro, L. J. (1983). "The asymmetric boundary layer flow under a translating hurricane," *J. Atmospheric Sci.* 39(Feb.).
- Thompson, E. F. (1993). "HURWIN: Tropical Storm Planetary Boundary Layer Wind Model," *Coastal Modeling System (CMS) User's Manual*, Instruction Report CERC-91-1, Supplement 2, M. A. Cialone, ed., U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- Tracy, B. A., and Hubertz, J. M. (1990). "Hindcast hurricane swell for the coast of southern California," WIS Report 21, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- WAMDI Group. (1988). "The WAM model - a third generation ocean wave prediction model," *J. Phys. Oceanog.* 18, 1275-1810.
- Willoughby, H. E. (1990). "Temporal changes of the primary circulation in tropical cyclones," *J. Atmospheric Sci.* (47), 242-264.

Appendix A

Comparison of Five-Nest and Seven-Nest Models for Hurricane Camille

Comparison of modeled winds at 20-m height and at 30-min intervals in alternative hindcasts of Hurricane Camille in the Gulf of Mexico during August 1969. The run labelled "5-Nests" used the standard CE model with 5-km spacing on the inner nest. The run labelled "7-Nests" used the upgraded CE model with seven-nests and grid spacing of 2 km on the inner nest. The first (second) line at each time step gives: maximum scalar (vector magnitude) wind speed difference found on the grid between the two runs, latitude and longitude of the grid point, and wind speed and direction of the alternative solutions at that grid point.

Table A1
Comparison of Wind Estimates from 5-Nest and 7-Nest Models,
Hurricane Camille

Day/ Hour	Max. Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg az	Speed m/s	Dir. deg az
161200	7.1	24.1	-85.7	27.9	151.7	20.8	162.6
	8.4	24.1	-85.7	27.9	151.7	20.8	162.6
161230	3.0	24.1	-86.0	39.7	336.6	36.7	342.5
	6.0	24.1	-85.7	42.0	172.2	43.1	180.1
161300	1.2	24.1	-85.7	41.6	181.0	42.8	183.7
	7.0	24.3	-86.0	52.6	47.1	52.9	54.6
161330	2.2	24.3	-86.0	43.6	78.8	41.4	88.0
	7.2	24.3	-86.0	43.6	78.8	41.4	88.0
161400	1.5	24.3	-86.0	38.1	131.1	36.7	140.6
	6.7	24.3	-86.2	51.0	2.0	50.1	9.5
161430	3.4	24.3	-86.2	40.7	369.4	37.3	5.4
	7.3	24.3	-86.0	43.5	150.1	45.2	159.3
161500	2.1	24.3	-86.2	21.2	312.9	23.2	306.1
	5.3	24.5	-86.2	53.0	52.8	54.0	58.3
161530	2.4	24.3	-86.2	31.2	240.3	33.6	242.5
	8.2	24.5	-86.2	49.6	80.5	49.2	90.0
161600	1.0	24.3	-86.4	46.5	312.6	45.5	316.1
	8.9	24.5	-86.2	47.6	106.6	46.9	117.4
161630	3.8	24.5	-86.4	39.5	16.6	35.7	22.6
	6.2	24.5	-86.2	46.3	139.6	47.9	145.9
161700	1.5	24.5	-86.4	9.8	339.9	8.4	342.7
	3.6	24.8	-86.4	53.0	57.2	54.1	60.8
161730	1.9	24.5	-86.4	23.2	226.5	25.1	232.6
	5.4	24.8	-86.4	52.2	74.4	52.9	80.2
161800	2.0	24.5	-86.4	36.8	209.7	38.8	212.5
	6.9	24.8	-86.4	49.9	103.1	51.0	110.8
161830	3.4	24.8	-86.7	43.7	27.9	40.3	36.3
	7.0	24.8	-86.7	43.7	27.9	40.3	36.3
161900	2.1	24.8	-86.7	14.7	2.9	12.7	359.3
	3.0	25.0	-86.7	53.2	53.0	54.2	55.9
161930	2.8	24.8	-86.7	25.2	226.3	28.0	231.6
	6.0	25.0	-86.7	52.0	76.3	52.6	82.9
162000	1.9	24.8	-86.7	36.1	217.8	38.0	219.8
	7.9	25.0	-86.7	48.9	102.0	49.9	111.1
162030	3.1	25.0	-86.9	44.4	20.2	41.3	28.9
	7.2	25.0	-86.9	44.4	20.2	41.3	28.9

(Sheet 1 of 6)

Table A1 (Continued)							
Day/ Hour	Max. Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg az	Speed m/s	Dir. deg az
162100	1.2	25.0	-86.7	44.1	159.6	45.3	163.4
	3.2	25.0	-86.7	44.1	159.6	45.3	163.4
162130	2.4	25.0	-86.9	24.7	255.5	27.0	257.8
	6.8	25.3	-86.9	51.9	68.2	52.2	75.7
162200	1.7	25.2	-86.9	47.8	95.4	46.2	106.5
	9.3	25.2	-86.9	47.8	95.4	46.2	106.5
162230	2.8	25.2	-87.1	45.4	13.3	42.6	22.2
	7.6	25.2	-86.9	46.9	132.4	46.9	141.6
162300	1.6	25.2	-86.9	43.4	163.1	44.9	167.5
	3.7	25.2	-86.9	43.4	163.1	44.9	167.5
162330	2.1	25.2	-87.1	26.5	267.8	28.6	268.0
	7.7	25.4	-87.1	51.0	64.2	51.3	72.8
170000	1.8	25.4	-87.1	44.0	94.1	42.2	104.8
	8.2	25.4	-87.1	44.0	94.1	42.2	104.8
170030	1.2	25.4	-87.4	48.6	345.6	47.3	352.7
	6.1	25.4	-87.4	48.6	345.6	47.3	352.7
170100	2.2	25.4	-87.4	41.8	313.1	39.6	318.0
	7.2	25.6	-87.4	51.9	29.6	51.8	37.5
170130	2.4	25.6	-87.4	31.0	7.0	28.6	6.2
	5.0	25.6	-87.1	45.7	149.9	46.8	155.9
170200	0.9	22.6	-88.5	8.4	265.9	7.4	271.6
	7.8	25.8	-87.4	51.4	54.0	51.4	62.7
170230	7.3	25.8	-87.4	19.8	104.9	12.6	124.3
	9.0	25.8	-87.4	19.8	104.9	12.6	124.3
170300	3.5	25.8	-87.4	28.9	221.5	32.3	226.8
	6.7	26.0	-87.4	51.2	81.4	52.0	88.8
170330	1.0	26.0	-87.6	51.3	7.4	50.4	14.3
	7.5	26.0	-87.4	42.1	121.2	41.2	131.4
170400	2.8	26.0	-87.6	38.2	333.4	35.4	336.4
	5.5	26.0	-87.4	41.5	175.3	42.9	182.5
170430	2.9	26.2	-87.6	45.2	39.4	42.3	48.6
	7.6	26.2	-87.6	45.2	39.4	42.3	48.6
170500	1.3	26.2	-87.4	44.2	161.7	45.5	164.7
	3.7	26.4	-87.6	53.4	53.5	54.4	57.3
170530	1.7	26.2	-87.6	32.2	250.2	34.1	251.5
	8.1	26.4	-87.6	46.2	78.9	45.2	89.0
(Sheet 2 of 6)							

Table A1 (Continued)

Day/ Hour	Max. Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg az	Speed m/s	Dir. deg az
170600	6.9 8.1	26.4 26.4	-87.6 -87.6	22.5 22.5	163.9 163.9	15.7 15.7	177.4 177.4
170630	2.5 5.2	26.4 26.4	-87.6 -87.6	37.7 37.7	192.9 192.9	40.2 40.2	199.6 199.6
170700	4.0 6.7	26.6 26.6	-87.8 -87.8	42.8 42.8	29.2 29.2	38.8 38.8	36.7 36.7
170730	2.4 3.4	26.6 26.6	-87.8 -87.8	6.5 6.5	353.2 353.2	4.1 4.1	20.6 20.6
170800	3.2 7.9	26.6 26.8	-87.8 -87.8	30.1 51.4	229.2 81.1	33.2 51.1	234.5 89.9
170830	1.5 7.3	26.8 26.8	-88.0 -87.8	49.3 41.8	7.7 129.6	47.8 40.9	16.1 139.7
170900	2.9 6.3	26.8 26.8	-88.0 -87.8	35.2 43.9	344.8 163.9	32.3 45.6	345.8 171.6
170930	0.9 8.6	24.5 27.0	-90.1 -88.0	8.8 49.4	290.2 53.7	8.0 48.5	296.4 63.7
171000	5.9 6.6	27.0 27.0	-88.0 -88.0	19.5 19.5	102.7 102.7	13.6 13.6	113.0 113.0
171030	1.4 6.4	27.0 27.0	-88.3 -88.0	45.3 32.6	342.6 186.0	43.9 33.3	349.2 197.1
171100	2.0 7.1	27.0 27.2	-88.3 -88.3	39.4 51.2	312.5 31.4	37.3 50.1	315.8 39.4
171130	2.3 5.3	27.2 27.2	-88.3 -88.0	26.3 48.7	24.5 145.2	24.0 49.6	20.5 151.4
171200	1.0 6.3	27.2 27.4	-88.0 -88.3	45.1 52.9	168.0 64.7	46.1 53.4	170.2 70.4
171230	3.7 5.8	27.4 27.4	-88.3 -88.3	39.6 39.6	96.0 96.0	35.9 35.9	102.8 102.8
171300	1.8 7.1	27.4 27.4	-88.5 -88.3	44.1 35.3	346.3 180.2	42.4 33.6	352.7 191.7
171330	1.7 7.5	27.4 27.6	-88.5 -88.3	40.1 50.7	313.1 111.3	38.4 51.0	316.2 119.7
171400	1.4 5.9	27.6 27.6	-88.5 -88.3	28.0 48.2	12.5 149.0	26.6 49.5	8.4 155.8
171430	2.3 8.4	27.6 27.8	-88.5 -88.5	30.2 48.7	280.3 58.4	32.6 47.3	279.7 68.2

(Sheet 3 of 6)

Table A1 (Continued)							
Day/ Hour	Max Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg az	Speed m/s	Dir. deg az
171500	6.0 6.8	27.8 27.8	-88.5 -88.5	19.3 19.3	114.2 114.2	13.3 13.3	125.6 125.6
171530	1.7 6.5	27.8 28.0	-88.7 -88.5	45.9 52.5	338.5 81.4	44.2 53.2	342.8 88.4
171600	1.6 7.6	28.0 28.0	-88.5 -88.5	41.8 41.8	126.4 126.4	40.1 40.1	136.8 136.8
171630	1.7 7.5	28.0 28.0	-88.7 -88.5	34.0 45.2	338.7 169.1	32.3 46.3	338.4 178.4
171700	3.1 7.5	28.3 28.3	-88.7 -88.7	44.9 44.9	45.2 45.2	41.8 41.8	54.2 54.2
171730	2.0 3.2	28.3 28.5	-88.7 -88.7	6.9 53.8	324.1 59.8	4.9 53.9	340.6 63.2
171800	2.6 8.5	28.3 28.5	-88.7 -88.7	33.7 47.2	240.9 81.6	36.4 45.0	246.3 91.9
171830	7.8 8.3	28.5 28.5	-88.7 -88.7	24.5 24.5	167.5 167.5	16.7 16.7	175.6 175.6
171900	2.5 8.9	28.5 28.7	-88.7 -88.7	38.2 50.1	214.3 97.5	40.7 49.6	221.1 107.7
171930	2.9 7.7	28.7 28.7	-89.0 -88.7	41.2 41.2	1.6 154.8	38.3 40.8	6.5 165.5
172000	1.8 7.2	28.7 28.9	-88.7 -89.0	43.2 50.0	192.8 38.1	45.0 49.0	197.7 46.4
172030	1.5 7.1	28.9 28.9	-88.7 -88.7	47.9 47.9	150.2 150.2	49.4 49.4	158.3 158.3
172100	2.0 8.2	28.9 29.1	-89.0 -89.0	31.1 47.6	283.6 55.6	33.2 46.1	283.5 65.4
172130	3.1 3.5	29.1 29.1	-89.0 -89.0	15.6 15.6	79.7 79.7	12.5 12.5	86.5 86.5
172200	3.6 8.5	29.1 29.3	-89.0 -89.0	27.7 50.1	250.0 72.7	31.3 49.6	255.4 82.6
172230	7.2 8.2	29.3 29.3	-89.0 -89.0	23.8 23.8	135.6 135.6	16.6 16.6	147.2 147.2
172300	1.6 7.1	29.3 29.5	-89.0 -89.0	37.8 51.5	205.3 93.0	39.4 52.0	214.6 100.9
172330	2.2 6.2	29.5 29.5	-89.2 -89.0	44.9 39.1	7.8 143.3	42.7 37.6	15.1 152.3

(Sheet 4 of 8)

Table A1 (Continued)

Day/ Hour	Max. Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg sz	Speed m/s	Dir. deg sz
180000	1.7	29.5	-89.0	43.4	188.7	45.1	195.4
	5.5	29.5	-89.0	43.4	188.7	45.1	195.4
180030	1.8	29.7	-89.2	27.4	30.7	25.6	26.6
	6.0	29.7	-89.0	49.7	142.6	50.7	149.4
180100	3.2	29.7	-89.2	27.0	274.3	30.2	276.4
	8.4	29.9	-89.2	50.6	62.6	49.5	72.1
180130	6.9	29.9	-89.2	20.1	126.8	13.2	141.7
	8.0	29.9	-89.2	20.1	126.8	13.2	141.7
180200	1.4	29.9	-89.2	36.5	197.3	37.9	208.1
	7.1	29.9	-89.2	36.5	197.3	37.9	208.1
180230	2.9	30.1	-89.4	43.9	16.8	41.0	24.2
	9.2	30.1	-89.2	46.9	132.5	45.5	143.9
180300	1.4	30.1	-89.2	45.9	176.3	47.3	181.7
	6.0	30.3	-89.4	52.0	47.1	52.1	53.6
180330	2.5	30.3	-89.4	23.1	71.2	20.6	66.5
	3.3	30.3	-89.2	49.9	139.7	50.5	143.4
180400	1.9	30.3	-89.4	24.1	245.7	26.0	252.7
	3.6	30.3	-89.4	24.1	245.7	26.0	252.7
180430	0.9	28.3	-92.2	8.4	293.9	7.5	299.6
	1.4	30.3	-89.4	38.9	234.0	39.7	235.6
180500	0.9	28.3	-92.2	8.3	291.2	7.5	296.5
	1.4	29.5	-94.0	4.4	353.8	4.3	11.9
180530	0.9	28.5	-92.2	8.8	292.6	7.9	298.1
	1.5	30.3	-89.4	39.5	236.7	38.8	234.8
180600	0.9	28.5	-92.4	7.8	293.4	7.0	299.2
	1.4	29.5	-93.3	6.5	334.2	6.0	345.8
180630	0.9	28.7	-92.4	7.5	293.6	6.6	299.3
	1.3	29.7	-92.9	8.0	328.1	7.2	336.0
180700	0.9	29.5	-92.6	7.6	315.2	6.7	322.1
	1.3	29.5	-92.6	7.6	315.2	6.7	322.1
180730	0.9	29.5	-92.6	6.7	310.7	5.8	317.2
	1.1	29.5	-92.6	6.7	310.7	5.8	317.2
180800	0.9	29.5	-92.4	6.8	301.6	5.9	306.7
	1.1	29.5	-92.4	6.8	301.6	5.9	306.7
180830	0.9	29.7	-92.2	7.2	298.6	6.3	302.9
	1.0	29.7	-92.0	8.2	294.2	7.3	298.0

(Sheet 5 of 6)

Table A1 (Concluded)							
Day/ Hour	Max. Speed Diff. m/s	Grid Point Coord.		5-Nest Model		7-Nest Model	
		Lat. deg	Long. deg	Speed m/s	Dir. deg az	Speed m/s	Dir. deg az
180900	0.9	29.7	-92.0	7.2	289.3	6.3	292.2
	0.9	29.7	-92.0	7.2	289.3	6.3	292.2
180930	0.9	29.7	-92.0	6.3	282.5	5.5	284.1
	0.9	30.3	-89.4	17.4	218.1	17.3	215.2
181000	0.8	29.7	-92.0	5.5	275.1	4.7	274.8
	0.8	30.3	-89.4	15.8	216.9	15.8	213.8
181030	0.7	29.7	-92.0	4.8	265.3	4.1	262.5
	0.8	30.3	-86.4	11.9	161.5	12.1	165.0
181100	0.5	29.7	-91.7	4.9	253.5	4.3	249.7
	0.8	30.3	-86.4	11.4	162.2	11.5	165.9
181130	0.4	28.3	-83.4	8.2	156.8	8.5	160.7
	0.8	30.1	-85.7	10.0	160.4	10.2	164.6
181200	0.4	29.7	-93.8	3.1	170.9	3.5	170.8
	0.8	30.3	-86.4	10.3	163.0	10.4	167.3
(Sheet 6 of 6)							

Appendix B

Documentation of CE Model Upgrades

This appendix provides brief documentation of new and modified programs in the upgraded CE tropical cyclone surface wind field model. The material is a supplement to the primary documentation of Cardone et al. (1992). Five FORTRAN programs are discussed. The programs HIST_ADC.7NE, SNAP_ADC.7NE, and SNAP_HOL.7NE are modified versions of the previous HIST and SNAP programs. Programs 1EYEWALL.HOL and 2EYEWALL.HOL are new. They are helpful in implementing the new generalized surface pressure specification.

Program HIST_ADC.7NE

HIST_ADC.7NE is a slight modification of HIST_ADC.F. All input files except LSNAP, and all output files, are unchanged from HIST_ADC.F to HIST_ADC.7NE. The changes to file LSNAP are as follows:

- pressure arrays, formerly dimensioned (21,21,5), are now dimensioned (21,21,7);
- wind arrays, formerly dimensioned (21,21,10), are now dimensioned (21,21,14);
- in the variables at the end of records in LSNAP, variable DX is followed by the new variable INSIDE. INSIDE is an integer indexing the innermost live nest of the 7 nests supported, so that the effective grid spacing is $DX * 2^{(INSIDE-1)}$.

Program SNAP_ADC.7NE

SNAP_ADC.7NE is derived from SNAP_ADC.F. The modifications allow the user to run up to 7 grid nests rather than the previous mandatory 5 nests.

Arrays of pressure, pressure gradient, wind, formerly dimensioned (21,21,5), are now dimensioned (21,21,7). Two changes are made to namelist /NAME3/ as follows:

- a variable name NOMEN (CHARACTER*4) for storm identification has been included;
- integer variable INSIDE has been added. INSIDE indexes the finest live nest of the 7 nests provided. Thus the number of live nests is (8-INSIDE), and the grid spacing of the finest live nest is $DX * 2^{(INSIDE-1)}$. Default values are $DX = 2$, and $INSIDE = 1$, yielding a 2 km grid spacing and an execution time roughly 4 times as long as the existing 5-nest model. The combination $DX = 6.25$, $INSIDE = 3$, (lines 304, 305) reproduces the 25 km spacing often used by the CE for global studies. In the great majority of applications, the useful values of INSIDE are 1, 2, and 3. $INSIDE = 4$ may be tried for running a quick preliminary study on a coarse grid.

Program SNAP_HOL.7NE

SNAP_HOL.7NE is an extensive modification of SNAP_ADC.7NE to include the generalized pressure profile as well as the capability for modeling up to 7 nests. The variable ST12 and the quadrantal variation of PFAR and RADIUS have been excised. In OWI's experience with the hurricane model, they have been used only once: for hurricane Eloise, September 13, 1975. Variable ITRACK has been excised: its use pertained to a 1969 study in which direction was specified in points. Namelist /NAME3/ is changed materially. Each variable and array in /NAME3/ is documented below. The method of computation of pressure and pressure gradient is discussed in a later part on Mathematical Method.

Revisions at beginning of program

```

REAL RADIUS(2),DPRESS(2),HOLL(2)
CHARACTER*4 NOMEN
EQUIVALENCE (RAD1,RADIUS), (RAD2,RADIUS(2)), (B1,HOLL),
$ (B2,HOLL(2)), (DP1,DPRESS), (DP2,DPRESS(2))
NAMELIST /NAME3/ SGW, AN1, NOMEN,
$ EYELAT, EYLONG, DIREC, SPEED, EYPRES, RADIUS, RAD1,
$ RAD2, PFAR, NM, DX, INSIDE, HOLL, B1, B2, DPRESS, DP1,
$ DP2

```

Definition of variables in namelist NAME3

SGW	Magnitude of surface geostrophic wind, m/sec
AN1	Angle between SGW and east, counterclockwise from east
NOMEN	Designator for tropical storm, e.g. two digits and one letter
EYELAT	Latitude of eye of storm at snap time, north positive
EYLONG	Longitude of eye of storm at snap time, east positive (EYLONG is included for archival purposes but not presently used in computation)
DIREC	Direction of forward motion of storm, clockwise from north
SPEED	Speed of forward motion, in kt (but redefinable according to the switch variable UNITS)
EYPRES	Pressure at eye of storm, in mb
RADIUS	Scale radius of the two components of exponential pressure profile
RAD1,RAD2	Alternate names for specifying RADIUS; convenient when only one exponential is modeled
PFAR	Ambient pressure exterior to storm, in mb
NM	Number of computational cycles in nest 1; NM should be a multiple of 64 (default: NM = 3200)
DX	Grid spacing in nest 1, in km (default: DX = 2.)
INSIDE	Index of finest nest actually used for computations; the finest active grid spacing is $DX \cdot 2^{(INSIDE-1)}$ (default: INSIDE = 1)
HOLL	Power to which radius is raised in the modified Holland's (1980) pressure profile model. When HOLL(2) = 0., only one exponential is used; RADIUS(2) and DPRESS(2) are then ignored.
B1,B2	Alternate names for specifying HOLL; convenient when only one exponential is modeled. Default values are B1 = 1., B2 = 0. These defaults are reinstated for every snapshot. Use of the defaults reverts to a standard exponential pressure profile, as used in SNAP_ADC.7NE.
DPRESS	DPRESS(I) is the pressure difference associated with RADIUS(I) and HOLL(I) in OWI's double-eyewall extension of Holland's (1980) modified exponential profile.
DP1,DP2	Alternate names for specifying DPRESS. As explained in the part on Mathematical Method, it is never advantageous to include DP2 in an input list; it is in the NAMELIST in order to force its appearance in the output file.

SPECIAL WARNING: Do not input both members of an equivalence. Input either RADIUS or RAD and RAD2; either HOLL or B1 and B2; either DPRESS or DP1 and DP2. The program imposes consistency checks on RADIUS, HOLL, and DPRESS; it does not check EYPRES and PFAR, so that it remains the user's duty to verify that $PFAR > EYPRES$.

Mathematical method

The program performs the following consistency checks:

1. If $B1 < 0$ or $B2 < 0$, stop.
2. If $B2 = 0$, run Holland's modified exponential model (ignore RAD2 and DP2).
 - 2.1 If $RAD1 \leq 0$, stop.
 - 2.2 If DP1 not specified, compute it as PFAR-EYPRES.
 - 2.3 If DP1 specified, but inconsistent with PFAR-EYPRES, stop.
 - 2.4 Set $N = 1$.
3. If $B2 > 0$, run OWI's extension of Holland's pressure profile.
 - 3.1 If $RAD1 \leq 0$ or $RAD2 \leq 0$, stop.
 - 3.2 If DP2 not specified, compute it as PFAR-EYPRES-DP1.
 - 3.3 If DP2 specified, but inconsistent with PFAR-EYPRES-DP1, stop.
 - 3.4 Set $N = 2$.

Program 1EYEWALL.HOL

Program 1EYEWALL.HOL attempts to fit snapshot parameters to a guessed wind profile. It considers only the case of one exponential ($B2 = 0.0$). 1EYEWALL.HOL requires the following input arguments (in namelist /INN/):

BLAT	Absolute value of latitude of eye, degrees & decimals; used in computation of the Coriolis parameter. Also, the value BLAT=99 is used as a flag to stop computation.
EYPRES	Pressure at eye, in mb
PFAR	Pressure at large (theoretically infinite) distance from eye, in mb
RW1	Radius at which a wind speed is guessed, in km
SP1	Wind speed corresponding to RW1, in m/sec
V150	Wind speed at radius of 150 km, in m/sec

The following outputs are printed:

1. In namelist /INN/:

SP11, SP12 = SP1 minus & plus 1 m/sec
SP31, SP32 = V150 minus & plus 1 m/sec
DP2 = pressure difference (far field minus eye), in pascal

2. In namelist /VORTEX/:

COR = Coriolis parameter, $2 \cdot \omega \cdot \sin(\text{BLAT})$

FR22 = the quantity $0.5 \cdot \text{COR} \cdot \text{RW1}$ (used in the computation of gradient wind)
 FR23 = $0.5 \cdot \text{COR} \cdot r$, where r is 150000 m or 150 km
 PEYE = pressure at eye, in pascal

3. Below namelist /VORTEX/, six parameters are printed, defined from left to right as:

- 3.1 DP2 (see above)
- 3.2 Fitted value of scale radius, in m
- 3.3 Fitted value of Holland's exponent
- 3.4 Fitted value of gradient wind at radius RW1, in m/sec
(in a good fit, this will be nearly equal to SP1)
- 3.5 Fitted value of gradient wind at radius 150 km, in m/sec
(in a good fit, this will be nearly equal to V150)
- 3.6 Goodness of fit measure: absolute value of gradient wind minus in put wind at radius RW1, plus the same at radius 150 km. A value less than 3.0 implies a tolerably well-fitting solution.

4. Table with 6 columns and 150 lines:

- 4.1 Radius, in km
- 4.2 Pressure, in mb
- 4.3 First component of pressure gradient, in pascal/m
- 4.4 Second component (this is zero, since only one exponential was fitted)
- 4.5 Pressure gradient (here equal to output #4.3)
- 4.6 Gradient wind, m/sec

5. Below the table are numbers that, if the fit is satisfactory, the user can insert into namelist /NAME3/ of SNAP_HOL.7NE:

EYELAT = echo of the input BLAT
 EYPRES = echo of input
 PFAR = echo of input
 RAD1 = scale radius, in nm
 HOLL = two values of Holland's exponent; the second value is zero, because only one exponential was fitted

Program 2EYEWALL.HOL

Program 2EYEWALL.HOL attempts to fit snapshot parameters to a guessed wind profile. It considers the case of two exponentials ($B2 > 0.0$). 2EYEWALL.HOL requires the following inputs in namelist /INN/:

BLAT Same usage as in 1EYEWALL.HOL
 EYPRES Same usage as in 1EYEWALL.HOL
 PFAR Same usage as in 1EYEWALL.HOL

RS1 Scale radius of inner ring, in km
 (numerical experiments with this scheme have shown that the inner
 scale radius can safely be taken equal to the inner radius to local
 maximum wind)

RW2 Radius to maximum wind of outer ring, in km

DRING An integer switch variable indexing the shape of the wind profile

DRING = 1: the maximum wind is greater in the inner ring
 DRING = 2: the maximum wind is greater in the outer ring

SP1 Desired wind speed at radius RS1, in m/sec

SP2 Desired wind speed at radius RW2, in m/sec

The following outputs are printed:

1. In namelist /INN/:

SP11, SP12 = SP1 minus and plus 1 m/sec
 SP21, SP22 = SP2 minus and plus 1 m/sec

2. In namelist /VORTEX/:

BLAT = echo of input
 COR = same usage as in 1EYEWALL.HOL
 RAD1 = RS1, in m
 RAD2 = RW2, in m
 RAD3 = $0.5 \cdot (RAD1 + RAD2)$; a local minimum of wind speed, if
 found, will be near RAD3
 RAD4 = 150000 m (= 150 km)
 FR21 = the quantity $0.5 \cdot COR \cdot RAD1$; used in the computation of
 gradient wind
 FR22 = the quantity $0.5 \cdot COR \cdot RAD2$
 FR23 = the quantity $0.5 \cdot COR \cdot RAD3$
 PEYE = same usage as in 1EYEWALL.HOL
 DP = pressure difference (far field minus eye), in pascal

3. Below namelist /VORTEX/, nine parameters are printed, defined from left
 to right as:

- 3.1 Fitted value of DP1 (partial pressure difference for first
exponential), in pascal
- 3.2 Fitted value of DP2 (partial pressure difference for second
exponential), in pascal
- 3.3 Scale radius of second exponential, in m (the scale radius of first
exponential has been fixed at RAD1)
- 3.4 Exponent for first exponential (Holland 1980)
- 3.5 Exponent for second exponential (OWI extension of Holland (1980))
- 3.6 Fitted wind speed at radius RAD1, m/sec
- 3.7 Fitted wind speed at radius RAD2, m/sec

- 3.8 Fitted wind speed at radius RAD3, m/sec
- 3.9 (printed below 3.1): fitted wind speed at radius 150 km

4. Second printing of namelist /INN/, if given:

The fit in the above two-line summary was unsatisfactory in that the wind at 150 km was greater than the wind at RAD2; a second fit will be attempted, this time minimizing the wind speed at 150 km.

SP11, SP12 = SP1 minus and plus 2 m/sec
SP21, SP22 = SP2 minus and plus 2 m/sec

5. Below second printing of /INN/: the same nine parameters as in #3 above, for the second attempted fit.

6. Table with 6 columns and 150 lines:

- 6.1 Radius, in km
- 6.2 Pressure, in mb
- 6.3 First component of pressure gradient, in pascal/m
- 6.4 Second component of pressure gradient, in pascal/m
- 6.5 Pressure gradient (sum of the two components), in pascal/m
- 6.6 Gradient wind, in m/sec

7. Below the table are numbers that, if the fit is satisfactory, the user can insert into namelist /NAME3/ of SNAP_HOL.7NE:

EYELAT = echo of the input BLAT
EYPRES = echo of input
PFAR = echo of input
RADIUS = two values of scale radius, in nm
HOLL = two values of Holland's exponent
DP1 = pressure difference for first component, in mb
(program SNAP_HOL.7NE computes DP2 by subtraction)

Appendix C

Sample Application of Upgraded CE Model to Simu- lation of 12 Snapshots of Hurricane Gilbert

This appendix provides input file information used by OWI in test runs with the upgraded CE model, including seven nests and the generalized pressure specification. Snapshots were generated at 6-hr intervals for Hurricane Gilbert, which occurred during September 1988. The first snapshot represents 1200 UTC (Universal Time Coordinate, formerly known as Greenwich Mean Time) 15 September 1988. In all, 12 snapshots were generated. Inputs for the programs SNAP_HOL.7NE and HIST_ADC.7NE are included as implemented on the OWI VAX computer. The listed values of parameter AN1 follow a meteorological convention (deg azimuth coming from) rather than the convention used by the Cardone et al. (1992).

Listings of the full field of surface (19-m elevation) wind speed and direction were generated on a polar output grid. They are included here at 6-hr intervals (snapshot times). Wind speed is in m/sec. Wind direction is in deg azimuth coming from. Printed output of the azimuthally averaged, surface wind speed and inflow angle is also given in this appendix. In addition to the 12 snapshot wind fields, this output includes a wind field interpolated halfway between each pair of snapshots.

```

$ ASSIGN GRID.312    FOR012
$ ASSIGN 05GILBERT21 FJR005
$ ASSIGN GILB.WIND21 FJR052
$ RUN MOLL3
$NAME1
KZM      =      8309,
KDM      =     151200,
KMIN     =      180,
DX       =     2.000000 ,
KSTRES   =      0,
NSTRES   =     17227,
KWINO    =      19,
NWINO    =     312,
HM       =     500.0000 ,
INSIDE   =      1,
KTIME    =      1
$END
$NAME2
EYELAT   =     16.00000 ,
OIREC    =     290.0000 ,
SPEED    =     11.00000 ,
EYPRES   =     972.0000 ,
PFAR     =     1011.000 ,
RAD1     =     25.38000 ,
RAD2     =     68.73000 ,
RADIUS   =     25.38000 ,    68.73000 ,
DP1      =     22.85000 ,
DP2      =     16.15000 ,
DPRES    =     22.85000 ,    16.15000 ,
B1       =     2.520000 ,
B2       =     2.520000 ,
MOLL     = 2*2.520000 ,
SGW      =     7.000000 ,
AN1      =     110.0000 ,
ST12     =     0.000000E+00
$END
$NAME2
EYELAT   =     16.00000 ,
DIREC    =     290.0000 ,
SPEED    =     11.00000 ,
EYPRES   =     968.0000 ,
PFAR     =     1011.000 ,
RAD1     =     31.32000 ,
RAD2     =     87.37000 ,
RADIUS   =     31.32000 ,    87.37000 ,
DP1      =     31.77000 ,
DP2      =     11.23000 ,
DPRES    =     31.77000 ,    11.23000 ,
B1       =     2.520000 ,
B2       =     2.520000 ,
MOLL     = 2*2.520000 ,
SGW      =     7.000000 ,
AN1      =     110.0000 ,
ST12     =     0.000000E+00
$END

```

Figure C1. Program inputs, Hurricane Gilbert (Sheet 1 of 6)

\$NAME2			
EYELAT	=	19.00000	,
OIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	905.0000	,
PFAR	=	1012.000	,
RAD1	=	8.640000	,
RAD2	=	67.28000	,
RADIUS	=	8.640000	, 67.28000 ,
DP1	=	93.83000	,
DP2	=	13.17000	,
DPRES	=	93.83000	, 13.17000 ,
B1	=	1.680000	,
B2	=	2.380000	,
HOLL	=	1.680000	, 2.380000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	,
\$END			
\$NAME2			
EYELAT	=	20.00000	,
DIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	888.0000	,
PFAR	=	1012.000	,
RAD1	=	7.020000	,
RAD2	=	54.00000	,
RADIUS	=	7.020000	, 54.00000 ,
DP1	=	110.2200	,
DP2	=	13.78000	,
DPRES	=	110.2200	, 13.78000 ,
B1	=	1.590000	,
B2	=	2.520000	,
HOLL	=	1.590000	, 2.520000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	,
\$END			
\$NAME2			
EYELAT	=	20.00000	,
DIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	893.0000	,
PFAR	=	1012.000	,
RAD1	=	7.020000	,
RAD2	=	37.80000	,
RADIUS	=	7.020000	, 37.80000 ,
DP1	=	101.1200	,
DP2	=	17.88000	,
DPRES	=	101.1200	, 17.88000 ,
B1	=	1.410000	,
B2	=	2.520000	,
HOLL	=	1.410000	, 2.520000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	,
\$END			

Figure C1. (Sheet 2 of 6)

\$NAME2			
EYELAT	=	21.00000	,
DIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	890.0000	,
PFAR	=	1012.000	,
RAD1	=	7.020000	,
RAD2	=	37.26000	,
RADIUS	=	7.020000	37.26000 ,
DP1	=	101.8000	,
DP2	=	20.20000	,
DPRES	=	101.8000	20.20000 ,
B1	=	1.410000	,
B2	=	2.520000	,
HOLL	=	1.410000	2.520000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	
\$END			
\$NAME2			
EYELAT	=	22.00000	,
DIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	951.0000	,
PFAR	=	1012.000	,
RAD1	=	11.88000	,
RAD2	=	46.85000	,
RADIUS	=	11.88000	46.85000 ,
DP1	=	45.07000	,
DP2	=	15.93000	,
DPRES	=	45.07000	15.93000 ,
B1	=	0.560000	,
B2	=	2.520000	,
HOLL	=	0.560000	2.520000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	
\$END			
\$NAME2			
EYELAT	=	22.00000	,
DIREC	=	290.0000	,
SPEED	=	11.00000	,
EYPRES	=	950.0000	,
PFAR	=	1012.000	,
RAD1	=	17.28000	,
RAD2	=	55.82000	,
RADIUS	=	17.28000	55.82000 ,
DP1	=	34.57000	,
DP2	=	27.43000	,
DPRES	=	34.57000	27.43000 ,
B1	=	0.940000	,
B2	=	2.520000	,
HOLL	=	0.940000	2.520000 ,
SGW	=	7.000000	,
AN1	=	110.0000	,
ST12	=	0.0000000E+00	
\$END			

Snapshot 6

Snapshot 7

Snapshot 8

Figure C1. (Sheet 3 of 6)

			Snapshot 9	
\$NAME2				
EYELAT	=	23.00000	,	
DIREC	=	290.00000	,	
SPEED	=	11.00000	,	
EYPRES	=	949.00000	,	
PFAR	=	1010.00000	,	
RAD1	=	11.89000	,	
RAD2	=	43.53000	,	
RADIUS	=	11.88000	,	43.53000 ,
DP1	=	40.67000	,	
DP2	=	20.33000	,	
DPRES	=	40.67000	,	20.33000 ,
B1	=	0.7500000	,	
B2	=	2.520000	,	
HOLL	=	0.7500000	,	2.520000 ,
SGW	=	7.000000	,	
AN1	=	110.00000	,	
ST12	=	0.0000000E+00	,	
\$END				
			Snapshot 10	
\$NAME2				
EYELAT	=	23.00000	,	
DIREC	=	290.00000	,	
SPEED	=	11.00000	,	
EYPRES	=	950.00000	,	
PFAR	=	1011.00000	,	
RAD1	=	29.70000	,	
RAD2	=	91.63000	,	
RADIUS	=	29.70000	,	91.63000 ,
DP1	=	51.84000	,	
DP2	=	9.160000	,	
DPRES	=	51.84000	,	9.160000 ,
B1	=	1.120000	,	
B2	=	2.240000	,	
HOLL	=	1.120000	,	2.240000 ,
SGW	=	7.000000	,	
AN1	=	110.00000	,	
ST12	=	0.0000000E+00	,	
\$END				
			Snapshot 11	
\$NAME2				
EYELAT	=	24.00000	,	
DIREC	=	290.00000	,	
SPEED	=	11.00000	,	
EYPRES	=	953.00000	,	
PFAR	=	1010.00000	,	
RAD1	=	27.00000	,	
RAD2	=	64.21000	,	
RADIUS	=	27.00000	,	64.21000 ,
DP1	=	46.62000	,	
DP2	=	10.38000	,	
DPRES	=	46.62000	,	10.38000 ,
B1	=	1.330000	,	
B2	=	2.520000	,	
HOLL	=	1.330000	,	2.520000 ,
SGW	=	7.000000	,	
AN1	=	110.00000	,	
ST12	=	0.0000000E+00	,	
\$END				

Figure C1. (Sheet 4 of 6)

Snapshot 12

```

$NAME2
EYELAT = 24.00000 ,
DIREC = 290.00000 ,
SPEED = 11.00000 ,
EYPRES = 954.00000 ,
PFAR = 1009.00000 ,
RAD1 = 21.60000 ,
RAD2 = 60.61000 ,
RADIUS = 21.60000 , 60.61000 ,
OP1 = 44.98000 ,
OP2 = 10.02000 ,
OPRES = 44.98000 , 10.02000 ,
B1 = 1.19000 ,
B2 = 2.52000 ,
HOLL = 1.19000 , 2.52000 ,
SGW = 7.00000 ,
AN1 = 110.00000 ,
ST12 = 0.000000E+00
SEND
$NAME2
EYELAT = 999.00000 ,
DIREC = 290.00000 ,
SPEED = 11.00000 ,
EYPRES = 954.00000 ,
PFAR = 1009.00000 ,
RAD1 = 0.000000E+00,
RAD2 = 0.000000E+00,
RADIUS = 2*0.000000E+00,
OP1 = 0.000000E+00,
OP2 = 0.000000E+00,
OPRES = 2*0.000000E+00,
B1 = 1.000000 ,
B2 = 0.000000E+00,
HOLL = 1.000000 , 0.000000E+00,
SGW = 7.000000 ,
AN1 = 110.00000 ,
ST12 = 0.000000E+00
SEND

```

```

0 20 0 0 3 1 0
2 20 0 0 3 2 0
4 20 0 0 3 3 0
6 20 0 0 3 4 0
8 20 0 0 3 5 0
10 20 0 0 3 6 0
12 20 0 0 3 7 0
14 20 0 0 3 8 0
16 20 0 0 3 9 0
18 20 0 0 3 10 0
20 20 0 0 3 11 0
22 20 0 0 3 12 0
999 0 0 0 3 0 0

```

Figure C1. (Sheet 5 of 6)

HOUR	LAT	STORM HISTORY LJNG	HISTORY SNAPS	ZERO HOUR INTERP	IS	8809	151200
0	20	0	0	1	0	0.0000	0
1	20	0	0	1	2	0.5000	0
2	20	0	0	2	0	0.0000	0
3	20	0	0	2	3	0.5000	0
4	20	0	0	3	0	0.0000	0
5	20	0	0	3	4	0.5000	0
6	20	0	0	4	0	0.0000	0
7	20	0	0	4	5	0.5000	0
8	20	0	0	5	0	0.0000	0
9	20	0	0	5	6	0.5000	0
10	20	0	0	6	0	0.0000	0
11	20	0	0	6	7	0.5000	0
12	20	0	0	7	0	0.0000	0
13	20	0	0	7	8	0.5000	0
14	20	0	0	8	0	0.0000	0
15	20	0	0	8	9	0.5000	0
16	20	0	0	9	0	0.0000	0
17	20	0	0	9	10	0.5000	0
18	20	0	0	10	0	0.0000	0
19	20	0	0	10	11	0.5000	0
20	20	0	0	11	0	0.0000	0
21	20	0	0	11	12	0.5000	0
22	20	0	0	12	0	0.0000	0

\$WHAT
 KSTEP2 = 22
 \$END
 WORKK: 0 8809 151200
 WORKK: 1 8809 151500
 WORKK: 2 8809 151800
 WORKK: 3 8809 152100
 WORKK: 4 8809 160000
 WORKK: 5 8809 160300
 WORKK: 6 8809 160600
 WORKK: 7 8809 160900
 WORKK: 8 8809 161200
 WORKK: 9 8809 161500
 WORKK: 10 8809 161800
 WORKK: 11 8809 162100
 WORKK: 12 8809 170000
 WORKK: 13 8809 170300
 WORKK: 14 8809 170600
 WORKK: 15 8809 170900
 WORKK: 16 8809 171200
 WORKK: 17 8809 171500
 WORKK: 18 8809 171800
 WORKK: 19 8809 172100
 WORKK: 20 8809 180000
 WORKK: 21 8809 180300
 WORKK: 22 8809 180600
 END OF STRESS RUN

Figure C1. (Sheet 6 of 6)

Hour	0	0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.
Radius from Eye (km)													
1.05	5.9196	5.9045	5.8998	5.8958	5.8968	5.9242	5.9450	5.9655	5.9752	5.9781	5.9717	5.9587	5.9396
	98.6093	98.4339	98.0925	97.4786	97.4786	97.3422	97.1356	97.1127	97.2932	97.6151	97.9934	98.3642	98.5962
3.70	5.9053	5.8707	5.8574	5.8731	5.8731	5.9104	5.9547	5.9906	6.0111	6.0155	6.0055	5.9828	5.9474
	98.4865	98.1123	98.3941	97.5705	97.5705	96.8860	96.4938	96.4565	96.8079	97.4243	98.1888	98.9282	99.4206
5.54	5.8987	5.8381	5.8130	5.8369	5.8369	5.8975	5.9648	6.0199	6.0471	6.0331	6.0429	6.0169	5.9667
	100.4493	99.8900	98.7797	97.5117	97.5117	96.4843	95.9071	95.8765	96.3707	97.2723	98.4071	99.5472	100.3353
7.41	5.9043	5.8081	5.7649	5.7649	5.7644	5.8336	5.9812	6.0509	6.0829	6.0908	6.0688	6.0431	6.0009
	101.5862	100.7703	99.2359	97.5273	97.5273	96.1222	95.3598	95.3331	95.9684	97.1365	98.6466	100.1960	101.3348
9.26	5.9283	5.7813	5.7138	5.7138	5.7486	5.8676	5.9942	6.0331	6.1109	6.1304	6.1428	6.1333	6.0610
	102.8765	101.8027	99.8451	97.4652	97.4652	95.8229	94.8414	94.8378	95.6022	97.0233	98.8963	100.9027	102.4407
11.11	5.9082	5.7649	5.6561	5.6561	5.6882	5.8429	6.0127	6.1163	6.1550	6.1807	6.2373	6.2529	6.1741
	104.4123	103.0760	100.6987	98.0189	98.0189	95.8352	94.4094	94.3301	95.2711	96.8747	99.0752	101.6151	103.7215
12.94	6.1281	5.7640	5.5923	5.5923	5.6034	5.8023	6.0255	6.1500	6.1925	6.2732	6.4122	6.5045	6.4462
	106.3334	104.7010	101.9891	98.8317	98.8317	95.4554	94.0073	93.9580	94.9563	96.3072	98.5138	102.1071	105.0828
14.82	6.5015	5.8091	5.5234	5.5234	5.4666	5.7212	6.0349	6.1339	6.2316	6.4952	6.9304	7.1461	7.1547
	108.7835	106.9004	104.1677	100.9022	100.9022	96.2655	93.8860	93.5750	94.6458	96.6712	99.3747	101.0836	105.8850
16.67	7.5463	5.9073	5.4917	5.4917	5.2338	5.5279	5.9943	6.1558	6.2647	7.0274	8.5797	8.7210	8.9364
	111.1102	110.2957	109.0354	107.7331	107.7331	98.9748	93.9497	93.3360	94.2947	85.6591	79.3355	95.6300	102.8374
18.52	9.8565	6.4193	5.8043	5.8043	5.2179	5.0923	5.4780	5.4764	6.2315	8.4014	12.2251	11.5958	12.0818
	118.9075	115.8443	120.7771	128.3313	128.3313	108.8314	97.0376	93.0320	93.6413	69.3796	55.4717	84.2490	94.4100
27.78	32.6373	24.3052	21.3874	18.7590	15.3180	11.9573	11.5172	21.4211	34.7541	41.4234	44.2547	42.3971	42.3971
	82.0297	120.4944	148.4917	173.5462	203.1869	262.9128	301.6315	335.9907	346.4803	0.4788	18.8326	44.0079	44.0079
37.04	46.2477	40.0244	33.2342	29.2763	27.3211	24.8795	32.0564	40.2791	43.2172	44.8647	46.8943	47.3146	47.3146
	56.4293	100.7914	139.7525	173.0478	208.9543	245.3624	280.0259	300.2534	319.3888	342.3094	362.3094	374.3094	374.3094
46.30	43.9367	43.5132	37.4322	33.4423	32.9490	34.1627	37.0384	39.7871	41.2559	42.8803	44.4086	45.3970	45.3970
	48.6297	84.0974	130.6747	171.3562	207.4249	238.1564	265.6593	287.9271	311.1664	335.1673	357.8099	377.8099	377.8099
55.54	43.9233	43.2629	39.0072	35.5084	34.4832	35.3837	36.7184	37.8654	38.9099	40.4207	41.9031	42.8609	42.8609
	48.2185	76.7072	119.8570	165.4430	201.1010	231.5239	258.2351	282.5763	307.4648	332.0189	355.7097	374.6294	374.6294
74.08	40.2472	40.5314	39.2017	36.5206	35.2295	33.9128	33.8853	34.7682	35.2842	36.6378	38.1559	39.2619	39.2619
	41.8043	70.3809	104.4480	146.0135	183.3792	216.6584	247.5184	274.8717	301.6903	327.5295	352.6945	374.6348	374.6348
92.40	37.6369	37.9756	37.6074	35.7140	33.8160	32.3110	31.7723	31.9663	32.5235	33.9074	35.1707	36.3348	36.3348
	39.8793	67.2037	98.0080	135.4094	172.1577	206.3064	239.5170	269.1052	297.4193	324.5133	350.4434	374.6348	374.6348
111.12	34.8055	35.2379	35.0753	33.7196	31.6906	30.0568	29.3595	29.1312	29.4297	30.9557	32.1910	33.4129	33.4129
	39.3473	65.9315	95.6080	130.0881	166.8306	201.3219	235.0364	268.5347	296.0707	323.5601	350.3058	374.6348	374.6348
130.90	30.2459	30.7611	30.7645	29.4682	27.5210	25.7919	24.7762	24.5025	24.9451	26.2332	27.4136	29.0277	29.0277
	40.7342	66.4469	94.3639	127.0138	163.9196	198.5079	233.3592	267.3182	297.5834	325.6798	352.8550	374.6348	374.6348
166.68	24.2941	24.7588	24.7038	25.5612	23.4829	21.6132	20.5307	20.1843	20.7486	22.1489	23.5127	24.9486	24.9486
	43.2822	67.7149	94.7039	125.9559	162.2868	198.2862	234.4804	270.1249	301.8985	329.9905	356.8000	374.6348	374.6348

Figure C2. Wind speed and direction fields, Snapshot 1, Hurricane Gilbert (Continued)

Azimuth (deg)													
Radius from Eye (km)	222.24	333.36	444.48	666.72	888.96	1111.20	1333.44	1555.68	1777.92	2000.16	2222.40	2444.64	2666.88
20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763	20.1763
49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151	49.9151
13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754	13.9754
42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214	42.6214
11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553	11.0553
73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235	73.3235
8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753	8.8753
84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473	84.1473
7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807	7.9807
88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425	88.3425
7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147	7.4147
91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157	91.5157
0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803	0.0803
0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303	0.0303
19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218	19.0218
29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808	29.6808
17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215	17.4215
7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929	7.7929
16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443	16.1443
343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226	343.5226
14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816	14.6816
315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402	315.5402
13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449	13.7449
281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733	281.1733
6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855	6.5855
320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015	320.8015
353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109	353.3109
6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803	6.9803
33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358	33.5358
4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311	4.2311
23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502	23.2502
6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444	6.0444
80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717	80.0717
74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345	74.9345
7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230	7.1230
85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615	85.2615
84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539	84.4539
7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871	7.2871
88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036	88.4036
7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080	7.4080
88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303	88.3303
87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437	87.9437
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731	7.4731
89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808	89.6808
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236	7.4236
92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308	92.3308

Figure C2. (Concluded)

HOUR	2	Azimuth (deg)												Speed Direction
		0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.	
1.05	5.9439	5.9520	5.9504	5.9598	5.9777	5.9975	6.0138	6.0233	6.0239	6.0157	6.0016	5.9827	5.9827	
	97.8063	97.6120	97.2786	96.8966	96.5998	96.4341	96.4125	96.4329	96.9469	97.3017	97.8331	97.8103	97.8103	
3.70	5.9453	5.9171	5.9119	5.9326	5.9705	6.0115	6.0128	6.0590	6.0597	6.0464	6.0211	5.9848	5.9848	
	98.5973	98.1840	97.4789	96.7213	96.1267	95.8205	95.8198	96.2098	96.8114	97.5298	98.1938	98.6028	98.6028	
5.56	5.9322	5.8831	5.8724	5.9050	5.9453	6.0282	6.0737	6.0949	6.0957	6.0805	6.0498	5.9970	5.9970	
	99.4793	98.8245	97.7274	96.5696	95.6958	95.2550	95.3361	95.8249	96.7057	97.7747	98.8057	99.4607	99.4607	
7.41	5.9273	5.8501	5.8304	5.8758	5.9607	6.0472	6.1359	6.1303	6.1316	6.1162	6.0891	6.0218	6.0218	
	100.4615	99.5362	98.0046	96.4519	95.2324	94.7278	94.8162	95.4686	96.6097	98.0362	99.4424	100.3925	100.3925	
9.26	5.9263	5.8108	5.7871	5.8434	5.9556	6.0672	6.1392	6.1658	6.1684	6.1681	6.1473	6.0672	6.0672	
	101.5811	100.3409	98.3463	96.3884	94.9333	94.2433	94.3159	95.1421	96.5329	98.3086	100.1290	101.4139	101.4139	
11.11	5.9454	5.7923	5.7397	5.8048	5.9467	6.0882	6.1733	6.2011	6.2114	6.2342	6.2398	6.1514	6.1514	
	102.8771	101.2927	98.7786	96.4175	94.8372	93.8816	93.9214	94.8442	96.4433	98.5499	100.8346	102.5744	102.5744	
12.96	6.0325	5.7719	5.6878	5.7522	5.9313	6.1086	6.2380	6.2370	6.2792	6.3636	6.4063	6.3243	6.3243	
	104.4223	102.4176	99.3627	96.4139	94.4258	93.3988	93.9206	94.5682	96.1548	98.3872	101.4874	103.0504	103.0504	
14.82	6.1772	5.7624	5.6294	5.6857	5.9040	6.1281	6.2638	6.2737	6.4276	6.7339	6.7647	6.7389	6.7389	
	106.3715	103.7812	100.1962	97.1333	94.3617	93.0328	93.1595	94.3009	96.8383	99.6924	101.9828	104.9185	104.9185	
16.67	6.4501	5.7237	5.5629	5.5761	5.8539	6.1453	6.2783	6.3142	6.7708	7.8700	7.9364	7.7737	7.7737	
	108.8111	105.5087	101.4775	98.3632	94.4765	92.7067	92.8018	94.0076	96.4646	85.2137	99.4146	104.3421	104.3421	
18.52	7.8853	5.8289	5.4905	5.3775	5.7684	6.1570	6.3314	6.3636	7.5009	10.7285	9.5238	9.9542	9.9542	
	110.8739	107.8401	103.6595	99.5091	95.4000	92.4389	92.5102	93.5831	88.4667	64.3699	92.6671	99.5503	99.5503	
27.78	26.8731	15.7405	12.5369	9.8057	6.7697	2.0472	3.2171	14.9049	30.6483	39.8221	42.4345	39.6113	39.6113	
	89.3194	127.2386	149.1053	171.5016	196.3009	225.8244	19.7736	359.4360	357.2250	6.7349	24.1872	50.8346	50.8346	
37.04	48.0327	41.2113	32.4583	27.1943	25.0830	24.9353	28.2568	41.0915	45.4548	47.3736	49.8524	49.9335	49.9335	
	57.7733	102.4577	142.0267	175.3357	211.2692	243.4606	281.3641	301.5291	319.2315	341.1176	1.6943	26.6466	26.6466	
46.30	49.8615	48.0132	43.0615	38.5967	38.4665	39.1754	40.2636	44.0577	45.3157	46.7354	48.4355	49.4028	49.4028	
	47.1331	82.4610	125.7951	155.2495	199.8044	229.3318	259.1231	282.2884	306.5441	331.4435	354.9141	379.3319	379.3319	
55.56	48.0318	47.3375	44.2973	41.4640	40.7925	40.5947	41.1214	42.1164	43.0315	44.5568	46.9580	46.9883	46.9883	
	43.2573	75.3721	115.6400	157.0487	190.8822	221.5014	250.4762	276.3603	302.3271	327.5806	352.4450	378.9811	378.9811	
74.08	42.4392	42.3529	40.9433	38.7025	37.2324	36.1754	36.1115	36.6904	37.3884	38.0198	40.1013	41.2800	41.2800	
	41.7037	71.2567	106.0336	146.1272	182.8858	215.1541	245.6175	273.9910	300.7360	326.4343	352.1374	378.4346	378.4346	
92.40	38.2892	38.3317	37.4405	35.7809	33.8876	32.4099	32.2264	32.4140	33.1382	34.4655	35.8155	37.0893	37.0893	
	41.3911	69.4862	101.2390	139.5944	176.6640	210.6687	243.0122	272.2526	299.9973	326.4628	352.3108	378.4327	378.4327	
111.12	35.1776	35.4379	35.0255	33.4980	31.4684	29.8380	29.3367	29.4569	30.0629	31.4681	32.7217	34.0281	34.0281	
	41.1493	68.2122	98.6283	134.4621	171.6859	209.4824	239.9527	270.5191	299.3256	326.2336	352.3690	378.4316	378.4316	
130.90	31.2913	31.7120	31.5796	30.1308	28.1733	26.4572	25.6350	25.6104	26.1244	27.4348	28.8264	30.1454	30.1454	
	41.5961	67.7803	96.2377	129.8442	167.1044	201.9287	236.6501	269.6312	299.2667	326.8049	353.5935	378.4337	378.4337	
146.68	27.8273	28.1971	28.1478	26.8397	24.8534	23.0127	22.0311	21.8949	22.4329	23.8330	25.2144	26.5792	26.5792	
	43.1142	68.1302	95.7161	127.8130	164.2305	200.1419	236.1340	270.4874	301.5839	329.5018	355.9854	378.4354	378.4354	

Figure C3. Wind speed and direction fields, Snapshot 2, Hurricane Gilbert (Continued)

Azimuth (deg)																				
Radius from Eye (km)	222.24	333.36	444.48	666.72	888.96	1111.20	1333.44	21.9911	22.3232	22.2726	21.0070	19.9701	17.0104	15.0922	15.4539	16.3320	17.9649	19.4206	20.8117	Speed Direction
	48.2227	15.2797	11.9073	9.2462	8.1847	7.7192	0.0003	71.0506	15.4210	96.5934	14.1749	161.9759	200.1071	240.1353	277.7679	311.2452	339.4258	4.3871	26.9649	
		59.4085	78.2312	83.7145	87.4849	91.0999	0.0000		78.2312	99.0084	124.0894	157.5215	198.7374	252.5386	307.8000	361.9550	5.4697	26.3856	43.4537	

Figure C3. (Concluded)

HOUR	Azimuth (deg)												Speed Direction
	4	0	30	60	90	120	150	180	210	240	270	300	330
1.05	4.3963	4.0342	5.2757	4.2752	4.2752	4.1167	4.3037	5.3263	5.9529	6.4900	6.0297	7.3454	7.1032
3.70	126.1605	127.8085	129.2227	129.2227	121.4585	111.8598	108.6827	99.3586	95.3692	97.1922	103.5944	108.2087	113.7288
5.36	21.4251	21.5344	20.4796	17.7524	17.7524	33	11.3704	9.3848	12.0194	15.7449	18.0165	20.6086	21.8749
7.41	37.0089	36.5428	34.7949	31.2838	27.2734	23.2734	23.2734	21.4502	24.9475	30.0264	36.6770	36.0251	37.1012
9.26	49.8882	48.9045	45.8225	41.2340	37.2407	33.2407	33.2407	33.2407	39.0780	45.8425	49.5049	51.9093	51.5030
11.11	57.1533	54.7085	51.8399	46.5805	42.6371	40.7362	43.7297	51.2851	56.0411	59.9010	60.6407	59.9402	59.9402
12.96	59.8893	56.8577	52.9880	48.9420	45.8379	45.8004	50.7343	57.4558	61.4242	63.2424	63.2424	61.8345	61.8345
14.02	59.9457	57.0390	53.2120	49.7794	47.7983	47.7983	54.7909	59.9112	62.2049	63.5493	63.5493	61.9236	61.9236
16.07	58.3341	56.1579	52.5230	49.4143	48.8094	50.9428	55.9151	59.6330	61.2777	62.4120	62.7174	61.0987	61.0987
18.52	56.7888	54.3898	51.1277	48.4443	49.1195	51.1177	54.8904	57.9288	59.5662	60.7103	61.3402	59.7725	59.7725
27.78	61.8421	57.0784	53.1462	43.1945	42.5715	43.0139	44.4941	47.9436	49.9844	51.3233	52.4197	52.2124	52.2124
37.04	45.2723	39.7696	34.9528	34.5312	37.3844	38.4476	39.8195	41.3220	42.8909	44.5716	45.9932	46.4385	46.4385
46.30	42.8749	38.6794	33.3399	32.5023	35.0328	36.3592	38.7942	39.9910	38.9378	40.3178	41.4510	42.5944	42.5944
55.56	40.7133	39.0645	32.9935	30.6409	30.8343	32.0090	33.2337	34.3760	35.7393	37.3275	38.8952	39.7059	39.7059
74.08	37.5181	37.7037	35.9396	31.8107	30.8217	30.2104	30.4323	31.6155	32.3080	33.7019	35.4440	36.4279	36.4279
92.40	35.8685	35.3101	34.6424	32.4351	30.6475	29.1240	28.6185	29.0998	29.7656	31.1144	32.5857	33.8197	33.8197
111.12	32.4035	32.7519	32.4719	31.0776	29.9380	27.2036	26.4352	26.4748	27.0522	28.3805	29.7433	31.0907	31.0907
138.00	28.2816	28.7423	28.4738	27.4948	25.3388	23.4652	22.4489	22.3391	22.8679	24.1456	25.4451	27.0026	27.0026
166.00	24.7912	25.1641	25.1344	24.0163	21.8495	19.8143	18.7196	18.5396	19.1710	20.5720	21.8760	23.4578	23.4578
	45.7233	70.2267	96.4324	127.2158	163.4677	208.1331	237.6380	273.7881	305.7702	333.9306	355.8031	375.9107	395.8031

Figure C-4. Wind speed and direction fields, Snapshot 3, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)																Speed Direction	
	225.24	19.4243	19.0213	19.7298	18.4517	16.4418	14.2169	12.9734	12.8710	13.9272	15.4506	16.9300	18.3479	19.7156	21.0834	22.4511	23.8188	25.1865
	52.5043	74.2517	98.0311	126.2401	160.9136	201.0063	244.6168	285.1865	319.9934	347.4928	367.5928	377.5933	381.2944	381.2944	377.5933	367.5928	347.4928	319.9934
333.36	13.9043	14.1046	13.9576	12.9278	10.7125	7.5964	4.9740	6.3039	8.8198	10.4849	12.0612	13.6375	15.2138	16.7901	18.3664	19.9427	21.5190	23.0953
	64.9363	82.2606	100.7419	123.0222	152.6733	192.3703	256.6308	325.4376	337.1131	17.2950	35.5267	53.9584	72.3901	90.8218	109.2535	127.6852	146.1169	164.5486
444.48	11.2427	11.4334	11.1020	10.0976	8.2240	4.7069	0.4328	4.0783	6.9944	8.9169	10.8394	12.7619	14.6844	16.6069	18.5294	20.4519	22.3744	24.2969
	75.1767	87.2204	100.7976	116.0226	136.3981	156.6264	123.1347	27.7766	35.5119	43.2472	50.9825	58.7178	66.4531	74.1884	81.9237	89.6590	97.3943	105.1296
666.72	9.1314	9.1445	8.8858	8.1080	7.1286	5.9349	5.2327	5.8709	6.8978	7.7410	8.3600	8.8415	9.2130	9.5845	9.9560	10.3275	10.6990	11.0705
	85.0483	91.8478	98.1386	104.9554	109.5968	109.3722	98.4381	86.3416	76.6166	75.1323	72.6080	70.0837	67.5594	65.0351	62.5108	60.0865	57.5622	55.0379
888.96	8.2405	8.2805	8.1111	7.7526	7.2863	6.8039	6.3340	6.7603	7.1626	7.5352	7.8979	8.2606	8.6233	8.9860	9.3487	9.7114	10.0741	10.4368
	90.3331	93.0460	96.1245	98.7809	100.3613	99.6455	96.2318	91.1883	87.3125	84.0833	80.8540	77.6247	74.3954	71.1661	67.9368	64.7075	61.4782	58.2489
1111.10	7.7573	7.8781	7.8150	7.5196	7.3797	7.1719	7.0875	7.1347	7.3113	7.4859	7.6605	7.8351	8.0097	8.1843	8.3589	8.5335	8.7081	8.8827
	93.2421	93.7816	95.1536	97.2275	97.2090	96.6678	95.1169	92.6936	90.7668	88.8400	86.9132	84.9864	83.0596	81.1328	79.2060	77.2792	75.3524	73.4256
1333.44	0.0803	7.2214	7.3573	0.0000	7.2617	7.3307	0.0300	7.3054	7.2957	0.0000	7.4033	7.4033	7.4033	7.4033	7.4033	7.4033	7.4033	7.4033
	0.0803	95.2750	95.5072	0.0000	96.9223	95.4119	0.0300	93.2323	92.8484	0.0000	91.4804	91.4804	91.4804	91.4804	91.4804	91.4804	91.4804	91.4804

Figure C4. (Concluded)

Hour	6	0	30	60	90	120	150	180	210	240	270	300	330
Radius from Eye (km)													
1.05	8.7387	8.8609	7.3751	4.2912	2.5068	2.0796	4.5706	6.2876	7.4405	8.4346	9.9084	9.8593	9.8593
	130.1325	144.1176	153.1155	155.2415	156.7912	108.7453	82.4150	75.2947	81.9592	95.7165	103.4595	114.1864	114.1864
3.70	10.8375	19.1038	18.1758	14.5375	12.0342	8.9114	6.5546	9.5680	13.7829	15.2382	17.4959	19.7043	19.7043
	116.3643	136.2980	158.3503	154.0287	208.0766	255.8532	321.2597	359.1774	26.7049	52.7187	70.0827	92.7629	92.7629
5.56	37.5673	36.0985	35.0390	31.5210	26.9626	23.0200	21.5755	26.4005	20.9589	32.3592	35.3477	37.1443	37.1443
	95.1091	119.9645	144.4408	171.5301	202.3993	238.3306	280.2272	311.0860	351.1961	18.9060	44.8649	68.2282	68.2282
7.41	52.9123	51.7840	48.8748	43.8276	39.4687	35.9573	34.1342	41.3744	44.8573	50.9019	52.5607	54.2765	54.2765
	83.7693	110.5392	137.4012	156.9833	199.6228	236.5251	278.5532	311.6802	339.1888	5.1511	31.0478	56.0400	56.0400
9.26	60.2722	58.3198	54.4180	49.4879	45.6534	43.7812	44.7960	54.1355	59.9512	61.0504	63.1895	62.2528	62.2528
	76.9301	104.9284	134.3890	166.1550	206.7424	239.1823	276.5372	307.2585	332.3792	356.6454	21.5529	48.2320	48.2320
11.11	61.7753	59.2660	55.3874	51.2279	48.1942	46.5938	51.4804	60.4581	63.7414	65.2773	65.2947	63.7361	63.7361
	72.6413	102.2596	133.6112	157.2547	203.7385	241.7413	278.0803	303.1634	326.1779	350.5936	15.0675	42.6065	42.6065
12.96	61.2395	58.3682	54.6777	51.2651	49.5085	51.5704	57.3164	61.9924	64.6038	55.6817	43.3283	63.4411	63.4411
	69.6785	100.8050	133.7934	169.1474	206.5206	243.0862	274.3547	299.2185	322.2219	346.0483	10.7120	38.5089	38.5089
14.82	59.8255	56.4528	53.1556	50.5646	50.0528	53.0123	58.3169	61.5660	63.3714	64.5352	64.3759	62.3326	62.3326
	67.5272	99.9906	134.2455	171.1573	208.6410	243.2386	271.9116	295.6800	318.7164	342.0263	7.7321	35.6283	35.6283
16.67	57.6073	54.4111	51.3413	49.4066	50.0538	53.1536	57.4593	60.2171	61.6626	62.7787	63.0473	61.1262	61.1262
	66.0825	99.4381	134.4933	172.7232	209.8975	242.6401	269.5732	293.0047	316.2450	340.5653	5.6432	31.5158	31.5158
18.52	55.4491	52.3679	49.2613	47.0018	49.4478	52.1387	55.4111	58.0281	59.4404	60.0240	61.3085	59.7945	59.7945
	64.9577	95.5450	135.2441	173.6429	210.2933	241.6570	267.6889	291.2797	314.7228	338.9867	3.9918	31.9720	31.9720
27.78	50.1155	49.6726	41.1240	41.2747	42.7040	44.6806	46.5360	47.9773	49.4243	51.3450	52.6041	52.9814	52.9814
	60.0535	100.9003	140.0168	177.4193	210.2838	239.2319	264.8191	288.8104	312.7512	336.5960	0.2626	28.8418	28.8418
37.84	47.4332	42.8484	37.3719	34.9134	38.1672	39.5486	40.8194	42.1048	43.4624	45.0299	46.5261	47.4065	47.4065
	52.1713	93.2250	140.2711	178.4740	210.9635	237.8774	264.9508	287.4868	311.4902	335.0175	358.7277	23.5724	23.5724
46.30	44.6671	43.0607	37.9987	35.4313	35.5423	36.4978	37.4746	38.3351	39.2725	41.1783	42.5748	43.6138	43.6138
	47.7361	81.1588	126.2534	170.9221	204.7558	232.3748	258.3769	283.3855	307.9628	332.8188	356.6253	28.9968	28.9968
55.56	42.3231	42.1377	39.3022	36.2074	35.1539	34.9848	35.4557	36.1846	37.0296	38.5948	40.0062	41.0082	41.0082
	44.5523	74.7401	113.0655	157.2174	192.7852	223.4742	251.9711	278.0828	304.2329	329.9241	354.4816	18.8977	18.8977
74.88	38.4837	39.0401	38.2846	34.3313	34.8051	33.0439	32.3817	32.9078	33.5304	34.4868	36.0998	37.3813	37.3813
	41.8676	66.9723	100.5228	137.9882	174.4284	207.9971	248.3938	285.4181	308.0038	335.1406	351.1395	15.0877	15.0877
92.48	34.7073	35.1943	35.0407	33.2377	31.5331	29.8140	28.9198	28.0842	29.2671	30.3728	31.9581	33.3674	33.3674
	40.6172	67.4680	94.8019	131.4945	167.4435	201.7901	235.8151	268.6578	296.4031	324.5994	351.1893	15.7644	15.7644
111.12	30.9171	31.4111	31.3769	30.1923	28.0457	26.2388	25.2340	24.9818	25.4827	26.4939	28.0788	29.5367	29.5367
	41.7617	67.7507	95.8992	128.7989	164.8235	199.9148	234.7124	267.2335	298.1273	326.3189	353.2555	17.0723	17.0723
138.90	26.0183	26.3379	26.5597	25.4220	23.2675	21.2988	20.1322	19.0343	20.3927	21.7892	23.2620	24.6844	24.6844
	44.9949	69.9380	96.0423	127.0765	163.7434	199.2784	234.3104	271.8036	303.2742	332.0342	358.8616	22.2574	22.2574
166.68	22.3615	22.7341	22.7297	21.7449	19.4888	17.2548	16.0748	15.0873	16.5683	18.0389	19.5481	21.0874	21.0874
	48.7892	72.2471	97.1235	128.3747	160.4485	200.0882	239.1173	277.9383	310.9147	339.8564	351.1367	27.6088	27.6088

Figure C5. Wind speed and direction fields, Snapshot 4, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)												Speed 16.2609 30.0515	Direction 16.2609 30.0515
	17.2347 57.3792	17.4536 77.5231	17.5176 99.4562	16.4748 125.8515	14.2267 159.5671	11.7034 201.2047	10.3109 249.0143	10.4290 295.1010	11.0034 330.8544	13.4415 357.6435	14.8759 19.4485	16.2609 30.0515		
222.24	17.2347 57.3792	17.4536 77.5231	17.5176 99.4562	16.4748 125.8515	14.2267 159.5671	11.7034 201.2047	10.3109 249.0143	10.4290 295.1010	11.0034 330.8544	13.4415 357.6435	14.8759 19.4485	16.2609 30.0515		
333.36	12.5978 70.0161	12.7505 85.9570	12.4597 101.8971	11.5346 121.2253	9.4265 146.4231	5.6401 180.7132	2.2301 261.4161	4.9374 333.9102	7.7820 16.3208	9.6954 31.5602	11.0005 46.1408	11.9226 58.5154		
444.48	10.4180 50.4844	10.5605 66.3027	10.2281 101.2231	9.3400 113.6600	7.6101 127.5735	4.8645 155.8766	2.6378 101.3300	4.4404 55.5247	6.9514 52.6874	8.6713 58.0583	9.3069 64.4418	10.0099 72.0876		
555.60	8.7068 39.2699	8.7949 55.1404	8.5321 98.3721	7.9987 123.1315	7.2681 105.9531	6.4323 105.3618	5.9130 98.0260	6.3725 89.6426	7.0713 83.5594	7.6877 81.7757	8.1610 83.1927	8.9232 85.8526		
666.72	8.0090 32.5539	8.1212 48.5714	7.9856 96.7942	7.7204 98.6809	7.3085 99.7154	7.0500 99.1711	6.6372 96.0599	7.0098 93.4547	7.2903 90.6066	7.5711 89.5374	7.8193 89.6378	8.0000 90.7763		
777.84	7.6842 24.4595	7.8127 40.0867	7.7697 96.0967	7.5105 97.6576	7.4548 97.5046	7.3042 97.1599	7.2160 96.0514	7.2743 94.3445	7.4108 92.9108	7.5394 92.3456	7.7054 92.1451	7.7495 93.0694		
888.96	8.0000 0.0000	7.4844 96.2097	7.5363 96.4078	8.0000 0.0000	7.2920 97.4512	7.4118 96.2850	8.0200 0.0200	7.3940 94.6869	7.3656 94.3605	8.0000 0.0000	7.6297 93.4625	7.4519 95.0748		

Figure C5. (Concluded)

HOUR	0	30	60	90	120	150	180	210	240	270	300	330	Speed Direction
1.05	9.6751 131.4743	10.2850 145.4287	8.9701 156.9169	5.0424 172.0941	3.2843 193.3322	0.8951 214.8410	3.0503 236.7135	5.7292 261.6068	7.2887 285.5712	9.8195 309.5335	10.3626 333.5165	10.5073 357.5112	10.5073 381.5112
3.70	22.1151 105.9075	22.7124 128.9179	21.9172 153.2021	18.5023 178.0285	15.4904 203.3124	12.4397 228.4941	10.3144 251.1562	11.1921 276.8825	14.4920 301.8825	16.1192 326.8825	18.7350 351.8825	21.8567 376.8825	21.8567 401.8825
5.56	40.1335 92.3423	39.9098 116.0332	37.9009 140.1048	34.4004 167.1422	29.6840 197.5324	25.3187 232.5270	23.7646 257.5745	24.9115 282.6220	28.1012 307.6665	31.6102 332.7111	35.3339 357.7665	38.3804 382.8111	38.3804 407.8111
7.41	52.3583 82.7491	51.6783 107.4450	48.7181 133.5187	43.5401 152.4378	38.7817 176.9618	34.4314 201.9661	33.4179 227.7785	37.2201 252.7785	41.8973 277.7785	46.4364 302.7785	50.2437 327.7785	52.1404 352.7785	52.1404 377.7785
9.26	57.4435 77.0041	55.8262 102.4278	52.0313 130.4785	46.7359 151.4817	41.8824 176.8730	38.2327 201.8730	40.5396 226.8730	46.5423 251.8730	52.5519 276.8730	56.4999 301.8730	58.8566 326.8730	58.8566 351.8730	58.8566 376.8730
11.11	58.4123 73.6843	55.7510 108.3106	51.0363 129.5666	46.9532 152.3754	42.4540 179.3018	41.0362 200.4132	45.6367 225.4132	53.2949 250.4132	59.1010 275.4132	61.8479 300.4132	62.0448 325.4132	60.5073 350.4132	60.5073 375.4132
12.96	57.7041 71.8643	56.4403 99.6431	50.8099 129.9590	45.9986 164.5091	42.4490 194.5091	43.4062 224.5091	49.7304 250.5091	57.4779 275.5091	61.4746 300.5091	63.5587 325.5091	63.3929 350.5091	61.0737 375.5091	61.0737 400.5091
14.62	56.6702 70.4987	52.4970 99.9625	48.7169 131.1084	46.6986 157.2944	42.4143 187.2944	45.3132 212.2944	52.6519 237.2944	59.2950 262.2944	62.1235 287.2944	63.7755 302.2944	63.7422 327.2944	61.3841 352.2944	61.3841 377.2944
16.67	55.9263 68.7113	50.9480 100.8564	46.9299 132.7207	43.2849 170.2868	42.5326 195.2868	46.9449 220.2868	54.1866 250.2868	59.3921 275.2868	61.5424 300.2868	62.8809 325.2868	62.4332 350.2868	61.5361 375.2868	61.5361 400.2868
18.52	55.7155 66.0263	49.3225 101.9039	45.2176 134.7840	42.1794 173.0711	42.8823 195.0711	48.0471 220.0711	54.2936 245.0711	58.3783 270.0711	60.2713 295.0711	61.5158 320.0711	62.3274 345.0711	61.2415 370.0711	61.2415 395.0711
27.78	56.3915 50.9549	50.0541 93.5469	43.0713 140.5219	41.8903 180.3155	44.6678 212.5274	47.7039 237.7044	50.1354 260.1354	51.4035 282.9339	52.7310 306.7090	54.3364 331.0107	55.7974 354.6830	56.4494 370.6344	56.4494 395.6344
37.04	52.7289 42.9993	52.1626 70.4174	47.0326 119.0424	44.7437 152.3575	42.5870 193.0726	45.4691 221.9692	46.1380 249.0666	47.2131 274.2194	47.8018 299.8888	49.1724 325.4920	50.7911 350.3728	51.7145 375.6125	51.7145 395.6125
46.30	49.4963 39.2413	49.4071 69.7949	47.0230 105.3398	45.4781 145.5439	44.7144 176.7207	43.4323 209.9461	43.3531 240.3531	43.7702 267.5004	44.2846 294.4684	45.7043 321.3986	46.9648 347.3514	48.2408 372.3514	48.2408 397.3514
55.56	46.2481 37.3033	46.5732 66.5984	45.7421 99.7081	44.3816 136.7935	42.7059 171.3428	41.2463 203.3123	40.7339 234.6666	40.6701 263.6939	41.0147 291.9500	42.3545 319.1009	43.5703 345.0168	44.9182 370.0168	44.9182 395.0168
74.08	39.5081 37.3406	40.0985 65.2433	39.0577 95.7058	38.4005 130.4793	36.8042 160.0787	35.9998 198.8785	34.2324 231.0133	33.9715 262.2479	34.2099 291.5577	35.3791 319.3531	36.7413 346.7242	38.1708 371.7413	38.1708 396.7413
92.40	32.7762 39.5185	34.2980 66.2406	34.2436 94.9796	33.0132 128.9923	30.9387 164.2048	29.2245 198.2890	28.3528 232.0567	27.7856 263.9776	28.1982 294.3946	29.5159 322.9063	30.8178 349.9463	32.3094 370.9463	32.3094 395.9463
111.12	29.0925 42.4703	29.6316 68.0642	29.6101 95.0500	28.4479 128.4033	26.3126 164.1621	24.4701 199.4439	23.4583 234.5357	22.9706 267.6908	23.4993 299.1931	24.7850 317.8202	26.2034 346.4448	27.7056 371.4448	27.7056 396.4448
130.90	26.1065 46.8933	26.6175 71.3079	24.5826 94.0819	23.4337 127.6674	21.1903 164.5188	19.1848 200.6886	18.0033 238.5966	17.7466 275.0992	18.4161 307.0056	19.7943 335.7482	21.3652 366.7482	22.7997 391.7482	22.7997 416.7482
146.68	20.7313 51.0565	21.0832 73.9968	21.0026 98.3159	20.0035 127.0672	17.5596 163.4597	15.5519 202.0964	14.2382 242.9711	14.0643 283.3518	14.9368 314.0491	16.5062 344.0491	18.0036 364.0491	19.4459 394.0491	19.4459 419.0491

Radius from Eye (km)

Figure C6. Wind speed and direction fields, Snapshot 5, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)															Speed Direction	
	222.24	16.2366	16.4459	16.4392	15.3768	13.1029	10.4823	8.9548	9.3177	10.9143	12.4443	14.0424	15.3786	16.4459	17.3768	18.4459	19.3768
	59.8413	79.1087	100.3974	126.2712	159.5497	202.5034	254.9291	302.8154	337.9561	357.9561	373.9561	384.9561	395.9561	406.9561	417.9561	428.9561	439.9561
339.36	12.3012	12.4639	12.1379	11.2045	9.1403	5.3362	1.4354	4.7048	7.5888	9.5158	10.8113	11.4709	12.1379	12.8045	13.4709	14.1379	14.8045
	72.0442	88.4573	102.1034	120.8771	144.8609	175.7883	241.3511	2.2034	21.3593	35.0852	46.3594	56.3594	66.3594	76.3594	86.3594	96.3594	106.3594
444.48	10.4068	10.5438	10.1955	9.3288	7.5925	4.9764	2.8550	4.5645	6.8749	8.4169	9.3432	10.2695	11.1958	12.1221	13.0484	13.9747	14.9010
	80.4962	90.3538	101.2533	113.6536	127.3365	135.4166	105.9514	58.9183	54.0608	58.5198	64.5864	70.6530	76.7196	82.7862	88.8528	94.9194	100.9860
446.72	8.9874	8.9254	8.4443	8.0536	7.2200	6.3117	5.7509	6.1776	6.9492	7.4584	7.8584	8.2584	8.6584	9.0584	9.4584	9.8584	10.2584
	88.4329	93.4644	98.6051	103.9245	107.3191	106.9290	99.9562	89.5139	82.4030	80.2801	81.6499	83.0197	84.3895	85.7593	87.1291	88.4989	89.8687
888.96	8.2143	8.2438	8.0752	7.7902	7.3391	6.9304	6.7107	6.4645	7.1903	7.5405	7.8907	8.2409	8.5911	8.9413	9.2915	9.6417	10.0000
	91.7831	94.2889	97.0345	99.4183	100.7916	100.2156	97.4378	93.1732	89.5303	86.1032	82.7801	79.4569	76.1337	72.8105	69.4873	66.1641	62.8409
1111.20	7.7793	7.9021	7.8292	7.5234	7.3981	7.1983	7.0787	7.1490	7.3257	7.5024	7.6791	7.8558	8.0325	8.2092	8.3859	8.5626	8.7393
	94.1029	94.8481	94.3721	98.2272	98.3170	97.8259	96.3825	94.0699	92.0809	91.2263	90.3717	89.5171	88.6625	87.8079	86.9533	86.0987	85.2441
1333.44	8.0003	7.5888	7.5720	8.0000	7.2542	7.3270	8.0308	7.2973	7.2944	7.2944	7.2944	7.2944	7.2944	7.2944	7.2944	7.2944	7.2944
	8.0003	94.0205	96.3524	0.0000	98.6106	96.7118	0.0300	94.4424	93.7458	93.7458	93.7458	93.7458	93.7458	93.7458	93.7458	93.7458	93.7458

Figure C6. (Concluded)

HOUR	Azimuth (deg)												Speed Direction
	10	0	30	60	90	120	150	180	210	240	270	300	330
1-05	9.5754	10.1489	8.8140	4.8803	3.2036	0.7628	3.5340	5.7002	7.2473	8.7338	10.3057	10.4284	112.8651
	131.3061	145.5391	157.1742	172.3176	193.9045	173.6769	65.3313	60.1013	72.6960	92.2133	100.2788	112.8651	
3-70	21.8349	22.5112	21.8087	18.4959	15.6772	12.9954	10.6750	11.3403	14.4418	16.0212	18.5949	21.4802	21.4802
	110.0727	129.3418	153.8130	178.8702	204.2604	245.2943	290.2307	333.2014	354.7009	40.7630	63.4798	87.3928	
5-56	39.9683	39.8839	38.0393	34.7197	30.2136	26.1395	24.3355	24.9039	27.7189	31.2022	35.2078	38.1353	38.1353
	92.8095	116.5906	140.6766	157.7189	197.8380	232.1158	271.3182	311.9154	346.3351	380.8025	44.1054	68.1871	
7-41	52.4135	51.9334	49.1763	44.1494	39.4865	35.3683	33.9757	36.6696	40.9160	45.5416	49.7462	51.9256	51.9256
	83.3271	108.1837	133.9338	162.8399	194.7056	230.8346	271.0784	308.6703	340.6453	369.0339	34.4334	58.4751	
9-26	57.4395	56.2852	52.6725	47.4795	42.4542	39.3353	40.1104	45.2045	50.9773	55.5520	58.2599	58.6482	58.6482
	77.5739	102.7956	130.6036	151.2347	190.9869	234.1264	274.5355	309.6670	338.6639	358.1883	27.8842	52.3983	
11-11	58.7309	56.2693	52.5187	47.4951	43.0319	41.2267	44.5965	51.5284	57.5391	61.0180	61.5788	60.4645	60.4645
	74.2327	100.5104	129.3953	151.7234	197.6701	238.4584	278.1257	310.1427	335.2515	358.7165	22.5929	47.9914	
12-96	58.0383	54.9767	51.1452	46.4519	42.7334	42.8059	48.2579	55.9123	60.8254	63.1104	63.8071	61.0043	61.0043
	72.4719	99.7595	129.5476	159.4785	201.7781	243.2130	280.4522	308.5649	333.0397	353.6751	17.7420	44.4688	
14-82	56.9962	53.1903	49.3068	45.2064	42.3613	44.3989	51.1519	58.3085	61.7839	63.5989	63.5989	61.3137	61.3137
	71.2343	99.9851	130.5242	155.9640	205.8608	246.9568	281.0129	305.3955	326.5873	348.0626	13.1431	40.9376	
16-67	56.2456	51.4185	47.4392	43.7170	42.2027	45.7242	53.0394	59.0150	61.5397	63.0095	63.4761	61.5397	61.5397
	69.7832	100.8813	132.0643	168.7837	207.7567	249.3455	279.8398	301.5139	322.2605	344.6946	8.9953	37.2638	
18-52	56.0443	49.8188	45.6521	42.3345	42.2330	46.8669	53.5906	58.4784	61.5426	61.8613	62.8233	61.4017	61.4017
	67.4003	102.0571	134.8959	171.5683	213.0774	260.3013	277.1200	297.5455	318.5396	341.3363	5.3063	33.6166	
27-78	57.1843	51.0141	43.6755	41.8925	44.5440	48.1817	50.8526	52.2907	53.6941	55.3218	56.8044	57.3805	57.3805
	52.3207	93.9816	140.0392	180.3004	213.5217	239.1872	261.4802	283.8847	307.5496	331.8859	355.5528	21.7381	21.7381
37-04	53.9147	53.4386	49.0093	45.8119	46.7055	46.8030	47.2721	48.4672	49.0258	50.3930	52.9557	52.9292	52.9292
	43.4042	76.7432	118.9008	161.5761	193.3779	211.4850	246.5771	274.0632	298.8261	325.5750	350.8764	16.0257	16.0257
46-30	50.8042	50.7789	49.2526	46.9166	46.1723	45.0147	44.7327	45.1200	45.4161	47.0309	48.3946	49.5576	49.5576
	39.3247	70.0083	105.1282	144.5389	177.4712	209.8611	239.6166	266.9173	294.2257	321.1307	347.2445	12.5691	12.5691
55-56	47.5335	47.0519	47.1005	45.7905	44.0913	42.0674	42.1337	41.9868	42.3103	43.6506	44.9514	46.2041	46.2041
	37.4645	66.7894	99.5110	135.9901	170.4592	202.4401	233.8561	263.0301	291.4028	318.6991	345.6883	11.2397	11.2397
74-08	40.3411	41.1248	40.9084	39.5887	37.9822	36.1924	35.3176	35.0257	35.2475	36.4124	37.7478	39.1944	39.1944
	37.5313	65.9270	95.7975	130.1001	165.4775	198.2427	230.3507	261.6772	291.0672	318.9815	346.5262	12.0373	12.0373
92-40	34.5822	35.0845	35.0508	35.0508	31.7985	30.0720	29.1326	28.5955	28.9941	30.3147	31.6080	33.1035	33.1035
	39.8089	66.4141	95.2519	128.8554	163.8989	197.8869	231.5259	263.4983	293.9749	322.6035	349.9277	14.8068	14.8068
111-12	29.7221	30.2573	30.2373	29.1093	28.9763	28.1259	24.1348	23.5935	24.1120	25.3994	26.0183	28.3268	28.3268
	42.7931	68.5360	96.2709	128.4688	163.9217	199.0788	234.1369	267.2756	298.8268	327.5847	354.3762	19.0502	19.0502
138-90	24.5593	25.0718	25.0241	23.9041	23.4714	19.4445	18.4588	18.1941	18.8394	20.2230	21.8041	23.2465	23.2465
	47.3193	71.9082	97.4697	127.9644	164.4535	200.4520	238.1339	274.7439	308.7056	335.6149	359.9277	25.0401	25.0401
146-57	21.0671	21.4215	21.3219	20.3967	17.9032	15.4757	14.5171	14.3544	15.2304	16.0151	18.2237	19.7702	19.7702
	51.5821	74.7010	98.9339	127.5326	163.5380	201.9574	242.6323	283.8029	316.2121	343.9663	369.9277	9.4450	9.4450

Figure C7. Wind speed and direction fields, Snapshot 6, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)										Speed Direction	
	1	2	3	4	5	6	7	8	9	10	11	12
222.24	16.4351	16.8498	16.4179	15.5711	13.2937	10.4382	9.3123	9.4671	11.0719	12.8149	14.2247	15.5499
	60.5953	75.9334	101.2857	127.0105	159.8904	201.5342	254.8345	302.8729	337.9539	3.4953	26.3332	42.8843
333.36	12.3933	12.5517	12.2023	11.2806	9.2285	5.4641	1.4396	4.7539	7.4746	9.4807	10.9831	11.7589
	73.0761	87.7937	103.1885	121.8343	145.4821	175.9317	219.7132	3.0542	22.0272	35.8881	49.1652	61.8295
444.48	10.4616	10.5918	10.2240	9.3475	7.6592	5.0010	2.9187	4.5965	6.9331	8.4802	9.4155	10.0406
	81.6973	91.5825	102.3836	114.6559	128.1188	136.1346	107.9175	60.5688	55.2227	59.5774	65.4380	73.2025
666.72	8.9342	8.9407	8.6591	8.0737	7.2374	6.3673	5.0335	6.2045	6.9752	7.6908	8.2474	8.6409
	89.7336	94.7250	99.7503	104.9848	108.3151	107.9895	101.3185	91.1226	83.8425	81.5327	82.9376	85.8631
888.96	8.2403	8.2522	8.0821	7.7424	7.3419	6.9518	6.7379	6.8645	7.2164	7.5644	7.8772	8.1125
	93.0151	95.2210	98.1807	100.5187	101.8878	101.3242	98.6124	94.5295	90.8974	89.4371	89.5126	90.0602
1111.20	7.7889	7.9091	7.8331	7.5249	7.4114	7.2193	7.0974	7.1631	7.3488	7.5347	7.7513	7.8297
	95.8639	95.9823	97.4078	99.2048	99.4150	98.9630	97.5109	95.3587	93.4042	92.4918	92.2960	93.3073
1333.44	6.0803	7.5530	7.5697	6.0800	7.2373	7.3415	6.0380	7.2109	7.3144	6.0800	7.4632	7.5831
	0.0003	94.0489	97.5185	0.0000	98.8891	97.8577	0.0166	95.8954	94.8563	0.0000	93.7957	95.2227

Figure C7. (Concluded)

HOUR 12	Azimuth (deg)												Speed Direction
	0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.	
1.85	16.3507	15.5492	14.7316	14.1334	11.8043	9.6643	8.8777	7.6513	9.3323	12.1211	13.1807	14.7227	14.7227 69.5132
3.70	89.0783	109.9267	133.8400	157.5741	182.6445	217.8008	259.2302	305.1008	331.2107	19.5790	45.4047	69.5132	
5.54	21.1541	21.0080	20.1147	18.6846	16.5956	14.1334	13.3480	14.2748	16.4207	18.4203	19.9848	22.4651	19.9848 62.6439
7.41	87.0193	111.0501	133.8895	151.1057	190.6693	221.6304	260.5167	301.2557	336.8775	10.3235	39.0295	62.6439	
9.26	23.6835	23.5946	22.4916	21.2237	19.1422	17.2592	16.1125	15.7209	16.4401	18.6777	20.6577	22.4651	22.4651 63.5799
11.11	88.0137	111.9452	136.7157	153.5315	192.3616	224.7860	263.0360	298.7363	335.5961	8.6204	37.5695	63.5799	
12.96	25.2937	25.3959	24.4926	22.8102	20.7299	18.7836	17.4735	17.1555	18.0420	19.9639	22.1604	24.0734	24.0734 64.4330
14.82	89.2517	111.7167	134.8552	150.5361	189.4996	223.8541	262.8109	302.0380	338.4953	10.8613	39.5920	65.4556	
16.67	26.4703	26.6732	25.7461	23.9256	21.6498	19.5501	18.1382	17.6897	18.9344	20.7806	23.0651	25.1829	25.1829 65.6881
18.52	90.1273	113.8179	138.4842	154.8467	193.5282	228.5671	262.0797	299.2004	336.1495	9.4293	38.8583	65.6881	
20.37	27.3912	27.6545	26.7276	24.7707	22.2290	19.9230	18.4369	18.2280	19.2976	21.3558	23.7542	25.9406	25.9406 66.0507
22.22	90.3942	113.8165	137.7407	153.8100	192.8550	225.8495	262.4388	300.2133	336.7144	10.0514	39.6523	66.0507	
24.07	28.0793	28.3793	27.4410	25.3956	22.6006	20.0496	18.5168	18.3867	19.4245	21.8171	24.2756	26.5268	26.5268 66.8327
25.92	90.0713	112.9781	136.4615	152.3443	191.5785	225.0270	262.6160	301.0903	337.3178	10.5108	39.8327	66.8327	
27.78	28.4974	28.8117	27.8449	25.7704	22.8019	19.9705	18.4324	18.3916	19.4217	22.1659	24.6413	26.8754	26.8754 67.1994
29.63	89.2517	111.7167	134.8552	150.5361	189.4996	223.8541	262.8109	302.0380	338.4953	10.8613	39.5920	67.1994	
31.48	28.5961	28.9769	27.9598	25.8431	22.8641	19.7458	18.2154	18.3104	19.9421	22.4137	24.8926	27.0094	27.0094 67.9557
33.33	88.2287	110.4239	133.2625	150.6981	187.6121	222.4896	262.9525	303.1747	339.5510	11.2531	39.1221	67.9557	
35.18	28.3763	28.8763	27.7838	25.6163	22.7516	19.9373	17.4332	18.1333	19.9668	22.5799	25.8168	28.9384	28.9384 68.7194
37.04	87.2983	109.3154	132.0436	157.1613	185.8946	221.2597	263.2337	304.5507	341.2560	11.9560	38.6337	68.7194	
38.89	27.5243	27.2395	26.1451	23.8829	20.4571	17.2621	15.8151	17.7982	21.9103	25.5891	27.4991	29.8356	29.8356 69.4865
40.74	87.5486	110.0339	132.7934	157.0876	185.6173	223.3199	271.3176	316.9973	351.2734	17.0865	40.1838	69.4865	
42.59	31.2762	27.9659	26.1313	23.2087	19.4146	16.8069	16.9352	21.3054	27.8439	32.5133	35.4437	37.7732	37.7732 69.9990
44.44	82.9183	114.0202	138.1378	153.5896	194.3630	235.4245	280.0775	326.1669	369.4353	8.8410	29.3420	53.2386	53.2386 70.7622
46.29	37.7403	33.9877	30.1342	26.0590	21.9835	20.7487	22.8364	28.7706	33.9362	36.8290	39.4773	39.9090	39.9090 71.5255
48.14	46.7495	102.8611	136.4655	156.9946	201.8632	242.0467	281.6146	311.7523	359.5922	350.6365	11.4635	36.2220	36.2220 72.2887
50.00	41.0631	35.6166	35.2725	31.0728	28.0371	27.2107	29.7101	33.3735	36.3337	38.1652	40.0435	40.8103	40.8103 73.0518
51.85	54.9455	87.9484	125.2973	152.0964	197.8336	233.8171	269.9597	291.9663	314.0026	338.2691	1.2881	26.6225	26.6225 73.8149
53.70	39.5231	35.7257	37.9999	35.4729	34.3411	32.8975	32.6347	33.0150	34.5005	35.7351	37.5624	38.9449	38.9449 74.5780
55.55	46.0911	75.7024	108.9256	145.6304	180.5994	219.7917	245.9622	274.2275	301.9324	328.9923	354.2159	19.6170	19.6170 75.3411
57.40	36.8387	36.1449	35.2514	33.5042	31.8309	30.2987	29.7382	30.0229	30.7258	32.0837	33.5911	34.8388	34.8388 76.1042
59.25	44.9325	73.1756	104.0901	139.5711	175.2785	207.3613	241.3360	271.0671	306.3315	328.2963	353.9312	19.0611	19.0611 76.8673
61.10	32.5401	32.7556	32.0507	30.6643	28.6943	27.0738	26.4187	26.4412	27.2036	28.5653	30.0238	31.3351	31.3351 77.6304
62.95	45.7313	73.1789	103.0804	136.6625	171.1934	206.1395	240.4534	272.0221	302.1886	330.1808	355.9885	26.8932	26.8932 78.3935
64.80	28.2071	28.5583	27.9393	26.5857	24.5283	22.7337	21.8940	22.0497	22.8525	24.2383	25.8227	27.1144	27.1144 79.1566
66.65	48.2481	78.8337	102.9048	135.1480	170.8138	206.0441	243.1395	276.3384	306.5859	334.7673	0.6820	25.3947	25.3947 79.9197
68.50	25.0965	25.3670	24.7497	23.5271	21.2642	19.2766	18.4352	18.6395	19.5896	21.1372	22.6660	24.0119	24.0119 80.6828
70.35	50.9229	76.3024	103.5784	134.5078	170.2054	204.8717	244.6567	280.0321	312.0575	339.7440	5.2074	26.2887	26.2887 81.4459

Figure C8. Wind speed and direction fields, Snapshot 7, Hurricane Gilbert (Continued)

Azimuth (deg)													
												Speed	Direction
222.24	20.8111	21.1862	20.8631	19.3016	16.9316	16.7055	13.7515	14.0595	15.4084	17.1109	18.5938	20.0075	
	56.5135	77.5689	104.8740	134.4426	168.6485	208.7104	251.7507	290.8839	323.5586	350.5375	35.8685	35.3829	
333.36	16.5603	16.8229	16.1883	15.0640	12.7496	10.1152	8.3060	9.3517	11.2449	13.1302	14.6756	15.9211	
	63.7467	84.4425	105.9520	131.8642	164.1942	204.0379	259.0377	311.2555	343.9753	7.6778	28.1276	45.8844	
444.48	14.3125	14.5290	13.9106	12.7955	10.6428	7.5634	4.4322	5.9584	9.1516	11.1680	12.7089	13.7544	
	69.7093	87.1339	106.5930	129.4431	156.7112	195.7780	258.7797	332.3108	2.9151	22.1357	38.5595	53.9381	
666.72	11.0379	12.1376	11.5583	10.4991	8.6628	5.4806	1.7738	3.0931	6.7957	9.2559	10.7025	11.9151	
	76.7527	90.8065	105.5706	123.8008	143.2619	164.4315	176.2188	32.3861	35.6422	43.9654	53.7976	64.6649	
888.96	10.7475	10.8701	10.3390	9.3544	7.7021	5.3080	3.1535	3.5826	6.1556	8.2807	9.5011	10.3149	
	81.8002	92.6319	104.3400	117.4387	131.1810	140.7968	127.6171	77.3321	59.1984	59.1180	44.0683	72.1120	
1111.20	9.9243	10.0397	9.5647	8.5923	7.3180	5.5693	4.1778	4.5115	6.0912	7.7176	8.9865	9.5568	
	85.9545	96.0354	103.4656	114.5397	122.5274	126.4194	114.9110	88.4732	72.1534	68.8356	71.2967	77.7603	
1333.44	8.0803	9.4190	8.9686	8.0000	7.0382	5.7541	0.0360	5.1692	6.0791	0.0000	8.5450	9.0801	
	0.0003	95.4576	103.4790	0.0000	117.4715	118.2853	0.0300	92.4314	79.4402	0.0000	76.5999	82.1442	

Radius from Eye (km)

Hour	Azimuth (deg)												Speed	Direction
	14	0	30	60	90	120	150	180	210	240	270	300	330	
1.05	6.3147	6.2123	5.7882	5.1433	4.7461	4.7461	5.1433	5.4502	5.8912	6.4114	6.8043	6.7546	6.7546	
3.70	113.4983	117.9277	118.9495	115.4730	113.6873	107.9817	101.3154	96.6061	97.0961	101.4459	103.3165	107.4558	107.4558	
5.56	9.3112	9.0842	8.2132	4.4910	4.7100	2.4043	2.1378	3.6093	5.8876	7.4573	8.6332	9.4594	9.4594	
7.41	109.5661	121.3492	135.8164	165.0103	151.1653	143.6505	90.4703	65.2639	44.1703	74.3638	83.6006	94.7260	94.7260	
9.26	13.1143	13.0617	12.2754	10.6279	8.2434	5.1429	3.2935	5.1408	7.9992	10.2942	13.7375	12.7349	12.7349	
11.11	101.9886	121.2035	140.1746	150.5261	185.4784	219.9188	285.0376	349.4021	19.9757	42.8766	63.3147	82.7475	82.7475	
12.96	16.8883	17.0289	16.2297	14.5031	13.2905	10.0180	8.8706	9.8225	11.5782	13.3750	15.0022	16.1879	16.1879	
14.82	97.9113	119.8363	141.6720	165.5396	193.9307	230.2339	277.3774	322.8787	357.4623	26.5500	31.7343	35.3055	35.3055	
16.67	20.2743	20.6665	19.9056	18.0561	15.6928	13.4830	12.4554	13.1633	14.5085	16.1500	17.9845	19.2806	19.2806	
18.52	96.4741	119.4323	142.4797	157.1964	196.3495	231.8090	273.3212	313.5628	348.1594	18.8159	43.3690	72.1667	72.1667	
20.37	23.1023	23.7701	23.0648	21.1403	18.5100	16.0379	14.9122	15.4324	16.6394	18.3887	20.1893	21.8452	21.8452	
22.22	95.8632	119.3792	142.4355	167.3588	196.2962	230.9966	270.5374	309.1006	343.8620	15.2845	44.1415	70.9994	70.9994	
24.07	25.4683	26.3959	25.6746	23.6849	20.7533	18.0016	16.7268	17.0047	18.3023	20.1405	22.0899	24.0113	24.0113	
25.92	95.1535	118.3341	141.2413	166.2523	194.8393	229.2747	268.4595	306.9566	342.0146	13.6836	43.0220	70.1846	70.1846	
27.78	27.4935	28.4418	27.6445	25.5862	22.4233	19.2311	17.8150	18.0439	19.4890	21.3674	23.6959	25.7950	25.7950	
29.63	93.9031	116.3605	139.2284	164.2486	192.6340	227.2160	267.0525	306.0743	341.5164	13.0753	42.1994	69.1750	69.1750	
31.48	29.1255	29.9088	28.9356	26.7439	23.5432	20.4442	18.3133	18.7069	20.3842	22.7366	25.0475	27.1694	27.1694	
33.33	92.1421	114.3354	136.8800	161.9113	190.2466	225.0239	266.0706	306.0851	341.9312	13.0889	41.4082	67.8509	67.8509	
35.18	29.8452	30.7179	29.5451	27.2449	24.1947	20.3251	18.3397	19.0814	21.0743	23.7232	26.1438	28.1101	28.1101	
37.04	90.2313	113.5165	138.5709	164.5568	196.1048	230.2922	266.4393	306.0619	347.6337	5.1355	26.8516	49.1850	49.1850	
38.89	43.7292	30.1410	32.3712	27.9068	23.1937	23.3939	27.2599	34.8386	40.5233	43.2903	45.9831	46.1238	46.1238	
40.74	43.5261	102.3553	139.5650	171.5198	208.1351	248.3961	284.5951	310.8670	326.7548	347.1288	7.8484	32.9169	32.9169	
42.59	47.7511	45.8981	39.9193	34.2487	30.9706	31.6231	35.8531	40.2867	43.0494	44.7792	46.7223	47.1961	47.1961	
44.44	51.4451	49.3982	126.0048	166.3225	204.1300	238.4617	267.7123	289.2571	310.8600	334.9314	357.9631	37.3347	37.3347	
46.29	47.3631	47.7271	46.1813	43.7267	43.0449	41.3480	40.9791	42.3924	42.6332	43.8149	45.5705	46.3935	46.3935	
48.14	41.0381	70.8107	104.1061	141.5234	176.0860	209.0109	240.5930	267.7920	295.4653	322.5008	348.3860	14.1311	14.1311	
50.00	44.3471	44.4299	44.1783	42.7210	41.1710	39.6451	38.9101	39.0944	39.4565	40.7029	41.9855	43.1862	43.1862	
51.85	38.2863	67.0357	97.4673	132.5309	166.5817	199.6309	232.5516	262.0262	290.9577	319.0395	345.9387	11.4524	11.4524	
53.70	40.4933	40.7662	40.5900	39.8421	37.6328	36.1350	35.4345	35.0934	35.4555	36.7140	37.8652	39.1700	39.1700	
55.56	38.0974	68.2596	96.0790	129.1239	163.5459	198.9458	229.9658	261.0835	290.8629	319.0143	346.4571	12.3195	12.3195	
57.41	34.7274	35.1190	34.9954	33.9626	32.1415	30.4496	29.5338	29.2223	29.5757	30.7724	32.1345	33.4266	33.4266	
59.26	40.1923	67.4828	95.9495	127.0322	162.9781	194.3827	230.3771	263.4073	293.7062	322.2280	350.0475	15.1750	15.1750	
61.11	30.1809	30.4352	30.3078	29.4031	27.3718	25.5357	24.4843	24.2397	24.7240	26.0802	27.4364	28.7774	28.7774	
62.96	43.0541	49.5160	97.0648	127.8678	162.8317	197.5289	232.4144	267.1837	298.4638	326.8257	354.3822	19.1913	19.1913	

Figure C9. Wind speed and direction fields, Snapshot 8, Hurricane Gilbert (Continued)

Radius from Eye (km)		Azimuth (deg)												Speed Direction	
222-24	23.5373 49.9887	23.9216 74.0385	23.4923 99.7461	22.7057 129.2248	20.9727 163.1637	18.5328 200.5521	17.4319 239.7161	17.1813 276.7259	18.0937 310.2991	19.9530 339.9927	21.0256 4.5320	22.4507 27.8618	22.4507 27.8618		
333-34	16.9581 48.9523	17.2036 81.7746	16.7890 103.3250	15.8408 128.7525	13.5750 161.3663	11.1491 200.5323	9.5154 251.2171	9.9422 302.6403	11.5523 337.1957	13.3426 2.4439	14.8198 24.5127	16.1364 43.0938	16.1364 43.0938		
444-48	13.7151 70.4807	13.9239 26.9782	13.4677 105.0343	12.4010 124.6117	10.3856 152.8858	7.1188 189.1112	3.8607 256.1107	5.4365 336.0115	8.4707 6.2445	10.4728 25.0111	12.1181 40.6994	13.1301 55.5206	13.1301 55.5206		
666-72	10.9215 81.0203	10.9859 92.4768	10.4888 104.3052	9.5582 118.8781	7.8155 132.5356	5.2300 163.0829	2.6743 124.8143	3.8326 66.3909	6.4167 54.2370	8.5909 56.4723	9.7168 63.2981	10.4348 71.5852	10.4348 71.5852		
888-96	9.6053 87.1413	9.4694 94.5647	9.2892 102.4350	8.4931 110.4453	7.2487 117.6783	5.7794 119.2359	4.8126 108.9161	5.1559 49.7832	6.4914 76.7934	7.7483 75.9729	8.7204 75.8702	9.2908 86.7049	9.2908 86.7049		
1111-20	8.8596 91.1103	8.9670 93.7082	8.4481 101.0322	7.8904 106.9456	7.1972 110.0447	6.3312 139.8507	5.7749 103.9513	5.9170 94.0379	6.4945 85.7161	7.4878 82.3210	8.2297 82.8965	8.6403 86.1850	8.6403 86.1850		
1333-44	8.0003 0.0001	8.3413 94.8043	8.0934 100.6786	8.0000 8.0000	7.9586 106.5256	4.6526 105.3662	0.0100 0.0100	6.4437 95.4493	6.7644 90.1171	8.0000 0.0000	7.9612 87.1371	8.1287 90.8352	8.1287 90.8352		

Figure C9. (Concluded)

HOUR 16	0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.	Speed Direction
1-05	11.2437 104.4045	11.4761 119.8223	10.3044 134.7001	7.7846 155.9167	6.1747 178.8932	3.4501 206.5628	0.9100 330.6789	3.5643 8.4306	5.8231 36.9258	8.4842 61.2475	10.4973 71.1910	11.1527 86.3555	
3-70	17.4475 94.1117	17.3363 115.7196	14.3296 138.5485	14.4879 154.2100	12.6388 193.5205	10.8943 228.4838	9.8741 270.4590	9.9159 314.4968	11.3789 352.8335	13.3923 24.0531	15.2323 49.9509	16.8249 72.8209	
5-56	22.1714 91.8008	21.0421 115.0407	20.9523 139.1991	19.3236 166.0622	17.2950 195.6106	15.3376 228.7250	14.4109 265.7180	14.3302 304.0561	15.1922 341.0821	17.1555 14.1527	19.2034 42.9448	20.9901 68.2491	
7-41	25.3356 91.6391	25.3739 115.3001	24.3093 139.5770	22.4571 165.5271	20.4302 196.0433	18.3694 228.2915	17.3412 283.9150	17.0477 300.8007	17.7637 337.2375	19.5743 11.4333	21.8980 41.1243	23.9225 67.3070	
9-26	27.4713 91.7173	27.7923 114.9937	26.6912 139.3335	24.6330 155.7386	22.3212 195.0855	20.2280 227.8562	18.0524 263.2146	18.3377 299.7166	19.2863 336.6582	21.1628 10.7804	23.6358 40.7505	25.9655 67.3752	
11-11	29.1225 91.2803	29.5067 114.1235	28.4123 137.7406	26.1495 154.0796	23.4336 193.6250	21.0612 228.8195	18.8221 283.0509	18.3092 300.2320	20.2181 356.7486	22.2723 10.8201	24.9188 40.9584	27.4868 67.3522	
12-96	30.2406 90.3642	30.4234 112.6070	29.5192 135.7348	27.1356 161.8877	24.0444 191.6194	21.3686 229.7049	19.0398 263.2120	19.7099 301.2206	20.8690 337.5411	23.0692 11.0479	25.8349 40.7868	28.4076 66.8027	
14-02	30.9333 89.1661	31.1804 110.9763	30.0344 133.7117	27.6361 159.6336	24.3828 189.4433	21.3039 224.7087	19.0231 283.8184	19.0700 302.8944	21.3363 338.8593	23.7362 11.5846	26.4579 40.3805	28.9790 65.9983	
16-07	30.9363 88.0717	31.2995 109.6573	30.1248 132.0880	27.6749 157.6458	24.3093 187.4785	20.9099 223.7131	19.4928 264.7399	19.9176 304.6505	21.7478 340.6091	24.2775 11.9460	26.0784 39.8489	29.2075 65.1334	
18-52	30.4512 87.3869	31.0731 108.8247	29.8138 132.1787	27.3308 156.3051	24.0747 185.8688	20.4539 223.0573	18.9192 266.1380	19.0871 307.0577	22.1434 342.9109	24.8445 12.8890	27.1478 39.5189	29.1802 64.5458	
27-78	30.3617 89.1491	29.4271 112.2728	27.9424 134.8369	25.1378 158.9907	21.4311 188.3302	17.9488 229.2735	17.6144 279.9115	21.5914 322.4847	27.3583 351.8725	31.4220 14.2909	33.0307 36.9171	32.0244 52.3394	
37-04	37.1555 76.1352	32.8482 113.4935	29.8507 140.5225	25.9423 157.5576	21.2331 201.0117	18.2930 243.3482	21.3885 289.0120	29.0146 322.8142	35.4894 358.8859	39.8401 356.4950	42.5303 18.6785	41.7294 42.5907	
46-20	43.6332 57.5135	41.5019 92.9338	37.8923 130.2828	32.1996 155.1445	28.2942 202.1307	28.1906 237.9048	30.7384 271.4577	36.4357 296.0308	39.8717 316.1778	41.6286 310.0486	44.0064 2.2253	44.5509 27.7181	
55-56	45.2505 48.0145	44.4212 79.7833	41.4394 116.2359	38.2384 154.4880	34.1424 189.6841	35.5101 222.5149	36.7192 253.2397	38.8504 278.8506	40.1942 304.2949	41.6717 336.3460	43.3627 354.9935	44.2354 28.6167	
74-08	41.7476 42.5465	42.1196 71.8083	41.0181 103.8438	39.2676 139.1621	38.0387 175.6022	36.3744 206.3804	35.7723 238.5726	36.2801 268.0439	36.4486 296.6426	37.8418 324.1752	39.5037 350.5375	40.6804 16.2282	
92-60	37.2312 42.8775	37.4994 70.7075	36.9212 100.8417	35.9824 135.0267	33.7248 169.0215	32.1302 202.7459	31.4307 236.2374	31.3324 266.8992	31.8627 296.6611	33.1926 324.9866	34.5990 351.4562	35.9117 16.8457	
111-12	33.0546 44.3073	33.3790 71.4830	32.9237 100.7526	31.7381 133.6174	29.7350 168.0328	28.0482 202.6438	27.2413 236.9269	27.0360 268.8583	27.4501 299.4995	28.9668 327.9138	30.3893 354.3301	31.7591 19.4809	
138-90	28.1503 47.3702	28.5594 73.8682	28.1347 101.3118	26.9237 132.8400	24.8945 168.3913	22.9849 205.3250	22.0139 239.3107	21.9838 274.0621	22.4717 304.8939	24.0334 333.5317	25.4173 359.9588	26.9531 23.8199	
166-08	24.6793 50.8242	24.9877 75.9275	24.5544 102.4551	23.4583 132.5715	21.1613 168.0828	19.1854 204.6216	18.1680 242.5515	18.1680 279.5340	19.0297 311.5864	20.5807 339.4410	22.1071 5.3503	23.4964 28.4697	

Figure C10. Wind speed and direction fields, Snapshot 9, Hurricane Gilbert (Continued)

Azimuth (deg)													
Radius from Eye (km)	222.24	333.36	444.48	666.72	888.96	1111.20	1333.44	1555.68	1777.92	2000.16	2222.40	2444.64	2666.88
19.9563	20.3401	19.8652	18.7060	16.3930	14.0335	12.9329	13.1464	14.4707	16.1736	17.6736	19.1063	20.5795	22.0927
57.6511	79.9810	104.3972	132.9872	166.6655	206.9336	251.0312	291.6588	325.5376	352.6827	372.8827	393.1327	413.4327	433.6827
15.4283	15.6706	15.1135	14.0677	11.7996	8.9986	6.4978	7.0123	10.1337	12.0652	13.5989	14.7448	15.8907	17.0366
66.8263	86.0111	106.2282	130.5753	160.9316	199.9198	240.0677	320.2440	352.3451	372.8827	393.1327	413.4327	433.6827	453.9327
13.1323	13.3257	12.7491	11.6796	9.4835	6.3206	2.3434	4.4607	8.0136	10.1799	11.6222	12.5701	13.5180	14.4659
74.1125	89.7195	106.6535	127.0406	151.2855	182.4228	245.9173	354.3651	46.9315	58.9478	70.9641	82.9804	94.9967	107.0130
10.9338	10.9990	10.4790	9.9330	7.8200	5.3051	2.8101	3.6343	4.4186	4.9800	5.5414	6.1028	6.6642	7.2256
82.1863	93.6273	105.4309	119.0760	133.5331	144.1448	129.8587	72.3699	56.9673	41.5647	26.1621	10.7595	-4.6431	-20.0405
9.7377	9.8326	9.4422	8.6238	7.2931	5.6923	4.5190	3.0463	4.3119	7.7488	8.0481	8.4520	8.8559	9.2598
87.2261	95.2725	103.7868	112.7698	120.7816	123.3870	112.8123	90.9422	76.0686	72.8333	71.9080	70.1716	68.4352	66.6988
9.0854	9.1855	8.8507	8.0946	7.1897	6.1904	5.4127	5.4353	6.9006	7.4789	8.3627	9.2465	10.1303	11.0141
90.7325	96.2081	102.5408	109.3689	113.9631	113.9000	107.0344	94.7669	84.5543	80.7419	81.3892	82.0365	82.6838	83.3311
0.0003	0.4001	0.2771	0.0000	7.0213	6.4374	0.0300	6.1209	4.5714	0.0000	0.0732	0.3444	0.6156	0.8868
0.0003	97.2023	102.1143	0.0000	109.7446	108.9660	0.0300	96.2094	88.9286	0.0000	85.5795	88.7696	91.9598	95.1500

Figure C10. (Concluded)

Hour 18	Azimuth (deg)												Speed	Direction
	0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.		
1.05	5.0791	5.8132	5.7591	5.7244	5.7350	5.7720	5.8250	5.8780	5.9223	5.9468	5.9444	5.9488	5.9488	5.9488
	104.9431	105.1008	104.6491	103.6973	102.8408	102.0790	101.4304	101.4966	102.1501	102.8366	103.7437	104.5127	104.5127	104.5127
3.70	6.0381	5.8556	5.6875	5.6033	5.4993	5.4677	5.4239	5.3208	6.0137	6.0952	6.1677	6.1779	6.1779	6.1779
	107.2981	107.7648	107.0980	105.3896	103.4183	101.3451	100.3555	100.4585	101.0648	102.4782	104.1249	105.9810	105.9810	105.9810
5.56	6.6052	6.2755	5.8403	5.4957	5.2514	5.2809	5.3704	5.4918	5.9782	6.3115	6.4404	6.4839	6.4839	6.4839
	109.3692	112.4100	113.8568	111.2792	108.6787	106.0910	100.2331	98.5569	97.6445	99.6729	101.8282	103.3813	103.3813	103.3813
7.41	8.1022	7.5052	6.7850	5.8232	4.8090	4.0650	3.9326	4.6831	5.6382	6.4329	7.5069	8.1191	8.1191	8.1191
	108.7145	117.0380	124.8834	128.6930	125.8730	116.1497	102.1179	91.8850	86.4838	87.8724	93.8237	100.7331	100.7331	100.7331
9.26	10.3151	9.8030	9.0202	7.4588	5.1709	2.8432	0.9344	3.0886	5.4814	7.4819	9.2482	10.1204	10.1204	10.1204
	105.0439	119.8408	134.0363	148.4417	160.4423	166.1032	108.8175	56.7296	58.3870	67.3143	79.8284	91.5931	91.5931	91.5931
11.11	12.8761	12.5065	11.6449	10.1405	7.8619	5.0321	2.3729	4.1879	7.2315	9.7813	11.5306	12.6221	12.6221	12.6221
	101.4369	120.0983	139.7015	150.4014	186.9847	217.7013	277.3177	353.9601	26.7457	47.6170	65.9497	83.5906	83.5906	83.5906
12.96	15.6671	15.4080	14.5311	13.0903	11.1054	8.8946	6.9754	7.6180	9.9707	12.2262	14.1034	15.2993	15.2993	15.2993
	98.6277	119.9411	142.3654	166.3339	193.9777	229.0841	276.8531	329.7876	7.5710	34.4939	56.9631	77.8704	77.8704	77.8704
14.02	18.0273	18.5335	17.6727	16.1361	14.1814	11.9965	10.4945	10.7774	12.5248	14.7444	16.8134	18.1619	18.1619	18.1619
	96.8716	119.8137	143.2739	168.6852	197.0950	230.8480	273.6293	319.2888	357.2303	26.5178	51.1506	76.1466	76.1466	76.1466
16.47	21.6328	21.7028	20.8465	19.2467	17.1703	14.4755	13.1134	13.4073	14.0966	17.2490	19.5127	21.0034	21.0034	21.0034
	95.6203	119.9404	143.3201	169.1813	197.4088	230.5326	271.3125	314.0730	351.4125	21.6671	47.7105	71.7587	71.7587	71.7587
18.32	24.6101	24.8284	23.9246	22.1237	19.8816	17.0101	15.2121	15.5523	17.1371	19.7091	22.1439	23.8249	23.8249	23.8249
	94.2873	118.8821	142.5574	168.2451	195.3827	229.3966	269.6173	310.9637	348.0617	18.8115	45.5671	69.9339	69.9339	69.9339
27.78	35.5229	34.8410	32.9125	30.1479	26.6152	23.1143	21.6590	23.1340	26.7359	30.7052	33.6706	34.9819	34.9819	34.9819
	85.5987	109.4278	135.0929	162.8338	192.8734	228.5039	270.0502	310.5603	344.5595	12.5334	37.2657	61.2740	61.2740	61.2740
37.04	39.3955	37.7291	34.9978	31.4366	28.3359	25.4674	23.7373	29.8866	36.3245	40.4115	40.8783	40.4728	40.4728	40.4728
	77.3821	103.4535	130.2106	160.2451	193.7711	232.4356	274.7835	311.8036	338.5124	2.1760	25.5867	50.4834	50.4834	50.4834
46.30	40.9423	38.2838	34.9545	31.4493	28.3984	27.0173	29.2189	34.1790	37.0622	40.6875	42.5411	42.6448	42.6448	42.6448
	70.4902	99.7451	128.8806	160.7803	196.4046	236.4919	275.4391	308.8399	329.1547	352.8350	15.1207	41.1693	41.1693	41.1693
55.56	41.7935	39.0205	35.0911	31.3828	28.7308	28.4614	31.8745	35.6987	38.5344	40.8439	42.3466	42.8135	42.8135	42.8135
	64.9161	96.4681	128.4886	162.2876	199.1399	238.6906	273.2134	299.1044	322.4314	345.9880	8.7131	36.8333	36.8333	36.8333
.00	41.0643	40.1197	36.2898	32.2104	30.3981	30.8071	32.9192	35.1327	36.8094	38.3970	40.2096	40.9671	40.9671	40.9671
	55.4141	87.4422	122.7576	160.1244	198.9355	233.5396	263.1399	288.0832	313.5711	338.4441	2.2220	27.4732	27.4732	27.4732
72.40	39.5187	39.0413	36.7864	33.5399	31.4988	31.2726	31.9172	33.3089	34.6699	36.1376	37.7737	38.7348	38.7348	38.7348
	50.4289	80.3435	114.2804	151.9942	188.9102	222.8338	254.2591	281.6341	308.0616	334.3213	358.6581	37.6885	37.6885	37.6885
111.12	37.7723	37.6338	36.1361	33.9693	32.0884	30.8058	30.9348	31.7090	32.7453	34.1408	35.7021	36.7882	36.7882	36.7882
	47.5269	76.4333	108.5887	144.7563	180.4136	215.0646	247.7752	276.7665	304.6755	331.5495	356.6666	25.7737	25.7737	25.7737
138.90	34.7661	34.9129	34.0209	32.4345	30.5914	28.9448	28.3886	28.9649	29.7139	30.9772	32.6234	33.4645	33.4645	33.4645
	46.0253	74.1238	103.8252	137.7684	175.6272	208.1007	242.3351	273.6733	302.5104	330.1435	356.1758	28.8916	28.8916	28.8916
166.68	31.8693	32.0541	31.3974	30.0672	28.2889	26.3365	25.5569	26.0123	26.6729	27.9706	29.5903	30.7129	30.7129	30.7129
	46.3329	73.3764	102.1377	134.6385	169.9289	205.0914	240.6537	272.9854	303.0412	331.0713	357.0790	21.8364	21.8364	21.8364

Figure C11. Wind speed and direction fields, Snapshot 10, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)										Speed Direction		
	222.24	26.7972 49.3817	27.0216 74.0211	28.5406 101.9207	28.4717 132.7341	23.3408 167.1542	21.4316 203.0656	20.0179 241.5149	20.2820 274.2262	21.3313 306.1366	22.9452 336.5665	24.4360 2.0208	25.7370 26.1352
333.36		20.2895 56.7751	20.4624 79.8549	19.9481 103.7922	18.9608 131.3417	16.7294 165.2771	16.5110 203.4128	13.3233 247.3558	13.3209 298.5602	14.7728 323.8227	16.4545 351.0950	17.9853 15.2997	19.3449 36.3604
444.48		16.3593 44.6461	16.5361 84.2943	16.0459 105.5963	14.9928 130.5963	12.8784 161.1408	10.3397 200.8354	8.4210 254.0887	9.0545 308.3550	11.0708 343.9234	13.0173 373.3664	14.4581 28.4901	15.7404 46.7683
464.72		12.6181 73.7863	12.7216 96.8558	12.1337 106.5348	11.1029 125.2475	9.1712 147.4763	8.0215 174.2474	1.7335 219.7147	3.6621 10.1466	7.4212 26.4106	9.7208 38.4016	11.2113 50.2214	12.0492 62.0601
800.96		10.7021 83.2691	10.8083 93.8443	10.2993 105.2178	9.3324 117.9364	7.4988 131.2879	5.2976 146.2654	3.1928 125.5141	3.7751 76.8229	6.3481 60.2250	8.3548 46.9334	9.5751 65.9497	10.2830 73.8207
1111.20		9.6051 88.4593	9.7236 95.6541	9.2984 103.7698	8.3599 113.8098	7.2471 119.6926	5.7635 121.7317	4.0719 111.5864	4.9803 91.2768	6.3158 77.4573	7.4736 74.0587	8.7938 75.9633	9.3019 81.2768
1333.44		8.0003 0.0003	8.9638 96.9843	8.5628 103.1059	8.0604 0.0004	7.0117 113.2149	4.1409 112.7698	0.0208 0.0208	5.7575 95.1015	6.3997 85.5864	0.0000 0.0000	8.2841 82.4577	8.4648 84.5409

Figure C11. (Concluded)

Hour	20	0	30	60	90	120	150	180	210	240	270	300	330
Azimuth (deg)													
Radius from Eye (km)													
													Speed Direction
1.85	5.9295	5.8023	5.8475	5.8352	5.8551	5.8926	5.9312	5.9747	6.0085	6.0085	6.0081	6.0052	5.9767
	103.3085	103.3145	102.8789	102.1129	101.4148	100.8360	100.5314	100.4673	101.0966	101.6880	101.6880	102.4317	103.0237
3.70	5.9813	5.8669	5.7664	5.7345	5.7774	5.8698	5.9524	6.0304	6.0758	6.1027	6.1130	6.1130	6.0821
	105.1183	105.2324	104.3956	102.8508	101.3052	100.0011	99.4194	99.6777	100.4034	101.6783	103.0752	104.4048	104.4048
5.56	6.1033	5.9303	5.7101	5.4101	5.6446	5.7917	5.9055	6.0720	6.1100	6.2274	6.3304	6.3446	6.3446
	107.4967	108.1465	107.1981	104.8389	102.3313	99.8342	98.5782	98.8351	99.7337	101.4827	103.4341	105.6725	105.6725
7.41	6.7645	6.2669	5.7929	5.2781	5.3647	5.4262	5.7160	5.9119	6.1369	6.4120	6.7301	6.9339	6.9339
	109.5193	112.2300	113.2055	111.5366	107.0325	101.8920	98.8176	97.9039	97.2748	98.7748	101.7471	105.5405	105.5405
9.26	8.2394	7.4281	6.4725	5.7277	4.6736	4.1552	4.0364	4.9663	5.7371	6.7563	7.6339	8.2045	8.2045
	109.0837	117.8212	124.7192	129.6361	124.8139	114.7697	100.7397	92.4308	87.6821	87.7368	94.8423	101.8705	101.8705
11.11	10.3923	9.7639	8.9160	7.3604	5.1277	2.6882	0.9107	3.1597	5.7189	7.4680	9.4140	10.3230	10.3230
	106.0663	126.4708	136.2229	151.2572	144.2407	171.8979	105.3585	58.1291	59.4342	68.3347	80.4002	92.4021	92.4021
12.94	12.9992	12.5085	11.4842	10.3057	8.2092	5.2037	2.9332	4.1178	7.4684	10.0225	11.7933	12.0035	12.0035
	102.9033	121.9654	142.5287	164.0940	189.1190	221.4341	278.4344	357.8077	29.5849	49.3927	67.4063	84.9384	84.9384
14.82	15.9861	15.4682	14.9280	13.6134	11.7990	9.3829	7.0365	7.5289	10.2768	12.4714	14.4086	15.0058	15.0058
	100.1197	122.1844	143.0974	159.6170	196.5877	229.8189	277.3311	333.6061	11.1384	36.4484	58.4430	79.0065	79.0065
16.67	19.2397	19.2051	18.5487	17.1984	15.1895	12.4795	10.4149	10.4005	13.0013	15.4478	17.7275	19.0104	19.0104
	98.1197	121.9331	149.4885	176.6803	198.0125	230.6691	274.5108	323.7882	1.6885	28.7682	52.4490	75.1802	75.1802
18.52	22.7203	22.0847	22.2024	20.6210	18.3616	15.0651	12.8013	13.3014	15.9718	18.9824	21.0070	22.3282	22.3282
	96.4337	121.2744	144.4894	169.9468	197.4510	229.9230	273.2328	319.6204	356.4006	23.9624	49.0842	72.3806	72.3806
20.37	25.7237	24.5800	22.6709	20.9005	24.1567	22.3295	21.4734	25.3418	31.3325	36.2174	38.1519	37.2988	37.2988
	87.6463	112.8603	136.1398	165.4177	195.4956	232.7752	277.7592	318.3313	347.0461	10.5687	33.9874	59.7553	59.7553
22.22	34.5233	34.9358	35.5777	32.1298	28.0965	27.0051	29.3277	36.4434	43.1668	44.4955	66.7200	66.0016	66.0016
	74.4131	107.4924	135.9530	156.2190	200.6117	239.9180	280.7308	311.2616	332.4404	333.0004	16.1769	42.6703	42.6703
24.07	45.5145	42.1673	37.5512	33.7562	31.3806	31.7408	35.1169	39.8362	42.5312	44.4370	46.3333	46.0355	46.0355
	62.9481	97.9804	133.7669	157.7660	204.1537	240.3868	272.9382	297.5981	319.7323	343.5621	6.2604	32.3419	32.3419
25.92	46.0265	44.3377	39.7135	35.9740	34.2357	34.9786	37.6324	39.7897	41.5712	43.2627	44.9356	45.4601	45.4601
	55.4423	88.5973	127.3518	155.7619	201.0400	235.0846	263.6134	288.0840	312.5301	337.4359	1.1779	26.9303	26.9303
27.77	43.4191	43.4944	41.3370	38.4435	37.4037	36.3556	36.4392	37.4987	38.4542	39.7370	41.4074	42.4629	42.4629
	48.0403	77.9856	112.0982	150.3156	185.6884	218.4609	249.3781	276.9474	304.1015	330.7860	355.9180	21.3843	21.3843
29.62	40.3345	40.4022	39.4321	37.5403	35.8956	34.4016	33.9322	34.4175	35.1165	36.4832	37.9006	39.1451	39.1451
	45.4591	76.0640	109.1505	146.8722	175.3963	209.1969	242.3394	271.6305	300.3736	328.1291	354.0091	19.3104	19.3104
31.47	37.0892	37.2325	36.4285	35.2348	33.3321	31.6708	31.0519	31.1381	31.7049	33.1351	34.5634	35.0873	35.0873
	44.0891	72.7627	102.4368	136.2499	171.0314	209.3954	239.1719	270.1206	299.8629	327.8306	354.2627	19.5995	19.5995
33.32	32.3885	32.7023	32.2608	31.0260	29.0486	27.2302	26.3302	26.4103	27.0126	28.3199	29.0996	31.1494	31.1494
	46.2781	73.3987	101.4861	133.4826	169.0282	203.3277	238.4230	271.7739	301.9199	330.3402	357.2231	21.7717	21.7717
35.17	28.5431	28.8026	28.4113	27.3210	25.1778	23.1919	22.2396	22.2691	22.9669	24.4164	25.9638	27.2816	27.2816
	48.6261	74.6354	101.9119	132.4059	167.0355	203.3952	239.7352	274.7785	308.0943	334.4221	0.9902	25.2034	25.2034

Figure C12. Wind speed and direction fields, Snapshot 11, Hurricane Gilbert (Continued)

Radius from Eye (km)	Azimuth (deg)												Speed Direction	
	222.24	22.7164	23.1301	22.7239	21.0340	19.3465	17.1805	16.0938	16.0998	17.2384	18.0421	20.3454	21.7985	33.0207
333.34	54.7832	103.7114	132.0044	166.7420	205.0479	245.0349	283.7704	317.3061	345.6508	365.6508	10.2331	14.6668	15.9346	47.4930
	16.0134	16.9134	16.3922	15.3021	13.0946	10.5121	8.7331	9.4515	11.2719	12.1598	13.1598	14.6668	15.9346	47.4930
444.48	65.0165	85.3609	106.4154	131.4219	163.2602	202.4668	256.2711	310.2054	364.0362	41.3469	29.5469	20.5469	47.4930	47.4930
	13.5337	13.7260	13.1828	12.0916	10.0621	6.6926	3.0949	5.0780	8.5471	10.5809	12.0211	12.9492	13.9492	59.7847
666.72	74.4161	90.3011	107.7544	126.5662	153.7168	187.7993	256.2804	344.8997	43.8027	30.9929	45.4130	59.7847	59.7847	59.7847
	10.7043	10.7060	10.2110	9.3165	7.6233	5.2998	3.1588	4.1276	6.4523	8.5064	9.5773	10.2320	10.2320	10.2320
888.96	85.1103	95.4938	104.5426	119.0615	131.5566	139.3376	121.0301	76.5244	62.2259	42.9819	48.7338	76.2879	76.2879	76.2879
	9.3461	9.3019	9.0390	8.2077	7.2128	5.9841	5.2125	5.5101	6.4458	7.7315	8.5796	9.1143	9.1143	9.1143
1111.20	91.1683	97.8937	104.3600	111.1915	116.6356	117.1069	108.6331	94.1247	82.9930	60.0907	41.4591	85.5395	85.5395	85.5395
	8.5903	8.6799	8.3925	7.7497	7.2106	6.5444	6.1193	6.2768	6.0785	7.5224	8.1249	8.4628	8.4628	8.4628
1333.44	94.4785	98.4139	102.7198	107.0723	109.5379	109.0395	104.4529	97.2281	90.8282	88.0055	88.2513	90.6072	90.6072	90.6072
	0.0202	0.0241	7.9979	0.0000	7.0902	6.8435	6.0360	6.6947	6.9374	8.0000	7.8939	7.9547	7.9547	7.9547
	0.0003	98.8749	101.8310	0.0000	105.9607	105.2798	0.0360	98.2644	94.2211	0.0000	92.0829	93.7653	93.7653	93.7653

Figure C12. (Concluded)

HOUR	22	Azimuth (deg)												Speed	Direction
		0.	30.	60.	90.	120.	150.	180.	210.	240.	270.	300.	330.		
1.85		5.8483	5.7804	5.6997	5.6099	5.5222	5.4040	5.2662	5.1202	5.9370	5.9738	6.0087	5.9708		
		106.5002	106.7510	106.2191	105.8235	103.3704	102.9887	102.3549	102.3888	102.9132	103.7604	104.9363	105.9163		
3.70		6.1945	5.9179	5.6022	5.4067	5.3474	5.4097	5.6592	5.8390	6.0445	6.2373	6.4174	6.4387		
		109.7323	110.9312	111.0330	108.2792	105.8942	102.6610	100.7512	100.2132	99.9980	102.2222	104.2408	107.3445		
5.56		7.5137	7.0323	6.3394	5.3752	4.3785	4.0591	4.4517	5.0094	5.8804	6.7344	7.4481	7.8156		
		111.6123	117.9845	125.1789	115.0418	122.0035	111.9417	99.8513	91.7266	88.0898	91.8978	96.2967	103.8074		
7.41		10.1193	9.5243	8.7733	7.3614	4.8045	2.4381	1.1314	3.4569	9.9378	7.9428	9.2984	10.0938		
		107.1556	121.7911	137.0622	130.7317	161.4687	165.5040	92.4304	57.9183	59.2401	68.4480	81.1289	93.7938		
9.26		13.3121	12.9320	12.2267	10.7793	8.6743	5.6443	3.5515	5.1242	8.1397	10.5079	12.1309	13.0631		
		102.8131	122.9756	142.8235	164.3818	190.3141	223.8259	283.8187	352.6953	23.0819	44.9584	65.1506	83.6623		
11.11		16.9411	16.8812	16.2157	16.7052	12.8338	10.2925	6.6545	9.4347	11.5406	13.4147	15.3609	16.4849		
		99.6387	122.2555	145.0753	169.1489	197.1801	231.8822	278.4590	327.1765	3.0855	30.7740	54.5714	77.3848		
12.96		20.7713	21.0445	20.4157	18.8188	16.4285	13.8330	12.3474	12.8624	14.4487	16.0082	18.4859	19.9888		
		98.6183	121.6941	143.2875	170.8977	198.8711	232.3898	274.5118	317.7514	353.6818	22.8793	49.8096	73.9633		
14.82		24.5263	25.1146	24.3814	22.5829	19.8353	16.8137	15.2182	15.7096	17.5922	19.8480	21.9935	23.3874		
		96.7485	120.6180	144.0745	169.4434	197.3929	231.2148	272.2394	313.3688	348.8700	18.9224	44.0263	71.7837		
16.67		27.9951	28.7738	27.7404	25.4301	22.5747	19.1495	17.4714	18.1192	20.1729	22.4708	24.9212	26.5949		
		95.1472	118.8140	142.0742	167.7234	196.6692	230.1030	271.0515	311.4927	348.7114	16.8353	44.1903	69.9429		
18.52		30.8923	31.7702	30.3424	27.7474	24.3794	20.7928	19.0538	20.1122	22.5434	25.3486	27.7873	29.5115		
		92.8013	116.4018	139.5762	155.4955	194.5629	229.1581	270.7348	311.1021	345.9366	19.5027	42.7749	67.9633		
27.78		37.8815	36.5787	34.4244	31.2648	27.3926	23.8345	23.8559	27.7243	32.8432	37.0634	38.9985	38.8035		
		82.9513	107.4056	132.8460	160.9985	192.9456	232.6450	277.0210	315.2740	344.0299	8.1449	31.4698	56.6615		
37.04		40.6303	37.3980	34.2299	30.6971	27.3187	25.4207	28.1365	34.3422	38.5401	41.4440	43.4304	43.2483		
		73.7816	105.0182	132.7246	153.8099	198.5433	240.1823	281.5569	312.0752	335.8204	355.1287	17.4479	43.5732		
46.30		42.3715	39.0784	34.4518	30.7874	27.9401	28.2714	31.8493	36.3364	39.1003	41.1692	42.9431	43.9302		
		64.4125	98.4601	132.8245	166.2447	203.7569	242.4842	274.3882	301.1424	322.9312	344.0280	8.5963	34.2627		
55.56		42.7425	41.0297	36.3285	32.2254	30.0780	30.8943	33.9232	36.2371	38.2261	39.9984	41.4496	42.4561		
		57.1113	89.9770	128.8894	164.3621	203.4987	238.7636	267.7222	291.6883	315.5853	339.9640	3.3877	28.7798		
74.08		40.5302	40.6599	38.4459	35.2583	34.0633	33.0826	33.3345	34.6161	35.4317	36.7987	38.4883	39.5999		
		49.1895	78.7955	112.8468	151.3618	187.4140	228.5939	251.5391	279.0654	304.1276	332.7593	357.5262	22.7743		
92.60		37.4485	37.7455	36.7335	34.7117	33.8518	31.5190	31.0137	31.5434	32.2354	33.4708	35.2294	36.4388		
		46.6213	74.8456	109.7711	141.5890	178.4216	210.4728	244.0718	273.4344	302.3351	330.1503	355.8884	26.7702		
111.12		34.5017	34.7113	34.0656	32.4936	30.4348	28.9383	28.2338	28.3774	29.0911	30.4404	31.9442	33.2273		
		46.2445	73.7865	103.3428	136.9694	171.8761	206.7871	240.9147	272.1779	302.1337	330.1787	356.2342	21.3897		
138.90		30.8537	30.4096	29.9345	28.4459	26.5958	24.7179	23.8162	23.9803	24.5860	25.9384	27.5578	28.8423		
		47.9149	74.5528	102.2921	134.1456	169.3535	204.7141	240.5173	275.3487	304.7552	333.2265	359.7835	23.8438		
146.68		26.5042	26.7982	26.3680	25.2636	23.9158	20.9518	19.9141	20.0596	20.8546	22.3884	23.9371	25.2852		
		50.4445	75.9031	102.7452	133.1483	168.5574	204.7376	242.8893	277.9359	309.5143	337.7746	3.8764	27.5431		

Figure C13. Wind speed and direction fields, Snapshot 12, Hurricane Gilbert (Continued)

Azimuth (deg)													
												Speed	Direction
222.24	21.2642	21.6436	21.2031	20.0824	17.7597	15.4786	14.3324	14.4726	15.7128	17.3848	18.9852	20.3482	
	56.7867	79.6663	104.4285	133.1846	166.8934	216.1586	248.8941	288.1352	321.9060	349.7544	13.6237	35.6282	
333.36	15.8521	16.0818	15.5516	14.5325	12.2543	9.5346	7.2102	8.3949	10.5082	12.4397	13.9458	15.1384	
	66.8981	86.4163	106.7736	131.0914	161.8358	206.9201	258.7548	317.1211	350.0761	13.0018	33.1369	50.0834	
444.48	13.0764	13.2374	12.7148	11.4307	9.6498	6.2261	2.2184	4.5313	8.0867	10.2010	11.6192	12.5173	
	75.7188	91.0077	107.6061	127.4948	151.4050	182.4662	247.9109	357.1548	19.9131	35.1326	48.4571	61.7384	
555.60	10.5345	10.5369	10.0407	9.1900	7.5597	5.3746	3.4547	4.2286	6.5564	8.3439	9.4281	10.0925	
	85.6181	95.7673	106.1711	118.0792	129.6998	136.4057	120.4382	80.5949	65.2061	64.9329	70.0051	77.1232	
666.72	9.3353	9.3324	8.9984	8.2584	7.2139	6.0248	5.2723	5.5444	6.6171	7.6791	8.5196	9.0636	
	91.1825	97.4677	104.1113	110.7762	116.0412	116.4920	108.4991	94.6153	83.6558	80.5457	81.7418	95.6730	
777.84	8.5432	8.6750	8.3883	7.7470	7.2993	6.5425	6.1128	6.2589	6.8518	7.4971	8.1059	8.4599	
	94.5825	98.2470	102.5881	106.9674	109.4575	139.8239	184.4554	97.2536	90.7928	87.8282	88.8696	90.4778	
888.96	8.0887	8.1000	7.9880	0.0880	7.0822	6.8234	0.0380	6.4594	6.9270	0.0000	7.8881	7.9624	
	0.0003	98.7140	101.7478	0.0000	104.0465	105.3944	0.0380	98.1342	93.9849	0.0000	91.7188	93.4368	
999.96													

Radius from Eye (km)

Figure C13. (Concluded)

```

$ ASSIGN GIL8.WIND21 FOR020
$ ASSIGN GIL8.WIND18 FOR018
$ RUN AZIM_AVER

```

		--- Wind Speed ---		Inflow Angle,
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)
WIND, HOUR		20	0	
1.	1.852	5.9405	0.0583	242.9772
2.	3.704	5.9437	0.1176	243.5015
3.	5.556	5.9498	0.1792	244.4844
4.	7.408	5.9595	0.2443	245.8895
5.	9.260	5.9755	0.3159	248.0143
6.	11.112	5.0049	0.4017	251.6257
7.	12.964	5.0747	0.5263	259.0292
8.	14.816	5.2682	0.7831	-85.1015
9.	16.668	5.7908	1.4971	-61.3046
10.	18.520	7.3736	3.2177	-39.8814
15.	27.780	25.7127	25.8542	0.0638
20.	37.040	39.1360	37.0043	14.4071
25.	46.300	39.8450	38.6980	21.4880
30.	55.560	39.2075	38.2327	26.3593
40.	74.080	35.9664	36.4542	35.2711
50.	92.600	34.7457	34.4134	40.8962
60.	111.120	32.1222	31.8455	43.3617
75.	138.900	27.6395	27.3607	43.5430
90.	166.680	23.5362	23.2120	41.9649
120.	222.240	17.3512	16.8293	36.0960
180.	333.360	12.8521	9.6021	23.6111
240.	444.480	7.9560	5.4558	15.0186
360.	666.720	7.4514	1.7981	10.4387
480.	888.960	7.4233	0.6930	11.4414
600.	1111.200	7.4100	0.3141	6.7318
720.	1333.440	4.9126	0.1089	-12.1050
WIND, HOUR		20	1	
1.	1.852	5.9644	0.0565	240.5800
2.	3.704	5.9677	0.1138	241.0424
3.	5.556	5.9738	0.1730	241.9138
4.	7.408	5.9834	0.2350	243.1496
5.	9.260	5.9985	0.3022	245.0328
6.	11.112	5.0250	0.3803	248.1936
7.	12.964	5.0830	0.4864	254.5270
8.	14.816	5.2368	0.6847	268.6367
9.	16.668	5.6499	1.2092	-68.0856
10.	18.520	7.5427	2.5093	-45.4020
15.	27.780	23.5379	22.5697	-2.4338
20.	37.040	33.3208	37.1779	14.3794
25.	46.300	42.0500	41.0345	23.7352
30.	55.560	41.5028	40.6994	29.0430
40.	74.080	37.9929	37.5078	35.4472
50.	92.600	34.9229	34.5727	39.4681
60.	111.120	32.1931	31.8974	41.7054
75.	138.900	23.1118	27.8268	42.5412
90.	166.680	24.3038	23.9868	41.6276
120.	222.240	13.2532	17.7728	36.8113
180.	333.360	11.5444	10.4276	25.1562
240.	444.480	3.2821	6.0906	16.3304
360.	666.720	7.4668	2.0921	10.6132
480.	888.960	7.4237	0.8189	11.3544
600.	1111.200	7.4093	0.3746	7.6189
720.	1333.440	4.9128	0.1289	-8.0053

Snapshot 1

Interpolation between
Snapshots 1 & 2

Figure C14. Azimuthally averaged speed and inflow angle, Hurricane Gilbert (Sheet 1 of 12)

		--- Wind Speed ---		Inflow Angle,
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)
WIND, HOUR		20	2	
1.	1.852	5.9885	0.0548	238.0248
2.	3.704	5.9919	0.1102	238.4156
3.	5.556	5.9982	0.1672	239.1560
4.	7.408	5.0076	0.2264	240.1999
5.	9.260	5.0220	0.2895	241.7754
6.	11.112	5.0457	0.3604	244.3654
7.	12.964	5.0921	0.4500	249.2603
8.	14.816	5.2074	0.5968	260.4110
9.	16.668	5.5173	0.9457	-78.7729
10.	18.520	7.2460	1.8151	-55.4724
15.	27.780	20.4553	19.1466	-5.2852
20.	37.040	33.5064	37.3467	14.3384
25.	46.300	44.2971	43.3895	25.7404
30.	55.560	43.8676	43.1995	31.4260
40.	74.080	39.0180	38.5573	35.6167
50.	92.600	35.1224	34.7513	38.0579
60.	111.120	32.2916	31.9735	40.0499
75.	138.900	23.5935	28.3006	41.5780
90.	166.680	25.0731	24.7614	41.3158
120.	222.240	19.1630	18.7172	37.4373
180.	333.360	12.2446	11.2392	26.5320
240.	444.480	3.6870	6.7227	17.4240
360.	666.720	7.4862	2.3823	10.7159
480.	888.960	7.4253	0.9447	11.2861
600.	1111.200	7.4090	0.4350	8.2587
720.	1333.440	4.9130	0.1493	-5.0173
WIND, HOUR		20	3	
1.	1.852	5.8402	0.7731	-75.1767
2.	3.704	5.4599	3.0543	-50.1969
3.	5.556	3.9973	8.7711	-22.2437
4.	7.408	17.1276	16.4325	-8.7850
5.	9.260	23.7617	23.2580	-1.7680
6.	11.112	27.9470	27.5536	2.6972
7.	12.964	29.9794	29.6319	6.0785
8.	14.816	30.5931	30.2645	8.6527
9.	16.668	30.4137	30.1121	10.4360
10.	18.520	29.9044	29.6449	11.3989
15.	27.780	33.3389	32.9973	10.4108
20.	37.040	33.8700	38.9509	15.7391
25.	46.300	40.8779	39.9576	22.2504
30.	55.560	39.5400	36.7501	26.6865
40.	74.080	35.3129	35.8119	33.3749
50.	92.600	33.4908	33.1396	37.8682
60.	111.120	30.9005	30.6016	40.2691
75.	138.900	27.0636	26.7709	41.2536
90.	166.680	23.5050	23.1748	40.4313
120.	222.240	17.8497	17.3439	35.7290
180.	333.360	11.4874	10.3226	24.5473
240.	444.480	3.3587	6.1182	16.4950
360.	666.720	7.5436	2.1977	11.5892
480.	888.960	7.4797	0.9074	12.1303
600.	1111.200	7.4515	0.4313	9.1300
720.	1333.440	4.9283	0.1473	-3.2691

Snapshot 2

Interpolation between
Snapshots 2 & 3

Figure C14. (Sheet 2 of 12)

--- Wind Speed ---					Inflow Angle,
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	4		
1.	1.852	5.8323	1.5088	-73.7257	Snapshot 3
2.	3.704	7.6811	5.8655	-48.3018	
3.	5.556	17.0601	16.3827	-18.8441	
4.	7.408	31.1340	30.6660	-5.6326	
5.	9.260	44.1059	43.7016	1.0484	
6.	11.112	52.0694	51.6435	5.5470	
7.	12.964	55.7219	55.1891	8.9149	
8.	14.816	55.9171	56.2661	11.6026	
9.	16.668	55.6530	55.9352	13.6930	
10.	18.520	55.4595	54.7346	15.2657	
15.	27.780	47.2739	46.6246	17.3370	
20.	37.040	41.2928	40.5148	17.0706	
25.	46.300	37.5578	36.6132	18.1008	
30.	55.560	35.4703	34.4779	20.7272	
40.	74.080	33.6395	33.0831	30.7598	
50.	92.600	31.8519	31.5189	37.6681	
60.	111.120	29.5078	29.2248	40.5194	
75.	138.900	25.5316	25.2342	40.8956	
90.	166.680	21.9416	21.5849	39.4102	
120.	222.240	15.5657	15.9818	33.7018	
180.	333.360	11.7602	9.3951	22.2754	
240.	444.480	3.1825	5.5112	15.3905	
360.	666.720	7.6131	2.0124	12.5970	
480.	888.960	7.5401	0.8702	13.0439	
600.	1111.200	7.4989	0.4276	10.0139	
720.	1333.440	4.9463	0.1454	-1.4962	
WIND, HOUR		20	5		
1.	1.852	5.2252	2.7628	-65.8165	Interpolation between Snapshots 3 & 4
2.	3.704	11.8849	9.7729	-34.6276	
3.	5.556	23.9177	23.3696	-10.5852	
4.	7.408	38.7603	38.3208	-0.9444	
5.	9.260	49.6471	49.2128	4.1015	
6.	11.112	55.1260	54.6246	7.4212	
7.	12.964	57.2447	56.6338	9.9296	
8.	14.816	57.5303	56.8154	11.9629	
9.	16.668	55.7618	55.9895	13.5702	
10.	18.520	55.3013	54.5162	14.8087	
15.	27.780	47.1459	46.3588	16.6690	
20.	37.040	41.7828	40.8349	17.7450	
25.	46.300	38.5645	37.6181	21.1510	
30.	55.560	35.6946	35.9205	25.7857	
40.	74.080	34.4778	34.0738	35.2891	
50.	92.600	31.8423	31.5568	40.0867	
60.	111.120	23.8347	28.5661	41.5009	
75.	138.900	24.3943	24.0850	40.6594	
90.	166.680	21.6857	20.2947	38.4191	
120.	222.240	15.4411	14.7694	31.7297	
180.	333.360	11.0126	8.4136	20.0608	
240.	444.480	3.0213	4.8038	13.9795	
360.	666.720	7.6176	1.7291	12.1352	
480.	888.960	7.5582	0.7501	12.4990	
600.	1111.200	7.5163	0.3689	9.0158	
720.	1333.440	4.9548	0.1238	-3.6095	

Figure C14. (Sheet 3 of 12)

		--- Wind Speed ---		Inflow Angle,	
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	6		
1.	1.852	5.7256	3.9907	-62.4913	Snapshot 4
2.	3.704	14.5032	13.6544	-28.3991	
3.	5.556	31.8972	30.3899	-6.2408	
4.	7.408	45.3251	45.8593	2.2482	
5.	9.260	54.9773	54.4563	6.4809	
6.	11.112	58.0636	57.4492	9.0340	
7.	12.964	53.7361	58.0230	10.8773	
8.	14.816	53.1499	57.3589	12.3154	
9.	16.668	55.8714	56.0365	13.4475	
10.	18.520	55.1522	54.2988	14.3488	
15.	27.780	47.0437	46.0940	15.9946	
20.	37.040	42.3020	41.1548	18.4114	
25.	46.300	39.6646	38.7001	24.0330	
30.	55.560	33.1960	37.5633	30.4291	
40.	74.080	35.5348	35.2260	39.5457	
50.	92.600	31.8955	31.6439	42.5023	
60.	111.120	28.1750	27.9150	42.5365	
75.	138.900	23.2591	22.9323	40.3830	
90.	166.680	19.4405	19.0049	37.2775	
120.	222.240	14.3366	13.5521	29.3917	
180.	333.360	3.3352	7.4333	17.3851	
240.	444.480	7.9289	4.0952	12.1178	
360.	666.720	7.6295	1.4431	11.4411	
480.	888.960	7.5739	0.6301	11.7333	
600.	1111.200	7.5351	0.3103	7.6245	
720.	1333.440	4.9639	0.1025	-6.6188	
WIND, HOUR		20	7		
1.	1.852	5.8491	4.5236	-58.1521	Interpolation between Snapshots 4 & 5
2.	3.704	15.3031	15.0616	-22.8319	
3.	5.556	31.6745	31.1321	-4.0379	
4.	7.408	45.2941	44.7367	3.0175	
5.	9.260	52.8056	52.1772	6.3979	
6.	11.112	55.6764	54.9776	8.3532	
7.	12.964	55.5360	55.7612	9.8517	
8.	14.816	55.2909	55.4289	11.1628	
9.	16.668	55.4900	54.5386	12.3841	
10.	18.520	54.2968	53.2621	13.5252	
15.	27.780	48.6838	47.4276	18.2287	
20.	37.040	45.1281	44.1740	25.3132	
25.	46.300	42.5121	41.9100	32.3032	
30.	55.560	40.5284	40.1261	37.4110	
40.	74.080	35.1586	35.9069	42.6494	
50.	92.600	31.4613	31.2270	43.5405	
60.	111.120	27.2626	27.0013	42.3935	
75.	138.900	22.2634	21.9178	39.4404	
90.	166.680	13.5853	18.1153	35.9769	
120.	222.240	13.8112	12.9681	27.9855	
180.	333.360	3.1801	7.2034	16.8972	
240.	444.480	7.9265	4.0666	12.5087	
360.	666.720	7.6258	1.5307	12.1834	
480.	888.960	7.5713	0.7078	12.4845	
600.	1111.200	7.5267	0.3684	8.9790	
720.	1333.440	4.9587	0.1301	-2.1435	

Figure C14. (Sheet 4 of 12)

		--- Wind Speed ---		Inflow Angle,	
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	8		
1.	1.852	7.04 26	5. 0716	-54.7408	Snapshot 5
2.	3.704	17.17 57	16. 5115	-18.2037	
3.	5.556	32.48 57	31. 9070	-1.9445	
4.	7.408	44.28 67	43. 6128	3.8353	
5.	9.260	50.55 59	49. 7581	6.2712	
6.	11.112	53.26 40	52. 4012	7.5746	
7.	12.964	54.29 64	53. 3844	8.7047	
8.	14.816	54.46 36	53. 4694	9.9306	
9.	16.668	54.14 09	53. 0254	11.2704	
10.	18.520	53.46 84	52. 2117	12.6752	
15.	27.780	50.39 44	48. 7947	20.3304	
20.	37.040	43.44 48	47. 5966	31.2649	
25.	46.300	45.07 61	45. 6723	39.2970	
30.	55.560	43.35 28	43. 0839	43.4863	
40.	74.080	35.87 95	36. 6723	45.6317	
50.	92.600	31.03 89	30. 8200	44.6116	
60.	111.120	25.34 89	26. 0853	42.2429	
75.	138.900	21.27 24	20. 9049	38.3987	
90.	166.680	17.74 16	17. 2313	34.5203	
120.	222.240	13.29 31	12. 3823	26.4577	
180.	333.360	9.03 01	6. 9736	16.3809	
240.	444.480	7.92 48	4. 0382	12.9052	
360.	666.720	7.62 09	1. 6167	12.8425	
480.	888.960	7.56 41	0. 7856	13.0809	
600.	1111.200	7.51 85	0. 4267	9.9572	
720.	1333.440	6.95 36	0. 1582	0.7499	
WIND, HOUR		20	9		
1.	1.852	6.99 81	5. 0795	-54.8159	Interpolation between Snapshots 5 & 6
2.	3.704	17.17 68	16. 5351	-18.2056	
3.	5.556	32.50 58	31. 9429	-1.9150	
4.	7.408	44.28 01	43. 6174	3.8725	
5.	9.260	50.47 46	49. 6803	6.2548	
6.	11.112	53.13 78	52. 2742	7.4287	
7.	12.964	54.16 63	53. 2625	8.4029	
8.	14.816	54.35 47	53. 3862	9.4955	
9.	16.668	54.07 87	53. 0050	10.7557	
10.	18.520	53.46 31	52. 2558	12.1347	
15.	27.780	50.72 77	49. 1375	19.9558	
20.	37.040	43.04 89	48. 2190	31.2943	
25.	46.300	45.75 82	46. 3703	39.4880	
30.	55.560	44.01 45	43. 7565	43.6872	
40.	74.080	37.40 74	37. 2072	45.7600	
50.	92.600	31.44 70	31. 2338	44.6753	
60.	111.120	25.66 54	26. 4072	42.2520	
75.	138.900	21.49 59	21. 1338	38.3407	
90.	166.680	17.90 24	17. 3978	34.4100	
120.	222.240	13.38 29	12. 4762	26.2241	
180.	333.360	9.06 83	7. 0029	15.9467	
240.	444.480	7.95 28	4. 0419	12.4316	
360.	666.720	7.63 55	1. 6109	12.3296	
480.	888.960	7.57 44	0. 7805	12.4548	
600.	1111.200	7.52 58	0. 4218	9.4619	
720.	1333.440	6.95 65	0. 1548	0.8799	

Figure C14. (Sheet 5 of 12)

		--- Wind Speed ---		Inflow Angle,
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)
WIND, HOUR		20	10	
1.	1.852	5.9537	5.0869	-54.8961
2.	3.704	17.1782	16.5585	-18.2091
3.	5.556	32.5267	31.9786	-1.8853
4.	7.408	44.2750	43.6215	3.9100
5.	9.260	53.3961	49.6013	6.2389
6.	11.112	53.0167	52.1447	7.2816
7.	12.964	54.0441	53.1380	8.0985
8.	14.816	54.2563	53.3016	9.0584
9.	16.668	54.0279	52.9847	10.2410
10.	18.520	53.4681	52.3011	11.5963
15.	27.780	51.0640	49.4815	19.5878
20.	37.040	49.6522	48.8398	31.3240
25.	46.300	47.4393	47.0666	39.6742
30.	55.560	44.6752	44.4276	43.8827
40.	74.080	37.9347	37.7411	45.8854
50.	92.600	31.8548	31.6470	44.7400
60.	111.120	25.9819	26.7288	42.2611
75.	138.900	21.7196	21.3627	38.2847
90.	166.680	13.0638	17.5646	34.3006
120.	222.240	13.4730	12.5704	25.9949
180.	333.360	9.1069	7.0325	15.5172
240.	444.480	7.9816	4.0458	11.9602
360.	666.720	7.6511	1.6052	11.8140
480.	888.960	7.5856	0.7755	11.8209
600.	1111.200	7.5338	0.4170	8.9545
720.	1333.440	4.9598	0.1515	1.0131
WIND, HOUR		20	11	
1.	1.852	8.7207	7.8357	-13.2877
2.	3.704	15.9519	16.5147	-6.2784
3.	5.556	25.1567	25.7571	0.5053
4.	7.408	32.9936	32.5674	3.7029
5.	9.260	35.6307	36.1683	5.0808
6.	11.112	33.3153	37.6633	5.7924
7.	12.964	33.0787	38.6623	6.5059
8.	14.816	33.2626	38.8826	7.4000
9.	16.668	33.0661	38.7132	8.4502
10.	18.520	33.5591	38.2241	9.5350
15.	27.780	35.5052	36.1724	13.9470
20.	37.040	35.8351	36.5306	20.8314
25.	46.300	38.2610	37.9182	28.2281
30.	55.560	39.2255	38.8999	34.0331
40.	74.080	35.8223	36.6041	40.1687
50.	92.600	32.2816	32.0769	41.0231
60.	111.120	23.2033	27.9708	39.6747
75.	138.900	23.4524	23.1454	36.7160
90.	166.680	23.0079	19.6021	33.6159
120.	222.240	15.5677	14.8986	27.1520
180.	333.360	11.1093	9.7741	18.8237
240.	444.480	8.9368	6.8459	15.5806
360.	666.720	7.8636	3.9343	14.4370
480.	888.960	7.6628	2.5745	14.8996
600.	1111.200	7.5550	1.8281	14.1238
720.	1333.440	4.9576	0.9003	12.5738

Snapshot 6

Interpolation between
Snapshots 6 & 7

Figure C14. (Sheet 6 of 12)

		--- Wind Speed ---		Inflow Angle,	
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	12		
1.	1.852	12.3410	11.8551	3.7051	Snapshot 7
2.	3.704	17.3732	17.0704	5.5010	
3.	5.556	19.8249	19.5672	4.8894	
4.	7.408	21.3645	21.1058	4.0851	
5.	9.260	22.3264	22.0409	3.5390	
6.	11.112	22.9808	22.6516	3.4733	
7.	12.964	23.4277	23.0439	3.8438	
8.	14.816	23.6688	23.2223	4.4859	
9.	16.668	23.7225	23.2100	5.1796	
10.	18.520	23.5859	23.0055	5.6476	
15.	27.780	23.2624	22.4453	1.8611	
20.	37.040	25.1342	25.5009	0.3552	
25.	46.300	31.0352	30.4071	10.2215	
30.	55.560	35.0799	34.4948	21.2548	
40.	74.080	35.0679	35.7961	34.1508	
50.	92.600	32.8376	32.6266	37.4436	
60.	111.120	29.4805	29.2604	37.3449	
75.	138.900	25.2107	24.9394	35.4033	
90.	166.680	21.9817	21.6405	33.0628	
120.	222.240	17.7000	17.1812	28.0628	
180.	333.360	13.3470	12.4114	21.4092	
240.	444.480	10.9123	9.5324	17.4889	
360.	666.720	8.6205	6.1845	15.2893	
480.	888.960	7.9491	4.2965	15.4385	
600.	1111.200	7.6724	3.1780	14.7235	
720.	1333.440	5.0044	1.6352	13.5201	
WIND, HOUR		20	13		
1.	1.852	7.7009	6.5613	-2.0170	Interpolation between Snapshots 7 & 8
2.	3.704	11.4624	10.8461	-1.3424	
3.	5.556	14.6585	14.2437	-0.4647	
4.	7.408	17.3708	17.0409	0.1374	
5.	9.260	19.5312	19.2268	0.5209	
6.	11.112	21.1956	20.8754	0.9853	
7.	12.964	22.4706	22.1060	1.7251	
8.	14.816	23.3862	22.9570	2.6858	
9.	16.668	23.9666	23.4606	3.6873	
10.	18.520	24.2226	23.6335	4.4648	
15.	27.780	24.8182	23.9490	1.5678	
20.	37.040	23.1526	27.4695	0.8347	
25.	46.300	33.2867	32.4993	10.3299	
30.	55.560	37.8870	37.1112	21.6899	
40.	74.080	40.1685	39.6787	37.0295	
50.	92.600	37.2299	37.0326	41.6416	
60.	111.120	33.6495	33.4597	42.3094	
75.	138.900	23.6322	28.4091	40.7412	
90.	166.680	24.6445	24.3656	38.3392	
120.	222.240	19.1697	18.7279	32.5782	
180.	333.360	13.6240	12.7291	23.5062	
240.	444.480	10.6611	9.2116	17.6683	
360.	666.720	8.2944	5.3560	14.5539	
480.	888.960	7.7899	3.4564	14.7954	
600.	1111.200	7.5948	2.4277	14.0900	
720.	1333.440	4.9736	1.1949	12.8509	

Figure C14. (Sheet 7 of 12)

Radius (n.m.)	Radius (km)	--- Wind Speed ---		Inflow Angle, (+ = in, - = out) (deg)
		Scalar Avg. (m/sec)	Vector Avg. (m/sec)	

WIND, HOUR

20

14

1.	1.852	5.7881	1.0245	-54.9114
2.	3.704	5.4541	3.9720	-24.5178
3.	5.556	9.4686	8.6090	-11.9362
4.	7.408	13.4829	13.0106	-6.3961
5.	9.260	15.7968	16.4585	-3.6516
6.	11.112	19.4415	19.1273	-2.0103
7.	12.964	21.5386	21.1914	-0.5934
8.	14.816	23.1255	22.7110	0.8438
9.	16.668	24.2274	23.7256	2.2342
10.	18.520	24.8698	24.2708	3.3539
15.	27.780	25.3710	25.4490	1.3220
20.	37.040	30.1687	29.4218	1.2605
25.	46.300	35.5447	34.5681	10.4418
30.	55.560	40.6915	39.6964	22.0873
40.	74.080	44.2657	43.9524	39.3821
50.	92.600	41.6690	41.4767	44.9388
60.	111.120	37.9086	37.7362	46.1393
75.	138.900	32.1717	31.9795	44.8648
90.	166.680	27.4255	27.1891	42.4840
120.	222.240	20.7241	20.3404	36.3204
180.	333.360	13.9054	13.0482	25.5059
240.	444.480	10.4115	8.8880	17.8943
360.	666.720	3.0717	4.5179	13.6535
480.	888.960	7.6928	2.6034	13.7065
600.	1111.200	7.5579	1.6662	12.8807
720.	1333.440	4.9537	0.7413	11.2863

Snapshot 8

WIND, HOUR

20

15

1.	1.852	5.2786	3.6952	-21.4673
2.	3.704	9.6598	8.8585	-8.8558
3.	5.556	13.9015	13.4537	-3.6465
4.	7.408	17.2845	16.9501	-1.3335
5.	9.260	19.9031	19.5926	-0.1562
6.	11.112	21.8548	21.5198	0.7374
7.	12.964	23.2916	22.9027	1.7017
8.	14.816	24.2837	23.8207	2.7128
9.	16.668	24.8923	24.3430	3.6006
10.	18.520	25.1624	24.5209	4.1324
15.	27.780	25.3268	25.4590	0.4130
20.	37.040	30.7382	30.0349	2.6953
25.	46.300	35.3498	35.5371	14.4592
30.	55.560	40.5023	39.6200	25.8454
40.	74.080	41.5230	41.2674	39.3602
50.	92.600	37.9830	37.7975	43.0899
60.	111.120	34.0207	33.8370	43.3371
75.	138.900	23.6710	26.4499	41.4519
90.	166.680	24.4793	24.1978	39.8258
120.	222.240	13.7628	18.3017	32.6069
180.	333.360	13.0273	12.0419	22.6556
240.	444.480	10.0310	8.3815	16.5407
360.	666.720	8.0627	4.5075	13.6395
480.	888.960	7.6978	2.7350	13.7364
600.	1111.200	7.5589	1.8231	12.9673
720.	1333.440	4.9534	0.8437	11.6417

Interpolation between
Snapshots 8 & 9

Figure C14. (Sheet 8 of 12)

		--- Wind Speed ---		Inflow Angle,	
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	16		
1.	1.852	7.5921	6.3574	-15.8577	Snapshot 9
2.	3.704	13.8447	13.4131	-2.9746	
3.	5.556	13.2339	17.9469	0.7354	
4.	7.408	21.1606	20.8925	1.7994	
5.	9.260	23.0540	22.7538	2.2868	
6.	11.112	24.2866	23.9272	2.8904	
7.	12.964	25.0617	24.6285	3.6555	
8.	14.816	25.4596	24.9436	4.4044	
9.	16.668	25.5713	24.9689	4.8958	
10.	18.520	25.4633	24.7739	4.8956	
15.	27.780	25.2953	25.4727	-0.4949	
20.	37.040	31.3771	30.6556	4.0804	
25.	46.300	37.3395	36.6335	18.2633	
30.	55.560	40.5397	40.0771	29.5947	
40.	74.080	33.7619	38.5545	39.3625	
50.	92.600	34.2823	34.0974	40.8550	
60.	111.120	30.1596	29.9541	39.8027	
75.	138.900	25.2403	24.9730	37.0471	
90.	166.680	21.6228	21.2727	34.0914	
120.	222.240	15.8975	16.3266	27.8725	
180.	333.360	12.1601	11.0181	19.3734	
240.	444.480	3.6775	7.8774	15.0447	
360.	666.720	3.0558	4.4971	13.6266	
480.	888.960	7.7047	2.8664	13.7609	
600.	1111.200	7.5622	1.9796	13.0339	
720.	1333.440	4.9545	0.9461	11.9152	
WIND, HOUR		20	17		
1.	1.852	5.1944	3.3138	-17.8760	Interpolation between Snapshots 9 & 10
2.	3.704	3.2681	7.2138	-6.8815	
3.	5.556	10.7056	10.0051	-4.1496	
4.	7.408	12.7647	12.1956	-3.0712	
5.	9.260	14.7353	14.2314	-2.2659	
6.	11.112	15.6943	16.2217	-1.2967	
7.	12.964	13.5415	18.0779	-0.2965	
8.	14.816	20.2149	19.7445	0.5915	
9.	16.668	21.6830	21.1908	1.2304	
10.	18.520	22.9397	22.4105	1.6022	
15.	27.780	27.8821	27.2105	1.1748	
20.	37.040	32.6080	32.0467	5.5860	
25.	46.300	35.3954	35.8652	14.8451	
30.	55.560	38.1757	37.7211	22.5590	
40.	74.080	37.0872	36.7704	30.7857	
50.	92.600	34.6084	34.3532	34.4098	
60.	111.120	32.1141	31.8807	36.0672	
75.	138.900	28.4567	28.2119	36.6382	
90.	166.680	25.2441	24.9620	35.9514	
120.	222.240	20.3278	19.9233	32.5304	
180.	333.360	14.6386	13.8605	25.1756	
240.	444.480	11.3865	10.1154	19.1383	
360.	666.720	3.4428	5.7836	14.1522	
480.	888.960	7.8172	3.5385	13.6463	
600.	1111.200	7.5980	2.3437	12.9271	
720.	1333.440	4.9691	1.0852	11.8318	

Figure C14. (Sheet 9 of 12)

		--- Wind Speed ---		Inflow Angle,
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)
WIND, HOUR		20	18	
1.	1.852	5.8467	0.1474	-88.3890
2.	3.704	5.8913	0.3323	-80.3511
3.	5.556	5.9854	0.7624	-51.3616
4.	7.408	5.1382	2.1004	-27.6604
5.	9.260	5.7706	4.7446	-17.3690
6.	11.112	9.0271	8.0799	-12.3260
7.	12.964	12.0708	11.4742	-8.8906
8.	14.816	15.0533	14.6107	-6.1866
9.	16.668	17.8664	17.4786	-4.1897
10.	18.520	20.4882	20.1007	-2.5294
15.	27.780	29.5051	28.9509	2.6555
20.	37.040	33.9718	33.4147	6.9510
25.	46.300	35.6832	35.1937	11.2949
30.	55.560	35.3991	35.8866	14.7093
40.	74.080	35.2753	35.7456	21.5719
50.	92.600	35.3740	34.9881	28.1950
60.	111.120	34.2038	33.9125	32.8383
75.	138.900	31.6678	31.4230	36.3589
90.	166.680	28.8703	28.6221	37.3360
120.	222.240	23.8659	23.5513	35.6325
180.	333.360	17.1794	16.6087	29.1446
240.	444.480	13.2542	12.2959	22.2227
360.	666.720	9.1195	7.0444	14.5881
480.	888.960	7.9716	4.2027	13.5547
600.	1111.200	7.6452	2.7066	12.8437
720.	1333.440	4.9840	1.2224	11.7472
WIND, HOUR		20	19	
1.	1.852	5.8873	0.1315	267.8173
2.	3.704	5.9185	0.2864	-85.9611
3.	5.556	5.9876	0.5704	-62.3600
4.	7.408	5.0828	1.4066	-35.5808
5.	9.260	5.4022	3.4218	-21.5389
6.	11.112	7.7488	6.4805	-15.1524
7.	12.964	10.6217	9.8852	-11.4492
8.	14.816	13.7639	13.2437	-8.3193
9.	16.668	15.7812	16.3407	-5.9519
10.	18.520	19.6647	19.2310	-4.1128
15.	27.780	30.2064	29.6647	1.3036
20.	37.040	35.6643	35.1813	7.1232
25.	46.300	37.6751	37.1826	12.9720
30.	55.560	38.4773	37.9349	17.8365
40.	74.080	37.8872	37.4660	26.6277
50.	92.600	35.1374	35.8437	32.4841
60.	111.120	34.0912	33.8478	35.6165
75.	138.900	30.5693	30.3335	37.1984
90.	166.680	27.2103	26.9485	36.9100
120.	222.240	21.8017	21.4339	33.6605
180.	333.360	15.3121	14.5863	25.7770
240.	444.480	11.6306	10.3863	18.7814
360.	666.720	8.3756	5.5758	13.0014
480.	888.960	7.7792	3.2149	12.4173
600.	1111.200	7.5839	2.0212	11.7434
720.	1333.440	4.9611	0.8834	10.6389

Snapshot 10

Interpolation between
Snapshots 10 & 11

Figure C14. (Sheet 10 of 12)

		--- Wind Speed ---		Inflow Angle,	
Radius (n.m.)	Radius (km)	Scalar Avg. (m/sec)	Vector Avg. (m/sec)	(+ = in, - = out) (deg)	
WIND, HOUR		20	20		
1.	1.852	5.9287	0.1162	262.9949	Snapshot 11
2.	3.704	5.9470	0.2442	266.3879	
3.	5.556	5.9963	0.4185	-82.6926	
4.	7.408	5.0763	0.7876	-57.0778	
5.	9.260	5.1921	2.0833	-30.7253	
6.	11.112	5.8094	4.8376	-19.6630	
7.	12.964	9.1999	8.2625	-14.5830	
8.	14.816	12.4422	11.8214	-10.8999	
9.	16.668	15.7084	15.2023	-7.9758	
10.	18.520	18.8605	18.3726	-5.8433	
15.	27.780	30.9314	30.3868	0.0276	
20.	37.040	37.4365	36.9167	7.2898	
25.	46.300	39.7792	39.1634	14.4881	
30.	55.560	40.6823	40.0401	20.6426	
40.	74.080	39.7404	39.3892	31.2106	
50.	92.600	37.0910	36.8561	36.5571	
60.	111.120	34.0673	33.8533	38.4093	
75.	138.900	29.4841	29.2478	38.1131	
90.	166.680	25.5521	25.2662	36.4341	
120.	222.240	19.7706	19.3250	31.2195	
180.	333.360	13.5125	12.5523	21.3094	
240.	444.480	10.1318	8.4430	14.2101	
360.	666.720	3.0124	4.0795	10.4747	
480.	888.960	7.6745	2.2099	10.1812	
600.	1111.200	7.5460	1.3164	9.3948	
720.	1333.440	6.9515	0.5429	8.0716	
WIND, HOUR		20	21		
1.	1.852	5.8757	0.1576	268.9495	Interpolation between Snapshots 11 & 12
2.	3.704	5.9111	0.3922	-77.2274	
3.	5.556	5.9792	1.0670	-45.1869	
4.	7.408	5.2267	2.7191	-27.0611	
5.	9.260	7.1538	5.5461	-17.8151	
6.	11.112	9.9381	9.1108	-12.9344	
7.	12.964	13.2739	12.7167	-9.3226	
8.	14.816	15.5174	16.0578	-6.5766	
9.	16.668	13.5786	19.1314	-4.5214	
10.	18.520	22.3568	21.8765	-2.8559	
15.	27.780	31.7253	31.1325	1.6857	
20.	37.040	35.4453	35.8979	7.4276	
25.	46.300	33.1408	37.5264	13.7821	
30.	55.560	33.9178	38.2712	19.6641	
40.	74.080	33.2284	37.8720	30.4967	
50.	92.600	33.6980	35.4598	35.9404	
60.	111.120	32.7401	32.5198	37.7223	
75.	138.900	23.2836	28.0357	37.3035	
90.	166.680	24.4976	24.1939	35.5394	
120.	222.240	13.9903	18.5127	30.2212	
180.	333.360	13.0686	12.0446	20.4456	
240.	444.480	9.6837	8.1095	13.8851	
360.	666.720	7.9783	3.9614	10.7447	
480.	888.960	7.5647	2.1807	10.4769	
600.	1111.200	7.5406	1.3178	9.6964	
720.	1333.440	6.9487	0.5516	8.3981	

Figure C14. (Sheet 11 of 12)

Radius (n.m.)	Radius (km)	--- Wind Speed --- Scalar Avg. (m/sec)	Vector Avg. (m/sec)	Inflow Angle, (+ = in, - = out) (deg)
WIND, HOUR		20	22	
1.	1.852	5.8255	0.2000	-87.6107
2.	3.704	5.8812	0.5546	-70.1721
3.	5.556	5.0218	1.8204	-37.1198
4.	7.408	5.7394	4.6981	-21.8820
5.	9.260	9.6611	8.8197	-14.1624
6.	11.112	13.5649	13.0636	-9.2704
7.	12.964	17.2198	16.8280	-6.1336
8.	14.816	20.5720	20.1906	-3.9692
9.	16.668	23.4862	23.0649	-2.2587
10.	18.520	25.8745	25.3865	-0.7408
15.	27.780	32.5430	31.8957	3.2647
20.	37.040	35.4582	34.8746	7.5786
25.	46.300	35.5038	35.8823	13.0151
30.	55.560	37.1546	36.4978	18.5939
40.	74.080	35.7130	36.3500	29.7262
50.	92.600	31.3014	34.0590	35.2759
60.	111.120	31.4108	31.1831	36.9782
75.	138.900	27.0841	26.8226	36.4202
90.	166.680	23.4467	23.1226	34.5579
120.	222.240	13.2176	17.7032	29.1176
180.	333.360	12.6231	11.5294	19.5335
240.	444.480	9.6441	7.7750	13.5450
360.	666.720	7.9456	3.8433	11.0326
480.	888.960	7.6550	2.1516	10.7810
600.	1111.200	7.5351	1.3193	9.9973
720.	1333.440	6.9459	0.5603	8.7143
FORTRAN STOP				

Snapshot 12

Figure C14. (Sheet 12 of 12)

Appendix D

Sample Application of Upgraded CE Model to Simulation of 36-Hr Period of Hurricane Gilbert in the Gulf of Mexico

This appendix provides information related to a 36-hr simulation of Hurricane Gilbert in the Gulf of Mexico. The simulation was performed by OWI as an additional test with the upgraded CE model. The simulation time period begins 1200 UTC (Universal Time Coordinate, formerly known as Greenwich Mean Time) 15 September 1988. The four snapshots used in the simulation all took advantage of the double exponential form for pressure profile specification. Input file information on the snapshots and storm track specification is provided in this appendix.

The appendix also includes plots of Hurricane Gilbert wind fields. Model wind fields at 19-m elevation are given at 6-hr intervals throughout the simulation period. Wind speed and direction is represented with the conventional weather map "wind barb" notation. The shaft of each wind arrow indicates the direction and the barbs or "feathers" indicate wind speed. A half-barb denotes 5 knots, full barb denotes 10 knots, and solid flag denotes 50 knots.

```

s type 05gilbert88.dat
$name1 kzm = 8809, kdh = 151100, kmin = 60, inside=1,
      rstres=17227, kstres = 0, kwind = 19, nwind = 4661, hh=500. send
$name2 eyelat=22, eypres=951, pfar=1012, radius=11.88,46.85, holl=.56,2.52,
      dpi=45.07, direc=290, speed=11, squ=7, ani=120 send
$name2 eyelat=23, eypres=949, pfar=1010, radius=11.88,43.53, holl=.75,2.52,
      dpi=40.67, squ=8 send
$name2 eyelat=24, eypres=953, pfar=1010, radius=27.64,21, holl=1.33,2.52,
      dpi=46.62, squ=9 send
$name2 eyelat=24, eypres=954, pfar=1009, radius=21.6,60.61, holl=1.19,2.52,
      dpi=44.98 send
$name2 eyelat = 999 send
0 21 54 -91 42 1
1 21 54 -91 42 1
7 22 5 -92 48
13 22 30 -93 48 2
19 22 54 -94 48
25 23 42 -95 54
31 23 54 -97 0 3
37 24 24 -98 12 4
999
$what kstep2 = 37 $enc

```

Figure D1. Snapshot and storm track specification, Hurricane Gilbert




Figure D2. Modelled surface wind field in Hurricane Gilbert (Sheet 1 of 7)




Figure D2. (Sheet 2 of 7)




Figure D2. (Sheet 3 of 7)




Figure D2. (Sheet 4 of 7)




Figure D2. (Sheet 5 of 7)




Figure D2. (Sheet 6 of 7)




Figure D2. (Sheet 7 of 7)

REPORT DOCUMENTATION PAGEForm Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1994	3. REPORT TYPE AND DATES COVERED Final report
4. TITLE AND SUBTITLE Upgrade of Tropical Cyclone Surface Wind Field Model			5. FUNDING NUMBERS WU 32683
6. AUTHOR(S) Vincent J. Cardone, Andrew T. Cox, J. Arthur Greenwood, Edward F. Thompson			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Oceanweather, Inc., 5 River Road, Suite 1, Cos Cob, CT 06807 U.S. Army Engineer Waterways Experiment Station 3909 Halls Ferry Road, Vicksburg, MS 39180-6199			8. PERFORMING ORGANIZATION REPORT NUMBER Miscellaneous Paper CERC-94-14
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Corps of Engineers Washington, DC 20314-1000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Available from National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) The U.S. Army Corps of Engineers (CE) tropical cyclone surface wind field model has been a very useful tool in ocean response modeling for more than a decade. Recently, its limitations were assessed in light of present knowledge and technology. Model limitations were identified and evaluated in terms of their perceived importance to ocean response modeling and the level of effort required to develop improved solutions. The limitations are summarized in this report. Two aspects of the CE model were targeted for improvement. This report describes the improvements developed for the upgraded model. First, the model was upgraded to include more computationally intensive options which give improved resolution and areal coverage. Up to seven nested grids are now available, compared to only five nests in the standard model. In a typical application, this upgrade can be used to achieve 2-km resolution around the eye (as compared to 5-km resolution often used in the standard model) and an expanded total coverage area. The second upgrade allows a more general specification of the axisymmetric pressure profile. This upgrade can be used to create wind fields with maxima at two different radii or with a broad maximum extending over a range of radii. It also provides more flexibility in fitting the shape of single peaked wind profiles. (Continued)			
14. SUBJECT TERMS Hurricanes Winds Numerical modeling Wind fields Tropical storms			15. NUMBER OF PAGES 101
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT

13. (Concluded).

The upgraded model is demonstrated with historical hurricanes. The five-nest and seven-nest models are applied to Hurricane Camille. The fully upgraded model, with seven nests and general pressure specification, is applied to Hurricane Gilbert. This hurricane was chosen because it is well-documented by Black and Willoughby (1992) and it evolved into some nontraditional storm structures. The upgraded model was more effective than the standard CE model in simulating the storm.