USAARL Report No. 94-40


AD-A285 213



Visual Perception in the Field-of-View of Partial Binocular Overlap Helmet-Mounted Displays

By

Victor Klymenko Robert W. Verona Howard H. Beasley John S. Martin



UES Incorporated

and

William E. McLean

Aircrew Health and Protection Division

August 1994



Approved for public release; distribution unlimited.

United States Army Aeromedical Research Laboratory Fort Rucker, Alabama 36362-0577

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Human use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:

RICHARD R.

LTĆ, MS

Director, Aircrew Health and

Performance Division

Released for publication:

ROGER W. WILLEY, O.D., Ph.D

Chairman, Scientific

Review Committee

DENNIS F. SHANAHAN

Colonel, MC, MFS

Commanding

01102-					
(TAILCINA	J PI AT	USIZ AT	IAN AF	7016	SAZE

REPORT DOCUMENTATION					N PAGE			Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION				1b. RESTRICTIVE MARKINGS					
Unclassified 2a. SECURITY CLASSIFICATION AUTHORITY					3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited				
26. DECLASSIFICATION / DOWNGRADING SCHEDULE									
4. PERFORMIN	G ORGANIZAT	ION RE	PORT NUMBE	R(S)	5. MONITORING ORGANIZATION REPORT NUMBER(S)				
USAARL Re	port No.	94-4	0						
U.S. Army Aeromedical Research			6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research, Development, Acquisition, and Logistics Command(Provisional					
Laboratory SGRD-UAS-VS 6c. ADDRESS (City, State, and ZIP Code)					7b. ADDRESS (City, State, and ZIP Code)				
P.O. Box 620577 Fort Rucker, AL 36362-0577				Fort Detrick Frederick, MD 21702-5012					
8a. NAME OF FUNDING/SPONSORING ORGANIZATION			8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER					
8c. ADDRESS (C	City, State, and	ZIP Co	de)		10. SOURCE OF FUNDING NUMBERS				
					PROGRAM ELEMENT NO.	PROJECT NO. 3M1627	TASK NO.	WORK UNIT ACCESSION NO.	
				062787A	87A879	1	BG 164		
11. TITLE (Include Security Classification) (U) Visual Perception in the Field-of-View of Partial Binocular Overlap Helmet-Mounted									
Displays	ALITHORISI								
Victor K	lymenko,	Robe	rt W. Ver	ona, Howard H. B	easley, Joh	n S. Martin,	and W	illiam E. McLean	
13e. TYPE OF I	REPORT	136. TIME CO FROM		OVERED TO	4. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT 1994 August 17				
16. SUPPLEMENTARY NOTATION									
17.	COSATI	CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)					
FIELD	GROUP	SU	B-GROUP	full binocular overlay, partial binocular overlap, helmet-					
23	04 02			mounted display, convergent FOV, divergent FOV, luning, dichoptic, contrast threshold, binocular occlusion, CONT'D			lusion, CONT'D		
		inue on reverse if necessary and identify by block number)							
Because of limitations in the size of the field-of-view (FOV) available in helmet-mounted displays (HMD) using the full overlap display mode, where the entire FOV is binocular, partial binocular overlap displays, which can be convergent or divergent, have been proposed. One consequence of this is a perceptual effect known as luning, which is a subjective darkening in the monocular regions of the FOV, which can in some cases cause fragmentation of the FOV into three regions. A concern is the possible effect on target identification in the monocular regions, particularly in areas affected by luning. We review data we have collected in our binocular vision lab on the effect of display mode on these aspects of visual perception.									
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT 21. ABSTRACT SECURITY CLASSIFICATION									
☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS					Unclassified 22b. TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL				
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Science Support Center				226. TELEPHONE 205-255-6			-UAX-SI		

1. BACKGROUND

Artificially small fields-of-view (FOV) can be detrimental to the visual tasks required of military pilots.¹⁻⁴ In order to increase the extent of the visual world available to U.S. Army helicopter pilots using helmet mounted displays (HMDs), without incurring increases in size, weight, or loses in central resolution, an unusual method of display---partial binocular overlap---has been proposed. Two flanking monocular regions and a central binocular overlap region constitute the FOV in partial binocular overlap displays, where the display mode may be convergent or divergent (see Figures 1 and 2). Increasing the FOV by this method has been the cause of some concern.⁵⁻¹⁸

One detrimental consequence of the partial binocular overlap display mode is a perceptual effect known as *luning*, which is a subjective darkening in the monocular regions of the FOV near the binocular overlap borders. ^{9,11,14,15} Sometimes luning is experienced as a visual fragmentation of the FOV into three distinct regions, where instead of the entire FOV appearing as one unitary visual area, the central binocular overlap region appears to be different than the two monocular side regions. The monocular side regions may appear to lie in a different depth plane, or to be darker than the binocular region. ¹⁶ Due to both luning and fragmentation, the monocular regions may appear less substantial and less stable than the binocular region in that they may fluctuate in appearance over time. These effects are due to the binocular rivalry and suppression caused by the dichoptic competition between the discordant stimulation presented to the two eyes. In each of the monocular regions making up the FOV, one eye sees a portion of the FOV and the other eye sees a dark background at the same phenomenal location in space (see Figure 2).

An additional concern is the effect of partial overlap on target detection and identification. The superiority of binocular vision over monocular vision is well known. For example, contrast sensitivity is increased by a factor of 1.4 for binocular vision compared to monocular vision.¹⁹ How does the additional factor of only partially overlapping the binocular display affect perception? How does this affect target threshold in the areas that undergo luning near the binocular overlap border? Is there a difference in the visibility of targets if the partial binocular overlapping FOV is displayed in the divergent as opposed to the convergent display mode (see Figure 2)?

Below, we review our research on the perceptual consequences of partial overlap displays. ¹⁵⁻¹⁸ First, we briefly describe our binocular vision lab, then our data, and finally interpretations of our results.

2. BINOCULAR VISION LAB

We designed a binocular vision lab to allow us to present computer controlled images simulating the display modes available in HMDs.¹⁵⁻¹⁷ The equipment consisted of three major components: A Hewlett-Packard HP-98731 Turbo-SRX computer graphics workstation used to generate the visual stimuli; an optical table configuration used to optically direct the visual stimuli from the workstation monitor to a pair of viewing binoculars; and a subject booth, a light proof enclosure where the subject viewed the stimuli via the binoculars and responded via a response keypad. The purpose of the optical table configuration was to allow the independent presentation of two channels, one to each ocular of the binoculars from the same monitor. The equipment is shown in Figure 3. Figure 4 shows examples of the three display modes for presenting the FOV.

Accesion For					
NTIS CRA&I DTIC TAB U.announced					
By					
Availability Codes					
Dist	Avail ar q / or Special				
A-1					




Figure 1. The unaided FOV is divergent with the right eye's monocular (M) region to the right of the binocular (B) overlap region and the left eye's monocular region to the left. The total FOV is normally around 190°.




Figure 2. A helicopter pilot's view of the visual world using a helmet mounted display in the partial binocular overlap display mode, where each eye sees a circular monocular field against a black background. The central binocular overlap region is flanked by two monocular regions. If the right eye views the right circular field, the effective field-of-view is in the divergent display mode; if the right eye instead views the left circular field, the mode is convergent. Separating the binocular region and monocular regions are the binocular overlap borders. Luning refers to the subjective darkening which can occur in the monocular regions near the binocular overlap borders. (A helicopter and an armored personnel carrier are in portions of the monocular regions affected by luning.) Luning can result in fragmentation of the field-of-view into three—two side and one central—phenomenally distinct regions.




Figure 3. Perspective and schematic illustrations of the optical table configuration, consisting of the monitor, eight mirrors, focusing lenses and binoculars. The image from the top half of the monitor is directed to the left eye (mirrors L1 to L4), and the image from the bottom half is directed to the right eye (mirrors R1 to R4). The binoculars and movable mirrors, L4 and R4, are set to correspond to each subject's interpupillary distance (IPD). Examples of resulting stimulus displays are shown in Figure 4.

Display modes Divergent Convergent Full overlap display mode display mode display mode Seen by: Left eye Right eye Elliptical monocular fields on the monitor R R R Through the binoculars

Field-of-view as seen by the observer

Figure 4. The top panel shows the positions of elliptical monocular fields on the monitor for three display modes. The middle panel shows the images of the monocular fields through the binoculars for the right (R) and left (L) eyes for each display mode. The bottom panel shows the field-of-view as seen by the observer when the monocular images are properly fused. The image on the right corresponds to the full overlap display mode and the image on the left corresponds to a partial binocular overlap display mode. If the right elliptical field is viewed by the right eye, the partial overlapped FOV is in the divergent mode, and if the left elliptical field is viewed by the right eye, it is in the convergent mode. The small black squares are the fusion locks. Elliptical visual fields were used in the luning and the contrast study.

3. LUNING IN THE FOV

The effect of a number of display factors on luning were tested. These factors included: (1) convergent versus divergent displays, (2) display luminance level, (3) the presence of either black or white contours or no (null) contours on the binocular overlap border, and (4) lowering or raising the luminance of the monocular side regions relative to the binocular overlap region. The stimulus dimensions of the visual fields are shown on the top of Figure 5. To ensure proper binocular fusion, fusion locks were present in the monocular fields as shown in Figures 4 and 5. If subjects lost fusion and/or experienced diplopia, they could call up a fusion stimulus pattern shown on the bottom of Figure 5. There were 22 stimulus conditions described in Figure 6, which were presented in three blocks. Each stimulus was viewed for 30 seconds during which time the subject was free to scan the FOV. The subject continuously pressed one of two buttons to indicate the presence or absence of luning. Data recording began after the initial 5 seconds of stimulus presentation. The mean percentage of the 25 second data recording time interval that luning was seen when measure of the amount of luning for each stimulus condition. The stimulus conditions tested are shown on the top and the corresponding results for 18 subjects are shown on the bottom of Figure 6.





Figure 5. Dimensions of elliptical monocular fields and fusion stimulus pattern. The visual dimensions in degrees of visual angle are given to the right and below the overlapping monocular ellipses. The distances between fusion locks are given above and to the left. The fusion stimulus pattern, in which the same image was presented to both eyes, is shown below the ellipses. This pattern consisted of the fusion locks and the binocular overlap region.

Monocular fields



Display luminance:




Figure 6. Top. Stimulus conditions in luning study. Null contour conditions: monocular fields were of uniform luminance against a black background. Black and white contour conditions: contours were added in location of binocular overlap borders. Monocular luminance difference conditions: monocular regions were bright or dim and the binocular overlap region was medium. (Luminance in footlamberts: dim 0.4, medium 2.0, bright 5.0, background 0.02). Bottom. Results. Mean percentage of 25 second stimulus presentation time luning was seen for each condition for 18 subjects.

The results indicated that the divergent display mode systematically induced more luning than the convergent display mode under the null contour condition. Adding black contours reduced luning in both the convergent and divergent display modes, where the convergent mode retained its relatively lower magnitude of luning: this confirmed previous studies. The display luminance level had no effect on luning for the null or black contour conditions. Adding white contours reduced luning by an amount which depended on display luminance, where there was less luning for lower display luminance levels. Changing the luminance of the monocular regions (relative to the overlap region) reduced the perceived amount of luning, where a decrease produced more of a reduction than an increase. Also, luning tended to increase over time in that there tended to be more reported luning in the second half of the stimulus interval compared to the first half. These and additional luning data are described more fully elsewhere. 15

4. CONTRAST THRESHOLD ACROSS THE FOV

We investigated the effect of display modes on visual sensitivity across the FOV. We measured the visual threshold to probe targets across the FOV for three display modes: the full overlap mode, the convergent mode, and the divergent mode. The experimental conditions included four types of position in the FOV: monocular and binocular, each of which could be either near to or distant from binocular overlap border (see Figure 7). All combinations of four spatial frequency (1.06, 2.12, 4.24, and 8.48 cycles per degree; see Figure 8) and four temporal frequency (0, 3.75, 7.5, and 15 Hertz; see Figure 9) probe targets were tested at each of the four positions. The nonzero Hz targets flickered sinusoidally from zero to full contrast. The monocular fields were of the same size and luminance as described previously. The only difference between display modes was the position of the monocular fields as shown in Figure 7.




Figure 7. The four probe positions. The relative positions of the elliptical monocular fields and the four probe positions are shown superimposed. Both eyes saw the ellipse with the solid line in the full overlap display mode. In the divergent display mode, the right eye saw the dotted ellipse on the right, and the left eye saw the dashed ellipse on the left, and the left eye saw the dotted ellipse on the right. Stimulus probes in positions 1 and 2 are monocular in the convergent and the divergent display modes and binocular in the full overlap display mode. Stimulus probes in positions 3 and 4 are binocular in all modes. In the convergent and divergent display modes, positions 2 and 3 are near (0.08 degrees of visual angle) the binocular overlap border, and positions 1 and 4 are more distant (2.03 degrees of visual angle) from the border. There is no border in the full overlap mode.




Figure 8. Spatial modulation of probe stimuli. The probe stimuli were four cycles of a sine wave grating modulated by a circularly symmetric half cosine envelope (dashed lines) of 1/4 the spatial frequency of the sine wave. L_X represents the maximum luminance, L_N the minimum luminance, and L_R the mean (and the background) luminance of the resulting stimulus patch. The phase of the cosine envelope is 0° in the center, and the sine wave is randomly either 0° or 180° . These are modulated with respect to L_R . Top shows a diagonal luminance cross section shown in the middle. Stimulus contrast defined at the bottom represents the peak contrast for the temporally modulated patterns shown in Figure 9. These probe stimuli are localized in space and have a narrow bandwidth in the Fourier domain.




Figure 9. Temporal modulation of probe stimuli. For the flickering probe stimuli, the contrast varied sinusoidally as shown on the top. Stimulus contrast is defined by the peak contrast. The bottom shows the luminance profile of a cross section of the probe at five points in time.

There were 192 experimental conditions, which consisted of the four spatial frequencies x four temporal frequencies x four probe positions x three display modes. These were divided into 16 types of experimental session, where each session presented the four temporal frequencies x the three display modes for one spatial frequency at one position. There were 31 subjects. Each subject took part in from 1 to 16 sessions, and between 15 and 27 subjects took part in each type of session. The 12 stimuli in each session were presented in three blocks.

The subject's task for each trial as to fixate the location of the probe stimulus and to set the modulation contrast of the probe, using the shod of adjustment, to the lowest level at which the orientation of the probe could be identified. The entrast step size changes were the smallest available for our 256 gray level monitor. The contrast was modulated about a mean luminance level of 2.0 footlamberts. For each trial the contrast of the stimulus probe began at zero. For each change in contrast one of four stimulus versions was presented randomly (2 orientations x 2 phases; see Figure 8). Subjects increased contrast with a button press and could decrease contrast with a button press if threshold was overshot. The data were the mean contrast levels for each stimulus condition.

A sample of results are shown in Figure 10. In general the results indicate that for all spatial and temporal frequencies, the probes in positions 1 and 2 had higher thresholds in both of the partial overlap display modes, where the probes were monocular, compared to the full overlap display mode, where the probes were binocular. This was as expected.¹⁹ We also found systematic increases in threshold for the divergent impared to the convergent display mode for the two highest (4.24 and 8.48 cpd) spatial frequencies and there was still somewhat of an increase for the next to lowest spatial frequency (2.12 cpd) for position 2. There may still have been threshold differences for the lower spatial frequencies, however, these would have been finer than our ability to measure in the current design.

For the partial overlap displays, thresholds tended to be higher in position 2 compared to portion 1. It appears that the darkening luning phenomenon, emanating from the binocular overlap border, which is greater in the divergent compared to the convergent display mode, is related to this decrement in sensitivity. This is interesting because when any feature is in the FOV, luning is less noticeable, yet, the degree of threshold decrement appears to be correlated with the magnitude of luning in a clear FOV for a display mode. Overall, these differences were more pronounced for the higher spatial frequencies.

In the partial overlap display modes, the reasons thresholds are higher in position 2 near the border compared to position 1 may be as follows: The monocular region is the binocular result of the dichoptic competition of the monocular field of one eye and the dark background of the contralateral eye. The eye contributing the monocular field to the monocular region, the **informational** eye, is a relatively poor competitor compared to the **noninformational** eye containing the border (edge) between the monocular field and background. It is known that edges are strong dichoptic competitors that tend to pull in surrounding areas into the binocular percept. This can be attenuated by placing an edge in the informational eye. This will income its relative dichoptic strength. Also softening the border in the noninformational eye will weake as strength.

In position 4, where the probe in each of the display modes was binocular and not adjacent to the binocular overlap border in the partial overlap distance, there were no differences in thresholds for any of the probe targets. In position 3, where the probe in each of the display modes was binocular but was adjacent to the binocular overlap border in the partial overlap display modes, there were some small differences in the thresholds for probe targets at the two intermediate spatial frequencies. Borders in

general are known to effect threshold.²² These data are described more fully elsewhere.¹⁸ All of the above results, with one exception, can be accounted for by known phenomena. The exception, discussed below, is the systematic differences between the divergent and the convergent display modes in terms of both luning and visual thresholds.






Figure 10. Sample of contrast threshold results. Spatial and temporal frequency of probe stimulus listed on top. Positions on bottom of graphs correspond to Figure 7. Below graphs are the results of the statistical analyses which test the effect of display mode on contrast threshold for each position.


5. FRAGMENTATION OF THE FOV

When the informational eye dominates the monocular regions of partial overlap displays, the FOV looks natural and the binocular and monocular regions are both seen as one continuous visual world; alternatively, if the noninformational eye dominates, the FOV appears fragmented into three distinct visual regions, and the two flanking monocular regions appear separate from and/or different than the central binocular overlap region.

We tested the influence of display factors on fragmentation. These included the display mode-convergent versus divergent—and orthogonal to this, the dimensions of the different visual areas. These were the size of (1) the monocular fields, (2) the monocular regions, (3) the FOV, and (4) the binocular overlap region. Rather than ellipses, the monocular fields were rectangles measuring 4 degrees of visual angle vertical and between 11 and 20 degrees horizontal. The positioning and size of the monocular fields determined the size of the other visual dimension factors. The stimulus details are described more fully elsewhere. Thirteen subjects each viewed 25 different pairs of FOVs simultaneously, where the two FOVs differed on either the display mode factor or visual dimension factors. Each subject viewed 200 stimulus pairs consisting of 25 stimulus pairs x 2 positions (top and bottom position in display) x 4 blocks.







Fields-of-view as seen by the observer when properly fused

Figure 11. An example of a pair of stimuli from the fragmentation study, where a convergent and a divergent FOV were present simultaneously for direct comparison. The top panel shows the rectangular monocular fields on the monitor and indicates the destination eyes. The middle panel shows the monocular fields through the binoculars, and the bottom panel shows the two FOVs as experienced by 're subject when the display is fused properly. The two display modes indicated in the bottom panel are similar in every respect, except for the regions of the retinas stimulated. The shading in the two FOVs in the bottom panel indicates areas of dichoptic competition which can cause fragmentation of each FOV into three phenomenally distinct regions. For those readers who can free fuse, one can test this by fusing the two images in the middle panel. The crossed squares in the monocular fields serve as fusion locks and fixation markers.

For each stimulus pair, the subject's task was to indicate, by a button press, which of two FOVs appeared more unitary as opposed to more fragmented. Nine stimulus pairs tested the display mode factor, where the only difference between the two members of each pair was how the FOV was displayed---in the convergent mode or the divergent mode. These nine pairs differed from each other in the dimensions of the visual areas. The results indicated that subjects reported the divergent member as fragmenting significantly more than the convergent member over 90 percent of the trials in each of the nine stimulus pairs. Of the four visual dimension factors tested in the remaining 16 pairs, where each member of the pair was in the same display mode but differed in the dimensions of the visual areas, only one of the four visual dimension factors produced significant results: The FOVs with smaller binocular overlap regions tended to fragment more than the larger FOVs, although, this factor was not as powerful as the display mode factor. In this study, subjects fixated the centers of the different FOVs when making their judgements. The finding that FOVs with larger binocular overlap regions fragmented less may be based on larger overlap regions per se or it may be based on the distance to the binocular overlap border. Informal observations suggest that distance to the binocular overlap border is the important factor, however, further study separating these factors is needed. We have also found that the degree of optical convergence (or horizontal alignment of the optical axes, not to be confused with display mode convergence), is not a factor in these results. Also, the location of the visual blind spots in the nasal retinas is not a factor. These data are described more fully elsewhere. 16

6. DISCUSSION

In summary, the psychophysical data indicates that there is more luning and more fragmentation and higher thresholds in the divergent mode than in the convergent display mode. This performance decrement for divergence compared to convergence was consistent throughout the three studies despite the differences in method such as free viewing in the luning study, fixation of the probe target in the contrast study and fixation of the center of the FOV in the fragmentation study. ¹⁵⁻¹⁸ There are methods to alleviate luning in partial binocular overlap displays such as the placement of black contours in the informational eye as shown in Figure 6, or the smoothing of the binocular overlap edge in the noninformational eye. ¹¹ While the differences in contrast threshold between display conditions were not large in terms of percent contrast (see Figure 10), we still do not know how the placement or smoothing of edges to attenuate luning will effect the threshold of targets in the FOV. This is an important question for research. There are other perceptual factors which we have not considered here, such as stereopsis, and other visual and cognitive factors, such as attentional workload, which need to be tested by additional performance measures such as reaction time.

Analyses in terms of ecological optics suggest that since the visual system has never encountered anything like an HMD in its evolutionary history, the displays are interpreted in terms of possible real world configurations (see Figures 12 and 13).²³⁻²⁷ Which of the many possible configurations the visual system interprets will presumably determine the visual processing mechanisms brought into play. For example, the convergent display mode may induce less luning because it simulates viewing through an aperture, where the visual system would tend to suppress the occluding portion of the aperture. It has been suggested that this mode is ecologically more valid, closer to a natural viewing situation, than the divergent mode.¹⁰ This, despite the fact that unaided viewing is divergent. More research is needed to investigate this. Another, though not mutually exclusive, possible explanantion for our findings of convergent superiority concerns diplopia suppression. Off-fixation object points in space will project double image points as shown in Figure 14, where each of the double images will be in dichoptic

An ecological interpretation of the convergent display mode




Figure 12. One of many possible geometric configurations corresponding to the convergent display mode. The background is represented by the occluders. The monocular region portion of the monocular field of each eye falls on the temporal retina, where it is in dichoptic competition with the background falling on the nasal retina of the contralateral eye. This configuration is what would be experienced if one were viewing the world through a small aperture, where the occluders represent the opaque surface around the aperture.

competition with an unrelated image point in the contralateral eye. Because of the greater importance of near space, the suppression of image points competing dichoptically with projections from near space will be assigned a higher priority by the visual system. The results demonstrating convergence superiority may simply be a byproduct of this mechanism. Recent evidence supporting functional differences between nasal and temporal retina may support this notion; however, it is counterintuitive in light of the reported superiority of nasal over temporal retina. This is discussed in more detail elsewhere. The support of the reported superiority of nasal over temporal retina.

In designing a helmet-mounted display, there are mechanical considerations for partial overlapping visual systems. Most imaging systems could be diverged to increase the total horizontal field of view.

An ecological interpretation of the divergent display mode




Figure 13. One of many possible geometric configurations corresponding to the divergent display mode. The background is represented by the occluders. For each eye, the monocular region portion of the monocular field projects onto the nasal retina, where it is in dichoptic competition with the background, represented by the central occluder in near space, falling on the temporal retina of the contralateral eye.

However, the eyepieces for an imaging system can only be converged within the limits of the eyepiece mounting dimensions and the user's interpupillary distance for a given FOV at a useable eye relief distance. Therefore, all known wide FOV HMDs with partially overlapping fields use the diverging design approach.³³⁻³⁴ Although the convergent display mode showed a slight advantage over the divergent mode in contrast sensitivity (and luning and fragmentation) in the area of the monocular region near the overlapped region, the performance was always less than the fully overlapped binocular FOV. Whether the larger FOV provided with a partial overlapping HMD will increase flight performance or reduce workload has not been adequately evaluated.




Figure 14. Retinal projection of non-fixated object points in far space and near space. Symmetrical image points on the nasal retinas representing object points in far space are in dichoptic competition with corresponding points on the contralateral temporal retinas representing the far background. Conversely, symmetrical image points on the temporal retinas representing object points in near space are in dichoptic competition with corresponding points on the contralateral nasal retinas representing the far background.

7. ACKNOWLEDGMENTS

The authors thank Dr. Roger Wiley for his research advice and Udo Volker Nowak for his editorial review.

This work is supported by the U.S. Army Medical Research and Development Command under Contract No. DAMD17-91-c-1081.

8. REFERENCES

- 1. Kenyon, R. V., and Kneller, E. W. 1993. The effects of field of view size on the control of roll motion. <u>IEEE transactions on systems, man, and cybernetics</u>, 25(1), 183-193.
- 2. Osgood, R. K., and Wells, M. J. 1991. The effect of field-of-view size on performance of a simulated air-to-ground night attack. <u>AGARD symposium on helmet-mounted displays and night vision goggles</u> (AGARD Conference Proceedings 517), 10-1 to 10-7, Aerospace medical panel symposium, Pensacola, FL.
- 3. Wells, M. J., Venturino, M., and Osgood, R. K. 1989. The effect of field-of-view on performance at a simple simulated air-to-air mission. <u>SPIE proceedings</u>, <u>Vol. 1116</u>, <u>helmet-mounted displays</u>, 126-137. San Jose, CA: SPIE-The International Society for Optical Engineering.
- 4. Wolpert, L. 1990. Field-of-view information for self-motion perception. In (Rik Warren and Alexander H. Wertheim) Perception and control of self-motion. Hillsdale, NJ: Lawrence Earlbaum Associates.
- 5. Alam, M. S., Zheng, S. H., Iftekharuddin, K. M., and Karim, M. A. 1992. Study of field-of-view overlap for night vision applications. <u>Proceeding of the 1992 IEEE National Aerospace and Electronics Conference</u>, <u>NEACON Vol 3</u>, 1249-1255. Dayton, OH.
- 6. Edgar, G. K., Carr, K. T., Williams, M., and Clark, A. L. 1991. The effect upon visual performance of varying binocular overlap. <u>AGARD symposium on helmet-mounted displays and night vision goggles</u>, Neuilly-sur-Seine, France. (AGARD Conference Proceedings 517), 8-1 to 8-15.
- 7. Kruk, R., and Longridge, T. M. 1984. Binocular overlap in a fiber optic helmet mounted display. The image 3 conference proceedings, 363, 363-377. Brooks Air Force Base, TX: Air Force Human Resources Laboratory, Air Force Systems Command. AFHRL-TR-84-36.
- 8. Landau, F. 1990. The effect on visual recognition performance of misregistration and overlap for a biocular helmet mounted display. <u>SPIE proceedings, Vol. 1290, helmet-mounted displays II</u>, 173-184. San Jose, CA: SPIE-The International Society for Optical Engineering.
- 9. Melzer, J. E., and Moffitt, K. 1989. Partial binocular overlap in helmet-mounted displays. <u>SPIE Proceedings, Vol. 1117</u>, <u>display system optics II</u>, 56-62. San Jose, CA: SPIE-The International Society for Optical Engineering.
- 10. Melzer, J. E., and Moffitt, K. 1991. An ecological approach to partial binocular-overlap. <u>SPIE proceedings, Vol. 1456, large screen projection, ionic, and helmet-mounted displays, 175-191.</u> San Jose, CA: SPIE-The International Society for Optical Engineering.
- 11. Moffitt, K. 1989. Luning and target detection. (company working document.) San Jose, CA: Kaiser Electronics.
- 12. Moffitt, K. 1991. Partial binocular overlap: concepts, research, & systems. (company working document.) San Jose, CA: Kaiser Electronics.
- 13. Moffitt, K., and Melzer, J. 1991. Partial binocular overlap. (company working document.) San Jose, CA: Kaiser Electronics.
- 14. CAE Electronics. 1984. Wide-field-of-view, helmet-mounted infinity display system development, Brooks Air Force Base, TX: Air Force Systems Command. AFHRL-TR-84-27.
- 15. Klymenko, V., Verona, R. W., Martin, J. S., Beasley, H. H. 1994a. Factors affecting the perception of luning in monocular regions of partial binocular overlap displays. (unpublished manuscript).
- 16. Klymenko, V., Verona, R. W., Beasley, H. H., Martin, J. S. 1994. Factors affecting the visual fragmentation of the field-of-view in partial binocular overlap displays. (unpublished manuscript).
- 17. Klymenko, V., Verona, R. W., Martin, J. S., and Beasley, H. H. 1994b. The effect of binocular overlap mode on contrast thresholds across the field-of-view as a function of spatial and temporal frequency. (unpublished manuscript).

- 18. Klymenko, V., Verona, R. W., Beasley, H. H., and Martin, J. S. 1993. Binocular viewing mode affects spatio-temporal contrast threshold. <u>Association for research in vision and ophthalmology</u>, annual convention, Sarasota, FL.
- 19. Campbell, F. W., and Green, D. G. 1965. Monocular versus binocular visual acuity. Nature, 208, 315-323
- 20. Kaufman, L. 1963. On the spread of suppression and binocular rivalry. <u>Vision research</u>, 3, 401-415.
- 21. Kaufman, L. 1964. Suppression and fusion in viewing complex stereograms. <u>American journal of psychology</u>, 77, 193-205.
- 22. Fry, G. A., and Bartley S. H., 1935. The effect of one border in the visual field upon the threshold of another. American journal of physiology, 112, 414-421.
- 23. Gibson, J. J. 1979. The ecological approach to visual perception. Boston, MA: Houghton-Mifflin. 24. Barrand, A. G. 1979. An ecological approach to binocular perception: the neglected facts of occlusion. Doctoral dissertation, Cornell University.
- 25. Nakayama, K., and Shimojo, S. 1990. Da Vinci stereopsis: aepth and subjective occluding contours from unpaired image points. Vision research, 30, 1811-1825.
- 26. Ono, H., Shimono, K., and Shibuta, K. 1992. Occlusion as a depth cue in the Wheatstone-Panum limiting case. <u>Perception & psychophysics</u>, 51, 3-13.
- 27. Shimojo, S., and Nakayama, K. 1990. Real world occlusion constraints and binocular rivalry. Vision research, 30, 69-80.
- 28. Blakemore, C. 1969. Binocular depth discrimination and the nasotemporal division. <u>Journal of physiology</u>, 205, 471-497.
- 29. Fahle, M. 1987. Naso-temporal asymmetry of binocular inhibition. <u>Investigative ophthalmology and visual science</u>, 28, 1016-1017.
- 30. Fahle, M., and Schmid, M. 1988. Naso-temporal asymmetry of visual perception and of the visual cortex. Vision research, 28(2), 293-300.
- 31. Gillam, B., and Borsting, E. 1988. The role of monocular regions in stereoscopic displays. Perception, 17, 603-608.
- 32. Grigsby, S. S., and Tsou, B. H. 1993. Visual factors in the design of partial overlap binocular helmet-mounted displays. 1993 Society for Information Display International Symposium: Display Technical Papers, Seattle, WA. 185-187.
- 33. McLean, W. E., and Smith, S. 1987. Developing a wide field of view HMD for simulators. <u>SPIE Proceedings</u>, Vol. 778, <u>Display system optics</u>, 79-82. Orlando, FL: SPIE-The International Society for Optical Engineering.
 - 34. Gaines, M. 1987. Super Cockpit. Flight International, March 7, 29-34.

Initial distribution

Commander, U.S. Army Natick Research, Development and Engineering Center ATTN: SATNC-MIL (Documents Librarian) Natick, MA 01760-5040

Library Naval Submarine Medical Research Lab Box 900. Naval Sub Base Groton, CT 06349-5900

Chairman **National Transportation Safety Board** 800 Independence Avenue, S.W.

Washington, DC 20594

Commander 10th Medical Laboratory ATTN: Audiologist APO New York 09180

Naval Air Development Center Technical Information Division Technical Support Detachment Warminster, PA 18974

Commanding Officer, Naval Medical Research and Development Command National Naval Medical Center Bethesda, MD 20814-5044

Deputy Director, Defense Research and Engineering ATTN: Military Assistant for Medical and Life Sciences Washington, DC 20301-3080

Commander, U.S. Army Research Institute of Environmental Medicine Natick, MA 01760

Executive Director, U.S. Army Human Research and Engineering Directorate ATTN: Technical Library Aberdeen Proving Ground, MD 21005

Commander Man-Machine Integration System Code 602 Naval Air Development Center Warminster, PA 18974

Commander Naval Air Development Center ATTN: Code 602-B Warminster, PA 18974

Commanding Officer **Armstrong Laboratory** Wright-Patterson Air Force Base, OH 45433-6573

Director Army Audiology and Speech Center Walter Reed Army Medical Center Washington, DC 20307-5001

Commander/Director U.S. Army Combat Surveillance and Target Acquisition Lab ATTN: SFAE-IEW-JS Fort Monmouth, NJ 07703-5305 Director
Federal Aviation Administration
FAA Technical Center
Atlantic City, NJ 08405

Commander, U.S. Army Test and Evaluation Command Directorate for Test and Evaluation ATTN: AMSTE-TA-M (Human Factors Group) Aberdeen Proving Ground, MD 21005-5055

Naval Air Systems Command Technical Air Library 950D Room 278, Jefferson Plaza II Department of the Navy Washington, DC 20361

Director
U.S. Army Ballistic
Research Laboratory
ATTN: DRXBR-OD-ST Tech Reports
Aberdeen Proving Ground, MD 21005

Commander
U.S. Army Medical Research
Institute of Chemical Defense
ATTN: SGRD-UV-AO
Aberdeen Proving Ground,
MD 21010-5425

Commander
USAMRDALC
ATTN: SGRD-RMS
Fort Detrick, Frederick, MD 21702-5012

Director Walter Reed Army Institute of Research Washington, DC 20307-5100 HQ DA (DASG-PSP-O) 5109 Leesburg Pike Falls Church, VA 22041-3258

Harry Diamond Laboratories ATTN: Technical Information Branch 2800 Powder Mill Road Adelphi, MD 20783-1197

U.S. Army Materiel Systems
Analysis Agency
ATTN: AMXSY-PA (Reports Processing)
Aberdeen Proving Ground
MD 21005-5071

U.S. Army Ordnance Center and School Library Simpson Hall, Building 3071 Aberdeen Proving Ground, MD 21005

U.S. Army Environmental
Hygiene Agency
ATTN: HSHB-MO-A
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research and Development Center Aberdeen Proving Ground, MD 21010-5423

Commander
U.S. Army Medical Research
Institute of Infectious Disease
ATTN: SGRD-UIZ-C
Fort Detrick, Frederick, MD 21702

Director, Biological Sciences Division Office of Naval Research 600 North Quincy Street Arlington, VA 22217 Commandant

U.S. Army Aviation
Logistics School ATTN: ATSQ-TDN

Fort Eustis, VA 23604

Headquarters (ATMD)
U.S. Army Training
and Doctrine Command
ATTN: ATBO-M
Fort Monroe, VA 23651

IAF Liaison Officer for Safety USAF Safety Agency/SEFF 9750 Avenue G, SE Kirtland Air Force Base NM 87117-5671

Naval Aerospace Medical Institute Library Building 1953, Code 03L Pensacola, FL 32508-5600

Command Surgeon
HQ USCENTCOM (CCSG)
U.S. Central Command
MacDill Air Force Base, FL 33608

Director
Directorate of Combat Developments
ATTN: ATZQ-CD
Building 515
Fort Rucker, AL 36362

U.S. Air Force Institute of Technology (AFIT/LDEE) Building 640, Area B Wright-Patterson Air Force Base, OH 45433

Henry L. Taylor Director, Institute of Aviation University of Illinois-Willard Airport Savoy, IL 61874 Chief, National Guard Bureau ATTN: NGB-ARS Arlington Hall Station 111 South George Mason Drive Arlington, VA 22204-1382

Commander

U.S. Army Aviation and Troop Command ATTN: AMSAT-R-ES 4300 Goodfellow Bouvelard St. Louis, MO 63120-1798

U.S. Army Aviation and Troop Command Library and Information Center Branch ATTN: AMSAV-DIL4300 Goodfellow BoulevardSt. Louis, MO 63120

Federal Aviation Administration Civil Aeromedical Institute Library AAM-400A P.O. Box 25082 Oklahoma City, OK 73125

Commander
U.S. Army Medical Department
and School
ATTN: Library
Fort Sam Houston, TX 78234

Commander
U.S. Army Institute of Surgical Research
ATTN: SGRD-USM
Fort Sam Houston, TX 78234-6200

AAMRL/HEX Wright-Patterson Air Force Base, OH 45433

Air University Library
(AUL/LSE)
Maxwell Air Force Base, AL 36112

Product Manager
Aviation Life Support Equipment
ATTN: SFAE-AV-LSE
4300 Goodfellow Boulevard
St. Louis, MO 63120-1798

Commander and Director
USAE Waterways Experiment Station
ATTN: CEWES-IM-MI-R,
CD Department
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Commanding Officer Naval Biodynamics Laboratory P.O. Box 24907 New Orleans, LA 70189-0407

Assistant Commandant
U.S. Army Field Artillery School
ATTN: Morris Swott Technolal Library
Fort Sill, OK 73503-0312

Mr. Peter Seib
Human Engineering Crew Station
Box 266
Westland Helicopters Limited
Yeovil, Somerset BA20 2YB UK

U.S. Army Dugway Proving Ground Technical Library, Building 5330 Dugway, UT 84022

U.S. Army Yuma Proving Ground Technical Library Yuma, AZ 85364

AFFTC Technical Library 6510 TW/TSTL Edwards Air Force Base, CA 93523-5000 Commander Code 3431 Naval Weapons Center China Lake, CA 93555

Aeromechanics Laboratory
U.S. Army Research and Technical Labs
Ames Research Center, M/S 215-1
Moffett Field, CA 94035

Sixth U.S. Army ATTN: SMA Presidio of San Francisco, CA 94129

Commander
U.S. Army Aeromedical Center
Fort Rucker, AL 36362

Strughold Aeromedical Library
Document Service Section
2511 Kennedy Circle
Brooks Air Force Base, TX 78235-5122

Dr. Diane Damos Department of Human Factors ISSM, USC Los Angeles, CA 90089-0021

U.S. Army White Sands
Missile Range
ATTN: STEWS-M-ST
White Sands Missile Range, NM 88002

U.S. Army Aviation Engineering
Flight Activity
ATTN: SAVTE-M (Tech Lib) Stop 217
Edwards Air Force Base, CA 93523-5000

Ms. Sandra G. Hart Ames Research Center MS 262-3 Moffett Field, CA 94035 Commander
USAMRDALC
ATTN: SGRD-UMZ
Fort Detrick, Frederick, MD 21702-5009

Commander
U.S. Army Health Services Command
ATTN: HSOP-SO
Fort Sam Houston, TX 78234-6000

U. S. Army Research Institute Aviation R&D Activity ATTN: PERI-IR Fort Rucker, AL 36362

Commander
U.S. Army Safety Center
Fort Rucker, AL 36362

U.S. Army Aircraft Development Test Activity ATTN: STEBG-MP-P Cairns Army Air Field Fort Rucker, AL 36362

Commander
USAMRDALC
ATTN: SGRD-PLC (COL R. Gifford)
Fort Detrick, Frederick, MD 21702

TRADOC Aviation LO Unit 21551, Box A-209-A APO AE 09777

Netherlands Army Liaison Office Building 602 Fort Rucker, AL 36362

British Army Liaison Office Building 602 Fort Rucker, AL 36362 Italian Army Liaison Office Building 602 Fort Rucker, AL 36362

Directorate of Training Development Building 502 Fort Rucker, AL 36362

Chief USAHEL/USAAVNC Field Office P. O. Box 716 Fort Rucker, AL 36362-5349

Commander, U.S. Army Aviation Center and Fort Rucker ATTN: ATZQ-CG Fort Rucker, AL 36362

Chief
Test & Evaluation Coordinating Board
Cairns Army Air Field
Fort Rucker, AL 36362

Canadian Army Liaison Office Building 602 Fort Rucker, AL 36362

German Army Liaison Office Building 602 Fort Rucker, AL 36362

French Army Liaison Office USAAVNC (Building 602) Fort Rucker, AL 36362-5021

Australian Army Liaison Office Building 602 Fort Rucker, AL 36362

Dr. Garrison Rapmund 6 Burning Tree Court Bethesda, MD 20817 Commandant, Royal Air Force Institute of Aviation Medicine Farnborough, Hampshire GU14 6SZ UK

Defense Technical Information Cameron Station, Building 5 Alexandra, VA 22304-6145

Commander, U.S. Army Foreign Science and Technology Center AIFRTA (Davis) 220 7th Street, NE Charlottesville, VA 22901-5396

Commander
Applied Technology Laboratory
USARTL-ATCOM
ATTN: Library, Building 401
Fort Eustis, VA 23604

Commander, U.S. Air Force
Development Test Center
101 West D Avenue, Suite 117
Eglin Air Force Base, FL 32542-5495

Aviation Medicine Clinic TMC #22, SAAF Fort Bragg, NC 28305

Dr. H. Dix Christensen Bio-Medical Science Building, Room 753 Post Office Box 26901 Oklahoma City, OK 73190

Commander, U.S. Army Missile
Command
Redstone Scientific Information Center
ATTN: AMSMI-RD-CS-R
/ILL Documents
Redstone Arsenal, AL 35898

Director Army Personnel Research Establishment Farnborough, Hants GU14 6SZ UK

U.S. Army Research and Technology Laboratories (AVSCOM) Propulsion Laboratory MS 302-2 NASA Lewis Research Center Cleveland, OH 44135

Commander
USAMRDALC
ATTN: SGRD-ZC (COL John F. Glenn)
Fort Detrick, Frederick, MD 21702-5012

Dr. Eugene S. Channing 166 Baughman's Lane Frederick, MD 21702-4083

U.S. Army Medical Department and School USAMRDALC Liaison ATTN: HSMC-FR Fort Sam Houston, TX 78234

Dr. A. Kornfield 895 Head Street San Francisco, CA 94132-2813

NVESD AMSEL-RD-NV-ASID-PST (Attn: Trang Bui) 10221 Burbeck Road Fort Belvior, VA 22060-5806

CA Av Med HQ DAAC Middle Wallop Stockbridge, Hants S020 8DY UK Dr. Christine Schlichting Behavioral Sciences Department Box 900, NAVUBASE NLON Groton, CT 06349-5900

Aerospace Medicine Team HQ ACC/SGST3 162 Dodd Boulevard, Suite 100 Langley Air Force Base, VA 23665-1995

Commander
Aviation Applied Technology Directorate
ATTN: AMSAT-R-TV
Fort Eustis, VA 23604-5577

COL Yehezkel G. Caine, MD Surgeon General, Israel Air Force Aeromedical Center Library P. O. Box 02166 I.D.F. Israel

HQ ACC/DOHP 205 Dodd Boulevard, Suite 101 Langley Air Force Base, VA 23665-2789

41st Rescue Squadron 41st RQS/SG 940 Range Road Patrick Air Force Base, FL 32925-5001

48th Rescue Squadron 48th RQS/SG 801 Dezonia Road Holloman Air Force Base, NM 88330-7715 35th Fighter Wing 35th FW/SG PSC 1013 APO AE 09725-2055

66th Rescue Squadron 66th RQS/SG 4345 Tyndall Avenue Nellis Air Force Base, NV 89191-6076

71st Rescue Squadron 71st RQS/SG 1139 Redstone Road Patrick Air Force Base, FL 32925-5000

Director
Aviation Research, Development
and Engineering Center
ATTN: AMSAT-R-Z
4300 Goodfellow Boulevard
St. Louis, MO 63120-1798

Commander
USAMRDAI C
ATTN: SGRD-ZB (COL C. Fred Tyner)
Fort Detrick, Frederick, MD 21702-5012

Commandant
U.S. Army Command and General Staff
College
ATTN: ATZL-SWS-L
Fort Levenworth, KS 66027-6900