

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 96/3/18		3. REPORT TYPE AND DATES COVERED Final Technical - 12/92 to 11/95
4. TITLE AND SUBTITLE Solving Large and Dense Eigenvalue Problems that Arise in Physics			5. FUNDING NUMBERS N00014-93-1-0268	
6. AUTHOR(S) Luk, Franklin T.				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Rensselaer Polytechnic Institute 110 Eighth Street Troy, New York 12180-3590			8. PERFORMING ORGANIZATION REPORT NUMBER A-10415	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) ONR Code 251 Attn JWK, Ballston Tower One 800 North Quincy Street Arlington, VA 22217-5660			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) We worked on a fundamental problem of decomposing a signal into a small set of decay- ing complex exponentials. This problem arises in a wide range of disciplines, inclu- ding nuclear magnetic resonance, speech processing and system identification. We developed a new class of numerical algorithms, and gave a simple, purely linear alge- braic proof on why our new approach works. Our class contains two arbitrary matrices F and G. Specific choices of these two matrices result in Prony's and Kung's methods. So all our theoretical results cover the two procedures. This advance is important, for Kung's proof can be difficult to digest. Other choices of F and G give rise to new methods with other desirable characteristics; e.g., our new Hankel QRD method is about ten times faster than Kung's scheme, also known as the Hankel SVD method. Another attraction of the QRD approach is that it is easily updatable to accommodate new data, which is not so for an SVD technique.				
14. SUBJECT TERMS signal enhancement, harmonic retrieval, matrix pencil, denoising			15. NUMBER OF PAGES 9 (total)	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED
				20. LIMITATION OF ABSTRACT UL

19960717 020

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to ***stay within the lines*** to meet ***optical scanning requirements***.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.



Rensselaer

Department of Computer Science

March 18, 1996

Scientific Officer Code: 1111MA
Richard L. Lau
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dear Dick:

In accordance with Attachment Number 2 under Grant No. N00014-93-1-0268, enclosed please find my Final Technical Report. Please contact me if you have any questions.

Thank you very much for supporting my work. I really appreciate it.

Sincerely,

Franklin T. Luk
Principal Investigator

Enclosures (3)

cc:Administrative Grants Officer (1)
Director, Naval Research Laboratory (1)
Defense Technical Information Center (2) ✓

DTIC QUALITY INSPECTED 1

1. Problem of Interest

We worked on a fundamental problem:

- Decompose a signal into a small set of decaying complex exponentials.

Usually, a limited sequence $\{s_k\}$ of noisy samples is available and the physics of the problem implies that the noiseless exponentials are damped sinusoids. The formal signal model is

$$s_k = \sum_{r=1}^R a_r z_r^{k-1}, \quad (1)$$

where the coefficients $\{a_r\}$ and knots $\{z_r\}$ are $2R$ unknowns to be determined. This problem arises in a wide range of disciplines, including nuclear magnetic resonance [1], speech processing [3], and system identification [4]. Two effective solution procedures were given by Prony in 1795 [5] and S.Y. Kung *et al.* in 1983 [4]. Unfortunately, Prony's method is relatively unknown and Kung's method and associated proof are tightly bound to the application in system identification.

1.1. Our Contributions

We developed a new class of numerical algorithms for solving this exponential approximation problem. Our class includes both methods of Prony and Kung as special cases. We gave a simple, purely linear algebraic proof on why our new approach works.

2. Novel Matrix Pencil Approach

The samples $\{s_k\}$ are laid out as entries in a Hankel matrix:

$$H^{K \times L} \equiv \begin{pmatrix} s_1 & s_2 & s_3 & \cdots & s_L \\ s_2 & s_3 & s_4 & \cdots & s_{L+1} \\ s_3 & s_4 & s_5 & \cdots & s_{L+2} \\ \vdots & \vdots & \vdots & & \vdots \\ s_K & s_{K+1} & s_{K+2} & \cdots & s_{K+L-1} \end{pmatrix},$$

where $K > R$. MatLab-like notations are used for matrix indexing, e.g., the colon ':' indicates a range (hence $A_{3,:}$ refers to the third row of A). We devised a new matrix pencil procedure for computing $\{z_r\}$, after which we would solve a special (called Yule-Walker) set of linear equations to find $\{a_r\}$. For full generality, we introduce two arbitrary but nonsingular transformations F and G , where F is $(K-1) \times (K-1)$ and G is $L \times L$. Define two new $(K-1) \times L$ matrices $C^{[1]}$ and $C^{[2]}$ by

$$C^{[1]} \equiv FH_{1:K-1,:}G \quad \text{and} \quad C^{[2]} \equiv FH_{2:K,:}G.$$

Consider the matrix pencil problem:

$$C^{[2]}y = \zeta C^{[1]}y.$$

We proved that solutions exist such that Y is a $L \times R$ matrix of linearly independent eigenvectors:

$$C^{[2]}Y = C^{[1]}YD_{\zeta}^R, \quad (2)$$

where D_{ζ}^R denotes a $R \times R$ diagonal matrix of eigenvalues $\{\zeta_l\}$. In addition, we also proved that $\{\zeta_l\} = \{z_r\}$.

Matrix Pencil Method.

Step 1. Choose matrices F and G .

Step 2. Solve the matrix pencil: $C^{[2]}Y = C^{[1]}YD_{\zeta}^R$. Set $\{\zeta_l\} = \{z_r\}$.

2.1. Our Contributions

The important result is that $\{\zeta_l\} = \{z_r\}$, so that eigenvalues of the matrix pencil provide the required solution. A huge benefit is the freedom to choose F and G . Specific choices result in Prony's and Kung's methods. Other choices of F and G could give us new methods with other desirable characteristics.

3. Full Column Rank Case

Both Prony's and Kung's methods assume full column rank, i.e., $L = R$. Hence the matrix Y is $R \times R$ and nonsingular and (2) becomes $C^{[2]} = C^{[1]}(YD_{\zeta}^R Y^{-1})$. Define $X \equiv YD_{\zeta}^R Y^{-1}$. We see that X satisfies

$$C^{[1]}X = C^{[2]}. \quad (3)$$

The matrix equation (3) is usually overdetermined; in the presence of noise, X may be solved by least-squares or total least-squares methods. The matrix pencil method simplifies to an eigenvalue procedure.

Eigenvalue Method.

Step 1. Choose matrices F and G .

Step 2. Find X by solving the linear equations: $C^{[1]}X = C^{[2]}$.

Step 3. Find an eigenvalue decomposition of X : $X = YD_{\zeta}^R Y^{-1}$. Set $\{\zeta_l\} = \{z_r\}$.

3.1. Prony's Procedure.

Prony further assumed that $K = R + 1$. Hence the matrices $C^{[1]}$ and $C^{[2]}$ are $R \times R$. Choose $F = I^{R \times R}$ and $G = H_{1:R,1:R}^{-1}$. So $C^{[1]} = I^{R \times R}$ and (3) simplifies to $X = C^{[2]}$. Note that

$$C^{[2]} = H_{2:R+1,1:R} H_{1:R,1:R}^{-1} = \begin{pmatrix} 0 & 1 & 0 & \cdots & 0 & 0 \\ 0 & 0 & 1 & \cdots & 0 & 0 \\ 0 & 0 & 0 & \cdots & 0 & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & 0 & \cdots & 0 & 1 \\ -\gamma_0 & -\gamma_1 & -\gamma_2 & \cdots & -\gamma_{R-2} & -\gamma_{R-1} \end{pmatrix},$$

where the $\{\gamma_i\}$ satisfy the Yule-Walker equation. Hence $C^{[2]}$ is a companion matrix to the polynomial $p_R(z)$, defined by $p_R(z) = \gamma_0 + \gamma_1 z + \cdots + \gamma_{R-1} z^{R-1} + z^R$.

Prony's Method.

Step 1. Choose $F = I^{R \times R}$ and $G = H_{1:R,1:R}^{-1}$.

Step 2. Solve the Yule-Walker equation.

Step 3. Find the roots $\{z_r\}$ of the Prony polynomial $p_R(z)$. Set $\{\zeta_l\} = \{z_r\}$.

3.2. Kung's Procedure

Start by computing a singular value decomposition (SVD) of a $K \times R$ Hankel matrix H : $H = U\Sigma V^H$. Choose $F = I^{(K-1) \times (K-1)}$ and $G = V\Sigma^{-1}$. Then $C^{[1]} = U_{1:K-1,:}$ and $C^{[2]} = U_{2:K,:}$. So (3) reduces to $U_{1:K-1,:}X = U_{2:K,:}$. An important advantage of Kung's method over Prony's procedure is that the polynomial $p_R(z)$ is not explicitly computed.

Kung's Method.

Step 1. Choose $F = I^{(K-1) \times (K-1)}$ and $G = V\Sigma^{-1}$. Compute an SVD of H : $H = U\Sigma V^H$.

Step 2. Solve the matrix equation: $U_{1:K-1,:}X = U_{2:K,:}$.

Step 3. Find an eigenvalue decomposition of X : $X = YD_{\zeta}^R Y^{-1}$. Set $\{\zeta_l\} = \{z_r\}$.

3.3. Our Contributions

We showed that our matrix pencil scheme includes both Prony's and Kung's methods as special cases. So all our theoretical results, including the purely linear algebraic proof on why our new method works, cover these two procedures too. This is an important advance, for Kung's proof [4] can be difficult to digest.

4. New Methods

We may replace the expensive SVD by other techniques. The only restriction is that we need to operate on H from the left side. An example of a much cheaper, and yet almost as accurate, technique is the QR decomposition (QRD). Compute a QR decomposition of a $K \times R$ Hankel matrix H : $H = QR$. Choose $F = I^{(K-1) \times (K-1)}$ and $G = R^{-1}$. We find that $C^{[1]} = Q_{1:K-1,:}$ and $C^{[2]} = Q_{2:K,:}$. So (3) reduces to

$$Q_{1:K-1,:}X = Q_{2:K,:} \quad (4)$$

Hankel QRD Method.

Step 1. Choose $F = I^{(K-1) \times (K-1)}$ and $G = R^{-1}$.

Step 2. Solve the linear equations: $Q_{1:K-1,:}X = Q_{2:K,:}$.

Step 3. Find an eigenvalue decomposition of X : $X = YD_{\zeta}^R Y^{-1}$. Set $\{\zeta_i\} = \{z_r\}$.

4.1. Our Contributions

Our new Hankel QRD method is about ten times faster than Kung's scheme (also known as the Hankel SVD method). An attractive property of the QRD approach is that it is easily updatable to accommodate new data, which is not so for an SVD technique.

5. Denoising

Our problem is particularly sensitive to errors in the samples $\{s_k\}$, and a preliminary noise removal procedure is all-important. We assume an additive error model:

$$H = H^{[s]} + H^{[n]},$$

where $H^{[s]}$ and $H^{[n]}$ denote the signal and noise components of H , respectively. The SVD of the signal matrix H provides a convenient and numerically stable way to determine the noise subspace. Indeed, it often suffices to find a "gap" in the entries on the diagonal of Σ . Unfortunately, the Hankel structure of H is almost certainly lost in $H^{[s]}$. Cadzow [2] proposed to iterate signal extraction with the SVD followed by a restoration of the Hankel structure via averaging along the antidiagonals. He showed that under relatively mild assumptions this procedure will converge and reported very good noise removal performance.

5.1. Our Contributions

First, we constructed a counter-example for Cadzow's method, and showed that it will converge to a Hankel matrix of the wrong rank.

Second, we proposed a new approach based on the following decomposition:

$$H = V^{K \times M}(z) D_a^M V^{L \times M}(z)^T, \quad (5)$$

where $V^{K \times M}(z)$ and $V^{L \times M}(z)$ are respectively $K \times M$ and $L \times M$ Vandemonde matrices, and the middle matrix D_a^M is diagonal. If $K \geq M$, $L \geq M$ and all the $\{z_r\}$ values are distinct, then the Hankel matrix H has exact rank M . We examined algorithms to determine the factorization (5) for a given Hankel matrix. It seems reasonable to attempt to synthesize another Hankel matrix $\hat{H}$ of rank R , where $R < M$, from zeroing out $(M - R)$ of the $\{a_r\}$ values. However, selecting which a_r to set to zero is a nontrivial task. Unlike singular vectors, the columns of a Vandemonde matrix are not orthonormal. Hence, it is not always appropriate to select the R largest (in magnitude) a_r 's to synthesize a good approximation to H . Our work is still in progress.

6. Combined Technique

In our overall computation, we chose to grossly “overestimate” the rank R of the available samples. Just as in Prony’s method, we would pick R so that the matrices were square. Figure 1 shows a cloud of zeros from the resulting polynomial for an example where the numerical rank of the signal was five, but a 65×65 noisy system had been solved. This example is taken from Van Huffel [6]; the signal-to-noise ratio is approximately 2.4 (not dB).




Figure 1. Prony’s method with 65 degrees of freedom on data with numerical rank 5. The ‘+’ are the computed z values while the exact values are depicted with ‘x’.

With the common assumption that the noise space is approximately orthogonal to the signal subspace, we would expect that a few components will still fit the embedded signal while most other zeros serve as outlets to fit the noise. Our numerical experiments seem to confirm this conjecture. Given our stability criterion, it is logical to discard those zeros (of the polynomial) that are greater than one in magnitude and hence cannot correspond to a stable component of the signal. Figure 2 shows the result.




Figure 2. **left:** The discrete Fourier spectrum of the given noisy signal. **right:** The spectrum after removing the unstable z values and computing the new samples s . The dashed curve shows the noiseless spectrum in both plots.

6.1. Our Contributions

There is a significant difference between our approach and Prony’s method: we fix N , the number of samples, and choose $R = \lfloor N/2 \rfloor$, whereas Prony fixed R , the rank of the matrix, and chose $N = 2R$. With noise, the Hankel matrix we get is always nonsingular. Our scheme has the important advantage that we do not need to decide on R at the very beginning. Another benefit is that the resultant Yule-Walker is square and can be solved using any of the well known techniques.

References

- [1] H. Barkhuijsen, R. de Beer and D. van Ormondt. Improved Algorithm for Noniterative Time-Domain Model Fitting to Exponentially Damped Magnetic Resonance Signals. *J. Magn. Reson.*, vol. 73 (1987), pp. 553-557.
- [2] J.A. Cadzow. Signal Enhancement – A Composite Property Mapping Algorithm. *IEEE Trans. Acoust., Speech, Signal Processing*, vol. 36 (1988), pp. 49-62.
- [3] R. Kumaresan and D.W. Tufts. Estimating the Parameters of Exponentially Damped Sinusoids and Pole-Zero Modeling in Noise. *IEEE Trans. Acoust. Speech and Sig. Proc.*, ASSP-30 (1982), pp. 833-840.
- [4] S.Y. Kung, K.S. Arun and B.D. Rao. State-Space and Singular Value Decomposition-based Approximation Methods for the Harmonic Retrieval Problem. *J. Opt. Soc. Am.*, vol. 73 (1983), pp. 1799-1811.
- [5] R. Prony. Essai Expérimental et Analytique sur les Lois de la Dilatabilité et sur celles de la Force Expansive de la Vapeur de l'Eau et de la Vapeur de l'Alcool, à Différentes Températures. *J. de l'École Polytechnique*, vol. 1 (1795), pp. 24-76.
- [6] S. Van Huffel. Enhanced Resolution Based on Minimum Variance Estimation and Exponential Data Modeling. *Signal Processing* vol. 33 (1993), pp. 333-355.