

O

AR-009-701

DSTO-GD-0093

F

Shear Rate Determination in a  
Concentric Cylinder Viscometer

H.H. Billon

S

EXEMPTION STATEMENT R  
Approved for public release  
Distribution Unlimited

1

19961009 132

] APPROVED FOR PUBLIC RELEASE

© Commonwealth of Australia

---

THE UNITED STATES NATIONAL  
TECHNICAL INFORMATION SERVICE  
IS AUTHORIZED TO  
REPRODUCE AND SELL THIS REPORT

---

# Shear Rate Determination in a Concentric Cylinder Viscometer

*H.H. Billon*

Ship Structures and Materials Division  
Aeronautical and Maritime Research Laboratory

DSTO-GD-0093

## ABSTRACT

A method is described for the determination of the true shear rate in a concentric cylinder viscometer. A computer program based on the MacSporran technique is used. The program is tested on model as well as real fluids and is shown to be satisfactory. Shear rate determination in yield stress and time-dependent fluids is also discussed.

## RELEASE LIMITATION

*Approved for public release*

**DTIC QUALITY INSPECTED 2**

DEPARTMENT OF DEFENCE

---

DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION

*Published by*

*DSTO Aeronautical and Maritime Research Laboratory  
PO Box 4331  
Melbourne Victoria 3001*

*Telephone: (03) 9626 8111  
Fax: (03) 9626 8999  
© Commonwealth of Australia 1996  
AR No. 009-701  
June 1996*

**APPROVED FOR PUBLIC RELEASE**

# Shear Rate Determination in a Concentric Cylinder Viscometer

## Executive Summary

Materials with a complex rheology are often encountered during investigation of the flow behaviour of explosives. These materials may be studied with a concentric cylinder rotational viscometer. This type of viscometer allows ease of sample insertion and ease of cleaning after use.

However, there is a problem associated with determining the true shear rate in a concentric cylinder viscometer. This is because the shear rate usually has to be calculated using a rheological model that describes the fluid under investigation. This fluid model is often unknown. In this paper a computational method is described. This method permits determination of the true shear rate from experimental data without recourse to a fluid model.

The method consists of determining the shear rates from the measured values of the shear stress and angular velocity. The shear rate at each data point is determined from an integral equation using a technique outlined by MacSporran. A computer program based on this technique was written and tested on model fluids and real fluids and shown to be satisfactory. Shear rate determination in yield stress and time-dependent fluids is also discussed.

---

# Contents

1. INTRODUCTION.....	1
2. DESCRIPTION OF THE PROBLEM.....	1
3. DETERMINATION OF THE SHEAR RATE BY SOLUTION OF AN INTEGRAL EQUATION .....	2
3.1 Description of the Method .....	2
3.2 The Computer Program.....	5
3.3 Yield Stress Fluids.....	6
4. REFERENCES.....	7

## 1. Introduction

In examining the flow behaviour of explosives it is often necessary to make an assessment of mixtures that are rheologically complex - An example is the suspension of one explosive in another, as occurs with suspensions of either RDX [1,2] or TATB [3] in molten TNT. At AMRL such studies are carried out in a Haake RV2 viscometer which operates on the concentric cylinder principle [4]. Such geometry allows ease of sample insertion and, after use, ease of cleaning. However, there is a problem associated with determining the true shear rate at the spinning rotor. This arises because the true shear rate usually has to be calculated using a rheological model that describes the fluid under investigation. This fluid model is often unknown.

In this paper a computational method is described. This method determines true shear rates from experimental data without recourse to a fluid model.

## 2. Description of the Problem

For any fluid the true shear rate  $\dot{\gamma}$  cannot easily be calculated unless there is only a very small gap between the bob and the cup. In this case the shear rate approaches a value given by

$$\dot{\gamma} = R_1 \Omega / (R_2 - R_1) \quad (1)$$

Where  $\dot{\gamma}$  is the shear rate,  $R_1$  is the bob radius,  $R_2$  is the cup radius and  $\Omega$  is the angular velocity of the bob. This relationship is independent of fluid properties.

Experimentally, however, it is impractical to use extremely small gaps, especially when suspensions of large particles are being investigated [4].

The problems associated with the determination of true shear rate are further exacerbated by the fact that many widely promoted, commercially available software packages sold by instrument manufacturers for automatic determination of shear rate erroneously employ the equation:

$$\dot{\gamma} = 2\Omega \epsilon^2 / (\epsilon^2 - 1) \quad (2)$$

which is strictly only valid for the determination of shear rates in Newtonian fluids. Here  $\epsilon$  is the ratio of cup to bob radii. This equation is a special case of a more general equation

$$\dot{\gamma} = 2 \left( \frac{\Omega}{n} \right) \epsilon^{2/n} / (\epsilon^{2/n} - 1) \quad (3)$$

which is valid for any power-law fluid. For a Newtonian fluid,  $n = 1$ .

Not all fluids can be described as "power-law fluids" whose behaviour follows equation (3). Some fluids exhibit a yield stress which can lead to incomplete shearing in the annular gap of the viscometer; a plot of measured rotational speed versus shear rate cannot always be described by a simple model and this is a further complication [6].

For some yield stress fluids the shear rate is given by a relationship such as

$$\dot{\gamma} / \dot{\gamma}_n = \frac{1 - \left(R_1 / R_2\right)^2}{1 - \left[1 / \left\{\left(R_y / R_1\right)^2 - 1\right\}\right] \ln \left(R_y / R_1\right)^2} \quad (4)$$

These are called "Bingham plastics" [5]. Here  $\dot{\gamma}_n$  is the apparent shear rate and  $R_y$  is the yield radius.

Krieger and Elrod [7] express the shear rate in a concentric cylinder viscometer in the form of an Euler-Maclaurin series,

$$\dot{\gamma} = \left(\Omega / \ln \varepsilon\right) \left[ 1 + \ln \varepsilon \left( d \ln \Omega / d \ln \tau \right) + \left( (\ln \varepsilon)^2 / 3 \Omega \right) \left( d^2 \Omega / d (\ln \tau)^2 \right) - \dots \right] \quad (5)$$

Such an expression does not require any assumptions to be made about the fluid model and may be used as the basis for a technique to determine the true shear rate in a concentric cylinder viscometer. This method would require the determination of derivatives in the torque versus rotation speed curve that is obtained as raw data. Techniques involving differentiation have been used by e.g. Nguyen et al. [6] and Krieger and Maron [9]. However, differentiation of discrete data can be noisy and inaccurate, particularly when high order derivatives must be determined. This problem could be overcome if a technique involving integration could be used.

### 3. Determination of the Shear Rate by Solution of an Integral Equation

#### 3.1 Description of the Method

The approach followed is outlined by MacSporran in [8]. The shear rate is evaluated by solving the integral relationship

$$\Omega = 0.5 \int_{\tau_1}^{\tau_2} \left( f(\tau) / \tau \right) d\tau \quad (6)$$

Here  $\tau_1$  and  $\tau_2$  are the shear stresses at the inner and outer cylinders, respectively.



Experimental data is obtained in the form  $(\Omega_n, \tau_n)$ , where  $\Omega_n$  is the angular velocity of the bob and  $\tau_n$  is the shear stress at either the bob or the cup. In this case  $\tau_n$  will be the stress at the bob. Therefore the problem is to determine the shear rates  $f(\tau_n)$  at each of the points  $(\Omega_n, \tau_n)$  by solution of the equation

$$\Omega(\tau_n) = \int_{c_n}^n w(\tau) f(\tau) d\tau \quad (7)$$

Here  $c_n = \tau_n / \varepsilon^2$  represents the shear stress at the cup and  $w(\tau) = 1/2\tau$  is a 'weighting function'.

The integral in equation (7) is regarded as the contribution from a number of strips in  $(\tau, f(\tau))$  space. For example, suppose we are testing a fluid in a viscometer that possesses a cup to bob radius ratio of  $\varepsilon = 1.2$  and that we obtain the following  $(\Omega, \tau)$  measurements:

$(1.4382 \times 10^{-2}, 1), (5.7527 \times 10^{-2}, 2), (0.1294, 3), (0.2301, 4)$ . (See Table 1).

The angular velocity at  $\tau_n = 4$  Pa would consist of contributions from the following strips:

strip 1:  $2.78 \text{ Pa} \leq \tau \leq 3 \text{ Pa}$

strip 2:  $3 \text{ Pa} \leq \tau \leq 4 \text{ Pa}$

Here 2.78 Pa is the stress at the cup when the stress at the bob is 4 Pa (i.e.  $4\text{Pa} / (1.2)^2$ ).

In general, for a bob stress  $\tau = \tau_n$ , the strips would possess the integration limits  $c_n$  and  $\tau_i$ , where the  $\tau_i$  lie between  $c_n$  and  $\tau_n$ .

Table 1: An explanation of the method of determining the number of strips for each data point.

Measured $\Omega$ (Rad/s)	Measured $\tau$ (at the bob) (Pa)	$\tau$ at the cup (Pa)	No. of data points with bob $\tau$ values lying between the cup and bob $\tau$ values of this data point.	No. of strips for this data point.
$1.4382 \times 10^{-2}$	1	0.69	0	1
$5.7527 \times 10^{-2}$	2	1.39	0	1
0.1294	3	2.08	0	1
0.2301	4	2.78	1*	2

\* Meaning the data point for which the measured  $\tau$  value is 3 Pa. Because  $2.78 < 3 < 4$ .

The shear rate  $f(\tau)$  is approximated in each strip by a cubic polynomial which interpolates to  $f(\tau)$  at four successive data points. Modifications are necessary to the interpolation points at the extremities of the data set [8]. In any event, the strip contribution, which is of the form  $\int_{x_p}^{x_q} w(\tau)f(\tau)d\tau$ , is rewritten (after approximating the shear rate by a cubic polynomial  $P_3(x)$ ) in the form:

$$\int_{x_p}^{x_q} w(x)P_3(x)dx = \sum_{l=j-2}^{l=j+1} W_l^j f_l \quad (8)$$

where  $x$  is the shear stress,  $x_p$  and  $x_q$  are the strip integration limits and the  $f_l$  are the desired shear rate values. Details of the method are given by MacSporran [8]. A brief summary is given below.

After summing contributions for all strips (for a given data point), the following expression is obtained for  $\Omega_n$ :

$$\Omega_n = \sum_{k=j}^{k=n} \sum_{l=k-2}^{l=k+1} W_l^k f_l = \sum_{l=j-2}^{l=n+1} W_{nl} f_l \quad (9)$$

Here  $W_{nl} = \sum_{k=j}^{k=n} W_l^k$  are the composite weights.

The integration weights for the individual strips are obtained from:

$$\begin{bmatrix} 1 & 1 & 1 & 1 \\ x_1 & x_2 & x_3 & x_4 \\ (x_1)^2 & (x_2)^2 & (x_3)^2 & (x_4)^2 \\ (x_1)^3 & (x_2)^3 & (x_3)^3 & (x_4)^3 \end{bmatrix} \begin{bmatrix} W_1 \\ W_2 \\ W_3 \\ W_4 \end{bmatrix} = \begin{bmatrix} M_1 \\ M_2 \\ M_3 \\ M_4 \end{bmatrix} \quad (10)$$

Here  $M_r = \int_{x_p}^{x_q} x^{r-1} w(x)dx$ .

Once the integration weights for the individual strips have been found they are used to calculate the composite weights. The shear rates  $f_n = f(\tau_n)$  for the data points 1 to  $N$  are calculated from:

$$\begin{bmatrix} W_{11} & W_{12} & \rightarrow & W_{1N} \\ W_{21} & W_{22} & \rightarrow & W_{2N} \\ \downarrow & \downarrow & & \downarrow \\ W_{N1} & W_{N2} & \rightarrow & W_{NN} \end{bmatrix} \begin{bmatrix} f_1 \\ f_2 \\ \downarrow \\ f_N \end{bmatrix} = \begin{bmatrix} \Omega_1 \\ \Omega_2 \\ \downarrow \\ \Omega_N \end{bmatrix} \quad (11)$$

### 3.2 The Computer Program

A BASIC computer program (called "SHEARE.RAT" ) has been written to perform the above calculations. The program requires input of the radius ratio for the concentric cylinder viscometer. The shear stress values at the viscometer bob and the rotation speed values are also input. The number of strips for each data point are determined by finding all the bob shear stress values that lie between the cup shear stress value and bob shear stress value for the data point. The program then determines the moments and weights.

In order to test the program,  $(\Omega_n, \tau_n)$  pairs were generated for a power law fluid with a constitutive equation of the form  $\tau = 3\dot{\gamma}^{0.5}$ . These  $(\Omega_n, \tau_n)$  values were then used as 'data' for the program. The results are presented in Table 2. In this case perfect agreement was achieved between the actual shear rates and the shear rates as calculated by "SHEARE.RAT". Another test was conducted using the solids GR-S latex data of Krieger and Maron [9] and these results are presented in Table 3. For comparison, the shear rates as determined by the Tanner and Williams method [10, 11] as well as by MacSporran [8] using the present method, are tabulated. Very good agreement is again obtained.

Table 2: A Comparison of the Actual Shear Rate with the Shear Rate as Calculated by "SHEARE.RAT" for a Power Law Fluid with Equation  $\tau = 3\dot{\gamma}^{0.5}$ .

$\tau$ (Pa)	$\Omega$ (Rad/s)	$\dot{\gamma}$ Actual (s <sup>-1</sup> )	$\dot{\gamma}$ Calculated (s <sup>-1</sup> )
1	$1.4382 \times 10^{-2}$	0.1111	0.1111
2	$5.7527 \times 10^{-2}$	0.4444	0.4444
3	0.1294	1.000	1.000
4	0.2301	1.778	1.778
5	0.3595	2.778	2.778
6	0.5177	4.000	4.000
7	0.7047	5.444	5.444
8	0.9204	7.111	7.111
9	1.1649	9.000	9.000
10	1.4381	11.11	11.11
11	1.7402	13.44	13.44
12	2.0710	16.00	16.00
13	2.4305	18.78	18.78
14	2.8188	21.78	21.78
15	3.2359	25.00	25.00

Table 3: Shear rates calculated by the Tanner and Williams method [10, 11], by MacSporran [8] and by "SHEARE.RAT" for the solids GR-S latex data of Krieger and Maron [9].

$\tau$ (Pa)	$\Omega$ (Rad/s)	$\dot{\gamma}$ Tanner & Williams (s <sup>-1</sup> )	$\dot{\gamma}$ MacSporran (s <sup>-1</sup> )	$\dot{\gamma}$ Present Work (s <sup>-1</sup> )
3.807	0.03670	0.7283	0.7211	0.7211
5.706	0.1310	2.611	2.528	2.528
9.536	0.6020	11.43	11.40	11.40
15.24	1.940	35.60	35.81	35.81
19.03	3.120	57.61	57.17	57.17
22.83	4.660	85.33	85.66	85.66
26.65	6.410	116.7	116.3	116.2
30.45	8.330	150.9	151.1	151.1
34.25	10.45	187.5	188.1	188.1
38.07	12.51	222.6	220.4	220.7
53.27	21.70	385.4	387.2	387.0
68.48	32.20	568.9	563.1	563.8

The program was run on an IBM-compatible PC (80486 processor and 640k base memory) and it was found that there were restrictions, due to memory, on the number of data points that could be processed. The maximum number of points that could be analysed at a time was seventeen. The program required 4 seconds to analyse seventeen points. Improvements in the software and computer memory would increase the efficiency of this program.

### 3.3 Yield Stress Fluids

The program can be used to determine the shear rates for many types of fluids once adequate rotation speed and torque data have been obtained. However, care must be exercised when dealing with plastic fluids i.e. those exhibiting a yield stress. In such cases the integration method cannot always be used if a fixed viscometer radius ratio is assumed.

If it is necessary to determine the shear rate in a non time-dependent yield stress fluid, the following procedure is recommended. The yield stress must first be accurately determined. A simple method for directly measuring the yield stress is described in [12]. The next step is to determine whether there is partial or complete shearing in the viscometer gap. Partial shear will occur when  $\tau_1/\varepsilon^2 < \tau_y < \tau_1$  and shear will only occur between the viscometer bob and a cylindrical surface at a radial distance  $R_p = R(\tau_1/\tau_y)^{0.5}$ . This distance is clearly less than the width of the entire gap. For the case of partial shear the shear rate may be precisely determined by means of the following equation [6].

$$\dot{\gamma}_1 = 2\Omega \left( d \ln \tau_1 / d \ln \Omega \right)^{-1} \quad (12)$$

The derivative may be determined e.g. by graphical differentiation of a double log plot of the original stress versus rotation speed data. For the completely sheared situation of a time-independent yield stress fluid, the shear rate may be determined by means of the described computer program.

The case of time-dependent fluids that also exhibit a yield stress is much more complex. An approximate procedure for shear rate determination in this case is presented in [6].

## 4. References

1. Parry, M. A. and Billon, H. H. (1988) Rotational Viscometry Investigation of Explosives: Molten TNT and RDX/TNT Suspensions, *10th International Congress on Rheology, Sydney*, **2**, 163.
2. Eadie, J. (1971). *The Viscosity of RDX/TNT Suspensions* (MRL Report 431). Maribyrnong, Vic: Materials Research Laboratory.
3. Billon, H. H. and Parry, M. A. (1991). *The Viscosity of TATB Types A and B Suspensions in Molten TNT. General Characteristics*. (MRL Technical Report MRL-TR-91-24). Maribyrnong, Vic: Materials Research Laboratory.
4. Schramm, G. (1981). *Optimization of Rotovisco Tests*, Gebruder HAAKE GmbH.
5. Bhattacharya, S. N. et al. (1987). *Flow and Rheological Measurements of Complex Fluids*. Rheology Science and Technology Centre (Royal Melbourne Institute of Technology).
6. Nguyen, Q. D. and Boger, D. V. (1987) Characterization of Yield Stress Fluids with Concentric Cylinder Viscometers, *Rheologica Acta*, **26**, 508.
7. Krieger, I. M. and Elrod, H. (1953) Direct Determination of the Flow Curves of Non-Newtonian Fluids. II. Shearing Rate in the Concentric Cylinder Viscometer, *Journal of Applied Physics*, **24**, 134.
8. MacSporran, W. C. (1986) Direct Numerical Evaluation of Shear Rates in Concentric Cylinder Viscometry, *Journal of Rheology*, **30**, 125.
9. Krieger, I. M. and Maron, S. H. (1954) Direct Determination of the Flow Curves of Non-Newtonian Fluids. III. Standardized Treatment of Viscometric Data, *Journal of Applied Physics*, **25**, 72.
10. Tanner, R. I. and Williams, G. (1970) Iterative Numerical Methods for Some Integral Equations Arising in Rheology. *Transactions of the Society of Rheology*, **14**, 19.

11. Williams, G. and Tanner, R. I. (1970) Appendix. Iterative Numerical Methods for Some Integral Equations Arising in Rheology. *Bulletin of the British Society of Rheology*, **13**, 122.
12. Dzuy, N. Q. and Boger, D. V. (1985) Direct Yield Stress Measurement with the Vane Method, *Journal of Rheology*, **29**, 335.

## Shear Rate Determination in a Concentric Cylinder Viscometer

Horace Billon

### DISTRIBUTION LIST

#### AUSTRALIA

TASK SPONSOR: DSTO

DEFENCE ORGANISATION

Defence Science and Technology Organisation

Chief Defence Scientist	} shared copy
FAS Science Policy	
AS Science Corporate Management	
Counsellor Defence Science, London (Doc Data Sheet only)	
Counsellor Defence Science, Washington	
Scientific Adviser to MRDC Thailand (Doc Data Sheet Only)	
Senior Defence Scientific Adviser/Scientific Adviser Policy and Command (shared copy)	
Navy Scientific Adviser (3 copies Doc Data Sheet and one copy of the distribution list)	
Scientific Adviser - Army (Doc Data Sheet and distribution list only)	
Air Force Scientific Adviser	
Director Trials	

#### Aeronautical and Maritime Research Laboratory

Director (AMRL only)  
 Chief, Weapons Systems Division  
 RLLWS  
 RLMPP  
 Mr R. Parker  
 Mr H. Billon

#### DSTO Library

Library Fishermens Bend  
 Library Maribyrnong  
 Library DSTOS ( 2 copies)  
 Library, MOD, Pyrmont (Doc Data Sheet only)

#### Defence Central

OIC TRS, Defence Central Library  
 Officer in Charge, Document Exchange Centre (DEC), 1 copy  
     DEC requires the following copies of public release reports to meet  
     exchange agreements under their management:  
     \*US Defence Technical Information Centre, 2 copies  
     \*UK Defence Research Information Centre, 2 copies  
     \*Canada Defence Scientific Information Service, 1 copy  
     \*NZ Defence Information Centre, 1 copy  
     National Library of Australia, 1 copy  
 Defence Intelligence Organisation  
 Library, Defence Signals Directorate (Doc Data Sheet only)

**Army**

Director General Force Development (Land) (Doc Data Sheet only)  
ABCA Office, G-1-34, Russell Offices, Canberra (4 copies)

**Navy**

Director General Force Development (Sea), (Doc Data Sheet only)

**UNIVERSITIES AND COLLEGES**

Australian Defence Force Academy  
Library  
Head of Aerospace and Mechanical Engineering  
Senior Librarian, Hargrave Library, Monash University  
Librarian Flinders University

**OTHER ORGANISATIONS**

NASA (Canberra  
AGPS

**ABSTRACTING AND INFORMATION ORGANISATIONS (Public Release only)**

INSPEC: Acquisitions Section Institution of Electrical Engineers  
Library, Chemical Abstracts Reference Service  
Engineering Societies Library, US  
American Society for Metals  
Documents Librarian, The Center for Research Libraries, US

**INFORMATION EXCHANGE AGREEMENT PARTNERS (PUBLIC RELEASE ONLY)**

Acquisitions Unit, Science Reference and Information Service, UK  
Library - Exchange Desk, National Institute of Standards and  
Technology, US  
SPARES (10 copies)



<b>DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION DOCUMENT CONTROL DATA</b>				1. PRIVACY MARKING/CAVEAT (OF DOCUMENT)					
2. TITLE  Shear Rate Determination in a Concentric Cylinder Viscometer			3. SECURITY CLASSIFICATION (FOR UNCLASSIFIED REPORTS THAT ARE LIMITED RELEASE USE (L) NEXT TO DOCUMENT CLASSIFICATION)  Document (U) Title (U) Abstract (U)						
4. AUTHOR(S)  H.H. Billon			5. CORPORATE AUTHOR  Aeronautical and Maritime Research Laboratory PO Box 4331 Melbourne Vic 3001						
6a. DSTO NUMBER DSTO-GD-0093		6b. AR NUMBER AR-009-701		6c. TYPE OF REPORT General Document		7. DOCUMENT DATE July 1996			
8. FILE NUMBER 510/207/0291		9. TASK NUMBER DST 94/229		10. TASK SPONSOR DSTO		11. NO. OF PAGES 10		12. NO. OF REFERENCES 12	
13. DOWNGRADING/DELIMITING INSTRUCTIONS					14. RELEASE AUTHORITY  Chief, Weapons Systems Division				
15. SECONDARY RELEASE STATEMENT OF THIS DOCUMENT  Approved for public release  OVERSEAS ENQUIRIES OUTSIDE STATED LIMITATIONS SHOULD BE REFERRED THROUGH DOCUMENT EXCHANGE CENTRE, DIS NETWORK OFFICE, DEPT OF DEFENCE, CAMPBELL PARK OFFICES, CANBERRA ACT 2600									
16. DELIBERATE ANNOUNCEMENT  No limitations									
17. CASUAL ANNOUNCEMENT Yes									
18. DEFTTEST DESCRIPTORS  Shear Rate; Viscometers; Computer Programs									
19. ABSTRACT A method is described for the determination of the true shear rate in a concentric cylinder viscometer. A computer program based on the MacSporran technique is used. The program is tested on model as well as real fluids and is shown to be satisfactory. Shear rate determination in yield stress and time-dependent fluids is also discussed.									