AEROSPACE REPORT NO. TR-95(5925)-8

Optical Pumping With Laser-Induced Fluorescence

15 June 1996

Prepared by

J. C. CAMPARO and S. B. DELCAMP Electronics Technology Center Technology Operations

Prepared for

SPACE AND MISSILE SYSTEMS CENTER AIR FORCE MATERIEL COMMAND 2430 E. El Segundo Boulevard Los Angeles Air Force Base, CA 90245

9961017 065

Engineering and Technology Group



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED This report was submitted by The Aerospace Corporation, El Segundo, CA 90245-4691, under Contract No. F04701-93-C-0094 with the Space and Missile Systems Center, 2430 E. El Segundo Blvd., Los Angeles Air Force Base, CA 90245. It was reviewed and approved for The Aerospace Corporation by T. A. Galantowicz Principal Director, Electronics Technology Center. Col. C. Whited was the project officer for the Mission-Oriented Investigation and Experimentation (MOIE) program.

This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

Chala En litel

C. WHITED, Col. USAF SMC/SD

REPORT DOCU	JMENTATION F	PAGE		Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is and maintaining the data needed, and completing and i information, including suggestions for reducing this burde 1204, Arlington, VA 22202-4302, and to the Office of Man	estimated to average 1 hour per re- eviewing the collection of informati n to Washington Headquarters Serv agement and Budget, Paperwork Re-	sponse, including the t on. Send comments ices, Directorate for In duction Project (0704	time for reviewing in regarding this burch formation Operation -0188), Washington	structions, searching existing data sources, gathering len estimate or any other aspect of this collection of ns and Reports, 1215 Jefferson Davis Highway, Suite , DC 20503.
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 15 June	1995	3. REPORT	TYPE AND DATES COVERED
4. TITLE AND SUBTITLE				5. FUNDING NUMBERS
Optical Pumping with Laser-	Induced Fluorescend	e		E04701 02 C 0004
6. AUTHOR(S) J. C. Camparo and S. B. Delca	mp			F04701-93-C-0094
The Aerospace Corporation	1			REPORT NUMBER
Technology Operations El Segundo, CA 90245-469	91			TR-95(5925)-8
9. SPONSORING/MONITORING AGENCY Space and Missile Systems	NAME(S) AND ADDRESS	(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER
Air Force Materiel Comma 2430 E. El Segundo Boule	and vard			SMC-TR-96-16
Los Angeles Alf Force Bas 11. SUPPLEMENTARY NOTES	se, CA 90245		1	
12a. DISTRIBUTION/AVAILABILITY STATE	MENT			12b. DISTRIBUTION CODE
Approved for public release;	distribution unlimit	ed		
13. ABSTRACT (Maximum 200 words)				
We describe a new procedur (LIF). The procedure is der create a population imbalan depopulation pumping." Th dependent light-shift coeffic reduces the frequency-depen Since the stabilization of the ment of laser-pumped gas-c will be of benefit to atomic	re for optical pumpin nonstrated by optica ce between the grou hough optical pumpi cient (i.e., ac Stark sindent light-shift coe e diode laser wavele ell atomic clocks, it clock technology.	ng that is bas lly exciting nd state hyp ng with this hift) of the R fficient by at ngth is a sign is anticipate	sed on lase: a sample of erfine leve technique technique t least an of nificant cha d that optio	r-induced fluorescence f Rb ⁸⁵ atoms, which then ls of Rb ⁸⁷ by "LIF increases the intensity- yperfine transition, it rder of magnitude. allenge in the develop- cal pumping with LIF
14. SUBJECT TERMS				15. NUMBER OF PAGES
Optical pumping, Laser-ind	uced fluorescence			10 16. PRICE CODE
17. SECURITY CLASSIFICATION 18. SEC OF REPORT OF UNCLASSIFIED UI	URITY CLASSIFICATION THIS PAGE NCLASSIFIED	19. SECURITY OF ABSTR UNCL	CLASSIFICAT	TION 20. LIMITATION OF ABSTRACT
NSN 7540-01-280-5500				Standard Form 298 (Rev. 2-89) Prescribed by ANSI Std. Z39-18

A

5

²⁹⁸⁻¹⁰²

Preface

The authors would like to thank B. Jaduszliwer and R. Frueholz for their encouragement and the helpful suggestions that they made during the course of these studies. This work was supported by the U.S. Air Force Space and Missiles Center under Contract No. F04701-93-C-0094.

Contents

.

.,

Ă

v

1.	Introduction	1
2.	Experiment	2
3.	Results	3
4.	Light shifts	3
5.	Discussion	5
Refe	rences	6

Figures

1.	Partial energy level diagram for Rb ⁸⁵ and Rb ⁸⁷	1
2.	Experimental arrangement as described in the text	2
3.	Probe laser's absorption spectrum for D ₁ excitation	2
4.	Oscilloscope traces of the Rb ⁹⁷ 0–Ohyperfine transition lineshapes under varied optical excitation conditions with the probe laser tuned to the Rb ⁸⁷ D ₁ [5 ² P _{1/2} (F _e = 2) –5 ² S _{1/2} (F _g = 1)] transition	4
5.	Resonant nature of the Rb^{87} hyperfine transition signal with laser tuning about the $F_g = 2Rb^{85}$ optical transition	4

Table

1.	Results of experiment comparing the light shifts in standard	
	and LIF depopulation pumping	5

1. Introduction

In the early eighties, Volk et al. [1] discovered that a rubidium (Rb) atomic clock, which is based on the 0-0 ground state hyperfine transition in Rb⁸⁷ (i.e., the $[F_g=2, m_F=0]-[F_g=1, m_F=0]$ transition) [2], could be operated by tuning a diode laser to a Rb⁸⁵ optical transition in an isotopically mixed Rb vapor. This observation was surprising, because it implied that optical excitation of one Rb isotope created a population imbalance between the ground state hyperfine levels of the other Rb isotope. Since the optical transitions of the two isotopes were well resolved, implying that the laser could not have been optically pumping the Rb⁸⁷ population directly, the authors suggested a collisional mechanism for the creation of Rb⁸⁷ ground state hyperfine polarization (i.e., $\langle I \cdot S \rangle_{87} \neq 0$, where I is the nuclear spin and S is the electronic spin). They hypothesized that laser optical pumping of Rb⁸⁵ created $\langle I \cdot S \rangle_{85} \neq 0$, and that $Rb^{85} - Rb^{87}$ spin-exchange collisions then transferred this hyperfine polarization to the Rb⁸⁷ population.

Unfortunately, there are several problems with this mechanism. First, in the absence of Rb⁸⁵ electron spin polarization, spin-exchange will simply act as an electron-randomization mechanism [3]. Thus, Volk et al.'s hypothesis requires $\langle S_z \rangle_{85} \neq 0$, and how this spin polarization could have been achieved is a problematic feature of the hypothesis. A non-zero electronic spin polarization in the Rb⁸⁵ ensemble could have been created if their laser has some degree of elliptical polarization. However, diode lasers typically display a high degree of linear polarization [4], though more complicated states of optical polarization in these devices have been observed [5]. Alternatively, elliptically polarized light might have been created within the vapor itself via the nonlinear Faraday effect [6]; or a non-zero Rb⁸⁵ electronic spin polarization might have been created by some more complicated spin-exchange process, for example the spontaneous spin polarization process of Forston and Heckel [7]. However, even if $\langle S_z \rangle_{85} \neq 0$, it might not be possible for spin-exchange to give rise to a significant 0-0 hyperfine population imbalance in the Rb⁸⁷ ensemble. If it is assumed that spin-exchange is rapid enough so as to set up a spintemperature equilibrium in the Rb87 population, then the density matrix operator describing the population distribution among the ground state sublevels can be written as [8]

$$\rho = C \exp(\beta F_z) , \qquad (1)$$

where β is the spin-temperature parameter, F_z is the azimuthal projection of the total atomic angular momentum (F = I + S for the alkali ground state), and C is a normalization factor:

$$C = \frac{\sinh(\beta/2)}{\sinh[\beta(I+1)] + \sinh(\beta I)}.$$
 (2)

Under such conditions, Eq. (1) predicts that $\rho_{87}(F=2, m_F=0) = C = \rho_{87}(F=1, m_F=0)$, so that there could be no 0-0 hyperfine signal for the atomic clock operation.

A more plausible mechanism, first suggested by Happer [9], is based on laser-induced fluorescence (LIF). Fig. 1 is a partial energy level diagram of Rb⁸⁵ and Rb⁸⁷ showing that D₂ transitions (5²P_{3/2}-5²S_{1/2} at 780.2 nm) corresponding to the $F_g = 3$ ground state hyperfine level of Rb^{85} are nearly resonant with D_2 transitions corresponding to the $F_{g} = 2$ hyperfine level of Rb⁸⁷ for a room temperature vapor. Furthermore, it is to be noted that radiation trapping in the alkali vapors is significant even at relatively low vapor densities [10], and that under conditions of radiation trapping fluorescent photons diffuse to the line wings¹. Thus, D2 Rb85 laser-induced fluorescence, specifically the $F_g = 3$ component of the fluorescence, will be reabsorbed by Rb^{87} atoms in the $F_g = 2$ hyperfine level. As a consequence of this "LIF depopulation pumping" of Rb⁸⁷, a Rb⁸⁷ hyperfine polarization will be created.



Fig. 1. Partial energy level diagram for Rb⁸⁵ and Rb⁸⁷. Within each fine structure level, the hyperfine energy level spacings are drawn to scale.

¹ For examples of how radiation trapping at a moderate temperature can cause distortions of alkali fluorescent spectra, see Ref. [11].

It is to be noted that three hallmarks of this LIF mechanism are: (1) that it can occur with linearly polarized light, (2) that it is *resonant* with Rb⁸⁵ excitation, and (3) that the optical pumping process results in a Rb⁸⁷ population transfer from the $F_g = 2$ hyperfine level to the $F_g = 1$ hyperfine level.

In the following section of this paper we describe an experiment examining the creation of Rb⁸⁷ hyperfine polarization due to Rb⁸⁵ optical excitation, and show that the mechanism of LIF depopulation pumping is consistent with observation. This is then followed by a section dealing with the light shifts (i.e., ac Stark shifts) associated with this optical pumping process. As will be shown, for the same hyperfine transition signal amplitudes, the frequency dependent light-shift coefficient associated with LIF depopulation pumping is at least an order of magnitude smaller than that associated with standard depopulation pumping. Conversely, the (relative) intensity dependent light-shift coefficient associated with LIF depopulation pumping is larger than that associated with standard depopulation pumping. Since the predicted performance capability of a diode-laser-pumped gas-cell atomic clock is strongly influenced by laser frequency fluctuations [12], an atomic clock based on LIF depopulation pumping could have considerable practical value.

2. Experiment

Fig. 2 shows our basic experimental arrangement. A cylindrical resonance cell (L=3 cm and R=1.25 cm), containing natural Rb (72 % Rb⁸⁵ and 28% Rb⁸⁷) along with 14 Torr of neon, was located in the path of two crossed diode laser beams; the cylindrical axis of the resonance cell was parallel to the probe beam's propagation direction. The resonance cell was located in a 0.19 G magnetic field in order to isolate the 0–0 hyperfine transition, and the pool of liquid alkali metal in the resonance cell was maintained at about 63°C, implying an alkali vapor density of $\sim 7 \times 10^{11} \text{ cm}^{-3}$ [13]. The neon was present as a buffer gas to impede Rb diffusion to the resonance cell walls which are highly depolarizing.

The probe laser at 794.7 nm had a linewidth of 56 MHz, and an intensity of 1.1 μ W/cm² after attenuation by an optical density filter. The probe beam filled the resonance cell's cross-sectional area, and it was always tuned to the 5²P_{1/2}($F_e = 2$)-5²S_{1/2}($F_g = 1$) transition of Rb⁸⁷. Thus, its transmission through the vapor essentially monitored the Rb⁸⁷ population in the $F_g = 1$



Fig. 2. Experimental arrangement as described in the text.

hyperfine level. For reference purposes, Fig. 3 shows the absorption profile of the probe beam, along with an indication of the ground state hyperfine levels involved in the transitions. (Due to the large $5^2 P_{1/2}$ excited state hyperfine splitting in Rb⁸⁷, the two outer profiles appear as doublets.) Note that the pressure and Doppler broadening of the optical transitions were not too severe, so that the transitions of the two isotopes were well resolved. The pump laser at 780.2 nm had a linewidth of 40 MHz, and an intensity of 7.6 mW/cm². An aperture placed in the pump beam path reduced the beam diameter to 0.8 cm, so that the probe beam would completely overlap the pump beam volume. After passing through the alkali vapor, the pump beam was split in two. One portion of the pump beam was detected with a photodiode, and the transmitted light intensity monitored by this photodiode was used to tune the pump



Fig. 3. Probe laser's absorption spectrum for D_1 excitation (i.e., $5^2P_{1/2}-5^2S_{1/2}$): (A) Rb^{87} ($F_e = 2$)-($F_g = 1$); (B) Rb^{87} ($F_e = 1$)-($F_g = 1$); (C) Rb^{85} ($F_e = 2$, 3)-($F_g = 2$); (D) Rb^{85} ($F_e = 2$, 3)-($F_g = 3$); (E) Rb^{87} ($F_e = 2$)-($F_g = 2$); (F) Rb^{87} ($F_e = 1$)-($F_g = 2$). Note that the excited state hyperfine splitting in Rb^{87} is resolved.

Ĵ

beam to an atomic resonance. The other portion of the pump beam passed into a confocal Fabry-Pérot interferometer having a free-spectral-range of 2 GHz and a finesse of about 150. The signal from the interferometer was observed on a calibrated oscilloscope, and was used to measure detunings of the pump beam from an atomic resonance. The degree of linear polarization of the pump beam was measured, and found to be 99.9%.

The output of a frequency synthesizer was centered at 13.349 MHz, and slowly ramped through approximately ± 20 MHz about that value. This output was then multiplied up to 6834.7 MHz, which corresponds to the ground state hyperfine splitting in Rb⁸⁷; the microwave signal strength was large enough to saturate the 0-0 hyperfine transitions. In the absence of resonance microwaves, a population pumping process (e.g., optical pumping) will cause a change in the Rb⁸⁷ $F_{g} = 1$ hyperfine level population, and consequently a change in the magnitude of probe laser light transmitted by the resonance cell. As the microwaves were tuned across the ground state Rb⁸⁷ 0-0 hyperfine transition, the population imbalance between the two Rb87 ground state hyperfine levels was reduced, with a concomitant change in the magnitude of transmitted probe laser light. The probe laser's transmission thus acted to trace out the Rb⁸⁷ 0-0 ground state hyperfine transition lineshape. The important point to note for the present purposes, however, is that when the hyperfine resonance corresponded to an increase in probe laser light absorption, it could be inferred that the operative population pumping process had reduced the atomic population in the Rb⁸⁷ $F_g = 1$ hyperfine level. Conversely, when the hyperfine resonance corresponded to a decrease in probe laser light absorption, the population pumping process must have increased the atomic population in the $\text{Rb}^{87} F_g = 1$ hyperfine level.

3. Results

Fig. 4 illustrates the Rb⁸⁷ 0–0 ground state hyperfine transition obtained in the present experiment under different optical excitation conditions. In the figure, probe laser absorption is shown as a function of time or, what is equivalent, microwave frequency. For Fig. 4a the pump beam was blocked, so that the small resonant increase in probe absorption was due solely to residual probe optical pumping. Note that since optical pumping by the probe necessarily reduced the number of atoms in the absorbing state, the figure shows the 0–0 hyper-

fine transition as an increase in probe absorption. Fig. 4b resulted when the pump beam was unblocked and tuned to the $F_{e} = 1 D_{2}$ transition of Rb⁸⁷. The 0–0 hyperfine transition again appeared as an increase in probe absorption (albeit a larger increase), since the pump now acted more efficiently to reduce the number of atoms in the probe absorbing state. Tuning the pump beam to the $F_g = 2 D_2$ transition of Rb⁸⁷ resulted in an optical pumping process that increased the number of atoms in the $F_g = 1$ state, and, as Fig. 4c shows, the 0-0 hyperfine transition corresponded to a decrease in probe absorption. Finally, when the pump was tuned to the $F_{e} = 2 D_{2}$ transition of Rb⁸⁵, Fig. 4d resulted. Since the 0-0 hyperfine transition appears as a decrease in probe absorption, the process creating the Rb87 population imbalance must have been increasing the population density in the $Rb^{87} F_g = 1$ hyperfine level.

Several other characteristics regarding the 0–0 hyperfine transition lineshape are worth noting. First, the resonance signal of Fig. 4d could be observed with an optical density of 1.0 in the pump beam path, and a similar (decreasing absorption resonance) was observed when the pump laser was tuned to the $F_g = 3$ D_2 transition of Rb⁸⁵. Additionally, the amplitude of the 0–0 hyperfine transition lineshape showed a clear resonant behavior as the pump laser was tuned about the $F_g = 2 D_2$ transition of Rb⁸⁵; this is illustrated in Fig. 5. Given these results, the LIF depopulation pumping mechanism described above seems the most likely explanation for the Rb⁸⁷ population imbalance generated by Rb⁸⁵ optical excitation.

4. Light shifts

In addition to optical pumping, a laser also gives rise to light shifts of the 0–0 hyperfine transition Δv_{LS} . These shifts arise from a second order interaction between the laser electric field, E, and the atom's induced dipole moment, $P: h\Delta v_{LS} = -P \cdot E/2 =$ $-\alpha(\omega) \Phi/2$, where $\alpha(\omega)$ is the frequency dependent ground state polarizability of the atom and Φ is the laser intensity [14]. Happer and Mathur [15,16] have performed detailed studies of the light shift in alkali atoms, and find that for standard hyperfine depopulation pumping² the laser frequency dependence of the light shift should be quite strong (i.e., $\partial(\Delta v_{LS})/\partial\omega_L$

² By standard depopulation pumping, we mean an optical pumping process like that giving rise to the hyperfine transition of Fig. 4a.



Fig. 4. Oscilloscope traces of the Rb⁸⁷ 0–0 hyperfine transition lineshapes under varied optical excitation conditions with the probe laser tuned to the Rb⁸⁷ D₁[5²P_{1/2} ($F_e = 2$)–5²S_{1/2}($F_g = 1$)] transition. The photocurrent generated by the probe laser's photodiode was detected across 200 k Ω , and amplified by 200 before being displayed on the oscilloscope: (a) pump laser blocked, 20 mV/cm; (b) pump laser exciting Rb⁸⁷ atoms out of $F_g = 1$ hyperfine level, 20 mV/cm; (c) pump laser exciting Rb⁸⁷ atoms out of $F_g = 2$ hyperfine level, 20 mV/cm; (d) pump laser exciting Rb⁸⁵ atoms out of the $F_g = 2$ hyperfine level, 10 mV/cm.



Fig. 5. Resonant nature of the Rb⁸⁷ hyperfine transition signal with laser tuning about the $F_g = 2$ Rb⁸⁵ optical transition. The closed circles correspond to our measurements of the hyperfine resonance amplitude. Contrary to Fig. 4 a positive amplitude corresponds to decreasing absorption, while a negative amplitude corresponds to increasing absorption. The solid curves are simply meant as markers to show the Doppler broadened absorption profiles, and include the influence of the 5²P_{1/2} excited state hyperfine structure.

relatively large, where ω_L is the laser frequency), while the laser intensity dependence should be zero (i.e., $\partial(\Delta \nu_{LS})/\partial \Phi = 0$). These expectations have been borne out numerous times in the past [1,17–20]. However, for our LIF depopulation pumping experiment, the laser is far-detuned from a Rb⁸⁷ optical transition, and consequently theory predicts just the opposite situation: $\partial(\Delta \nu_{LS})/\partial \omega_L \cong 0$ and $\partial(\Delta \nu_{LS})/\partial \Phi$ non-zero.

To test these expectations, we first measured the frequency and intensity dependence of the light shift for standard depopulation pumping. The frequency dependence was established by tuning the pump laser to the $F_g = 1 D_2$ transition of Rb⁸⁷, and inserting a 2.6 optical density filter in the pump beam path so that the magnitude of the hyperfine resonance was equivalent to that shown in Fig. 4d (i.e., the same as for LIF depopulation pumping). The change in center position of the hyperfine resonance was then recorded for the pump laser detuned by + 400 and -400 MHz from resonance, and the experiment was repeated several times to obtain an estimate of the measurement uncer-

J

tainty. The intensity dependence was established by keeping the pump laser tuned to the $F_g = 1 D_2$ transition of Rb⁸⁷, and examining the change in the hyperfine resonance's center position as the optical density filter in the pump beam path was changed from 2 to 3. Again, the experiment was repeated several times to obtain an estimate of the measurement uncertainty. A similar set of measurements was performed for LIF depopulation pumping with the pump laser tuned to the $F_g = 2 D_2$ transition of Rb⁸⁵, except that for the intensity dependence measurements the change in the optical density filter was from 0 to 1.

The results of these measurements are collected in Table 1, where for later reference the values are given in terms of fractional-frequency (i.e., $\Delta v_{LS}/v_{hfs}$). Though we quote an intensity dependent light-shift coefficient in terms of fractional-frequency/ $\mu W \text{ cm}^{-2}$, for comparative purposes it is better to consider the intensity dependent light-shift coefficient quoted in terms of percentile light intensity change, since the absolute light intensity required for the two optical pumping processes differs appreciably. As the results demonstrate, the frequency dependent lightshift coefficient of the 0–0 hyperfine transition is at least an order of magnitude smaller than that obtained in standard depopulation pumping, while the relative intensity dependent light-shift coefficient is larger.

5. Discussion

As demonstrated in the previous section, LIF depopulation pumping trades an enhanced sensitivity to (relative) laser intensity fluctuations for a diminished sensitivity to laser frequency fluctuations, and it is just this decreased sensitivity to laser frequency noise that provides LIF depopulation pumping with its principal advantage over standard depopulation pumping. As an example, consider diode laser optical pumping in the gas-cell atomic frequency standard (i.e., atomic clock), which has been lauded as a means of achieving

"maser-like" performance in the compact device. Essentially, the use of diode lasers allows for very efficient standard depopulation pumping, resulting in large signal-to-noise ratios and narrow hyperfine transition lineshapes. Theory predicts that by averaging the atomic standard's output frequency for several minutes it should be possible to achieve a shot-noise limited fractional-frequency stability better than 10^{-15} [12]. In order to achieve this expectation though, it is necessary to tightly stabilize the laser frequency, since laser frequency instability maps onto the atomic frequency standard's output as a consequence of the light-shift effect. Measurements of the light-shift coefficient in laser-pumped gas-cell clock's have been found to be $\sim 2 \times 10^{-11}$ /MHz [21], implying that the theoretical expectation necessitates locking the diode laser to within 50 Hz of an atomic resonance for periods of minutes.

In the course of our experiment, we measured the hyperfine signal's amplitude and linewidth for LIF depopulation pumping. On the basis of those measurements, we estimated that the resulting signal could have given rise to a shot-noise limited performance of $3 \times 10^{-11} / \sqrt{\tau}$, where τ is the frequency-averaging time [22]. This was obtained without any optimization of resonance cell temperature or beam geometry, and one would anticipate that the value could be considerably improved by increasing the cross-sectional area of the probe beam and the resonance cell. The significance of the result, however, is that it indicates that LIF depopulation has a capability to achieve reasonable signalto-noise levels. Moreover, since LIF depopulation pumping has a reduced frequency dependent light-shift coefficient, the laser frequency locking requirements for such an atomic clock would be considerably relaxed compared to an atomic clock based on standard depopulation pumping.

Of course, if LIF depopulation pumping was to be employed in an atomic clock, the fluctuations in laser intensity would need to be restricted. However, this may not be too serious a technological challenge.

тո	hlo	1	

Results of experiment comparing light shifts in standard and LIF depopulation pumping

	Unit	Standard depopulation pumping	LIF depopulation pumping
$\partial (\Delta v_{\rm LS}) / \partial \omega_{\rm L}$	MHz ⁻¹	$(-1.9\pm0.3)\times10^{-11}$	$(0.08 \pm 0.27) \times 10^{-11}$
$\partial (\Delta \nu_{\rm LS}) / \partial \Phi$	$\mu W^{-1} \cdot cm^2$ $\%^{-1}$	$(-3\pm4)\times10^{-11}$ $(-1.2\pm1.7)\times10^{-11}$	$(-2.5\pm0.1)\times10^{-12}$ $(-1.09\pm0.06)\times10^{-10}$

Tsuchida and Tako [23] have found that the intensity noise for a frequency stabilized laser, operating without any control on laser intensity, has a flicker-noise Allan standard deviation ³, $\sigma_{\Delta P/P}(\tau)$, of 3×10^{-5} . Consequently, employing the intensity dependent light-shift coefficient obtained in the present work, their result would imply a flicker-noise light-shift contribution to the clock performance of 3×10^{-13} . Moreover, by employing an external electro-optic modulator it might be possible to reduce this level of intensity noise still further [26]. Thus, LIF depopulation pumping could be advantageous for situations where light shifts are problematic; specifically, diode laser optical pumping in gas-cell atomic clocks.

References

- C.H. Volk, J.C. Camparo and R.P. Frueholz, in: Proc. 13th Annual Precise Time and Time Interval (PTTI) Applications and Planning Meeting (US Naval Observatory, Washington, DC, 1981) pp. 631-640.
- [2] J. Vanier and C. Audoin, The quantum physics of atomic frequency standards, Vol. 2 (Adam Hilger, Bristol, 1989).
- [3] W. Happer, Rev. Mod. Phys. 44 (1972) 169.
- [4] J.C. Camparo, Contemp. Phys. 26 (1985) 443.
- [5] T.L. Paoli, IEEE J. Quantum Electron. QE-11 (1975) 489.
- [6] S.I. Kanorsky, A. Weis, J. Wurster and T.W. Hansch, Phys. Rev. 47 (1993) 1220.

- [7] N. Fortson and B. Heckel, Phys. Rev. Lett. 59 (1987) 1281.
- [8] L.W. Anderson and A.T. Ramsey, Phys. Rev. 132 (1963) 712;
 W. Happer and A.C. Tam, Phys. Rev. A 16 (1977) 1877.
- [9] W. Happer, private communication.
- [10] B.P. Kibble, G. Copley and L. Krause, Phys. Rev. 153 (1967)
 9.
- [11] T. Tako, Y. Koga and I. Hirano, Jpn. J. Appl. Phys. 14 (1975) 591;
 - F. Vermeersch, V. Fiermans, J. Ongena, H.A. Post and W. Wierne, J. Phys. B 21 (1988) 1933.
- [12] J.C. Camparo and R.P. Frueholz, J. Appl. Phys. 59 (1986) 3313.
- [13] T.J. Killian, Phys. Rev. 27 (1926) 578.
- [14] S. Pancharatnam, J. Opt. Soc. Am. 56 (1966) 1636.
- [15] W. Happer and B.S. Mathur, Phys. Rev. 163 (1967) 12.
- [16] B.S. Mathur, H. Tang and W. Happer, Phys. Rev. 171 (1968) 11.
- [17] M. Arditi and J-L. Picque, J. Phys. B 8 (1975) L331.
- [18] J.C. Camparo, R.P. Frueholz and C.H. Volk, Phys. Rev. A 27 (1983) 1914.
- [19] M. Hashimoto and M. Ohtsu, IEEE J. Quantum Electron. QE-23 (1987) 446.
- [20] A. Michaud, P. Tremblay and M. Tetu, IEEE Trans. Instrum. Meas. 40 (1991) 170.
- [21] M. Hashimoto and M. Ohtsu, IEEE J. Quantum Electron. QE-23 (1987) 446;

L.A. Budkin, V.L. Velichanskii, A.S. Zibrov, A.A. Lyalyaskin, M.N. Penenkov and A.I. Pikhtelev, Sov. J. Quantum Electron. 20 (1990) 301.

- [22] J. Vanier and L-G. Bernier, IEEE Trans. Instrum. Meas. IM-30 (1981) 277.
- [23] H. Tsuchida and T. Tako, Jpn. J. Appl. Phys. 22 (1983) 1152.
- [24] S.R. Stein, Frequency and time their measurement and characterization, in: Precision frequency control, Vol. 2, eds. E.A. Gerber and A. Ballato (Academic Press, New York, 1985) Ch. 12.
- [25] S. Yamaguchi and M. Suzuki, IEEE J. Quantum Electron. QE-19 (1983) 1514.
- [26] V.N. Korolev, A.V. Marugin, A.V. Kharachev and V.B. Tsaregradskii, Sov. Phys. Tech. Phys. 34 (1989) 863.

³ Fig. 3 of Ref. [23] shows an Allan standard deviation for the intensity noise that increases linearly with averaging time beyond one second. This is the hallmark of a deterministic drift; see Ref. [24]. The power drift of the laser, however, can be significantly reduced if not eliminated; see Ref. [25].