

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE	3. REPORT TYPE AND DATES COVERED FINAL REPORT 30 Sep 93 - 31 Mar 96	
4. TITLE AND SUBTITLE development of compact 1.06 and 2.1 MICRON LASERS			5. FUNDING NUMBERS 62228D 4276/AS	
6. AUTHOR(S) Professor Kushawaha				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Howard University Washington, DC 20059			AFOSR-TR-96 0558	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NE 110 Duncan Avenue Suite B115 Bolling AFB DC 20332-8080			10. SPONSORING/MONITORING AGENCY REPORT NUMBER F49620-93-1-0571	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED			12b. DISTRIBUTION CODE	
13. ABSTRACT During the project period, extensive studies of the laser performance of a Nd: and Ho:Tm ions doped in YAG (Y ₃ Al ₅ O ₁₂), KGW (KGd(WO ₄) ₂) host crystals pumped by diode lasers operating in continuous wave or pulsed modes of operation. The diode lasers were temperature tuned to select the appropriate wavelengths to pump the Nd-ions at 785 nm. The laser action from these ions was observed at 1.06 and 2.1 micron, respectively. These laser actions were observed by using various pumping schemes such as end-pumping or side-pumping in different configurations such as fixed rod, rotating disks, and moving slabs. These configurations were used only in case of Nd:YAG or Nd:KGW laser crystals. For Tm:Ho:LuAG, only the rod configuration was used at low temperature to observe the laser action at 2.1 micron. A slightly improved laser performance as observed using the rotating disk or moving slab configurations as compared to the fixed configurations. The Nd:YAG and Nd:KGW laser experiments were also performed at very low temperature (approx. 78 K). The laser performance from Nd:KGW at the low temperature was found to be slightly better than the Nd:YAG laser. These results have either been published or submitted for publication in refereed Journals.				
14. SUBJECT TERMS			15. NUMBER OF PAGES	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED			16. PRICE CODE	
18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED			19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	
20. LIMITATION OF ABSTRACT				

19961125 186

DTIC QUALITY INSPECTED 3

RECEIVED

96 OCT 24 PM 1:59

Howard University

Washington DC 20059

ASSOC. V.P. FOR RESEARCH

1. NAME OF THE AGENCY: Air Force Office of Scientific Research
2. PERIOD COVERED BY REPORT (Final): 30 September 1993 - 31 May 1996
3. TITLE OF THE PROPOSAL: Development of compact 1.06 and 2.1 Micron
Lasers
4. CONTRACT OR GRANT NO: F49620-93-1-0571
5. NAME OF THE INSTITUTION: Howard University
6. AUTHOR OF THE REPORT: Vikram S. Kushawaha
7. LIST OF THE MANUSCRIPTS SUBMITTED OR PUBLISHED UNDER
WRIGHT LABORATORY SPONSORSHIP DURING THIS REPORTING
PERIOD:
 1. Relative performance of a 1.06 μm laser with various Nd doped crystals
V. Kushawaha and L. Major, Optics and Laser Techn. **26** 351 (1994)
 2. Effect of Nd concentration on the Nd:KGW laser
V. Kushawaha, A. Michael, and L. Major, Appl. Phys. **B58**, 533 (1994)
 3. Diode End Pumped High Efficiency Nd:YAG Laser
V. Kushawaha and Y. Chen, Appl. Phys. **B59**, 659 (1994)
 4. Q-switched operation of a SGGM laser
V. Kushawaha and . Michael, Optics and Laser Techn. **27**, 137 (1995)
 5. Rotating Disk Diode Pumped Continuous Wave Nd:YAG Laser
Y. Chen and V. Kushawaha, Appl. Phys **B61**, 525 (1995)
 6. CW and quasi-CW diode laser pumped Nd:SSGM
V. Kushawaha and Y. Chen, Appl. Phys. **B60** 67 (1995)
 7. Efficiency of diode pumped 1.35 μm laser from diode pumped Nd:KGW
V. Kushawaha, Y. Yan, and Y. Chen, Appl. Phys. **B62**, 533 (1996)
 8. High efficiency continuous wave diode pumped Tm:Ho:LuAG laser at 2.1 μm
V. Kushawaha, Y. Chen, Y. Yan and L. Major, Appl. Phys. **B62** , 109 (1996)
 8. Efficient laser operation of diode pumped Nd:KGd(WO₄)₂ crystal at 1.067 μm
Y. Chen, L. Major, and V. Kushawaha, Appl. Opt. (In Press 1996)
 9. Diode Pumped Moving Nd:YAG and Nd:KGW Slab Lasers
Y. Chen, L. Major, Y. Yan, and V. Kushawaha, Appl. Phys. **B** (Submitted 96)
8. SCIENTIFIC PERSONNEL SUPPORTED BY THIS PROJECT AND
DEGREES AWARDED DURING THIS REPORTING PERIOD: None
9. REPORT OF INVESTIGATION (BY TITLE ONLY): None

10. BRIEF OUTLINE OF RESEARCH FINDINGS:

During the project period (October 1, 1993 - May 15, 1996), we have extensively studied the laser performance of a Nd: and Ho:Tm ions doped in YAG ($Y_3 Al_5 O_{12}$), KGW ($KGd (WO_4)_2$) and LuAG ($Lu_3 Al_5 O_{12}$) host crystals pumped by diode lasers operating in continuous wave or pulsed modes of operation. The diode lasers were temperature tuned to select the appropriate wavelengths to pump the Nd-ions at 808 nm and Ho-ions at 785 nm. The laser action from these ions was observed at 1.06 and 2.1 micron, respectively. These laser actions were observed by using various pumping schemes such as end-pumping or side-pumping in different configurations such as fixed rod, rotating disks, and moving slabs. These configurations were used only in case of Nd:YAG or Nd:KGW laser crystals. For Tm:Ho:LuAG, only the rod configuration was used at low temperature to observe the laser action at 2.1 micron. A slightly improved laser performance was observed using the rotating disk or moving slab configurations as compared to the fixed configurations. The Nd:YAG and Nd:KGW laser experiments were also performed at very low temperature (approx. 78 K). The laser performance from Nd:KGW at the low temperature was found to be slightly better than the Nd:YAG laser. These results have either been published or submitted for publication in refereed Journals.