

AL/CF-SR-1995-0005



**EVALUATION OF THE COMBAT EDGE AND MBU-20/P  
MASK SYSTEM DURING +GZ IMPACT ACCELERATION**

**Chris E. Perry**

**CREW SYSTEMS DIRECTORATE  
BIODYNAMICS AND BIOCOMMUNICATIONS DIVISION  
WRIGHT-PATTERSON AFB OH 45433-7901**

**AUGUST 1994**

**19970919 073**

*DO NOT CHANGE INFORMATION*

**INTERIM REPORT FOR THE PERIOD MARCH 1994 THROUGH AUGUST 1994**

**Approved for public release; distribution is unlimited**

**AIR FORCE MATERIEL COMMAND  
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433-6573**

**ARMSTRONG  
LABORATORY**

## NOTICES

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Please do not request copies of this report from the Armstrong Laboratory. Additional copies may be purchased from:

National Technical Information Service  
5285 Port Royal Road  
Springfield, Virginia 22161

Federal Government agencies registered with the Defense Technical Information Center should direct requests for copies of this report to:

Defense Technical Information Center  
Cameron Station  
Alexandria, Virginia 22314

### TECHNICAL REVIEW AND APPROVAL

AL/CF-SR-1995-0005

The voluntary informed consent of the subjects in this research was obtained as required by AFI 40-402.

This report has been reviewed by the Office of Public Affairs (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

FOR THE DIRECTOR



THOMAS J. MOORE, Chief  
Biodynamics and Biocommunications Division  
Crew Systems Directorate  
Armstrong Laboratory

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE August 1994	3. REPORT TYPE AND DATES COVERED Interim - Mar 94 - Aug 94		
4. TITLE AND SUBTITLE Evaluation of the Combat Edge and MBU-20/P Mask System During +Gz Impact Acceleration			5. FUNDING NUMBERS PE - 62202F PR - 7231 TA - 31/24 WU - 01/01	
6. AUTHOR(S) Chris E. Perry				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Armstrong Laboratory, Crew Systems Directorate Biodynamics and Biocommunications Division Human Systems Center Air Force Materiel Command Wright-Patterson AFB OH 45433-7901			8. PERFORMING ORGANIZATION REPORT NUMBER  AL/CF-SR-1995-0005	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  An experimental effort was conducted on a vertical deceleration tower to determine the compatibility of the COMBAT EDGE & MBU-20/P mask system with a HGU-55/P helmet in a +Gz impact acceleration environment. Tests were conducted at 10 G impact levels and a MBU-12/P mask with a HGU-55/P helmet was used as a baseline for comparison. The test results were used to evaluate the structural integrity, mask stability, and weight and center-of-gravity effects of the COMBAT EDGE & MBU-20/P system. Inertial property results indicated that the COMBAT EDGE mask system was approximately 0.4 lbs heavier and had lower center-of-gravity compared to the baseline. Results indicated that there were no major problems with the structural integrity of the COMBAT EDGE mask system during impact. Mask stability results indicated that the COMBAT EDGE mask displaced downward twice the distance the baseline mask did during impact. Further evaluation of the mask indicated that the adjustment webbing guide paths would need modifications to prevent slippage.				
14. SUBJECT TERMS COMBAT EDGE system    Vertical impact acceleration MBU-20/P mask        Vertical deceleration tower			15. NUMBER OF PAGES 22	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL	

THIS PAGE INTENTIONALLY LEFT BLANK

## PREFACE

An experimental effort was conducted to evaluate the structural integrity, stability, and inertial properties of the COMBAT EDGE & MBU-20/P mask system with a HGU-55/P helmet during +Gz impact accelerations. Test results were used to compare the system to a baseline system consisting of a MBU-12/P mask with a HGU-55/P helmet. The experimental tests were conducted on the Armstrong Laboratory's Vertical Deceleration Tower at WP-AFB OH. The effort was conducted for HSC/YA at Brooks AFB TX.

All tests described in this report were conducted by the Escape and Impact Protection Branch of the Armstrong Laboratory. Facility and data acquisition support were provided by DynCorp under Contract F33615-91-C-0531.

TABLE OF CONTENTS

	PAGE NO.
INTRODUCTION . . . . .	1
METHODOLOGY . . . . .	2
RESULTS . . . . .	9
CONCLUSIONS . . . . .	15
REFERENCES . . . . .	16

## LIST OF FIGURES

FIGURE		PAGE NO.
1	AL/CFBE Vertical Deceleration Tower (VDT) . .	3
2	VDT 10 G Impact Acceleration Pulse Shape . .	4
3	SELSPOT LED Locations for COMBAT EDGE Impact Testing . . . . .	6
4	HGU-55/P Helmet and MBU-12/P Mask Baseline System . . . . .	7
5	HGU-55/P Helmet and COMBAT Edge Mask System .	8
6	Headform Anatomical Axis System . . . . .	9
7	Interim Head and Neck Criteria Relative to COMBAT EDGE and Baseline Systems with Full Hose . . . . .	12
8	Location of Frayed Webbing on COMBAT EDGE System After Impact . . . . .	13

## LIST OF TABLES

TABLE		PAGE NO.
1	COMBAT EDGE Test Matrix . . . . .	5
2	Head and Helmet System Inertial Properties for COMBAT EDGE Program . . . . .	11
3	COMBAT EDGE Impact Program Data Summary . . .	14

THIS PAGE INTENTIONALLY LEFT BLANK



## INTRODUCTION

Research to provide pilots with the proper equipment for G-protection has been on-going for several decades. This research is on-going because improving flight control systems are allowing pilots to fly their mission profiles higher and faster which increases the physiological load on the human body and in particular, the cardiovascular and respiratory systems. To help improve pilot performance and reduce physiological loads, the COMBAT EDGE & MBU-20/P mask system has been developed to provide the pilot a positive pressure breathing and mask coupling system which would help reduce the chance of G-induced loss of consciousness during a high-G maneuver.

The COMBAT EDGE system consists of a low profile mask, an occipital bladder to seal the mask during pressure breathing, a regulator, and additional torso anti-G systems. Improvements to the mask and bladder system have necessitated additional testing of these components in an aerospace environment.

At the request of the Life Support Systems Program Office at Brooks AFB, the Armstrong Laboratory's Escape and Impact Protection Branch (AL/CFBE) at Wright Patterson AFB was requested to test the improved COMBAT EDGE and MBU-20/P mask system with an HGU-55/P helmet in an impact acceleration environment simulating the forces the system may experience during the catapult phase of an emergency escape. The test objectives were to evaluate the system's structural integrity, stability, and inertial properties during a +Gz impact acceleration. Results were compared to a baseline system consisting of a MBU-12/P mask with a HGU-55/P helmet.

## METHODOLOGY

To evaluate the integrity, stability, and inertial property effects of the COMBAT EDGE and MBU-20/P mask system (from here on referred to as the COMBAT EDGE system) in an ejection environment, a series of short duration, +Gz impact acceleration tests were conducted using the AL/CFBE Vertical Deceleration Tower (VDT) and the Advanced Dynamic Anthropomorphic Manikin or ADAM. The VDT, shown in Figure 1, provided a +Gz impact acceleration that produces a biodynamic response approximating the ACES II ejection catapult response. The ADAM, a specialized instrumented manikin, was used to estimate the biodynamic response of humans in the dynamic impact environment.

The VDT functions to simulate an ejection seat catapult acceleration pulse by producing a +z-axis (inferior to superior) impact acceleration using a hydraulic decelerator. A seat pan and seat back configuration are mounted to a carriage which can move vertically on a pair of guide rails. The carriage can be hoisted to a specific height and then allowed to free-fall. A contoured plunger mounted on the back of the carriage is then guided into a cylindrical reservoir filled with water. The action of the plunger displacing the water in the reservoir generates the deceleration or impact profile of the carriage. This profile is then transmitted to a subject sitting in the carriage mounted seat. The profile is shaped by the height of the carriage at free-fall (controlling the magnitude of the impact pulse), and by the shape of the plunger (controlling the rise-time of the impact pulse). The 10 G pulse used for this program is shown in Figure 2.

The ADAM was restrained in a seated posture to the VDT seat by a standard USAF lap belt and double shoulder strap configuration. The upper limbs were restrained to the thigh, and the lower limbs restrained in a vertical position using Velcro strapping. The seat back angle was set to 0°, and the plane of the headrest was in-line with the seat back. An un-cushioned, flat, rigid seat pan was used for all tests. The test facility was instrumented with load cells to collect seat pan loads and loads in the restraint system. Accelerometers were used to measure carriage and seat accelerations. The ADAM was instrumented to collect linear head and chest accelerations, and angular head and chest velocities. The ADAM cervical spine was also instrumented with a special six-axis Denton load cell to allow the collection of neck loads and torques generated at the occipital condyle or head/neck junction. The restraints

were pre-tensioned to  $20 \pm 5$  pounds prior to each test. All accelerations, velocities, and forces were collected with a carriage-mounted automatic data acquisition system located above the seat assembly.




FIGURE 1. AL/CFBE VERTICAL DECELERATION TOWER (VDT)

# VERTICAL DECELERATION TOWER IMPACT PULSE




FIGURE 2. VDT 10 G IMPACT ACCELERATION PULSE SHAPE

In addition to the electronic data, motion analysis data was collected during each test using two different systems mounted on special supports attached to the carriage. Each test was documented with a KODAK high-speed video system. The single camera captured the detailed movements of the ADAM and the helmet/mask systems during the impact acceleration. In addition to the video coverage, a SELSPOT motion analysis system was used to track the displacement of targets on the carriage and the ADAM. The location of the targets is shown in Figure 3. The SELSPOT system utilizes two photosensitive cameras to track the motion of the infrared LED targets. By tracking specific points on the head and the mask during each test, the relative displacement of the mask during impact could be determined using the SELSPOT displacement data.

Prior to impact testing, the inertial properties, including weight and center-of-gravity (Cg), of the COMBAT EDGE system and the baseline were measured. This was accomplished in order to combine the inertial properties of the tested systems with those of the ADAM headform. By having the combined inertial properties, comparisons and relationships could potentially be established between the systems themselves, and between the inertial property parameters and the biodynamic response parameters of the ADAM. This procedure was completed by the Vulnerability Assessment Branch of the Armstrong Laboratory (AL/CFBE).


The impact tests were conducted using both the baseline helmet and mask, and the modified COMBAT EDGE system and an HGU-55/P helmet. The baseline system is shown in Figure 4, and the COMBAT EDGE system is shown in Figure 5. Approximately 5 tests were run with the baseline helmet at a 10 G impact level, followed by 6 tests with the COMBAT EDGE helmet system also at a 10 G impact level. The initial baseline series allowed verification and modification of procedures used to compare and contrast the two systems, including the measurement of mask slippage. A test matrix is shown in Table 1.

TABLE 1. COMBAT EDGE TEST MATRIX

Test Cell	No. of Tests	Helmet	O <sub>2</sub> Mask
A	5	HGU-55/P	MBU-12/P
B	6	HUG-55/P	COMBAT EDGE

Upon completion of the tests, the motion and displacement data, and the electronic data were analyzed using standard statistical methods. The weight and Cg data were compared to the baseline system and to the AL Head/Neck Weight and Cg Criteria. Slippage of the mask was estimated by analyzing its relative z-axis displacement as compared to the brow position on the ADAM.

### COMBAT EDGE IMPACT CIE-VWI2 Study LED LOCATIONS



1. TOP OF HELMET
2. BOTTOM OF HELMET
3. BROW
4. MASK
5. NECK
6. CHEST
7. TOP OF HEADREST
8. TOP OF NUMBER FRAME
9. BOTTOM OF NUMBER FRAME
10. STATIONARY SEAT BACK

FIGURE 3. SELSPOT LED LOCATIONS FOR COMBAT EDGE IMPACT TESTING




FIGURE 4. HGU-55/P HELMET AND MBU-12/P MASK BASELINE SYSTEM



FIGURE 5. HGU-55/P HELMET AND COMBAT EDGE MASK SYSTEM



## RESULTS

The specific objectives of this test program were to evaluate the structural integrity, mask stability, and inertial property effects of the new COMBAT EDGE and MBU-20/P mask system during vertical impact. The equipment was mounted on a HGU-55/P helmet and the results were compared to similar impacts conducted with a baseline system consisting of a HGU-55/P helmet and a MBU-12/P mask.

A part of the biodynamic evaluation of a head mounted system is the calculation of the inertial properties. All inertial property data is relative to the head anatomical axis system of the ADAM. This coordinate system is defined by a line connecting the right and left trasion (notch above ear canal) which is the y-axis, a line connecting the infra-orbital notch (bone ridge below eye) and the y-axis, and shifted equidistantly between the trasions, which is the x-axis, and a line perpendicular to the intersection of the y-axis and x-axis which is the z-axis. The intersection of all three axes forms the coordinate origin of the anatomical axis system. The axes system is shown in Figure 6.




FIGURE 6. HEADFORM ANATOMICAL AXIS SYSTEM

A summary of the inertial properties of various headforms and various combinations of the ADAM headform, HGU-55/P helmet, MBU-12/P mask, and the COMBAT EDGE system are shown in Table 2. In the table, 55/P refers to the HGU-55/P helmet, CE refers to the COMBAT EDGE helmet bladder system, 12/P refers to the MBU-12/P mask, and 20/P refers to the MBU-20/P mask. All Cg values are referenced to the ADAM anatomical coordinate system. The systems with masks have a full hose wrapped to the right side of the ADAM neck. The ADAM headform inertial properties shown in the table are for the same headform used during calculation of the inertial properties of the additional systems shown in the table. The data shows that as you add equipment to the helmet, the weight will correspondingly increase. It should be noted that the weight of the helmet, COMBAT EDGE bladder, and MBU-20/P mask is under 4.0 lbs. The Cg data also shows logical shifts in the x-axis and z-axis values as systems are added to the baseline helmet. It should also be noted that the full COMBAT EDGE system with helmet has a Cg a little forward and below that of the baseline helmet and mask, and that both systems are acceptable relative to the USAF Interim Head/Neck Criteria as shown in Figure 7.

The structural integrity and mask slippage evaluation was also completed on the COMBAT EDGE system to determine the system's tolerance to +z-axis impact accelerations. The system had no structural failures during the 10 G impact test series, however, after the second test, it was documented that the retention straps or webbing on the MBU-20/P mask began to loosen and fray at the points where the straps interfaced with the mask structure. This can be shown in Figure 8. The slippage of the mask was quantitatively analyzed and compared to slippage in the baseline system using SELSPOT data. For each test cell, the relative displacement of the mask in the z-axis was measured by with reference to a point on the head (brow) also measured by SELSPOT. The difference between peak displacements of the brow and mask was calculated for each test and a mean and standard deviation calculated for each cell. Table 3 contains this data in addition to data for other parameters. The relative displacement data shows the COMBAT EDGE system to displace approximately 0.5 inches which is roughly twice the baseline system. This is most likely due to the mask webbing not keeping the mask structure secure against the face of the manikin during impact. It could also be due to small variations in the pre-test positioning and tightening of the mask.

The additional data in table 3 shows the biodynamic response of the ADAM with the baseline system compared to the ADAM with the COMBAT EDGE system. As the small variations in inertial properties would suggest, the biodynamic data indicates that there is little difference between the two systems. The COMBAT EDGE system having a larger compressive (z-axis) neck load compared to the baseline would be expected due to its slightly higher weight, however, both systems generate loads that are well below the 400 lb major injury threshold as determined by Mertz and Patrick. The angular velocity values are also well below the 20 to 30 rad/sec major injury threshold. The biodynamic data in table 3 indicates that there is no significant differences in the impact response of the two systems during a 10 G impact acceleration. Data indicates a trend for the neck loads to slightly increase and for no increase in forward head rotation.


TABLE 2. HEAD AND HELMET SYSTEM INERTIAL PROPERTIES FOR COMBAT EDGE PROGRAM

SYSTEM	WEIGHT OF SYSTEM (LBS)	WEIGHT WITH ADAM (LBS)	CENTER OF GRAVITY (IN)
Large Human Head		9.70	-0.28 , 0.00 , 1.32
Large ADAM Head		9.39	-0.32 , -0.03 , 1.01
ADAM + HGU-55/P	2.54	11.93	-0.46 , 0.21 , 1.13
ADAM + 55/P + CE	2.78	12.17	-0.59 , 0.31 , 1.17
ADAM + 55/P + 12/P	3.64	13.03	-0.39 , 0.12 , 0.86
ADAM + 55/P + 20/P + CE	3.81	13.19	-0.36 , 0.36 , 0.75

# USAF INTERIM HEAD AND NECK CRITERIA

## Center of Gravity in ADAM Anatomical Coordinates

MBU-12/P Mask with 1/3 hose with all systems; COMBAT EDGE and HGU-55/P-(2) have full hose.



• LARGE HUMAN HEAD	+ LARGE ADAM HEAD	* HGU-55/P-(1)
■ INIGHTS NVG	▼ HGU-33/P	★ HGU-26/P
⊠ INIGHTS NVG/HMD	⊕ COMBAT EDGE & 20/P	× HGU-55/P-(2)

Outer Cg Box Limits: Weight Criteria... 4.0 lb for B-52 seat, 5.0 lb for ACES II

Inner Cg Box Limits: Weight Criteria... 4.5 lb for B-52 seat

FIGURE 7. INTERIM HEAD AND NECK CRITERIA RELATIVE TO COMBAT EDGE AND BASELINE SYSTEMS WITH FULL HOSE



FIGURE 8. LOCATION OF FRAYED WEBBING ON COMBAT EDGE SYSTEM AFTER IMPACT

Table 3. Combat Edge Impact Program Data Summary

Helmet System		ADAM Z-Axis Head Accel (G)	ADAM Head Angular Vel (Rad/Sec)	ADAM Head Z-Axis Load (Lbs)	Relative Mask Disp. (In)
Cell A  (HGU-55/P, 12/P)	Mean	13.95	4.24	155.48	0.233
	Std Dev	0.275	0.12	2.84	0.063
Cell B  (HGU-55/P, 20/P, CE)	Mean	14.08	4.18	160.67	0.479
	Std Dev	0.188	0.15	2.7	0.035

## CONCLUSIONS

Tests were conducted on the AL/CFBE VDT facility to evaluate the compatibility of the COMBAT EDGE mask system with an HGU-55/P helmet during positive vertical impact accelerations. The results were compared to similar impacts of a baseline system consisting of an HGU-55/P helmet and a MBU-12/P mask. The baseline helmet was subjected to 5 impacts and the COMBAT EDGE system was subjected to 6 impacts. All tests were conducted with the systems mounted on the head of an ADAM and at impacts of 10 G. Inertial property evaluation revealed the COMBAT EDGE system to be very similar to the baseline system being less than a half pound heavier. Both systems as expected meet the USAF Interim Head and Neck Criteria in terms of weight and center-of-gravity. The impact tests revealed little biodynamic difference between the two systems with the COMBAT EDGE system having slightly higher compressive neck loads as expected. The impact tests did reveal the need for a modification of the webbing that adjusts the mask pressure on the face because the z-axis displacement of the COMBAT EDGE MBU-20/P mask was approximately twice the displacement of the baseline mask system.

## REFERENCES

1. Brinkley, J.W. and Schaffer, J.T. Dynamic Simulation Techniques for the Design of Escape Systems: Current Applications and Future Air Force Requirements. AFAMRL-TR-71-29, 1971.
2. Melvin, J.W. Human Neck Injury Tolerance. Society of Automotive Engineers Publication 790136, 1979.
3. Mertz, H.J. and Patrick, L.M. Strength and Response of the Human Neck. Proceedings of the Fifteenth Stapp Car Crash Conference, Society of Automotive Engineers Publication 710855, 1971.
4. Perry, C.E. Evaluation of the Effects of Visually Coupled Systems on the Biodynamic Response to Simulated Ejection Accelerations. AL/CF-TR-1993-0159.
5. Tripp, L.D. Combat Edge: A Test Subject Perspective. SAFE Journal, Vol. 21, No. 1, pp 21-25, Spring Quarter-1991.