			35R-TR-(17-02
	CUMENTATION PA		Form Approved OMB No. 0704-0188
pathening and maintaining the data needed, and con collection of information, including suggestions for r Davis Highway, Suite 1294, Arlington, VA 22202-430	ation is estimated to average 1 hour per in pleting and reviewing the collection of u reducing this burden. To Washington Hea 2, and to the Office of Management and i	response, including the time for n nformation. Send comments regu dquarters Services, Directorate fo Budget, Paperwork Reduction Pro	eviewing instructions, searching existing data sources reling this burden estimate or any other aspect of the r Information Operations and Reports, 1215 Jefferson ject (0704-0188), Washington, DC 20503.
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AN	D DATES COVERED cal (1994-1997)
A TITLE AND SUBTITLE	8/5/97	Fillai lecimi	5. FUNDING NUMBERS
Development and Utiliz Optical Materials	ation of Device Qual	ity Nonlinear	F49620-94-1-0312 1651/01
S. AUTHOR(S)			
Larry R. Dalton		62173C	
7. PERFORMING ORGANIZATION NAM	E(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER
University of Southern Department of Chemistry Loker Hydrocarbon Rese Los Angeles, CA 90089-	y arch Insitute		NEF OKT NOMBER
9. SPONSORING / MONITORING AGENC	Y NAME(S) AND ADDRESS(ES	5)	10. SPONSORING / MONITORING
Dr. Charles YC. Lee Air Force Office of Sc Bolling Air Force Base		n_{1}	AGENCY REPORT NUMBER
11 CHOREMENTARY NOTES		100	71000 045 -
	ATEMENT	199	71003 045
12a. DISTRIBUTION AVAILABILITY ST Approved for Public Re			
13. A3STRACT (Maximum 200 words) Chromophores with impro incorporated into polym thin films, poled near poling-induced electro-	lease :_ Distribution wed molecular hyperp ers which can be use the glass transition optic activity. A v used to prepare mate ty when examimed for pare buried channel w waveguide with sili s have been provided	n Unlimited polarizability ha ed to prepared op a temperature, an variety of lattic erials which show 1000 hours at 1 vaveguides and to ica fibers and VL to a number of c	12b. DISTRIBUTION CODE ve been covalently tical quality spin cast d hardened to lock-in e hardening protocols no significant loss of 00°C. Reactive ion integrate polymeric SI semiconductor ompanies and academic
 12a. DISTRIBUTION AVAILABILITY STA Approved for Public Res 13. A3STRACT (Maximum 200 words) Chromophores with impro- incorporated into polym thin films, poled near poling-induced electro- have been developed as electro-optical activil etching is used to prep electro-optic modulator electronics. Materials 	lease :_ Distribution wed molecular hyperp ers which can be use the glass transition optic activity. A v used to prepare mate ty when examimed for pare buried channel w waveguide with sili s have been provided	n Unlimited polarizability ha ed to prepared op a temperature, an variety of lattic erials which show 1000 hours at 1 vaveguides and to ica fibers and VL to a number of c	12b. DISTRIBUTION CODE ve been covalently tical quality spin cast d hardened to lock-in e hardening protocols no significant loss of 00°C. Reactive ion integrate polymeric SI semiconductor ompanies and academic
 12a. DISTRIBUTION AVAILABILITY ST/ Approved for Public Res 13. A3STRACT (Maximum 200 words) Chromophores with improvincorporated into polym thin films, poled near poling-induced electro- have been developed as electro-optical activil etching is used to prep electro-optic modulator electronics. Materials laboratories attempting 	lease :_ Distribution wed molecular hyperp ers which can be use the glass transition optic activity. A v used to prepare mate ty when examimed for pare buried channel w waveguide with sili s have been provided	n Unlimited polarizability ha ed to prepared op a temperature, an variety of lattic erials which show 1000 hours at 1 vaveguides and to ica fibers and VL to a number of c	12b. DISTRIBUTION CODE ve been covalently tical quality spin cast d hardened to lock-in e hardening protocols no significant loss of 00°C. Reactive ion integrate polymeric SI semiconductor ompanies and academic
 12a. DISTRIBUTION AVAILABILITY STA Approved for Public Res 13. A3STRACT (Maximum 200 words) Chromophores with impro- incorporated into polym thin films, poled near poling-induced electro- have been developed as electro-optical activil etching is used to prep electro-optic modulator electronics. Materials laboratories attempting 14. SUSJECT TERMS Polymeric electro-optic transducers, integration 	<pre>lease :_ Distribution wed molecular hyperp mers which can be use the glass transition optic activity. A v used to prepare mate ty when examimed for pare buried channel w waveguide with sili have been provided to utilize polymeri modulators, lattice h with VLSI electronic</pre>	n Unlimited polarizability ha ed to prepared op a temperature, an variety of lattic erials which show 1000 hours at 1 vaveguides and to ica fibers and VL to a number of c ic electro-optic hardening, signa ics and fiber opt	12b. DISTRIBUTION CODE ve been covalently tical quality spin cast d hardened to lock-in e hardening protocols no significant loss of 00°C. Reactive ion integrate polymeric SI semiconductor ompanies and academic modulators. 15. NUMBER OF PAGES 15
 12a. DISTRIBUTION AVAILABILITY STA Approved for Public Res 13. A3STRACT (Maximum 200 words) Chromophores with impro incorporated into polym thin films, poled near poling-induced electro- have been developed as electro-optical activil etching is used to prep electro-optic modulator electronics. Materials laboratories attempting 14. SUSIECT TERMS Polymeric electro-optic transducers, integration 100 GHz bandwidth, phase 	<pre>lease :_ Distribution wed molecular hyperp mers which can be use the glass transition optic activity. A v used to prepare mate ty when examimed for pare buried channel w waveguide with sili have been provided to utilize polymeri modulators, lattice h with VLSI electronic</pre>	h Unlimited olarizability ha ed to prepared op h temperature, an variety of lattic erials which show 1000 hours at 1 vaveguides and to ica fibers and VL to a number of c ic electro-optic hardening, signa ics and fiber opt conversion	12b. DISTRIBUTION CODE ve been covalently tical quality spin cast d hardened to lock-in e hardening protocols no significant loss of 00°C. Reactive ion integrate polymeric SI semiconductor ompanies and academic modulators. 11 15. NUMBER OF PAGES 15 11 15. NUMBER OF PAGES 15 11 15. NUMBER OF PAGES 15

•

DEVELOPMENT AND UTILIZATION OF DEVICE QUALITY NONLINEAR OPTICAL MATERIALS

F49620-94-1-0312

Final Progress Report Submitted to

DR. CHARLES Y-C. LEE DIRECTORATE OF CHEMISTRY AND MATERIALS SCIENCE AIR FORCE OFFICE OF SCIENTIFIC RESEARCH BOLLING AFB, WASHINGTON, D.C. 20332-6448

by

LARRY R. DALTON PROFESSOR OF CHEMISTRY LOKER HYDROCARBON RESEARCH INSTITUTE UNIVERSITY OF SOUTHERN CALIFORNIA LOS ANGELES, CALIFORNIA 90089-1661

R. DALTON

PRINCIPAL INVESTIGATOR

Philip of Stephens 815197 **PHILIP J. STEPHENS** DATE CHAIRMAN, CHEMISTRY DEPT.

REVIEW OF OBJECTIVES:

The primary objective of this contract is to develop processible nonlinear optical materials and processing protocols which permit fabrication of prototype electro-optic modulator devices and integrated opto-electronic circuits. This effort provides the primary materials support for device development efforts carried out by W. H. Steier at USC, H. Fetterman at UCLA, Y. Shi at TACAN, W. Bischel at Deacon Research, and R. Mustacich at RVM Scientific.

STATUS OF EFFORT:

An excellent overview of this effort is provided by the article "Polymeric electrooptic modulators" by L. R. Dalton published in Chemistry & Industry, No. 13, pp. 510-514, July 7, 1997 issue. A reprint of this article is provided as an appendix to this report.

Three classes of electric field poling/lattice hardening reactions have been developed for preparing thermally stable nonlinear optical materials exhibiting electrooptic coefficients in excess of 15 pm/V (Dalton, et al., Chemistry of Materials, 7, 1060-1081 (1995)). Thermally stability is defined as retention of 95% or greater of optical nonlinearity after 1000 hours at 100°C. Both intra and intermolecular condensation reactions have been used to lock-in poling-induced order and to harden materials sufficiently to permit subsequent processing. These efforts have permitted the fabrication of a variety of prototype electro-optic modulator devices and the performance of these devices has been demonstrated to 113 GHz (Chen, et al., Proc. SPIE, 3007, 314-317, 1997). Both reactive ion (reactive ion etching and electron cyclotron resonance etching) and photolithographic methods have been developed for preparing buried channel nonlinear optically active waveguides. These methods have been coupled with silicon v-groove techniques to develop mechanically stable coupling of polymeric waveguides with silica fiber transmission lines. Tapered transitions have been fabricated and tested to reduce optical loss due to mode size mismatch between silica fibers and polymer EO modulator waveguide. Recently processing protocols have been developed which permit integration of polymer electro-optic devices on non-planar silicon integrated circuits (e.g., VLSI wafers). Both vertical and horizontal integration has been demonstrated (Dalton, Chemistry & Industry, no. 14, 510-514, 1997).

Recently, London theory has been used to identify problems in poling efficiency and lattice hardening efficiency and show that these problems arise from chromophorechromophore electrostatic interactions (Proc. Natl. Acad. Sci. USA, 94, 4842-4847, 1997). Problems of transient and non-transient chromophore association and aggregation can be circumvented by chromophore redesign. In particular, prolate ellipsoidal structures should be avoided in favor of spherical and oblate ellipsoidal structures. Pulsed poling protocols have been successfully used to overcome problems of chromophore association; such techniques exploit knowledge of orientation and distance dependence of electrostratic interactions which can be obtained from London electrical conductivity theory calculations. Problems associated with and photoconductivity effects have been identified and insight gained has been used to develop improved active polymer waveguides and improved cladding materials.

A detailed study of the effect of processing conditions upon modulator performance has been carried out. Optical loss due to material inhomogeneity associated with processing conditions has been investigated. Oligomer distributions and phase separation of crosslinking reagents in thermosetting reactions have been studied employing a variety of techniques including GPC. Not only have conditions leading to reduced optical loss been defined but the reproducibility of production of acceptable modulators has been achieved. Poling-induced optical loss has also been systematically investigated. Such loss has been shown to arise either from surface damage due to corona poling or an electrophoretic effect involving high dipole moment chromophores. Again conditions have been defined which lead to lowest possible optical loss.

ACCOMPLISHMENTS/NEW FINDINGS:

Three different schemes have been devised for fabricating hardened polymeric NLO lattices. The first is a precursor route where a soluble and processible polymer containing an NLO chromophore is prepared and processed into optical quality films by spin casting. The material is then poled and a crosslinking reaction is initiated while the This lattice hardening reaction locks in the poling-induced poling field is on. noncentrosymmetric order (i.e., elevates the glass transition temperature of the polymer lattice). This process typically yields materials which retain optical nonlinearity (during dynamic assays) to temperatures greater than 170°C. The precursor route has the advantage of permitting use of solvents compatible with clean room operation and permits reproducible poling with minimal effort. An example of the precursor route is the LD-3 material (developed under this program) currently used by TACAN/lpitek, AdTech, Radiant Research, Deacon Research/Gemfire and RVM Scientific. The second route involves the use of thermosetting materials such as in sol-gel processing. With this approach, poling and hardening processes are not well-separated and "stepped" poling protocols have been found to yield dramatically improved optical nonlinearities relative to single temperature/electric field poling. The thermosetting approach requires more effort to achieve optimal results but this approach does have the advantage of permitting high chromophore number densities to be obtained and is compatible with clean room processing. An example of this approach is the PU-DR19 material used by TACAN (Shi et al., IEEE J. Selected Topics in Quantum Electronics, 2, 289-99, 1996). The final approach started as a modification of polyimide chemistry where an intramolecular condensation (imidization) reaction is used to achieve lattice hardening. A variety of synthetic schemes were developed for incorporating chromophores into polyamic acid/polyimide polymers. This approach has the advantage of permitting excellent thermal stability of optical nonlinearity to be achieved but suffers from the requirement of harsh solvents which are difficult to use with clean room processing and which can effect chromophore stability when high $\mu\beta$ chromophores are used. These problems with the polyimide approach have been addressed recently by generalizing the synthesis of heteroaromatic polymers exploiting both intra and intermolecular condensation for lattice hardening. This generalization permits precursor polymers with improved solubility in conventional processing solvents to be prepared.

With all of the above approaches, attention must be given to chromophore aggregation associated with strong electrostatic interactions. Such interactions can be overcome by improved chromophore design and by utilization of pulsed poling protocols.

New processing techniques, e.g., laser-assisted poling and molecular selfassembly assisted poling, have been developed to improve the order parameter for noncentrosymmetric alignment of chromophores in polymeric materials. Laser-assisted poling is particularly important for development of devices (such as 100 GHz modulators) employing in-plane electrode configurations.

3

Major progress has been made in the area of fabrication of buried channel nonlinear optical waveguides and in the interface (coupling) of such polymeric waveguides to silica fiber optic transmission lines. The Dalton and Steier groups at USC have pioneered the use of reactive ion etching techniques and new photolithographic techniques for the fabrication of buried channel waveguides characterized by reduced optical loss. Electron cyclotron resonance etching, which facilitates greater control over plasma conditions, has been shown to permit realization of smoother channel walls (hence reduced optical loss) than can be achieved by conventional reactive ion etching. Reactive ion processing has been used to effect silicon v-groove etching which, in turn, has served as the basis for precise alignment of polymer and silica waveguides and the development of mechanically-stable, low loss couplings.

Öptical loss due to mode mismatch has been dramatically reduced by fabrication of tapered transitions (A. Chen et al., Proc. SPIE, 3005, 65-76, 1997). Such tapered transitions have been generated both by reactive ion etching (RIE) and multicolor photolithography (MCP) processing methods.

The final area where major progress has been made is that of integration of polymeric optical circuitry with semiconductor electronic circuitry. We have demonstrated that an NLO active polymeric waveguide structure can be fabricated on a planarized VLSI semiconductor wafer and that integration can be accomplished without degradation of either electronic or optical circuit function.

The above advances in processing and materials technology has permitted demonstration of electro-optic modulation to 113 GHz and has permitted the first demonstration of integration of polymeric and semiconductor circuitry. The materials effort supported by this contract has permitted fundamental questions to be answered concerning the feasibility of utilizing polymeric materials for commercial modulator applications.

As noted in the Chemistry & Industry article, work under this contract has achieved for the first time polymeric electro-optic modulator materials which are competitive and even superior to lithium niobate in terms of electro-optic coefficient, permit greater bandwidth to be achieved, permit easy integration with semiconductor electronics and silica fiber optics, and exhibit excellent stability in field tests. Further material improvements (particularly further improvement in electro-optic coefficient and reduction in optical loss at various operating wavelengths) are necessary for wide scale commercial application; however, work performed under this contract has set the stage for initial niche commercial applications.

PERSONNEL SUPPORTED:

Larry R. Dalton, Principal Investigator, 1 month summer Fritz Strohkendl, Postdoctoral Fellow, partial support Zhixin Yang, Postdoctoral Fellow, partial support Beth Etzenhouser, Postdoctoral Fellow, partial support Mingqian He, Postdoctoral Fellow, partial support Shane Mao, Postdoctoral Fellow, partial support Aaron Harper, Postdoctoral Fellow, partial support Theresa Axenson, Graduate Research Assistant, partial support Rima Ghosn, Graduate Research Assistant, partial support Jingsong Zhu, Graduate Research Assistant, partial support Hu Li, Graduate Research Assistant, partial support Michael Lee, Graduate Research Assistant, partial support Darin Files, Graduate Research Assistant, partial support Jim Yan, Graduate Research Assistant, partial support

F49620-94-1-0312 PUBLICATIONS:

- 1. H. H. B. Meng, L. R. Dalton, and S. T. Wu, "Synthesis and Physical Properties of Asymmetric Diphenyldiacetylenic Liquid Crystals," <u>Mol. Cryst. Liq. Cryst.</u>, 250, 303-313 (1994).
- 2. F. P. Strohekendl, D. Files, and L. R. Dalton, "Highly Stable Amplification of Femtosecond Pulses," J. Opt. Soc. Amer, <u>B11</u>, 742-749 (1994).
- W. Wang, D. Chen, H. R. Fetterman, Y. Shi, W. H. Steier, and L. R. Dalton, "Traveling Wave Electro-Optic Modulator Using Cross-Linked Nonlinear Optical Polymer," <u>Appl. Phys. Lett.</u>, <u>65</u>, 929-31 (1994).
- S. Ť. Wu, J. D. Margerum, H. B. Meng, Č. S. Hsu, and L. R. Dalton, "Potential Liquid Crystal Mixtures for CO₂ Laser Application," <u>Appl. Phys. Lett.</u>, <u>64</u>, 1204-6 (1994).
- 5. M. W. Becker, L. S. Sapochak, L. R. Dalton, Y. Shi, W. H. Steier, and A. K. Jen, "Large and Stable Nonlinear Optical Effects for a Polyimide Covalently Incorporating an NLO Chromophrore," <u>Chemistry of Matierals</u>, 6, 104-6 (1994).
- 6. S. Kalluri, W. H. Steier, Z. Yang, C. Xu, B. Wu, L. R. Dalton, Y. Shi, and J. H. Bechtel, "Enhancement of Electro-Optic Properties and Temperature Stability in Sol-Gel Polymer Thin Films," Proc. SPIE, 2285, 67-75 (1994).
- Y. Shi, J. H. Bechtel, S. Kalluri, W. H. Steier, C. Xu, B. Wu, and L. R. Dalton, "Measurement of Electro-Optic Coefficient Dispersion in Poled Nonlinear Optical Polymer Thin Films," <u>Proc. SPIE</u>, <u>2285</u>, 131-40 (1994).
- 8. Z. Yang, C. Xu, B. Wu, L. R. Dalton, S. Kalluri, W. H. Steier, Y. Shi, and J. H. Bechtel, "Anchoring Both Ends of Chromophores into Sol-Gel Neworks for Large and Stable Optical Nonlinearities, <u>Chemistry of Materials</u>, <u>6</u>, 1899-901 (1994).
- S.Kalluri, Y. Shi, W. H. Steier, Z. Yang, C. Xu, and L. R. Dalton, "Improved Poling and Thermal Stability of Sol-Gel Nonlinear Optical Polymers," <u>Appl.</u> <u>Phys. Lett.</u>, <u>65</u>, 2651-3 (1994).
- 10. S. T. Wu, J. D. Margerum, H. B. Meng, C. S. Hsu, and L. R. Dalton, "Potential Liquid-Crystal Mixtures for CO₂-Laser Application," <u>Appl. Phys. Lett.</u>, <u>64</u>, 1204-1206 (1994).
- 11. F. P. Strohkendl, R. J. Larsen, L. R. Dalton, and R. W. Hellwarth, "Nonlinear Optical Properties of a C60 Film Between 740 nm and 880 nm", <u>Proc. SPIE</u>, 2285, 186-195 (1994).
- B. Wu, C. Xu, L. R. Dalton, S. Kalluri, Y. Shi, and W. H. Steier, "Second-Order Nonlinear Optical Polymers With Different Chromophore Arrangements," Materials Research Society Symposium Proceedings, <u>Vol. 328</u>, <u>Electrical</u>, <u>Optical and Magnetic Properties of Organic Solid State Materials</u> (Materials Research Society, Pittsburgh, 1994) pp. 529-34.
- C. Xu, B. Wu, L. R. Dalton, Y. Shi, P. M. Ranon, S. Kalluri, and W. H. Steier, "Realization of Large, Stable Second Order Optical Nonlinearities Through Double-End Crosslinkable Chromophores," Materials Research Society Symposium Proceedings, <u>Vol. 328</u>, <u>Electrical, Optical and Magnetic Properties</u> <u>of Organic Solid State Materials</u> (Materials Research Society, Pittsburgh, 1994) pp. 461-6.

- L. R. Dalton, B. Wu, A. Harper, R. Ghosn, Y. Ra, Z. Liang, R. Montgomery, S. Kalluri, Y. Shi, W. H. Steier, A. K.-Y. Jen, "Techniques of Ultrastructure and Chromophore Synthesis Relevant to the Fabrication of High Frequency Electro-Optic Modulators," <u>Polymer Preprints</u>, <u>35</u>, 128-9 (1994); <u>Polymers for Second-Order Nonlinear Optics</u>, Chap. 12, ACS Symposium Series 601 (G. A. Lindsay and K. D. Singer, eds) Amer. Chem. Soc., Washington, DC, 1995, pp. 158-171.
- 15. M. Ziari, W. H. Steier, L. R. Dalton, Y. Shi, W. Wang, D. Chen, and H. R. Fetterman, "Electrooptic Polymer Waveguide Fabrication," <u>Polymer Preprints</u>, <u>35</u>, 227 (1994).
- 16. L. R. Dalton, C. Xu, A. W. Harper, R. Ghosn, B. Wu, Z. Liang, R. Montgomery, and A. K.-Y. Jen, "Development and Application of Organic Electro-Optic Modulators," <u>Nonlinear Optics</u>, <u>10</u>, 383-407 (1995).
- 17. L. R. Dalton, A. W. Harper, B. Wu, R. Ghosn, J. Laquindanum, Z. Liang, A. Hubbel, and C. Xu "Polymeric Electro-Optic Modulators: Materials Synthesis and Processing," <u>Advanced Materials</u>, 7, 519-40 (1995).
- H. W. Oviatt, Jr., K. J. Shea, S. Kalluri, Y. Shi, W. H. Steier, and L. R. Dalton, "Applications of Organic Bridged Polysilsesquioxane Xerogels to Nonlinear Optical Materials by the Sol-Gel Method," <u>Chemistry of Materials</u>, 7, 493-8 (1995).
- Ż. Liang, L. R. Dalton, S. M. Garner, S. Kalluri, A. Chen, and W. H. Steier, "Crosslinkable Polyimide for Second-Order Optical Nonlinearities," <u>Chemistry of</u> <u>Materials</u>, 7, 941-4 (1995).
- 20. L. R. Dalton, A. W. Harper, R. Ghosn, W. H. Steier, M. Ziari, H. Fetterman, Y.
- Shi, R. Mustacich, A. K.-Y. Jen, and K. J. Shea, "Synthesis and Processing of Improved Second Order Nonlinear Optical Materials for Applications in Photonics," <u>Chemistry of Materials</u>, 7, 1060-81 (1995).
- 21. W. Wang, D. Chen, H. R. Fetterman, Y. Shi, W. H. Steier, and L. R. Dalton, "40-GHz Polymer Electrooptic Phase Modulators," IEEE Photonics Technology Letters, 7, 638-640 (1995).
- M. Ziari, S. Kalluri, S. Garner, W. H. Steier, Z. Liang, L. R. Dalton, and Y. Shi, "Novel Electro-Optic Measurement Technique for Coplanar Electrode-Poled Polymers," <u>Proc. SPIE</u>, <u>2527</u>, 218-27 (1995).
- S. Kalluri, A. Chen, V. Chuyanov, M. Ziari, W. H. Steier, and L. R. Dalton, "Integration of Polymer Electrooptic Devices on Non-Planar Silicon Integrated Circuits," <u>Proc. SPIE</u>, <u>2527</u>, 375-83 (1995).
- L. R. Dalton, "Nonlinear Optical Materials," <u>Kirk-Othmer Encyclopedia of</u> <u>Chemical Technology</u>, 4th Ed., Vol. 17, (John Wiley & Sons, New York, 1995), pp 288-302.
- 25. Z. Liang, L. R. Dalton, S. M. Garner, S. Kalluri, A. Chen and W. H. Steier, "A Heterocyclic Polymer With Thermally Stable Second-Order Optical Nonlinearity, <u>Chemistry of Materials</u>, 7, 1756-8 (1995).
- S. Kalluri, A. Chen, M. Ziari, W. H. Steier, Z. Liang, L. R. Dalton, D. Chen, B. Jalali, and H. R. Fetterman, "Vertical Integration of Polymer Electro-Optic Devices on Electronic Circuits," <u>Opt. Soc. Amer. Tech. Digest. Ser.</u>, <u>21</u>, 317-20 (1995).
- W. Wang, D. Chen, H. R. Fetterman, Y. Shi, J. H. Bechtel, S. Kalluri, W. H. Steier, and L. R. Dalton, "60 GHz Electro-optic Modulation by Polymer Waveguide Phase Modulators," Opt. Soc. Amer. Tech. Digest. Ser., 21, 293-6 (1995).

- S. Garner, S. Kalluri, M. Ziari, W. H. Steier, Y. Shi, Z. Liang, and L. R. Dalton, "A Two Slit Electrooptic Coefficient Measurement Technique and Efficient In-Plane Poling of Polymer Thin Films," <u>Opt. Soc. Amer. Tech. Digest. Ser.</u>, <u>21</u>, 383-5 (1995).
- W. Wang, D. Chen, H. R. Fetterman, W. H. Steier, L. R. Dalton, P. M. D. Chow, "Optical Heterodyne Detection of 60 GHz Electro-Optic Modulation From Polymer Waveguide Modulators," <u>Appl. Phys. Lett.</u>, <u>67</u>, 1806-8 (1995).
- F. P. Strohkendl, R. J. Larsen, T. J. Axenson, L. R. Dalton, R. W. Hellwarth, H. W. Sarkas, and Z. H. Kafafi, "Nonlinear Optical Properties of a C₇₀ Film Between 740 and 880 nm", Proc. SPIE, 2530, 165-74 (1995).
- N. Tang, R. W. Hellwarth, J. P. Partanen, S. Sun, and L. R. Dalton, "Optical Limiting in Protonic Doped Bis-Benzothiazole," <u>Mat. Res. Soc. Symp. Proc.</u>, <u>374</u>, 225-40 (1995).
- 32. L. R. Dalton, "High Frequency Electro-Optic Modulation and Integration of Photonic and VLSI Electronic Circuitry Demonstrated," <u>Photonics Science</u> <u>News</u>, <u>1</u>, 7-9 (1995).
- 33. S. Kalluri, M. Ziari, A. Chen, V. Chuyanov, W. H. Steier, D. Chen, B. Jalali, H. R. Fetterman, and L. R. Dalton, "Monolithic Integration of Waveguide Polymer Electrooptic Modulators on VLSI Circuitry," <u>IEEE Photonics Technology Letters</u>, 8, 644-6 (1996).
- 34. S. Kalluri, S. Garner, M. Ziari, W. H. Steier, and L. R. Dalton, "Simple two-slit interference electrooptic coefficients measurement technique and efficient coplanar electrode poling of polymer thin films," <u>Appl. Phys. Lett.</u>, <u>69</u>, 275-7 (1996).
- 35. S. J. Sun, A. W. Harper, C. Zhang, L. R. Dalton, S. M. Garner, A. Chen, A. Yacoubian, and W. H. Steier, "Synthesis and Characterization of 1,3-Bis(Dicyanomethylene)indane (BDMI) Derived Second Order NLO Materials," Materials Research Society Symposium Proceedings, <u>Vol. 413, Electrical,</u> <u>Optical and Magnetic Properties of Organic Solid State Materials</u> (Materials Research Society, Pittsburgh, 1996) 263-8.
- W. H. Steier, S. Kalluri, A. Chen, S. Garner, V. Chuyanov, M. Ziari, Y. Shi, H. Fetterman, B. Jalali, W. Wang, D. Chen, and L. R. Dalton, "Applications of Electro-Optic Polymers in Photonics," Materials Research Society Symposium Proceedings, Vol. 413, Electrical. Optical and Magnetic Properties of Organic Solid State Materials (Materials Research Society, Pittsburgh, 1996) 147-58.
- L. R. Dalton, "Polymers for Electro-Optic Modulator Waveguides," in <u>Electrical</u> and Optical Polymer Systems: Fundamentals, Methods, and Applications, eds.
 D. L. Wise, T. M. Cooper, J. D. Gresser, D. J. Trantolo, and G. E. Wnek, (World Scientific, Sinapore, 1996).
- F. P. Strohkendl, L. R. Dalton, R. W. Hellwarth, H. W. Sarkas, and Z. H. Kafafi, "Phase-Mismatch in Degenerate Four-Wave-Mixing: The Complex Third-Order Susceptibility Tensor of C₆₀ at 768 nm," <u>J. Opt. Soc. Amer. B</u>, <u>14</u>, 92-8 (1997).
- Z. Liang, Z. Yang, S. Sun, B. Wu, L. R. Dalton, S. M. Garner, S. Kalluri, A. Chen, and W. H. Steier, "Processible and Thermally Stable Heterocyclic Polymers for Second-Order Nonlinear Optical Studies," <u>Chemistry of Materials</u>, <u>8</u>, 2681-5 (1996).
- S. Sun, C. Zhang, L. R. Dalton, S. M. Garner, A. Chen, and W. H. Steier, "1,3-Bis(Dicyanomethylene)indane Based Second Order NLO Materials," <u>Chemistry</u> of Materials, 8, 2539-41 (1996).

- 41. A. Chen, K. Kaviani, A. Remple, S. Kalluri, W. H. Steier, Y. Shi, Z. Lliang, and L. R. Dalton, "Optimized Oxygen Plasma Etching of Polyurethane Based Electrooptic Polymers for Low Loss Waveguide Fabrication," <u>Journal of the Electrochemical Society</u>, <u>143</u>, 3648-51 (1996).
- 42. F. P. Strohkendl, T. J. Axenson, L. R. Dalton, R. W. Hellwarth, H. W. Sarkas, and Z. H. Kafafi, "Degenerate Four-Wave Mixing Spectrum of C₆₀ Between 0.74 and 1.7 mm," Proc. SPIE, 2854, 191-8 (1996).
- 43. L. R. Dalton, "Polymeric Electro-Optic Modulators," <u>Chemistry & Industry</u>, No. 13, 510-4 (1997).
- 44. Y. Shi, W. Wang, J. H. Bechtel, A. Chen, S. Garner, S. Kalluri, W. H. Steier, D. Chen, H. R. Fetterman, L. R. Dalton, L. Yu, "Fabrication and Characterization of High-Speed Polyurethane-Disperse Red 19 Integrated Electro-Optic Modulators for Analog System Applications," <u>IEEE Journal of Selected Topics in Quantum Electronics</u>, 2, 289-99 (1996).
- 45. L. R. Dalton, A. W. Harper, and B. H. Robinson, "The Role of London Forces in Defining Noncentrosymmetric Order of High Dipole Moment-High Hyperpolarizability Chromophores in Electrically Poled Polymeric Thin Films," Proc. Natl. Acad. Sci. USA, 94, 4842-4847 (1997).
- 46. L. R. Dalton, A. W. Harper, S. Sun, W. H. Steier, R. V. Mustacich, and A. K. Y. Jen, "Charge Transfer Interactions in Polymers and the Fabrication of High Frequency Electro-Optic Modulators," <u>Macromol. Symp.</u>, <u>116</u>, 135-42 (1997).
- 47. D. Chen, H. R. Fetterman, A. Chen, W. H. Steier, L. R. Dalton, W. Wang, and Y. Shi, "High-Bandwidth Polymer Modulators," <u>Proc. SPIE</u>, <u>3007</u>, 314-17 (1997).
- 48. F. P. Strohkendl, T. J. Axenson, R. J. Larsen, L. R. Dalton, R. W. Hellwarth, and Z. H. Kafafi, "Observation of the Lowest Lying Electric-Dipole-Allowed Two-Photon Resonance in C60," <u>J. Phys. Chem</u>., submitted.
- 49. S. S. Sun, C. Zhang, Z. Yang, L. R. Dalton, S. M. Garner, A. Chen, and W. H. Steier, "Synthesis and Characterization of 1,3-Bis(dicyanomethylidene)Indane (BDMI) Based Nonlinear Optical Polymers," <u>Macromolecules</u>, submitted.
- 50. D. Chen, H. R. Fetterman, A. Chen, W. H. Steier, L. R. Dalton, W. Weng, and Y. Shi, "Demonstration of 110 GHz Electro-Optic Polymer Modulators," <u>Appl. Phys.</u> Lett., submitted.
- 51. A. Chen, V. Chuyanov, F. I. Marti-Carrera, S. Garner, W. H. Steier, S. S. H. Mao, Y. Ra, L. R. Dalton, and Y. Shi, "Trimming of Polymer Waveguide Y-Junction by Rapid Photobleaching for Tuning the Power Splitting Ratio," <u>Photonics</u> <u>Technology Letter</u>, in press.
- A. Chen, V. Chuyanov, F. I. Marti-Carrera, S. Garner, W. H. Steier, J. Chen, S. Sun, and L. R. Dalton, "Integrated Polymer Waveguide Mode Size Transformer with a Vertical Taper for Improved Fiber Coupling," Optoelectronic Interconnects and Packaging IV, eds., R. P. Chen and P. S. Gulfoyle, <u>Proc. SPIE</u>, 3005, 65-76 (1997).
- 53. L. R. Dalton, A. W. Harper, J. Chen, S. Mao, S. Sun, and M. He, "Polymeric Electro-Optic Modulators: From Chromophore Design to Integration with Semiconductor VLSI Electronics and Silica Fiber Optics," <u>Ind. Eng. Chem. Res.</u> in press (1998).
- 54. S. S. H. Mao, Y. Ra, L. Guo, C. Zhang, L. R. Dalton, A. Chen, S. Garner, and W. H. Steier, "Progress Towards Device-Quality Second-Order Nonlinear Optical Materials: 1. Influence of Composition and Processing Conditions on

Nonlinearity, Temporal Stability and Optical Loss," <u>Chemistry of Materials</u>, 510-14 (1997).

- 55. L. R. Dalton, A. W. Harper, J. Chen, S. Sun, and S. Mao, S. Garner, A. Chen, and W. H. Steier, "The Role of Intermolecular Interactions in Fabricating Hardened Electro-Optic Materials," <u>Proc. SPIE</u>, <u>CR68</u>, 313-21 (1997).
- A. W. Harper, S. Sun, L. R. Dalton, S. M. Garner, A. Chen, S. Kalluri, W. H. Steier, and B. H. Robinson, "Translating Microscopic Optical Nonlinearity to Macroscopic Optical Nonlinearity: The Role of Chromophore-Chromophore Electrostatic Interactions," <u>J. Opt. Soc. Amer. B</u>, In press; <u>Opt. Soc. Amer. Tech.</u> <u>Digest, Solid State Lasers: Materials and Applications</u>, 82-4 (1997).
- 57. S. Garner, V. Chuyanov, A. Chen, S. Kalluri, F. I. Marti-Carrera, W. H. Steier, and L. R. Dalton, "Three Dimensional Integrated Optics Using Polymers," <u>Opt.</u> <u>Soc. Amer. Tech. Digest. Ser.</u>, in press.
- 58. A. Chen, F. I. Marti-Carrera, V. Chuyanov, S. Garner, W. H. Steier, S. S. H. Mao, Y. Ra, L. R. Dalton, Y. Shi, "In-Situ Trimming of Polymer Optical Waveguides by Rapid Photobleaching for Tuning Device Specifications," <u>Opt. Soc. Amer. Tech.</u> <u>Digest. Ser.</u>, in press.
- 59. A. Chen, V. Chuyanov, S. Garner, W. H. Steier, L. R. Dalton, "Modified Attenuated Total Reflection for the Fast and Routine Electrooptic Measurements of Nonlinear Optical Polymer Thin Films," <u>Opt. Soc. Amer. Tech. Digest. Ser</u>., in press.
- 60. A. Chen, V. Chuyanov, F. I. Marti-Carrera, S. Garner, W. H. Steier, J. Chen, S. Sun, S. S. H. Mao, Y. Ra, and L. R. Dalton, "Vertical Tapered Mode Size Transformer in Polymer Waveguides for Efficient Fiber Coupling," <u>Opt. Soc.</u> <u>Amer. Tech. Digest. Ser.</u>, in press.
- 61. A. Chen, S. Garner, A. Yacoubian, W. H. Steier, J. Chen, A. Harper, J. Zhu, M. He, S. Sun, F. Wang, Y. Ra, S. S. H. Mao, C. Zhang, L. R. Dalton, D. Chen, and H. R. Fetterman, "Characterization of Electro-Optic Polymers with High mb Chromophores for Photonic Device Applications," <u>Opt. Soc. Amer. Tech. Digest.</u> <u>Ser</u>., in press.
- 62. A. W. Harper and L. R. Dalton, "Polymeric Electro-Optic Modulators: Generation of Acentric Chromophore Lattices and Processing of Buried Channel Waveguides," <u>ANTEC Proceedings 97</u>, <u>919</u>, 1382-5 (1997).
- 63. F. Wang, A. W. Harper, M. He, A. Ren, L. R. Dalton, S. M. Garner, A. Yacoubian, A. Chen, and W. H. Steier, "Design and Synthesis of a Perfluoroalkyldicyanovinyl-Based NLO Material for Electro-Optic Applications," <u>Organic Thin Films</u>, ACS Symposium Series 000 (C. W. Frank, ed.) Amer. Chem. Soc., Washington, DC, 1997, in press.
- M. He, J. Zhu, A. W. Harper, S. S. Sun, L. R. Dalton, S. M. Garner, and W. H. Steier, "Progress Towards the Transition of Large Microscopic Nonlinearities to Large Macroscopic Nonlinearities for High-mb Materials," <u>Organic Thin Films</u>, ACS Symposium Series 000 (C. W. Frank, ed.) Amer. Chem. Soc., Washington, DC, 1997, in press.
- F. P. Strohkendl, T. J. Axenson, R. J. Larson, L. R. Dalton, R. W. Hellwarth, and Z. H. Kafafi, "Two-Photon Absorption Spectra of C₆₀ and C₇₀ Between 0.7 and 1.7 mm," <u>Proc. SPIE</u>, <u>3142</u>, in press (1997).
- 66. A. Chen, V. Chuyanov, F. I. Marti-Carrera, S. Garner, W. H. Steier, and L. R. Dalton, "Fast Trimming of Electro-Optic Polymer Waveguide Y-branch by Post-

Photobleaching for Tuning the Power Splitting Ratio," Proc. SPIE, 3147, in press (1997).

- 67. S. Garner, V. Ghuyanov, A. Chen, A. Yacoubian, W. H. Steier, and L. R. Dalton, "Design and Fabrication of Y-Branched Vertical Power Splitters Using Polymers," <u>Proc. LEOS'97</u>, in press (1997).
- F. P. Strohkendl, T. J. Axenson, L. R. Dalton, and Z. H. Kafafi, "Two-Photoabsorption Spectra of Fullerenes," Paper QWD39, <u>Proc. Int. Quant. Elect.</u> <u>Conf.</u>, Baltimore, May, 1997.
- 69. A. Chen, V. Chuyanov, S. Garner, W. H. Steier, J. Chen, Y. Ra, S. S. H. Mao, L. Guo, and L. R. Dalton, "Fast Maskless Fabrication of Electrooptic Polymer Devices by Simultaneous Direct Laser Writing and Electric Field Poling of Channel Waveguides," <u>Proc. LEOS'97</u>, in press (1997).
- S. S. H. Mao, Y. S. Ra, M. He, J. Zhu, C. Zhang, L. R. Dalton, S. Garner, and W. H. Steier, "Progress Toward Device-Quality Second-Order NLO Materials. 2. Enhancement of Electric Poling Efficiency and Temporal Stability by Modification of Isoxazolone Based High mb Chromophores," <u>Chemistry of</u> <u>Materials</u>, submitted.
- 71. S. S. H. Mao, Y. S. Ra, L. Guo, C. Zhang, L. R. Dalton, A. Chen, and W. H. Steier, "Progress Toward Device-Quality Second-Order NLO Materials. 3. Deteriorative Effect of Chromophore Aggregation on Optical Loss," <u>Chemistry of Materials</u>, submitted.
- 72. Y. S. Ra, S. S. H. Mao, B. Wu, L. Guo, L. R. Dalton, A. Chen, and W. H. Steier, "Thermoset Second-Order NLO Materials From a Trifunctionalized Chromophore," Polym. Prepr., 38, 86-8 (1997).
- 73. A. Chen, V. Chuyanov, H. Zhang, S. Garner, W. H. Steier, J. Chen, J. Zhu, M. He, S. S. H. Mao, and L. R. Dalton, "Demonstration of the Full Potential of Second Order Nonlinear Optic Polymers for Electrooptic Moudlation Using a High mb Chromophore and a Constant Bias Field," <u>Appl. Phys. Lett.</u>, submitted.
- A. W. Harper, J. Zhu, M. He, L. R. Dalton, S. M. Garner, and W. H. Steier, "Characterization and Circumventing Electrostatic Intermolecular Interactions in Highly Electro-Optic Polymers," Materials Research Society Symposium Proceedings, <u>Vol. 000, Electrical, Optical and Magnetic Properties of Organic</u> <u>Solid State Materials</u> (Materials Research Society, Pittsburgh, 1998) in press.

INTERACTIONS/TRANSITIONS:

INVITED LECTURES:

- 1. Third International Conference on Frontiers of Polymers and Advanced Materials, Kuala Lumpur
- 2. 28th Organosilicon Symposium, Gainesville, Florida
- 3. 1995 AČS/PMSE Symposium on Polymeric Organic Materials: Solid State Properties and Smart Materials, Anaheim, California
- 4. Materials Research Society Symposium on Thin Films for Integrated Optics Applications, San Francisco, California
- 5. National Technology Transfer Center, Technology Applications Review, Orlando, Florida
- 6. NASA Lecturer, Fifty Fourth Frontiers in Chemistry Lecture Series, Cleveland, Ohio

- 7. NATO Advanced Research Workshop on Photoactive Organic Materials: Science and Applications, Avignon, France
- 8. SPIE International Symposium on Nonlinear Optical Properties of Organic Materials VIII, San Diego, California
- 9. SPIE International Symposium of Optical and Photonic Applications of Electroactive and Conducting Polymers, San Diego, California
- 10. SPIE International Symposium on Fullerenes and Photonics II, San Diego, California
- 11. Symposium on Optoelectronic Materials and Conjugated Polymers, IV International Conference on Advanced Matierals, Cancun, Mexico
- 12. 7th International Conference on Unconventional Photoactive Systems, Stanford, California
- 13. OSA/ACS Organic Thin Films for Photonics Applications, Portland, Oregon
- 14. International Business Communications Conference on Commercial Applications for Organo Electronic Materials, Marina del Rey, CA
- 15. Society of Plastics Engineers (SPE) annual technical meeting ANTEC, Indianapolis, IN
- 16. American Chemical Society National Meeting, New Orleans, LA
- 17. American Chemical Society National Meeting, Orlando, FL
- 18. SPIE International Symposium on Fullerenes and Photonics III, Denver, CO.
- 19. ACS/OSA Symposium on Organic Thin Films for Photonic Applications, Orlando, Florida
- 20. International Conference on Nonlinear Optics 3, Marco Island, Florida
- 21. Fourth International Conference on Frontiers of Polymers and Advanced Materials, Cairo, Egypt
- 22. Symposium on Dendrimers and Hyperbranched Polymers, Spring American Physical Society National Meeting, Kansas City, Mo.
- 23. National Meeting, ANTEC, Society of Plastics Engineers, Toronto, Canada
- 24. AFOSR/ONR Photonic and Electro-Optic Polymer Review, Atlantic Beach, Florida
- 25. Sino-American Topical Meeting and Exhibit, Solid State Lasers: Materials and Applications, Tianjin, People's Republic of China
- 26. Gordon Coference on Organic Thin Films, Salve Regina
- 27. The International Society of Optical Engineering 42nd Annual Meeting, San Diego, CA.

INVITED SEMINARS:

Numerous seminars at various industries, government laboratories, and universities including seminars at University of Florida, University of Illinois, University of Washington, NASA Marshall Space Flight Center, University of California at Los Angeles, the Max-Planck-Institut fur Polymerforschung (Mainz FRG) and the Optical Science Center of the University of Arizona.

Presentations were also made before the Board of Gemfire Corporation, senior management of Hughes Research Laboratories, the Board of the Loker Hydrocarbon Research Institute and the Board of Trustees of the University of Southern California, etc.

CONSULTATIVE AND ADVISORY PANEL SERVICE:

- 1. Blue Ribbon (Final Phase) Panel for the Selection of Presidential Faculty Fellows (National Science Foundation)
- 2. Consultant, Medical Research Service, Veterans Administration
- 3. Materials Research Science & Engineering Center Panel, National Science Foundation
- 4. Panel 15, Office of Energy Efficiency and Renewable Energy Photovoltaics Review, U.S. Department of Energy
- 5. Advisory Committee, National Institutes of Health Biomedical Technology Centers at the University of Illinois and at Dartmouth University
- 6. Consultant, Arizona Disease Control Research Commission, State of Arizona
- 7. Immunobiology Study Section, National Institutes of Health
- 8. Advisory Committee, The New York Herman F. Mark Institute for Polymers Science and Engineering at the Polytechnic University, NY, NY
- 9. Editorial Advisory Board, Chemistry of Materials, American Chemical Society
- 10. Consultant, Princeton Materials Research Center.

INTERACTIONS AND TRANSITIONS:

Research Interactions and Technology Transitions include EniChem/ROI Tech/Lightwave Microsystems Corp. (A. Jen/J. Kenney), Cal Tech/JPL (S. Marder and J. Perry), Hughes Research Laboratory (U. Efron), TACAN/Integrated Photonics Technology, Ipitek (Y. Shi), AdTech (S. Sinha), Deacon Research/Gemfire (W. Bischel), RVM Scientific (R. Mustacich), IBM (D. Burland), Physical Opitcs Corporation (G. Savant), and Thermax Systems, Inc. (Bruce Sangster), Radiant Research, Inc (B. Davies and R. Chen). Also interacted with the Los Angeles Regional Development Association (LARDA).

NLO active polymeric films were provided to TACAN/lpitek, RVM Scientific, Deacon Research/Gemfire and Physical Optics Corporation to permit these organizations to pursue evaluation of these materials for prototype device development. TACAN and POC are interested in low frequency, low cost modulator fabrication. TACAN is interested in evaluating the long term, in-field performance of polymeric electro-optic modulators. RVM Scientific is interested in using new photolithographic techniques to fabricate low loss waveguides and low loss transitions from polymer waveguides to silica fiber transmission lines. Deacon Research is interested in fabricating full color, flat panel displays from polymeric electro-optic modulators.

Photoactive chromophores were transitioned to Hughes Research Laboratory for use in development of high density optical memories.

Thermax Systems, Inc. Is interested in using photoactive chromophores in cooling applications.

Discussions have been held with Exxon, Allied Signal and Audemars Corporations and with NASA Marshall Space Flight Center who have expressed interest in collaborating and participating in technology transfer.

INVENTIONS:

١.

None

HONORS/AWARDS

1. The 1996 Richard C. Tolman of the American Chemical Society (April 23,1997)

- 2. Paul C. Cross Endowed Lectureship in Chemistry, University of Washington, Seattle, WA, May 29, 1996
- 3. NASA Lecturer, 54th Frontiers of Chemistry Lecture Series, Case Western Reserve University, Cleveland, OH, April 27, 1995.
- 4. Harold and Lillian Moulton Distinguished Professorship of Chemistry (Endowed Chair), University of Southern California
- 5. Scientific Co-Director of the Loker Hydrocarbon Research Institute, University of Southern California
- 6. Nominated for the National Academy of Science
- 7. Nominated for the Chemistry of Materials Award of the American Chemical Society

The research has been featured in the news articles in the following publications: The Baltimore Sun newspaper, Chemical & Engineering News, Research & Development Magazine, Laser World Focus, Business Week, Science, BMDO Update, Wired Magazine, Photonics Spectra, Chemistry & Industry, Polymer Science News, Photonics Science News, Ind. Eng. Chem. Res., etc. A television episode of "Strange Universe" will focus on the research; the filming was completed recently at the Loker Hydrocarbon Research Institute. The research has been featured on two occasions on local radio broadcasts.

Note: Mr. Aaron Harper, who worked on this project both as a graduate student and briefly as a postdoctoral fellow, was the first recipient of the American Chemical Society Organic Division Fellowship. This fellowship provided partial salary support for Mr. Harper. Mr. Harper is now an Assistant Professor of Chemistry at Texas A&M University.

ASSERT Evaluation Report

١.

F49620-95-1-0450, An ASSERT Proposal for the Development of Advanced Polymeric E-O Modulators

During the support-period to 9/1/97. Theresa Axenson received support to carry out materials synthesis and processing activities relevant to the fabrication of advanced electro-optic modulators. This research resulted in several significant improvements in polymeric electro-optic modulator technology. The evaluation of modulators fabricated employing new technology has been extended to 113 GHz and recently vertical integration of the modulator with VLSI electronics has been demonstrated (see article by L. Dalton, Chemistry & Industry, no. 13, 510-514, 1997). Training of Ms. Axenson involved laboratory research (including training in state-of-the-art synthetic methods and use of analytical instrumentation), group meetings and symposia involving graduate and undergraduate students pursuing research under the direction of Dr. Dalton, joint research group meetings involving the research groups of Professor William Steier (USC Electrical Engineering), Professor Robert Hellwarth (USC Electrical Engineering/Electrophysics), Professor Harold Fetterman (UCLA Electrical Engineering) and Professor Dalton and meetings with visiting scientists from industrial laboratories (participating in BMDO or AFOSR research programs). Visiting industrial scientists (receiving BMDO support) included Dr. William Bischel (Deacon Research) and Dr. Robert Mustacich (RVM Scientific). During this period, a constant interaction was maintained with Dr. Y. Shi of TACAN Corporation. As Ms. Axenson has completed all formal course requirements for the Ph.D. and has passed her Ph.D. qualifying examination, she did not take formal courses but did benefit from a rich seminar program including by such distinguished visitors as Dr. F. Kajzar (CEA, France), Dr. Joseph Zyss (France Telecom), Dr. John Reynolds (Univ. of Florida), and Dr. Robert Grubbs (Cal. Tech.). Ms. Axenson's research involved the first effort to incorporate high $\mu\beta$ chromophores into polymer lattices. Three different schemes were developed for stabilization of poling-induced noncentrosymmetric chromophore order. The first is a precursor polymer route where a soluble and processable polymer, containing an NLO chromophore as a pendant to the polymer main chain, is prepared and processed into optical guality films by spin casting. The material is then poled and a crosslinking reaction is initiated while the poling field is on. This lattice hardening reaction locks in the poling-induced noncentrosymmetric order (i.e., elevates the glass transition temperature of the polymer lattice). The process typically yields materials which retain optical nonlinearity to temperatures as high as 170°C (during dynamic assays). The precursor route has the advantage of permitting use of solvents compatible with clean room operation and permits reproducible poling with minimal effort. The second route involves use of thermosetting materials such as in sol-gel processing. With this approach, poling and hardening processes are not wellseparated and "stepped" poling protocols have been found to yield dramatically improved optical nonlinearities relative to single temperature/electric field poling. The thermosetting approach requires more effort to achieve optimal results but this approach does have the advantage of permitting high chromophore number densities to be realized. The final approach utilizes intramolecular crosslinking (as in the imidization reaction) to achieve lattice hardening.

Ms. Axenson also worked on extension of London theory to provide the first quantitative understanding of the role of chromophore electrostatic interactions in defining poling efficiency and lattice hardening efficiency observed for high dipole moment/high polarizability chromophores. She also pioneered the development of new spectroscopic techniques for characterizing both optical nonlinearity and photochemical stability. Her work during the past year has already resulted in several publications (with more to follow from work already completed) and has resulted in several invited lecture presentations including an SPIE presentation and a presentation at the Naval Research Laboratories in Washington.