

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 8/28/97	3. REPORT TYPE AND DATES COVERED Final Report, 7/1/93-6/30/97	
4. TITLE AND SUBTITLE A CAD System for Optical Waveguide Circuits: A "Spice" Program for Optical Circuits			5. FUNDING NUMBERS F49620-93-1-0425	
6. AUTHOR(S) Prof. Richard M. Osgood, Jr.				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Columbia University Columbia Radiation Laboratory 530 West 120th St., rm. 1001 New York, NY 10027			8. PERFORMING ORGANIZATION REPORT NUMBER AFOSR-TR-97 0444	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/DARPA 110 Duncan Avenue, Suite B115 Bolling AFB, Washington DC 20332-001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NE	
11. SUPPLEMENTARY NOTES			19971006 031	
<p>DISTRIBUTION STATEMENT A Approved for public release Distribution Unlimited</p> <p><i>Unlimited</i></p>				
13. ABSTRACT (Maximum 200 words) A major focus of our current DARPA/AFOSR contract is the development of photonic devices appropriate to integrated optical circuits. Success in this area requires a significant effort in the area of modeling and simulation of optical wave propagation. The focus of this AASERT was to develop computer-aided design and modeling software for photonic integrated circuits. This effort built on software previously developed in our group for optical waveguide simulation using the beam propagation method. In this AASERT program we have developed a broadly applicable tool for device simulation which includes the ability to handle arbitrary device structures in 2D and 3D, along with state-of-the-art numerical algorithms dealing with all possible physical phenomena of interest. A graphical user interface enables researchers and engineers to rapidly use the tool to solve problems, without being an expert in numerical methods and programming. In this report, we outline the technical achievements of this work.				
14. SUBJECT TERMS computer-aided design, beam propagation method, integrated optics			15. NUMBER OF PAGES 10	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	

CRL

Columbia University

**AUGMENTATION AWARDS FOR SCIENCE AND ENGINEERING
RESEARCH TRAINING (AASERT)**

FINAL REPORT

for Grant: F49620-93-1-0425

for the Period: 7/1/93-6/30/97

submitted to:

Air Force Office of Scientific Research

110 Duncan Avenue, Ste. B115

Bolling AFB, DC 20332-0001

submitted by:

Columbia Radiation Laboratory

Columbia University in the City of New York

530 West 120th St., Rm. 1001, MC8903

New York, NY 10027

prepared by:

Richard M. Osgood, Jr.

Columbia Radiation Laboratory

August 28, 1997

DTIC QUALITY INSPECTED 3

Table of Contents

Abstract	3
1. Statement Of the Problem Studied	4
2. Summary of Results	4
3. Publications	8
4. Technical Reports Published	9
5. Inventions	9
6. Degrees Supported and Degrees Earned	9

ABSTRACT

A major focus of our current DARPA/AFOSR contract is the development of photonic devices appropriate to integrated optical circuits. Success in this area requires a significant effort in the area of modeling and simulation of optical wave propagation. The focus of this AASERT was to develop computer-aided design and modeling software for photonic integrated circuits. This effort built on software previously developed in our group for optical waveguide simulation using the beam propagation method. In this AASERT program we have developed a broadly applicable tool for device simulation which includes the ability to handle arbitrary device structures in 2D and 3D, along with state-of-the-art numerical algorithms dealing with all possible physical phenomena of interest. A graphical user interface enables researchers and engineers to rapidly use the tool to solve problems, without being an expert in numerical methods and programming. In this report, we outline the technical achievements of this work.

1. STATEMENT OF THE PROBLEM STUDIED

A major focus of our current DARPA/AFOSR contract is the development of photonic devices appropriate to integrated optical circuits. Success in this area requires a significant effort in the area of modeling and simulation of optical wave propagation.

The focus of this AASERT was to develop computer-aided design and modeling software for photonic integrated circuits. This effort built on software previously developed in our group for optical waveguide simulation using the beam propagation method.¹

In this AASERT program we intended to develop a broadly applicable tool for device simulation which would include the following features:

- 1) Ability to handle arbitrary device structures in 2D and 3D;
- 2) State-of-the-art numerical algorithms dealing with all possible physical phenomena of interest;
- 3) A graphical user interface enabling researchers and engineers to rapidly use the tool to solve problems, without being an expert in numerical methods and programming.

In this report, we outline the technical achievements of this work. In summary, the above objectives have been successfully met, as evidenced by the fact that the software we have developed has been licensed to a commercial software company, RSoft, Inc., and the product, *BeamPROP*, is the leading software of its type in the U.S. market.

2. SUMMARY OF RESULTS

In this section, we outline the key accomplishments made under this AASERT.

In the first task, the previously existing program¹, which was written in FORTRAN, was hand-translated into C++. This accomplished two goals central to the success of the project. First, it allows the use of modern class libraries for GUI development, which simplifies programming and increases portability. Second, it provides a highly-portable base of code which allows the simulation to be run on PCs, workstations, and supercomputers if necessary.

In the second major task, a modern, object-oriented graphical interface was added to the program, using a portable class library that spans DOS, Windows, OS/2, and

UNIX/Motif. The interface includes a complete CAD system which allows optical circuits to be laid out using the mouse. A palette of basic waveguide slopes including straight, curved, y-branch, and s-bend waveguides is available. Standard CAD operatives exist to allow components to be moved, sized, flipped, and duplicated. Specialized programming features of the software allow the user to design a circuit based on user-defined variables, such as a branch angle, and then modify the entire circuit by simply changing the value of the variable. This allows parametric design studies to be made conveniently and efficiently.

The above newly-developed CAD software was then seamlessly linked with the translated simulation software to produce the total package. After laying out a circuit using the CAD tools of the main program, a simulation is initiated by simply clicking on a button. A dialog presents the user with a choice of numerical parameters to be used in the simulation, and the program provides intelligently-chosen default parameters based on the characteristics of the circuit being simulated. The actual simulation incorporates real-time display and analysis of results.

The third major area of development consisted of incorporating algorithms to address all key physical phenomena of interest. The first was the inclusion of techniques to address propagation in circuits with large angles or refractive index differences. The software implements a multi-step Padé based algorithm as described by Hadley.²

In addition, we have complete a large body of original work on analysis and application of wide-angle beam propagation techniques to large-area PICs. This has been published in the *Journal of Lightwave Technology*.³ This work has determined the key issues in being able to model large-area PICs, and demonstrates that accurate simulation can be performed on such devices. Design rules are provided to guide the modeler as to the relative merits of different algorithms and techniques.

Next, the simulation software was expanded to incorporate polarization by developing and implementing a new full-vector beam propagation method. This method follows work done by W.P. Huang,⁴ but provides a faster and more robust algorithm.

In addition, the ability to handle anisotropic media has been included. Recently, the program has been expanded to incorporate nonlinear optical effects in the simulation, and developments on bi-directional simulation are underway.

In summary, we have developed a complete CAD system for designing arbitrarily complex photonic integrated circuits which employs all state-of-the-art beam propagation techniques for simulation. As an example, Fig. 1 shows the design of an arrayed-waveguide grating router, which has become the component of choice for large WDM systems. As noted above, this software has been licensed and is available as a commercial product called *BeamPROP*, through RSoft, Inc., Montrose, NY.

References:

1. R. Scarmozzino and R.M. Osgood, Jr., J. Opt. Soc. Amer. A, 8, 724 (1991).
2. G.R. Hadley, Opt. Lett., 17, 1743 (1992).
3. I. Ilic, R. Scarmozzino and R. M. Osgood Jr., IEEE J. Lightwave Tech. 14, 2813 (1996).
4. W.P. Huang and C.L. Xu, J. Quantum Electron., 29, 2639 (1993).




Figure 1. Computer-Aided Design of Arrayed-Waveguide Grating Router for WDM

3. PUBLICATIONS

1. L. Eldada, M. N. Ruberto, R. Scarmozzino, M. Levy and R. M. Osgood Jr., "Laser-Fabricated Low-Loss Single-Mode Waveguiding Devices in GaAs," J. Lightwave Tech. 10, 1610 (1993).
2. I. Ilic, R. Scarmozzino and R.M. Osgood, Jr., "Modelling Multimode-Input Star Couplers in Polymers," J. Lightwave Tech. 12, 996 (1994).
3. L. Eldada, N. Zhu, M. Ruberto, M. Levy, R. Scarmozzino and R. M. Osgood, Jr. "Rapid Direct Fabrication of Active Electro-Optic Modulators in GaAs," J. Lightwave Technology 12, 1588 (1994).
4. L. Eldada, M. Levy, R. Scarmozzino and R. M. Osgood Jr., "Laser Rapid Prototyping of Photonic Integrated Circuits," in the Proceedings of International Symposium on Integrated Optics, Lindau, Germany, v. 2213, April 11-15, 1994.
5. L. Eldada, R. Scarmozzino, R. M. Osgood, Jr., D. C. Scott, Y. Chang and H. R. Fetterman, "Laser-Fabricated Delay Lines in GaAs for Optically-Steered Phased-Array Radar," J. Lightwave Tech. 13, 2034 (1995). /
6. I. Ilic, R. Scarmozzino, R. M. Osgood Jr., J. T. Yardley, K. W. Beeson and M. J. McFarland, "Photopatterned Polymer Multimode 8x8 Star Couplers: Comparative Design Methodologies and Device Measurements," IEICE Trans. Commun. E80-B, (1997).
7. I. Ilic, R. Scarmozzino and R. M. Osgood Jr., "Investigation of the Padé Approximant-Based Wide-Angle Beam Propagation Method for Accurate Modeling of Waveguiding Circuits," IEEE J. Lightwave Tech. 14, 2813 (1996).
8. R. Scarmozzino, R. M. Osgood Jr., L. Eldada, M. Hu, Z. Huang, D. Levy, P. Marbach, and M. Levy, "Rapid Design and Fabrication of New Photonic Integrated Circuits for Lightwave Systems," Proceedings of SPIE Photonics East Conference, 2613, (1995).pp. 60
9. M. H. Hu, J. Z. Huang, R. Scarmozzino, M. Levy and R. M. Osgood Jr., "A Low-Loss and Compact Waveguide Y-branch Using Refractive-Index Tapering," IEEE Photon. Tech. Lett. 9, 203 (1997).
10. M. H. Hu, J. Z. Huang, R. Scarmozzino, M. Levy and R. M. Osgood, Jr., "Tunable Mach-Zehnder Polarization Splitter Using Height-Tapered Y-branches," IEEE Photon. Technol. Lett. 9, 773 (1997).

11. D. S. Levy, Y. M. Li, R. Scarmozzino and R. M. Osgood, Jr., "A Multi-Mode Interference-Based Variable Power Splitter in GaAs/AlGaAs," submitted to IEEE Photonics Technology Letters (April 10, 1997).
12. T. A. Ramadan, R. Scarmozzino and R. M. Osgood, Jr., "Adiabatic Couplers: Design Rules and Optimization," submitted to J. Lightwave Tech. (April 16, 1997).
13. D.S. Levy, R. S. Scarmozzino, Y.M. Li, and R.M. Osgood, Jr., "A New Design for Ultracompact Multimode Interference-Based 2x2 Couplers," submitted to IEEE Photonics Technol. Lett. (July 14, 1997).

4. TECHNICAL REPORTS PUBLISHED

None

5. INVENTIONS

None

6. PERSONNEL SUPPORTED AND DEGREES EARNED

Dave Levy, graduate research assistant

Jason Sayres, graduate research assistant

Jae Choe, graduate research assistant

AIR FORCE OF SOUTH AFRICA
NOTICE OF 1
THIS 1990
APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED
DISTRIBUTION UNLIMITED
JOAN BOYGS
STINFO Program Manager

(AFSC)
Reviewed and is
AFR 190-12