

National Defence Research and Development Branch Défense nationale Bureau de recherche et développement

> TECHNICAL MEMORANDUM 97/216 August 1997

VALIDATION OF SHIPMO7 AND PRECAL WITH THE CPF HYDROELASTIC MODEL

Kevin A. McTaggart — Dann L. Chow



19980417 004

Defence Research Establishment Atlantic

Canad^a

А



Centre de Recherches pour la Défense Atlantique

DTIC QUALITY INSPECTED 3

DEFENCE RESEARCH ESTABLISHMENT ATLANTIC

9 GROVE STREET

P.O. BOX 1012 DARTMOUTH, N.S. B2Y 3Z7

TELEPHONE (902) 426-3100

CENTRE DE RECHERCHES POUR LA DÉFENSE ATLANTIQUE

9 GROVE STREET

C.P. BOX 1012 DARTMOUTH, N.É. B2Y 3Z7



National Defence Research and Development Branch Défense nationale Bureau de recherche et développement

VALIDATION OF SHIPMO7 AND PRECAL WITH THE CPF HYDROELASTIC MODEL

Kevin A. McTaggart — Dann L. Chow

August 1997

Approved by: R.W. Graham Head / Hydronautics Section

TECHNICAL MEMORANDUM 97/216

Defence Research Establishment Atlantic



i

Centre de Recherches pour la Défense Atlantique

Canada

DTIC QUALITY INCRECIED 3

Abstract

This report gives results of an extensive validation of DND's strip theory program SHIPMO7 and the three-dimensional ship motion code PRECAL developed by Cooperative Research Ships. Ship motion and sea load predictions are compared with results for the CPF hydroelastic model, which was tested in regular and irregular waves in both head and oblique seas. In general, both codes give excellent agreement for ship motions and reasonable agreement for sea loads. In irregular head seas, PRECAL overpredicts vertical bending moment at midships by an average of 9 percent, which is superior to the average overprediction by SHIPMO7 of 25 percent.

Résumé

Le présent rapport présent une validation complète du programme de théorie des bandes SHIPMO7 et du code PRECAL des mouvements de navires en trois dimensions du MDN, développés par les navires de recherche coopérative. Les prédictions des mouvements des navires et des charges de mer sont comparées aux résultats du modèle hydroélastique FCP qui a été mis à l'essai dans des vagues régulières et irrégulières venant de l'avant et en oblique. En général, les deux codes ont un rapport de concordance excellent avec les mouvements des navires et un rapport de concordance raisonnable avec les charges de mer. Pour la houle avant irrégulière, PRECAL surestime le moment de flexion verticale au milieu du navire de 9 p. 100 en moyenne, ce qui est supérieur à la surestimation moyenne de 25 p. 100 par SHIPMO7.

DREA TM/97/216

VALIDATION OF SHIPMO7 AND PRECAL WITH THE CPF HYDROELASTIC MODEL

by

Kevin A. McTaggart and Dann L. Chow

EXECUTIVE SUMMARY

Introduction

Predictions of ship motions and sea loads in waves are required for rational ship design and maintenance. This study compares results from two seakeeping codes with model test data for the Canadian Patrol Frigate (CPF). The first code is DND's strip theory program SHIPMO7, and the second code is PRECAL, a three-dimensional program developed by the Cooperative Research Ships organization. Both codes are being considered for ongoing support of ship maintenance for the CPF. The model tests were carried out at the Institute for Marine Dynamics, and consist of ship motions and sea loads experiments in regular and oblique seas for both head and oblique sea directions. While the majority of experimental results for the CPF hydroelastic model are proprietary to DND, this report includes a selection of plots used in the validation study.

Principal Results

In general, SHIPMO7 and PRECAL give excellent agreement with experimental results for ship motions and reasonable agreement for sea loads, with PRECAL giving the better results. For vertical bending moment at midships in irregular head seas, PRECAL overpredicts experimental values by 3 percent at low speed, increasing to 15 percent at high speed. SHIPMO7 consistently overpredicts vertical bending moment at midships by approximately 25 percent, with little dependence on speed.

Both SHIPMO7 and PRECAL give relatively poor torsion predictions. PRECAL incorrectly assumes constant metacentric height along the length of the ship. Although SHIPMO7 correctly considers the longitudinal variation of sectional metacentric height, the geometry of the CPF combined with the limitations of strip theory likely cause poor torsion predictions. Another source of errors for torsion predictions is that the roll gyradii of the model segments are unknown.

Experimental measurements of vertical bending moments and shear forces in irregular head seas show that vertical loads are almost identical for the operational light and deep departure loading conditions.

Significance of Results

The superior load predictions of PRECAL over SHIPMO7 indicate that the transom stern of the CPF causes three-dimensional effects to be significant. At high forward speed, the accuracy of PRECAL deteriorates, likely due to assumptions related to the zero speed Green function and to neglect of the steady speed diffraction potential. The consistency of the experimental results suggests that the model test data are generally reliable. Uncertainty remains regarding roll inertia properties of the CPF hydroelastic model during the IMD tests; thus, the present torsion experimental data must be used with caution. Given that lateral plane loads are small relative to vertical plane loads for the CPF, the uncertainty of the segment roll inertia properties does not significantly affect the overall usefulness of the IMD data.

The very close agreement of vertical plane sea loads for the deep departure and operational light loading conditions indicates that sea loads for a representative loading condition can be applied to a range of loading conditions. This result could significantly reduce the amount of computational work required for future analysis in support of CPF maintenance.

When selecting a code for motion and sea load analysis, the relative merits of both codes must be considered. PRECAL's three-dimensional theory gives better vertical plane load predictions. For lateral plane motions and sea loads, SHIPMO7 has the advantages of good roll damping predictions and correct treatment of the longitudinal variation of sectional metacentric height for torsion computations. For general predictions of ship motions and sea loads, SHIPMO7 can provide comprehensive results for both vertical and lateral modes. PRECAL is recommended for cases requiring hydrodynamic pressures on the hull or more accurate vertical plane loads.

Future Plans

Because of the importance of three-dimensional effects for the CPF, DREA will continue to monitor new developments with PRECAL. PRECAL has good potential for better predictions through improvements in the areas of roll damping, forward speed Green function, and sectional roll restoring forces.

In support of future maintenance, a database of CPF motions and sea loads in waves will be developed. The present results suggest that the database will only require a single operational load condition. An important initial task will be evaluation of the actual mass distribution for the CPF. The database will then be generated using the most suitable code for predicting ship motions and sea loads. Updates to the database will be made as more accurate prediction tools become available.

Contents

Α	bstract	ii					
E	Executive Summary iii						
Ta	able of Contents	v					
N	otation	vii					
1	Introduction	1					
2	SHIPMO7 Strip Theory Program	1					
3	PRECAL Program Suite	2					
4	MOSOLV Time Domain Suite	2					
5	Prediction Code Input Parameters	3					
6	Description of IMD Experiments	9					
8	Presentation of Experimental and Numerical Results 7.1 Regular Waves 7.2 Irregular Waves 7.2 Irregular Waves 8.1 Heave 8.2 Roll 8.3 Pitch 8.4 Yaw 8.5 Vertical Bending Moment 8.6 Horizontal Bending Moment 8.7 Torsion 8.8 Vertical Shear 8.9 Horizontal Shear	 11 11 17 22 22 22 22 23 23 23 23 23 23 24 					
9	Sources of Discrepancies between Predictions and Experiments	2 4					
10	Further Examination of SHIPMO7 Torsion Predictions	27					
11 Analysis of Errors for Predicted Motions and Sea Loads in Irregular Head Seas 33							
12	2 Sensitivity of Sea Loads in Head Seas to Loading Condition 30						
13	Conclusions	40					

Appendices

A	SHIPMO7 Sample Input File	41
B	PRECAL Sample Input Files	45
	B.1 HYDMES Pre-processor Input File 1 - cpfmodel.hin	45
	B.2 HYDMES Pre-processor Input File 2 - cpfmodel.hul	46
	B.3 HYDCAL Input File - cpfmodel.cnd	49
	B.4 RESCAL Input File - cpfmodel.inp	50
Re	leferences	51

41

Notation

a	wave amplitude
AP	aft perpendicular
В	beam
C_B	block coefficient
FP	forward perpendicular
Fn	Froude number
\overline{GM}	metacentric height
g	gravitational acceleration
Η	wave height
H_s	significant wave height
k	wavenumber
\overline{KG}	vertical height of centre of gravity above baseline
L	ship length between forward and aft perpendiculars
LCG	longitudinal location of centre of gravity (aft of midships)
LCGFP	longitudinal location of centre of gravity (aft of FP)
m	mean
n_4	number of roll cycles
T	period of oscillation or draft
T_p	peak wave period
T_z	zero-crossing period
T_0	modal wave period
T_4	natural roll period
U	mean forward ship speed
V_i	amplitude of load component i
β_s	incident sea direction (relative to ship speed)
ζ_i	motion amplitude for mode i
λ	wavelength or linear model scaling factor
ξ_4	roll damping coefficient
ρ	water density
σ	standard deviation
σ_{ϕ}	RMS roll displacement
$\hat{oldsymbol{\phi}}$	initial roll displacement
ω	wave frequency
ω_e	encounter frequency
\bigtriangleup	ship mass displacement

vii



viii

1 Introduction

Predictions of ship motions and sea loads are essential elements of ship design and maintenance. This report describes a validation study of the ship motions and sea loads of the Canadian Patrol Frigate (CPF) hydroelastic model predicted by two codes, SHIPMO7 and PRECAL. Another validation study [1] compares SHIPMO7 and PRECAL predictions with data for the warship model of Lloyd et al. [2, 3].

SHIPMO7 is an updated version of DREA's ship motion code SHIPMO [4], a strip theory program for evaluating seakeeping of slender ships in moderate seas. PRECAL is a suite of programs developed by the Cooperative Research Ships (CRS) PRECAL Working Group and is based on three-dimensional panel theory. Both programs are designed to predict ship motions in regular waves, and in uni-directional and multi-directional irregular seas.

Reference 5 gives an overview of the CPF hydroelastic model experiments and some comparisons with SHIPMO7 and PRECAL. The 1:20 scale model of the CPF was built by Fleet Technology Limited and was tested by the Institute for Marine Dynamics (IMD) in St. John's, Newfoundland. Reference 6 describes construction of the model and gives a detailed description of the model properties. The models tests were conducted in both regular and irregular waves with head and bow seas.

Previous SHIPMO versions have shown good agreement with experimental data for ship motions, but have not been as accurate in predicting sea loads [7, 8]. Validations of previous versions of PRECAL demonstrate a similar trend [9, 10]. PRECAL ship motion predictions demonstrated good agreement with experimental results, yet its sea load predictions were not significantly better than those from two-dimensional codes. Serious problems were also discovered with the roll motion prediction capabilities of PRECAL.

This study also includes some predictions from the time domain code MOSOLV [11, 12], which was developed for DREA by Aerospace Engineering and Research Consultants Limited (AERCOL). MOSOLV results are presented for only a small number of test cases because of generally poor agreement with experimental results and with the two frequency domain codes.

This report begins with descriptions of SHIPMO7 and PRECAL and their capabilities. MOSOLV is also briefly described. Section 5 discusses preparation of input files for the CPF. The hydroelastic model of the CPF and the tests conducted by IMD are subsequently described in Section 6. The report then presents comparisons of the model tests with numerical predictions in Section 7. A subsequent discussion in Section 8 highlights areas of good agreement and areas of deficiencies for the numerical predictions. Section 9 considers possible sources of discrepancies between predictions and experiments, and initiates further examination of numerical torsion predictions in Section 10. In Section 11, an error analysis of predicted motions and sea loads in irregular head seas gives practical insight for application of numerical predictions to design cases for the CPF. Section 12 examines sea loads in head seas for the operational light and deep departure loading conditions. The report finishes with general conclusions.

2 SHIPMO7 Strip Theory Program

SHIPMO7 [4] is the newest version of DREA's ship motion program SHIPMO, a strip theory program that is suitable for evaluating seakeeping of slender ships in moderate seas. Because of

its simple user input requirements and relatively fast computational time, SHIPMO7 is widely used for seakeeping analysis.

SHIPMO7 is a frequency domain code, based on the strip theory of Salvesen, Tuck and Faltinsen [13]. SHIPMO includes extensions first proposed by Schmitke [14] to include appendage forces and viscous roll damping forces. Graham [15] introduced further improvements to roll damping predictions. The most important update for SHIPMO7 is computation of sea loads including appendage and viscous forces. Other enhancements include elimination of irregular frequencies and prediction of added resistance in waves.

3 PRECAL Program Suite

PRECAL is a set of codes for predicting ship motions and sea loads of displacement hull vessels. The programs were developed through three Cooperative Research Ships (CRS) Working Groups. PRECAL is based on three-dimensional panel theory rather than the two-dimensional strip theory of SHIPMO7. It was expected that PRECAL predictions for sea loads would demonstrate better agreement with experimental results than SHIPMO7. Further discussion of PRECAL's theoretical basis and code design can be found in References 16 and 17.

The version of PRECAL used in this study (Version 1.0) has problems with predicting roll damping correctly. In this study, roll damping coefficients obtained from SHIPMO7 are input to PRECAL.

For irregular waves, PRECAL requires each ship speed to be run separately to obtain consistent results. This limitation is not noted in the PRECAL user's manual [16]. Initial load predictions in irregular waves were incorrect due to a bug in subroutine RDRAO of the program RESCAL. This bug was corrected and the resulting sea load predictions in irregular waves are included in this report.

In order to make comparisons with the experimental data, all SHIPMO7 and PRECAL RAO values were non-dimensionalized to a common format. For irregular waves, results from the prediction codes were converted to full-scale dimensional values.

4 MOSOLV Time Domain Suite

The time domain suite MOSOLV was developed by AERCOL under contract to DREA [11, 12, 18, 19]. The programs, which are based largely on the theory of Reference 20, use a time domain Green function and impulse response method to predict hydrodynamic forces. This approach was developed because of its potential for modelling forward speed effects, three-dimensional effects, and nonlinearities.

The MOSOLV program suite consists of the following three modules:

- STATEQ: calculates equilibrium hydrostatic conditions,
- IMPRSP: determines the radiation and diffraction hydrodynamic impulse response functions,
- MOSOLV: solves the hydrodynamic response equations for ship motions and resulting sea loads in the time domain.

The MOSOLV suite is limited to solving vertical plane motions and sea loads in head and following seas only. The code IMPRSP requires very large amounts of CPU time and memory for computing the hydrodynamic impulse response functions, and its computed impulse response functions are very prone to numerical instabilities. Given the problems with the MOSOLV suite and that AERCOL has not maintained expertise in this area, DREA plans no further development of the suite.

5 Prediction Code Input Parameters

Sample input files are given in Appendix A for SHIPMO7 and in Appendix B for PRECAL. It is essential that the input parameters describing the CPF hydroelastic model be correct. For sea load predictions, particular attention must be given to the ship mass distribution. For input into the prediction codes, sectional masses supplied by IMD were combined such that masses are assumed to be uniformly distributed between mid-stations (e.g. between stations 0.5 and 1.5). Provisions for bow and stern overhang masses are also available in the codes. The resulting sectional mass distributions for the CPF hydroelastic model are shown in Figures 1 and 2.



Figure 1: Input Sectional Mass Distribution for Deep Departure Condition

For the operational light condition, the longitudinal center of gravity location for segment 1 (nearest the bow) based on the estimated mass distribution was found to be significantly different from the value reported by IMD. In order to alleviate this problem, the sectional masses near the bow were redistributed so that the total segment mass and the longitudinal center of gravity of the segment approach the reported values. The results of the redistribution are shown in Table 1. Figure 2 shows the redistributed sectional mass distribution at the bow for the operational light condition.



Figure 2: Input Sectional Mass Distribution for Operational Light Condition

	IMD Segment Values	IMD Sectional Values	SHIPMO7 Input
Bow overhang mass (kg)		3.402	0
Station 0 mass (kg)		3.853	6.635
Station 1 mass (kg)		8.231	7.500
Station 2 mass (kg)		10.155	10.715
Total Segment Mass (kg)	24.85	25.64	24.85
Segment LCGFP (mm)	362.4	326.0	383.4

Table 1: Mass Distributions for Model Segment 1, Operational Light Condition

Figures 3 and 4 show the segment mass distributions for the deep departure and operational light conditions, respectively. For both loading conditions, good agreement exists between segment properties reported by IMD and those based on the sectional mass distributions.



Figure 3: Model Segment Mass Distribution for Deep Departure Condition

For consistent load computations, the mass and longitudinal center of gravity location calculated from hydrostatics must match those of the mass distribution. Although the trim conditions calculated by SHIPMO7 and PRECAL did not match those of the experiments, correct modelling is more important for the mass distribution than for the trim condition, which can vary slightly without significantly affecting results. Thus the midships draft and trim by stern are adjusted such that the displacement and longitudinal center of gravity location from the ship hydrostatics match the values from the mass distribution.

To represent the roll properties of the hydroelastic model accurately, sectional roll inertia terms are required. Because oblique seas tests were conducted only for the deep departure condition, roll properties given here are only for that condition. SHIPMO7 requires roll gyradii to be input and PRECAL requires roll inertia. These input parameters were estimated using the roll gyradius given by IMD for the entire model. The resulting dry roll gyradius combined with an input roll metacentric height of 1.08 m allows SHIPMO7 to match the natural roll period of 12.3 s full-scale given by IMD; however, this dry roll gyradius gives a slightly lower roll period of 11.8 s from PRECAL due to differences between SHIPMO7 and PRECAL roll added masses. The procedure described in Reference 1 was used to determine the sectional roll inertia properties. This method provides reasonable estimates of the sectional properties which are consistent with the inertia properties of the entire model. These calculations were performed for each of the two weight conditions.

Initial SHIPMO7 roll predictions in oblique seas were significantly higher than experimental values at wave encounter frequencies near the ship roll natural frequency. This discrepancy was



Figure 4: Model Segment Mass Distribution for Operational Light Condition

alleviated by increasing the SHIPMO7 input \overline{KG} value for the deep departure condition from the reported value of 6.26 m to 6.50 m full scale, which allowed the metacentric height computed by SHIPMO7 to agree with the value of 1.08 m reported by IMD. Although the reported \overline{GM} value of 1.08 m had initially been used as input to SHIPMO7, the revised \overline{KG} value leads to improved roll predictions because of the sensitivity of roll excitation forces to vertical centre of gravity location. To maintain consistency with the revised \overline{KG} value, all sectional \overline{KG} values were increased by 0.24 m full scale. Unlike SHIPMO7, PRECAL appears to include the influence of a user input metacentric height on roll excitation forces; thus, \overline{KG} values input to PRECAL were not modified.

When running PRECAL, the number of facets for computations must be selected carefully, with consideration for computational requirements and accuracy. The present study uses 160 facets on one side of the hull.

As mentioned earlier, the version of PRECAL used in this study has deficiencies with roll damping calculations. For each ship speed and heading, the SHIPMO7 roll damping at a wave encounter frequency near the ship roll natural frequency was used as input to PRECAL. The selection of a single damping coefficient for all wave frequencies was considered acceptable because roll damping is most important near resonance and because roll damping exhibits relatively little variation with wave frequency. For regular seas, SHIPMO7 roll damping coefficients for a wave steepness of 1/30 were used. For irregular seas, roll damping coefficients were taken for a Bretschneider spectrum with significant wave height of 5 m and peak wave period of 11 s. Tables 2 and 3 show damping coefficient values from SHIPMO7 used as input to PRECAL.

Unpublished results of roll decay tests obtained from IMD were used to estimate roll damping coefficients at zero speed. For a time series of lightly damped roll motions, the following equation

Froude number	Sea direction β_s (degrees)		
Fn	135	165	180
0.06	0.135	0.108	0.050
0.12	0.147	0.119	0.050
0.20	0.162	0.132	0.050
0.25	0.171	0.141	0.050

 Table 2: Regular Wave Roll Damping Coefficients

 Table 3: Irregular Wave Roll Damping Coefficients

Froude number	Sea direction β_s (degrees)			
Fn	135	150	165	180
0.06	0.087	0.074	0.063	0.050
0.12	0.093	0.086	0.076	0.050
0.20	0.106	0.100	0.097	0.050
0.25	0.117	0.112	0.111	0.050

gives the ratio of initial absolute roll displacement $\hat{\phi}$ to RMS roll σ_{ϕ} :

$$\frac{\hat{\phi}}{\sigma_{\phi}} = \sqrt{\frac{8\pi\xi_4 n_4}{1 - \exp\left(-4\pi\xi_4 n_4\right)}}$$
(5.1)

where ξ_4 is the roll damping coefficient as a fraction of critical damping and n_4 is the number of roll cycles in the time series. For each time series provided by IMD with an initial roll displacement of at least 2 degrees and at least 2 roll cycles, the damping coefficient ξ_4 has been estimated by satisfying the above equation. Figure 5 shows the estimated roll damping coefficients as a function of roll amplitude. For the roll decay tests, the effective roll amplitude in Figure 5 is taken as $\sqrt{2}\sigma_{\phi}$. The estimated experimental damping values show a moderate amount of scatter, and tend to increase with roll amplitude due to increased viscous roll damping. Predicted roll damping values from SHIPMO7 are somewhat higher than the experimental results.

In the SHIPMO7 and PRECAL analyses for regular waves, the range of wave frequencies was 2 rad/s to 5 rad/s (model scale), similar to the range used for the hydroelastic model tests. However, for irregular wave computations, a wave frequency range of 1 rad/s to 9 rad/s was used to encompass the wave spectral energies.

For computations in irregular seas, attention must be given to the definition of the characteristic wave period. The IMD reports incorrectly use the term modal wave period T_0 (wave spectral energy density S(T) is a maximum at period T_0) for what is actually the peak wave period T_p (wave spectral energy density $S(\omega)$ is a maximum at frequency $2\pi/T_p$). This report uses the correct term T_p instead of T_0 . For the Bretschneider and JONSWAP spectra in SHIPMO7,



Figure 5: Roll Damping at Zero Ship Speed for Deep Departure Condition

the peak wave period is the characteristic period used as input. However, PRECAL requires the input wave period to be either an average period or a zero-crossing period T_z . The latter is chosen, and the conversion factor from T_p to T_z is 0.710 [21].

6 Description of IMD Experiments

The 1:20 scale hydroelastic model of the Canadian Patrol Frigate was designed and built by Fleet Technology Limited [6]. The final design was a six segment model with a continuous elastic backbone serving as the sole longitudinal support. Froude scaling was used, where lengths scale linearly and masses and forces are scaled by the cubic power of the linear scaling factor λ .

The model was built from fiberglass, with a backbone of carbon/epoxy composite. Selfpropulsion was achieved by two small motors each powering a propeller. Rudder control was provided by a third motor, which was controlled by a human operator via telemetry. Safety restraint wires at the bow and stern were present in case control of the model was lost.

The model was segmented at stations 2.5, 5 (forward quarter point), 7.5, 10 (midships), and 13.7 (by SHIPMO7 convention, station 0 is FP and 20 is AP). The last segment was significantly larger than the others to accommodate the propulsion equipment. Strain gauges were attached to the backbone at each of the segment joints to measure the loads acting on the ship. An inertial reference system was fitted at the model center of gravity to allow measurement of the global motions of the ship.

Head seas (180 degrees) trials were performed in the Clearwater Towing Tank and oblique seas (135, 150 and 165 degrees) cases were performed in the Offshore Engineering Basin. Regular wave test cases were conducted for both deep departure and operational light conditions, but only the deep departure condition was considered for irregular waves. Data were collected at four different ship speeds, ranging from 4.1 to 17.0 knots (full-scale values). A full summary of regular wave test cases is presented in Table 4 and irregular wave cases are shown in Table 5. All irregular wave cases in Table 5 were run using a Bretschneider spectrum. For a heading of 180 degrees and ship speed of 8.2 knots, the tests were repeated with a JONSWAP spectrum.

For regular waves, data from the IMD tests are reported as non-dimensionalized response amplitude operators (RAOs). Dimensional values for the full-scale CPF are used for irregular wave responses.

Weight Condition	Heading	Froude	U (knots)	Wave Steepnesses
	(degrees)	number	(full-scale)	
Deep Departure	180	0.06	4.1	1/30, 1/20, 1/15
		0.12	8.2	1/30, 1/20, 1/15
		0.20	13.6	1/30, 1/20
		0.25	17.0	1/30, 1/20
	165	0.06	4.1	1/30, 1/20
		0.12	8.2	1/30, 1/20
		0.20	13.6	1/30, 1/20
		0.25	17.0	1/30
	135	0.12	8.2	1/30, 1/20
		0.20	13.6	1/30, 1/20
		0.25	17.0	1/30
Operational Light	180	0.06	4.1	1/20
		0.12	8.2	1/30, 1/20, 1/15
		0.20	13.6	1/20

 Table 4: Regular Wave Test Cases

Table 5: Irregular Wave Test Cases

Heading	Froude	U (knots)	H _s /T _p Pairs
(degrees)	number	(full-scale)	
180	0.06	4.1	4 m/9 s, 5 m/11 s, 6 m/13 s
	0.12	8.2	4 m/9 s, 5 m/11 s, 6 m/13 s
	0.20	13.6	4 m/9 s, 5 m/11 s, 6 m/13 s
	0.25	17.0	4 m/9 s, 5 m/11 s, 6 m/13 s
165	0.06	4.1	5 m/11 s
	0.12	8.2	5 m/11 s
	0.20	13.6	5 m/11 s
150	0.06	4.1	5 m/11 s
	0.12	8.2	5 m/11 s
	0.20	13.6	5 m/11 s
135	0.06	4.1	5 m/11 s
	0.12	8.2	5 m/11 s
	0.20	13.6	5 m/11 s

7 Presentation of Experimental and Numerical Results

This section gives some representative plots of comparisons between experimental data and predictions from SHIPMO7, PRECAL, and MOSOLV.

7.1 Regular Waves

For regular waves, the numerical predictions are for a wave steepness H/λ of 1/30 for both the deep departure condition and the operational light condition, which was tested only in head seas. For SHIPMO7 and PRECAL, vertical plane predictions are strictly linear while lateral plane predictions include nonlinearities from roll damping. MOSOLV predictions are included for a limited number of cases to demonstrate the deficiencies of the code. Motion and load amplitudes are presented as non-dimensional values. Non-dimensional bending moments are multiplied by a factor of 1000 and shear forces by 100.

Although IMD performed some head seas verification trials in the Offshore Engineering Basin, experimental results for all head seas cases in this study were obtained from Towing Tank test data. Head seas comparisons were done for deep departure and operational light loading conditions. For head seas, only vertical plane motions and sea loads were considered. All sea loads (moments, shears, and torsions) were analyzed at five locations: stations 2.5, 5.0, 7.5, 10.0 and 13.7 (by SHIPMO7 convention). Figures 6 to 11 give representative regular head seas results for the deep departure condition. Figures 12 to 16 give representative regular oblique seas results for the deep departure condition with a heading of 135 degrees and a Froude number of 0.12.



Figure 6: Heave Motion, Heading = 180 degrees, Deep Departure, Fn = 0.12



Figure 7: Pitch Motion, Heading = 180 degrees, Deep Departure, Fn = 0.12



Figure 8: Vertical Bending Moment at Station 10.0, Heading = 180 degrees, Deep Departure, Fn = 0.12



Figure 9: Vertical Bending Moment at Station 10.0, Heading = 180 degrees, Deep Departure, Fn = 0.20



Figure 10: Vertical Bending Moment at Station 10.0, Heading = 180 degrees, Deep Departure, Fn = 0.25



Figure 11: Vertical Shear Force at Station 5.0, Heading = 180 degrees, Deep Departure, Fn = 0.12



Figure 12: Roll Motion, Heading = 135 degrees, Deep Departure, Fn = 0.12

14



Figure 13: Yaw Motion, Heading = 135 degrees, Deep Departure, Fn = 0.12



Figure 14: Horizontal Bending Moment at Station 10.0, Heading = 135 degrees, Deep Departure, Fn = 0.12







Figure 16: Horizontal Shear Force at Station 5.0, Heading = 135 degrees, Deep Departure, Fn = 0.12

7.2 Irregular Waves

Only the deep departure load condition was tested in irregular waves. Motions for head seas cases are presented as a function of significant wave height and as a function of ship speed for oblique cases. All sea loads are presented as a function of station number. Ship speeds and station locations used for irregular waves are identical to those used for regular waves. Bretschneider spectra were used for both head and oblique seas. Additional head seas tests were performed using JONSWAP spectra. Full-scale dimensional RMS values are used for all irregular wave cases. For sea loads, the PRECAL RMS values were obtained after correcting a bug in the code RESCAL. Figures 17 to 25 give selected irregular seas results for the deep departure condition with Bretschneider spectra.

Figure 17: Heave Motion, Heading = 180 degrees, $F_n = 0.12$, Bretschneider Spectrum

Figure 19: Vertical Bending Moment, Heading = 180 degrees, $F_n = 0.12$, $H_s = 5$ m, $T_p = 11$ s, Bretschneider Spectrum

Figure 21: Roll Motion, Heading = 135 degrees, $H_s = 5$ m, $T_p = 11$ s, Bretschneider Spectrum

Figure 24: Torsional Moment, Heading = 135 degrees, Fn = 0.12, $H_s = 5$ m, $T_p = 11$ s, Bretschneider Spectrum

Figure 25: Horizontal Shear Force, Heading = 135 degrees, Fn = 0.12, $H_s = 5$ m, $T_p = 11$ s, Bretschneider Spectrum

8 Discussion of Results

In general, SHIPMO7 and PRECAL consistently demonstrate good agreement with each other and with the experimental data. In particular, comparisons for ship motions are good for most test conditions. For sea load predictions, both codes typically overpredict the vertical bending moments and shear forces. PRECAL demonstrates somewhat better accuracy in predicting sea loads than SHIPMO7.

MOSOLV predictions are generally poor, particularly for sea loads (e.g. Figures 9 and 10). Due to the poor quality of MOSOLV predictions, further discussion will be limited to SHIPMO7 and PRECAL.

8.1 Heave

As expected, both SHIPMO7 and PRECAL give excellent predictions of heave motions. In regular head seas, the experimental results appear to be consistent and show limited variation with wave steepness. There is a surprising amount of scatter for the regular seas experimental data at a heading of 135 degrees, with SHIPMO7 and PRECAL following the experimental trends. At a heading of 165 degrees in regular seas, there is less experimental scatter than at 135 degrees and the numerical predictions are very good. There is a general trend of less experimental scatter and improved predictions at higher wave frequencies.

In irregular seas, SHIPMO7 and PRECAL give excellent agreement with the experimental data for all cases except a heading of 135 degrees at a Froude number of 0.12. The discrepancy at this heading is consistent with the regular seas results.

8.2 Roll

In regular seas, the experimental roll data are very consistent and show little variation with wave steepness for both headings (135 and 165 degrees). SHIPMO7 shows overprediction at 135 degrees while PRECAL gives better agreement. As mentioned previously, the SHIPMO7 input \overline{KG} values for the ship and all sections were increased by 0.24 m full scale so that the computed metacentric height would coincide with the measured metacentric height. When the original \overline{KG} value of 6.26 m full scale was used, the SHIPMO7 roll excitation forces were significantly larger, causing greater overprediction of roll motions. At a heading of 165 degrees in regular seas, SHIPMO7 gives very good agreement with the experimental values while PRECAL tends to underpredict.

In irregular seas, SHIPMO7 and PRECAL give similar results, with some overprediction at a heading of 135 degrees but better agreement with experiments at headings of 150 and 165 degrees.

8.3 Pitch

In regular seas, the experimental pitch motions are very consistent and show little variation with wave steepness for all headings. Both SHIPMO7 and PRECAL give excellent agreement with experimental data for both regular and irregular seas.

8.4 Yaw

In regular seas, the experimental yaw data are consistent and exhibit little variation with wave steepness. SHIPMO7 and PRECAL predictions are very good, with the exception of underprediction at lower frequencies at a heading of 165 degrees for Froude numbers of 0.06 and 0.25.

In irregular seas, the agreement between experimental data and numerical predictions is much worse than for regular seas. The very high experimental value at a heading of 135 degrees and Froude number of 0.12 is likely incorrect. The numerical codes also significantly underpredict the experimental results at headings of 150 and 165 degrees.

8.5 Vertical Bending Moment

In regular waves, the experimental vertical bending moment data appear to be consistent. Vertical bending moments exhibit significant dependence on wave steepness, with nondimensional bending moment usually decreasing with increasing wave steepness. Both SHIPMO7 and PRECAL overpredict vertical bending moment at midships, with PRECAL giving better results than SHIPMO7. The degree of overprediction for both codes increases as Froude number increases. The poorest agreement between experiments and predictions occurs for the operational light condition at station 2.5. This poor agreement is likely due to an incorrect weight distribution for the foremost model segment, as discussed in Section 5.

In irregular seas, SHIPMO7 and PRECAL give good predictions of bending moment at all stations. At low Froude numbers, PRECAL is very accurate while SHIPMO7 is somewhat less accurate. At high Froude numbers, PRECAL predictions deteriorate somewhat but are still more accurate than SHIPMO7.

8.6 Horizontal Bending Moment

In regular waves, the horizontal bending moment experimental data show quite good consistency, with moderate dependence on wave steepness. SHIPMO7 and PRECAL give good agreement with experiments. As expected, this agreement tends to deteriorate as Froude number increases.

In irregular seas, both SHIPMO7 and PRECAL give very good agreement for the horizontal bending moment distribution.

8.7 Torsion

The torsion data indicate that the measurements were not working at station 13.7 for some of the tests. In regular waves, SHIPMO7 torsion predictions are typically much greater than experimental results, while PRECAL predictions appear to be better.

In irregular seas, PRECAL gives reasonable agreement while SHIPMO7 predictions are approximately twice as large as experimental values.

8.8 Vertical Shear

In regular waves, the vertical shear predictions appear to be consistent, with a moderate dependence on wave steepness. Agreement between predictions and experiments exhibits trends

similar to those for vertical bending moment. Both SHIPMO7 and PRECAL tend to overpredict vertical shear, with PRECAL giving better results than SHIPMO7. Results are somewhat better at lower Froude numbers.

In irregular waves, SHIPMO7 and PRECAL give good agreement with the experimental vertical shear distribution, with SHIPMO7 consistently overpredicting shear force.

8.9 Horizontal Shear

In regular waves, the horizontal shear predictions appear to be consistent, with moderate dependence on wave steepness. Both SHIPMO7 and PRECAL tend to overpredict horizontal shear.

In irregular waves, SHIPMO7 and PRECAL give good agreement with the experimental values at all stations except for Station 2.5, where there is significant overprediction.

9 Sources of Discrepancies between Predictions and Experiments

Discrepancies between the code predictions and experimental results could be due to general deficiencies of the codes or could be specific to the CPF experiments. Consideration of the current results and Reference 1 for a warship model can help to isolate possible sources of inaccuracy.

In general, comparison results for the CPF are inferior to those for the warship model. Possible sources of discrepancies for the CPF include the following:

- the hull geometry violates slenderness assumptions in numerical predictions,
- the experimental motions and loads have errors,
- the mass distribution for the CPF model is incorrect,
- PRECAL assumes that all sections have a transverse metacentric height equal to the ship metacentric height,
- SHIPMO7 roll damping predictions are incorrect,
- rudder motions, which are ignored by the numerical predictions, affect lateral plane motions and loads,
- nonlinear effects which are ignored by the numerical predictions.

Figure 26 shows the waterplanes for the CPF and warship models. The most important difference between the hull forms is that the CPF has a wide transom stern while the warship has a narrow stern. Considering the slenderness assumptions of strip theory, SHIPMO7 should be able to give very good results for the warship but less accurate results for the CPF. The three-dimensional code PRECAL should give better results than SHIPMO7 for a transom stern ship; however, PRECAL results will also deteriorate as transom width increases because of the assumption that the steady flow diffraction potential is negligible and because the PRECAL predictions use the zero-speed Green function. Figure 27 shows vertical bending moment at

CPF, Deep Departure

Figure 26: Waterplanes for CPF and Warship Model

midships in head seas for the warship at Fn = 0.21. PRECAL and SHIPMO7 give predictions that are close to the experimental results. In contrast, Figures 8 to 10 show SHIPMO7 consistently overpredicts vertical bending moment at midships in head seas for the CPF. For all four speeds considered in this study, PRECAL results are always better than SHIPMO, suggesting that three dimensional effects are important for the CPF. The accuracy of both SHIPMO7 and PRECAL predictions decrease as ship speed increases; thus, the dynamic waterline and steady diffraction potential, which are ignored by both codes, are likely significant for the CPF. In contrast, predictions of vertical bending moment at midships for the narrow stern warship model are excellent at Froude numbers of 0.21 and 0.29. In summary, the non-slender CPF stern likely causes significant prediction errors for both SHIPMO7 and PRECAL.

The accuracy of experimental motions and sea loads can be partially assessed by examining the consistency of the experimental data. With the exception of torsion at Station 13.7 for some tests, the experimental data given in the appendices have consistent trends, suggesting that they are correct.

Most aspects of the input mass properties for the CPF model are likely correct; however, some significant errors appear to exist. As discussed in Section 5, the sectional mass distribution for the operational light condition was inconsistent with the inertial properties of the foremost model segment. The sea loads comparisons for the operational light condition suggest that the total mass of the foremost segment was likely correct but an incorrect longitudinal centre of gravity likely introduced significant errors to predicted vertical bending moments.

As mentioned previously, there were no measurements of segment roll gyradii; thus, the sectional distribution of roll gyradii had to be estimated. Inaccuracies of estimated sectional roll gyradii likely introduced significant errors to predicted torsion values. Possible errors in sectional \overline{KG} values may have also introduced errors in torsion predictions. As discussed earlier, the measured \overline{GM} value for the ship suggested a possible error of 3 percent in the reported ship \overline{KG} value.

For torsion calculations, the assumption by PRECAL that all sections have the same metacentric height introduces major errors for the CPF model, which has a low metacentric height

Figure 27: Vertical Bending Moment at Midships in Regular Head Seas for Warship at Fn = 0.21

forward of midships and a high metacentric height aft of midships. In contrast, SHIPMO7 correctly considers the variation of sectional metacentric height. The better agreement with experiments by PRECAL is more likely due to chance than to superior prediction of relevant force components. The distribution of sectional metacentric height for the CPF model causes torsion at midships to be very sensitive to roll displacement. Consequently, differences between experimental and predicted roll motions can cause large differences for torsion.

For regular waves at a heading of 135 degrees, the numerical roll predictions are significantly greater than experimental results at low wave frequencies, at which the wave encounter frequency approaches the ship roll natural frequency. A possible explanation for the roll overprediction is that SHIPMO7 underestimates roll damping, which greatly influences roll amplitude in the vicinity of roll resonance; however, the roll decay test results of Figure 5 indicate that SHIPMO7 is more likely to overpredict rather than underpredict roll damping for the CPF model. The roll overpredictions at low wave frequencies for a heading of 135 degrees are more likely due to inaccuracies of other hydrodynamic force terms. Examination of hydrodynamic force components indicated that roll-sway and roll-yaw coupling terms are relatively large; thus, a number of hydrodynamic terms could cause the roll overprediction.

The neglect of rudder motions by the numerical codes can cause errors in predicted ship motions and loads in the lateral plane. For the regular wave experiments, the good agreement between measured and predicted yaw motions suggests that the rudder motions had a relatively small effect on ship motions in the lateral plane. Rudder motions were likely greater for the irregular wave tests, causing more erratic experimental results and poorer agreement by the numerical codes. Horizontal shear and bending moment predictions give good agreement with experiments, suggesting that these sea loads were not significantly affected by rudder motions. Regular wave tests conducted at various wave steepnesses provide insight regarding the importance of nonlinear effects. The experimental results suggest that nonlinear effects do not have a major influence on ship motions, with the possible exception of heave at a heading of 135 degrees. As expected, sea loads are more sensitive than ship motions to nonlinear effects. Nonlinear effects have the greatest influence on loads at Station 2.5, which is expected because the foremost portion of the ship has the greatest flare, thus violating the vertical wall assumption of linear theory.

10 Further Examination of SHIPMO7 Torsion Predictions

The relatively poor agreement between SHIPMO7 and experimental torsion values warrants further examination. Of major consideration is whether torsion predictions are correctly implemented in SHIPMO7.

The good agreement between SHIPMO7 torsion predictions and experimental data for the warship of Lloyd, Brown, and Anslow [2, 3] suggests that SHIPMO7 has a correct implementation of strip theory. The warship model has a narrow transom and nearly vertical sides in the vicinity of the waterline, making it well suited to strip theory modelling. Furthermore, the warship model tests were conducted in waves of low steepness, minimizing the influence of nonlinear effects. In contrast, the wide transom of the CPF violates slenderness assumptions of strip theory. The CPF transom also has a shallow draft, which will lead to significant nonlinearities. Based on the results for the warship and the CPF, it is suggested that the SHIPMO7 torsion predictions are correctly implemented and that poor results are due primarily to limitations of strip theory.

Given the good torsion results for the warship and the poor results for the CPF, it is worthwhile to examine SHIPMO7 torsion predictions for a third ship. Figures 28 to 36 show experimental data and SHIPMO7 predictions of torsion at midships for a Series 60 model with a block coefficient of 0.80 tested by Wahab [22]. A slight modification was made to program SHIPMO7 to compute the lateral responses for a constant wave height of 0.02L for all wave frequencies. Agreement between SHIPMO7 and experimental values is generally better than for the CPF but worse than for the warship. A possible source of error for the torsion predictions is that Wahab does not give the heights of the vertical centres of gravity for the two model segments; thus, it was assumed that the two segments have the same height for the centre of gravity, which is based on the reported metacentric height. Another likely cause of discrepancies between experimental and prediction values is that the hull form is quite full and violates slenderness assumptions of strip theory.

In general, it appears that the limitations of strip theory lead to marginal predictions of torsional loads. Another problem for torsion predictions is that roll inertial properties required for computations are often unavailable.

Figure 30: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 50 degrees

Figure 31: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 70 degrees

Figure 32: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 90 degrees

Figure 33: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 110 degrees

Figure 34: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 130 degrees

Figure 35: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 150 degrees

Figure 36: Torsion for Series 60, $C_B = 0.80$, Fn = 0.15, Heading = 170 degrees

11 Analysis of Errors for Predicted Motions and Sea Loads in Irregular Head Seas

The CPF hydroelastic model tests were conducted in response to a requirement for design sea load values. Numerical codes such as SHIPMO7 and PRECAL can also provide design sea load values, subject to the limitations of the codes. This section provides an analysis of the ratios of predicted to experimental values for ship motions and sea loads. The current analysis is limited to irregular head seas and Bretschneider spectra. The loads under consideration are vertical shear at Station 5 and vertical bending moment at midships, which is typically the most important design load.

Tables 6 to 9 give statistics for the ratios of predicted to experimental motions and loads. In the tables, m denotes the mean value while σ denotes the standard deviation. The standard deviations of the ratios are small, indicating that the ratio of predicted to experimental values exhibits relatively little scatter for each motion or load. The remaining discussion here will focus on general trends for the mean values.

Froude	H _s	$\zeta_3(SHIPMO)/\zeta_3(exp)$	$\zeta_3(PRECAL)/\zeta_3(exp)$
Number	(m)	m σ	m σ
0.06	4, 5, 6	0.90 0.04	0.93 0.02
0.12	4, 5, 6	0.92 0.01	0.97 0.03
0.20	4, 5, 6	0.94 0.02	1.01 0.03
0.25	4, 5, 6	0.96 0.02	1.04 0.01
0.06, 0.12, 0.20, 0.25	4	0.91 0.04	0.99 0.05
0.06, 0.12, 0.20, 0.25	5	0.93 0.03	0.99 0.05
0.06, 0.12, 0.20, 0.25	6	0.95 0.02	0.98 0.04
0.06, 0.12, 0.20, 0.25	4, 5, 6	0.93 0.03	0.99 0.05

Table 6: Statistics of Ratios of Predicted to Experimental Heave in Irregular Head Seas, Bretschneider Spectra

The heave ratios in Table 6 indicate SHIPMO7 slightly underpredicts heave motion while PRECAL predictions are almost identical to experimental results. For pitch, both SHIPMO7 and PRECAL predictions are virtually identical to the experiments.

As expected, discrepancies are greater for sea loads than for motions. Table 8 indicates that SHIPMO7 overpredicts midships bending moment by an average of 25 percent while PRECAL overpredicts by 9 percent on average. The SHIPMO7 overprediction shows little variation with speed. PRECAL is very accurate at low speed but deteriorates at high speed due to the zero speed Green function approximation and neglect of the steady speed diffraction potential. The degree of overprediction increases with wave height for both codes, suggesting that nonlinearities associated with wave height tend to reduce nondimensional midships bending moment.

Froude	Hs	$\zeta_5(SHIPMO)/\zeta_5(exp)$	$\zeta_5(PRECAL)/\zeta_5(exp)$
Number	(m)	m σ	$m \sigma$
0.06	4, 5, 6	1.00 0.04	0.97 0.04
0.12	4, 5, 6	1.01 0.03	1.01 0.03
0.20	4, 5, 6	0.96 0.04	1.00 0.04
0.25	4, 5, 6	0.93 0.04	0.99 0.04
0.06, 0.12, 0.20, 0.25	4	0.93 0.04	0.95 0.02
0.06, 0.12, 0.20, 0.25	5	0.98 0.03	0.99 0.02
0.06, 0.12, 0.20, 0.25	6	1.02 0.02	1.04 0.01
0.06, 0.12, 0.20, 0.25	4, 5, 6	0.98 0.05	0.99 0.04

Table 7: Statistics of Ratios of Predicted to Experimental Pitch in Irregular Head Seas, Bretschneider Spectra

Table 8: Statistics of Ratios of Predicted to Experimental Midships Vertical Bending Moment in Irregular Head Seas, Bretschneider Spectra

Froude	H _s	$V_5(SHIPMO)/V_5(exp)$	$V_5(PRECAL)/V_5(exp)$
Number	(m)	m σ	m σ
0.06	4, 5, 6	1.24 0.05	1.03 0.06
0.12	4, 5, 6	1.23 0.03	1.05 0.02
0.20	4, 5, 6	1.26 0.04	1.12 0.02
0.25	4, 5, 6	1.27 0.06	1.15 0.04
0.06, 0.12, 0.20, 0.25	4	1.19 0.01	1.04 0.05
0.06, 0.12, 0.20, 0.25	5	1.26 0.02	1.10 0.05
0.06, 0.12, 0.20, 0.25	6	1.30 0.03	1.13 0.04
0.06, 0.12, 0.20, 0.25	4, 5, 6	1.25 0.05	1.09 0.06

Froude	H _s	$V_3(SHIPMO)/V_3(exp)$	$V_3(PRECAL)/V_3(exp)$
Number	(m)	m σ	$m \sigma$
0.06	4, 5, 6	1.20 0.05	0.96 0.04
0.12	4, 5, 6	1.19 0.03	0.89 0.03
0.20	4, 5, 6	1.22 0.05	0.81 0.03
0.25	4, 5, 6	1.25 0.07	0.75 0.04
0.06, 0.12, 0.20, 0.25	4	1.15 0.01	0.81 0.08
0.06, 0.12, 0.20, 0.25	5	1.23 0.03	0.86 0.08
0.06, 0.12, 0.20, 0.25	6	1.27 0.03	0.89 0.08
0.06, 0.12, 0.20, 0.25	4, 5, 6	1.22 0.06	0.85 0.09

Table 9: Statistics of Ratios of Predicted to Experimental Vertical Shear at Station 5 in Irregular Head Seas, Bretschneider Spectra

Table 9 shows that SHIPMO7 overpredicts vertical shear at Station 5 by an average of 22 percent while PRECAL underpredicts vertical shear by an average of 15 percent. The SHIPMO7 overprediction shows little sensitivity to speed. PRECAL results deteriorate as speed increases, as occurs for bending moment. Variations with wave height suggest that nonlinear effects give reductions in nondimensional loads as wave height increases.

In summary, both SHIPMO7 and PRECAL give excellent predictions of heave and pitch in irregular head seas. SHIPMO7 consistently overpredicts vertical bending moment at midships and vertical shear at Station 5 by approximately 25 percent. PRECAL gives excellent predictions of vertical plane loads at low Froude numbers, but overpredicts bending moment at midships by 15 percent and underpredicts vertical shear at Station 5 by 25 percent as Froude number increases to 0.25.

12 Sensitivity of Sea Loads in Head Seas to Loading Condition

The sensitivity of sea loads to ship loading condition is of great practical concern. If sea loads were relatively insensitive to ship loading condition, then loads for a single loading condition could be considered representative of values for all loading conditions. Alternatively, high sensitivity of loads to loading condition would require separate evaluation of motions and loads for each loading condition.

Figures 37 to 42 compare measurements of vertical bending moment and vertical shear in irregular head seas for the deep departure condition with predictions based on measured regular seas RAOs for the deep departure and operational light conditions. In all cases, the plotted loads show a surprisingly degree of consistency. In the deep departure condition, RMS loads based on regular wave RAOs are essentially the same as loads from irregular wave tests. Furthermore, loads for the deep departure condition are approximately equal to those for the operational light condition, suggesting that a single operational condition can be used to generate representative sea loads for all loading conditions.

Figure 37: Vertical Bending Moment in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5 \text{ m}$, $T_p = 11 \text{ s}$, Fn = 0.06

Figure 38: Vertical Bending Moment in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5 \text{ m}, T_p = 11 \text{ s}, Fn = 0.12$

Figure 39: Vertical Bending Moment in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5$ m, $T_p = 11$ s, Fn = 0.20

Figure 40: Vertical Shear in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5$ m, $T_p = 11$ s, Fn = 0.06

Figure 41: Vertical Shear in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5$ m, $T_p = 11$ s, Fn = 0.12

Figure 42: Vertical Shear in Irregular Head Seas for Deep Departure and Operational Light Conditions, Bretschneider Spectrum, $H_s = 5$ m, $T_p = 11$ s, Fn = 0.20

13 Conclusions

Both SHIPMO7 and PRECAL give generally good agreement with motions and sea loads for the CPF hydroelastic model. In contrast, MOSOLV gives generally poor agreement with experimental results.

The three-dimensional capability of PRECAL leads to vertical plane load predictions which are better than the strip theory program SHIPMO7. At high speeds, PRECAL results deteriorate somewhat because the code neglects the steady speed diffraction potential and the current study uses the PRECAL zero speed Green function approximation.

The only major discrepancies between experiments and predictions occur for torsion. The PRECAL torsion predictions assume constant metacentric height along the length of the ship, which introduces major errors. Although SHIPMO7 correctly considers the longitudinal variation of sectional metacentric height, its limited accuracy for the CPF is likely due to limitations of strip theory. The better torsion results for a more slender warship model support this conclusion.

In irregular head seas, SHIPMO7 overpredicts vertical bending moment at midships by approximately 25 percent. By comparison, PRECAL typically gives modest overpredictions between 3 and 15 percent, increasing with ship speed. The degree of overprediction for both SHIPMO7 and PRECAL increases modestly with wave height.

Vertical shear and vertical moments in head seas exhibit little variation between operational light and deep departure loading conditions; thus, a single representative loading condition can be used to determine design loads for all loading conditions.

A SHIPMO7 Sample Input File

21

42

43

0.3151 0.3160 0.3160 0.3160 0.3160 0.3160 0.3160 <----- Station KG's (model-scaled) 0.1360 0.1406 0.1561 0.2560 0.2498 0.2525 0.2508 0.2979 0.3373 0.3171 0.3317 0.3020 0.3175 0.2659 0.3022 0.3581 0.2295 0.2441 0.2084 0.1489 0.1135 <---- Station roll gyradii (model) 0.0021 0.372 0.061 0.039 0.104 <---- Bow overhang data 0.0 0.0 <---- Stern overhang data 0.0 0.0 0.0 0 5.0 0.01 <---- Seakeeping position data 1 <---- Number of bilge keel pairs <---- First and last stations spanned by bilge keel 4 14 <---- Bilge keel data (model-scaled)</pre> 3.84 4.5 0.196 0.200 0.04 4.5 5.5 0.223 0.166 0.04 5.5 6.5 0.253 0.139 0.04 6.5 7.5 0.265 0.108 0.04 7.5 8.5 0.287 0.100 0.04 8.5 9.5 0.296 0.091 0.04 9.5 10.5 0.303 0.086 0.04 10.5 11.5 0.305 0.085 0.04 11.5 12.5 0.301 0.085 0.04 12.5 13.5 0.294 0.087 0.04 13.5 14.47 0.277 0.093 0.04 <---- Skeg data (model-scaled) 20 0.001 0.001 19.3 0.0 0.184 0.265 0.236 0.1055 0.0 0.0 <---- Rudder data (model-scaled) 0.0 0.0 0.0 0.0 0.0 0.0 0.0 <---- Rudder roll gains <---- Rudder yaw gains 0.0 0.0 0.0 <---- Number of stationary foil pairs 4 16.4 0.195 0.135 0.070 0.035 0.035 0.000 -105.5 1.00 <---- Shaft bracket data 16.4 0.090 0.125 0.070 0.035 0.035 0.000 -48.0 1.00 (model-scaled) 18.3 0.215 0.195 0.163 0.050 0.050 0.000 -104.5 1.00 18.3 0.030 0.170 0.170 0.050 0.050 0.000 -51.0 1.00 <---- Fin or tank stabilization NOSTAB

B PRECAL Sample Input Files

B.1 HYDMES Pre-processor Input File 1 - cpfmodel.hin

```
#
## TITLE
#
AUTOMATIC FACET GENERATION - SHIPMO7/PRECAL VALIDATION STUDY, May 1997
#
## SHIP NAME
#
CPF Hydroelastic Model, Deep Departure Conditions
#
## SHIP TYPE
#
MONOHULL
#
## HYDMES OPTIONS
#
OPTION
OCAL
OINP
OOUT
OMAS
ENDOPT
#
## CONSTANTS
#
CONSTS
CDEN 1.000
CACC 9.80665
ENDCON
#
## SHIP DIMENSIONS
#
SHIPDS
SDIM 6.735 6.225 0.740 0.2485 0.0019
SGMS 16.263 0.0541
SSYM Y=0
ENDSHI
#
## MASS DISTRIBUTION DATA
#
   DM
            XM
                    ΥM
                            ΖM
                                   Ixx
                                           Iyy
                                                   Izz
#
MASSDI
         3.1515 0.0000 0.1115 0.00001
0.0021
                                         0.00000
                                                   0.00000
0.0039
        3.1125
                0.0000 0.1115
                                 0.00007
                                          0.00000
                                                   0.00000
0.0082
        2.8013
                0.0000 0.1115
                                 0.00016
                                          0.00000
                                                   0.00000
0.0102
        2.4900 0.0000 0.1115
                                 0.00025
                                          0.00000
                                                   0.00000
0.0273
        2.1788 0.0000 0.0739
                                 0.00179
                                          0.00000
                                                   0.00000
0.0260
        1.8675 0.0000 0.0739
                                 0.00162 0.00000 0.00000
```

					A AAAAA	<u> </u>		
0.0266	1.5563	0.0000	0.0860	0.00169	0.00000	0.00000		
0.0262	1.2450	0.0000	0.0980	0.00165	0.00000	0.00000		
0.0370	0.9338	0.0000	0.0980	0.00328	0.00000	0.00000		
0.0474	0.6225	0.0000	0.0538	0.00539	0.00000	0.00000		
0.0419	0.3113	0.0000	0.0538	0.00421	0.00000	0.00000		
0.0458	0.0000	0.0000	0.0525	0.00505	0.00000	0.00000		
0.0380	-0.3113	0.0000	0.0511	0.00346	0.00000	0.00000		
0.0420	-0.6225	0.0000	0.0511	0.00423	0.00000	0.00000		
0.0295	-0.9338	0.0000	0.0511	0.00208	0.00000	0.00000		
0.0380	-1.2450	0.0000	0.0546	0.00347	0.00000	0.00000		
0.0534	-1.5563	0.0000	0.0555	0.00685	0.00000	0.00000		
0.0220	-1.8675	0.0000	0.0555	0.00116	0.00000	0.00000		
0.0248	-2.1788	0.0000	0.0555	0.00148	0.00000	0.00000		
0.0181	-2.4900	0.0000	0.0555	0.00079	0.00000	0.00000		
0.0092	-2.8013	0.0000	0.0555	0.00020	0.00000	0.00000		
0.0027	-3.1125	0.0000	0.0555	0.00003	0.00000	0.00000		
ENDMAS		•						
#	•							
## AUTO	MATIC FAC	ETIZATIC	IN PARAME	TERS				
#								
AFTEND								
TOTFAC								
0.5 1.0	80							
ENDTOT								
ENDAFT								
FOREND								
TOTFAC								
0.5 1.0	80							
ENDTOT								
ENDFOR								
#								
## END OF INPUT FILE								
#								
ENDFIL								

B.2 HYDMES Pre-processor Input File 2 - cpfmodel.hul

CPF Hydroelastic Model, Deep Departure Conditions 6.225 0.740 21 0.0 14 0.0000 0.1000 0.1750 0.2500 0.2717 0.2775 0.2815 0.2884 0.2962 0.3000 0.3041 0.3119 0.3197 0.3247 0.2315 0.2315 0.2315 0.2316 0.2500 0.2610 0.2750 0.3000 0.3500 0.3743 0.4000 0.4500 0.5000 0.5316 0.5 18 0.0000 0.0500 0.1000 0.1500 0.1936 0.2000 0.2500 0.2904 0.2957 0.3000 0.3063 0.3143 0.3224 0.3237 0.3304 0.3385 0.3465 0.3480 0.1835 0.1870 0.1906 0.1947 0.2000 0.2010 0.2143 0.2500 0.2610 0.2731 0.3000 0.3500 0.4000 0.4080 0.4500 0.5000 0.5500 0.5592 1.0 20

0.0000 0.0074 0.0500 0.1000 0.1500 0.2000 0.2500 0.2566 0.3000 0.3059 0.3230 0.3246 0.3309 0.3388 0.3440 0.3468 0.3500 0.3547 0.3626 0.3639 0.1485 0.1500 0.1577 0.1659 0.1744 0.1838 0.1973 0.2000 0.2339 0.2500 0.3000 0.3100 0.3500 0.4000 0.4325 0.4500 0.4706 0.5000 0.5500 0.5582 1.5 20 0.0000 0.0089 0.0500 0.1000 0.1500 0.1647 0.2000 0.2500 0.2784 0.2946 0.3000 0.3256 0.3379 0.3456 0.3500 0.3533 0.3609 0.3686 0.3763 0.3774 0.0940 0.1000 0.1227 0.1375 0.1472 0.1500 0.1576 0.1731 0.1875 0.2000 0.2055 0.2500 0.3000 0.3500 0.3790 0.4000 0.4500 0.5000 0.5500 0.5573 2.0 22 0.0000 0.0171 0.0380 0.0500 0.0858 0.1000 0.1500 0.2000 0.2500 0.2688 0.3000 0.3108 0.3193 0.3406 0.3500 0.3506 0.3586 0.3655 0.3729 0.3803 0.3877 0.3887 0.0259 0.0500 0.0750 0.0841 0.1000 0.1038 0.1130 0.1233 0.1402 0.1500 0.1747 0.1875 0.2000 0.2500 0.2959 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5565 2.5 22 0.0000 0.0500 0.0592 0.1000 0.1500 0.1543 0.2000 0.2394 0.2500 0.3000 0.3092 0.3334 0.3390 0.3500 0.3532 0.3611 0.3682 0.3754 0.3826 0.3898 0.3970 0.3978 0.0000 0.0449 0.0500 0.0641 0.0742 0.0750 0.0860 0.1000 0.1049 0.1397 0.1500 0.1875 0.2000 0.2354 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5559 3.0 22 0.0000 0.0500 0.1000 0.1500 0.1719 0.2000 0.2448 0.2500 0.2889 0.3000 0.3337 0.3494 0.3500 0.3530 0.3630 0.3699 0.3767 0.3835 0.3903 0.3971 0.4040 0.4047 0.0000 0.0173 0.0324 0.0448 0.0500 0.0578 0.0750 0.0775 0.1000 0.1088 0.1500 0.1875 0.1895 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5554 3.5 21 0.0000 0.0500 0.1000 0.1500 0.2000 0.2217 0.2500 0.2764 0.3000 0.3091 0.3448 0.3500 0.3613 0.3695 0.3760 0.3824 0.3888 0.3952 0.4017 0.4081 0.4087 0.0000 0.0075 0.0179 0.0295 0.0430 0.0500 0.0613 0.0750 0.0918 0.1000 0.1500 0.1623 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5551 4.0 20 0.0000 0.0500 0.1000 0.1500 0.2000 0.2412 0.2500 0.3000 0.3174 0.3500 0.3503 0.3650 0.3723 0.3785 0.3847 0.3908 0.3970 0.4032 0.4094 0.4100 0.0000 0.0075 0.0169 0.0263 0.0367 0.0500 0.0537 0.0837 0.1000 0.1494 0.1500 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5550 4.5 20 0.0000 0.0500 0.1000 0.1500 0.2000 0.2470 0.2500 0.3000 0.3208 0.3500 0.3522 0.3656 0.3723 0.3785 0.3847 0.3908 0.3970 0.4032 0.4093 0.4100 0.0000 0.0075 0.0169 0.0263 0.0357 0.0500 0.0513 0.0806 0.1000 0.1450 0.1500 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5550 5.0 20 0.0000 0.0500 0.1000 0.1500 0.2000 0.2448 0.2500 0.3000 0.3174 0.3495 0.3500 0.3629 0.3699 0.3764 0.3829 0.3894 0.3959 0.4024 0.4089 0.4096 0.0000 0.0075 0.0169 0.0263 0.0358 0.0500 0.0523 0.0834 0.1000 0.1500 0.1514 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5551 5.5 20 0.0000 0.0500 0.1000 0.1500 0.2000 0.2362 0.2500 0.3000 0.3061 0.3407 0.3500 0.3552 0.3634 0.3709 0.3784 0.3859 0.3934 0.4009 0.4084 0.4099 0.0000 0.0075 0.0169 0.0263 0.0366 0.0500 0.0570 0.0939 0.1000 0.1500 0.1769 0.2000 0.2500 0.3000 0.3500 0.4000 0.4500 0.5000 0.5500 0.5573 6.0 22 0.0000 0.0500 0.1000 0.1500 0.2000 0.2170 0.2500 0.2583 0.2877 0.3000 0.3247

 $0.3406 \ 0.3500 \ 0.3510 \ 0.3604 \ 0.3623 \ 0.3698 \ 0.3792 \ 0.3886 \ 0.3980 \ 0.4074 \ 0.4092$ 0.0000 0.0075 0.0169 0.0264 0.0422 0.0500 0.0693 0.0750 0.1000 0.1131 0.1500 0.2000 0.2449 0.2500 0.3000 0.3100 0.3500 0.4000 0.4500 0.5000 0.5500 0.5596 6.5 23 0.0000 0.0500 0.1000 0.1500 0.1857 0.2000 0.2287 0.2500 0.2595 0.2990 0.3000 0.3180 0.3311 0.3428 0.3452 0.3500 0.3551 0.3682 0.3792 0.3816 0.3928 0.4040 0.4067 0.0000 0.0075 0.0182 0.0340 0.0500 0.0571 0.0750 0.0915 0.1000 0.1500 0.1520 0.2000 0.2500 0.3000 0.3100 0.3299 0.3500 0.4000 0.4392 0.4500 0.5000 0.5500 0.5620 7.0 21 0.0000 0.0500 0.1000 0.1486 0.1500 0.2000 0.2187 0.2500 0.2602 0.2851 0.3000 0.3029 0.3183 0.3344 0.3500 0.3524 0.3705 0.3718 0.3847 0.3976 0.4025 $0.0000\ 0.0094\ 0.0267\ 0.0500\ 0.0508\ 0.0840\ 0.1000\ 0.1351\ 0.1500\ 0.2000\ 0.2412$ 0.2500 0.3000 0.3500 0.3938 0.4000 0.4450 0.4500 0.5000 0.5500 0.5690 7.5 21 0.0000 0.0500 0.1000 0.1134 0.1500 0.1735 0.2000 0.2137 0.2435 0.2500 0.2665 0.2866 0.3000 0.3069 0.3297 0.3500 0.3574 0.3607 0.3739 0.3887 0.3978 0.0000 0.0152 0.0414 0.0500 0.0778 0.1000 0.1311 0.1500 0.2000 0.2131 0.2500 0.3000 0.3336 0.3500 0.4000 0.4377 0.4500 0.4555 0.5000 0.5500 0.5809 8.0 21 0.0000 0.0500 0.0833 0.1000 0.1294 0.1500 0.1653 0.1958 0.2000 0.2223 0.2465 0.2500 0.2702 0.2963 0.3000 0.3281 0.3424 0.3500 0.3537 0.3721 0.3882 0.0000 0.0237 0.0500 0.0662 0.1000 0.1276 0.1500 0.2000 0.2075 0.2500 0.3000 0.3075 0.3500 0.4000 0.4064 0.4500 0.4695 0.4901 0.5000 0.5500 0.5936 8.5 22 0.0000 0.0500 0.0580 0.0919 0.1000 0.1195 0.1457 0.1500 0.1713 0.1966 0.2000 0.2219 0.2492 0.2500 0.2812 0.3000 0.3080 0.3147 0.3391 0.3500 0.3635 0.3669 0.0000 0.0400 0.0500 0.1000 0.1140 0.1500 0.2000 0.2084 0.2500 0.3000 0.3068 0.3500 0.4000 0.4014 0.4500 0.4759 0.4862 0.5000 0.5500 0.5724 0.6000 0.6070 9.0 21 0.0000 0.0361 0.0500 0.0583 0.0776 0.0965 0.1000 0.1167 0.1387 0.1500 0.1628 0.1893 0.2000 0.2188 0.2500 0.2539 0.2580 0.2856 0.3000 0.3164 0.3295 0.0000 0.0500 0.0804 0.1000 0.1500 0.2000 0.2090 0.2500 0.3000 0.3241 0.3500 0.4000 0.4190 0.4500 0.4950 0.5000 0.5053 0.5500 0.5734 0.6000 0.6213 9.5 20 0.0000 0.0145 0.0258 0.0368 0.0487 0.0500 0.0628 0.0793 0.0988 0.1000 0.1212 0.1469 0.1500 0.1767 0.1946 0.2000 0.2116 0.2476 0.2500 0.2699 0.0063 0.0500 0.1000 0.1500 0.2000 0.2050 0.2500 0.3000 0.3500 0.3530 0.4000 0.4500 0.4556 0.5000 0.5265 0.5340 0.5500 0.6000 0.6034 0.6311 10.0 14 0.0000 0.0015 0.0030 0.0055 0.0159 0.0290 0.0449 0.0500 0.0641 0.0879 0.1000 0.1181 0.1500 0.1808 0.2315 0.2365 0.2416 0.2500 0.3000 0.3500 0.4000 0.4144 0.4500 0.5000 0.5216 0.5500 0.5956 0.6363

48

B.3 HYDCAL Input File - cpfmodel.cnd

TITLE HYDCAL RUN AT FR = 0.06, HEADING = 135 (May 1997) ## SHIP NAME CPF Hydroelastic Model, Deep Departure Conditions ## SHIP TYPE MONOHULL **## HYDCAL OPTIONS** OPTION OKTS OFSP ENDOPT **## OPERATING CONDITIONS** CONDNS SPED 0.917 HEAD 135.0 FREQ 2.00 2.10 2.20 2.30 2.40 2.50 2.60 2.70 2.80 2.90 3.00 3.10 3.20 3.30 3.40 3.50 3.60 3.70 3.80 3.90 4.00 4.10 4.20 4.30 4.40 ENDCON **##** FREE-SURFACE PANEL INFORMATION FSPANS 2 ENDFSP ENDFIL

B.4 RESCAL Input File - cpfmodel.inp

```
## TITLE
RESCAL RUN AT FN=0.06, HEAD = 135, DAMPING = 0.135 FROM SHIPM07 (June 1996)
## SHIP NAME
CPF Hydroelastic Model, Deep Departure Conditions
## SHIP TYPE
MONOHULL
## RESCAL OPTIONS
OPTION
OMOT
OPRE
OLOA
ENDOPT
## ROLL DAMPING INPUT
ROLLIN
DAMP 0.135
ENDROL
## LOAD POSITION - Long. loads are calculated at SHIPMO7 stations 2.5, 5.0,
                   7.5, 10.0, 13.7 (PRECAL convention - 0.0 at AP, 1.0 at FP)
#
LOPOSN
LONGI
0.875
0.750
0.625
0.500
0.315
ENDLOP
## END OF INPUT FILE
ENDFIL
```

References

- [1] D.L. Chow and K.A. McTaggart, "Validation of SHIPMO7 and PRECAL Predictions with a Warship Model," DREA Technical Memorandum 97/203, November 1996.
- [2] A.R.J.M. Lloyd, J.C. Brown, and J.F.W. Anslow, "Motions and Loads on Ship Models in Regular Oblique Waves," Transactions, Royal Institution of Naval Architects 122, 21-43 (1980).
- [3] A.R.J.M. Lloyd, J.C. Brown, and J.F.W. Anslow, *Wave Induced Motions and Loads on a Model Warship*, Royal Institution of Naval Architects, Occasional Publication No. 3, 1980.
- [4] K.A. McTaggart, "SHIPMO7: An Updated Strip Theory Program for Predicting Ship Motions and Sea Loads in Waves," DREA Technical Memorandum 96/243, March 1997.
- [5] K. McTaggart, I. Datta, A. Stirling, S. Gibson, and I. Glen, "Motions and Loads of a Hydroelastic Frigate Model in Severe Seas," *Transactions, Society of Naval Architects and Marine Engineers* 105 (1997).
- [6] K. Hardiman and C. Daley, "Final Report Construction of a Hydroelastic Canadian Patrol Frigate Model for Testing in Severe Seas," Report 3838C, Fleet Technology Limited, 1993.
- [7] S. Ando, "Wave Load Prediction for the SHIPMO Computer Program," DREA Technical Memorandum 82/L, October 1982.
- [8] S. Ando, "Correlation of Wave Loads Predicted by the Extended SHIPMO Computer Program and Experiments," DREA Technical Memorandum 85/218, August 1985.
- [9] D. Cooper and A.K. Brook, "Hydrodynamic Pressure Project Correlation between HPC-FEM and Experiment," Report W1815 (Parts 1 and 2), BMT, November 1988. Distribution limited to CRS members.
- [10] S. Ando, "Testing of New PRECAL for a Case of a Destroyer in Regular Head Waves," DREA Technical Memorandum 95/230, December 1995. Distribution limited to CRS members.
- [11] G.W. Johnston and D. Yamane, "Improved Time-Domain Code for Prediction of Ship Motion and Sea Loads in Head and Following Seas – Final Report," DREA Contractor Report CR/95/481, October 1995.
- [12] G.W. Johnston and D. Yamane, "Improved Time-Domain Code for Prediction of Ship Motion and Sea Loads in Head Seas – User's Manual," DREA Contractor Report CR/95/482, October 1995.
- [13] N. Salvesen, E.O. Tuck, and O. Faltinsen, "Ship Motions and Sea Loads," Transactions, Society of Naval Architects and Marine Engineers 78, 250-287 (1970).
- [14] R.T. Schmitke, "Ship Sway, Roll, and Yaw Motions in Oblique Seas," Transactions, Society of Naval Architects and Marine Engineers 86, 26-46 (1978).

- [15] R. Graham, "SHIPMO3: Improved Viscous Roll Damping Predictions for the SHIPMO Computer Program," DREA Technical Memorandum 86/212, May 1986.
- [16] BMT SeaTech, "User's Manual for Motion, Load and Pressure Program Suite PRECAL," Technical Report, prepared for NSMB CRS PRECAL Working Group, January 1995. Distribution limited to CRS members.
- [17] J.M. Toring, Y.S. Shin, and H.H. Chen, "Theoretical Manual for Three-dimensional Hydrodynamic Pressure Calculation Program (PRECAL)," Technical Report RD-88025, American Bureau of Shipping, December 1988. Distribution limited to CRS members.
- [18] G.W. Johnston and S. Foster, "Time-Domain Program of Ship Motions and Sea Loads in Irregular Head Seas – Final Report," DREA Contractor Report CR/93/464, September 1993.
- [19] G.W. Johnston and S. Foster, "Time-Domain Program of Ship Motions and Sea Loads in Irregular Head Seas – User's Manual," DREA Contractor Report CR/93/463, September 1993.
- [20] B.K. King, R.F. Beck, and A.R. Magee, "Seakeeping Calculations with Forward Speed Using Time-Domain Analysis," in *Seventeenth Symposium on Naval Hydrodynamics* (The Hague, 1988), pp. 577–596.
- [21] T. Sarpkaya and M. Isaacson, Mechanics of Wave Forces on Offshore Structures, Van Nostrand Reinhold, 1981.
- [22] R. Wahab, "Amidships Forces and Moments on a $C_B = 0.80$ Series 60 Model in Waves from Various Directions," Report 100 S, Netherlands Ship Research Centre TNO, 1967.

UNCLASSIFIED

SECURITY CLASSIFICATION OF FORM (highest classification of Title, Abstract, Keywords)

DOCUMENT		ТЛ					
DOCUMENT CONTROL DATA (Security classification of title, body of abstract and indexing annotation must be entered when the overall document is classified)							
 ORIGINATOR (The name and address of the organization prepa document. Organizations for whom the document was prepared, Establishment sponsoring a contractor's report, or tasking agenc in section 8.) 	aring the e.g. y, are entered	 SECURITY CLASSIFICATION (Overall security of the document including special warning terms if applicable.) 					
Defence Research Establishment Atlantic P.O. Box 1012, Dartmouth, N.S. B2Y 32	UNCLASSIFIED						
 TITLE (The complete document title as indicated on the title page. Its classification should be indicated by the appropriate abbreviation (S,C.R or U) in parentheses after the title.) 							
Validation of SHIPMO7 and PRECAL with the CPF Hydroelastic Model							
4. AUTHORS (Last name, first name, middle initial. If military, show rank, e.g. Doe, Maj. John E.)							
McTAGGART, Kevin A. and CHOW, Dann L.							
 DATE OF PUBLICATION (Month and year of publication of document.) 	6a. NO. OF PAC containing i	GES (Total nformation.	6b. NO. OF REFS. (Total cited in document.)				
August 1997	etc.)	61	22				
 DESCRIPTIVE NOTES (The category of the document, e.g. technical report, technical note or memorandum. If appropriate, enter the type of report, e.g. interim, progress, summary, annual or final. Give the inclusive dates when a specific reporting period is covered.) 							
Technical Memorandum							
8. SPONSORING ACTIVITY (The name of the department project office or laboratory sponsoring the reseach and development. include the address.)							
Defence Research Establishment Atlantic P.O. Box 1012, Dartmouth, N.S. B2Y 3Z7							
9a. PROJECT OR GRANT NUMBER (If appropriate, the applicable research and development project or grant number under which the document was written. Please specify whether project or grant.)	9b. CONTRACT NUMBER (If appropriate, the applicable number under which the document was written.)						
Project 1.g.b							
10a. ORIGINATOR'S DOCUMENT NUMBER (The official document number by which the document is identified by the originating activity. This number mrst be unique to this document.)	10b. OTHER DOCUMENT NUMBERS (Any other numbers which may be assigned this document either by the originator or by the sponsor.)						
DREA Technical Memorandum 97/216							
11. DOCUMENT AVAILABILITY (Any limitations on further dissemination of the document, other than those imposed by security classification)							
 (X) Unlimited distribution Distribution limited to defence departments and defence contractors; further distribution only as approved Distribution limited to defence departments and Canadian defence contractors; further distribution only as approved Distribution limited to government departments and agencies; futher distribution only as approved Distribution limited to defence departments; further distribution only as approved Distribution limited to defence departments; further distribution only as approved Other (please specify): 							
12. DOCUMENT ANNOUNCEMENT (Any limitation to the bibliographic annoucement of this document. This will normally correspond to the Document Availability (11). However, where futher distribution (beyond the audience specified in 11) is possible, a wider announcement audience may be selected.)							

UNCLASSIFIED

SECURITY CLASSIFICATION OF FORM

DCDO3 2/06/87

ABSTRACT (a brief and factual summary of the document. It may also appear elsewhere in the body of the document itself. It is highly desirable that the abstract of classified documents be unclassified. Each paragraph of the abstract shall begin with an indication of the security classification of the information in the paragraph (unless the document itself is unclassified) represented as (S), (C), (R), or (U). It is not necessary to include here abstracts in both official languages unless the text is bilingual).

This report gives results of an extensive validation of DND's strip theory program SHIPMO7 and the three-dimensional ship motion code PRECAL developed by Cooperative Research Ships. Ship motion and sea load predictions are compared with results for the CPF hydroelastic model, which was tested in regular and irregular waves in both head and oblique seas. In general, both codes give excellent agreement for ship motions and reasonable agreement for sea loads. In irregular head seas, PRECAL overpredicts vertical bending moment at midships by an average of 9 percent, which is superior to the average overprediction by SHIPMO7 of 25 percent.

14. KEYWORDS, DESCRIPTORS or IDENTIFIERS (technically meaningful terms or short phrases that characterize a document and could be helpful in cataloguing the document. They should be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location may also be included. If possible keywords should be selected from a published thesaurus. e.g. Thesaurus of Engineering and Scientific Terms (TEST) and that thesaurus-identified. If it not possible to select indexing terms which are Unclassified, the classification of each should be indicated as with the title).

seakeeping ship motions strip theory panel methods sea loads heave roll pitch yaw shear bending moment torsion

54

UNCLASSIFIED SECURITY CLASSIFICATION OF FORM