

LOAN DOCUMENT

DTIC ACCESSION NUMBER		PHOTOGRAPH THIS SHEET																					
	LEVEL		INVENTORY																				
	DOCUMENT IDENTIFICATION																						
DISTRIBUTION STATEMENT																							
<table border="1"><tr><td colspan="2">ACCESSION FOR</td></tr><tr><td>NTIS</td><td>GRAM <input checked="" type="checkbox"/></td></tr><tr><td>DTIC</td><td>TRAC <input type="checkbox"/></td></tr><tr><td>UNANNOUNCED</td><td><input type="checkbox"/></td></tr><tr><td>JUSTIFICATION</td><td></td></tr><tr><td colspan="2">BY</td></tr><tr><td colspan="2">DISTRIBUTION/</td></tr><tr><td colspan="2">AVAILABILITY CODES</td></tr><tr><td>DISTRIBUTION</td><td>AVAILABILITY AND/OR SPECIAL</td></tr><tr><td>A-1</td><td></td></tr></table>		ACCESSION FOR		NTIS	GRAM <input checked="" type="checkbox"/>	DTIC	TRAC <input type="checkbox"/>	UNANNOUNCED	<input type="checkbox"/>	JUSTIFICATION		BY		DISTRIBUTION/		AVAILABILITY CODES		DISTRIBUTION	AVAILABILITY AND/OR SPECIAL	A-1		DATE RECEIVED IN DTIC	
ACCESSION FOR																							
NTIS	GRAM <input checked="" type="checkbox"/>																						
DTIC	TRAC <input type="checkbox"/>																						
UNANNOUNCED	<input type="checkbox"/>																						
JUSTIFICATION																							
BY																							
DISTRIBUTION/																							
AVAILABILITY CODES																							
DISTRIBUTION	AVAILABILITY AND/OR SPECIAL																						
A-1																							
DISTRIBUTION STAMP																							
DATE RETURNED																							
19981223 061		REGISTERED OR CERTIFIED NUMBER																					

H
A
N
D
L
E

W
I
T
H

C
A
R
E

UNCLASSIFIED

DIC
12-18-77

NO DISTRIBUTION
STATEMENT

NADC
Tech. Info.

APPENDIX 25
SIGNAL SORTER COMMON DATA BASE
FINAL SOFTWARE REPORT
DATA ITEM NO. A005

**INTEGRATED ELECTRONIC WARFARE SYSTEM
ADVANCED DEVELOPMENT MODEL (ADM)**

780098725

PREPARED FOR:
NAVAL AIR DEVELOPMENT CENTER
WARMINSTER, PENNSYLVANIA
CONTRACT N62269-75-C-0070



ELECTROMAGNETIC
SYSTEMS DIVISION

1 OCTOBER 1977

UNCLASSIFIED

APPENDIX 25
SIGNAL SORTER COMMON DATA BASE
FINAL SOFTWARE REPORT
DATA ITEM A005

INTEGRATED ELECTRONIC WARFARE SYSTEM (IEWS)
ADVANCED DEVELOPMENT MODEL (ADM)

Contract No. N62269-75-C-0070

Prepared for:

Naval Air Development Center
Warminster, Pennsylvania

Prepared by:

RAYTHEON COMPANY
Electromagnetic Systems Division
6380 Hollister Avenue
Goleta, California 93017

1 OCTOBER 1977

Reproduced From
Best Available Copy

COMMON DATA BASE DESIGN DOCUMENT

IEWS SIGNAL SORTER SOFTWARE

1.0 SCOPE

This document describes the data base for the IEWS Signal Sorter software.

2.0 APPLICABLE DOCUMENTS

- WS-8506 Requirements for Digital Computer Program Documentation, Rev. 1, dated 1 November 1971.
- CG-983645 IEWS Signal Sorter Computer Program Performance Specification.
- CG-983645 IEWS Signal Sorter Supervisor Software Program Design Specification.
- CG-983645 IEWS Signal Sorter NESU Software Program Design Specification.
- RP-16 Microprocessor Manual.

3.0 REQUIREMENTS

3.1 TABLES

3.1.1 NESU Emitter File (EMFL)

Purpose and Type - Fixed length of 256 words. Used to maintain NESU CAM and detect and generate new emitter files.

Size and Indexing Procedure - 32 entries of 8 words apiece. Each entry corresponds to a CAM file. The first entry corresponds to the first CAM file, the second entry corresponds to the second CAM file, etc. All entries are referenced relative to the start of the file.



RAYTHEON COMPANY
LEXINGTON, MASS. 02173

CODE IDENT NO.

49956

SPEC NO.

SHEET
2 OF 9

REV

Entry Format:

15 14 13 0

Word 0	v	n	p	
Word 1	SOQ Pointer			
Word 2	EOQ Pointer			
Word 3	PDW count			
Word 4	Azimuth			
Word 5	Frequency			
Word 6	TOA msb			
Word 7	TOA lsb			

Field		Units	LSB
v	if set, indicates entry is a valid file		
n	if set, indicates entry is a newly generated emitter		
p	if set, indicates entry is to be processed by the next purge cycle		
SOQ pointer	memory address of the first word of the first PDW linked to the entry		
EOQ pointer	memory address of the first word of the last PDW linked to the entry		
PDW count	number of PDW's linked to the entry		1
azimuth	azimuth of emitter. Value from 0 to 63.	cells	1 cell
frequency	frequency of emitter contained in in bits 0-13.	MHz	1.25 Mhz.
TOA	Time of Arrival of last PDW. 20 bits with the 4 msb's right justified in word 6.	µsec	1.0 µsec



RAYTHEON COMPANY
LEXINGTON, MASS. 02173


CODE IDENT NO.	SPEC NO.	
49956	SHEET 3 OF 9	REV

3.1.2 NESU AOA FILE (AAFL)

Purpose and Type - Fixed length. Used for detecting frequency agile emitters.

Size and Indexing Procedure - 64 words, each word corresponding to an angle cell. Each word is referenced relative to the start of the file.

Entry Description -



Field		Units	LSB
PDW count	Count of number of PDW's whose azimuth corresponds to this angle cell.		1

3.1.3 SUPERVISOR EMITTER TABLE (EMTB)

Purpose and Type - Fixed length. Used for updating and maintaining the TC Track Data Memory files.

Size and Indexing Procedure - 128 entries of 9 words apiece. Each entry corresponds to one file in the TDM.

Entry Description -

	15	14	13	12	11	10	7	0
Word 0	v	u	t	n	e	p		priority/time
Word 1	PDW SOQ pointer							
Word 2	PDW EOQ pointer							
Word 3	PDW count							
Word 4	last PDW time							

RAYTHEON

RAYTHEON COMPANY
 LEXINGTON, MASS. 02173

CODE IDENT NO.

49956

SPEC NO.

4 SHEET
 OF 9

REV

Word 5	New Track PDW pointer
Word 6	throttle file no.
Word 7	update queue entry
Word 8	update queue entry

Field		Units	LSB
v	if set indicates entry is valid		
u	if set indicates corresponding file is being updated		
t	if set indicates corresponding file is being throttled by Input Buffer		
n	if set indicates corresponding file is not to be updated		
e	if set indicates a newly generated track file		
p	if set indicates file to be processed on next time-out cycle		
priority/time	number of seconds between updates	seconds	250ms
PDW SOQ pointer	memory address of the first word of the first PDW block to be used for updating		
PDW EOQ pointer	memory address of the first word of the last update PDW block currently linked		
PDW count	number of update PDW blocks linked to entry		1
last PDW time	The internal time last PDW block was received	seconds	250ms
new track PDW pointer	memory address of the first word of the first block of PDW's used to generate the track file. Contains zero if list has been purged.		

RAYTHEON

RAYTHEON COMPANY
LEXINGTON, MASS. 02173

CODE IDENT NO.

49956

SPEC NO.

SHEET
5 OF 9 REV

Throttle file no.

File number of the throttle file in the Input Buffer and Throttle Table.

Update queue entry

Two words used as an entry on the Update Queue. 2nd word contains the file number (0-127)

3.1.4 SUPERVISOR THROTTLE TABLE

Purpose and Type - fixed length. Used to maintain the Input Buffer CAM.

Size and Indexing Procedure - 8 entries of 2 words apiece. Each entry corresponds to a file in the IB CAM.

Entry Description -

	15	0
Word 0	emitter number	
Word 1	throttle count	

Field		Units	LSB
Emitter number	Number of TDM file and Emitter table entry		
Throttle count	Count in IB buffer CAM for corresponding file		

3.2 VARIABLES

3.2.1 NESU AOA THRESHOLD (AZTH)

Purpose - contains integer value of PDW count in an AOA field entry at which to generate an agile emitter file.

Size - 1 word

Range and Initial Condition - TBD

Changeable by the SC.

Positive integer value with LSB = 1

3.2.2 FREE CORE EOQ POINTER (CEOQ)

Purpose - contains memory address of the first word of the last free core block.

Size - 1 word

Range - 4096 to 20475

Initial value - TBD

Dynamic

3.2.3 FREE CORE SOQ POINTER (CSOQ)

Purpose - contains memory address of the first word of the first free core block

Size - 1 word

Range - 4096 to 20475

Initial Value - TBD

Dynamic

3.2.4 SUPERVISOR EMITTER PURGE TIME (PGTM)

Purpose - contains emitter purge time in seconds.

Size - 1 word

Range - TBD

Initial Condition - 10 seconds

Dynamic

LSB = 250 ms

3.2.5 SYSTEM TIME (TIME)

Purpose - contains current time value.

Size - 1 word

Range - 0 to 8195.75 seconds

Initial Condition - 0

Dynamic

LSB = 250 ms.

3.2.6 NEW TRACK START THRESHOLD (TRTH)

Purpose - contains number of PDW's to be used to generate a new emitter.

Size - 1 word

Range - TBD

Initial Condition - 0

Dynamic

LSB = 1

3.3 CONSTANTS

None

3.4 FLAGS

3.4.1 NESU PDW BUFFER INTERRUPT FLAG (INTR)

Purpose - indicates occurrence of PDW Buffer interrupt if non-zero.

Initial Condition - zero

Size - 1 word

3.4.2 NESU IDLE FLAG (NIDLE)

Purpose - indicates NESU is in idle state if non-zero.

Initial Condition - non-zero

Size - 1 word

3.4.3 NESU PURGE FLAG (PURGE)

Purpose - indicates NESU is to perform a purge cycle if non-zero.

Initial Condition - zero

Size - 1 word

3.4.4 SUPERVISOR IDLE FLAG (SIDLE)

Purpose - indicates Supervisor is in idle state if non-zero.

Initial Condition - non-zero

Size - 1 word

3.5 INDEXES

None

3.6 SUBPROGRAM REFERENCE

Figure 3.1 shows the usage of data base items by the routines.

4.0 NOTES

None

RAYTHEON

RAYTHEON COMPANY
LEXINGTON, MASS. 02173

CODE IDENT NO.

49956

SPEC NO.

SHEET
9 OF 9

REV

	NESU Core Manager	NESU PDW Buff. Int. Hand.	NESU Initial.	NESU Main Program	Supv. Aux. Functions	Supv. Core Manager	Supv. Mess. Hand.	Supv. SC	Supv. Init.
Variables									
AZTH	--	--	S	U	--	--	--		S S S S S
CEOQ	B	--	--	--	--	B	--		
CSOQ	B	--	--	--	--	B	--		
PGTM	--	--	--	--	U	--	S		
TIME	--	--	--	--	B	--	--		
TRTH	--	--	S	U	--	--	--		
Flags									
INTR	--	S	S	U	--	--	--		
NIDLE	--	--	S	B	--	--	--		
PURGE	--	--	--	B	S	--	--		
SIDLE	--	--	--	--	U	--	S		

FIGURE 1