REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188	
gathering and maintaining the data needed, and of information, including suggestions for reduc	completing and reviewing the collection of inf	ormation. Send comment re ervices, Directorate for info	for reviewing instructions, searching existing data sources, egarding this burden estimates or any other aspect of this collection ormation Operations and Reports, 1215 Jefferson Davis Highway, 4-0188 ) Washington DC 20503	
1. AGENCY USE ONLY ( Leave Blank		- 3.	REPORT TYPE AND DATES COVERED   NAL 01 Mar 99 - 29 Feb 00	
4. TITLE AND SUBTITLE Instrumentation for the Dynamic Response and Failure of Polymer Matrix Composites		Matrix	FUNDING NUMBERS AAD19-99-1-0102	
6. AUTHOR(S) A.M. Waas				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Michigan - Ann Arbor			PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)			). SPONSORING / MONITORING AGENCY REPORT NUMBER	
U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			ARO - 39319.1-EG-RIP	
	findings contained in this report and a policy or decision, unless so de		hor(s) and should not be construed as an official documentation.	
12 a. DISTRIBUTION / AVAILABILITY STATEMENT			12 b. DISTRIBUTION CODE	
Approved for public release; distribution unlimited.				
13. ABSTRACT (Maximum 200 words	)	I		
dynamic compressive loads. A h	ligh speed framing camera with va	ariable frames, instru	ponse and failure of polymer composites under umentation amplifiers for load cells, strain gage ort. The total budget with cost sharing was	
	_			
20010117 104				
	DTIC QUALITY INC	egeed 4		
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CL OF ABSTRACT UNCLASS		
NSN 7540-01-280-5500		1,,	Standard Form 298 (Rev.2-89) Prescribed by ANSI Std. 239-18	

Т

# Instrumentation for the Dynamic Response and Failure of Polymer Matrix Composites

US-DOD-Department of the Army, Reference No: 89319-EG-RIP Univ. of Michigan Project Grant F001104 Univ. of Michigan Account No. 038071

#### PI

Anthony M. Waas, Professor of Aerospace Engineering

> Tel: 734-764-8227. Fax: 734-763-0578. E-mail: dcw@umich.edu.

Final Report submitted on

Dec. 11, 2000

### Army Research Office Scientific Officer : Dr. M. Zikry

DEGEIVE DEC 2 0 2000 By\_\_\_\_\_ This document constitutes the final report on work carried out under ARO Grant 39319-EG-RIP for the purchase of instrumentation that is necessary to carry out experimentation for-the purpose of understanding and uncovering the dynamic response and failure of polymer matrix composite materials under dynamic compressive loading. Specifically, we purchased a high speed framing camera with variable framing rates and digital capability, instrumentation amplifiers for amplifying load cell and strain gage signals for the purpose of recording, a modern high speed data acquisition system for acquiring the data signals at high rates(5 Msa/s) and also with the capability of performing large scale operations on digital images, and a tetrahedron press for the in-house manufacture of the composite samples. In addition, accessories that are needed to supplement the efficient use of these pieces of equipment were also purchased. Table 1, shows the purchased items and the costs associated with the purchases.

, **'** 

-:

The research that the instrumentation will facilitate has three phases. In phase I, test coupons (polymer based fibrous laminated composites) that have a circular cylindrical shape and also flat plaque type coupons are manufactured in-house. These samples contain fibers of different mechanical properties in the same polymer matrix material. The ability to manufacture specimens of this type lends itself immediately to examining the effect of fiber properties on the dynamic compressive response of such materials. In addition, the effect of fiber volume fraction on the dynamic compressive response is also equally important and is being currently studied. The tetrahedron press allows the possibility of curing test samples under controlled pressure and temperature. Several, currently popular matrix materials require a controlled temperature/pressure cycle for proper processing. Such a capability is present in the Tetrahedron press. This capability was used in manufacturing the samples. Furthermore, because of the high temperature (600 degrees Celcius) curing capability, this press allows us to examine and experiment with materials that have a very high glass transition temperature. Experiments with such materials is planned for the near future. In phase two, the specimens are loaded dynamically using the SHPB and the NSWC, thereby characterizing the strain rate dependency and the mechanism of failure and how the mechanisms are influenced by constituent properties and microstructural detail. In this manner, information about the constituents are obtained in a consistent manner, which enables the development of associated mechanics models for assessing dynamic compressive strength.

The experimental work that that the instruments facilitate is currently underway. For the research component of this work, the PI has received funding from the ARO under a separate grant (Compressive Failure of . Several papers and presentations stemming from this\_research have been made and/or are slated for future publication. These are given below:

- 1) S.H. Lee and A. Waas, "Compressive Failure of Unidirectional Composites", *Int. J. of Fracture*, vol. 100, pp275-306, 1999.
- S. Lee, Chandra S. Yerramalli and Waas, A. M. "Compressive Splitting Response of Glass Fiber Reinforced Unidirectional Composites", accepted to appear. <u>J. Composites</u> <u>Science and Technology</u>, 2000
- Chandra S. Yerramalli and Waas, A. M. "Compressive Splitting Response of Glass Fiber Reinforced Unidirectional Composites using a Shear Lag Approach", in review, Int. J. Fracture, 2000
- Chandra S. Yerramalli and A. Waas, "In-situ static matrix properties obtained from torsional response of glass fiber and carbon fiber polyester composites ", in review, <u>ASME J. Engineering Materials and Technology</u>, 2000.
- Chandra S. Yerramalli and A. Waas, "In-situ dynamic matrix properties obtained from dynamic torsional response of glass fiber and carbon fiber polyester composites", in preparation, to be submitted to <u>ASME J. Engineering Materials and Technology</u>, 1999.
- 6) Y. Chandrasekar and A. Waas, Torsional and Combined Load Response of Glass Fiber and Carbon Fiber Vinyl Ester Composites, Soc. Engineering Science Meeting, Univ. of Texas at Austin, Sept. 1999.
- 7) Chandra S. Yerramalli and Waas, A. M. "Compressive Splitting Response of Glass Fiber Reinforced Unidirectional Composites using a Shear Lag Approach", to be presented at AIAA SDM Meeting, April 2001.

The above publications serve the purpose of disseminating the research work that the purchased equipment facilitate. In addition to the above publications, several other ongoing research programs have also benefited from the purchased instrumentation. Thus, the purchased equipment serves the purpose it was intended for as well as supplement additional research work conducted by the PI and his associates. Table 1 shows the purchased equipment.

## <u>Table 1</u>

### <u>UM. Cost sharing Funds: \$44,000.00</u> <u>US-DOD – ARO Funds: \$325,600.00</u> <u>Total Cost of Purchases: \$369, 147.05</u> <u>Total Budget: \$370,000.00</u>

" , **\*** 

Item No.	Item description	Price	
1	Data Acquisition System,	\$31,960	
	with image processing		
	capability. Dual Pentium II	1	
	Xeon Class	3	
2	Vishay Signal Amplifiers \$20,804		
	and Conditioners with		
	Signal Processing Software		
3	Kodak 4.2.1 Mega Plus	\$37,995	
	CCD Camera		
4	National Instruments Data	\$6,316	
	Acquisition Cards		
5	4 channels of high speed	\$3,215	
	data acquisition		
6	Variable Framing Rate	\$220,000	
	Cordin Digital Camera		
7	HP Infimum Oscilloscope	\$11,397	
8	Questar Imaging Lens	\$4,494	
9	Tetrahedron Press	\$20,274	
10	Portable Field Image Data	Portable Field Image Data \$5,792	
	Acquisition System		
11	Small Oven for Curing	\$4,315	
12	50 GB Hard Drive for Data	\$2,585.05	
	Storage and other		
	accessories		