


ARMY RESEARCH LABORATORY



Determining Inertial Orientation of a Spinning Body With Body-Fixed Sensors

David J. Hepner
Thomas E. Harkins

ARL-TR-2313

JANUARY 2001

20010227 121

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-TR-2313

January 2001

Determining Inertial Orientation of a Spinning Body With Body-Fixed Sensors

David J. Hepner

Thomas E. Harkins

Weapons and Materials Research Directorate

Approved for public release; distribution is unlimited.

Abstract

A methodology for determining absolute inertial angular orientation of a spinning body via independent angular measurements from two arbitrary body-fixed sensor systems is demonstrated. A particular application is denoted that uses U.S. Army Research Laboratory solar likeness indicating transducers and magneto-resistive sensors that provide body-fixed, independent angular measurements with regard to their respective local fields. Knowledge of the local field orientations and a coordinate transformation provides the inertial orientation angles, commonly called ψ and θ , which are useful for evaluating and developing advanced flight bodies and as a navigational aid for brilliant munitions. The combination of a dual field sensor system and the orientation determination methodology is called POINTER (Projectile Orientation In Navigation TERms). Typical sensor data and reduction processes are reviewed for a spinning body containing optical and magnetic sensors, and alternate field measurements are discussed.

ACKNOWLEDGMENTS

Mr. Brad Davis has been the lead engineer for the magnetic sensor experiments performed at the Weapons and Materials Research Directorate of the U.S. Army Research Laboratory. His efforts have greatly aided the authors in their appreciation of the potential of magnetic sensors. He is an integral part of the team pursuing engineering development of the MAGSONDE (MAGnetic SONDE).

The authors appreciate that the advances in body-fixed sensor use, which we believe MAGSONDE and POINTER represent, are only made possible by our augmenting previous efforts. Newton's famous statement in a letter to Robert Hooke comes to mind, "If I have seen farther, it is by standing upon the shoulders of giants." The bibliography, which is an attempt to recognize these predecessors, is far from exhaustive but will hopefully allow interested readers to further pursue related topics.

INTENTIONALLY LEFT BLANK

Contents

1.	Introduction	1
2.	Generalized Multi-Field Orientation	2
3.	Pointer.....	4
4.	SOLARSONDE	5
5.	MAGSONDE	7
6.	Launch Window	11
7.	Pointer Flight Experimental Design	12
8.	Alternate Fields	13
9.	Conclusions	14
	Bibliography	17
	Distribution List	21
	Report Documentation Page	27

Figures

1.	A Spinning Body Within a Convenient Navigational Coordinate System	3
2.	A Spinning Body Within Solar and Magnetic Fields Suitable for POINTER	4
3.	SOLARSONDE: Solar Field Geometry and Exemplary Sensor Installation	5
4.	A Solar Likeness Indicating Transducer (SLIT)	6
5.	Example of SOLARSONDE Sensor Excitations and Aspect Angle History Derived From Those Pulses	7
6.	MAGSONDE Projectile and Sensor Geometries	8
7.	Representative MAGSONDE Sensor Installation and Signals	10
8.	MAGSONDE Orientation Estimates and Errors for Simulated Idealized System	11
9.	Experimental Flight Data of Mixed Optical Sensor and Magnetometer Onto a Single Data Channel	13
10.	Variations in Sensor Response can Provide Projectile Orientation Information	14

INTENTIONALLY LEFT BLANK

DETERMINING INERTIAL ORIENTATION OF A SPINNING BODY WITH BODY-FIXED SENSORS

1. Introduction

During development of and diagnostic experiments with military munitions and weapons systems, a significant need exists for projectile aerodynamic characterization, evaluation of guidance and maneuver systems, and measures of truth for inertial measurement units (IMUs). Accurate measurement of projectile motion via body-fixed sensors can contribute significantly toward the development of projectiles, rockets, and weapons systems and to the diagnosis of failures in existing systems. Ground-based instrumentation systems can provide such measurements but are generally used for only limited portions of a projectile flight for reasons of both expense and practicability in application. On-board instrumentation would seem a logical candidate for obtaining data throughout a flight, except for current expense and reusability. Additionally, a host of packaging and survivability issues is associated with the use of such systems in military applications. One such difficulty arises from g-loads exerted during impulsive launch and continuous free-flight roll. Traditional sensors, signal conditioning, acquisition, and telemetry devices that survive this mechanical loading have had a significant impact on a wide range of military systems, and therefore, similar qualification of state-of-the-art components, packaging, and processing schemes could lead to extremely reliable built-in measurement systems.

It is the primary objective of this report to describe a device and a simple, robust methodology wherein an on-board, multi-sensor system solution that employs optical sensors and magnetometers completely determines the orientation of a principal rotation axis of a spinning body with respect to a convenient navigational system. This device is called POINTER (Projectile Orientation In Navigational TERMS). The continuous in-flight angular orientation histories obtained with POINTER can be used for projectile aerodynamic characterization and for investigation and evaluation of guidance and maneuver systems. POINTER will also provide a truth measure for the investigation and evaluation of other pointing angle measurement systems, such as rate-integrating inertial systems. The determination of the navigational pointing angle is important for the effectiveness of guidance and terminal seeking systems and advanced video imaging systems for target location. The POINTER orientation algorithm can be implemented within the device via electronics and signal processing to generate real-time navigational orientation or during post-flight processing of stored or telemetered data.

Many research and tactical applications of POINTER or some of its components are possible. POINTER can be generalized to include sensed alignments for any multi-field environment such as gravity or radio frequency (RF) fields. Conversely, if the navigational orientation is known, a magnetic field orientation can be defined. In addition, the mapping of deep space magnetic fields would be possible with multiple stars as light sources.

2. Generalized Multi-Field Orientation

The principal axis of rotation of a three-dimensional (3-D) freely flying solid body can be defined by a coordinate system that employs three variables denoting location and two variables defining angular orientation. The derivative of the location with respect to time is commonly referred to as the velocity vector, \vec{V} . The principal axis of rotation of a spinning body is often not co-linear with the velocity vector. In this case, orientation via a time history and derivatives of location variables does not provide an accurate determination of the navigational pointing angle. For a symmetrical, spinning body, the navigational pointing vector, \vec{P} , is coincident with the principal axis of rotation, commonly called the "spin axis." The rotation rate of the body about this axis is commonly called the "spin rate." The navigational variables ψ and θ are used to denote the two angular variables required to orient the body's principal axis of rotation within the navigational system. Measurement of the included angle between the axis of rotation and each field, knowledge of the field orientations, and favorable orientations of the fields with respect to the axis of rotation are required. Finally, a tabular pointing angle time history can be generated for this navigational coordinate system.

The generalized field transformation can be exemplified by combining the coordinate system with two representative field vectors of known orientation, \vec{F}_1 , and \vec{F}_2 , to yield the angle definitions shown in Figure 1.

Let the unit vectors \vec{P} , \vec{F}_1 , and \vec{F}_2 along \vec{P} , \vec{F}_1 , and \vec{F}_2 be defined within the (X, Y, Z) system as

$$\begin{aligned}\vec{P} &= (P_x, P_y, P_z) \\ \vec{F}_1 &= (F_{1_x}, F_{1_y}, F_{1_z}) \\ \vec{F}_2 &= (F_{2_x}, F_{2_y}, F_{2_z})\end{aligned}\tag{1}$$




Figure 1. A Spinning Body Within a Convenient Navigational Coordinate System.

The components of \bar{P} are obtained from the simultaneous solution of the system:

$$\begin{aligned}\bar{P} \cdot \bar{F}_1 &= \cos(\sigma_1) \\ \bar{P} \cdot \bar{F}_2 &= \cos(\sigma_2) \\ |\bar{P}| &= 1\end{aligned}\tag{2}$$

in which \bar{F}_1 , \bar{F}_2 , σ_1 , σ_2 are known, estimated, or measured. The pointing angles are then given by

$$\theta = \tan^{-1} \left(\frac{P_z}{\sqrt{P_x^2 + P_y^2}} \right) \quad \phi = \tan^{-1} \left(\frac{P_y}{P_x} \right)\tag{3}$$

The methodology yields two possible diametrically opposed pointing angle solutions. Knowledge of the initial navigational orientation resolves this trivial ambiguity. Furthermore, the unique solution can be maintained as long as vectors \bar{P} , \bar{F}_1 , and \bar{F}_2 are not coplanar. It is a certainty that combining the angular measurements with respect to the fields requires restraint in application in order to preserve an accurate and unique solution. One can avoid numerical difficulties arising from small denominators in Equation 3 by choosing a favorable coordinate system.

3. Pointer

POINTER can be described as a hybrid device encompassing body-fixed sensors to uniquely define the navigational pointing angle of a spinning body. One particular example of POINTER is comprised of a number of high-g hardened optical sensors and magnetometers contained within a fuze volume suitable for gun-launched projectiles. The optical sensors are in a configuration consistent with SOLARSONDE to sense the solar field while the magnetometers are in a configuration consistent with MAGSONDE (MAGnetic SONDE) to sense the earth's magnetic field.

The ability of POINTER to determine a body's orientation in an earth-fixed navigational system rests on that body spinning within a dual field system, when the individual fields are distinct and have knowable orientations with respect to the earth. Measurement systems capable of attitude determination with respect to a single field have been successfully employed for many years in projectile testing, but the orientation within the navigational system is not unique for most cases.




Figure 2. A Spinning Body Within Solar and Magnetic Fields Suitable for POINTER.

The accuracy and resolution of POINTER's navigational angle solution depend on the resolutions of the angular measurements with respect to the two fields and on the accuracy of the knowledge of the field orientations. Given that (a) the angle of the projectile with respect to each of the fields can be estimated to within 0.1 degree, (b) the orientations of the two fields are favorable, and (c) those field orientations can be determined to within 0.25 degree, POINTER can provide the navigational pointing angle to within 0.5 degree. Given a stationary magnetic

field and a solar field that varies significantly during the day, a measurement can be generated for most scenarios at some time during a day.

4. SOLARSONDE

Restricted slit silicon solar cells have been used at the Weapons and Materials Research Directorate¹ of the U.S. Army Research Laboratory (ARL) since the early 1970's to indicate solar attitude and roll rate of projectiles. These cells have been recently used in many projectile and missile programs for in-flight measurements of the solar aspect angle, which is defined as the angle between a spinning projectile's axis of rotation and the solar vector (see Figure 3a). However, determination of the angle between the spin axis and the solar vector does not uniquely specify the orientation of the spin axis within the navigational system. Figure 3b depicts installed sensors on a fuze body.




Figure 3. SOLARSONDE: Solar Field Geometry and Exemplary Sensor Installation.

An optical sensor installed on a body at a known orientation and circumferential location embodies a device called a SOLARSONDE ("to sense the sun"), more commonly called a "yawsonde". Configurations that employ multiple sensors can be used to determine the solar aspect attitude of spinning, freely flying vehicles with respect to any parallel light source. A configuration of multiple sensors includes sensor(s) deliberately misaligned with the roll axis of the spinning body. SOLARSONDEs are routinely calibrated on an optical bench that contains a parallel light source and a 2-degree-of-freedom rotary table to determine the sensor installation parameters.

¹formerly the Ballistic Research Laboratory

The optical sensor currently used as an indicator of solar field alignments was developed at ARL.² The common name for the current version of the sensor is a solar likeness indicating transducer (SLIT). Figure 4 exhibits an exploded assembly view of the sensor cell sides, sensor base, sensor, reflecting surfaces, obstructing pillar, and assembly pins. The sensor is compact, lightweight, and requires no power. The sensor housing includes obstructing geometry that restricts the amount of sunlight that enters and impinges upon the photoelectric cell. The restriction of light properly maintains a constant surface area of sensor illumination over a nearly theoretical half-plane of light acceptance. Thus, the device produces a significant output when it is aligned with the solar field and no output when it is misaligned.





Figure 4. A Solar Likeness Indicating Transducer (SLIT).

Figure 5 shows a trivial period measurement that can provide a solar roll rate estimate for a projectile equipped with six sensors. Also depicted is the experimental measure of the solar aspect angle as derived from the phase relationship between sensor occurrences. Figure 5b portrays actual experimental flight data measurements of the solar aspect angle. The solar aspect angle can be further correlated to the calibration roll position data, and the accumulated roll history and related derivatives (roll rate and roll acceleration) can be generated with greater accuracy than can be achieved from the period measurement. Typical resolution is greater than 0.1 degree for solar aspect angle and 0.05 degree for solar roll position.

²U.S. patent number 5,909,275, entitled "G-Hardened Optical Alignment Sensor," was issued in June 1999 to D.J. Hepner and M.S.L. Hollis.



- a. A consecutive series of sensor alignments. b. Complement of the angle between the body and the sun.

Figure 5. Example of SOLARSONDE Sensor Excitations and Aspect Angle History Derived From Those Pulses.

5. MAGSONDE

Another familiar measurable earth-fixed field is the magnetic field. Recent advances in magnetic sensor technologies have resulted in devices small enough, rugged enough, and sensitive enough to be usable on rapidly spinning bodies subjected to high-g forces. A developmental effort is patent pending for a measurement system called MAGSONDE, which uses such devices.³ MAGSONDE employs fixed magnetic sensor(s) on a rotating body for the estimation of that body's orientation with respect to a stationary magnetic field. MAGSONDE is comprised of both an apparatus and a methodology that use sensor phase measurements to determine orientation. A MAGSONDE application of particular interest to the Army is measurement of in-flight angular orientation of spinning projectiles with respect to the earth's magnetic field.

Although devices responsive to the earth's magnetic field have long been used for heading estimation, MAGSONDE is a new and unique technology. It differs from all other known systems that give orientations with respect to a magnetic field in that those systems use one or more of four basic measurement types to determine orientations: 1) field strength along a sensor axis, 2) relative field strength along multiple sensor axes, 3) rate of change of field strength along a sensor axis, 4) relative rates of change along multiple sensor axes. In every case,

³ by T.E. Harkins, D.J. Hepner, and B.S. Davis, all of ARL.

the angles are derived from measurements of magnetic field component along a sensor axis and require prior knowledge of the field and/or accurate sensitivity calibration. MAGSONDE only requires the magnetic sensor(s) to be used in identifying the times when the sensor axis is orthogonal to the ambient magnetic field. In this case, the angular estimates are premised on the detection of the absence of a magnetic field component along the sensor axis. At these zero crossings, MAGSONDE derives angular orientation from relative phase information in the sensor output. Thus, MAGSONDE is amplitude independent. This feature is important for several reasons: 1) No knowledge of the field strength is required, 2) manufacturing tolerances that affect sensitivity have no impact on orientation determination, and 3) only scalar arithmetical operations are required for the derived angular measurements.

Magnetic field strength along a sensor axis is a function of the total magnetic field intensity, the orientation of the body's axis of rotation, the body's magnetic roll angle, and the geometry of the sensor installation. Figure 6 defines the variables describing projectile orientation within a magnetic field and displays the orientation and excitation of two body-fixed magnetometers within that field. The magnetic plane is defined by the body's axis of rotation and a magnetic field vector. The sensor plane is defined by the body's axis of rotation and a sensor's sensitive axis. The angle between the magnetometer sensitive axis and the body's axis of rotation is defined as λ (λ). The application of two sensors with distinct and non-supplementary λ_1 and λ_2 uniquely determines σ_M , the angle between the magnetic field and the axis of rotation. Knowledge of σ_M and calibration data yields a tabulation of roll angles between the magnetic plane for each sensor at the zero-output occurrence. Further, the magnetic roll angle (ϕ_M) is then the total accumulated rotation of the body. Related derivatives with respect to time can be generated to determine magnetic roll rate and magnetic roll acceleration.




Figure 6. MAGSONDE Projectile and Sensor Geometries.

A fundamental MAGSONDE requirement is that projectile spin rotates the sensor(s) in a stationary magnetic field. The sensor(s) must have a nearly flat frequency response with minimal phase shift over a frequency range until it reaches at least two times the roll rate of the body to which it is fitted. A magnetometer suitable for a MAGSONDE must also have a direct current (DC) response characteristic to the magnetic field. For the epicyclical motion typical of spinning projectiles, the processing of the sensor data for MAGSONDE is straightforward when the spin rates are much greater than the precession and nutation rates. When this condition is not met, more advanced processing algorithms are employed with comparable results.

The MAGSONDE system makes only a single demand of its magnetic sensors, the identification of zero output. Thus, material sensitivity variations, field strength variations, and attenuating flight body materials will have no effect on MAGSONDE performance. Given existing materials responsive to the desired range of magnetic field strength, a sensing device with a favorable signal-to-noise ratio is readily achievable. However, units with built-in electronics must provide a stable scale factor (gain) and bias (offset) characteristics.

One can derive magnetic attitude by evaluating the output from a pair of sensors. For sensors situated with their sensitive axes coplanar with the projectile's spin axis and oriented at non-zero tilt angles ($\lambda_1 = 90^\circ$ and $\lambda_2 = 60^\circ$) from the spin axis, Figure 7 depicts the sensor installation within an artillery fuze and the resulting non-dimensional idealized DC sensor output throughout two magnetic roll periods when $\sigma_M = 45^\circ$. Because of tolerances in the manufacturing and installing of the various sensors, the actual orientations of the sensors on a flight body will differ from their designed values. After sensor installation, each MAGSONDE system will be calibrated with a magnetic field generator and a 2-degree-of-freedom rotary table. The flight body will be installed on a calibration table that allows angular orientation to be changed in both ϕ_M and σ_M . Magnetic roll positions at orthogonality versus σ_M will be tabulated. These data are used to determine the installed circumferential location and tilt angle of each magnetometer's sensitive axis.

The temporal sequence of zero crossings of these sensors is similar to a sequence of solar crossings obtained with a SLIT optical sensor. This methodology of magnetometer sensor data interpretation makes MAGSONDEs in many ways analogous to SOLARSONDEs. This is a conscious design decision that employs the data reduction and analysis capabilities developed during 30 years of SOLARSONDE use in gun- and tube-launched projectile flight tests. There are four important distinctions: outer surface access, launch window, bias sensitivity, and frequency response. The main disadvantages for a SOLARSONDE are the requirement for access to the exterior surface of a rotating body and the dependence on an unobscured solar line of sight. Given that an observable measurement is possible, the internally mounted magnetic sensors of

a MAGSONDE have the advantage of an unchanging magnetic launch window suitable for day/night and all-weather conditions. For some projectile orientations, the converse argument for the SOLARSONDE is that, as time passes, the daily variation in the solar vector will always ensure an observable solar angle measurement while the unchanging magnetic field may not ever yield a measurement. The current SOLARSONDE has no susceptibility to bias or frequency response that can drastically change the derived angular measurement from a MAGSONDE. Thus, the MAGSONDE has a stringent signal conditioning and instrumentation calibration requirement.





Figure 7. Representative MAGSONDE Sensor Installation and Signals.

Potential applications for MAGSONDE output include determination of angular motion histories of experimental, developmental, and tactical projectiles. The resulting angle data can be used with diagnostic tools for projectile aeroballistic characterization, determination of maneuver authority for guided munitions, and weapon-projectile-payload interaction analysis. The sensor data can also provide a relative roll orientation and roll rate reference for the calibration of on-board data sources such as accelerometers and angular rate sensors. Finally, the combination of magnetic sensors and on-board processing data potentially provides navigational assistance for "jammed" global positioning system (GPS) fitted munitions.

Using a 6-degree-of-freedom trajectory code, the authors simulated a flight of the exemplary MAGSONDE configuration on board an M483A1 artillery projectile. For the shot line and magnetic field orientation at ARL's transonic range, a σ_M history throughout the trajectory was generated for idealized 64-bit sensors via the standard MAGSONDE algorithm. These results represent the theoretical boundary on accuracy of that algorithm when applied to this trajectory.

Although experimental results are not yet analyzed, it is expected that an accuracy of 0.1° or better in estimates of σ_M will be achievable.



a. MAGSONDE estimate of angle between spin axis and magnetic field, σ_M b. Error in MAGSONDE estimate of σ_M

Figure 8. MAGSONDE Orientation Estimates and Errors for Simulated Idealized System.

6. Launch Window

The suitability of this particular POINTER system for a given flight depends on the range of possible solar and magnetic headings during that flight. Given known and sufficiently distinct solar and magnetic field orientations at the flight location and an estimate of the anticipated trajectory, possible sensor configurations and lines of fire that result in good geometry can be determined.

Although the orientation of the earth's magnetic field varies slowly over both location and time, these variations are regular and known or measurable. Moreover, the variations over the length and duration of a projectile trajectory are typically negligible, except for local anomalies. Thus, given knowledge of the flight location, the magnetic field near the earth's surface can be obtained from geodetic survey data, computer models, or direct measurement. Simulated trajectory data are then used to estimate the nominal anticipated magnetic heading angle history. In some cases, it will be true that for a portion of the trajectory, the body's attitude with respect to the magnetic field will be within the MAGSONDE measurement capability some times and outside that capability at other times.

The orientation of the solar vector for any location can be measured or estimated from an algorithm with a single, time-stamped solar observation and an estimate

for the seasonal variation in tilt angle and rotation rate of the earth. An additional requirement for a SOLARSONDE measurement is an unobstructed solar line of sight. The diurnal variation in solar vector orientation is advantageous to the POINTER launch window since field orientations can be optimized to ensure a highly accurate measurement, regardless of the shot line.

7. Pointer Flight Experimental Design

For military applications, the sensor(s) must be small and rugged and must consume very little power. Devices of this nature are currently being developed by the Defense Advanced Research Program Agency (DARPA). Investigation of their applicability to MAGSONDE is a main consideration for the development, experimentation, and final vendor selection for particular military applications. While the sensor selection is significant, a listing and evaluation of candidate devices is beyond the scope of this report and would needlessly date the otherwise time-independent content. In general, sensors and instrumentation systems are routinely qualified to 40,000 gs to verify survivability and operation.

The Advanced Munitions Concept Branch, Weapons and Materials Research Directorate, of the U.S. Army Research Laboratory (ARL) can produce a miniature on-board data acquisition system within a North Atlantic Treaty Organization (NATO)-compatible fuze volume fitted with ARL patented optical sensors, magnetic sensors, a micro-electro-mechanical systems (MEMS) accelerometer, a lithium manganese dioxide (LiMnO_2) primary battery, and a commercially available high-g transmitter-antenna package. The current diagnostic fuze design has an available internal volume of 8 in³. The primary battery, connector, and the transmitter package account for almost 75% of the volume, with 1.56 in³ remaining for sensors and instrumentation payloads.

Current practices of sensor data collection methods include telemetry transmission to a ground station. The ultimate objective is to acquire a temporal history of critical data points within the sensor time history from which to derive the individual angular measurements of σ_M and σ_S . These angles are then used to determine the navigational orientation of the rotation axis, as previously described. All available data will be collected and archived and can be processed in the field environment to provide feedback during an experiment and to enhance the flexibility of the study requirements. Advanced reduction techniques can be substituted when appropriate (including but not limited to) compensation for rapid changes in either aspect angle or spin rate is absent.

The first implementation of POINTER used solar and magnetic sensors that were installed in a NATO-compatible fuze volume suitable for use on a spinning

projectile. In addition, the optical and magnetic sensor signals were combined on board to reduce the number of signal channels required. An ancillary benefit of this on-board mixing is that phase and amplitude errors introduced by multi-channel telemetry are reduced. Figure 9 exhibits combined data from a spinning artillery shell fired at Yuma Proving Ground, Arizona. The optical and magnetic data are easily separable.




Figure 9. Experimental Flight Data of Mixed Optical Sensor and Magnetometer Onto a Single Data Channel.

8. Alternate Fields

Several examples of fields that can be distinguished with ease are gravity, sunlight, and the earth's magnetic field. Gravity can be easily sensed on a rotating body fixed to the earth via accelerometers. A body in free flight, however, cannot sense the earth's gravitational field since the force acts upon both the body and the sensing element equally. For a body in free flight, the earth's magnetic field and sunlight offer two convenient reference fields whose orientation can be defined with sufficient resolution to provide an inertial angular orientation solution. Other examples of reference fields that can be determined and sensed include telemetry radio frequency (RF) fields, GPS RF fields, millimeter wave radar, and passive radiometric fields. The sole requirement of the field sensing is to provide a response of some nature that will indicate orientation with respect to that field.

For each projectile fitted with an RF transmitter, data related to the received signal strength, automatic gain control (AGC), can be acquired. Calibrated AGC data are a measure of the signal strength at the receiver input, which provide a quantitative measure of the telemetry link performance. The AGC data can serve as an independent metric of data confidence and can be used as weighting values in data analysis algorithms. The characteristic decay of signal strength is largely a function of distance squared, although transmission and reception antenna patterns also play a large role in measured signal strength. Finally, multi-path effects can cause cancellation because of out-of-phase wave arrival at the receiving antenna. Figure 10 shows representative received signal strength from a body-fixed bi-directional radiator antenna in S-band. Upon close inspection of Figure 10b, a repeating pattern of attenuation is evident as the two nulls of the projectile-borne antenna are detectable with respect to the receiving antenna. Thus, the body roll rate is earth referenced by a rotating body-fixed RF field. In addition, advanced applications could include spinning fields that can be generated by a rapidly rotating body and can be sensed by stationary ground-based measurement systems.




Figure 10. Variations in Sensor Response can Provide Projectile Orientation Information.

9. Conclusions

POINTER is a device and a methodology wherein a multiple field environment is used to determine the orientation of a spinning body within a convenient navigational coordinate system. An example is described that contains a constellation of optical and magnetic sensors. Methodologies are developed for data processing to generate angular orientation in real time or post flight. Potential applications for POINTER data include determination of angular motion histories of experimental, developmental, and tactical projectiles. The

resulting angle data can be used with diagnostic tools for projectile aeroballistic characterization, determination of maneuver authority for guided munitions, and weapon-projectile-payload interaction analysis. The processed data can also provide a relative roll orientation and roll rate reference for calibrating on-board data sources such as accelerometers and angular rate sensors. Finally, the combination of magnetic sensors and on-board processing data potentially provides navigational assistance for "jammed" GPS-fitted munitions.

INTENTIONALLY LEFT BLANK

Select Bibliography for Sensor-Related Measurements, Tests, Applications, and Simulations on Munitions

High-g Flight Experiments, Applications, and Analyses With Magnetic Sensors

1. Harkins, T.E., "Assessing the Feasibility of Accelerometer-Only Inertial Measurement Units for Artillery Projectiles," ARL-MR-200, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, November 1994. [Accelerometers]
2. Davis, B.S., T.E. Harkins, and L.W. Burke, "Flight Test Results of Miniature, Low-Cost, Spin, Accelerometer, and Yaw Sensors," AIAA 97-0422, Reno, NV, January 6-10, 1997. [Accelerometers, Magnetometers, Optical Sensors]
3. Harkins, T.E., and B.S. Davis, "Using Giant Magnetoresistive Ratio (GMR) Materials as a Navigation Aid for Smart Artillery Projectiles," ARL-TR-1330, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, March 1997. [Magnetometers]
4. Brown, T.G., and B.S. Davis, "Dynamic High-G Loading of MEMS Sensors: Ground and Flight Testing," Volume 3512, SPIE Proceedings from Materials and Device Characterization in Micromachining, Santa Clara, CA, September 21-22, 1998. [MEMS Sensors]
5. Davis, B.S., "Using Low-Cost MEMS Accelerometers and Gyroscopes as Strapdown IMUs on Rolling Projectiles," IEEE 1998 Position Location and Navigation Symposium, Vol. 1, No. 1, Palm Springs, CA, April 20-23, 1998. [Accelerometers, Gyroscopes]
6. D'Amico, W.P., F.J. Brandon, B.S. Davis, T.E. Harkins, M.S.L. Hollis, and E.M. Ferguson, "Integration of a Range-Only Drag-Correction Device and Inertial Measurement Sensors Into a NATO-Compatible Artillery Fuze," ARL-MR-401, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, April 1998. [General]
7. Davis, B.S., and D.J. Hepner, "Yawsonde and Microelectromechanical Systems (MEMS) Accelerometer Data of the M898 Sense and Destroy Armor (SADARM) Projectile During Flight Performance Tests (FPTs) II, II, and IV," ARL-MR-417, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, September 1998. [Accelerometers, Optical Sensors]

8. Davis, B.S., and T.G. Brown, "Combining Sensors with Airborne Telemetry Instrumentation to Make Range Measurements and Obtain Aerodynamics," International Telemetry Symposium, November 1999. [Accelerometers, Gyroscopes]
9. Harkins, T.E., "Potential Accuracy Improvements of Inventory Artillery Projectiles Using a NATO-Compatible Dragster Fuze," ARL-MR-438, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, February 1999. [Algorithm using accelerometers and magnetometers]
10. Hepner, D.J., and G. Borgen, "A High-G Flight Experiment of a Field-Programmable Gate Array (FPGA) Pulse Code Modulation (PCM) Encoder," 46th ISA, Bellevue, WA, May 2000. [Instrumentation]

Low-g Flight Experiments, Applications, and Analyses With Magnetic Sensors

11. Harkins, T.E., B.S. Davis, and D.J. Hepner, "Using Accelerometers for Velocity and Position Estimation: Results from 2.75-Inch Rocket Flight Tests," ARL-MR-305, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, June 1996. [Accelerometers]
12. Brown, T.G., F.J. Brandon, T.E. Harkins, and W.H. Hathaway, "Drag and Moment Coefficients Measured During Flight Testing of a 2.75-inch Rocket," AIAA 97-0634, 35th Aerospace Sciences Meeting & Exhibit, Reno, NV, January 1997. [Accelerometers]
13. Brown, T.G., D.J. Hepner, F.J. Brandon, M.S. Hollis, E.M. Ferguson, W.P. D'Amico, L.W. Burke, and T.E. Harkins, "Flight Testing of a 2.75-INCH Rocket," Proceedings of the 16th International Ballistics Symposium, ADPA, September 1996. [Accelerometers]
14. Condon, J.A., "A Mechanical Design for an Inertial Measurement Unit (IMU) for 2.75-inch Rockets and Missiles," ARL-MR-456, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, July 1999. [IMU of Accelerometers, Gyroscopes, Magnetometers]
15. Davis, B.S., T.G. Brown, J.A. Condon, D.J. Hepner, and S. Myers, "Development of an IMU/Telemetry System for Range Flight Testing of Missiles and Rockets," Proceedings of the 18th International Ballistics Symposium, NDIA, November 1999. [IMU of Accelerometers, Gyroscopes, Magnetometers]
16. Harkins, T.E., and T.G. Brown, "Practicability Issues in Deriving Angular Rates from Accelerometer Data for the 2.75-inch Rocket," Proceedings of the

18th International Ballistics Symposium, NDIA, November 1999.
[Gyroscopes]

17. Harkins, T.E., and T.G. Brown, "Using Active Damping as a Precision-Enhancing Technology for 2.75" Rockets," ARL-TR-1772, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, July 1999. [Gyroscopes]

General Munition Applications and Insertion Opportunities With Sensors

18. Hepner, D.J., and T.E. Harkins, "Determining Inertial Orientation of a Spinning Body With Body-fixed Sensors," SPIE Volume 4025, Acquisition, Tracking, and Pointing Orlando, FL, April 2000. [Application for Optical sensors and Magnetometers]
19. Harkins, T.E., and D.J. Hepner, "MAGSONDE: A device for Making Angular Measurements on Spinning Projectiles Using Magnetic Sensors," SPIE Volume 4025, Acquisition, Tracking, and Pointing, Orlando, FL, April 2000. [Application for Magnetometers]
20. Davis, B.S., T.G. Brown, C.R. Myers, and M.S.L. Hollis, "Ground and Flight Testing of Microelectromechanical Systems (MEMS) Sensors for the Commercial Technology Insertion Program (CTIP)," ARL-MR-384, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, January 1998. [High-g Tests of Accelerometers, Magnetometers]
21. Brown, T.G., and B.S. Davis, "Commercial Technology Insertion Program: Military Ground and Flight Experimentation With MEMS Sensors at the U.S. Army Research Laboratory," ARL-TR-2073, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, December 1999. [High-g tests of Accelerometers]
22. Davis, B.S., "Flight Simulator Performance Tests of the Boeing/Draper Microelectromechanical Systems (MEMS) Gyroscope," ARL-MR-388, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, March 1998. [Gyroscopes]

INTENTIONALLY LEFT BLANK

NO. OF
COPIES ORGANIZATION

1 ADMINISTRATOR
DEFENSE TECHNICAL INFO CTR
ATTN DTIC OCA
8725 JOHN J KINGMAN RD
STE 0944
FT BELVOIR VA 22060-6218

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL CI AI R REC MGMT
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL CI LL TECH LIB
2800 POWDER MILL RD
ADELPHI MD 207830-1197

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL D D SMITH
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 CDR WL/MNMF
ATTN R MABRY
101 W EGLIN BLVD STE 219
EGLIN AFB FL 32542

2 CDR WL/MNAV
ATTN G WINCHENBACH
G ABATE
101 W EGLIN BLVD
EGLIN AFB FL 32542

8 CDR US ARMY ARMAMENT
RD&E CTR
ATTN AMSTA AR AET A
M AMORUSO
SUNG CHUNG
AMSTA AR FSP
S PEARCY
AMSTA AR FSP I
D COLLETT
AMSTA FSP A N GRAY
V ILARDI
R SICIGNANO
AMSTA AR AEC T
S LONGO
PICATINNY ARSENAL NJ
07806-5000

NO. OF
COPIES ORGANIZATION

3 CDR PM SADARM
ATTN SSAE GCSS SD A BAHIA
D CARLUCCI W VOGT
PICATINNY ARSENAL NJ
07806-5000

2 ALLIANT TECHSYSTEMS
ATTN C CANDLAND
R DOHRN
600 SECOND ST NE
HOPKINS MN 55343-8384

1 LOCKHEED/MARTIN-SANDERS
ATTN M CARLSON
NCA1-2078 95 CANAL ST
NASHUA NH 03061

2 LOCKHEED/MARTIN-SANDERS
ATTN P ZEMANY
J DEMPSEY
PO BOX 868
NASHUA NH 03061-0868

8 JHU APL
ATTN R BENSON M BOEHME
H CHARLES B D'AMICO
R DENNISON W DEVEREUX
A DRIESMAN D WICKENDEN
1110 JOHNS HOPKINS RD
LAUREL MD 20723-6099

1 CDR NSWC
ATTN CODE 40D J BLANKENSHIP
6703 WEST HIGHWAY 98
PANAMA CITY FL 32407

1 BULL SYSTEMS ASSOC
ATTN R BODENSCHATZ
96 HIGH ST
WARRENTON VA 20186-2901

1 CDR NAWC/WPNS
ATTN CODE 543200 G BORGEN
BLDG 311
PT MUGU CA 93042-5001

1 NOESS INC
ATTN A BOUTZ
4200 WILSON BLVD STE 900
ARLINGTON VA 22203

NO. OF
COPIES ORGANIZATION

1 BOEING NORTH AMERICAN
AUTONETICS ELEC SYS DIV
ATTN G BRAND
3370 MIRALOMA AVE
ANAHEIM CA 92803-3105

1 AUBURN UNIVERSITY
ATTN R BARRETT
211 AEROSPACE ENG BLDG
UBURN UNIV AL 36849-5338

7 CDR NSWC/IH DIV
ATTN CODE 4120 V CARLSON
CODE 5710 E EAGLES
CODE 4110C L FAN
CODE 40D D GARVICK
CODE 450D T GRIFFIN
CODE 440C4 E LITCHER
CODE 57 C PARAS
101 STRAUSS AVE
INDIAN HEAD MD 20640-5000

1 NATIONS INC
ATTN R CARPENTER
12249 SCIENCE DR STE 150
ORLANDO FL 32826

1 METACOMP TECHNOLOGIES INC
ATTN S CHAKRAVARTHY
650 HAMPSHIRE RD STE 200
WESTLAKE VILLAGE CA 91361

1 STRICOM-PM ITTS
ATTN AMCPM ITTS I
R COLANGELO
12350 RESEARCH PKWY
ORLANDO FL 32826-3276

3 CHLS STARK DRAPER LAB INC
ATTN J CONNELLY
J ELWELL J SITOMER
555 TECHNOLOGY SQ
CAMBRIDGE MA 02139-3563

1 CDR US ARMY
YUMA PROVING GROUND
ATTN R COUCH
YPG AZ 95365-9106

NO. OF
COPIES ORGANIZATION

4 NAWC
ATTN WEAPONS DIV
D CRABTREE
CODE C3923 S GATTIS
CODE C3904 D SCOFIELD
S MEYER L ROLLINGSON
CHINA LAKE CA 93555-6100

1 CDR MICOM
ATTN AMSMI RD ST GD D DAVIS
REDSTONE ARSENAL AL 35898

1 UNIV OF CAL AT BERKELEY
ATTN G DELORY
SPACE SCIENCE LAB MS 7450
BERKELEY CA 94720-1740

1 SAIC
ATTN J DISHON III
16701 W BERNARDO DR
SAN DIEGO CA 92127

2 ONR
ATTN J GOLDWASSER
P MORRISON
800 N QUINCY ST RM 507
ARLINGTON VA 22217-5660

2 DIRECTOR
US ARMY RTTC
ATTN STERT TE F TD R EPPS
S HAATAJA
REDSTONE ARSENAL AL 35898

1 PATUXENT RIVER
ATTN R FAULSTITCH
UNIT 1 47765 RANCH RD
PATUXENT RIVER NAS MD
20670-1469

4 NASA/GSFC
ATTN B FLOWERS E RANSONE
N SCHULTZ A TORRES
SOUNDING ROCKET PGM
WALLOPS ISLAND VA 23337

6 NSWC/DD
ATTN G33 FRAYSSE G32 ELLIS
G61 LARACH G34 WENDT
A EVANS D HAGAN
17320 DAHLGREN RD
DAHLGREN VA 22448-5100

NO. OF
COPIES ORGANIZATION

1 ALLIANT DEFENSE
ATTN A GAUZENS
PO BOX 4648
CLEARWATER FL 33758-4648

1 SAIC
ATTN J GLISH
3800 W 80TH ST STE 1090
BLOOMINGTON MN 55431

4 ARROW TECH ASSOC
ATTN W HATHAWAY
M STEINHOFF
J WHYTE R WHYTE
PO BOX 4218
SOUTH BURLINGTON VT 05403

1 THE AEROSPACE CORP
ATTN H HELVAJIAN
2350 E EL SEGUNDO BLVD M5/753
EL SEGUNDO CA 90245-4691

1 TI
ATTN T HICKS
8816 CROSSWIND DR
FORT WORTH TX 76719

2 CDR US ARMY
ATTN STEYPTD ATO
A HOOPER C RAMSDELL
YPG AZ 85365-9106

2 ROCKWELL-COLLINS
ATTN M JOHNSON R MINOR
350 COLLINS RD NE
CEDAR RAPIDS IA 52498

1 UCLA
ATTN J JUDY
68-121 ENGINEERING IV
BOX 951594
LOS ANGELES CA 90095-1594

1 IMI INC
ATTN T JUNEAU
2140 SHATTUCK AVE STE 205
BERKELEY CA 94703

1 TACOM/ARDEC
ATTN AMSTA AR CCF A
W KONICK
2800 POWDER MILL RD
ADELPHI MD 20783-1197

NO. OF
COPIES ORGANIZATION

4 DIR ARL
ATTN A LADAS B PIEKARSKI
J PRICE J EICKE
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 SWALES AEROSPACE
ATTN Q LAM
5050 POWDER MILL RD
BELTSVILLE MD 20705

1 LUTRONIX CORP
ATTN G LEE
13627 PORTOFINO DR
DEL MAR CA 92014

2 STRICOM-PM ITTS
ATTN R LONGENBACH
D SCHNEIDER
12350 RESEARCH PKWY
ORLANDO FL 07806-5000

1 MACROVISION
ATTN T MACDONALD
55 WALKER'S BROOK DR
READING MA 01867-3297

1 SUNY
ATTN R MARCHAND
DEPT OF MATHEMATICS &
COMPUTER SCIENCE
FREDONIA NY 14063

1 ARDEC
ATTN M MATTICE
FIRE CONTROL LDIV
PICATINNY ARSENAL NJ
07806-5000

1 GEORGIA TECH RSCH INST
AEROSPACE TRANSPORTATION
& ADVANCED SYSTEMS LAB
ATTN J MCMICHAEL
7220 RICHARDSON RD
SMYRNA GA 30080

1 USAF
ATTN J MERTS
303 N SEVENTH ST STE 109
EGLIN AFG FL 32542

NO. OF
COPIES ORGANIZATION

1 AEROVIRONMENT INC
ATTN C MIRALLES
4685-3H INDUSTRIAL ST
SIMI VALLEY CA 93063

1 SAIC
ATTN M PALMER
1410 SPRING HILL RD STE 400
MCLEAN VA 22102

1 GEORGIA TECH
ATTN D PAREKH
7220 RICHARDSON RD
SMYRNA GA 30080

1 UNIV OF CA AT BERKELEY
ATTN A PIASANO
DEPT OF MECH & ELEC ENG &
COMPUTER SCI
5101-B ETCHEVERRY HALL
BERKELEY CA 94720-1740

1 NAWC/PM
ATTN D POWELL
PT MUGU CA 93042-5000

1 OPTEC
ATTN R REDMOND
4501 FORD AVE PARK CTR IV
ALEXANDRIA VA 22302-1435

1 FIBERSENSE TECHNOLOGY CORP
ATTN C REYNOLDS
198 VANDERBILT AVE
NORWOOD MA 02062

1 MRDEC
ATTN P RUFFIN
REDSTONE ARSENAL AL
35898-5000

1 IDA
ATTN R SINGER
1801 N BEAUREGARD ST
ALEXANDRIA VA 22311-1772

1 ANALOG DEVICES
ATTN B SULOUFF
21 OSBORNE ST
CAMBRIDGE MA 02139

NO. OF
COPIES ORGANIZATION

1 US ARMY CECOM
ATTN J VIG
FORT MONMOUTH NJ 07703-5203

1 TECOM-RTTC
ATTN K WHIGHAM
BLDG 7855
REDSTONE ARSENAL AL
35898-8052

1 MARK CLYMER
BOX 325
MYSTIC CT 06355

ABERDEEN PROVING GROUND

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL CI LP (TECH LIB)
BLDG 305 APG AA

3 CDR ARDEC
ATTN R LIESKE J WHITESIDE
J MATTS
BLDG 120

1 CDR ATEC
ATTN AMSTE CT T J SCHNELL
RYAN BLDG

1 CDR ATC
ATTN A ELLIS
BLDG 400

1 CDR ATC
ATTN K MCMULLEN
BLDG 359

1 APG EDGEWOOD AREA
ATTN D WEBER
BLDG E3516
5183 BLACKHAWK RD
APG-EA MD 21010-5424

2 CDR USA AMSAA
ATTN AMXSY EV G CASTLEBURY
AMXSY EF S MCKEY
BLDG 328

1 CDR US AEC
ATTN R MIRABELLE
BLDG 4120

NO. OF
COPIES ORGANIZATION

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM E SCHMIDT
T ROSENBERGER
BLDG 4600

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM B A HORST
W CIEPIELLA
BLDG 4600

27 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BA
T BROWN R MCGEE
L BURKE B DAVIS
T HARKINS (10 CYS)
D HEPNER (10 CYS)
V LEITZKE M HOLLIS
A THOMPSON
BLDG 4600

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BB B HAUG
BLDG 390

9 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BC P PLOSTINS
D LYON J GARNER
A MIKHAIL H EDGE
B GUIDOS S WILKERSON
J SAHU P WEINACHT
BLDG 390

1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BD B FORCH
BLDG 4600

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BF J LACETERA
P HILL
BLDG 390

2 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRL WM BR J BORNSTEIN
C SHOEMAKER
BLDG 1121

INTENTIONALLY LEFT BLANK

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 2001		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE Determining Inertial Orientation of a Spinning Body With Body-Fixed Sensors				5. FUNDING NUMBERS PR: 1L162618AH80	
6. AUTHOR(S) Hepner, D.J.; Harkins, T.E. (both of ARL)					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons & Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons & Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066				10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARL-TR-2313	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A methodology for determining absolute inertial angular orientation of a spinning body via independent angular measurements from two arbitrary body-fixed sensor systems is demonstrated. A particular application is denoted that uses Army Research Laboratory solar likeness indicating transducers and magneto-resistive sensors that provide body-fixed, independent angular measurements with regard to their respective local fields. Knowledge of the local field orientations and a coordinate transformation provides the inertial orientation angles, commonly called γ and q , which are useful for evaluating and developing advanced flight bodies and as a navigational aid for brilliant munitions. The combination of a dual field sensor system and the orientation determination methodology is called POINTER (Projectile Orientation In Navigation TERms). Typical sensor data and reduction processes are reviewed for a spinning body containing optical and magnetic sensors, and alternate field measurements are discussed.					
14. SUBJECT TERMS angular motion spinning projectiles magnetic sensors				15. NUMBER OF PAGES 33	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified		20. LIMITATION OF ABSTRACT	