


ARMY RESEARCH LABORATORY



# MAGSONDE: A Device for Making Angular Measurements on Spinning Projectiles With Magnetic Sensors

Thomas E. Harkins  
David J. Hepner

ARL-TR-2310

DECEMBER 2000

20010301 057

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

**Army Research Laboratory**  
Aberdeen Proving Ground, MD 21005-5066

---

---

ARL-TR-2310

December 2000

---

# MAGSONDE: A Device for Making Angular Measurements on Spinning Projectiles Via Magnetic Sensors

Thomas E. Harkins  
David J. Hepner  
Weapons and Materials Research Directorate

---

Approved for public release; distribution is unlimited.

---

---

---

## Abstract

---

Accurate measurement of angular motion of spinning bodies with on-board sensors has long been recognized as a daunting task. Recent advances in magnetic sensor technologies have yielded devices small enough, rugged enough, and sensitive enough to be useful in systems that make high-speed, high-resolution measurements of attitude relative to magnetic fields when these sensors are installed on free-flying bodies.

Such a measurement system, called a "MAGSONDE" (MAGnetic SONDE), has been designed for use in spinning projectiles for the estimation of in-flight angular orientation with respect to the earth's magnetic field. The MAGSONDE is comprised of both an apparatus and a methodology that determine orientation from sensor phase measurements. Sensor scale factor variations will not affect MAGSONDE performance. Other significant features of the MAGSONDE are its day/night and all-weather capability and its use of non-emissive, passive sensors. Potential applications for MAGSONDE include (but are not limited to) navigational aids and determination of angular motion histories of experimental, developmental, and tactical projectiles.

## ACKNOWLEDGMENTS

Mr. Brad Davis of the Weapons and Materials Research Directorate (WMRD) of the U.S. Army Research Laboratory (ARL) has been the lead engineer for the magnetic sensor experiments performed at ARL. His efforts have greatly aided the authors in their appreciation of the potential of magnetic sensors. He is an integral part of the team pursuing engineering development of the MAGSONDE. He has also reviewed this report. Ms Rachel Harkins' assistance in document preparation is also gratefully recognized.

INTENTIONALLY LEFT BLANK

---

## Contents

---

1.	Introduction .....	1
2.	Sensor Design and Qualification .....	2
3.	A Multiple Sensor Application .....	5
4.	Installation and Calibration .....	8
5.	Launch Window Simulation .....	8
6.	Acquisition of Flight Data .....	9
7.	Data Processing .....	9
	7.1 Magnetic Aspect Angle Measurement .....	10
	7.2 Magnetic Roll Rate Measurement .....	11
8.	Conclusions .....	11
	Bibliography .....	13
	Distribution List .....	15
	Report Documentation Page .....	21
<b>Figures</b>		
1.	Magnetic Field Through a Point .....	3
2.	Geometry of Projectile-Borne Magnetic Sensors .....	4
3.	A Fuze-configured MAGSONDE With Two Sensors .....	5
4.	Normalized Magnetic Field Strength Along Sensor Axes .....	6
5.	Roll Angle at Orthogonality for Two Sensor Orientations .....	7
6.	Ratio ( $\Phi$ ) Versus Magnetic Aspect Angle ( $\sigma_M$ ) for Three Sensor Orientations ( $\lambda$ ) .....	7
7.	Errors in $\sigma_M$ Estimates Attributable to Violation of Standard Reduction Assumptions in a Simulated Flight .....	11

INTENTIONALLY LEFT BLANK



# MAGSONDE<sup>1</sup>: A DEVICE FOR MAKING ANGULAR MEASUREMENTS ON SPINNING PROJECTILES VIA MAGNETIC SENSORS

---

## 1. Introduction

---

Recent advances in magnetic sensor technologies have resulted in devices small enough, rugged enough, and sensitive enough to be useful in systems capable of making high-speed, high-resolution measurements of attitude relative to magnetic fields when these sensors are installed on free-flying bodies. This report provides the analytical support for such a measurement system, called a "MAGSONDE" (MAGnetic SONDE), which employs fixed magnetic sensor(s) on a rotating body for the estimation of that body's orientation with respect to a stationary magnetic field. An application of particular interest to the Army is measurement of in-flight angular orientation of spinning projectiles with respect to the earth's magnetic field.

Although devices responsive to the earth's magnetic field have long been used for heading estimation, MAGSONDE is a new and unique technology. It differs from all other known systems that give orientations with respect to a magnetic field in that those systems use one or more of four basic measurement types to determine orientations: 1) field strength along a sensor axis, 2) relative field strength along multiple sensor axes, 3) rate of change of field strength along a sensor axis, and 4) relative rates of change along multiple sensor axes. In every case, the measurements are premised on some evaluation of a component of the magnetic field along a sensor axis and require prior knowledge of the field and/or accurate sensitivity calibration. Making angular measurements with MAGSONDE only requires the magnetic sensor(s) to identify the times when there is no magnetic field along the sensor axis. In this case, the measurements are premised on the absence of a magnetic field component along a sensor axis. MAGSONDE determines orientation from relative phase information in the sensor output at zero crossings and is therefore independent of amplitude. This feature is important for several reasons: 1) No knowledge of the field strength is required, 2) manufacturing tolerances that affect sensitivity have no impact on orientation determination, and 3) only scalar arithmetical operations are required for the angular measurements.

Potential applications for MAGSONDEs include (but are not limited to) navigational aids and determination of angular motion histories of experimental, developmental, and tactical projectiles. The processed sensor data can be used as a diagnostic tool for aerodynamic performance, projectile-payload interactions,

---

<sup>1</sup>patent pending

projectile-weapon interactions, determination of maneuver authority for guided munitions, and as a navigational aid for "jammed" global positioning system (GPS)-fitted munitions. The sensor data can also provide a relative roll orientation and roll rate reference for calibrating ancillary data sources such as accelerometers and angular rate sensors.

A SOLARSONDE, commonly called "yawsonde," is a similar sensor-based angular measurement capability that uses sunlight as a reference field. It is widely used in many projectile study programs for in-flight measurements of the solar aspect angle, which is defined as the angle between a spinning projectile's axis of rotation and a vector from the center of gravity (CG) to the sun. MAGSONDE systems are in many ways analogous to SOLARSONDE. However, there are four important distinctions: outer surface access, launch window, bias sensitivity, and frequency response. The main disadvantages of a SOLARSONDE are the requirement for access to the exterior surface of a rotating body and the dependence on an unobscured solar line of sight. Given that an observable measurement is possible, the internally mounted magnetic sensors of a MAGSONDE have the advantage of an unchanging magnetic launch window suitable for day/night and all-weather conditions. For some projectile orientations, the converse argument for the SOLARSONDE is that as time passes, the daily variation in the solar vector will always ensure an observable solar angle measurement, while the unchanging magnetic field may not ever yield a measurement. The current SOLARSONDE has no bias or frequency response susceptibility, either of which can drastically change the derived angular measurement from a MAGSONDE. Thus, the MAGSONDE has a stringent signal-conditioning and instrumentation calibration requirement.

A complete MAGSONDE system includes the sensor design and qualification, a multiple sensor application, calibration, launch window simulation, successful acquisition of flight data, and data processing. Each of these aspects is discussed in sequence.

---

## 2. Sensor Design and Qualification

---

A fundamental MAGSONDE requirement is that projectile spin rotates the sensor(s) in a stationary magnetic field. The sensor(s) must have a nearly flat frequency response with minimal phase shift over a frequency range to at least two times the roll rate of the body to which it is fitted. A magnetometer suitable for a MAGSONDE must also have a direct current (DC) response characteristic to the magnetic field. For the epicyclic motion typical of spinning projectiles, the processing of the sensor data for MAGSONDE is straightforward when the spin rates are much greater than the precession and nutation rates. When this

condition is not met, more advanced processing algorithms are employed with comparable results.

The MAGSONDE system makes only a single demand of its magnetic sensors, namely, the identification of zero output. Thus, material sensitivity variations, field strength variations, and attenuating flight body materials will have no effect on MAGSONDE performance. Given existing materials responsive to the desired range of magnetic field strength, a sensing device with a favorable signal-to-noise ratio is readily achievable. However, units with built-in electronics must provide both a stable scale factor (gain) and bias (offset) characteristics.

Finally, for military applications, the sensor must be small and rugged and must consume very little power. Devices of this nature are currently being developed by the Defense Advanced Research Program Agency (DARPA). Investigation of their applicability to MAGSONDE is a main consideration for the development, experimentation, and final vendor selection for particular military applications. While the sensor selection is significant, a listing and evaluation of candidate devices is beyond the scope of this report and would needlessly date the otherwise time-independent content.

Within a magnetic field, the flux line through any point can be described by a vector,  $\vec{M}$ , resolvable into orthogonal components. Without the loss of generality, a system (I, J, K) can be defined so that  $\vec{M}$  is in the I-K plane (see Figure 1). The angle between  $\vec{M}$  and the +I axis is designated as  $\sigma_M$ . The components of  $\vec{M}$  in the I, J, K system are then given by

$$\begin{aligned} M_I &= |\vec{M}| \cos(\sigma_M) \\ M_J &= 0 \\ M_K &= |\vec{M}| \sin(\sigma_M) \end{aligned} \quad (1)$$




Figure 1. Magnetic Field Through a Point.

The derivation of magnetic attitude is accomplished in MAGSONDE by the evaluation of the output from a pair of rotating sensors crossing the magnetic field. Consider a spinning projectile with its CG at the origin of the I, J, K system, its axis of rotation on the I axis, and its nose pointed in the +I direction (see Figure 2). On board this projectile is a magnetic sensor (S) situated so that its sensitive axis is coplanar with the projectile's spin axis and oriented at a non-zero angle  $\lambda$  (called the tilt angle) from the spin axis. If the projectile roll angle ( $\phi_s$ ) is indexed so that the sensor axis lies in the half-plane containing the +J axis and the I axis when the roll angle is zero, the field strength along the sensor axis at any instant is given by

$$\begin{aligned} M_s &= \cos(\lambda)M_I + \sin(\lambda)M_K \sin(\phi_s) \\ &= \cos(\lambda)|\vec{M}| \cos(\sigma_M) + \sin(\lambda)|\vec{M}| \sin(\sigma_M) \sin(\phi_s) \end{aligned} \quad (2)$$




Figure 2. Geometry of Projectile-Borne Magnetic Sensors.

The field strength along a sensor axis, when described with respect to the body-fixed system, has two basic types of contributing terms: an axial (bias) component,  $\cos(\lambda)|\vec{M}| \cos(\sigma_M)$ , and a radial (usually roll-modulated) component,  $\sin(\lambda)|\vec{M}| \sin(\sigma_M) \sin(\phi_s)$ .

When  $\lambda = 90$ , there is no axial component and Equation 2 simplifies to

$$M_s = |\vec{M}| \sin(\sigma_M) \sin(\phi_s) \quad (3)$$

Whenever the sensor axis is orthogonal to the field,  $M_s = 0$ . Two possibilities exist; either  $\sin(\sigma_M) = 0$  or  $\sin(\phi_s) = 0$ . In the first case,  $\sigma_M = 0^\circ$  or  $\sigma_M = 180^\circ$ , the axis of rotation is parallel to the magnetic field, and the field strength is

invariant throughout a roll cycle. In the latter case,  $\sin(\sigma_M) \neq 0$ , the variation of field strength along the sensor axis is sinusoidal, and  $M_s = 0$  when  $\phi_s = 0^\circ$  and  $180^\circ$ .

When  $\lambda \neq 90^\circ$ , solving Equation 2 for the roll angles at which  $M_s = 0$  yields

$$\sin(\phi_s) = \left( \frac{-\cos(\sigma_M) \cos(\lambda)}{\sin(\sigma_M) \sin(\lambda)} \right) \quad (4)$$

The existence criterion for  $\phi_s$  to be a real number of

$$\left| \frac{-\cos(\sigma_M) \cos(\lambda)}{\sin(\sigma_M) \sin(\lambda)} \right| \leq 1$$

leads to the requirement that  $90 - \lambda \leq \sigma_M \leq 90 + \lambda$  for the occurrence of an orthogonal condition. This is discussed further in Section 5.

### 3. A Multiple Sensor Application

Although MAGSONDE style measurements can be made with a single sensor, a two-sensor application is better suited for projectiles that are possibly undergoing complex in-flight kinematics. In Figure 3, two sensors are installed in an artillery fuze body so that their sensitive axes and the axis of rotation of the fuze are co-planar. The sensor tilt angles ( $\lambda$ s) are  $90^\circ$  and  $60^\circ$ , respectively.




Figure 3. A Fuze-configured MAGSONDE With Two Sensors.

Figure 4 shows the normalized field strength along the sensitive axis for these sensors throughout several roll cycles when the angle between the axis of rotation and the magnetic field ( $\sigma_M$ ) is  $45^\circ$ . The critical observation to be made about these curves is that the roll angles at which each of the sensors is

orthogonal to the field, i.e., the zero crossings, are irregularly spaced throughout a roll cycle for  $\lambda_2 = 60^\circ$ .




Figure 4. Normalized Magnetic Field Strength Along Sensor Axes.

It was seen in Equations 3 and 4 that, given any fixed tilt angle ( $\lambda$ ), the roll angle at orthogonality ( $\phi_S$ ) is a function of  $\sigma_M$ . This relationship is plotted in Figure 5 for two sensors with tilt angles of  $90^\circ$  and  $60^\circ$ , as in Figure 3. As previously noted, the zero crossings for a radially oriented sensor, ( $\lambda = 90^\circ$ ), are at roll angles of  $0^\circ$  and  $180^\circ$  for all  $\sigma_M \neq 0^\circ$  or  $180^\circ$ . If  $\sigma_M = 0^\circ$  or  $180^\circ$ , the projectile spin axis is parallel to the magnetic field, and a radially oriented sensor would be orthogonal to the field at all roll angles. For the  $60^\circ$  tilted sensor, the zero crossings are also at roll angles of  $0^\circ$  and  $180^\circ$  for  $\sigma_M = 90^\circ$ . For other values of  $\sigma_M$ , a phase shift of the zero crossings results, the magnitude of which varies directly with  $|\sigma_M - 90|$ .

Denoting the two sensors as  $S_1$  ( $90^\circ$ ) and  $S_2$  ( $60^\circ$ ) and the two pairs of roll angles at the zero crossings for these sensors as  $(\phi_{S_{1A}}, \phi_{S_{1B}})$  and  $(\phi_{S_{2A}}, \phi_{S_{2B}})$ , the ratio

$$\Phi = \left| \frac{\phi_{S_{2B}} - \phi_{S_{2A}}}{\phi_{S_{1B}} - \phi_{S_{1A}}} \right|$$

is formed (see Figure 6). Also included are similar ratios for sensors,  $S_2$ , with tilt angles of  $45^\circ$  and  $75^\circ$ . The ambiguity arising from the symmetry of this ratio about  $\sigma_M = 90^\circ$  is easily resolved by checking the parity of the field along  $S_1$  when  $S_2$  is orthogonal to the field. Thus, the combination of the ratio,  $\Phi$ , and a parity check completely specifies the angle between the projectile axis and the magnetic field. This discriminant can likewise be generated for any two magnetic

sensors with unequal, non-supplementary tilt angles. The choice of sensor orientations in the preceding discussion was made to simplify the algebra, but the number of sensors and sensor orientations in any application could be tailored to meet particular requirements.




Figure 5. Roll Angle at Orthogonality for Two Sensor Orientations.




Figure 6. Ratio ( $\Phi$ ) Versus Magnetic Aspect Angle ( $\sigma_M$ ) for Three Sensor Orientations ( $\lambda$ ).

---

## 4. Installation and Calibration

---

Because of tolerances in the manufacturing and installing of the sensors, the actual orientations of the sensors on a flight body will differ from their designed orientations. These differences in turn will result in different values of the ratio  $\Phi$  for given values of  $\sigma_M$ . Calibration of each MAGSONDE system after sensor installation will be accomplished with a magnetic field generator and a 2-degree-of-freedom rotary table. The flight body will be installed on a fixture that allows changing angular orientation with respect to the magnetic field in both roll ( $\phi_s$ ) and heading ( $\sigma_M$ ). Roll positions at orthogonality versus  $\sigma_M$  will be tabulated, and the corresponding ratios will be generated. The tabulated data can be fitted via linear least squares to determine the installed circumferential location and tilt angle of the magnetometer sensitive axis, thus reducing the calibration to two parameters per sensor.

---

## 5. Launch Window Simulation

---

The necessity of each of the magnetic sensors being orthogonal to the field during a roll cycle defines the range of magnetic aspect angles within which a MAGSONDE with a particular sensor configuration is able to operate. This region of applicability is called the MAGSONDE window. As stated in Section 2, a sensor with a tilt angle  $\lambda$  will be orthogonal to the field if and when the roll angle is a solution of

$$\phi_s = \sin^{-1} \left( \frac{-\cos(\sigma_M) \cos(\lambda)}{\sin(\sigma_M) \sin(\lambda)} \right).$$

The existence criterion for  $\phi_s$  of

$$\left| \frac{-\cos(\sigma_M) \cos(\lambda)}{\sin(\sigma_M) \sin(\lambda)} \right| \leq 1$$

leads to the requirement that  $90 - \lambda \leq \sigma_M \leq 90 + \lambda$ .

The suitability of a MAGSONDE system for a particular flight depends of the range of possible magnetic headings ( $\sigma_M$ s) during that flight. Given the direction of the earth's magnetic field at the flight location and an estimate of the anticipated trajectory, possible sensor packages and lines of fire that result in good geometry can be determined.

Although the earth's magnetic field varies with both location and time, these variations are regular and known. Moreover, the variations over the length and



duration of a projectile trajectory are typically negligible, excluding local anomalies. Thus, given knowledge of the flight location, the magnetic field near the earth's surface can be obtained from geodetic survey data, computer models, or direct measurement.

Simulated trajectory data are then used to estimate the nominal anticipated magnetic heading angle history. In some cases, it will be true that for a portion of the trajectory, the body's attitude with respect to the magnetic field is inside the MAGSONDE measurement capability sometimes and outside that capability at other times. For applications in which limited portions of a flight are of interest, MAGSONDE coverage at only those times need be guaranteed.

---

## 6. Acquisition of Flight Data

---

Raw sensor data can either be stored on board and recovered or be transmitted to a ground station. Two methods of data collections can be used for telemetry applications: analog data via FM/FM or digital data via pulse code modulation (PCM). Analog applications include FM/FM telemetry via high frequency voltage-controlled oscillators. Digital applications would primarily use on-board PCM systems to digitize and serialize the data for common telemetry practices. Typical reduction techniques employing non-causal, digital filtering and curve fitting would be used to determine the occurrence of orthogonality (i.e., zero crossings of the signal).

---

## 7. Data Processing

---

Whatever acquisition and processing techniques are employed, the objective is to tabulate a temporal history of three data at each of the zero crossings during the flight: the sensor identification (1 or 2), the time of the crossing, and the polarity of the other sensor at that time. With these data, a standard methodology for extracting magnetic aspect angle and roll rate is presented. All available data will be collected and archived and can be reduced in the field environment to provide feedback during an experiment and enhance the flexibility of the study requirements. Advanced reduction techniques can be substituted when appropriate, including (but not limited to) compensation for rapid changes in magnetic aspect angle or roll rate.

## 7.1 Magnetic Aspect Angle Measurement

In Sections 2 and 3, the value of the ratio

$$\Phi = \left| \frac{\phi_{S_{2B}} - \phi_{S_{2A}}}{\phi_{S_{1B}} - \phi_{S_{1A}}} \right|$$

combined with the polarity of  $S_1$  when  $S_2=0$  was shown to uniquely specify  $\sigma_M$ . Flight data will not give sensor roll angles at zero crossings but times when these crossings occurred. If two constraints are present, the crossing times can also be used to directly compute  $\sigma_M$ . These constraints are

The magnetic roll rate is constant for four consecutive zero crossings; and  $\sigma_M$  is constant for these four crossings.


With these two restrictions, the magnetic roll acceleration, roll rate, roll position, and ratio of four consecutive sensor occurrences in the sequence  $S_{1A}, S_{2A}, S_{2B}, S_{1B}$  are given by

$$\begin{aligned} \ddot{\phi}_{S_{1A}, S_{2A}, S_{2B}, S_{1B}} &= 0 \\ \dot{\phi}_{S_{1A}, S_{2A}, S_{2B}, S_{1B}} &= a_1 \\ \phi_{S_{1A}, S_{2A}, S_{2B}, S_{1B}} &= a_0 + a_1 t_{S_{1A}, S_{2A}, S_{2B}, S_{1B}} \end{aligned} \quad (5)$$

$$\Phi = \left| \frac{\phi_{S_{2B}} - \phi_{S_{2A}}}{\phi_{S_{1B}} - \phi_{S_{1A}}} \right| = \left| \frac{(a_0 + a_1 t_{S_{2B}}) - (a_0 + a_1 t_{S_{2A}})}{(a_0 + a_1 t_{S_{1B}}) - (a_0 + a_1 t_{S_{1A}})} \right| = \left| \frac{t_{S_{2B}} - t_{S_{2A}}}{t_{S_{1B}} - t_{S_{1A}}} \right| \quad (6)$$

Thus,  $\Phi$  computed from zero crossing times is the same as that computed from roll position calibration data at any constant  $\sigma_M$ .

In flight, these constraints are seldom true, but for simulated flights of several types of projectiles, the differences between  $\Phi$  computed from in-flight crossing times with the standard methodology and  $\Phi$  from calibration only resulted in errors in  $\sigma_M$  estimates on the order of hundredths of degrees. A representative example is seen in Figure 7 where the  $\sigma_M$  history for a simulated trajectory of an M483A1 artillery projectile at the transonic range at Aberdeen Proving Ground and the errors in the  $\sigma_M$  estimates are given. In these simulations, noiseless sensors and 64-bit precision were assumed.



a)  $\sigma_M$  history during simulated flight      b) Error in  $\sigma_M$  estimates with MAGSONDE

Figure 7. Errors in  $\sigma_M$  Estimates Attributable to Violation of Standard Reduction Assumptions in a Simulated Flight.

## 7.2 Magnetic Roll Rate Measurement

The standard reduction estimates magnetic roll rate by numerically differentiating the magnetic roll position history. The calibrated roll positions ( $\phi_{S_{1A_1}}, \phi_{S_{2A_1}}, \phi_{S_{2B_1}}, \phi_{S_{1B_1}}, \phi_{S_{1A_2}}, \phi_{S_{2A_2}}, \phi_{S_{2B_2}}, \phi_{S_{1B_2}}, \dots$ ) for each of the zero crossing times and magnetic aspect angles are assigned. Using the sensor identification in the flight data, one can determine a temporal history of the sensor's roll positions. This crossing times history is used to estimate the roll rate. When  $\sigma_M$  is near  $90^\circ$  and/or when the yaw and pitch rates are relatively low compared to the roll rate, magnetic roll rate and the body's spin rate are equivalent.

---

## 8. Conclusions

---

A methodology for deriving the heading and the roll rate of a spinning projectile relative to a magnetic field has been formulated. Devices employing this methodology, called "MAGSONDEs," are currently in engineering development. It is planned to include MAGSONDEs in flight study programs in the near future. MAGSONDEs will provide an all-weather, day/night angular measurement capability for spinning projectiles that does not currently exist.

INTENTIONALLY LEFT BLANK

---

## Bibliography

---

### *High-g Flight Experiments, Applications, and Analyses With Magnetic Sensors*

1. Davis, B.S., T.E. Harkins, and L.W. Burke. "Flight Test Results of Miniature, Low-Cost, Spin, Accelerometer, and Yaw Sensors," AIAA 97-0422, Reno, NV, January 6-10, 1997.
2. Harkins, T.E., and B.S. Davis. "Using Giant Magnetoresistive Ratio (GMR) Materials as a Navigation Aid for Smart Artillery Projectiles," ARL-TR-1330, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, March 1997.
3. D'Amico, W.P., F.J. Brandon, B.S. Davis, T.E. Harkins, M.S.L. Hollis, and E.M. Ferguson, "Integration of a Range-Only Drag-Correction Device and Inertial Measurement Sensors Into a NATO-Compatible Artillery Fuze," ARL-MR-401, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, April 1998.
4. Harkins, T.E., "Potential Accuracy Improvements of Inventory Artillery Projectiles Using a NATO-Compatible Dragster Fuze," ARL-MR-438, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, February 1999.

### *Low-g Flight Experiments, Applications, and Analyses With Magnetic Sensors*

5. Condon, J.A., "A Mechanical Design for an Inertial Measurement Unit (IMU) for 2.75-inch Rockets and Missiles," ARL-MR-456, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, July 1999.
6. Davis, B.S., T.G. Brown, J.A. Condon, D.J. Hepner, and S. Myers, "Development of an IMU/Telemetry System for Range Flight Testing of Missiles and Rockets," Proceedings of the 18th International Ballistics Symposium, NDIA, November 1999.

### *General Munition Applications and Insertion Opportunities With Sensors*

7. Hepner, D.J., and T.E. Harkins, "Determining Inertial Orientation of a Spinning Body With Body-fixed Sensors," SPIE Volume 4025, Acquisition, Tracking, and Pointing Orlando, FL, April 2000.

8. Harkins, T.E., and D.J. Hepner, "MAGSONDE: A device for Making Angular Measurements on Spinning Projectiles Using Magnetic Sensors," SPIE Volume 4025, Acquisition, Tracking, and Pointing, Orlando, FL, April 2000.
9. Davis, B.S., T.G. Brown, C.R. Myers, and M.S.L. Hollis, "Ground and Flight Testing of Microelectromechanical Systems (MEMS) Sensors for the Commercial Technology Insertion Program (CTIP)," ARL-MR-384, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, January 1998.

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	ADMINISTRATOR DEFENSE TECHNICAL INFO CTR ATTN DTIC OCA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	3	CDR PM SADARM ATTN SSAE GCSS SD A BAHIA D CARLUCCI W VOGT PICATINNY ARSENAL NJ 07806-5000
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRL CI AIR REC MGMT 2800 POWDER MILL RD ADELPHI MD 20783-1197	2	ALLIANT TECHSYSTEMS ATTN C CANDLAND R DOHRN 600 SECOND ST NE HOPKINS MN 55343-8384
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRL CI LL TECH LIB 2800 POWDER MILL RD ADELPHI MD 207830-1197	1	LOCKHEED/MARTIN-SANDERS ATTN M CARLSON NCA1-2078 95 CANAL ST NASHUA NH 03061
1	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRL D D SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197	2	LOCKHEED/MARTIN-SANDERS ATTN P ZEMANY J DEMPSEY PO BOX 868 NASHUA NH 03061-0868
1	CDR WL/MNMF ATTN R MABRY 101 W EGLIN BLVD STE 219 EGLIN AFB FL 32542	8	JHU APL ATTN R BENSON M BOEHME H CHARLES B D'AMICO R DENNISON W DEVEREUX A DRIESMAN D WICKENDEN 1110 JOHNS HOPKINS RD LAUREL MD 20723-6099
2	CDR WL/MNAV ATTN G WINCHENBACH G ABATE 101 W EGLIN BLVD EGLIN AFB FL 32542	1	CDR NSWC ATTN CODE 40D J BLANKENSHIP 6703 WEST HIGHWAY 98 PANAMA CITY FL 32407
8	CDR US ARMY ARMAMENT RD&E CTR ATTN AMSTA AR AET A M AMORUSO SUNG CHUNG AMSTA AR FSP S PEARCY AMSTA AR FSP I D COLLETT AMSTA FSP A N GRAY V ILARDI R SICIGNANO AMSTA AR AEC T S LONGO PICATINNY ARSENAL NJ 07806-5000	1	BULL SYSTEMS ASSOC ATTN R BODENSCHATZ 96 HIGH ST WARRENTON VA 20186-2901
		1	CDR NAWC/WPNS ATTN CODE 543200 G BORGEN BLDG 311 PT MUGU CA 93042-5001
		1	NOESS INC ATTN A BOUTZ 4200 WILSON BLVD STE 900 ARLINGTON VA 22203

NO. OF  
COPIES ORGANIZATION

1 BOEING NORTH AMERICAN  
AUTONETICS ELEC SYS DIV  
ATTN G BRAND  
3370 MIRALOMA AVE  
ANAHEIM CA 92803-3105

1 AUBURN UNIVERSITY  
ATTN R BARRETT  
211 AEROSPACE ENG BLDG  
UBURN UNIV AL 36849-5338

7 CDR NSWC/IH DIV  
ATTN CODE 4120 V CARLSON  
CODE 5710 E EAGLES  
CODE 4110C L FAN  
CODE 40D D GARVICK  
CODE 450D T GRIFFIN  
CODE 440C4 E LITCHER  
CODE 57 C PARAS  
101 STRAUSS AVE  
INDIAN HEAD MD 20640-5000

1 NATIONS INC  
ATTN R CARPENTER  
12249 SCIENCE DR STE 150  
ORLANDO FL 32826

1 METACOMP TECHNOLOGIES INC  
ATTN S CHAKRAVARTHY  
650 HAMPSHIRE RD STE 200  
WESTLAKE VILLAGE CA 91361

1 STRICOM-PM ITTS  
ATTN AMCPM ITTS I  
R COLANGELO  
12350 RESEARCH PKWY  
ORLANDO FL 32826-3276

3 CHLS STARK DRAPER LAB INC  
ATTN J CONNELLY  
J ELWELL J SITOMER  
555 TECHNOLOGY SQ  
CAMBRIDGE MA 02139-3563

1 CDR US ARMY  
YUMA PROVING GROUND  
ATTN R COUCH  
YPG AZ 95365-9106

NO. OF  
COPIES ORGANIZATION

4 NAWC  
ATTN WEAPONS DIV  
D CRABTREE  
CODE C3923 S GATTIS  
CODE C3904 D SCOFIELD  
S MEYER L ROLLINGSON  
CHINA LAKE CA 93555-6100

1 CDR MICOM  
ATTN AMSMI RD ST GD D DAVIS  
REDSTONE ARSENAL AL 35898

1 UNIV OF CAL AT BERKELEY  
ATTN G DELORY  
SPACE SCIENCE LAB MS 7450  
BERKELEY CA 94720-1740

1 SAIC  
ATTN J DISHON III  
16701 W BERNARDO DR  
SAN DIEGO CA 92127

2 ONR  
ATTN J GOLDWASSER  
P MORRISON  
800 N QUINCY ST RM 507  
ARLINGTON VA 22217-5660

2 DIRECTOR  
US ARMY RTTC  
ATTN STERT TE F TD R EPPS  
S HAATAJA  
REDSTONE ARSENAL AL 35898

1 PATUXENT RIVER  
ATTN R FAULSTITCH  
UNIT 1 47765 RANCH RD  
PATUXENT RIVER NAS MD  
20670-1469

4 NASA/GSFC  
ATTN B FLOWERS E RANSONE  
N SCHULTZ A TORRES  
SOUNDING ROCKET PGM  
WALLOPS ISLAND VA 23337

6 NSWC/DD  
ATTN G33 FRAYSSE G32 ELLIS  
G61 LARACH G34 WENDT  
A EVANS D HAGAN  
17320 DAHLGREN RD  
DAHLGREN VA 22448-5100



NO. OF  
COPIES   ORGANIZATION

1   ALLIANT DEFENSE  
ATTN A GAUZENS  
PO BOX 4648  
CLEARWATER FL 33758-4648

1   SAIC  
ATTN J GLISH  
3800 W 80TH ST STE 1090  
BLOOMINGTON MN 55431

4   ARROW TECH ASSOC  
ATTN W HATHAWAY  
M STEINHOFF  
J WHYTE R WHYTE  
PO BOX 4218  
SOUTH BURLINGTON VT 05403

1   THE AEROSPACE CORP  
ATTN H HELVAJIAN  
2350 E EL SEGUNDO BLVD M5/753  
EL SEGUNDO CA 90245-4691

1   TI  
ATTN T HICKS  
8816 CROSSWIND DR  
FORT WORTH TX 76719

2   CDR US ARMY  
ATTN STEYP TD ATO  
A HOOPER C RAMSDELL  
YPG AZ 85365-9106

2   ROCKWELL-COLLINS  
ATTN M JOHNSON R MINOR  
350 COLLINS RD NE  
CEDAR RAPIDS IA 52498

1   UCLA  
ATTN J JUDY  
68-121 ENGINEERING IV  
BOX 951594  
LOS ANGELES CA 90095-1594

1   IMI INC  
ATTN T JUNEAU  
2140 SHATTUCK AVE STE 205  
BERKELEY CA 94703

1   TACOM/ARDEC  
ATTN AMSTA AR CCF A  
W KONICK  
2800 POWDER MILL RD  
ADELPHI MD 20783-1197

NO. OF  
COPIES   ORGANIZATION

4   DIR ARL  
ATTN A LADAS B PIEKARSKI  
J PRICE J EICKE  
2800 POWDER MILL RD  
ADELPHI MD 20783-1197

1   SWALES AEROSPACE  
ATTN Q LAM  
5050 POWDER MILL RD  
BELTSVILLE MD 20705

1   LUTRONIX CORP  
ATTN G LEE  
13627 PORTOFINO DR  
DEL MAR CA 92014

2   STRICOM-PM ITTS  
ATTN R LONGENBACH  
D SCHNEIDER  
12350 RESEARCH PKWY  
ORLANDO FL 07806-5000

1   MACROVISION  
ATTN T MACDONALD  
55 WALKER'S BROOK DR  
READING MA 01867-3297

1   SUNY  
ATTN R MARCHAND  
DEPT OF MATHMATICS &  
COMPUTER SCIENCE  
FREDONIA NY 14063

1   ARDEC  
ATTN M MATTICE  
FIRE CONTROL LDIV  
PICATINNY ARSENAL NJ  
07806-5000

1   GEORGIA TECH RSCH INST  
AEROSPACE TRANSPORTATION  
& ADVANCED SYSTEMS LAB  
ATTN J MCMICHAEL  
7220 RICHARDSON RD  
SMYRNA GA 30080

1   USAF  
ATTN J MERTS  
303 N SEVENTH ST STE 109  
EGLIN AFG FL 32542

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	AEROVIRONMENT INC ATTN C MIRALLES 4685-3H INDUSTRIAL ST SIMI VALLEY CA 93063	1	US ARMY CECOM ATTN J VIG FORT MONMOUTH NJ 07703-5203
1	SAIC ATTN M PALMER 1410 SPRING HILL RD STE 400 MCLEAN VA 22102	1	TECOM-RTTC ATTN K WHIGHAM BLDG 7855 REDSTONE ARSENAL AL 35898-8052
1	GEORGIA TECH ATTN D PAREKH 7220 RICHARDSON RD SMYRNA GA 30080	1	MARK CLYMER BOX 325 MYSTIC CT 06355
1	UNIV OF CA AT BERKELEY ATTN A PIASANO DEPT OF MECH & ELEC ENG & COMPUTER SCI 5101-B ETCHEVERRY HALL BERKELEY CA 94720-1740		<u>ABERDEEN PROVING GROUND</u>
1	NAWC/PM ATTN D POWELL PT MUGU CA 93042-5000	2	DIRECTOR US ARMY RSCH LABORATORY ATTN AMSRL CI LP (TECH LIB) BLDG 305 APG AA
1	OPTEC ATTN R REDMOND 4501 FORD AVE PARK CTR IV ALEXANDRIA VA 22302-1435	3	CDR ARDEC ATTN R LIESKE J WHITESIDE J MATTS BLDG 120
1	FIBERSENSE TECHNOLOGY CORP ATTN C REYNOLDS 198 VANDERBILT AVE NORWOOD MA 02062	1	CDR ATEC ATTN AMSTE CT T J SCHNELL RYAN BLDG
1	MRDEC ATTN P RUFFIN REDSTONE ARSENAL AL 35898-5000	1	CDR ATC ATTN A ELLIS BLDG 400
1	IDA ATTN R SINGER 1801 N BEAUREGARD ST ALEXANDRIA VA 22311-1772	1	CDR ATC ATTN K MCMULLEN BLDG 359
1	ANALOG DEVICES ATTN B SULOUFF 21 OSBORNE ST CAMBRIDGE MA 02139	1	APG EDGEWOOD AREA ATTN D WEBER BLDG E3516 5183 BLACKHAWK RD APG-EA MD 21010-5424
		2	CDR USA AMSAA ATTN AMXSU EV G CASTLEBURY AMXSU EF S MCKEY BLDG 328
		1	CDR US AEC ATTN R MIRABELLE BLDG 4120

NO. OF  
COPIES   ORGANIZATION

NO. OF  
COPIES   ORGANIZATION

2   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM E SCHMIDT  
T ROSENBERGER  
BLDG 4600

2   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM B A HORST  
W CIEPIELLA  
BLDG 4600

27   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BA  
T BROWN R MCGEE  
L BURKE B DAVIS  
T HARKINS (10 CYS)  
D HEPNER (10 CYS)  
V LEITZKE M HOLLIS  
A THOMPSON  
BLDG 4600

1   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BB B HAUG  
BLDG 390

9   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BC P PLOSTINS  
D LYON J GARNER  
A MIKHAIL H EDGE  
B GUIDOS S WILKERSON  
J SAHU P WEINACHT  
BLDG 390

1   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BD B FORCH  
BLDG 4600

2   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BF J LACETERA  
P HILL  
BLDG 390

2   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL WM BR J BORNSTEIN  
C SHOEMAKER  
BLDG 1121

ABSTRACT ONLY

1   DIRECTOR  
US ARMY RSCH LABORATORY  
ATTN AMSRL CI AP TECH PUB BR  
2800 POWDER MILL RD  
ADELPHI MD 20783-1197

INTENTIONALLY LEFT BLANK

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE December 2000	3. REPORT TYPE AND DATES COVERED Final
4. TITLE AND SUBTITLE MAGSONDE: A Device for Making Angular Measurements on Spinning Projectiles Via Magnetic Sensors			5. FUNDING NUMBERS PR: 1L162618AH80
6. AUTHOR(S) Harkins, T.E.; Hepner, D.J. (both of ARL)			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons & Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Weapons & Materials Research Directorate Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARL-TR-2310
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words)  Accurate measurement of angular motion of spinning bodies with on-board sensors has long been recognized as a daunting task. Recent advances in magnetic sensor technologies have yielded devices small enough, rugged enough, and sensitive enough to be useful in systems that make high-speed, high-resolution measurements of attitude relative to magnetic fields when these sensors are installed on free-flying bodies.  Such a measurement system, called a "MAGSONDE" (MAGnetic SONDE), has been designed for use in spinning projectiles for the estimation of in-flight angular orientation with respect to the earth's magnetic field. The MAGSONDE is comprised of both an apparatus and a methodology that determine orientation from sensor phase measurements. Sensor scale factor variations will not affect MAGSONDE performance. Other significant features of MAGSONDE are its day/night and all-weather capability and its use of non-emissive, passive sensors. Potential applications for MAGSONDE include (but are not limited to) navigational aids and determination of angular motion histories of experimental, developmental, and tactical projectiles.			
14. SUBJECT TERMS angular motion                      spinning projectiles magnetic sensors			15. NUMBER OF PAGES 25
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT